



Usman Akinyemi

U20220090

Lab10: Neural Network and Perceptron



QUESTIONS

1. What are the parallels between Biological NNs and Artificial NNs? List any three.
 - i. They both use neurons for processing information though one is artificial.
 - ii. They both are able to recognize patterns and complex behaviour.
 - iii. They both have the ability to learn through experience.
2. What was the McCulloch-Pitts Neuron model? List any two of its limitations.
 - i. It cannot be used to create complex model that requires non linear activation function.
 - ii. It is unable to model continuous-valued inputs and output
3. How does a perceptron learn?

A perceptron learns by adjusting its weights based on the error in its predictions.
4. List any three activation functions and their respective output ranges.

Hyperbolic tangent (tanh) function: Output range is $(-1, 1)$.
Rectified Linear Unit (ReLU) function: Output range is $[0, \infty)$.
Identity $f(x)=x$: Output range is $(-\infty, \infty)$
5. Why was the classical perceptron not able to solve the XOR problem? Can you suggest a way to solve the XOR problem using neural networks but without going into a higher dimensional space?

The classical perceptron, with a linear activation function, cannot solve the XOR problem because XOR is not a linearly separable problem. A single perceptron can only learn linearly separable patterns, and XOR requires a non-linear decision boundary.

Solution without going into a higher dimensional space:

One way to solve the XOR problem without going into a higher dimensional space is to use a multi-layer perceptron (MLP) with at least one hidden layer. The hidden layer(s) introduce non-linearity, allowing the network to learn the XOR function.