

1. Authentication APIs
 - 1.1 Login Used in: LoginScreen.js - When user submits login form http Copy POST /api/v1/auth/login Content-Type: application/json Request Body: JSON Copy { "email": "user@example.com", "password": "SecurePassword123" } Success Response (200): JSON Copy { "success": true, "data": { "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...", "refreshToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...", "user": { "id": "uuid", "firstName": "John", "lastName": "Doe", "email": "user@example.com", "avatar": "<https://cdn.example.com/avatars/uuid.jpg>", "currency": "USD", "createdAt": "2024-01-15T10:30:00Z" } } } Error Response (401): JSON Copy { "success": false, "message": "Invalid email or password" }
 - 1.2 Register Used in: RegisterScreen.js - When user submits registration form http Copy POST /api/v1/auth/register Content-Type: application/json Request Body: JSON Copy { "firstName": "John", "lastName": "Doe", "email": "user@example.com", "password": "SecurePassword123" } Success Response (201): JSON Copy { "success": true, "message": "Registration successful. Please verify your email.", "data": { "userId": "uuid", "email": "user@example.com" } } Error Response (400): JSON Copy { "success": false, "message": "Email already exists" }
 - 1.3 Logout Used in: ProfileScreen.js - When user clicks logout http Copy POST /api/v1/auth/logout Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "refreshToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..." } Success Response (200): JSON Copy { "success": true, "message": "Logged out successfully" }
 - 1.4 Refresh Token Used in: axiosClient.js - Automatically when access token expires (401) http Copy POST /api/v1/auth/refresh Content-Type: application/json Request Body: JSON Copy { "refreshToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..." } Success Response (200): JSON Copy { "success": true, "data": { "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...", "refreshToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9..." } } Error Response (401): JSON Copy { "success": false, "message": "Invalid refresh token" }
 - 1.5 Forgot Password Used in: ForgotPasswordScreen.js - When user requests password reset http Copy POST /api/v1/auth/forgot-password Content-Type: application/json Request Body: JSON Copy { "email": "user@example.com" } Success Response (200): JSON Copy { "success": true, "message": "Password reset link sent to your email" }
 - 1.6 Reset Password Used in: (Deep link from email) - When user sets new password http Copy POST /api/v1/auth/reset-password Content-Type: application/json Request Body: JSON Copy { "token": "reset-token-from-email", "password": "NewSecurePassword123" } Success Response (200): JSON Copy { "success": true, "message": "Password reset successful" }
 - 1.7 Verify Email Used in: (Deep link from email) - After registration http Copy POST /api/v1/auth/verify-email Content-Type: application/json

Request Body: JSON Copy { "token": "verification-token-from-email" } Success Response (200): JSON Copy { "success": true, "message": "Email verified successfully" }

2. User APIs
 - 2.1 Get Current User (Me) Used in: useAuth.js hook - On app load to check auth status, ProfileScreen.js http Copy GET /api/v1/users/me Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": { "id": "uuid", "firstName": "John", "lastName": "Doe", "email": "user@example.com", "phone": "+1234567890", "avatar": "<https://cdn.example.com/avatars/uuid.jpg>", "currency": "USD", "totalExpenses": 150, "totalGroups": 5, "totalFriends": 12, "createdAt": "2024-01-15T10:30:00Z", "updatedAt": "2024-03-15T14:20:00Z" } }
 - 2.2 Update Profile Used in: EditProfileScreen.js - When user saves profile changes http Copy PUT /api/v1/users/me Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "firstName": "John", "lastName": "Doe", "email": "user@example.com", "phone": "+1234567890", "currency": "EUR" } Success Response (200): JSON Copy { "success": true, "data": { "id": "uuid", "firstName": "John", "lastName": "Doe", "email": "user@example.com", "phone": "+1234567890", "avatar": "<https://cdn.example.com/avatars/uuid.jpg>", "currency": "EUR", "updatedAt": "2024-03-15T14:25:00Z" } }
 - 2.3 Change Password Used in: ChangePasswordScreen.js - When user changes password http Copy POST /api/v1/users/change-password Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "currentPassword": "OldPassword123", "newPassword": "NewSecurePassword123" } Success Response (200): JSON Copy { "success": true, "message": "Password changed successfully" } Error Response (400): JSON Copy { "success": false, "message": "Current password is incorrect" }
 - 2.4 Upload Avatar Used in: EditProfileScreen.js - When user uploads profile picture http Copy POST /api/v1/users/avatar Authorization: Bearer {token} Content-Type: multipart/form-data Request Body (multipart): plain Copy avatar: (binary file) Success Response (200): JSON Copy { "success": true, "data": { "avatar": "<https://cdn.example.com/avatars/uuid.jpg>" } }
 - 2.5 Delete Account Used in: ProfileScreen.js - When user deletes account http Copy DELETE /api/v1/users/me Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "Account deleted successfully" }
 - 2.6 Search Users Used in: AddFriendScreen.js - When searching for friends by email/name http Copy GET /api/v1/users/search?q={query}&page=1&limit=20 Authorization: Bearer {token} Query Parameters: q: Search query (email or name) page: Page number (default: 1) limit: Items per page (default: 20) Success Response (200): JSON Copy { "success": true, "data": { "users": [{ "id": "uuid",

"firstName": "Jane", "lastName": "Smith", "email": "jane@example.com", "avatar": "<https://cdn.example.com/avatars/uuid.jpg>" }], "total": 1, "page": 1, "limit": 20 } }

3. Friend APIs
- 3.1 Get Friends List Used in: FriendsListScreen.js - On screen load, useFriends hook http Copy GET /api/v1/friends?page=1&limit=20 Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": [{ "id": "friend-uuid", "firstName": "Jane", "lastName": "Smith", "email": "jane@example.com", "avatar": "<https://cdn.example.com/avatars/uuid.jpg>", "friendSince": "2024-02-01T10:00:00Z" }] }
- 3.2 Get Friend Requests Used in: FriendRequestsScreen.js - On screen load, FriendsListScreen.js (badge count) http Copy GET /api/v1/friends/requests Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": [{ "id": "request-uuid", "fromUser": { "id": "user-uuid", "firstName": "Bob", "lastName": "Wilson", "email": "bob@example.com", "avatar": "<https://cdn.example.com/avatars/uuid.jpg>" }, "toUser": { "id": "current-user-uuid", "firstName": "John", "lastName": "Doe", "email": "user@example.com" }, "status": "pending", "direction": "incoming", "createdAt": "2024-03-10T08:30:00Z" }] }
- 3.3 Send Friend Request Used in: AddFriendScreen.js - When user sends friend request http Copy POST /api/v1/friends/request Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "email": "friend@example.com" } Success Response (201): JSON Copy { "success": true, "message": "Friend request sent", "data": { "id": "request-uuid", "status": "pending", "createdAt": "2024-03-15T10:00:00Z" } } Error Response (404): JSON Copy { "success": false, "message": "User not found with this email" } Error Response (409): JSON Copy { "success": false, "message": "Friend request already pending or users are already friends" }
- 3.4 Accept Friend Request Used in: FriendRequestsScreen.js - When user accepts request http Copy POST /api/v1/friends/requests/{requestId}/accept Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "Friend request accepted", "data": { "friendshipId": "friendship-uuid", "friend": { "id": "user-uuid", "firstName": "Bob", "lastName": "Wilson", "email": "bob@example.com", "avatar": "<https://cdn.example.com/avatars/uuid.jpg>" } } }
- 3.5 Reject Friend Request Used in: FriendRequestsScreen.js - When user rejects request http Copy POST /api/v1/friends/requests/{requestId}/reject Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "Friend request rejected" }
- 3.6 Remove Friend Used in: FriendsListScreen.js, FriendProfileScreen.js - When user removes friend http Copy DELETE /api/v1/friends/{friendId} Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "Friend removed successfully" }
- 3.7 Get Friend Balances Used in: DashboardScreen.js, FriendsListScreen.js, useFriends

hook http Copy GET /api/v1/friends/balances Authorization: Bearer {token}
 Success Response (200): JSON Copy { "success": true, "data": [{ "friendId":
 "friend-uuid", "friend": { "id": "friend-uuid", "firstName": "Jane", "lastName":
 "Smith", "email": "jane@example.com", "avatar":
 "<https://cdn.example.com/avatars/uuid.jpg>" }, "amount": 45.50, "currency":
 "USD", "youOwe": false, "lastActivity": "2024-03-14T16:30:00Z" }, { "friendId":
 "friend-uuid-2", "friend": { "id": "friend-uuid-2", "firstName": "Bob", "lastName":
 "Wilson", "email": "bob@example.com", "avatar":
 "<https://cdn.example.com/avatars/uuid2.jpg>" }, "amount": -23.75, "currency":
 "USD", "youOwe": true, "lastActivity": "2024-03-13T10:15:00Z" }] } 3.8 Get Friend
 Details Used in: FriendProfileScreen.js - When viewing friend profile http Copy
 GET /api/v1/friends/{friendId} Authorization: Bearer {token} Success Response
 (200): JSON Copy { "success": true, "data": { "id": "friend-uuid", "firstName":
 "Jane", "lastName": "Smith", "email": "jane@example.com", "avatar":
 "<https://cdn.example.com/avatars/uuid.jpg>", "friendSince": "2024-02-
 01T10:00:00Z", "totalExpensesTogether": 25, "balance": { "amount": 45.50,
 "currency": "USD", "youOwe": false } } }

4. Group APIs 4.1 Get Groups List Used in: GroupsListScreen.js - On screen load
 http Copy GET /api/v1/groups?page=1&limit=20 Authorization: Bearer {token}
 Success Response (200): JSON Copy { "success": true, "data": [{ "id": "group-
 uuid", "name": "Weekend Trip to Vegas", "description": "Spring break 2024",
 "members": [{ "id": "user-uuid-1", "firstName": "John", "lastName": "Doe",
 "avatar": "<https://cdn.example.com/avatars/uuid1.jpg>", "isAdmin": true }, { "id":
 "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "avatar":
 "<https://cdn.example.com/avatars/uuid2.jpg>", "isAdmin": false }],
 "totalExpenses": 1250.00, "currency": "USD", "userBalance": 150.00, "createdAt":
 "2024-03-01T10:00:00Z", "updatedAt": "2024-03-14T18:30:00Z" }] } 4.2 Create
 Group Used in: CreateGroupScreen.js - When creating new group http Copy
 POST /api/v1/groups Authorization: Bearer {token} Content-Type:
 application/json Request Body: JSON Copy { "name": "Weekend Trip to Vegas",
 "description": "Spring break 2024", "members": ["user-uuid-1", "user-uuid-2",
 "user-uuid-3"], "currency": "USD" } Success Response (201): JSON Copy {
 "success": true, "data": { "id": "group-uuid", "name": "Weekend Trip to Vegas",
 "description": "Spring break 2024", "members": [{ "id": "current-user-uuid",
 "firstName": "John", "lastName": "Doe", "isAdmin": true }, { "id": "user-uuid-2",
 "firstName": "Jane", "lastName": "Smith", "isAdmin": false }, { "id": "user-uuid-3",
 "firstName": "Bob", "lastName": "Wilson", "isAdmin": false }], "currency": "USD",
 "createdAt": "2024-03-15T10:00:00Z" } } 4.3 Get Group Details Used in:
 GroupDetailsScreen.js - On screen load http Copy GET /api/v1/groups/{groupId}

Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": { "id": "group-uuid", "name": "Weekend Trip to Vegas", "description": "Spring break 2024", "currency": "USD", "simplifyDebts": true, "members": [{ "id": "user-uuid-1", "firstName": "John", "lastName": "Doe", "email": "john@example.com", "avatar": "<https://cdn.example.com/avatars/uuid1.jpg>", "isAdmin": true, "isCurrentUser": true, "joinedAt": "2024-03-01T10:00:00Z" }, { "id": "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "email": "jane@example.com", "avatar": "<https://cdn.example.com/avatars/uuid2.jpg>", "isAdmin": false, "isCurrentUser": false, "joinedAt": "2024-03-01T10:30:00Z" }], "totalExpenses": 1250.00, "userBalance": 150.00, "balances": [{ "userId": "user-uuid-1", "user": { "id": "user-uuid-1", "firstName": "John", "lastName": "Doe", "avatar": "<https://cdn.example.com/avatars/uuid1.jpg>", "paid": 500.00, "owed": 350.00, "net": 150.00 }, { "userId": "user-uuid-2", "user": { "id": "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "avatar": "<https://cdn.example.com/avatars/uuid2.jpg>", "paid": 750.00, "owed": 900.00, "net": -150.00 }], "createdAt": "2024-03-01T10:00:00Z", "updatedAt": "2024-03-14T18:30:00Z" } } }

4.4 Update Group Used in: GroupSettingsScreen.js - When saving group settings http Copy PUT /api/v1/groups/{groupId} Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "name": "Updated Group Name", "description": "Updated description", "currency": "EUR", "simplifyDebts": true } Success Response (200): JSON Copy { "success": true, "data": { "id": "group-uuid", "name": "Updated Group Name", "description": "Updated description", "currency": "EUR", "simplifyDebts": true, "updatedAt": "2024-03-15T11:00:00Z" } }

4.5 Delete Group Used in: GroupDetailsScreen.js, GroupSettingsScreen.js - When deleting group http Copy DELETE /api/v1/groups/{groupId} Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "Group deleted successfully" }

4.6 Get Group Members Used in: GroupMembersScreen.js - When viewing/managing members http Copy GET /api/v1/groups/{groupId}/members Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": [{ "id": "user-uuid-1", "firstName": "John", "lastName": "Doe", "email": "john@example.com", "avatar": "<https://cdn.example.com/avatars/uuid1.jpg>", "isAdmin": true, "isCurrentUser": true, "joinedAt": "2024-03-01T10:00:00Z" }, { "id": "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "email": "jane@example.com", "avatar": "<https://cdn.example.com/avatars/uuid2.jpg>", "isAdmin": false, "isCurrentUser": false, "joinedAt": "2024-03-01T10:30:00Z" }] }

4.7 Add Member to Group Used in: GroupMembersScreen.js - When adding new member http Copy POST

/api/v1/groups/{groupId}/members Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "userId": "user-uuid-to-add" } Success Response (201): JSON Copy { "success": true, "data": { "id": "user-uuid-to-add", "firstName": "Bob", "lastName": "Wilson", "email": "bob@example.com", "avatar": "<https://cdn.example.com/avatars/uuid3.jpg>", "isAdmin": false, "joinedAt": "2024-03-15T12:00:00Z" } } 4.8 Remove Member from Group Used in: GroupMembersScreen.js - When removing member http Copy DELETE /api/v1/groups/{groupId}/members/{userId} Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "Member removed successfully" } 4.9 Get Group Expenses Used in: GroupDetailsScreen.js - When viewing group expenses tab http Copy GET /api/v1/groups/{groupId}/expenses?page=1&limit=20 Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": [{ "id": "expense-uuid", "description": "Dinner at Italian Place", "amount": 120.00, "currency": "USD", "paidBy": { "id": "user-uuid-1", "firstName": "John", "lastName": "Doe", "isCurrentUser": true }, "createdAt": "2024-03-14T19:30:00Z", "userShare": 40.00 }] } 4.10 Settle Group Used in: (Group settlement feature) http Copy POST /api/v1/groups/{groupId}/settle Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "settlements": [{ "fromUserId": "user-uuid-1", "toUserId": "user-uuid-2", "amount": 150.00 }] } Success Response (200): JSON Copy { "success": true, "message": "Group settled successfully" }

5. Expense APIs 5.1 Get Expenses Used in: ExpenseListScreen.js, useExpenses hook, DashboardScreen.js http Copy GET /api/v1/expenses?page=1&limit=20&groupId=&friendId=&startDate=&endDate=&category= Authorization: Bearer {token} Query Parameters: page: Page number limit: Items per page groupId: Filter by group (optional) friendId: Filter by friend (optional) startDate: Filter from date (ISO format, optional) endDate: Filter to date (ISO format, optional) category: Filter by category ID (optional) Success Response (200): JSON Copy { "success": true, "data": { "expenses": [{ "id": "expense-uuid", "description": "Grocery shopping", "amount": 85.50, "currency": "USD", "category": { "id": "food", "name": "Food & Dining", "icon": "food", "color": "#FF5722" }, "paidBy": { "id": "user-uuid-1", "firstName": "John", "lastName": "Doe", "isCurrentUser": true }, "group": { "id": "group-uuid", "name": "Apartment" }, "date": "2024-03-14T10:00:00Z", "createdAt": "2024-03-14T10:05:00Z", "notes": "Weekly groceries", "receipt": "<https://cdn.example.com/receipts/uuid.jpg>", "participants": [{ "userId": "user-uuid-1", "firstName": "John", "lastName": "Doe", "isCurrentUser": true, "amountOwed": 42.75, "percentage": 50, "shares": 1 }, { "userId": "user-uuid-2", "firstName": "Jane", "lastName": "Smith",

"isCurrentUser": false, "amountOwed": 42.75, "percentage": 50, "shares": 1 }],
 "userShare": 42.75, "split": { "type": "equal", "participants": [{ "userId": "user-
 uuid-1", "amount": 42.75, "percentage": 50, "shares": 1 }, { "userId": "user-uuid-2",
 "amount": 42.75, "percentage": 50, "shares": 1 }] } }, "total": 150, "page": 1,
 "limit": 20 } } 5.2 Create Expense Used in: CreateExpenseScreen.js,
 AddExpenseScreen.js - When adding new expense http Copy POST
 /api/v1/expenses Authorization: Bearer {token} Content-Type: application/json
 Request Body: JSON Copy { "description": "Dinner with friends", "amount":
 120.00, "currency": "USD", "category": "food", "date": "2024-03-14T19:00:00Z",
 "notes": "Birthday celebration", "groupId": "group-uuid", "paidById": "user-uuid-
 1", "split": { "type": "equal", "participants": [{ "userId": "user-uuid-1", "amount":
 40.00, "percentage": 33.33, "shares": 1 }, { "userId": "user-uuid-2", "amount":
 40.00, "percentage": 33.33, "shares": 1 }, { "userId": "user-uuid-3", "amount":
 40.00, "percentage": 33.34, "shares": 1 }] } } Success Response (201): JSON Copy {
 "success": true, "data": { "id": "expense-uuid", "description": "Dinner with
 friends", "amount": 120.00, "currency": "USD", "category": { "id": "food", "name":
 "Food & Dining", "icon": "food", "color": "#FF5722" }, "paidBy": { "id": "user-uuid-
 1", "firstName": "John", "lastName": "Doe", "isCurrentUser": true }, "date": "2024-
 03-14T19:00:00Z", "createdAt": "2024-03-14T19:05:00Z", "notes": "Birthday
 celebration", "participants": [{ "userId": "user-uuid-1", "firstName": "John",
 "lastName": "Doe", "isCurrentUser": true, "amountOwed": 40.00 }, { "userId":
 "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "isCurrentUser": false,
 "amountOwed": 40.00 }, { "userId": "user-uuid-3", "firstName": "Bob",
 "lastName": "Wilson", "isCurrentUser": false, "amountOwed": 40.00 }], "split": {
 "type": "equal", "participants": [{ "userId": "user-uuid-1", "amount": 40.00,
 "percentage": 33.33, "shares": 1 }, { "userId": "user-uuid-2", "amount": 40.00,
 "percentage": 33.33, "shares": 1 }, { "userId": "user-uuid-3", "amount": 40.00,
 "percentage": 33.34, "shares": 1 }] } } } 5.3 Get Expense Details Used in:
 ExpenseDetailsScreen.js - When viewing expense details http Copy GET
 /api/v1/expenses/{expenseId} Authorization: Bearer {token} Success Response
 (200): JSON Copy { "success": true, "data": { "id": "expense-uuid", "description":
 "Dinner with friends", "amount": 120.00, "currency": "USD", "category": { "id":
 "food", "name": "Food & Dining", "icon": "food", "color": "#FF5722" }, "paidBy": {
 "id": "user-uuid-1", "firstName": "John", "lastName": "Doe", "email":
john@example.com, "avatar": <https://cdn.example.com/avatars/uuid1.jpg>,
 "isCurrentUser": true }, "group": { "id": "group-uuid", "name": "Weekend Trip" },
 "date": "2024-03-14T19:00:00Z", "createdAt": "2024-03-14T19:05:00Z",
 "createdBy": { "id": "user-uuid-1", "firstName": "John", "lastName": "Doe" },
 "notes": "Birthday celebration", "receipt":

"<https://cdn.example.com/receipts/uuid.jpg>", "participants": [{ "userId": "user-uuid-1", "firstName": "John", "lastName": "Doe", "email": "john@example.com", "avatar": "<https://cdn.example.com/avatars/uuid1.jpg>", "isCurrentUser": true, "amountOwed": 40.00, "percentage": 33.33, "shares": 1, "settled": false }, { "userId": "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "email": "jane@example.com", "avatar": "<https://cdn.example.com/avatars/uuid2.jpg>", "isCurrentUser": false, "amountOwed": 40.00, "percentage": 33.33, "shares": 1, "settled": false }], "split": { "type": "equal", "participants": [{ "userId": "user-uuid-1", "amount": 40.00, "percentage": 33.33, "shares": 1 }, { "userId": "user-uuid-2", "amount": 40.00, "percentage": 33.33, "shares": 1 }, { "userId": "user-uuid-3", "amount": 40.00, "percentage": 33.34, "shares": 1 }] }, "comments": [{ "id": "comment-uuid", "user": { "id": "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "avatar": "<https://cdn.example.com/avatars/uuid2.jpg>" }, "text": "Thanks for covering!", "createdAt": "2024-03-14T20:00:00Z" }] } }

5.4 Update Expense

Used in: EditExpenseScreen.js - When editing expense
 http Copy PUT /api/v1/expenses/{expenseId} Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "description": "Updated description", "amount": 130.00, "currency": "USD", "category": "food", "date": "2024-03-14T19:00:00Z", "notes": "Updated notes" } Success Response (200): JSON Copy { "success": true, "data": { "id": "expense-uuid", "description": "Updated description", "amount": 130.00, "updatedAt": "2024-03-15T10:00:00Z" } }

5.5 Delete Expense

Used in: ExpenseDetailsScreen.js, EditExpenseScreen.js - When deleting expense
 http Copy DELETE /api/v1/expenses/{expenseId} Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "Expense deleted successfully" }

5.6 Upload Receipt

Used in: CreateExpenseScreen.js, EditExpenseScreen.js - After creating/updating expense with image
 http Copy POST /api/v1/expenses/{expenseId}/receipt Authorization: Bearer {token} Content-Type: multipart/form-data Request Body (multipart): plain Copy receipt: (binary image file) Success Response (200): JSON Copy { "success": true, "data": { "receipt": "<https://cdn.example.com/receipts/uuid.jpg>" } }

5.7 Update Split

Used in: SplitExpenseScreen.js - When modifying how expense is split
 http Copy PUT /api/v1/expenses/{expenseId}/split Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "type": "percentage", "participants": [{ "userId": "user-uuid-1", "amount": 60.00, "percentage": 50, "shares": 1 }, { "userId": "user-uuid-2", "amount": 30.00, "percentage": 25, "shares": 1 }, { "userId": "user-uuid-3", "amount": 30.00, "percentage": 25, "shares": 1 }] } Success Response (200): JSON Copy { "success": true, "data": { "id": "expense-uuid", "split": { "type": "percentage", "participants": [{ "userId": "user-uuid-1", "amount": 60.00, "percentage": 50, "shares": 1 },


```
{
  "userId": "user-uuid-2", "amount": 30.00, "percentage": 25, "shares": 1},
  {
    "userId": "user-uuid-3", "amount": 30.00, "percentage": 25, "shares": 1 } ] },
  "participants": [ { "userId": "user-uuid-1", "firstName": "John", "lastName": "Doe",
    "amountOwed": 60.00 }, { "userId": "user-uuid-2", "firstName": "Jane",
    "lastName": "Smith", "amountOwed": 30.00 }, { "userId": "user-uuid-3",
    "firstName": "Bob", "lastName": "Wilson", "amountOwed": 30.00 } ] } }
5.8 Get Expense Comments Used in: ExpenseDetailsScreen.js - Loading comments
section http Copy GET /api/v1/expenses/{expenseId}/comments Authorization:
Bearer {token} Success Response (200): JSON Copy { "success": true, "data": [ {
  "id": "comment-uuid", "user": { "id": "user-uuid-2", "firstName": "Jane",
  "lastName": "Smith", "avatar": "https://cdn.example.com/avatars/uuid2.jpg" },
  "text": "Thanks for covering dinner!", "createdAt": "2024-03-14T20:00:00Z" } ] }
5.9 Add Comment Used in: ExpenseDetailsScreen.js - When user adds comment
http Copy POST /api/v1/expenses/{expenseId}/comments Authorization: Bearer
{token} Content-Type: application/json Request Body: JSON Copy { "text":
  "Thanks for covering dinner!" } Success Response (201): JSON Copy { "success":
  true, "data": { "id": "comment-uuid", "user": { "id": "current-user-uuid",
  "firstName": "John", "lastName": "Doe", "avatar":
  "https://cdn.example.com/avatars/uuid1.jpg" }, "text": "Thanks for covering
  dinner!", "createdAt": "2024-03-14T20:05:00Z" } }
```

6. Settlement APIs
- 6.1 Get Settlements Used in: SettlementsScreen.js, SettlementHistoryScreen.js http Copy GET /api/v1/settlements?page=1&limit=20&status=pending&friendId= Authorization: Bearer {token} Query Parameters: page: Page number limit: Items per page status: pending or completed friendId: Filter by friend (optional) Success Response (200): JSON Copy { "success": true, "data": { "settlements": [{ "id": "settlement-uuid", "amount": 45.50, "currency": "USD", "fromUser": { "id": "user-uuid-1", "firstName": "John", "lastName": "Doe", "email": "[john@example.com](\"john@example.com\")", "avatar": "[https://cdn.example.com/avatars/uuid1.jpg](\"https://cdn.example.com/avatars/uuid1.jpg\")", "isCurrentUser": true }, "toUser": { "id": "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "email": "[jane@example.com](\"jane@example.com\")", "avatar": "[https://cdn.example.com/avatars/uuid2.jpg](\"https://cdn.example.com/avatars/uuid2.jpg\")", "isCurrentUser": false }, "status": "pending", "paymentMethod": "cash", "note": "Paid in cash at lunch", "date": "2024-03-14T12:00:00Z", "createdAt": "2024-03-14T12:05:00Z", "relatedExpenses": ["expense-uuid-1", "expense-uuid-2"] }], "total": 5, "page": 1, "limit": 20 } } }
- 6.2 Create Settlement Used in: SettleDebtScreen.js - When recording a payment http Copy POST /api/v1/settlements Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "toUserId": "user-uuid-2", "amount": 45.50, "currency": "USD", "paymentMethod": "cash", "note": "Paid in cash at

lunch", "date": "2024-03-14T12:00:00Z", "relatedExpenses": ["expense-uuid-1", "expense-uuid-2"] } Success Response (201): JSON Copy { "success": true, "data": { "id": "settlement-uuid", "amount": 45.50, "currency": "USD", "fromUser": { "id": "user-uuid-1", "firstName": "John", "lastName": "Doe", "isCurrentUser": true }, "toUser": { "id": "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "isCurrentUser": false }, "status": "pending", "paymentMethod": "cash", "note": "Paid in cash at lunch", "date": "2024-03-14T12:00:00Z", "createdAt": "2024-03-14T12:05:00Z" } } 6.3 Get Settlement Details Used in: (Settlement detail view) http Copy GET /api/v1/settlements/{settlementId} Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": { "id": "settlement-uuid", "amount": 45.50, "currency": "USD", "fromUser": { "id": "user-uuid-1", "firstName": "John", "lastName": "Doe", "email": "john@example.com", "avatar": "<https://cdn.example.com/avatars/uuid1.jpg>", "isCurrentUser": true }, "toUser": { "id": "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "email": "jane@example.com", "avatar": "<https://cdn.example.com/avatars/uuid2.jpg>", "isCurrentUser": false }, "status": "pending", "paymentMethod": "cash", "note": "Paid in cash at lunch", "date": "2024-03-14T12:00:00Z", "createdAt": "2024-03-14T12:05:00Z", "confirmedAt": null, "relatedExpenses": [{ "id": "expense-uuid-1", "description": "Dinner", "amount": 25.00 }, { "id": "expense-uuid-2", "description": "Taxi", "amount": 20.50 }] } } 6.4 Update Settlement Used in: (Edit settlement - rarely used) http Copy PUT /api/v1/settlements/{settlementId} Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "note": "Updated note", "paymentMethod": "bank_transfer" } Success Response (200): JSON Copy { "success": true, "data": { "id": "settlement-uuid", "note": "Updated note", "paymentMethod": "bank_transfer", "updatedAt": "2024-03-15T10:00:00Z" } } 6.5 Delete Settlement Used in: (Cancel pending settlement) http Copy DELETE /api/v1/settlements/{settlementId} Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "Settlement cancelled successfully" } 6.6 Confirm Settlement (Receiver confirms they got paid) Used in: SettlementsScreen.js - When recipient confirms receipt http Copy POST /api/v1/settlements/{settlementId}/confirm Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": { "id": "settlement-uuid", "status": "completed", "confirmedAt": "2024-03-15T10:30:00Z" } } }

7. Transaction APIs (Personal Finance) 7.1 Get Transactions Used in:

TransactionListScreen.js, personal finance tracking http Copy GET /api/v1/transactions?

page=1&limit=20&type=expense&category=&startDate=&endDate=

Authorization: Bearer {token} Query Parameters: page: Page number limit:

Items per page type: expense or income category: Category ID filter startDate: Start date filter endDate: End date filter Success Response (200): JSON Copy { "success": true, "data": { "transactions": [{ "id": "transaction-uuid", "description": "Salary", "amount": 5000.00, "type": "income", "currency": "USD", "category": { "id": "salary", "name": "Salary", "icon": "cash", "color": "#4CAF50" }, "date": "2024-03-01T09:00:00Z", "notes": "Monthly salary", "receipt": null, "createdAt": "2024-03-01T09:05:00Z" }, { "id": "transaction-uuid-2", "description": "Grocery shopping", "amount": 85.50, "type": "expense", "currency": "USD", "category": { "id": "food", "name": "Food & Dining", "icon": "food", "color": "#FF5722" }, "date": "2024-03-05T18:30:00Z", "notes": "Weekly groceries", "receipt": "[https://cdn.example.com/receipts/uuid.jpg](\"https://cdn.example.com/receipts/uuid.jpg\")", "createdAt": "2024-03-05T18:35:00Z" }], "total": 150, "page": 1, "limit": 20 } } 7.2 Create Transaction Used in: AddExpenseScreen.js, AddIncomeScreen.js - Personal transactions http Copy POST /api/v1/transactions Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "description": "Freelance payment", "amount": 500.00, "type": "income", "currency": "USD", "category": "freelance", "date": "2024-03-10T14:00:00Z", "notes": "Website design project" } Success Response (201): JSON Copy { "success": true, "data": { "id": "transaction-uuid", "description": "Freelance payment", "amount": 500.00, "type": "income", "currency": "USD", "category": { "id": "freelance", "name": "Freelance", "icon": "laptop", "color": "#2196F3" }, "date": "2024-03-10T14:00:00Z", "notes": "Website design project", "createdAt": "2024-03-10T14:05:00Z" } } 7.3 Get Transaction Details Used in: TransactionDetailsScreen.js http Copy GET /api/v1/transactions/{transactionId} Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": { "id": "transaction-uuid", "description": "Freelance payment", "amount": 500.00, "type": "income", "currency": "USD", "category": { "id": "freelance", "name": "Freelance", "icon": "laptop", "color": "#2196F3" }, "date": "2024-03-10T14:00:00Z", "notes": "Website design project", "receipt": null, "createdAt": "2024-03-10T14:05:00Z", "updatedAt": "2024-03-10T14:05:00Z" } } 7.4 Update Transaction Used in: TransactionDetailsScreen.js - Edit transaction http Copy PUT /api/v1/transactions/{transactionId} Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "description": "Updated description", "amount": 550.00, "category": "freelance", "date": "2024-03-10T14:00:00Z", "notes": "Updated notes" } Success Response (200): JSON Copy { "success": true, "data": { "id": "transaction-uuid", "description": "Updated description", "amount": 550.00, "updatedAt": "2024-03-11T10:00:00Z" } } 7.5 Delete Transaction Used in: TransactionDetailsScreen.js http Copy DELETE /api/v1/transactions/{transactionId} Authorization: Bearer {token} Success

Response (200): JSON Copy { "success": true, "message": "Transaction deleted successfully" } 7.6 Get Transaction Categories Used in: TransactionListScreen.js, AddExpenseScreen.js, AddIncomeScreen.js http Copy GET

/api/v1/transactions/categories?type=expense Authorization: Bearer {token}
Query Parameters: type: expense or income (optional, returns all if not specified) Success Response (200): JSON Copy { "success": true, "data": [{ "id": "food", "name": "Food & Dining", "icon": "food", "color": "#FF5722", "type": "expense" }, { "id": "transport", "name": "Transportation", "icon": "car", "color": "#2196F3", "type": "expense" }, { "id": "salary", "name": "Salary", "icon": "cash", "color": "#4CAF50", "type": "income" }, { "id": "freelance", "name": "Freelance", "icon": "laptop", "color": "#2196F3", "type": "income" }] }

8. Notification APIs 8.1 Get Notifications Used in: NotificationsScreen.js, MainNavigator.js (badge count) http Copy GET /api/v1/notifications?page=1&limit=20 Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": { "notifications": [{ "id": "notification-uuid", "type": "friend_request", "title": "New Friend Request", "message": "Bob Wilson sent you a friend request", "read": false, "createdAt": "2024-03-15T10:00:00Z", "sender": { "id": "user-uuid", "firstName": "Bob", "lastName": "Wilson", "avatar": "[https://cdn.example.com/avatars/uuid.jpg](\"https://cdn.example.com/avatars/uuid.jpg\")" }, "data": { "requestId": "request-uuid" } }, { "id": "notification-uuid-2", "type": "expense_created", "title": "New Expense", "message": "Jane Smith added 'Dinner at Italian Place' for \$120.00", "read": true, "createdAt": "2024-03-14T19:35:00Z", "sender": { "id": "user-uuid-2", "firstName": "Jane", "lastName": "Smith", "avatar": "[https://cdn.example.com/avatars/uuid2.jpg](\"https://cdn.example.com/avatars/uuid2.jpg\")" }, "data": { "expenseId": "expense-uuid", "groupId": "group-uuid" } }, { "id": "notification-uuid-3", "type": "settlement_completed", "title": "Payment Received", "message": "John Doe confirmed your \$45.50 payment", "read": false, "createdAt": "2024-03-14T12:30:00Z", "sender": { "id": "user-uuid-1", "firstName": "John", "lastName": "Doe", "avatar": "[https://cdn.example.com/avatars/uuid1.jpg](\"https://cdn.example.com/avatars/uuid1.jpg\")" }, "data": { "settlementId": "settlement-uuid" } }], "unreadCount": 2, "total": 45, "page": 1, "limit": 20 } } 8.2 Mark Notification as Read Used in: NotificationsScreen.js - When user taps notification http Copy POST /api/v1/notifications/{notificationId}/read Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": { "id": "notification-uuid", "read": true, "readAt": "2024-03-15T10:05:00Z" } } 8.3 Mark All Notifications as Read Used in: NotificationsScreen.js - "Mark all as read" button http Copy POST /api/v1/notifications/read-all Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "All notifications marked as read", "data": { "markedCount": 5 } } 8.4 Delete Notification Used in:

NotificationsScreen.js - Swipe to delete http Copy DELETE

/api/v1/notifications/{notificationId} Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "Notification deleted" }

8.5 Get Notification Settings Used in: NotificationSettingsScreen.js - On screen load http Copy GET /api/v1/notifications/settings Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": {

"expenseCreated": true, "expenseUpdated": true, "payments": true, "friendRequests": true, "groupInvites": true, "reminders": true, "emailEnabled": true, "pushEnabled": true } }

8.6 Update Notification Settings Used in: NotificationSettingsScreen.js - When toggling settings http Copy PUT

/api/v1/notifications/settings Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "expenseCreated": true,

"expenseUpdated": false, "payments": true, "friendRequests": true, "groupInvites": true, "reminders": false, "emailEnabled": true, "pushEnabled": true }

Success Response (200): JSON Copy { "success": true, "data": { "expenseCreated": true, "expenseUpdated": false, "payments": true, "friendRequests": true, "groupInvites": true, "reminders": false, "emailEnabled": true, "pushEnabled": true } }

9. Analytics APIs 9.1 Get Dashboard Data Used in: DashboardScreen.js - Main

dashboard load http Copy GET /api/v1/analytics/dashboard Authorization:

Bearer {token} Success Response (200): JSON Copy { "success": true, "data": { "totalBalance": 150.00, "totalOwed": 0, "totalOwe": 150.00, "currency": "USD",

"monthlyData": [{ "month": "Oct", "income": 5000, "expense": 3200 }, { "month": "Nov", "income": 5000, "expense": 2800 }, { "month": "Dec", "income": 5500,

"expense": 3500 }, { "month": "Jan", "income": 5000, "expense": 3000 }, { "month": "Feb", "income": 5200, "expense": 2900 }, { "month": "Mar", "income": 2000,

"expense": 1500 }], "categoryBreakdown": [{ "id": "food", "name": "Food & Dining", "amount": 450.00, "percentage": 30, "color": "#FF5722", "icon": "food",

"transactionCount": 15 }, { "id": "transport", "name": "Transportation", "amount": 300.00, "percentage": 20, "color": "#2196F3", "icon": "car", "transactionCount": 8

}], "recentTransactions": [{ "id": "transaction-uuid", "description": "Grocery shopping", "amount": 85.50, "type": "expense", "category": { "id": "food", "name": "Food & Dining", "icon": "food" }, "date": "2024-03-14T10:00:00Z" }] } }

9.2 Get Spending by Category Used in: AnalyticsScreen.js, CategoryBreakdownScreen.js http Copy GET /api/v1/analytics/spending-by-category?startDate=2024-03-

01&endDate=2024-03-31 Authorization: Bearer {token} Query Parameters: startDate: Start date (ISO format) endDate: End date (ISO format) Success

Response (200): JSON Copy { "success": true, "data": [{ "id": "food", "name": "Food & Dining", "amount": 450.00, "percentage": 30, "color": "#FF5722", "icon":

"Food & Dining", "amount": 450.00, "percentage": 30, "color": "#FF5722", "icon":

"food", "transactionCount": 15 }, { "id": "transport", "name": "Transportation", "amount": 300.00, "percentage": 20, "color": "#2196F3", "icon": "car", "transactionCount": 8 }, { "id": "shopping", "name": "Shopping", "amount": 250.00, "percentage": 16.7, "color": "#9C27B0", "icon": "shopping", "transactionCount": 5 }] }

9.3 Get Income vs Expense Used in: AnalyticsScreen.js - Charts http Copy GET /api/v1/analytics/income-vs-expense?startDate=2024-03-01&endDate=2024-03-31 Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": { "income": 5000.00, "expense": 3200.00, "net": 1800.00, "dailyData": [{"date": "03-01", "income": 0, "expense": 50}, {"date": "03-02", "income": 0, "expense": 120}, {"date": "03-03", "income": 0, "expense": 0}, {"date": "03-15", "income": 5000, "expense": 200}] } }

9.4 Get Monthly Trends Used in: AnalyticsScreen.js, TrendsScreen.js http Copy GET /api/v1/analytics/monthly-trends?months=6 Authorization: Bearer {token} Query Parameters: months: Number of months to return (default: 6) Success Response (200): JSON Copy { "success": true, "data": [{"month": "Oct 2023", "income": 5000, "expense": 3200}, {"month": "Nov 2023", "income": 5000, "expense": 2800}, {"month": "Dec 2023", "income": 5500, "expense": 3500}, {"month": "Jan 2024", "income": 5000, "expense": 3000}, {"month": "Feb 2024", "income": 5200, "expense": 2900}, {"month": "Mar 2024", "income": 2000, "expense": 1500}] }

9.5 Get Friend Balances for Analytics Used in: AnalyticsScreen.js http Copy GET /api/v1/analytics/friend-balances Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "data": [{ "friendId": "friend-uuid-1", "friend": { "id": "friend-uuid-1", "firstName": "Jane", "lastName": "Smith", "avatar": "[https://cdn.example.com/avatars/uuid1.jpg](\"https://cdn.example.com/avatars/uuid1.jpg\")" }, "totalShared": 1250.00, "youOwe": 0, "youAreOwed": 150.00, "netBalance": 150.00, "expenseCount": 25 }, { "friendId": "friend-uuid-2", "friend": { "id": "friend-uuid-2", "firstName": "Bob", "lastName": "Wilson", "avatar": "[https://cdn.example.com/avatars/uuid2.jpg](\"https://cdn.example.com/avatars/uuid2.jpg\")" }, "totalShared": 800.00, "youOwe": 75.00, "youAreOwed": 0, "netBalance": -75.00, "expenseCount": 18 }] }

10. Category APIs 10.1 Get Categories Used in: CreateExpenseScreen.js, EditExpenseScreen.js http Copy GET /api/v1/categories?type=expense Authorization: Bearer {token} Query Parameters: type: expense or income (optional) Success Response (200): JSON Copy { "success": true, "data": [{ "id": "food", "name": "Food & Dining", "icon": "food", "color": "#FF5722", "type": "expense", "isDefault": true }, { "id": "custom-category-uuid", "name": "Gym Membership", "icon": "dumbbell", "color": "#4CAF50", "type": "expense", "isDefault": false, "createdBy": "user-uuid" }] }
- 10.2 Create Custom Category Used in: (Custom category creation feature) http Copy POST /api/v1/categories

Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "name": "Gym Membership", "icon": "dumbbell", "color": "#4CAF50", "type": "expense" } Success Response (201): JSON Copy { "success": true, "data": { "id": "custom-category-uuid", "name": "Gym Membership", "icon": "dumbbell", "color": "#4CAF50", "type": "expense", "isDefault": false, "createdBy": "user-uuid", "createdAt": "2024-03-15T10:00:00Z" } } 10.3 Update Category Used in: (Edit custom category) http Copy PUT /api/v1/categories/{categoryId} Authorization: Bearer {token} Content-Type: application/json Request Body: JSON Copy { "name": "Updated Name", "icon": "fitness-center", "color": "#2196F3" } Success Response (200): JSON Copy { "success": true, "data": { "id": "custom-category-uuid", "name": "Updated Name", "icon": "fitness-center", "color": "#2196F3", "updatedAt": "2024-03-15T11:00:00Z" } } 10.4 Delete Category Used in: (Delete custom category) http Copy DELETE /api/v1/categories/{categoryId} Authorization: Bearer {token} Success Response (200): JSON Copy { "success": true, "message": "Category deleted successfully" }