

Methodology

Query

Overview

While our online reporting interface allows merchants to quickly and easily retrieve detailed information about past transactions, a need for additional flexibility may be required. For example, a merchant may have custom accounting software that requires up-to-date information about the settlement status of all credit card transactions every day.

This document describes how developers can query our reporting engine directly to retrieve transaction reports in a machine readable format. Once the data has been retrieved, it can then be parsed and imported into a variety of software applications.

Communication

The communication protocol used to send messages to the Payment Gateway is through the HTTP protocol over an SSL connection (HTTPS). The format you must use is name/value pairs delimited by ampersand.

URL:	<code>https://secure.reverepayments.com/api/query.php</code>
Example Post Data:	<code>security_key=security_key&transaction_id=123456789</code>

You should POST your request to the Query API. The name/value pairs that are accepted by the Payment Gateway can be found in the 'Variables' section of this API.

The Query API can be tested with live credentials or a dedicated test account only. Please contact your Merchant Service Provider for more information.

The Query API will respond in Universal Time Coordinated (UTC).

Variables

Query

POST URL

POST URL: <https://secure.reverepayments.com/api/query.php>

Variable Name	Description(Allowed Values)[Format]
security_key*	API Security Key assigned to a merchant account. New keys can be generated from the merchant control panel in Settings > Security Keys
condition	A combination of values listed below can be passed and should be separated by commas. For example, to retrieve all transactions pending settlement or complete, the following could be used: Example: condition=pendingsettlement,complete
	<i>pending</i> : 'Auth Only' transactions that are awaiting capture.
	<i>pendingsettlement</i> : This transaction is awaiting settlement.
	<i>in_progress</i> : This Three-Step Redirect API transaction has not yet been completed. The transaction condition will change to 'abandoned' if 24 hours pass with no further action.
	<i>abandoned</i> : This Three-Step Redirect API transaction has not been completed, and has timed out.
	<i>failed</i> : This transaction has failed.
	<i>canceled</i> : This transaction has been voided.
	<i>complete</i> : This transaction has settled.
	<i>unknown</i> : An unknown error was encountered while processing this transaction.
transaction_type	Retrieves only transactions with the specified transaction type. Use one of the following to specify payment type:
	cc: A credit card transaction.
	ck: A check transaction.

action_type	Retrieves only transactions with the specified action types. A combination of the values can be used and should be separated by commas. For example, to retrieve all transactions with credit or refund actions, use the following:
	Example: action_type=refund,credit
	<i>sale</i> : Sale transactions.
	<i>refund</i> : Refund transactions.
	<i>credit</i> : Credit transactions.
	<i>auth</i> : 'Auth Only' transactions.
	<i>capture</i> : Captured transactions.
	<i>void</i> : Voided transactions.
source	<i>return</i> : Electronic Check (ACH) transactions that have returned, as well as credit card chargebacks.
	Retrieves only transactions with a particular 'transaction source'. A combination of the values can be used and should be separated by commas. For example, to retrieve all transactions with api or recurring actions, use the following:
	Example: source=api,recurring
	<i>api</i> : API transactions.
	<i>batch_upload</i> : Batch Upload transactions.
	<i>mobile</i> : Mobile (iProcess) transactions.
	<i>quickclick</i> : QuickClick transactions.
	<i>quickbooks</i> : QuickBooks SyncPay transactions.
	<i>recurring</i> : Recurring transactions when using Recurring module.
transaction_id	<i>swipe</i> : Swipe transactions.
	<i>virtual_terminal</i> : Virtual Terminal transactions.
subscription_id	<i>internal</i> : Internal transactions. Typically indicates settlement
	Specify a transaction ID or a comma separated list of transaction IDs to retrieve information on. Alternatively, provide a Subscription ID to retrieve processed (approved and declined) transactions associated with it.
	Set a specific subscription record or comma separated list of records. Using this with a transaction search will return all transactions associated with this subscription. This will return this subscription's payment/plan information when used with report_type=recurring.

invoice_id	Set a specific Invoice ID. Should only be used when report_type=invoicing.
partial_payment_id	Retrieves only transactions with the specified partial payment ID.
order_id	Retrieves only transactions with the specified Order ID.
first_name	Retrieves only transactions with the specified first name.
last_name	Retrieves only transactions with the specified last name.
address1	Retrieves only transactions with the specified specified address.
city	Retrieves only transactions with the specified city.
state	Retrieves only transactions with the specified state.
zip	Retrieves only transactions with the specified zip/postal code.
phone	Retrieves only transactions with the specified phone number.
fax	Retrieves only transactions with the specified fax number.
order_description	Retrieves only transactions with the specified order description.
drivers_license_number	Retrieves only transactions with the specified driver's license number.
drivers_license_dob	Retrieves only transactions with the specified driver's license date of birth.
drivers_license_state	Retrieves only transactions with the specified driver's license state.
email	Retrieves only transactions with the specified billing email address.
authorization_code	Retrieves only transactions with the specified authorization code.
cc_number	Retrieves only transactions with the specified credit card number. You can use either the full number or the last 4 digits of the credit card number.
merchant_defined_field_#	Retrieves only transactions with the specified merchant defined field value. Replace the '#' with a field number (1-20) (Example: merchant_defined_field_12=value)

start_date	Only transactions that have been modified on or after this date will be retrieved. Note that any actions performed on a transaction will cause the modified date to be updated. Format: YYYYMMDDhhmmss
end_date	Only transactions that have been modified on or before this date will be retrieved. Note that any actions performed on a transaction will cause the modified date to be updated. Format: YYYYMMDDhhmmss
report_type	Allows Customer Vault information or a html receipt to be returned. If you would like to query the Customer Vault to view what customer information is stored in the Customer Vault, you must set the customer_vault variable. If you omit the customer_vault_id, the system will return all customers that are stored in the vault. If you include a customer_vault_id, it will return the customer record associated with that ID. Example: report_type=customer_vault&customer_vault_id=123456789 <i>receipt</i>: Will return an html receipt for a specified transaction id. <i>customer_vault</i>: Set the Query API to return Customer Vault data. <i>recurring</i>: Set the Query API to return subscription data. <i>recurring_plans</i>: Set the Query API to return plan data. <i>invoicing</i>: Set the Query API to return invoicing data. <i>gateway_processors</i>: Will return Processor details a user has permissions for. Specify a "user" by querying with that security key. <i>account_updater</i>: Will return Customer Vault data that has been updated using the Account Updater service. <i>test_mode_status</i>: Will return whether the account has test mode active or inactive. <i>profile</i>: Return merchant profile (company, email, address, timezone, defined fields, gateway, favicon, status). It will also return card_schemes with 'processor_details' set to 'true'

mobile_device_license	Retrieves only transactions processed using the specified mobile device. The device IDs for this parameter are available in the License Manager. Use 'any_mobile' to retrieve all mobile transactions. A combination of the values can be used and should be separated by commas. Can not be used with 'mobile_device_nickname'. Example 1: mobile_device_license=D91AC56A-4242-3131-2323-2AE4AA6DB6EB Example 2: mobile_device_license=any_mobile
mobile_device_nickname	Retrieves only transactions processed using mobile devices with the specified nickname. The nicknames for this parameter are available in the License Manager. Can not be used with 'mobile_device_license'. Example (URL encoded): mobile_device_nickname=Jim's%20iPhone
customer_vault_id	Set a specific Customer Vault record. Should only be used when report_type=customer_vault.
date_search	Allows Customer Vault information to be returned based on the 'created' or 'updated' date. If you would like to query the Customer Vault to view when customer information was created or updated, you must set the report_type variable with the customer_vault value. If you omit the report_type variable, the system will ignore the date_search variable. Example: report_type=customer_vault&date_search=created,updated&start_date=20170101000000&end_date=20201231232359 <i>created</i>: Will return Customer Vault data created during a specified date range. <i>updated</i>: Will return Customer Vault data updated during a specified date range.
result_limit	Determines the maximum number of results that may return for the current query.
page_number	Determines which "page" of results are returned. For example, "result_limit=100&page_number=0" will return the first 100 results. Using "page_number=1" will return the next 100 results. Default is "0".

result_order	Determines order of in which results are returned. Default value is "standard".
	<i>standard</i> : Returns the results from oldest to newest.
	<i>reverse</i> : Returns the results from newest to oldest.
invoice_status	Specify a comma separated list of what invoice statuses will return when using an "invoicing" report type.
	Example: invoice_status=open,closed,paid
	<i>open</i> : Open Invoices
	<i>paid</i> : Paid Invoices
	<i>closed</i> : Closed Invoices
	<i>past_due</i> : Past Due Invoices
processor_details	Can be use with "report_type"="profile", this will include merchant "card_schemes" in the response

Sample Response

Query with no report_type or report_type "transaction"

```
<nm_response>
<transaction>
<transaction_id>2612675976</transaction_id>
<partial_payment_id></partial_payment_id>
<partial_payment_balance></partial_payment_balance>
<platform_id></platform_id>
<transaction_type>cc</transaction_type>
<condition>complete</condition>
<order_id>1234567890</order_id>
<authorization_code>123456</authorization_code>
<ponumber></ponumber>
<order_description></order_description>
<first_name>John</first_name>
<last_name>Smith</last_name>
<address_1>123 Main St</address_1>
<address_2>Apt B</address_2>
<company></company>
<city>New York City</city>
<state>NY</state>
<postal_code>10001</postal_code>
<country>US</country>
<email>johnsmith@example.com</email>
<phone>1234567890</phone>
<fax></fax>
<cell_phone></cell_phone>
<customertaxid></customertaxid>
<customerid></customerid>
<website></website>
<shipping_first_name></shipping_first_name>
<shipping_last_name></shipping_last_name>
<shipping_address_1></shipping_address_1>
<shipping_address_2></shipping_address_2>
<shipping_company></shipping_company>
<shipping_city></shipping_city>
<shipping_state></shipping_state>
<shipping_postal_code></shipping_postal_code>
<shipping_country></shipping_country>
<shipping_email></shipping_email>
<shipping_carrier></shipping_carrier>
<tracking_number></tracking_number>
<shipping_date></shipping_date>
<shipping>1.00</shipping>
<shipping_phone></shipping_phone>
<cc_number>4xxxxxxxxxxx1111</cc_number>
<cc_hash>f6c609e195d9d4c185dcc8ca662f0180</cc_hash>
<cc_exp>1215</cc_exp>
<cavv></cavv>
<cavv_result></cavv_result>
<xid></xid>
```

<eci></eci>
<directory_server_id></directory_server_id>
<three_ds_version></three_ds_version>
<avs_response>N</avs_response>
<csc_response>M</csc_response>
<cardholder_auth></cardholder_auth>
<cc_start_date></cc_start_date>
<cc_issue_number></cc_issue_number>
<check_account></check_account>
<check_hash></check_hash>
<check_aba></check_aba>
<check_name></check_name>
<account_holder_type></account_holder_type>
<account_type></account_type>
<sec_code></sec_code>
<drivers_license_number></drivers_license_number>
<drivers_license_state></drivers_license_state>
<drivers_license_dob></drivers_license_dob>
<social_security_number></social_security_number>
<processor_id>processora</processor_id>
<tax>1.00</tax>
<currency>USD</currency>
<surcharge></surcharge>
<convenience_fee></convenience_fee>
<misc_fee_name></misc_fee_name>
<misc_fee></misc_fee>
<cash_discount></cash_discount>
<tip></tip>
<card_balance></card_balance>
<card_available_balance></card_available_balance>
<entry_mode>Keyed</entry_mode>
<cc_bin>411111</cc_bin>
<cc_type>visa</cc_type>
<signature_image>
iVBORw0KGgoAAAANSUUhEUgAAABAAAAAQCAIAAACQkwg2AAAAAXNSR0IArs4c6QAAARnQU1BAA
Cxjwv8YQUAAAAJcEhZcwAAEnQA
ABJ0Ad5mH3gAAACGSURBVDhPLZGBEoAgCE01//9nG83mxMrr3dkBG0hVW2vFqLX26CYbPIc7yS
AVE8LBq5u4elyV4M0NXIoGXYqA
w4QqMAWJCRu+Az7HSlvgHtexlFKwGrLjG/h/rESmhrhRnLCKwjiNeLYv5QsX0oNSig8IsNYaZ0
tXJoGU9hU1k18XlZL0QHTenf7I
cf3BwAAAABJRU5ErkJggg==
</signature_image>
<network_token_used>Y</network_token_used>
<network_token_created>true</network_token_created>
<network_token_cryptogram_created>true</network_token_cryptogram_created>
<network_token>4xxxxxxxxxxx1000</network_token>
<token_or_card_number>4xxxxxxxxxxx1000</token_or_card_number>
<network_token_expiration>1229</network_token_expiration>
<product>
<sku>RS-100</sku>
<quantity>1.0000</quantity>
<description>Red Shirt</description>
<amount>10.0000</amount>
</product>
<action>
<amount>11.00</amount>
<action_type>sale</action_type>

```
<date>20150312215205</date>
<success>1</success>
<ip_address>1.1.1.1</ip_address>
<source>virtual_terminal</source>
<api_method></api_method>
<username>demo</username>
<response_text>SUCCESS</response_text>
<batch_id>0</batch_id>
<processor_batch_id></processor_batch_id>
<response_code>100</response_code>
<processor_response_text>NO MATCH</processor_response_text>
<processor_response_code>00</processor_response_code>
<requested_amount>11.00</requested_amount>
<device_license_number></device_license_number>
<device_nickname></device_nickname>
</action>
<action>
<amount>11.00</amount>
<action_type>level3</action_type>
<date>20150312215205</date>
<success>1</success>
<ip_address>1.1.1.1</ip_address>
<source>virtual_terminal</source>
<api_method></api_method>
<username>demo</username>
<response_text></response_text>
<batch_id>0</batch_id>
<processor_batch_id></processor_batch_id>
<response_code>100</response_code>
<processor_response_text></processor_response_text>
<processor_response_code></processor_response_code>
<device_license_number></device_license_number>
<device_nickname></device_nickname>
</action>
<action>
<amount>11.00</amount>
<action_type>settle</action_type>
<date>20150313171503</date>
<success>1</success>
<ip_address></ip_address>
<source>internal</source>
<api_method></api_method>
<username></username>
<response_text>ACCEPTED</response_text>
<batch_id>76158269</batch_id>
<processor_batch_id>782</processor_batch_id>
<response_code>100</response_code>
<processor_response_text></processor_response_text>
<processor_response_code>00000000000021980</processor_response_code>
<device_license_number></device_license_number>
<device_nickname></device_nickname>
</action>
</transaction>
</nm_response>
```

Query with report_type "profile" and processor_details "true"

```
<nm_response>
<protected>false</protected>
<is_gateway>false</is_gateway>
<merchant>
<company>Test Company</company>
<email>johnsmith@example.com</email>
<phone>123-456-7890</phone>
<url></url>
<address1>123 Fake St</address1>
<address2></address2>
<city>Beverly Hills</city>
<state>CA</state>
<zip>90210</zip>
<country>US</country>
<timezone>America/New_York (GMT-05:00) Eastern Time (US & Canada)</timezone>
<card_schemes>Visa,Mastercard,American Express,Discover,Diner's
Club,JCB,Maestro,Banco Popular,Isracard,Hipercard,Credomatic
Card,EBT</card_schemes>
</merchant>
<gateway>
<company>Test Reseller</company>
<url></url>
<email>johnsmith@example.com</email>
<phone>123-456-7890</phone>
<primary_color>36175F</primary_color>
<complimentary_color_1>F1577B</complimentary_color_1>
<complimentary_color_2>26CC9D</complimentary_color_2>
</gateway>
<merchant_defined_fields></merchant_defined_fields>
<merchant_favicon>iVBORw0KGgoAAAANSUHEUgAAALQAAAC0CAMAAAAAKE/YAAAAABGdBTUEAALGPC/xh
BQAAAAFzUkdCAK7OH0KAAACfUEXURUdwTPX19fX19fb29vn5+fX19fX19fb29vX19fX19fb29vb29v/////
b29vX19f/////n5+fX19fn5+fX19ff39/X19fb29vX19fb29vX19f/////X19fX19fb29vX19fb29vX19fX1
9fb29mRkZBcXF/X19e7u7hsbGx8fH0dHR8rKytjY2IWFhb6+vqysrDk50Tg40FBQUCgoKCEhISIiIj0J5R
MAAAAJdFJOUwD83x8tUeeStfk9rAbl7w8wzDHsINJ82Y42CcFnf/0/9v4+JiMvSAAAAqRJREFUeNrt3dls
wkAUBNBhkSTsyCqr4lyRffP/v81dS0wmQCnc1u5Hn85DhAxV022MK+1ht+XXk9VATpSgmqz7re6wbY7Mva
9zMuw3fKd3dbi41mjKmdNs1A4iX+b6oiD930Xe5LIvauKX9yKXvIQoSsIrxZsvMqIsmYsYct4ThfHyLn0q
IipTSUwb0wVRmkI6ypwtitoUsxHma1Gc61B1uiiqUwx5QlIFUZ7Ct//GfEXUp7L7yecJQLyd70GByJfvxl
IGA50poT0c0w9IOYGCTny+qfoCE//jnCJAeT/L5JDQubcz7A0Suv962m0IVBov6CYWuvnym4yA5flXnB4a
uveE7qCh08a0AzR00DYDgcvAdPHQXdPCQ7eQXpY+X5rqe0i6SeKhk6aKh66aiI/pyWy92tpzZrtazybhH9
Qm9M+LpdWR5SKMF4aejq2ejKd7oecbqymb+R7o+cjqymgei55urLZspnHosdWxcQx6YTVm4UYvVaKXTvTE
6szEhZ4pRc9c6LVS9NqFXilFr1zorVL01ow2WkM00Uei77XGhb7VGqKJJppooookmmmmiiiSaaaKKJJlTeq
Q1/FmMaKKJJppooookm+qfQd78aookmmmmiiiSaaaKKJ/ttonlyIJhrgYES00UQTtTTR/wPNdw+iMS6cPfy5
q32Qlyghr6tCXgyGvIKNedkdsLYAs8ABsioDs5QEs/4Fs2hHe6VRJFp1TIBnDjBruiAL0ScR5yBL/iDrFC
GLKwErQoeYZayQtbeYBC0QVc6QpdmY9eSQRfCQlFuY4waQMxKYgx2Q0yiYIzSQcz+Yw0qYE1aQY2GYs2yY
A3iYU40Yo46Y85mYQ6WYk7Cg47uYM8evg9Iqzo2HDEqDTneDjqS/zdEPzjNHP3DP0T8C4oBc15g2YiAAAA
AASUVORK5CYII=</merchant_favicon>
<account_details>
<account_status>active</account_status>
<test_mode_enabled>false</test_mode_enabled>
</account_details>
</nm_response>
```