

Lecture 22 - Query Performance Tuning

Explain Plans and Query Performance - <https://youtu.be/nnSPpLKTrbY>

Final Review - <https://youtu.be/3PP6L8nrppE>

From Amazon S3 - for download (same as youtube videos)

[Explain Plans and Query Performance](#)

[Final Review](#)

```
SELECT CurrentInvoices.seller_no, ArchivedInvoices.sales_amt, CurrentInvoices.sales_amt
FROM
(
    SELECT
        seller_no,
        sum(invoice_amt) as sales_amt
    FROM invoice
    WHERE invoice_date < CURRENT_DATE
    GROUP BY
        seller_no,
        invoice_date
    ORDER BY
        seller_no,
        invoice_date
) as CurrentInvoices,
(
    SELECT
        seller_no,
        sum(invoice_amt) as sales_amt
    FROM archived_invoice
    WHERE invoice_date >= date_trunc('month', CURRENT_DATE - interval '1' month)
        and invoice_date < date_trunc('month', CURRENT_DATE)
    GROUP BY
        seller_no,
        invoice_date
    ORDER BY
        seller_no,
        invoice_date
) as ArchivedInvoices
WHERE CurrentInvoices.seller_no = ArchivedInvoices.seller_no
;
```

Indexes are good and bad.

Good:

1. Search's faster, sorts faster. This is the 43 min to 11 min.
2. Unique constraints. PostgreSQL requires an index for this. Oracle, DB2 can have unique constraints w/o an index. This is good for small tables - and a disaster for large ones. I don't remember if MS SQL Server or MySQL allow this.
3. Foreign Key check. Think triggers.

Bad:

1. Indexes mean that when you insert/update they have to get updates. More indexes mean slower write operations. Most d.b.'s are 90% search and 10% write. This is not true for TimeSeries data where it is 90% write and 10% search. Network database, Cassandra, Neo4j etc, are write heavy also.
2. They take space also.

Functions in where

You can use functions in the where clause. A good example is `soundex` or other data check / search functions.

```
select name
  from users
 where soundex($1) = soundex(name)
;
```

This will actually perform a full table scan and run `soundex` 2 times for every row. PG has no way of knowing if the function `soundex` is pure-functional or not!

V.S.

```
create materialized view users_soundex as
  select t1.*, soundex(name) as name_soundex
    from users as t1
;

create index users_soundex_p1 on users_soundex ( users_soundex )

select name
  from users_soundex
 where name_soundex = soundex($1)
;
```

This runs `soundex(name)` once for every row and saves the result during the view creation. Then once for every insert/update.

Then the query runs `soundex` once for every key/index value.

Side Note:

PostgreSQL can pull data directly from the index, so...

```
create materialized view users_soundex as
  select t1.name, soundex(name) as name_soundex
  from users as t1
;

create index users_soundex_p1 on users_soundex ( users_soundex, name )

select name
  from users_soundex
 where name_soundex = soundex($1)
;
```

will not access the table at all!

```
select name
  from users_soundex
 where name_soundex = soundex($1)
 order by name
;
```

will return data in sorted order for "free".

Explain Plan

Explain plan 2 modified for printing:

```
pschlump=# \i explain-p3.sql
explain analyze
  select
    "t2"."username"
  ,    "t2"."id" as "user_id"
  ,    'root' as "user_role"
  from
    "t1_customer" as "t3" inner join "t1_user" as "t2"
      on "t3"."root_user_id" = "t2"."id"
```

```

where
    "t3"."id" = '3f9f4a09-2d8d-414e-5afc-038ef6cec3e0'
union
select
    "t2"."username"
,    "t2"."id" as "user_id"
,    "t4"."user_role"
from
    "t1_customer_users" as "t4" inner join "t1_user" as "t2"
        on "t4"."user_id" = "t2"."id"
where
    "t4"."customer_id" = '3f9f4a09-2d8d-414e-5afc-038ef6cec3e0'
order by 1 asc, 3 asc
;

```

QUERY PLAN

```

-----
Sort (cost=6052.40..6052.41 rows=4 width=80) (actual time=38.323..38.324
    ~~~~~ !!!!!
rows=1 loops=1)
  Sort Key: t2.username, ('root'::text)
  Sort Method: quicksort Memory: 25kB
-> HashAggregate (cost=6052.32..6052.36 rows=4 width=80) (actual
    time=38.270..38.270 rows=1 loops=1)
    ~~~~~
      Group Key: t2.username, t2.id, ('root'::text)
      -> Append (cost=136.24..6052.29 rows=4 width=80) (actual
        time=1.339..38.258 rows=1 loops=1)
        -> Hash Join (cost=136.24..3085.15 rows=1 width=58)
          (actual time=1.339..38.212 rows=1 loops=1)
          Hash Cond: (t2.id = t3.root_user_id)
            ~~~~~
            -> Seq Scan on t1_user t2 (cost=0.00..2500.02 rows=119702
              width=26) (actual time=0.024..16.775 rows=119702
                ~~~~~
                loops=1)
            -> Hash (cost=136.23..136.23 rows=1 width=16) (actual
              time=1.295..1.295 rows=1 loops=1)
                ~~~~~
                Buckets: 1024 Batches: 1 Memory Usage: 9kB
            -> Seq Scan on t1_customer t3 (cost=0.00..136.23
              rows=1 width=16) (actual time=0.018..1.287
              rows=1 loops=1)
              Filter: (id =
                '3f9f4a09-2d8d-414e-5afc-038ef6cec3e0'::uuid)
              Rows Removed by Filter: 5937
              ~~~~~
            -> Hash Join (cost=18.16..2967.10 rows=3 width=58) (actual
              time=0.044..0.044 rows=0 loops=1)
              Hash Cond: (t2_1.id = t4.user_id)
              -> Seq Scan on t1_user t2_1 (cost=0.00..2500.02
                ~~~~~

```

```

rows=119702 width=26) (actual
time=0.010..0.010 rows=1 loops=1)
-> Hash (cost=18.12..18.12 rows=3 width=48) (actual
time=0.003..0.003 rows=0 loops=1)
    Buckets: 1024 Batches: 1 Memory Usage: 8kB
    -> Seq Scan on t1_customer_users t4
        (cost=0.00..18.12 rows=3 width=48) (actual
time=0.002..0.002 rows=0 loops=1)
        Filter: (customer_id =
'3f9f4a09-2d8d-414e-5afc-038ef6cec3e0'::uuid)

Planning time: 1.158 ms
Execution time: 38.521 ms
(23 rows)

```

Explain works on any DML

... so not just selects. It works on UPDATE, DELETE etc.

EXPLAIN v.s. EXPLAIN ANALYZE

ANALYZE takes a bunch more time - but uses statistics from the last time you did an ANALYZE on the database. Also EXPLAIN ANALYZE may run the query to get actual times. So if the query takes 43 minutes you should go for coffee.

(cost=6052.40..6052.41 and Nodes. Each block is a "processing node" and the time it reports is the time that that node took plus the sum of all child nodes. At the top is the total cost for running the query. This lets you isolate the chunks of the query that take the most time.

6052.40 - first number is startup cost. This is cost to get to 1st row.

6052.41 - time to process entire set.

(cost 1.339..38.258 rows=1 loops=1) better example 1.339 for first, 38.258 for all rows. (cost is an *estimate* based on analyze data. DBs use a "cost" minimize approach - so with different possibilities it will pick the sub-nodes in the tree that give it the least cost. This also means that if you load 10,000,000 new rows to a table that used to have 10 rows and you don't do a new ANALYZE on the database then the cost values are way way out of wack and the plans generated will be horrid.

(actual time=0.024..16.775 rows=119702 this is initial/total time with data for actually running the query. The units are in milliseconds.

... loops=1) this shows where it is actually looping over something in the plan.

Rows Removed by Filter: 5937 how many rows were eliminated.

Seq Scan on t1_user t2_1 This is how it is accessing the data, and what table was used and any indexes used.

Let's start simple and work up:

```
create table exp_1 (  
    i int  
);
```

```
EXPLAIN  
    SELECT *  
    FROM exp_1  
    WHERE i = 0;
```

Output:

QUERY PLAN

```
Seq Scan on exp_1 (cost=0.00..41.88 rows=13 width=4)  
  Filter: (i = 0)  
(2 rows)
```

or

```
create table exp_1 (  
    i int  
);
```

```
EXPLAIN ANALYZE  
    SELECT *  
    FROM exp_1  
    WHERE i = 0;
```

QUERY PLAN

```
Seq Scan on exp_1 (cost=0.00..41.88 rows=13 width=4) (actual time=0.003..0.003  
  rows=0 loops=1)  
  Filter: (i = 0)  
  Planning time: 0.059 ms  
  Execution time: 0.034 ms  
(4 rows)
```

Seq Scan on <Table> means full table scan.

Now a table with a primary key:

```
CREATE SEQUENCE exp_3_id_seq
  INCREMENT 1
  MINVALUE 1
  MAXVALUE 9223372036854775807
  START 1
  CACHE 1;

create table exp_3 (
  id                bigint DEFAULT nextval('exp_3_id_seq'::regclass) NOT NU
  user_data         bigint
);

explain analyze
  select *
  from exp_3
  where id = 55
;

explain analyze
  select *
  from exp_3
  where user_data = 55
;
```

output:

...

```
explain analyze
  select *
  from exp_3
  where id = 55
;
```

QUERY PLAN

```
-----
Index Scan using exp_3_pkey on exp_3 (cost=0.15..8.17 rows=1 width=16)
(actual time=0.021..0.021 rows=0 loops=1)
  Index Cond: (id = 55)
Planning time: 0.217 ms
Execution time: 0.047 ms
(4 rows)
```

```
explain analyze
```

```

select *
from exp_3
where user_data = 55
;

```

QUERY PLAN

```

-----
Seq Scan on exp_3  (cost=0.00..33.12 rows=9 width=16) (actual time=0.002..0.002
rows=0 loops=1)
  Filter: (user_data = 55)
Planning time: 0.043 ms
Execution time: 0.017 ms
(4 rows)

```

You can tune the "costs" that it uses - this is set in postgresql.conf. In Oracle it is in <database>_init.ora , in DB2 in <instanceName>_setup . In MySQL... and in SQL Server... hm... Nobody knows what nobody knows.

postgresql.conf, these params:

seq_page_cost = 1.0	# measured ON an arbitrary scale
random_page_cost = 4.0	# same scale AS above
cpu_tuple_cost = 0.01	# same scale AS above
cpu_index_tuple_cost = 0.005	# same scale AS above
cpu_operator_cost = 0.0025	# same scale AS above

Postgres lacks the ability to set this on a per-volume basis - so you may want to set random_page_cost = 1.0 on SSD and 4.0 is low for a real disk - it is more in the range of 16 to 50.

Let's add an index to exp_3 and see the result:

```

create index exp_3_p1 on exp_3 ( user_data );

explain analyze
  select *
  from exp_3
  where user_data = 55
;

```

output:

```

create index exp_3_p1 on exp_3 ( user_data );
CREATE INDEX

```



```
explain analyze
  select *
  from exp_3
  where user_data = 55
;
```

QUERY PLAN

```
Bitmap Heap Scan on exp_3 (cost=4.22..14.76 rows=9 width=16) (actual
time=0.031..0.031 rows=0 loops=1)
  Recheck Cond: (user_data = 55)
    -> Bitmap Index Scan on exp_3_p1 (cost=0.00..4.22 rows=9 width=0) (actual
        time=0.003..0.003 rows=0 loops=1)
          Index Cond: (user_data = 55)
Planning time: 0.259 ms
Execution time: 0.666 ms
(6 rows)
```

Copyright

Copyright © University of Wyoming, 2021