```php
1    <?
2
3    session_start();
4
5    require "include/template.inc.php";
6    require "include/dbms.inc.php";
7    require "include/auth.inc.php";
8    require "include/functions.inc.php";
9
10   $editortype = 0;
11   $main = new Template("dtml/cms_layout.html");
12   $menu = new Template("dtml/cms_menu_admin.html");
13   $content = new Template("dtml/cms_form_contenuto.html");
14   $main->setContent("utente", getResult("SELECT nome,cognome FROM utente
     WHERE username = '{$_SESSION['user']['username']}'"));
15   $main->setContent("username", $_SESSION['user']['username']);
16   $menu->setContent("pubblicati", getResult("SELECT * FROM contenuto
     WHERE (pubblicato = 'Y') AND (username =
     '{$_SESSION['user']['username']}')"));
17   $menu->setContent("bozze", getResult("SELECT * FROM contenuto WHERE
     (pubblicato = 'N') AND (username =
     '{$_SESSION['user']['username']}')"));
18   $menu->setContent("presenti", getResult("SELECT * FROM sezione"));
19   $menu->setContent("segnalati", getResult("SELECT * FROM link"));
20   $menu->setContent("archivio", getResult("SELECT * FROM file WHERE
     username = '{$_SESSION['user']['username']}'"));
21   $main->setContent("menu", $menu->get() );
22   $content->setContent("sezioni", getResult("SELECT id,nome FROM sezione
     ORDER BY nome"));
23
24   switch($_REQUEST['editor']) {
25       case 0:
26       default:
27           $content->setContent("editortype", "0");
28           break;
29       case 1:
30           $kindatext = new Template("dtml/cms_rich_text.html");
31           $content->setContent("kindatext", $kindatext->get());
32           $content->setContent("editortype", "1");
33           $editortype = 1;
34           break;
35   }
36   // Contenuto
37
38   switch($_REQUEST['page']) {
39       case 0:
40           $main->setContent("content", $content->get() );
41           break;
42       case 1:
43
44           foreach ($_REQUEST as $k=>$value) {
```

```php
45              $_REQUEST[$k] = addslashes($value);
46          }
47
48          if(!$editortype) {
49              $_REQUEST['testo'] = nl2br($_REQUEST['testo']);
50          }
51
52          $subsections = explode("|", $_REQUEST['sezioni']);
53          $selectedFiles = explode("|", $_REQUEST['selectedFiles']);
54
55          $today = date('Y-m-d');
56          $now = date('H:i:s');
57
58          $oid = mysql_query("INSERT INTO contenuto
59                              VALUES (NULL,
60
   '{$_SESSION['user']['username']}',
61                                      '{$_REQUEST['titolo']}',
62                                      '{$_REQUEST['testo']}',
63                                      '{$now}',
64                                      '{$today}',
65                                      '{$now}',
66                                      '{$today}',
67                                      '{$_REQUEST['pubblicato']}',
68                                      {$editortype})");
69
70          $hid = mysql_query("SELECT id FROM contenuto
71                              WHERE (titolo = '{$_REQUEST['titolo']}')
72                              AND (ora_creazione = '$now')
73                              AND (data_creazione = '$today')");
74
75          $aux = mysql_fetch_assoc($hid);
76
77          /* Inserimento FILE (se associati) */
78          if (count($selectedFiles) > 0) {
79              foreach ($selectedFiles as $key => $value) {
80                  if ($value != "") {
81                      $qid = mysql_query("INSERT INTO contenuto_file
82                                          VALUES ({$aux['id']},
   '".addslashes($value)."')");
83                  }
84              }
85          }
86
87          /* Inserimento SOTTOSEZIONI */
88          foreach ($subsections as $key => $value) {
89              $suid = mysql_query("INSERT INTO contenuto_sottosezione
90                                   VALUES ({$aux['id']}, {$value})
   ");
91          }
92
```

```php
 93            if($oid) {
 94                    $main = new Template("dtml/cms_layout.html");
 95                    $main->setContent("utente", getResult("SELECT nome,cognome
     FROM utente WHERE username = '{$_SESSION['user']['username']}'"));
 96                    $main->setContent("username",
     $_SESSION['user']['username']);
 97                    $menu = new Template("dtml/cms_menu_admin.html");
 98                    $content = new Template("dtml/cms_form_contenuto.html");
 99                    $menu->setContent("pubblicati", getResult("SELECT * FROM
     contenuto WHERE (pubblicato = 'Y') AND (username =
     '{$_SESSION['user']['username']}')"));
100                    $menu->setContent("bozze", getResult("SELECT * FROM
     contenuto WHERE (pubblicato = 'N') AND (username =
     '{$_SESSION['user']['username']}')"));
101                    $menu->setContent("presenti", getResult("SELECT * FROM
     sezione"));
102                    $menu->setContent("segnalati", getResult("SELECT * FROM
     link"));
103                    $menu->setContent("archivio", getResult("SELECT * FROM file
     WHERE username = '{$_SESSION['user']['username']}'"));
104                    $main->setContent("menu", $menu->get() );
105                    $content->setContent("sezioni", getResult("SELECT id,nome
     FROM sezione ORDER BY nome"));
106                    $content->setContent("message", "  Articolo
     inserito correttamente.", "esito=\"ok\"");
107            } else {
108                    $content->setContent("message", "  Articolo non
     inserito. Controllare i campi.", "esito=\"ko\"");
109            }
110
111        $main->setContent("content", $content->get() );
112        break;
113 }
114
115 $main->close();
116
117 ?>
```