بسمه تعالی

School of Computer Engineering

Advanced Computer Networks

Transport Layer and Congestion Control

Part 1 & 2

Seyed Hamed Rastegar

Fall 1401

Lecture: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Connection-oriented transport: TCP
- Principles of congestion control
- Congestion Control Techniques

- **Note**: Parts of these slides are adapted from the book and supplementary slides of:
- Kurose, J.F. and Ross, K.W. Computer Networking: A Top-Down Approach. Addision Wesley. 8th edition, 2020.

All material copyright 1996-2020
J.F Kurose and K.W. Ross, All Rights Reserved

Transport services and protocols

- provide *logical communication* between application processes running on different hosts
- transport protocols actions in end systems:
  - sender: breaks application messages into *segments*, passes to network layer
  - receiver: reassembles segments into messages, passes to application layer
- two transport protocols available to Internet applications
  - TCP, UDP



Transport vs. network layer services and protocols

household analogy:

12 kids in Ann's house sending letters to 12 kids in Bill's house:

- hosts = houses
- processes = kids
- app messages = letters in envelopes

Transport vs. network layer services and protocols

- network layer: logical communication between *hosts*
- transport layer*:* logical communication between *processes*
  - relies on, enhances, network layer services

household analogy:

12 kids in Ann's house sending letters to 12 kids in Bill's house:

- hosts = houses
- processes = kids
- app messages = letters in envelopes

Transport Layer Actions

Sender:

- is passed an application-layer message
- determines segment header fields values
- creates segment
- passes segment to IP



Transport Layer Actions



Receiver:

- receives segment from IP
- checks header values
- extracts application-layer message
- demultiplexes message up to application via socket





Two principal Internet transport protocols

- **TCP:** Transmission Control Protocol
  - reliable, in-order delivery
  - congestion control
  - flow control
  - connection setup
- **UDP:** User Datagram Protocol
  - unreliable, unordered delivery
  - no-frills extension of "best-effort" IP
- services not available:
  - delay guarantees
  - bandwidth guarantees



Lecture: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Connection-oriented transport: TCP
- Principles of congestion control
- Congestion Control Techniques

Multiplexing and Demultiplexing

- It happens in all layers of the protocol stack.
- We study it here in the context of transport layer.





Multiplexing and Demultiplexing

- The inverse action of de-multiplexing.



multiplexing



multiplexing

HTTP server


client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
HTTP msg
transport
network
link
physical
application
transport
network
link
physical

HTTP server


client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
HTTP msg
H_t HTTP msg
network
link
physical
application
transport
network
link
physical



HTTP server
client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
HTTP msg
H_t HTTP msg
$H_n H_t$ HTTP msg
link
physical
application
transport
network
link
physical

HTTP server



client
application
NETFLIX
transport
network
link
physical
APACHE
HTTP SERVER
transport
network
link
physical
application
transport
network
link
physical
H_n H_t HTTP msg


HTTP
client$_1$
application
NETFLIX
transport
network
link
physical
P-client$_1$
P-client$_2$
transport
network
link
physical
client$_2$
application
transport
network
link
physical

Multiplexing/demultiplexing

multiplexing at sender:

handle data from multiple sockets, add transport header (later used for demultiplexing)

demultiplexing at receiver:

use header info to deliver received segments to correct socket



How demultiplexing works

- host receives IP datagrams
  - each datagram has source IP address, destination IP address
  - each datagram carries one transport-layer segment
  - each segment has source, destination port number
- host uses *IP addresses & port numbers* to direct segment to appropriate socket



TCP/UDP segment format

Connectionless demultiplexing

Recall:

- when creating socket, must specify *host-local* port #:

```
DatagramSocket mySocket1
  = new DatagramSocket(12534);
```

- when creating datagram to send into UDP socket, must specify
  - destination IP address
  - destination port #

when receiving host receives *UDP* segment:

- checks destination port # in segment
- directs UDP segment to socket with that port #

IP/UDP datagrams with *same dest. port #,* but different source IP addresses and/or source port numbers will be directed to *same socket* at receiving host

Connectionless demultiplexing: an example

```
DatagramSocket mySocket2 =
 new DatagramSocket
 (9157);
```

```
DatagramSocket
 serverSocket = new
 DatagramSocket
 (6428);
```

```
DatagramSocket mySocket1 =
 new DatagramSocket (5775);
```



Connection-oriented demultiplexing

- TCP socket identified by 4-tuple:
  - source IP address
  - source port number
  - dest IP address
  - dest port number
- demux: receiver uses *all four values (4-tuple)* to direct segment to appropriate socket
- server may support many simultaneous TCP sockets:
  - each socket identified by its own 4-tuple
  - each socket associated with a different connecting client

Connection-oriented demultiplexing: example



Three segments, all destined to IP address: B,
dest port: 80 are demultiplexed to *different* sockets

Summary

- Multiplexing, demultiplexing: based on segment, datagram header field values
- **UDP:** demultiplexing using destination port number (only)
- **TCP:** demultiplexing using 4-tuple: source and destination IP addresses, and port numbers
- Multiplexing/demultiplexing happen at *all* layers

Chapter 3: roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Connection-oriented transport: TCP
- Principles of congestion control
- Congestion Control Techniques

UDP: User Datagram Protocol

- "no frills," "bare bones" Internet transport protocol
- "best effort" service, UDP segments may be:
  - lost
  - delivered out-of-order to app
- *connectionless:*
  - no handshaking between UDP sender, receiver
  - each UDP segment handled independently of others

Why is there a UDP?

- no connection establishment (which can add RTT delay)
- simple: no connection state at sender, receiver
- small header size
- no congestion control
  - UDP can blast away as fast as desired!
  - can function in the face of congestion

UDP: User Datagram Protocol

- UDP use:
  - streaming multimedia apps (loss tolerant, rate sensitive)
  - DNS
  - SNMP
  - HTTP/3
- if reliable transfer needed over UDP (e.g., HTTP/3):
  - add needed reliability at application layer
  - add congestion control at application layer

UDP: User Datagram Protocol [RFC 768]

INTERNET STANDARD

RFC 768 J. Postel
ISI
28 August 1980

User Datagram Protocol

Introduction

This User Datagram Protocol (UDP) is defined to make available a datagram mode of packet-switched computer communication in the environment of an interconnected set of computer networks. This protocol assumes that the Internet Protocol (IP) [1] is used as the underlying protocol.

This protocol provides a procedure for application programs to send messages to other programs with a minimum of protocol mechanism. The protocol is transaction oriented, and delivery and duplicate protection are not guaranteed. Applications requiring ordered reliable delivery of streams of data should use the Transmission Control Protocol (TCP) [2].

Format

```
 0      7 8     15 16    23 24    31
+--------+--------+--------+--------+
|     Source      |   Destination   |
|      Port       |      Port       |
+--------+--------+--------+--------+
|                 |                 |
|     Length      |    Checksum     |
+--------+--------+--------+--------+
|
|          data octets ...
+---------------- ...
```

UDP: Transport Layer Actions



UDP: Transport Layer Actions



UDP sender actions:

- is passed an application-layer message
- determines UDP segment header fields values
- creates UDP segment
- passes segment to IP

UDP: Transport Layer Actions



UDP receiver actions:

- receives segment from IP
- checks UDP checksum header value
- extracts application-layer message
- demultiplexes message up to application via socket

UDP segment header



UDP segment format

UDP checksum

Goal: detect errors (*i.e.*, flipped bits) in transmitted segment

	1st number	2nd number	sum
Transmitted:	5	6	11
Received:	4	6	11

receiver-computed checksum ≠ sender-computed checksum (as received)

UDP checksum

Goal: detect errors (*i.e.*, flipped bits) in transmitted segment

sender:

- treat contents of UDP segment (including UDP header fields and IP addresses) as sequence of 16-bit integers
- checksum: addition (one's complement sum) of segment content
- checksum value put into UDP checksum field

receiver:

- compute checksum of received segment
- check if computed checksum equals checksum field value:
  - Not equal - error detected
  - Equal - no error detected. *But maybe errors nonetheless?* More later ….

Internet checksum: an example

example: add two 16-bit integers

		1	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0
		1	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1
wraparound	1	1	0	1	1	1	0	1	1	1	0	1	1	1	0	1	1
sum		1	0	1	1	1	0	1	1	1	0	1	1	1	1	0	0
checksum		0	1	0	0	0	1	0	0	0	1	0	0	0	0	1	1

Note: when adding numbers, a carryout from the most significant bit needs to be added to the result

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

Internet checksum: weak protection!

example: add two 16-bit integers

		1	1	1	0	0	1	1	0	0	1	1	0	0	1	1	0
		1	1	0	1	0	1	0	1	0	1	0	1	0	1	0	1
wraparound	1	1	0	1	1	1	0	1	1	1	0	1	1	1	0	1	1
sum		1	0	1	1	1	0	1	1	1	0	1	1	1	1	0	0
checksum		0	1	0	0	0	1	0	0	0	1	0	0	0	0	1	1

0 1
1 0

Even though numbers have changed (bit flips), *no* change in checksum!

Summary: UDP

- "no frills" protocol:
  - segments may be lost, delivered out of order
  - best effort service: "send and hope for the best"
- UDP has its plusses:
  - no setup/handshaking needed (no RTT incurred)
  - can function when network service is compromised
  - helps with reliability (checksum)
- build additional functionality on top of UDP in application layer (e.g., HTTP/3)

Lecture roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Connection-oriented transport: TCP
  - ARQ schemes
  - segment structure
  - reliable data transfer
  - flow control
  - connection management
- Principles of congestion control
- Congestion control Techniques

ARQ Schemes (ACK protocols)

- Automatic Repeat ReQuest (ARQ) is an error-control protocol that automatically initiates a call to retransmit any data packet or frame after receiving flawed or incorrect data.

- When the transmitting device fails to receive an acknowledgement signal to confirm the data has been received, it usually retransmits the data after a predefined timeout and repeats the process a predetermined number of times until the transmitting device receives the acknowledgement.

- ARQ schemes generally has three main parts:
  - Error detection,
  - Receiver feedback,
  - Retransmission

ARQ Schemes (ACK protocols)

- Three main types of ARQ:
  - **Stop and Wait ARQ**: The sender expects an ACK for each sent packet before transmitting the next one until a timeout.

❑ What is the problem with S&W ARQ?





ARQ Schemes (ACK protocols)



Very Low Resource Utilization!

ARQ Schemes (ACK protocols)

Why not send other packets meanwhile?



ARQ Schemes (ACK protocols)

Pipelining

- Rather than operate in a stop-and-wait manner, the sender is allowed to send multiple packets without waiting for acknowledgments.
- **Other types of ARQ use this approach.**



a. A stop-and-wait protocol in operation



b. A pipelined protocol in operation

ARQ Schemes (ACK protocols)

- Three main types of ARQ:
  - **Go back N ARQ**: The sender after a timeout start transmitting from the first unACKed packet. (uses sliding window mechanism)



ARQ Schemes (ACK protocols)

- Types of Automatic Repeat ReQuest (ARQ):
  - **Selective Repeat ARQ**: The sender after a timeout start **just** unacked packets and the next unsent packets (uses sliding window mechanism)



ARQ Schemes (ACK protocols)

- **Hybrid ARQ (HARQ)**: it is a more advanced version of ARQ schemes.

- In HARQ, when the receiver detects an error, it does **not** immediately request a retransmission from the sender, but tries to recover the information itself.

- Type main types:
  - **HARQ Incremental Redundancy (IR):** In this scheme, the receiver employ error correcting coding schemes to recover from the errors.
  - **HARQ Chase Combining (CC):** In this scheme, the receiver concatenate all the received (but error detected) versions of the packets and tries to recover the correct one from them.

TCP: overview RFCs: 793,1122, 2018, 5681, 7323

- point-to-point:
  - one sender, one receiver
- reliable, in-order *byte steam:*
  - no “message boundaries"
- full duplex data:
  - bi-directional data flow in same connection
  - MSS: maximum segment size
- cumulative ACKs
- pipelining:
  - TCP congestion and flow control set window size
- connection-oriented:
  - handshaking (exchange of control messages) initializes sender, receiver state before data exchange
- flow controlled:
  - sender will not overwhelm receiver

TCP segment structure

ACK: seq # of next expected byte; A bit: this is an ACK

length (of TCP header)

Internet checksum

C, E: congestion notification

TCP options

RST, SYN, FIN: connection management



segment seq #: counting bytes of data into bytestream (not segments!)

flow control: # bytes receiver willing to accept

data sent by application into TCP socket

TCP sequence numbers, ACKs

Sequence numbers:

- byte stream "number" of first byte in segment's data

Acknowledgements:

- seq # of next byte expected from other side
- cumulative ACK
- TCP uses a variant of Go back N ARQ

Q: how receiver handles out-of-order segments

- *A:* TCP spec doesn't say, - up to implementor



TCP sequence numbers, ACKs



simple telnet scenario

TCP round trip time, timeout

Q: how to set TCP timeout value?

- longer than RTT, but RTT varies!
- *too short:* premature timeout, unnecessary retransmissions
- *too long:* slow reaction to segment loss

Q: how to estimate RTT?

- `SampleRTT`: measured time from segment transmission until ACK receipt
  - ignore retransmissions
- `SampleRTT` will vary, want estimated RTT "smoother"
  - average several *recent* measurements, not just current `SampleRTT`

TCP round trip time, timeout

EstimatedRTT = (1- α)*EstimatedRTT + α*SampleRTT

- exponential weighted moving average (EWMA)
- influence of past sample decreases exponentially fast
- typical value: α = 0.125



TCP round trip time, timeout

- timeout interval: **`EstimatedRTT`** plus “safety margin”
  - large variation in **`EstimatedRTT`**: want a larger safety margin

```
TimeoutInterval = EstimatedRTT + 4*DevRTT
```

estimated RTT “safety margin”

- **`DevRTT`**: EWMA of **`SampleRTT`** deviation from **`EstimatedRTT`**:

```
DevRTT = (1-β)*DevRTT + β*|SampleRTT-EstimatedRTT|
```

(typically, β = 0.25)

* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

TCP round trip time, timeout

- **Exercise**: Plot the EstimatedRTT vs. time for RTT from your PC to a specified destination (The destination list will be announced on LMS).
  - Do the same for TimeoutInterval
  - Study the effect of parameters (α, and β).

- **Due date**: 22 Aban 1401

TCP Sender (simplified)

event: data received from application

- create segment with seq #
- seq # is byte-stream number of first data byte in segment
- start timer if not already running
  - think of timer as for oldest unACKed segment
  - expiration interval: **`TimeOutInterval`**

event: timeout

- retransmit segment that caused timeout
- restart timer

event: ACK received

- if ACK acknowledges previously unACKed segments
  - update what is known to be ACKed
  - start timer if there are still unACKed segments

TCP Receiver: ACK generation [RFC 5681]

Event at receiver	*TCP receiver action*

TCP: retransmission scenarios



lost ACK scenario



premature timeout

TCP: retransmission scenarios



cumulative ACK covers
for earlier lost ACK

TCP fast retransmit

TCP fast retransmit

if sender receives 3 additional ACKs for same data ("triple duplicate ACKs"), resend unACKed segment with smallest seq #

- likely that unACKed segment lost, so don't wait for timeout



Receipt of three duplicate ACKs indicates 3 segments received after a missing segment – lost segment is likely. So retransmit!

Lecture roadmap

- Transport-layer services
- Multiplexing and demultiplexing
- Connectionless transport: UDP
- Connection-oriented transport: TCP
  - segment structure
  - reliable data transfer
  - flow control
  - connection management
- Principles of congestion control
- Congestion control techniques

TCP flow control

Q: What happens if network layer delivers data faster than application layer removes data from socket buffers?



receiver protocol stack

TCP flow control

Q: What happens if network layer delivers data faster than application layer removes data from socket buffers?



receiver protocol stack

TCP flow control

Q: What happens if network layer delivers data faster than application layer removes data from socket buffers?



flow control: # bytes receiver willing to accept

Application removing data from TCP socket buffers



receiver protocol stack

TCP flow control

Q: What happens if network layer delivers data faster than application layer removes data from socket buffers?

Application removing data from TCP socket buffers



receiver protocol stack

flow control

receiver controls sender, so sender won't overflow receiver's buffer by transmitting too much, too fast

TCP flow control

- TCP receiver "advertises" free buffer space in **rwnd** field in TCP header
  - **RcvBuffer** size set via socket options (typical default is 4096 bytes)
  - many operating systems autoadjust **RcvBuffer**
- sender limits amount of unACKed ("in-flight") data to received **rwnd**
- guarantees receive buffer will not overflow



TCP receiver-side buffering

TCP flow control

- TCP receiver “advertises” free buffer space in **`rwnd`** field in TCP header
  - **`RcvBuffer`** size set via socket options (typical default is 4096 bytes)
  - many operating systems autoadjust **`RcvBuffer`**
- sender limits amount of unACKed (“in-flight”) data to received **`rwnd`**
- guarantees receive buffer will not overflow



TCP segment format

TCP connection management

before exchanging data, sender/receiver "handshake":

- agree to establish connection (each knowing the other willing to establish connection)
- agree on connection parameters (e.g., starting seq #s)




```
Socket clientSocket =
  newSocket("hostname","port number");
```

```
Socket connectionSocket =
  welcomeSocket.accept();
```

Agreeing to establish a connection

2-way handshake:



Q: will 2-way handshake always work in network?

- variable delays
- retransmitted messages (e.g. req_conn(x)) due to message loss
- message reordering
- can't "see" other side

2-way handshake scenarios



No problem!

2-way handshake scenarios



Problem: half open connection! (no client)

2-way handshake scenarios



Problem: dup data accepted!

TCP 3-way handshake

Client state

```
clientSocket = socket(AF_INET, SOCK_STREAM)
```

LISTEN

```
clientSocket.connect((serverName,serverPort))
```

SYNSENT

choose init seq num, x
send TCP SYN msg

SYNbit=1, Seq=x

ESTAB

received SYNACK(x)
indicates server is live;
send ACK for SYNACK;
this segment may contain
client-to-server data

ACKbit=1, ACKnum=y+1

Server state

```
serverSocket = socket(AF_INET,SOCK_STREAM)
serverSocket.bind(('',serverPort))
serverSocket.listen(1)
connectionSocket, addr = serverSocket.accept()
```



LISTEN

choose init seq num, y
send TCP SYNACK
msg, acking SYN

SYN RCVD

SYNbit=1, Seq=y
ACKbit=1; ACKnum=x+1

received ACK(y)
indicates client is live

ESTAB

Closing a TCP connection

- client, server each close their side of connection
  - send TCP segment with FIN bit = 1
- respond to received FIN with ACK
  - on receiving FIN, ACK can be combined with own FIN
- simultaneous FIN exchanges can be handled