

# Formal Languages and Compilers

Matteo Secco

March 2, 2021

## Contents

<b>1</b>	<b>Formal Language Theory</b>	<b>3</b>
1.1	Operations on strings . . . . .	3
1.2	Operations on Languages . . . . .	4

# 1 Formal Language Theory

**Alphabet  $\Sigma$ :** any finite set of symbols  $\Sigma = \{a_1, a_2, \dots, a_k\}$

**String:** a sequence of alphabeth elements

**Language:** a set (possibly infinite) of strings

$$\Sigma = \{a, b, c\} \quad L_1 = \{ab, ac\} \quad L_2 = \{ab, aab, aaab, aaaab, \dots\}$$

**Sentences/Phrases:** strings belonging to a language

**Language cardinality:** number of sentences of the language

$$|L_1| = |\{ab, ab\}| = 2 \quad |L_2| = |\{ab, aab, aaab, aaaab, \dots\}| = \infty$$

**Number of occurrences of a symbol in a string:**  $|bbc|_b = 2, |bbc|_a = 0$

**Length of a string:** number of its elements

$$|bbc| = 3 \quad |abbc| = 4$$

**String equality:** two strings  $x = a_1a_2\dots a_h$  and  $y = a_1a_2\dots a_k$  are equal  $\iff$

- have same length:  $|x| = |y| \iff h = k$
- elements from left to right coincide:  $a_i = b_i \quad \forall i \in \{1..h\}$

## 1.1 Operations on strings

**Concatenation**  $x = a_1a_2\dots a_h \wedge y = b_1b_2\dots b_k \implies x \cdot y = a_1a_2\dots a_hb_1b_2\dots b_k$

- associative:  $(xy)z = x(yz)$
- length:  $|xy| = |x| + |y|$

**Empty string**  $\epsilon$  is the neutral element for concatenation:  $x\epsilon = \epsilon x = x \forall x$ .

- length:  $|\epsilon| = 0$
- **NB:**  $\epsilon \neq \emptyset$

**Substrings:** if  $x = uyv$  then

- $y$  is a substring of  $x$
- $y$  is a proper substring of  $x \iff u \neq \epsilon \vee v \neq \epsilon$
- $u$  is a prefix of  $x$
- $v$  is a suffix of  $y$

**Reflection:** if  $x = a_1a_2\dots a_h$  then  $x^R = a_ha_{h-1}\dots a_1$

- $(x^R)^R = x$
- $(xy)^R = y^R x^R$
- $\epsilon^R = \epsilon$

**Repetition:**  $x^m = \underbrace{xxx\dots x}_{m \text{ times}}$ . Inductive definition:

- $x^0 = \epsilon$
- $x^m = x^{m-1}x$  if  $m > 0$

## 1.2 Operations on Languages

**Reflection:**  $L^R = \{x | \exists y (y \in L \wedge x = y^R)\}$

**Prefixes(L):**  $\{y | y \neq \epsilon \wedge \exists x \exists z (x \in L \wedge z \neq \epsilon \wedge x = yz)\}$

- **Prefix-free language:**  $L \cap \text{Prefixes}(L) = \emptyset$

**Concatenation:**  $L'L'' = \{xy | x \in L' \wedge y \in L''\}$

**Power:** inductive definition:

- $L^0 = \{\epsilon\}$
- $L^m = L^{m-1}L$  for  $m > 0$
- Consequences:
  - $\emptyset^0 = \{\epsilon\}$
  - $L \cdot \emptyset = \emptyset \cdot L = \emptyset$
  - $L \cdot \{\epsilon\} = \{\epsilon\} \cdot L = L$

**Universal language:** over alphabet  $\Sigma$ :  $L_{\text{universal}} = \Sigma^0 \cup \Sigma^1 \cup \dots$

**Complement:** of  $L$  over  $\Sigma$ :  $\neg L = L_{\text{universal}} \setminus L$