

Processed DataIndex		
🔞 🐿 Processed DataIndex (BigInteger, Timestamp, BigInteger, String)		
Processed DataIndex()		
(f) A datetime	Timestamp	
① A year	String	
predicted_data_id	BigInteger	
⊕ id	BigInteger	
⊕ △ prediction_type	String	
📵 🕦 getPredicted_data_id 0	BigInteger	
m = setDatetime(Timestamp)	void	
getPrediction_type 0	String	
	ProcessedData	
	String	
@ getYear()	String	
n setPredicted_data_id (BigInteger)	void	
@ getDatetime()	Timestamp	
🕠 🐿 setld(BigInteger)	void	
m setPrediction_type (String)	void	
m = setYear(String)	void	
m = getld0	BigInteger	
📵 🐿 addToPredictedDataSet(ProcessedData, BigInteger)	ProcessedData	

😉 🌥 RawData


🌀 🍗 getYear()

🔞 🖢 setData(byte[])

🔞 🍅 RawData(byte[], dataType, Long, Timestamp, String)	
RawData(Long, byte[], dataType, Long, Timestamp, String)	
@ RawData()	
⊕ type	dataType
	byte[]
⊕ △ processedDataID	Long
	String
	Timestamp
	Long
m = setId(Long)	void
getType0	dataType
getStringType()	String
toString()	String
@ @ getDateTime()	Timestamp
setProcessedDataID(Long)	void
	void
🕡 🕒 getData()	byte[]
	Long
m '= setYear(String)	void
mage setDateTime(Timestamp)	void
@ getId()	Long

String

void



() User 🔞 📜 User() 颐 🖿 User (String , String , Set < AccessGroup 🐎 , Set < Role > , Set < RawData > , String , String) lastName String firstName String String String Set <RawData > rawDataIDs Set < Access Group > 🚮 🔒 id Long roleIDs Set < Role > getLastName () String 📵 🎾 getld () Long 📵 🐚 setFirstName (String) void 😈 🆢 getFirstName () String 📵 🐚 getPassword 🚺 String 📵 🕼 setRoleIDs (Set<Role >) void 🔞 🎾 getRawDataIDs () Set <RawData > 📵 🐚 getUsername 0 String መ 🖢 isAccesGroupIDsLoaded 🚺 isRawDatalDsLoaded 0 🎟 🐚 setAccessGroupiDs (Set < AccessGroup >) 🔟 🐚 setUsername (String) 📵 🆫 setLastName (String) void 🔟 🞾 getRoleIDs () Set < Role > m = setId(Long) void toString () String 🔟 🖢 setPassword (String) 🔞 🐚 isRoleIDsLoaded () Set < AccessGroup > 💷 🖢 getAccessGroupIDs () 📵 🖢 setRawDataIDs (Set <RawData >) void

