Features

Card

Built in Beeper

LED Light Indicator

Card Reader

ULtraCR802E/M

- Meets the standard of ISO 11784/11785 and the card reading frequency is 125KHz. The number of ID cards can be read (ULtraCR802E/M).

- Meets the standard of ISO 14443-A and the card reading frequency is 13.56MHz. The number and content of the MIFARE card can be read (ULtraCR802E/M).

- Watchdog is designed for repairing itself in case that exception occurs, to ensure the long service life of the reader.

- Wiegand(w26, w34) protocol.

- Built-in buzzer for identifying the reading status.

- IP65 Standard.

(+91)-11-41916615
+91-95999-53923

D-162, Okhla Industrial Area
Phase I, New Delhi, 110020

sales@timewatchindia.com
www.timewatchindia.com

Specification

Model	ULtraCR802E/M
Power Supply	12V DC
Power Consume	<2W
Processor	8-bit
Reading Frequency	125KHz/13.56MHz
Reading Range	<50mm (≤1.97")
Radio Frequency Standard	ISO 11784/11785/ISO14443-A
Audio Alert	Beeper
Keypad	No Keypad
LED Indicator	Power Indicator, Status Indicator
Working Temperature	-20°C to +65°C (-4°F to 149°F)
Working Humidity	10% to 90% (Non-Condensing)
Dimensions	115.9×43.3×17mm (4.56"×1.70"×0.67")
Protection Level	IP65
Installing Method	Wall Mount with Screws; Do Not Support Gang Box