


## Verification




## Features



## TrueFace Recognition Device

### TrueFace50FP



- 7" LCD with a resolution of 1024 × 600.
- The 2-MP dual-lens CMOS camera and high-performance image sensor ensure accurate recognition even in poor lighting and dark locations that lack illumination.
- Supports 50,000 users (up to 50 administrators), 50,000 faces, 10,000 Fingerprint, 50,000 passwords, 50,000 cards, and 300,000 records.
- Multiple unlock methods including Face, Fingerprint, Card, Password and QR code. You can also combine them to create your own personal unlock methods.
- Displays the face bounding box and detects the face that occupies the most pixels in real time. You can also set target face filtering by configuring the face pixel threshold.
- Recognizes faces 0.3 m to 2.0 m away (0.98 ft–6.56 ft), and detects persons between the height of 0.9 m and 2.4 m (2.95 ft–7.87 ft) when the camera is installed 1.4 m above the ground.
- Powered by the face recognition deep learning algorithm, the device can accurately locate over 360 key points on the face of a target.
- Faces can be recognized within 0.2 seconds, without need for the person to touch the device.
- Features face mask detection and safety helmet detection.
- Multiple display modes and voice prompts are available for broadcasting recognition results to protect the privacy of users.
- Features face mask detection and safety helmet detection.
- Liveness detection is used to detect spoof attempt, such as using a photo or video to gain access.
- Offers multiple types of alarms such as duress, tamper, intrusion, unlock timeout, and excessive use of illegal card and password.
- Supports different types of users, including general, patrol, blocklist, VIP, guest and other.



(+91)-11-41916615  
+91-95999-53923



D-162, Okhla Industrial Area  
Phase I, New Delhi, 110020



sales@timewatchindia.com  
www.timewatchindia.com

## Specification

<b>Capacity</b>	
User Capacity	50,000
Face Capacity	50,000
Fingerprint Capacity	10,000
Card Capacity	50,000
Password Capacity	50,000
QR Capacity	50,000
Log Capacity	3,00,000
<b>System</b>	
Main Processor	Embedded Processor
Network Protocol	UDP; TCP; IPv4; RTSP; SIP; P2P; RTP
OSDP Protocol	Yes
SDK and API	Yes
<b>Basic</b>	
Product Type	Standalone
Display Screen	7" LCD
Screen Type	Capacitive Touchscreen
Screen Resolution	600 (H) × 1024 (V)
Camera	2-MP CMOS HD dual-lens camera
WDR	DWDR
Light Compensation	Auto IR
Voice Prompt	Yes
Casing	PC + ABS
<b>Function</b>	
Unlock Mode	Face, Fingerprint, Card, Password and QR
Card Type	Mi-Fare Card
Period List	128 periods
Holiday Period	128 periods
Network Update	Yes
First User Unlock	Yes
Remote Verification	Yes
Restricted List/Trusted List	Yes
Wi-Fi	Yes
Advertisement Playing	Support graphic advertisement play




Peripheral Card Reader	1 × RS-485 card reader; 1 × Wiegand card reader
Multi-user Authentication	Yes
Real-time Monitoring	Yes
Multi-Factor Authentication	Yes
Capture Function	Yes
Web Configuration	Yes
Auto Registration	Yes
<b>Performance</b>	
Card Reading Distance	0 cm–3 cm (0"-1.18")
Face Recognition Height Range	0.9 m–2.4 m (2.95 ft–7.87 ft)
Face Recognition Distance	0.3 m–2.0 m (0.98 ft–6.56 ft)
Face Recognition Accuracy	99.9%
Face Recognition Time	0.2 s
Fingerprint Recognition Time	0.2 s
Read Speed (QR Code )	500 ms
<b>Port</b>	
RS-485	1
RS-232	1
Wiegand	1
USB	1 × USB 2.0
Network Port	1 × RJ-45 10/100 Mbps self-adaptive Ethernet port
Exit Button	1
Alarm Input	1
Alarm Output	1
Alarm Linkage	Yes
Lock Control	1
Door Status Detection	1
<b>Alarm</b>	
Anti-pass Back	Yes
Tamper Alarm	Yes
Duress Alarm	Yes
Door Sensor Timeout	Yes
Intrusion	Yes
Illegal Card Exceeding Threshold	Yes
<b>General</b>	
Power Adapter	Included
Power Supply	12 VDC, 2 A



Power Consumption	≤24 W
Protection	IP65
Product Dimensions	218mm*118mm*24.2mm (8.58"*4.65"*0.95") (H*W*D)
Packaging Dimensions	390mm*320mm*360mm (15.35"*12.60"*14.17") (H*W*D) Protection Box
Operating Temperature	-20 °C to +55 °C (-4 °F to +131 °F)
Operating Humidity	0%-90% (RH), non-condensing
Operating Altitude	0 m-1,300 m (0 ft-4,265.09 ft)
Operating Environment	Indoor
Gross Weight	0.67 kg (1.48 lb)
Accessory	Included: Wall mount bracket
Installation	Turnstile Mount; 86 case mount; wall; floor bracket mount

## Dimensional Drawing



## Applications



Education

Retail

Government

Health

Bank

Logistics

Office

Factory

 **Head Office :** D-162, Okhla Industrial Area Phase I,  
New Delhi, 110020.

 **Regional Office :** Mumbai, Bengaluru, Ahmedabad,  
Chennai, Kolkata.

**International Office :** Dubai

**Disclaimer :** All pictures shown are for illustration purposes only. The actual product and color may vary due to product enhancement. The brief specification is mentioned and may change without prior notice. Please consult us before placing any order.