




5 Million Movement Life



3-4 Pairs Infra Red



Illegal Intrusion Infrared Alarm



24V DC Brushless Motor, Low Noise



Auto Self Inspection & Alarm Prompt



Negligible Maintenance



SS304



Full Automatic Flap Barrier

TW-FB2000/TWF-B2200

TW FB2000/TWF-B2200 is a fully automatic swing gate barrier that is driven by a 24V brushless DC motor, which supports multiple opening modes like ID & IC card swiping, other reading head Verification opening, infrared induction automatic opening, button opening, etc.

The device has accurate identification techniques with protection and safety functions like electro-mechanical anti-collision, infrared anti-pinch, and illegal intrusion infrared alarm. The device uses rapid, efficient, and safe access control and very convenient and easy-to-use features.


 (+91)-11-41916615
 +91-95999-53923

 D-162, Okhla Industrial Area
 Phase I, New Delhi, 110020

 sales@timewatchindia.com
 www.timewatchindia.com

- The guide rail type movement structure makes the operation more stable
- The mechanical part adopts the CNC process, and the connector adopts a high-temperature quenching process, which will not deform after long-term operation
- It has the function of fault self-test and alarm prompt, with its inbuilt voice prompt function, which is convenient for users to maintain and use
- Infrared alarm for illegal intrusion
- It has an automatic reset function. After opening the gate, if there is no passage within the specified time, the system will automatically cancel the user's permission to pass this time. The standard is automatic reset 3 seconds after opening
- Audible and visual alarm function: including illegal intrusion, trailing alarm and closing the gate

Specifications

Appearance Dimension	300x1000x1200mm
Material Structure	304 original brushed stainless steel, acrylic
Channel Width	550mm
Thickness	The full thickness of the outer box is 1.2 + 1.0mm
Drive Motor	24V DC brushless motor, low noise
Traffic Speed	25-30 Peoples / Min.
Movement Structure	Guide rail structure
Traffic Direction	One-way traffic/two-way traffic
Opening Mode	Proximity / Mi-Fare card swiping and other reading head verification opening, infrared induction automatic opening, button opening etc.



(+91)-11-41916615
+91-95999-53923



D-162, Okhla Industrial Area
Phase I, New Delhi, 110020



sales@timewatchindia.com
www.timewatchindia.com

Opening Signal	Dry contact signal
Protection Function	Current anti pinch, infrared anti pinch, illegal intrusion infrared alarm
Service Life	≥ 5 million times
Infrared Quantity	3 pairs (4 pairs can be customized)
Power	30-60w
Applicable Temperature	-15~70 °C (add thermostat below this temperature)
Optional	Accessories

Applications



Education



Retail



Government



Health



Logistics



Bank



Office



Factory

-  **Head Office :** D-162, Okhla Industrial Area Phase I,
New Delhi, 110020.
 **Regional Office :** Mumbai, Bengaluru, Ahmedabad,
Chennai, Kolkata.
International Office : Dubai

Disclaimer : All pictures shown are for illustration purposes only. The actual product and color may vary due to product enhancement. The brief specification is mentioned and may change without prior notice. Please consult us before placing any order.