



Life Time No Maintenance



No attrition & High Temperature Resistant



Failure proof Electromagnetic Solenoid valves



Low Noise & High Intelligence



SS304



≤5 million time



Turnstile Gate

TWLD-TS2700

The Semi-Automatic Tripod Turnstile ensures smooth and easy passage with minimal passing resistance. It offers versatile working modes, including bi-directional and single-directional operation, all configurable through buttons on the main control board.

In case of a power outage, the arms automatically drop for unimpeded access. Additionally, the turnstile features obstacle detection with automatic stopping for enhanced safety. It can also be seamlessly integrated with facial recognition biometrics and other contactless systems for a no-touch user experience.







Specification

Dimension	260*360*980 (mm)
Material	304 Original brushed stainless steel, acrylic
Channel Width	510mm
Thickness	The full thickness of the outer box is 1.0+3.0mm
Traffic Direction	One-way traffic/two-way traffic
Traffic Speed	25~30 people/min in normally open mode and 15~20 people/min in normally closed mode The actual traffic speed is different from the traffic environment and personnel
Opening Mode	ID & IC card swiping and other reading head verification opening, button opening, etc.
Opening Signal	Dry contact signal
Life	≤5 million times
Power	30-60W
Applicable Temperature	-20~75°C (add thermostat below this temperature)

Disclaimer: All pictures shown are for illustration purposes only. The actual product and color may vary due to product enhancement. The brief specification is mentioned and may













- Head Office: D-162, Okhla Industrial Area Phase I, New Delhi, 110020.
- Regional Office: Mumbai, Bengaluru, Ahmedabad, Chennai, Kolkata.

change without prior notice. Please consult us before placing any order.

International Office: Dubai

Sales: sales@timewatchindia.com

Phone: +91-95999-53923

Support: helpdesk@timewatchindia.com

www.timewatchindia.com





