



Tripod Turnstile

TW-1200

Specification

Passage Width	520mm
Throughput rate	35p/m
Power Supply	100 ~ 240V
Operational Voltage	24V
Max Power Consumption	30 W
Frequency	50~60hz
Protection Level	IP 54
Working Temperature	25°C ~ +70°C
Electro - magnetic Drive	DC
Dimension Excluding Bar	560x480x960 mm
Net Weight Including Bar	80kg



(+91)-11-41916615
+91-95999-53923



D-162, Okhla Industrial Area
Phase I, New Delhi, 110020



sales@timewatchindia.com
www.timewatchindia.com

Semi-Auto mode

Semi-Auto mode

Pure Mechanical mode

Single or Bi-directional function in mechanical and electrical versions

Automatic reset of barrier arms after each passage

Adjustable time out delay

Operating Mode

Single passage in the set direction

Bi-directional passage

Drop arm feature

Materials

Housing : stainless steel AISI 304 or AISI 316

Barrier Arms : Stainless steel

Lid (Optional) : Stainless steel or artificial stone (black / brown)

Colours & Finishes

High quality powder coating plus lacquered finish

Dark grey color high quality powder coating plus

Lacquered finish

Sandpaper powder coating with pearl mica effect



Head Office : D-162, Okhla Industrial Area Phase I,
New Delhi, 110020.



Regional Office : Mumbai, Bengaluru, Ahmedabad,
Chennai, Kolkata.

International Office : Dubai



Phone : +91-95999-53923



Sales : sales@timewatchindia.com



Support : helpdesk@timewatchindia.com

Disclaimer : All pictures shown are for illustration purposes only. The actual product and color may vary due to product enhancement. The brief specification is mentioned and may change without prior notice. Please consult us before placing any order.

