


8 Million
Movement Life



2 Pairs
Infra Red



Illegal Intrusion
Infrared Alarm



24V Servo
Motor, Low Noise



Auto Self Inspection
& Alarm Prompt



Negligible
Maintenance



Swing Gate Barrier

TW-SG-2712

TWLD-SG-2712 is a fully automatic speed gate swing barrier that is driven by a 24V brushless DC motor, which supports multiple opening modes like Proximity & Mi-Fare card swiping, other reading head verification opening, infrared induction automatic opening, button opening, etc. The device has accurate identification techniques with protection and safety functions like electromechanical anti-collision, infrared anti-pinch and illegal intrusion infrared alarm. The device ensures rapid, efficient and safe access control and very convenient and easy-to-use features.

- SUS304 original drawing.
- Clutch anti-collision.
- Current clamp: resistance rebound.
- Built-in voice prompt function.



(+91)-11-41916615
+91-95999-53923



D-162, Okhla Industrial Area
Phase I, New Delhi, 110020



sales@timewatchindia.com
www.timewatchindia.com

- Infrared alarm for illegal intrusion.
- Reverse alarm when swiping the card and opening the brake.
- Servo control system.
- Three-ring curve control mode, fast, stable, and low noise.
- Servo motor driving torque is soft, not wounding.
- Domestic first-line brand infrared, high light resistance: ultimate light intensity of 100,000 LUX, light Angle of 6°C.
- Integrated with face biometric & card.

Specifications

Size	380mm * 300mm * 1024mm
Material structure	Carbon steel plate + paint, toughened glass, acrylic
Channel width	Standard 600mm (≤ 1200mm can be customized)
Drive motor	24 V brushless DC motor, low noise
Control Board	Integrated brushless control system
Traffic direction	One-way traffic / two-way traffic
Operating speed	0.5 ~ 0.8 S
Switch mode	Biological identification, Face, Fingerprint, QR, Card, Password and remote control switch, etc.
Switch signal	Dry contact signal, customizable RS232 mode
Protection function	Electromechanical collision avoidance scheme
Life expectancy	8 million times
IR Quantity	2 Pairs
Power	40-70w
Applicable temperature	-15 ~ 70 °C (below -15 °C plus thermostat)
Support	Indoor use



Head Office : D-162, Okhla Industrial Area Phase I, New Delhi, 110020.



Regional Office : Mumbai, Bengaluru, Ahmedabad, Chennai, Kolkata.

International Office : Dubai



Phone : +91-95999-53923



Sales : sales@timewatchindia.com



Support : helpdesk@timewatchindia.com

Disclaimer : All pictures shown are for illustration purposes only. The actual product and color may vary due to product enhancement. The brief specification is mentioned and may change without prior notice. Please consult us before placing any order.

