

```

//srtf
#include<stdio.h>

int main(){

int a[10],b[10],x[10];
int waiting[10],turnaround[10],completion[10];
int i,j,smallest,count=0,time,n;
double avg=0,tt=0,end;

printf("\nEnter the number of Processes: ");
scanf("%d",&n);
for(i=0;i<n;i++){
    printf("\nEnter arrival time of process %d : ",i+1);
    scanf("%d",&a[i]);
}
for(i=0;i<n;i++){
    printf("\nEnter burst time of process %d : ",i+1);
    scanf("%d",&b[i]);
}
for(i=0;i<n;i++){
    x[i]=b[i];
}
b[9]=9999;
for(time=0;count!=n;time++){
    smallest=9;
    for(i=0;i<n;i++){
        if(a[i]<=time && b[i]<b[smallest] && b[i]>0){
            smallest=i;
        }
    }
    b[smallest]--;
    if(b[smallest]==0){
        count++;
        end=time+1;
        completion[smallest] = end;
        waiting[smallest] = end - a[smallest] - x[smallest];
        turnaround[smallest] = end - a[smallest];
    }
}
printf("pid\t\t\tburst\t\tarrival\t\t\twaiting\t\t\tturnaround\t\t\tcompletion");
for(i=0;i<n;i++){

printf("\n%d\t\t\t\t%d\t\t\t\t%d\t\t\t\t%d\t\t\t\t%d\t\t\t\t%d\t\t\t\t%d",i+1,x[i],a[i],waiting[i],turnaround[i],completion[i]);
    avg = avg + waiting[i];
    tt = tt + turnaround[i];
}
}

```

```
printf("\n %lf %lf",avg,tt);  
printf("\n\nAverage waiting time = %lf\n",avg/n);  
printf("Average Turnaround time = %lf",tt/n);  
return 0;  
}
```