

Printing date 17.07.2023 Version number 9 Revision: 17.07.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CORRETTIVO PER RESINE DAP VSR 3015
- · Article number: 351396
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- · Technical function Electroinsulation
- · Application of the substance / the mixture No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Von Roll Italia S.r.l. Via Rigolfo, 73 10028 TROFARELLO (TO)

ITALY

- · Further information obtainable from: Giovanni Rocco info.italy@vonroll.com
- · 1.4 Emergency telephone number:

Tel: +390116493111 (h. 8/12 ÷ 13/17 italian time)

Fax: +390116493112

National Poisons Information Service (Birmingham Unit)

City Hospital

Dudley Rd - Birmingham Tel: 844 892 0111

mail@npis.org"

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



health hazard

Repr. 1B H360D May damage the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



environment

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Printing date 17.07.2023 Version number 9 Revision: 17.07.2023

Trade name: CORRETTIVO PER RESINE DAP VSR 3015

(Contd. of page 1)

· Hazard pictograms







· Signal word Danger

· Hazard-determining components of labelling:

Ftalato di diallile dibutyl maleate

bis (alpha, alpha-dimethylbenzyl) peroxide

maleic anhydride

· Hazard statements

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H360D May damage the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P280

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

Rinse mouth. P330 P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 131-17-9 EINECS: 205-016-3 Index number: 607-086-00-4 Reg.nr.: 01-2119832891-34	Ftalato di diallile Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1B, H317	>60-<70%
CAS: 105-76-0 EINECS: 203-328-4	dibutyl maleate ♦ STOT RE 2, H373; ♦ Aquatic Acute 1, H400; ♦ Skin Sens. 1, H317	≥25-<35%

(Contd. on page 3)



Printing date 17.07.2023 Version number 9 Revision: 17.07.2023

Trade name: CORRETTIVO PER RESINE DAP VSR 3015

		(Contd. of page 2)
CAS: 80-43-3	bis (alpha,alpha-dimethylbenzyl) peroxide	≥0.3-<0.4%
EINECS: 201-279-3	🕚 Org. Perox. F, H242; 🚯 Repr. 1B, H360D; 🕸 Aquatic	
Index number: 617-006-00-X	Chronic 2, H411; (1) Skin Irrit. 2, H315; Eye Irrit. 2, H319	
Reg.nr.: 01-2119541688-27	*	
CAS: 108-31-6	maleic anhydride	<i>≥</i> 0.001-<0.1%
EINECS: 203-571-6	♦ Resp. Sens. 1, H334; STOT RE 1, H372; ♦ Skin Corr. 1B,	
Index number: 607-096-00-9	H314; Eye Dam. 1, H318; 🕦 Acute Tox. 4, H302; Skin Sens. 1A,	
Reg.nr.: 01-2119472428-31	H317	
	Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	
· Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)



Printing date 17.07.2023 Version number 9 Revision: 17.07.2023

Trade name: CORRETTIVO PER RESINE DAP VSR 3015

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities Store away from foodstuffs.
- · Storage: Store in accordance with local/regional/national/international regulations.
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

None.

Store in a well-ventilated place. Keep container tightly closed.

- · Recommended storage temperature: /
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:

131-17-9 Ftalato di diallile

WEL Long-term value: 5 mg/m³

108-31-6 maleic anhydride

WEL Short-term value: 3 mg/m³

Long-term value: 1 mg/m³

Sen

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)



Printing date 17.07.2023 Version number 9 Revision: 17.07.2023

Trade name: CORRETTIVO PER RESINE DAP VSR 3015

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical	and chemical	propert	ties
---------------------	--------------	---------	------

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Light yellow
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

• Flash point: >105 °C

· Flammability (solid, gas): Not applicable.

• Decomposition temperature: Not determined.

Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Upper: Not determined.

(Contd. on page 6)



Printing date 17.07.2023 Version number 9 Revision: 17.07.2023

Trade name: CORRETTIVO PER RESINE DAP VSR 3015

	(Contd. of pag
Vapour pressure at 100 °C:	0.3 hPa
Density at 20 °C:	$0.95-1.05 \text{ g/cm}^3$
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0 %
VÕC (EC)	0.01 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information · 11.1 Information on toxicological effects · Acute toxicity Harmful if swallowed. · LD/LC50 values relevant for classification: ATE (Acute Toxicity Estimates) LD50 1,197–1,203 mg/kg (rat) Oral 131-17-9 Ftalato di diallile LD50 770 mg/kg (rat) Dermal LD50 3,400 mg/kg (rabbit) 105-76-0 dibutyl maleate Oral LD50 3,730 mg/kg (rat) Dermal LD50 10,000 mg/kg (rabbit) (Contd. on page 7)

GB



Printing date 17.07.2023 Version number 9 Revision: 17.07.2023

Trade name: CORRETTIVO PER RESINE DAP VSR 3015

(Contd. of page 6)

80-43-3	80-43-3 bis (alpha,alpha-dimethylbenzyl) peroxide		
Oral	LD50	4,100 mg/kg (rat)	
108-31-	6 male	ic anhydride	
Oral	LD50	400 mg/kg (rat)	
Dermal	LD50	2,620 mg/kg (rabbit)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

May damage the unborn child.

- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

This disposal considerations refer to intact product without external contaminations.

(Contd. on page 8)



Printing date 17.07.2023 Version number 9 Revision: 17.07.2023

Trade name: CORRETTIVO PER RESINE DAP VSR 3015

(Contd. of page 7)

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (diallyl phthalate, dibutyl maleate)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI N.O.S. (diallyl phthalate, dibutyl maleate), MARIN POLLUTANT
IATA	Environmentally hazardous substance, liquid, n.o.s. (dial phthalate, dibutyl maleate)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles. 9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Hazard identification number (Kemler code):	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Transport in bulk according to Annex II o	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	er
Limited quantities (LQ)	5L Code: E1
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging. 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	(-)

(Contd. on page 9)



Printing date 17.07.2023 Version number 9 Revision: 17.07.2023

Trade name: CORRETTIVO PER RESINE DAP VSR 3015

(Contd. of page 8)

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIALLYL PHTHALATE, DIBUTYL MALEATE), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H242 Heating may cause a fire.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eve damage.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H360D May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department.
- · Contact: -

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 10)



Printing date 17.07.2023 Version number 9 Revision: 17.07.2023

Trade name: CORRETTIVO PER RESINE DAP VSR 3015

(Contd. of page 9)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Org. Perox. F: Organic peroxides – Type E/F

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1. Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* * Data compared to the previous version altered.

GB ·