

Printing date 04.09.2023 Version number 8 Revision: 04.09.2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SMALTO SYNTHITE ER-41 (ROSSO)
- · Article number: 351225
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- · Technical function Electroinsulation
- · Application of the substance / the mixture

Coloured glaze

No further relevant information available.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Von Roll Italia S.r.l. - Società con unico socio Via Rigolfo 73 - 10028 - Trofarello (TO) - Italia

*Tel:* +39/0116493111 *Fax:* +39/0116493112

- · Further information obtainable from: Giovanni Rocco info.italy@yonroll.com
- · 1.4 Emergency telephone number:

Tel: +390116493111 (h.  $8/12 \div 13/17$  italian time)

Fax: +390116493112

"National Poisons Information Service (Birmingham Unit)

City Hospital

Dudley Rd - Birmingham

Tel: 844 892 0111

mail@npis.org"

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Printing date 04.09.2023 Version number 8 Revision: 04.09.2023

Trade name: SMALTO SYNTHITE ER-41 (ROSSO)

(Contd. of page 1)

#### · Hazard pictograms





GHS02 GHS07

#### · Signal word Warning

### · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

#### · Hazard statements

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 64742-48-9 EC number: 919-857-5 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33-XXXX	Naphtha (petroleum), hydrotreated heavy  Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	>40-<60%	
CAS: 1317-65-3 EINECS: 215-279-6	Calcium carbonate substance with a Community workplace exposure limit	<2.1%	
EC number: 905-588-0 Reg.nr.: 01-2119488216-32-XXXX	REACTION MIXTURE OF ETHYLBENZENE AND XYLENES  Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<2.0%	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.



Printing date 04.09.2023 Version number 8 Revision: 04.09.2023

Trade name: SMALTO SYNTHITE ER-41 (ROSSO)

(Contd. of page 2)

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities Store away from foodstuffs.
- · Storage: Store in accordance with local/regional/national/international regulations.
- · Requirements to be met by storerooms and receptacles: Protect from moisture and heating sources.

(Contd. on page 4)



Printing date 04.09.2023 Version number 8 Revision: 04.09.2023

Trade name: SMALTO SYNTHITE ER-41 (ROSSO)

(Contd. of page 3)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store in a well-ventilated place. Keep container tightly closed.
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

#### 1317-65-3 Calcium carbonate

WEL Long-term value: 10\* 4\*\* mg/m³
\*inhalable dust; \*\*respirable

### • DNELs

#### 64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	Long-term - oral, systemic effects - Consumers	125 mg/kg (human)
Dermal	Long-term – dermal, systemic effects - Workers	208 mg/kg (human)
	Long-term - dermal, systemic effects - Consumers	125 mg/kg (human)
Inhalative	Long-term – inhalation, systemic effects - Workers	$871 \text{ mg/m}^3 \text{ (human)}$
	Long-term - inhalation, systemic effects - Consum.	

### REACTION MIXTURE OF ETHYLBENZENE AND XYLENES

Oral	Acute - inhalation, systemic effects - Consumer	$260 \text{ mg/m}^3 \text{ (human)}$
	Long-term - oral, systemic effects - Consumers	12.5 mg/kg (human)
Inhalative	Acute - inhalation, local effects - Consumer	$260 \text{ mg/m}^3 \text{ (human)}$
	Long-term - inhalation, systemic effects - Consum.	$65.3 \text{ mg/m}^3 \text{ (human)}$

#### · PNECs

#### REACTION MIXTURE OF ETHYLBENZENE AND XYLENES

Fresh Water	0.18 mg/l (/)
Water,intermittentrelease	
Marine water	0.0981 mg/l (/)
Freshwater sediments	0.981 mg/kg (/)
Marine water sediments	0.0981 mg/kg (/)
STP Microorganisms	35.6 mg/l (/)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)



Printing date 04.09.2023 Version number 8 Revision: 04.09.2023

Trade name: SMALTO SYNTHITE ER-41 (ROSSO)

(Contd. of page 4)

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION	9: Physical	and chemical	properties

9.1 Information on basic physical and	d chemical properties
· General Information	
· Appearance:	
Form:	Fluid
Colour:	Red
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ran	ge: Undetermined.
· Flash point:	38 °C
· Flammability (solid, gas):	Flammable.
Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1 Vol %
Upper:	7 Vol %

(Contd. on page 6)



Printing date 04.09.2023 Version number 8 Revision: 04.09.2023

Trade name: SMALTO SYNTHITE ER-41 (ROSSO)

	(Contd.	of page
· Vapour pressure at 20 °C:	1 hPa	
Density at 20 °C:	$0.9-1 \text{ g/cm}^3$	
Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.6 %	
VÕC (EC)	45.40 %	
· 9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

Hent toxicity Bused on available adia, the classification effects are not met.				
· LD/LC50 values relevant for classification:				
ATE (Acute Toxicity Estimates)				
Dermal	LD50	57,201 mg/kg		
Inhalative	LC50/4 h	572 mg/l		
64742-48-9 Naphtha (petroleum), hydrotreated heavy				
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>3,000 mg/kg (rab)		
REACTION MIXTURE OF ETHYLBENZENE AND XYLENES				
Dermal	LD50	1,100 mg/kg (ATE)		
Inhalative	LC50/4 h	11 mg/l (ATE)		
· Primary ir	ritant effec	afo		

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 04.09.2023 Version number 8 Revision: 04.09.2023

Trade name: SMALTO SYNTHITE ER-41 (ROSSO)

(Contd. of page 6)

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. This disposal considerations refer to intact product without external contaminations.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport informati	ion
---------------------------------	-----

• 14.1 UN-Number • ADR, IMDG, IATA UN1263

· 14.2 UN proper shipping name

 $\cdot$  ADR UN1263 PAINT  $\cdot$  IMDG PAINT  $\cdot$  IATA Paint

(Contd. on page 8)



# Safety data sheet

### according to 1907/2006/EC, Article 31 and Regulation 878/2020/EU

Printing date 04.09.2023 Version number 8 Revision: 04.09.2023

Trade name: SMALTO SYNTHITE ER-41 (ROSSO)

(Contd. of page 7)

· 14.3	<b>Transport</b>	hazard	class(	es	)
--------	------------------	--------	--------	----	---

· ADR, IMDG, IATA



3 Flammable liquids. · Class

· Label

· 14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards: Not applicable.

· 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30

· EMS Number: *F-E,S-E* · Stowage Category A

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

 $\cdot ADR$ 

· Limited quantities (LQ) 5L

· Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· Transport category D/E

· Tunnel restriction code

 $\cdot$  IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1263 PAINT, 3, III

# **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 04.09.2023 Version number 8 Revision: 04.09.2023

Trade name: SMALTO SYNTHITE ER-41 (ROSSO)

(Contd. of page 8)

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Product safety department.
- · Contact: -

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

· \* Data compared to the previous version altered.

GB