Printing date 03.01.2023 Revision: 03.01.2023

#### I Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: EPOXINJECT 300 - A - Component

· Article number: 05-300 A

- · Relevant identified uses of the substance or mixture and uses advised against Only for professional use.
- · Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

ADCOS NV

Ambachtsstraat 15 2390 MALLE BELGIUM

info@adcosgroup.com

- · Further information obtainable from: Product safety department.
- · Emergency telephone number: During normal opening times: +32 3 385 38 50

#### 2 Hazards identification

· Classification according to Regulation (EC) No 1272/2008



health hazard

Repr. 1B H360 May damage fertility or the unborn child.



Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS05





GHS08



GHS09

· Signal word Danger

(Contd. on page 2)

Printing date 03.01.2023 Revision: 03.01.2023

Trade name: EPOXINJECT 300 - A - Component

(Contd. of page 1)

#### · Hazard-determining components of labelling:

Benzyl alcohol

4,4'-

Isopropylidenediphenol

, oligomeric reaction

products with 1-chloro-

2,3-epoxypropane,

reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

*m-phenylenebis*(*methylamine*)

salicylic acid

#### · Hazard statements

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

P260 Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

*P321* Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Restricted to professional users.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

· Description: Mixture of substances with nonhazardous additions.

· Dangerous components:		
CAS: 100-51-6	Benzyl alcohol	25-50%
EINECS: 202-859-9	♠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Eye Irrit. 2, H319	
CAS: 38294-64-3	4,4'-	25-50%
NLP: 500-101-4	Isopropylidenediphenol	
	, oligomeric reaction	
	products with 1-chloro-	
	2,3-epoxypropane,	
	reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine	
	<ul> <li>Repr. 1B, H360;</li> <li>Skin Corr. 1C, H314;</li> <li>Aquatic Chronic 2, H411;</li> <li>Skin Sens. 1B, H317</li> </ul>	
CAS: 1477-55-0	m-phenylenebis(methylamine)	2.5-10%
EINECS: 216-032-5	Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Aquatic Chronic 3, H412	
CAS: 69-72-7	salicylic acid	0-10%
EINECS: 200-712-3	♦ Repr. 2, H361d; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302	
	(Cont	d. on page 3)

ĠВ

Printing date 03.01.2023 Revision: 03.01.2023

Trade name: EPOXINJECT 300 - A - Component

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

(Contd. on page 4)

Printing date 03.01.2023 Revision: 03.01.2023

Trade name: EPOXINJECT 300 - A - Component

(Contd. of page 3)

- Information about fire and explosion protection: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Printing date 03.01.2023 Revision: 03.01.2023

Trade name: EPOXINJECT 300 - A - Component

(Contd. of page 4)

1.6	*I
Information on basic physical and chem General Information	ucal properties
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	: Undetermined.
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	$1.035 \text{ g/cm}^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C:	800-900 mPas
Kinematic:	Not determined.
Solvent content:	
VOC (EC)	25-47 %

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability

· Other information

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

No further relevant information available.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Printing date 03.01.2023 Revision: 03.01.2023

Trade name: EPOXINJECT 300 - A - Component

(Contd. of page 5)

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

Harmful if swallowed or if inhaled.

· LD/LC50 1	LD/LC50 values relevant for classification:				
100-51-6 E	100-51-6 Benzyl alcohol				
Oral	LD50	1,040 mg/kg (mouse)			
		1,230 mg/kg (rat)			
		1,040 mg/kg (rabbit)			
Dermal	<i>LD50</i>	2,000 mg/kg (rabbit)			
Inhalative	LC50/4 h	4,178 mg/l (rat)			

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

May damage fertility or the unborn child.

- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

#### 12 Ecological information

· Toxicity

### · Aquatic toxicity:

#### 100-51-6 Benzyl alcohol

LC50/96 h | 460 mg/l (fathead minnow)

EC50/24 h 400 mg/l (daphnia)

EC50/96 h 640 mg/l (algae)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

Printing date 03.01.2023 Revision: 03.01.2023

Trade name: EPOXINJECT 300 - A - Component

 $\cdot \textit{Other adverse effects} \ \textit{No further relevant information available}.$ 

(Contd. of page 6)

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADR, IMDG, IATA	UN3082
UN proper shipping name ADR	UN3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (formaldehyd
· IMDG	oligomeric reaction products with 1-chloro-2, epoxypropane and phenol) ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenomarine pollutant
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (formaldehyde, oligomeric reactiproducts with 1-chloro-2,3-epoxypropane and phenol)
Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous dangerous substances as articles.
· IMDG, IATA	
Class Label	<ul><li>9 Miscellaneous dangerous substances and articles.</li><li>9</li></ul>
Packing group	
ADR, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardo substances: formaldehyde, oligomeric reaction production with 1-chloro-2,3-epoxypropane and phenol
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)

- GP

Printing date 03.01.2023 Revision: 03.01.2023

Trade name: EPOXINJECT 300 - A - Component

	(Contd. of page
· Special precautions for user	Warning: Miscellaneous dangerous substances an articles.
· Hazard identification number (Kemler code):	90
· EMS Number:	F- $A$ , $S$ - $F$
· Stowage Category	A
· Transport in bulk according to Annex II of Mar	pol
and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot$ ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU
-	SUBSTANCE, LIQUID, N.O.S. (FORMALDEHYD)
	OLIGOMERIC REACTION PRODUCTS WITH
	CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, 1

#### 15 Regulatory information

- $\cdot \textit{Safety, health and environmental regulations/legislation specific for the product} \\$
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases referred to under sections 2 and 3
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H360 May damage fertility or the unborn child.
- H361d Suspected of damaging the unborn child.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department.

(Contd. on page 9)

Printing date 03.01.2023 Revision: 03.01.2023

Trade name: EPOXINJECT 300 - A - Component

(Contd. of page 8)

· Contact: Mr. Devroe

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Repr. 1B: Reproductive toxicity - Category 1B

Repr. 2: Reproductive toxicity – Category 2

 $A quatic\ Chronic\ 2:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long\ -term\ aquatic\ hazard\ -\ Category\ 2$ 

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· \* Data compared to the previous version altered.