

Case name: Eine kritische Auseinandersetzung mit der Dissertation von Prof. Dr. :
Veronica SaÃŸ

Note: just give some note as test

Plag Bibtext: source is undefined

Source Bibtextsource is undefined

Page from: 1 to:1

Page from: to:1

Plagiarized Text

Line from: 1 to:1

Source Text

Line from: 1 to:1

EYEIITYTIIIG III YOUREYEIITYTIIIG III YOUR

Plag Bibtext: source is undefined

Source Bibtextsource is undefined

Page from: 1 to:1

Page from: to:1

Plagiarized Text

Line from: 1 to:10

Source Text

Line from: 3 to:10

EYEIITYTIIIG III YOURLIFE IS A IIEFLEKTIOIIOF II CHOICE YOU IIIYEMADE. IF YOU
YIIIIIâ€™ ADIFFERENT RESULT.IIIKE II DIFFERENTnWwW.IIVEIIF[~HAVFY.COMOF II
CHOICE YOU IIIYEMADE. IF YOU YIIIIIâ€™ ADIFFERENT RESULT.IIIKE II DIFFERENTn
WwW.IIVEIIF[~HAVFY.COM

Plag Bibtext: source is unknown

Source Bibtextsource is unknown

Page from: 1 to:6

Page from: to:6

Plagiarized Text

Line from: 2 to:9

Source Text

Line from: 3 to:11

Sequential or Linear Search Input int A[] = {4,2,6,3,1,7,5} OrdFindVal-3 er: Algorithms for Searching Q Best-case -> Big-Omega-> Q(1) i { nt Seq Find(A, findVal) a/:rr;%:::;_igEjâ€™™Â§__I2e(t:)_> em/2 } for(i=0; i { { _ | 2"f!"4) v=6I-m+1'=5"=4 While(..) { { 1-!) J IJ= - lf |=2i Partition(m, n) wh,-|e(-,QuickSort(m,i-1) { sWap(A[2]=6,A[4]=1) if (iQuickSort(i+1,n)) } } while(A[i]++while(A[j]>v)j_if (iswap!/[i],A[i])i++; iâ€™";i--; \$wvP(v,A[i])return i;} ->A={3,2,1,4,6,7,5}->A={4,2,1,3,6,7,5} swap(A[5]=7,A[6]=5)i=3;j=3 ->A={1,2,3,4,6,5,7} } while(A[i]=3i=4 ->A={1,2,3,4,5, 6, 7} while(A[j]>4)i=3;swap(v=A[0]=4,A[3]=3) Â§Â§Â§Â§Â§Â§Â§Â§Â§Â§Â§Â§22%Â§gasaasssggÃ©sasazeÂ§Â§Â§Â§Â§Â§Â§aazsÂ§Â§Â§sÂ§Â§Â§sÂ§Â§Â§â€™ lru.\1FI8\0c.[7880-57890Insa|tnnSc:tMhReveneNumban" MergeSanwIhRsveueN.n'ber1: m sec Quck Son wIh PovervaNunben. 28ml|=Â¢Â¢Inse:tbNsmuAlhRa1da'n Numbers 2&S61m1lsecMug: Sui vlh Rmdan Nmbn 145mlis=cQuckSoI(wIhRond.1mN\mbc|s: 35r1I'lisa:.50508rIllia9c95 Illmm Rana .l 7-67890!Inaauon Sontmh kveno Number: :50566mIIuacMergeSanwIhRavonoN.nrbn: 120n-nlnecOack Soot with Reverse Numbers. 19nIll:eclnsenbn Sm ulh Random Numbers 26732n1Ilse1:Ha? Snâ€™! wih Rmdun Nurbcs ' 147rI|i!zcQua: Sod with Random Nirnbcm ' 3Gr1iliaocHound!IIi'|78Wuwï¬,ï¬,Input int A[] = {4,2,6,3,1,7,5} OrdFindVal-3 er: Algorithms for Searching Sequential or Linear Search Q Best-case -> Big-Omega-> Q(1) i { nt Seq Find(A, findVal) a/:rr;%:::;_igEjâ€™™Â§__I2e(t:)_> em/2 } for(i=0; i { if(A[i]==val) I-m+1'=5"=4 While(..) { { 1-!) J IJ= - lf |=2i Partition(m, n) wh,-|e(-,QuickSort(m,i-1) { sWap(A[2]=6,A[4]=1) if (iQuickSort(i+1,n)) } } while(A[i]++while(A[j]>v)j_if (iswap!/[i],A[i])i++; iâ€™";i--; \$wvP(v,A[i])return i;} ->A={3,2,1,4,6,7,5}->A={4,2,1,3,6,7,5} swap(A[5]=7,A[6]=5)i=3;j=3 ->A={1,2,3,4,6,5,7} } while(A[i]=3i=4 ->A={1,2,3,4,5, 6, 7} while(A[j]>4)i=3;swap(v=A[0]=4,A[3]=3) Â§Â§Â§Â§Â§Â§Â§Â§Â§Â§Â§Â§22%Â§gasaasssggÃ©sasazeÂ§Â§Â§Â§Â§Â§Â§aazsÂ§Â§Â§sÂ§Â§Â§sÂ§Â§Â§â€™ lru.\1FI8\0c.[7880-57890Insa|tnnSc:tMhReveneNumban" MergeSanwIhRsveueN.n'ber1: m sec Quck Son wIh PovervaNunben. 28ml|=Â¢Â¢Inse:tbNsmuAlhRa1da'n Numbers 2&S61m1lsecMug: Sui vlh Rmdan Nmbn 145mlis=cQuckSoI(wIhRond.1mN\mbc|s: 35r1I'lisa:.50508rIllia9c95 Illmm Rana .l 7-67890!Inaauon Sontmh kveno Number: :50566mIIuacMergeSanwIhRavonoN.nrbn: 120n-nlnecOack Soot with Reverse Numbers. 19nIll:eclnsenbn Sm ulh Random Numbers 26732n1Ilse1:Ha? Snâ€™! wih Rmdun Nurbcs ' 147rI|i!zcQua: Sod with Random Nirnbcm ' 3Gr1iliaocHound!IIi'|78Wuwï¬,ï¬,