NEC

MOS FIELD EFFECT POWER TRANSISTORS
2SJ324, 2SJ324-Z

SWITCHING
P-CHANNEL POWER MOS FET
INDUSTRIAL USE

DESCRIPTION

The 2SJ324 is P-channel MOS Field Effect Transistor designed for solenoid, motor and lamp driver.

FEATURES

- Low On-state Resistance
  $R_{DS(on)}$ = 0.18 Ω TYP. (V_{GS} = −10 V, I_D = −1 A)
  $R_{DS(on)}$ = 0.36 Ω TYP. (V_{GS} = −4 V, I_D = −0.8 A)
- Low C_{iss} C_{iss} = 330 pF TYP.
- Built-in G-S Gate Protection Diode

QUALITY GRADE

Standard

Please refer to "Quality grade on NEC Semiconductor Devices" (Document number IEI-1209) published by NEC Corporation to know the specification of quality grade on the devices and its recommended applications.

ABSOLUTE MAXIMUM RATINGS (T_a = 25 °C)

Drain to Source Voltage	V_{DSS}	−30	V
Gate to Source Voltage (AC)	V_{GSS}	∓20	V
Gate to Source Voltage (DC)	V_{GSS}	−20, +10	V
Drain Current (DC)	$I_{D(DC)}$	∓2.0	A
Drain Current (pulse)	$I_{D(pulse)}$*	∓8.0	A
Total Power Dissipation (T_c = 25 °C)	P_{T1}	20	W
Total Power Dissipation (T_a = 25 °C)	P_{T2}	1.0	W
Channel Temperature	T_{ch}	150	°C
Storage Temperature	T_{stg}	−55 to +150	°C

* PW ≦ 10 μs, Duty Cycle ≦ 1 %

PACKAGE DIMENSIONS
in millimeters

2SJ324



2SJ324-Z



1. Gate
2. Drain
3. Source
4. Drain



Document No. TC-2459
(O.D. No. TC-7959)
Date Published October 1993 M
Printed in Japan

ELECTRICAL CHARACTERISTICS (T_a = 25 °C)

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Drain to Source On-state Resistance	$R_{DS(on)}$		0.18	0.25	Ω	V_{GS} = −10 V, I_D = −1.0 A
Drain to Source On-state Resistance	$R_{DS(on)}$		0.36	0.52	Ω	V_{GS} = −4 V, I_D = −0.8 A
Gate to Source Cutoff Voltage	$V_{GS(off)}$	−1.0	−1.5	−2.0	V	V_{DS} = −10 V, I_D = −1 mA
Forward Transfer Admittance	$\|y_{fs}\|$	1.0	1.9		S	V_{DS} = −10 V, I_D = −1.0 A
Drain Leakage Current	I_{DSS}			−10	μA	V_{DS} = −30 V, V_{GS} = 0
Gate to Source Leakage Current	I_{GSS}			±10	μA	V_{GS} = ∓16 V, V_{DS} = 0
Input Capacitance	C_{iss}		330		pF	V_{DS} = −10 V V_{GS} = 0 f = 1 MHz
Output Capacitance	C_{oss}		290		pF	
Reverse Transfer Capacitance	C_{rss}		105		pF	
Turn-On Delay Time	$t_{d(on)}$		7		ns	$V_{GS(on)}$ = −10 V V_{DD} = −15 V I_D = −1.0 A, R_G = 10 Ω R_L = 15 Ω
Rise Time	t_r		35		ns	
Turn-Off Delay Time	$t_{d(off)}$		40		ns	
Fall Time	t_f		30		ns	
Total Gate Charge	Q_G		12		nC	V_{GS} = −10 V I_D = −2.0 A V_{DD} = −24 V
Gate to Source Charge	Q_{GS}		1.5		nC	
Gate to Drain Charge	Q_{GD}		4.5		nC	
Body Diode Forward Voltage	V_F		0.9		V	I_F = 2.0 A, V_{GS} = 0
Reverse Recovery Time	t_{rr}		50		ns	I_F = 2.0 A, V_{GS} = 0 di/dt = 50 A/μs
Reverse Recovery Charge	Q_{rr}		40		nC	
ESD	V_{ESD}		±130		V	C = 200 pF, R = 0, Single Pulse

Test Circuit 1: Switching Time



Test Circuit 2: Gate Charge



TYPICAL CHARACTERISTICS (T_a = 25 °C)

DERATING FACTOR OF FORWARD BIAS SAFE OPERATING AREA



FORWARD BIAS SAFE OPERATING AREA



TOTAL POWER DISSIPATION vs. CASE TEMPERATURE



DRAIN CURRENT vs. DRAIN TO SOURCE VOLTAGE



TRANSIENT THERMAL RESISTANCE vs. PULSE WIDTH



TRANSFER CHARACTERISTICS



FORWARD TRANSFER ADMITTANCE vs. DRAIN CURRENT



DRAIN TO SOURCE ON-STATE RESISTANCE vs. GATE TO SOURCE VOLTAGE



DRAIN TO SOURCE ON-STATE RESISTANCE vs. DRAIN CURRENT



GATE TO SOURCE CUTOFF VOLTAGE vs. CHANNEL TEMPERATURE



DRAIN TO SOURCE ON-STATE RESISTANCE vs. CHANNEL TEMPERATURE



SOURCE TO DRAIN DIODE FORWARD VOLTAGE



CAPACITANCE vs. DRAIN TO SOURCE VOLTAGE



SWITCHING CHARACTERISTICS



DYNAMIC INPUT/OUTPUT CHARACTERISTICS



REVERSE RECOVERY TIME vs. REVERSE DRAIN CURRENT



Reference

Application note name	No.
Safe operating area of Power MOS FET.	TEA-1034
Application circuit using Power MOS FET.	TEA-1035
Quality control of NEC semiconductors devices.	TEI-1202
Quality control guide of semiconductors devices.	MEI-1202
Assembly manual of semiconductors devices.	IEI-1207

M4 92.6