Ordering number: EN 2605B

Monolithic Linear IC

SANYO No.2605B

L79M00T Series

−5 to −12V 0.5A 3-Pin Voltage Regulators

Features

- Output voltage: L79M05T: −5V, L79M06T: −6V, L79M08T: −8V, L79M09T: −9V, L79M10T: −10V, L79M12T: −12V
- 500mA output
- Small-sized power package TP-3H permitting the equipment to be made compact
- The allowable power dissipation can be increased by being surface-mounted on the board.
- Capable of being mounted in a variety of methods because of various lead forming versions available
- On-chip protectors (overcurrent limiter, ASO protector, thermal protector)
- Can meet tape-used automatic mounting requirements.

[Common to L79M00T series]

Maximum Ratings at Ta = 25°C

				unit
Maximum Supply Voltage	V_{CC} max	−5 to −12V output	−35	V
Allowable Power Dissipation	Pd max		1.0	W
Operating Temperature	**Topr**		−30 to +80	°C
Storage Temperature	Tstg		−40 to +150	°C

[L79M05T]

Recommended Operating Conditions at Ta = 25°C

			unit
Input Voltage	V_{IN}	−20 to −7.5	V
Output Current	I_{OUT}	5 to 500	mA

Operating Characteristics at Ta = 25°C, V_{IN} = −10V, I_{OUT} = 350mA, C_{IN} = 2μF, C_{OUT} = 1μF

			min	typ	max	unit
Output Voltage	V_{OUT}	Tj = 25°C	−5.2	−5.0	−4.8	V
Line Regulation	ΔV_{oline}	Tj = 25°C, −25V ≦ V_{IN} ≦ −7V		7.0	50	mV
		Tj = 25°C, −18V ≦ V_{IN} ≦ −8V		3.0	30	mV
Load Regulation	ΔV_{oload}	Tj = 25°C, 5mA ≦ I_{OUT} ≦ 500mA		10	100	mV
		Tj = 25°C, 5mA ≦ I_{OUT} ≦ 350mA		5		mV

Continued on next page.

Equivalent Circuit



Package Dimensions (unit: mm) 3110-S3HIC



1. COMMON
2. INPUT
3. OUTPUT

SANYO: TP-3H

Continued from preceding page.

			min	typ	max	unit
Output Voltage	V_{OUT}	$-25V \leqq V_{IN} \leqq -7V$, $5mA \leqq I_{OUT} \leqq 350mA$	−5.25		−4.75	V
Current Dissipation	I_{CC}	Tj=25°C		1.0	2.5	mA
Current Dissipation Variation (Line)	ΔI_{CCline}	$-25V \leqq V_{IN} \leqq -8V$			1.0	mA
Current Dissipation Variation (Load)	ΔI_{CCload}	$5mA \leqq I_{OUT} \leqq 350mA$			0.4	mA
Output Noise Voltage	V_{NO}	$10Hz \leqq f \leqq 100kHz$		125		μV
Ripple Rejection	R_{rej}	f=120Hz, I_{OUT}=100mA	50			dB
		$-18V \leqq V_{IN} \leqq -8V$, I_{OUT}=300mA, Tj=25°C	50	65		dB
Minimum Input-Output Voltage Drop	V_{drop}	Tj=25°C, I_{OUT}=350mA		1.1		V
Short Current	I_{OS}	Tj=25°C, V_{IN}=−30V		130		mA
Peak Output Current	Iop			800		mA

[L79M06T]

Recommended Operating Conditions at Ta=25°C

			unit
Input Voltage	V_{IN}	−21 to −8.5	V
Output Current	I_{OUT}	5 to 500	mA

Operating Characteristics at Ta=25°C, V_{IN}=−11V, I_{OUT}=350mA, C_{IN}=2μF, C_{OUT}=1μF

			min	typ	max	unit
Output Voltage	V_{OUT}	Tj=25°C	−6.25	−6.0	−5.75	V
Line Regulation	ΔV_{oline}	Tj=25°C, $-25V \leqq V_{IN} \leqq -8V$		7.0	60	mV
		Tj=25°C, $-19V \leqq V_{IN} \leqq -9V$		3.0	40	mV
Load Regulation	ΔV_{oload}	Tj=25°C, $5mA \leqq I_{OUT} \leqq 500mA$		10	120	mV
		Tj=25°C, $5mA \leqq I_{OUT} \leqq 350mA$		5		mV
Output Voltage	V_{OUT}	$-25V \leqq V_{IN} \leqq -8V$, $5mA \leqq I_{OUT} \leqq 350mA$	−6.3		−5.7	V
Current Dissipation	I_{CC}	Tj=25°C		1.0	2.5	mA
Current Dissipation Variation (Line)	ΔI_{CCline}	$-25V \leqq V_{IN} \leqq -9V$			1.0	mA
Current Dissipation Variation (Load)	ΔI_{CCload}	$5mA \leqq I_{OUT} \leqq 350mA$			0.4	mA
Output Noise Voltage	V_{NO}	$10Hz \leqq f \leqq 100kHz$		150		μV
Ripple Rejection	R_{rej}	f=120Hz, I_{OUT}=100mA	50			dB
		$-19V \leqq V_{IN} \leqq -9V$, I_{OUT}=300mA, Tj=25°C	50	65		dB
Minimum Input-Output Voltage Drop	V_{drop}	Tj=25°C, I_{OUT}=350mA		1.1		V
Short Current	I_{OS}	Tj=25°C, V_{IN}=−30V		130		mA
Peak Output Current	Iop			800		mA

[L79M08T]

Recommended Operating Conditions at Ta=25°C

			unit
Input Voltage	V_{IN}	−23 to −11	V
Output Current	I_{OUT}	5 to 500	mA

Operating Characteristics at Ta = 25°C, V_{IN} = −14V, I_{OUT} = 350mA, C_{IN} = 2μF, C_{OUT} = 1μF

				min	typ	max	unit
Output Voltage	V_{OUT}	Tj = 25°C		−8.3	−8.0	−7.7	V
Line Regulation	ΔV_{oline}	Tj = 25°C, −25V ≦ V_{IN} ≦ −10.5V			8.0	80	mV
		Tj = 25°C, −21V ≦ V_{IN} ≦ −11V			4.0	50	mV
Load Regulation	ΔV_{oload}	Tj = 25°C, 5mA ≦ I_{OUT} ≦ 500mA			11	160	mV
		Tj = 25°C, 5mA ≦ I_{OUT} ≦ 350mA			6		mV
Output Voltage	V_{OUT}	−25V ≦ V_{IN} ≦ −10.5V, 5mA ≦ I_{OUT} ≦ 350mA		−8.4		−7.6	V
Current Dissipation	I_{CC}	Tj = 25°C			1.0	2.5	mA
Current Dissipation Variation (Line)	ΔI_{CCline}	−25V ≦ V_{IN} ≦ −10.5V				1.0	mA
Current Dissipation Variation (Load)	ΔI_{CCload}	5mA ≦ I_{OUT} ≦ 350mA				0.4	mA
Output Noise Voltage	V_{NO}	10Hz ≦ f ≦ 100kHz			200		μV
Ripple Rejection	R_{rej}	f = 120Hz	I_{OUT} = 100mA	50			dB
		−21.5V ≦ V_{IN} ≦ −11.5V, Tj = 25°C	I_{OUT} = 300mA	50	64		dB
Minimum Input-Output Voltage Drop	V_{drop}	Tj = 25°C, I_{OUT} = 350mA			1.1		V
Short Current	I_{OS}	Tj = 25°C, V_{IN} = −30V			130		mA
Peak Output Current	Iop				800		mA

[L79M09T]

Recommended Operating Conditions at Ta = 25°C

			unit
Input Voltage	V_{IN}	−25 to −12	V
Output Current	I_{OUT}	5 to 500	mA

Operating Characteristics at Ta = 25°C, V_{IN} = −16V, I_{OUT} = 350mA, C_{IN} = 2μF, C_{OUT} = 1μF

				min	typ	max	unit
Output Voltage	V_{OUT}	Tj = 25°C		−9.4	−9.0	−8.6	V
Line Regulation	ΔV_{oline}	Tj = 25°C, −25V ≦ V_{IN} ≦ −11.5V			8.0	80	mV
		Tj = 25°C, −20V ≦ V_{IN} ≦ −12V			4.0	50	mV
Load Regulation	ΔV_{oload}	Tj = 25°C, 5mA ≦ I_{OUT} ≦ 500mA			12	200	mV
		Tj = 25°C, 5mA ≦ I_{OUT} ≦ 350mA			7		mV
Output Voltage	V_{OUT}	−25V ≦ V_{IN} ≦ −11.5V, 5mA ≦ I_{OUT} ≦ 350mA		−9.5		−8.5	V
Current Dissipation	I_{CC}	Tj = 25°C			1.0	2.5	mA
Current Dissipation Variation (Line)	ΔI_{CCline}	−25V ≦ V_{IN} ≦ −11.5V				1.0	mA
Current Dissipation Variation (Load)	ΔI_{CCload}	5mA ≦ I_{OUT} ≦ 350mA				0.4	mA
Output Noise Voltage	V_{NO}	10Hz ≦ f ≦ 100kHz			225		μV
Ripple Rejection	R_{rej}	f = 120Hz	I_{OUT} = 100mA	50			dB
		−22.5V ≦ V_{IN} ≦ −12.5V, Tj = 25°C	I_{OUT} = 300mA	50	63		dB
Minimum Input-Output Voltage Drop	V_{drop}	Tj = 25°C, I_{OUT} = 350mA			1.1		V
Short Current	I_{OS}	Tj = 25°C, V_{IN} = −30V			130		mA
Peak Output Current	Iop				800		mA

[L79M10T]

Recommended Operating Conditions at Ta = 25°C

			unit
Input Voltage	V_{IN}	−25 to −13	V
Output Current	I_{OUT}	5 to 500	mA

Operating Characteristics at Ta = 25°C, V_{IN} = −17V, I_{OUT} = 350mA, C_{IN} = 2μF, C_{OUT} = 1μF

				min	typ	max	unit
Output Voltage	V_{OUT}	Tj = 25°C		−10.4	−10	−9.6	V
Line Regulation	ΔV_{oline}	Tj = 25°C, −25V ≦ V_{IN} ≦ −12.5V			9.0	80	mV
		Tj = 25°C, −22V ≦ V_{IN} ≦ −13V			5.0	50	mV
Load Regulation	ΔV_{oload}	Tj = 25°C, 5mA ≦ I_{OUT} ≦ 500mA			12	200	mV
		Tj = 25°C, 5mA ≦ I_{OUT} ≦ 350mA			7		mV
Output Voltage	V_{OUT}	−25V ≦ V_{IN} ≦ −12.5V, 5mA ≦ I_{OUT} ≦ 350mA		−10.5		−9.5	V
Current Dissipation	I_{CC}	Tj = 25°C			1.0	2.5	mA
Current Dissipation Variation (Line)	ΔI_{CCline}	−25V ≦ V_{IN} ≦ −12.5V				1.0	mA
Current Dissipation Variation (Load)	ΔI_{CCload}	5mA ≦ I_{OUT} ≦ 350mA				0.4	mA
Output Noise Voltage	V_{NO}	10Hz ≦ f ≦ 100kHz			250		μV
Ripple Rejection	R_{rej}	f = 120Hz	I_{OUT} = 100mA	50			dB
		−23.5V ≦ V_{IN} ≦ −13.5V, Tj = 25°C	I_{OUT} = 300mA	50	63		dB
Minimum Input-Output Voltage Drop	V_{drop}	Tj = 25°C, I_{OUT} = 350mA			1.1		V
Short Current	I_{OS}	Tj = 25°C, V_{IN} = −30V			130		mA
Peak Output Current	Iop				800		mA

[L79M12T]

Recommended Operating Conditions at Ta = 25°C

			unit
Input Voltage	V_{IN}	−25 to −15	V
Output Current	I_{OUT}	5 to 500	mA

Operating Characteristics at Ta = 25°C, V_{IN} = −19V, I_{OUT} = 350mA, C_{IN} = 2μF, C_{OUT} = 1μF

				min	typ	max	unit
Output Voltage	V_{OUT}	Tj = 25°C		−12.5	−12	−11.5	V
Line Regulation	ΔV_{oline}	Tj = 25°C, −30V ≦ V_{IN} ≦ −14.5V			9.0	80	mV
		Tj = 25°C, −25V ≦ V_{IN} ≦ −15V			5.0	50	mV
Load Regulation	ΔV_{oload}	Tj = 25°C, 5mA ≦ I_{OUT} ≦ 500mA			9	240	mV
		Tj = 25°C, 5mA ≦ I_{OUT} ≦ 350mA			6		mV
Output Voltage	V_{OUT}	−30V ≦ V_{IN} ≦ −14.5V, 5mA ≦ I_{OUT} ≦ 350mA		−12.6		−11.4	V
Current Dissipation	I_{CC}	Tj = 25°C			1.6	3.5	mA
Current Dissipation Variation (Line)	ΔI_{CCline}	−30V ≦ V_{IN} ≦ −14.5V				1.0	mA
Current Dissipation Variation (Load)	ΔI_{CCload}	5mA ≦ I_{OUT} ≦ 350mA				0.4	mA
Output Noise Voltage	V_{NO}	10Hz ≦ f ≦ 100kHz			300		μV
Ripple Rejection	R_{rej}	f = 120Hz	I_{OUT} = 100mA	50			dB
		−25V ≦ V_{IN} ≦ −15V, Tj = 25°C	I_{OUT} = 300mA	50	72		dB
Minimum Input-Output Voltage Drop	V_{drop}	Tj = 25°C, I_{OUT} = 350mA			1.1		V
Short Current	I_{OS}	Tj = 25°C, V_{IN} = −30V			130		mA
Peak Output Current	Iop				800		mA





Specified Test Circuit (Common to L79M00T series)



Unit (capacitance: F)

Note) V_{IN} max must be in the range specified above, with regulation, etc. considered.

■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:
① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.