

Practical No. 10

Aim: Install Samba to share folders or files between Windows and Linux.

Description:


1. Explain: Samba

Steps:

A Samba file server enables file sharing across different operating systems over a network. It lets you access your desktop files from a laptop and share files with Windows and macOS users.

Installing Samba

1. update all repository


A terminal window with a dark background and light text. The prompt is 'cs@cs: ~'. The command 'sudo apt update -y' is entered. The output shows the password prompt, four 'Hit' messages for different Ubuntu repositories, and a summary stating that 7 packages can be upgraded. The prompt returns to 'cs@cs: ~\$'.

```
cs@cs: ~$ sudo apt update -y
[sudo] password for cs:
Hit:1 http://in.archive.ubuntu.com/ubuntu xenial InRelease
Hit:2 http://in.archive.ubuntu.com/ubuntu xenial-updates InRelease
Hit:3 http://in.archive.ubuntu.com/ubuntu xenial-backports InRelease
Hit:4 http://security.ubuntu.com/ubuntu xenial-security InRelease
Reading package lists... Done
Building dependency tree
Reading state information... Done
7 packages can be upgraded. Run 'apt list --upgradable' to see them.
cs@cs: ~$
```

2. install samba

```
cs@cs:~$ sudo apt install samba -y
Reading package lists... Done
Building dependency tree
Reading state information... Done
The following packages were automatically installed and are no longer required:
  libirs-export141 libisccfg-export140
Use 'sudo apt autoremove' to remove them.
The following additional packages will be installed:
  attr python-crypto python-dnspython python-ldb python-samba python-tdb
  samba-common samba-common-bin samba-dsdb-modules samba-vfs-modules tdb-tools
Suggested packages:
  python-crypto-dbg python-crypto-doc ctdb ldb-tools ntp smbldap-tools winbind
  heimdal-clients
The following NEW packages will be installed:
  attr python-crypto python-dnspython python-ldb python-samba python-tdb samba
  samba-common samba-common-bin samba-dsdb-modules samba-vfs-modules tdb-tools
0 upgraded, 12 newly installed, 0 to remove and 7 not upgraded.
Need to get 3,444 kB of archives.
After this operation, 25.8 MB of additional disk space will be used.
```

3. we'll create a directory to share. So we'll create a directory under / and then change the permission to 777.



```
cs@cs:~$ sudo mkdir /share
cs@cs:~$ sudo chmod 777 /share
cs@cs:~$
```

4. Now we have to edit the main configuration file of samba.

```
cs@cs:~$ sudo nano /etc/samba/smb.conf
```

```
GNU nano 2.5.3      File: /etc/samba/smb.conf
##
# Sample configuration file for the Samba suite for Debian GNU/Linux.
#
#
# This is the main Samba configuration file. You should read the
# smb.conf(5) manual page in order to understand the options listed
# here. Samba has a huge number of configurable options most of which
# are not shown in this example
#
# Some options that are often worth tuning have been included as
# commented-out examples in this file.
# - When such options are commented with ";", the proposed setting
#   differs from the default Samba behaviour
# - When commented with "#", the proposed setting is the default
#   behaviour of Samba but the option is considered important
#   enough to be mentioned here
#
# NOTE: Whenever you modify this file you should run the command
# "testparm" to check that you have not made any basic syntactic
# errors.

#===== Global Settings =====

[global]

## Browsing/Identification ##

# Change this to the workgroup/NT-domain name your Samba server will part of
[ Read 260 lines ]
^G Get Help  ^O Write Out ^W Where Is  ^K Cut Text  ^J Justify   ^C Cur Pos
^X Exit      ^R Read File ^\ Replace   ^U Uncut Text ^T To Spell  ^_ Go To Line
```

Press Ctrl+end to get to the end of file.

Then we'll write the shared definition

[my-samba-share] - share name

path = /share – directory which you want to share

public = no – this samba server is not public which means to access this file its requires authentication

valid users = tom jerry – users who can connect

read list = tom – user tom will have read access to this directory

write list = jerry – user jerry will have write access to this directory

browseable = yes – in the client system all the users will be able to access network share

comment = "My Samba File Server" - Any comment you can give

```
GNU nano 2.5.3      File: /etc/samba/smb.conf      Modified

printable = yes
guest ok = no
read only = yes
create mask = 0700

# Windows clients look for this share name as a source of downloadable
# printer drivers
[print$]
    comment = Printer Drivers
    path = /var/lib/samba/printers
    browseable = yes
    read only = yes
    guest ok = no
# Uncomment to allow remote administration of Windows print drivers.
# You may need to replace 'lpadmin' with the name of the group your
# admin users are members of.
# Please note that you also need to set appropriate Unix permissions
# to the drivers directory for these users to have write rights in it
;   write list = root, @lpadmin

[my-samba-share]
    path = /share
    public = no
    valid users = tom, harry
    read list = tom
    write list = jerry
    browseable = yes
    comment = "My Samba File Server"

^G Get Help  ^O Write Out ^W Where Is  ^K Cut Text  ^J Justify   ^C Cur Pos
^X Exit      ^R Read File ^\ Replace   ^U Uncut Text ^T To Spell  ^_ Go To Line
```

Press ctrl+O to write to the file

5. to validate the configuration which we just did type the command **testparm**

```
cs@cs:~$ sudo testparm
Load smb config files from /etc/samba/smb.conf
rlimit_max: increasing rlimit_max (1024) to minimum Windows limit (16384)
WARNING: The "syslog" option is deprecated
Processing section "[printers]"
Processing section "[print$]"
Processing section "[my-samba-share]"
Loaded services file OK.
WARNING: You have some share names that are longer than 12 characters.
These may not be accessible to some older clients.
(Eg. Windows9x, WindowsMe, and smbclient prior to Samba 3.0.)
Server role: ROLE_STANDALONE

Press enter to see a dump of your service definitions
```



```

cs@cs:~$ sudo testparm
Load smb config files from /etc/samba/smb.conf
rlimit_max: increasing rlimit_max (1024) to minimum Windows limit (16384)
WARNING: The "syslog" option is deprecated
Processing section "[printers]"
Processing section "[print$]"
Processing section "[my-samba-share]"
Loaded services file OK.
WARNING: You have some share names that are longer than 12 characters.
These may not be accessible to some older clients.
(Eg. Windows9x, WindowsMe, and smbclient prior to Samba 3.0.)
Server role: ROLE_STANDALONE

```

```

    passwd program = /usr/bin/passwd %u
    passwd chat = *Enter\snew\s*\spassword:* %n\n *Retype\snew\s*\spassword:
* %n\n *password\supdated\ssuccessfully* .
    unix password sync = Yes
    syslog = 0
    log file = /var/log/samba/log.%m
    max log size = 1000
    dns proxy = No
    usershare allow guests = Yes
    panic action = /usr/share/samba/panic-action %d
    idmap config * : backend = tdb

[printers]
    comment = All Printers
    path = /var/spool/samba
    create mask = 0700
    printable = Yes
    browseable = No

[print$]
    comment = Printer Drivers
    path = /var/lib/samba/printers

[my-samba-share]
    comment = "My Samba File Server"
    path = /share
    valid users = tom harry
    read list = tom
    write list = jerry
cs@cs:~$

```

6. Now we'll create the users to samba access. [Note: users create here are not system users only for samba authentication]

```

cs@cs:~$ sudo useradd tom -s /sbin/nologin
cs@cs:~$ sudo useradd jerry -s /sbin/nologin
cs@cs:~$

```

7. Set the samba password for the users we create above.

```
cs@cs:~$ sudo smbpasswd -a tom
New SMB password:
Retype new SMB password:
Added user tom.
cs@cs:~$ sudo smbpasswd -a jerry
New SMB password:
Retype new SMB password:
Added user jerry.
cs@cs:~$
```

8. Now we have to start the services of samba.

`sudo systemctl start smbd`

`sudo systemctl start nmbd` [net bios service – to perform network discovery]

also enable both services

```
cs@cs:~$ sudo systemctl start smbd
cs@cs:~$ sudo systemctl start nmbd
cs@cs:~$ sudo systemctl enable smbd nmbd
smbd.service is not a native service, redirecting to systemd-sysv-install
Executing /lib/systemd/systemd-sysv-install enable smbd
nmbd.service is not a native service, redirecting to systemd-sysv-install
Executing /lib/systemd/systemd-sysv-install enable nmbd
cs@cs:~$
```

9. check ip address of server machine


```
cs@cs:~$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: ens33: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast state UP group default qlen 1000
    link/ether 00:0c:29:1c:f5:7d brd ff:ff:ff:ff:ff:ff
    inet 192.168.173.132/24 brd 192.168.173.255 scope global dynamic ens33
        valid_lft 1298sec preferred_lft 1298sec
    inet6 fe80::c8fa:acec:af2:c62d/64 scope link
        valid_lft forever preferred_lft forever
cs@cs:~$
```



Client Side:


1. open terminal and ping the server ip. If you are able to ping the server that means you are in network with the server

```
cs2@cs2:~$ ping 192.168.173.132
PING 192.168.173.132 (192.168.173.132) 56(84) bytes of data.
64 bytes from 192.168.173.132: icmp_seq=1 ttl=64 time=0.436 ms
64 bytes from 192.168.173.132: icmp_seq=2 ttl=64 time=0.468 ms
64 bytes from 192.168.173.132: icmp_seq=3 ttl=64 time=0.478 ms
64 bytes from 192.168.173.132: icmp_seq=4 ttl=64 time=0.534 ms
64 bytes from 192.168.173.132: icmp_seq=5 ttl=64 time=0.484 ms
64 bytes from 192.168.173.132: icmp_seq=6 ttl=64 time=0.473 ms
64 bytes from 192.168.173.132: icmp_seq=7 ttl=64 time=0.536 ms
64 bytes from 192.168.173.132: icmp_seq=8 ttl=64 time=0.489 ms
```

2. Then open File Manager -> Other Locations -> connect to server -> smb://192.168.173.132











"my-samba-share" selected



MVLU College




Windows Client Side:

1. Press window + R then enter cmd. And then ping the server to check whether we are in the network or not.







Windows Security

Enter network credentials

Enter your credentials to connect to: 192.168.173.132

jerry

•••••

☐ Remember my credentials

Access is denied.

OK

Cancel

MVLU College

