TRINEXIS: An Alert-Aware Narration Policy, Preregistered Measurement Protocol, and Software Verification

Yug G. Lakhani[1]
[1]Department of Computer Engineering, Gyanmanjari Innovative University, Bhavnagar, Gujarat, India
Corresponding author: Yug G. Lakhani, yglakhani@gmiu.edu.in
ORCID: https://orcid.org/0009-0004-2930-4953

Abstract— Open-vocabulary webcam systems must decide which detected objects to speak when output is short and time-limited. This protocol and software-verification report defines an alert-aware narration policy and a preregistered plan for measuring its effect on alert delivery. The policy ranks user-designated alert objects before truncating the spoken shortlist; confidence-first and nearest-object-first baselines provide two comparison orderings. The research question is whether alert-first narration makes users notice a designated object faster or more often than confidence-first narration, with log-derived delivery and consented user noticing kept as distinct endpoints. TRINEXIS implements the policy in an interval-throttled, language-configured webcam system with optional real-log instrumentation, a frozen alert manifest, a 5-10 session replay harness, a guarded within-subject study worksheet, Flask route tests, and continuous integration. Experiments A-E specify hardware timing, labeled detection evaluation, a frozen vocabulary/confidence grid, real-log alert replay, checked-language ratings, and ethics-gated user noticing. The verified contribution is the policy, its failable software checks, and a protocol designed to report positive, null, or negative alert-first effects without presupposing the result. No empirical detection, latency, language, distance, or user-benefit measurement is reported; the protocol is the deliverable, not a description of a Flask application.

Keywords / Index Terms— alert-aware narration; open-vocabulary detection; preregistered protocol; research software; software verification; speech interface; interval throttling

I. INTRODUCTION

A. Motivation and Research Question

Object detection predicts bounding boxes and semantic labels for objects in an image. The YOLO family formulated detection as a single regression problem [1], and COCO-style benchmarks standardized evaluation over a fixed vocabulary of 80 released categories [2]. Vision-language pre-training broadened the interface: CLIP enabled zero-shot transfer from natural-language supervision [3], Grounding DINO fused language and vision for open-set detection [4], and YOLO-World introduced a prompt-then-detect paradigm [5]. Ultralytics exposes that family through a set_classes interface [6]. These advances make configurable object names possible, but an interactive narration system still has to decide what to say first when only a few objects can be spoken.

The research question is: Does alert-first narration make users notice a designated object faster or more often than confidence-first narration? This protocol separates two measurable endpoints. Replayed real logs can measure whether an alert reaches the spoken shortlist and how long alert-to-speech delivery takes. Whether a person notices the object faster or more often requires a separate consented user study. The protocol is constructed so that neither endpoint is inferred from software checks alone.

TRINEXIS is the research instrument used to implement the policy: an interval-throttled YOLO-World webcam pipeline with a browser dashboard, language-configured speech output, session telemetry, and optional real-log instrumentation. Its maintained backend, app23.py, uses Flask control routes [7], OpenCV capture [8], Ultralytics YOLO [15], and gTTS speech [9]. The Flask application is implementation infrastructure, not the paper's contribution.

B. Contribution

The contribution is an alert-aware narration policy, a preregistered measurement protocol, and reproducible software verification, not a Flask app or a general webcam-application description. User-designated alert objects are ranked before the spoken shortlist is truncated. The ordering is isolated in a dependency-free policy module, checked by mutation-sensitive unit tests, instrumented for real-log replay, and deliberately kept separate from empirical detection or user-benefit claims.

- A policy and research question: alert-first, confidence-first, and nearest-object-first narration for a predesignated object, with delivery and noticing treated as distinct endpoints.
- A maintained implementation with AGPL-3.0 licensing [24], configurable camera/security settings, optional real-log timing and speech-event recorders, and a frozen alert-manifest mode.
- Real Flask test-client route tests, deterministic policy tests, continuous integration, and a source-level evidence-boundary check.
- A preregistered Experiments A-E measurement plan with hardware/data/rating manifests, runnable harnesses, and unfilled result templates.

C. Scope and Limitations

This protocol and software-verification report contains no empirical measurements; all empirical result cells remain NO DATA. It is not submission-ready as an empirical article. No labeled detection dataset, hardware timing campaign, known-distance calibration, translated-template rating, consented user study, dashboard screenshot, or spoken input-to-output example was completed. The author selected arXiv/institutional-report formatting; current official submission, moderation, metadata, and content-type pages were read on 10 Nov 2026 and recorded in paper/venue_guide_notes.md. arXiv has no mandatory venue template, so the generic single-column layout and numeric citations are retained. The author confirmed no external funding, no competing interests, and the CRediT roles actually performed; the AI-tool disclosure was checked against arXiv's current text-to-text generative-AI policy. The named author is responsible for final verification of numbers and declarations. No detection-quality, latency, distance-error, robustness, multilingual-comprehension, assistive-effectiveness, or user-benefit result is claimed.

II. RELATED WORK / LITERATURE REVIEW

A. Detection and Open-Vocabulary Models

The original YOLO paper evaluated PASCAL VOC 2007/2012 and artwork-domain generalization on the Picasso and People-Art datasets; it did not evaluate on COCO [1]. COCO later supplied a fixed-vocabulary benchmark [2]. CLIP [3], Grounding DINO [4], YOLO-World [5], OWL-ViT [11], GLIP [12], Detic [13], and YOLOE [14] represent successive approaches to language-conditioned or open-vocabulary recognition. Their published results were obtained under distinct datasets, splits, prompts, hardware, and protocols, so they are not treated here as comparative baselines for TRINEXIS. Table I summarizes scope and non-comparability.

TABLE I. VERIFIED RELATED WORK AND NON-COMPARABILITY

Source	Contribution	Verified evaluation context	Relevance and limitation
Redmon et al. [1], 2016	One-stage YOLO detector	PASCAL VOC 2007/2012; Picasso and People-Art artwork generalization	Established real-time closed-set detection; no COCO evaluation in that paper and a different hardware/protocol context
Lin et al. [2], 2014	Microsoft COCO benchmark	Approximately 328,000 images, 2.5 million labeled instances, 80 released categories	Standard fixed-vocabulary protocol; utils/coco.txt is only a label list in this repository
Radford et al. [3], 2021	CLIP contrastive pre-training	400 million image–text pairs; zero-shot transfer over more than 30 datasets	Representation learning, not a real-time bounding-box detector

Source	Contribution	Verified evaluation context	Relevance and limitation
Liu et al. [4], 2024	Grounding DINO, ECCV 2024 published version	Open-set and referring-expression benchmarks under published protocols	Alternative open-set approach; not used in this repository
Cheng et al. [5], 2024	YOLO-World and RepVL-PAN	CVPR 2024, pp. 16901–16911	Direct model-family basis; published benchmark results are not reproduced here
Minderer et al. [11]; Li et al. [12]; Zhou et al. [13]; Wang et al. [14]	OWL-ViT, GLIP, Detic, YOLOE	ECCV/CVPR/arXiv protocols with distinct vocabularies and datasets	Expanded open-vocabulary context; incompatible with this repository's prompts and runtime
Alqahtani et al. [19], 2024	Edge accuracy–latency–energy benchmark	YOLOv8, SSD, and EfficientDet Lite across heterogeneous edge devices	Motivates separate timing instrumentation; its measurements are not reused as TRINEXIS results

Published numeric context (not TRINEXIS results). The scale facts below are verifiable bibliographic facts from the cited sources, included only to characterize their scope. They are not TRINEXIS measurements, are not entered into Table V, and are not used to claim detection quality, latency, distance accuracy, multilingual comprehension, or user benefit. Ref. [19] is an edge accuracy-latency-energy benchmark under its own devices and protocol; none of its device-specific accuracy, latency, or energy numbers are reused here.

TABLE I-B. PUBLISHED CONTEXT (NOT TRINEXIS MEASUREMENTS)

Source	Published numeric context	Status in this report
Lin et al. [2], 2014	Approximately 328,000 images, 2.5 million labeled instances, and 80 released categories in the 2014 COCO release	Cited benchmark scale only; utils/coco.txt is a label list in this repository, not an evaluation of this app
Radford et al. [3], 2021	400 million image-text pairs; zero-shot transfer over more than 30 datasets	Cited pre-training/transfer scope only; CLIP is not the deployed detector here
Alqahtani et al. [19], 2024/2026	Edge accuracy-latency-energy benchmark of YOLOv8, SSD, and EfficientDet Lite across heterogeneous edge devices	Motivates separate timing instrumentation; no device-specific value is reused as a TRINEXIS result

B. Assistive Interfaces, Speech, and Privacy

Remote sighted assistance has been studied through Be My Eyes [16], while Seeing AI [17] and AI scene-description applications [18] illustrate practical auditory presentation of visual information. These systems are relevant to the design space but do not validate TRINEXIS. The repository configures 72 language codes and 62 top-level speech resources. Ten language codes use an English template fallback in the UI; the remaining 72-language claim is unchecked. gTTS uses Google Translate's speech service [9], so raters should listen to sample audio and the author should listen to a few languages before any quality claim. Camera-based systems also raise privacy and face-recognition concerns [20], [21]. The optional face-recognition hook remains unavailable, and no consent, retention, or biometric-processing protocol is claimed.

C. Research Software and Reproducibility

Git LFS stores small pointer files in Git while large model content is held elsewhere [10]. The prior immutable software release [23] includes CITATION.cff, codemeta.json, dependency-license notes, pinned manifests, and a weights download script that verifies Git LFS object identifiers as SHA-256 checksums. The current software snapshot adds experiment protocols, route tests, CI, and instrumentation beyond that release; no final v1.0.0 tag exists. The project adopts AGPL-3.0-only [24] because Ultralytics YOLO is distributed under AGPL-3.0 [22]. Zenodo DOI has not been minted; the final GitHub/Zenodo release must come last because a DOI is permanent for the exact version.

III. SYSTEM DESIGN

A. Architecture and Control Flow

Figure 1 shows the runtime and control flow. A browser client calls Flask control routes and displays a Motion JPEG stream. A configurable camera backend supplies frames to OpenCV. Detector calls are gated by an interval throttle, after which YOLO-World produces text-conditioned detection records. Those records feed visual overlays, a relative distance index, a time-decayed heatmap, session telemetry, an alert-aware speech selector, and optional real-log recorders. Optional face recognition is shown as a dashed, unavailable path. There is no training or benchmark-evaluation path.



Fig. 1. TRINEXIS system architecture. Solid arrows denote implemented runtime paths; the dashed arrow denotes an optional/unavailable face-recognition hook. Vector SVG/PDF versions are provided as figure exports.

B. Interval Throttle and Alert-Aware Narration

Let t be the current capture time, t_prev the previous detector invocation, and Delta the configured throttle interval. A detector call is admitted when

```
t - t_prev >= Delta. (1)
```

The default is Delta = 1.5 s and the spoken shortlist is limited to two objects. Let A be the set of user-designated alert names, c(o) the detector confidence, and d(o) the relative distance index. The selector sorts every detection record o by the ascending key

```
R(o) = (I_alert(o), -c(o), d(o)), (2)
```

and only then takes the first two records. In Eq. (2), I_alert(o) = 0 when o.name is in A and 1 otherwise; alert objects therefore receive priority regardless of whether they are among the two highest-confidence detections. A confidence-first shortlist followed by alert-aware reranking inside the shortlist would not provide this invariant. For Experiment C, alert names A are declared in a manifest before collection; the runtime freezes /set_alerts and embeds the manifest hash in detection and speech-event records.

C. Time-Based Heatmap and Relative Distance Index

Eq. (3) replaces the older per-frame 0.995 multiplier, whose decay depends on camera frame rate, with elapsed wall-clock time dt and an adjustable half-life tau:

$$H_t = 2^{(-dt/\tau)} * H_{(t-1)} + \sum_i C(c_i; 35). \quad (3)$$

In Eq. (3), H_t is the heatmap at time t, C(c_i; 35) is a filled circle of radius 35 pixels centered on detection box c_i, and tau defaults to 60 s. The 60 s value is an adjustable default chosen to retain visible activity for roughly one minute; it is not fitted to data. The distance overlay is a unitless, relative size-based index

$$d_{idx} = (W * F) / \max(w_{px}, 1), \quad (4)$$

where w_px is the observed box width, W = 60, and F = 360. W and F are heuristic constants, not calibrated physical measurements; d_idx has no metric unit and must not be interpreted as centimetres or metres.

D. Configuration, Security, Language Fallback, and Instrumentation

Camera index, backend, resolution, host, port, optional API token, read-only mode, single-client mode, client timeout, session secret, and heatmap half-life are read from environment variables. The default bind address is 127.0.0.1 rather than 0.0.0.0. /set_model accepts only a checked-in model allowlist. Mutating control endpoints can require an X-API-Token or Bearer header: missing or invalid tokens return 401, unsupported schemes and read-only mutations return 403, and a second controlling client receives 409. Capture-frame and detector-invocation rates are reported separately. Optional JSONL recorders remain off unless TRINEXIS_LATENCY_LOG and TRINEXIS_EVENT_LOG are configured; they timestamp capture, inference, TTS synthesis, playback, rendering, speech enqueue, and playback events. /get_languages exposes the English-fallback language list and an empty verified-language list.

TABLE II. IMPLEMENTATION FEATURES AND VERIFICATION

Feature	Implementation	Verification
Open-source distribution	AGPL-3.0 LICENSE [24], README, pinned requirements, CITATION.cff, codemeta.json, and dependency-license notes	Source-contract tests and README instructions
Confidence display	Dashboard reports AVG CONFIDENCE rather than ACCURACY	Source-contract test
Alert-aware speech	Rank alerts before shortlist truncation via trinexis_core.select_speech_objects	Mutation-sensitive unit test and tests/ synthetic unit-test artifact
Client-state safety	Single-client control arbitration, 401/403/409 behavior, and stale-session timeout	Flask route tests and pure-function unit tests
Network defaults	Default host 127.0.0.1; optional API token and read-only mode on mutating control routes	Flask route tests and source-contract tests
Model loading	Allowlisted model filenames with HTTP 400 on rejection	Unit and route tests
Heatmap decay	Wall-clock exponential decay with adjustable half-life	Unit test
Distance display	Unitless relative distance index with explicit non-calibration note	Unit and source-contract tests
Camera portability	Configurable camera index and backend	Unit and source-contract tests
Rate reporting	Separate capture_fps and inference_fps counters and dashboard displays	Source-contract test
Language fallback	Ten missing templates fall back to English; 72 language codes remain unchecked	Route, language, and source-contract tests
Real-log instrumentation	Optional JSONL timing and speech-event recorders with manifest hashes	Telemetry unit tests and Experiment C protocol
Figures	Enlarged PNG plus standalone SVG and vector-PDF exports	make_updated_figures.py

IV. SOFTWARE VERIFICATION

A. Verification Environment

All checks were static, synthetic, or exercised through Flask's test client with mocked native modules. The preparation environment used Python 3.11.2 with the standard library and Flask 3.1.3 for route tests; manuscript and figure generation used the pinned packages in paper/requirements-paper.txt. No model weights were hydrated, no camera was opened, no live Flask server was run, no network speech request was made, and no human participant was involved. Figure 2 summarizes the workflow. GitHub Actions is configured to run the same test suite on every push; a local CI-equivalent run passed, but no empirical result follows from a green test suite.



Fig. 2. Software-verification workflow. Every step is static, synthetic, or a mocked Flask route test; no model inference, camera capture, labeled dataset, or human data is used. The diagram shows an untagged software snapshot rather than a final tagged release. Vector SVG/PDF versions are provided as figure exports.

B. Synthetic Alert-Selection Unit Test

The seeded 1,000-case synthetic check is generated only by tests/test_synthetic_regression.py; the old experiments/ generator was removed. Each case has six records, one alert object, and a two-object speech shortlist. With six records and a top-2 shortlist, a uniformly ranked alert falls outside the shortlist with probability 4/6 (66.7%). The confidence-first ordering omitted the alert object in 681 of 1000 cases (68.1%), consistent with that probability setup; the alert-first ordering omitted it in 0 of 1000 cases (0.0%). A deliberately broken confidence-first selector makes the unit test fail. This is a failable unit-test artifact of an ordering invariant, not an experiment: it does not show how often real detections contain alerts, whether a real user hears an alert, or whether speech output is useful.

TABLE III. SEEDED SYNTHETIC UNIT-TEST REGRESSION CHECK

Metric	Confidence-first	Alert-first	Change
Cases with a configured alert object	1,000	1,000	—
Alert omissions from the two-object shortlist	681	0	–681
Omission rate	68.1%	0.0%	–68.1 pp
Evidence type	Synthetic unit test	Synthetic unit test	No model inference

C. Route, Policy, and Source-Contract Tests

The standard-library unittest suite contains 93 tests: 43 + 37 + 13 = 93, namely 43 Flask route tests, 37 policy/harness/telemetry tests, and 13 source-contract tests. The exact CI statement is: 43 route tests plus 37 policy tests, run in CI. Route tests are reported separately from source-text tests. They exercise all 23 routes' status codes, JSON-object validation, clamping, API-token 401 behavior, unsupported-scheme/read-only 403 behavior, Bearer authentication, single-client 409 behavior, frozen alert manifests, and language-support metadata. Camera, NumPy, detector, and TTS imports are mocked with unittest.mock; no live runtime is validated by these counts. Policy tests cover narration ranking, mutation sensitivity, control status, telemetry arithmetic, language fallback, experiment-harness self-checks, and the seeded synthetic unit test. Continuous integration runs the suite on every push and pull request.

TABLE IV. TEST-SUITE SUMMARY

Test group	Tests	Failures	Errors
Flask test-client route tests	43	0	0
Policy/harness/telemetry tests	37	0	0
Repository/source-contract tests	13	0	0
Total	93	0	0

D. Snapshot and Reproducibility

The prior immutable software release is GitHub release v0.3.0-standalone [23]. The current software snapshot has no final tag; it adds CITATION.cff/codemeta metadata updates, experiment protocols, real-log instrumentation, route tests, CI, language-fallback documentation, and this protocol report. weights/download_weights.py parses the checked-in Git LFS pointers and verifies the declared SHA-256 object identifiers after Git LFS materialization. Appendix A lists reproduction commands, and Appendix B lists the principal artifacts.

E. Protocol Execution

- Execute Experiments A-D on declared hardware, labeled data, real logs, and checked languages; report negative or null results as-is.
- Obtain consent and institutional ethics approval before any user-noticing study.
- Calibrate the distance proxy at known distances or retain the unitless index with its current disclaimer.

V. PREREGISTERED MEASUREMENT PROTOCOL

A. Protocol Freeze and Real Logs

This protocol fixes the measurement plan before collection. Before collection, freeze hardware/software manifests, the paper and code, a 200-300-image report split, frozen prompt sets, and a predeclared alert-object manifest. The live app writes timestamped JSONL only when TRINEXIS_LATENCY_LOG and TRINEXIS_EVENT_LOG are configured. /export_logs supplies detection frames; event logs supply speech enqueue/playback records. The harnesses reject explicitly synthetic rows for empirical runs. Alert objects must be chosen in advance; the frozen manifest prevents post-hoc selection. No tuning on reported images is allowed.

B. Experiments A-E

Experiment A collects at least 500 camera frames per setting at 416, 640, and 832 input sizes on declared CPU/GPU/RAM/OS, Python, camera, audio, and TTS-backend configuration. It reports median and p95 for capture, inference, TTS synthesis, playback, and rendering. Experiment B evaluates 200-300 labeled COCO, LVIS, or own images with pycocotools or Ultralytics val, reporting precision, recall, mAP@0.5, and speed; its grid is {455, 20, 50, 80} prompts x {0.15, 0.25, 0.35}. Experiment C declares alert objects in advance, runs 5-10 real webcam sessions with TRINEXIS_EVENT_LOG, and replays the same detection frames through alert-first, confidence-first, and nearest-object-first orderings. It reports delivery rate and mean alert-to-speech delay exactly as observed even if alert-first helps less than hoped. Experiment D samples 5-10 languages with native or reliable bilingual raters on 10 announcements each, rated 1-5 for correctness and naturalness; only checked languages may be reported, and raters should listen to gTTS/Google Translate speech samples. Optional Experiment E uses a consented, ethics-approved 8-12 person within-subject design with three policies, counterbalanced order, and preregistered notice rate and time-to-notice outcomes. Positive, null, or negative alert-first effects are reportable.

The C harness is experiments/multi_session_replay.py. It rejects fewer than 5 or more than 10 sessions, explicitly synthetic rows, unmatched alert-manifest hashes, and missing speech-event logs. This report ships the harness and an unfilled session manifest; no session data are included. The optional E harness, experiments/user_study.py, generates only a blank counterbalanced worksheet and refuses to summarize without an institutional ethics approval identifier, documented consent, 8-12 real participants, all three conditions per participant, and numeric outcomes.

C. Preregistered Measurement Plan

TABLE V. PREREGISTERED MEASUREMENT PLAN (NO EMPIRICAL VALUES REPORTED)

Experiment	Primary endpoint	Prerequisite	Protocol status
A. Latency	Median/p95 by stage and input size	Declared hardware; 500+ frames per 416/640/832 setting	Preregistered
B. Detection	Precision/recall/mAP@0.5/speed	200-300 labeled images; separate tuning split; pycocotools or Ultralytics val	Preregistered
B. Grid	Twelve vocabulary/confidence cells	Frozen {455, 20, 50, 80} prompts x {0.15, 0.25, 0.35}	Preregistered
C. Alert replay	Delivery rate; mean alert-to-speech delay	Real /export_logs and speech events; predeclared alert manifest	Preregistered
D. Language	Mean correctness/naturalness	5-10 checked languages x 10 announcements; 1-5 ratings; listen to samples	Preregistered
E. User noticing	Notice rate; time-to-notice	Consent and institutional ethics approval; three-policy 8-12 person within-subject study	Preregistered (ethics-gated)

D. What Replay Does Not Establish

Experiment C measures alert delivery from logs, not whether a person notices a designated object faster or more often. A nearest-object-first comparison clarifies the ordering question but cannot substitute for a consented, ethics-approved user study with preregistered notice rate and time-to-notice outcomes. No approval, participant, or user benefit is claimed.

VI. PROTOCOL INTERPRETATION AND ETHICS

A. Interpretation

The alert-aware policy makes the spoken shortlist independent of whether a designated object happens to be among the highest-confidence detections. Interval throttling separates detector cadence from camera frame rate; time-based heatmap decay and the unitless distance index remove two frame-rate- and calibration-dependent ambiguities. The Flask route tests establish control behavior under mocked dependencies, not live deployment success. Published detector literature is not comparable to this webcam pipeline because its datasets, prompts, splits, and hardware protocols differ. The protocol is designed to estimate the alert-delivery effect without presupposing its sign or magnitude. Table I-B is bibliographic context only; it is not a TRINEXIS result and is not entered into Table V.

B. Ethical and Practical Implications

Camera-based interfaces can expose bystanders and sensitive environments. Privacy, consent, retention, and biometric-processing policies must be defined before any real-world or assistive-use study [20], [21]. The AGPL-3.0 license [24] and dependency-license notice clarify redistribution obligations but do not substitute for an ethics review. The system should not be described as assistive technology for blind or low-vision users until a consented study demonstrates benefit.

C. Language Coverage and TTS

Seventy-two language codes and 62 top-level speech resources are configured. Ten language codes lack a top-level template and use the English fallback, which is now disclosed by /get_languages and the UI. The current 72-code configuration is unverified; only languages actually rated may later be reported. gTTS uses Google Translate's speech service [9]. A checked-language study must use native or reliable bilingual raters, listen to sample audio, and report only the 5-10 languages actually rated. Missing templates may be added later only with reliable review; English fallback is documented rather than silently assumed.

VII. CONCLUSION

This report defines an alert-aware narration policy, implements it in a configurable open-vocabulary webcam system, and supplies a preregistered measurement protocol and reproducible software verification. The verified software properties are the ordering invariant, HTTP control behavior, language fallback, and failable harness self-checks. Empirical measurements are outside the scope of this protocol report; the protocol is the deliverable and is designed to report positive, null, or negative alert-first effects without presupposing the result. A final empirical article, immutable release, and Zenodo DOI should follow only after real data and author verification.

DECLARATIONS

A. Funding and Competing Interests

The author confirmed no external funding and no competing interests on 10 Nov 2026.

B. Author Contributions (CRediT)

Only roles actually performed are listed: Yug G. Lakhani—conceptualization, software, and writing—original draft. No methodology, investigation, formal analysis, validation, data curation, or review/editing role is claimed. No validation dataset or curated research data were used in this report.

C. AI-Tool Disclosure

Arena.ai Agent Mode, a text-to-text generative AI tool, was used for source auditing, harness/test scripting, figure generation, repository scripting, and manuscript formatting. This disclosure was checked against the current arXiv moderation policy, which requires significant text-to-text generative-AI use to be reported, places full responsibility on the named author, and does not permit an AI language tool to be listed as an author. The named author takes full responsibility for the manuscript. No institutional ethics approval is claimed.

D. Data and Code Availability

The prior immutable software release is available from GitHub release v0.3.0-standalone [23] under AGPL-3.0-only [24]; Ultralytics' AGPL-3.0 license is cited directly [22]. The current software snapshot contains this protocol report, three-policy experiment protocols, instrumentation, route tests, CI, and language-fallback UI; it has no final v1.0.0 tag and is not part of that release. Model weights are Git LFS pointers and are fetched and checked with weights/download_weights.py [10]. No labeled dataset, experimental log, or valid Zenodo DOI is claimed. A final immutable release and DOI are intentionally deferred until empirical results and a frozen version exist. Dependency licenses are documented in THIRD_PARTY_LICENSES.md. The author selected arXiv/institutional-report formatting; official current arXiv policies were read and recorded in paper/venue_guide_notes.md, and no mandatory venue template exists, so the generic single-column PDF and numeric citations are retained.

REFERENCES

[1] J. Redmon, S. Divvala, R. Girshick, and A. Farhadi, “You Only Look Once: Unified, Real-Time Object Detection,” in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), 2016, pp. 779–788, doi: 10.1109/CVPR.2016.91.

[2] T.-Y. Lin et al., “Microsoft COCO: Common Objects in Context,” in Proc. Eur. Conf. Comput. Vis. (ECCV), 2014, pp. 740–755.

[3] A. Radford et al., “Learning Transferable Visual Models From Natural Language Supervision,” in Proc. Int. Conf. Mach. Learn. (ICML), PMLR 139, 2021, pp. 8748–8763.

[4] S. Liu et al., “Grounding DINO: Marrying DINO with Grounded Pre-Training for Open-Set Object Detection,” in Computer Vision – ECCV 2024, LNCS vol. 15105, 2024, pp. 38–55, doi: 10.1007/978-3-031-72970-6_3.

[5] T. Cheng, L. Song, Y. Ge, W. Liu, X. Wang, and Y. Shan, “YOLO-World: Real-Time Open-Vocabulary Object Detection,” in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), 2024, pp. 16901–16911, doi: 10.1109/CVPR52733.2024.01599.

[6] Ultralytics, “YOLO-World documentation,” accessed Nov. 10, 2026. [Online]. Available: https://docs.ultralytics.com/models/yolo-world/

[7] Flask Project, “Flask documentation,” accessed Nov. 10, 2026. [Online]. Available: https://flask.palletsprojects.com/

[8] OpenCV, “Getting Started with Videos,” accessed Nov. 10, 2026. [Online]. Available: https://docs.opencv.org/4.13.0/dd/d43/tutorial_py_video_display.html

[9] P. N. Durette, “gTTS: Python library and CLI tool to interface with Google Translate's text-to-speech API,” GitHub repository, accessed Nov. 10, 2026. [Online]. Available: https://github.com/pndurette/gTTS

[10] Git LFS Project, “Git LFS Specification: The Pointer,” accessed Nov. 10, 2026. [Online]. Available: https://github.com/git-lfs/git-lfs/blob/main/docs/spec.md

[11] M. Minderer et al., “Simple Open-Vocabulary Object Detection,” in Computer Vision – ECCV 2022, LNCS, 2022, pp. 728–755, doi: 10.1007/978-3-031-20080-9_42.

[12] L. H. Li et al., “Grounded Language-Image Pre-Training,” in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), 2022, pp. 10955–10965, doi: 10.1109/CVPR52688.2022.01069.

[13] X. Zhou, R. Girdhar, A. Joulin, P. Krähenbühl, and I. Misra, “Detecting Twenty-Thousand Classes Using Image-Level Supervision,” in Computer Vision – ECCV 2022, LNCS vol. 13669, 2022, pp. 350–368, doi: 10.1007/978-3-031-20077-9_21.

[14] A. Wang, L. Liu, H. Chen, Z. Lin, J. Han, and G. Ding, “YOLOE: Real-Time Seeing Anything,” arXiv:2503.07465, 2025, doi: 10.48550/arXiv.2503.07465.

[15] Ultralytics, “Ultralytics YOLO,” GitHub repository, accessed Nov. 10, 2026. [Online]. Available: https://github.com/ultralytics/ultralytics

[16] M. Avila, K. Wolf, A. Brock, and N. Henze, “Remote Assistance for Blind Users in Daily Life: A Survey about Be My Eyes,” in Proc. 9th ACM Int. Conf. Pervasive Technol. Related Assistive Environ. (PETRA), 2016, Article 85, 2 pages, doi: 10.1145/2910674.2935839.

[17] Microsoft, “Seeing AI,” accessed Nov. 10, 2026. [Online]. Available: https://www.seeingai.com/

[18] R. E. Gonzalez Penuela, J. Collins, C. L. Bennett, and S. Azenkot, “Investigating Use Cases of AI-Powered Scene Description Applications for Blind and Low Vision People,” in Proc. CHI Conf. Human Factors Comput. Syst. (CHI), 2024, Article 901, pp. 1–21, doi: 10.1145/3613904.3642211.

[19] D. K. Alqahtani, M. A. Cheema, M. A. Rodriguez, and A. N. Toosi, “A Comprehensive Evaluation of Deep Learning Object Detection Models on Heterogeneous Edge Devices,” arXiv:2409.16808, v1 2024, revised 2026, doi: 10.48550/arXiv.2409.16808.

[20] I. D. Raji, T. Gebru, M. Mitchell, J. Buolamwini, J. Lee, and R. Denton, “Saving Face: Investigating the Ethical Concerns of Facial Recognition Auditing,” in Proc. AAAI/ACM Conf. AI, Ethics, Soc. (AIES), 2020, pp. 145–151, doi: 10.1145/3375627.3375820.

[21] M. R. Hasan, R. Guest, and F. Deravi, “Presentation-level Privacy Protection Techniques for Automated Face Recognition—A Survey,” ACM Comput. Surv., vol. 55, no. 13s, Article 286, pp. 1–27, 2023, doi: 10.1145/3583135.

[22] Ultralytics, “LICENSE,” GitHub repository, AGPL-3.0, accessed Nov. 10, 2026. [Online]. Available: https://github.com/ultralytics/ultralytics/blob/main/LICENSE

[23] Unusualyug, “tech_yolo release v0.3.0-standalone,” GitHub, 2026. [Online]. Available: https://github.com/Unusualyug/tech_yolo/releases/tag/v0.3.0-standalone

[24] Free Software Foundation, “GNU Affero General Public License, Version 3,” 2007. [Online]. Available: https://www.gnu.org/licenses/agpl-3.0.txt

APPENDIX A. REPRODUCTION COMMANDS

The commands below reproduce the current untagged snapshot from checked-in scripts. Pin the exact commit hash printed by git rev-parse before archiving; no final v1.0.0 tag exists.

```
git clone https://github.com/Unusualyug/tech_yolo.git
cd tech_yolo
git rev-parse HEAD > reproduction_commit.txt
python3 -m pip install -r requirements-ci.txt
python3 -m unittest discover -s tests -v
python3 -m unittest tests.test_synthetic_regression -v
python3 scripts/report_test_counts.py
python3 experiments/latency_benchmark.py --self-check
python3 experiments/detection_eval.py --self-check
python3 experiments/vocab_confidence_grid.py --self-check
python3 experiments/alert_replay.py --self-check
python3 experiments/language_eval.py --self-check
python3 experiments/multi_session_replay.py --self-check
python3 experiments/user_study.py --self-check
python3 scripts/live_smoke_test.py --self-check
python3 scripts/check_arxiv_metadata.py --check
python3 scripts/final_release_checklist.py --self-check
python3 scripts/verify_no_fabricated_results.py
# Live studies only; CI does not install these or open hardware:
python3 scripts/live_smoke_test.py --check-prereqs
python3 scripts/live_smoke_test.py --verify-evidence
python3 -m pip install -r requirements.txt
python3 weights/download_weights.py --fetch --verify
python3 -m pip install -r paper/requirements-paper.txt
python3 paper/make_updated_figures.py
python3 paper/build_updated_manuscript.py
python3 paper/audit_updated_repository.py
```

APPENDIX B. PRINCIPAL ARTIFACTS

- paper/tech_yolo_updated_research_paper.pdf, .docx, and .md: protocol and software-verification report with no empirical measurements.
- paper/artifacts/alert_selection_audit.json: tests/ unit-test artifact for the seeded synthetic alert-ordering regression.
- paper/artifacts/test_summary.json: route/policy/source-contract counts and exact CI report phrase.
- paper/artifacts/fig1_system_architecture_updated.{png,svg,pdf} and fig2_implementation_verification.{png,svg,pdf}: figure exports.
- paper/artifacts/updated_repository_audit.json: machine-readable repository/test summary.
- experiments/README.md and experiments/RESULTS_TEMPLATE.md: preregistered measurement protocols and unfilled result templates.
- experiments/latency_benchmark.py, detection_eval.py, vocab_confidence_grid.py, alert_replay.py, language_eval.py, and common.py: runnable harnesses.
- tests/test_routes.py, tests/route_test_support.py, and tests/test_synthetic_regression.py: real Flask route tests and the synthetic unit test.
- .github/workflows/ci.yml, requirements-ci.txt, scripts/report_test_counts.py, and scripts/verify_no_fabricated_results.py: CI and evidence-boundary checks.
- weights/download_weights.py and weights/weights_checksums.sha256: Git LFS pointer parser and SHA-256 manifest.

- zenodo.json and ZENODO.md: prepared DOI metadata; no DOI minted.
- paper/reference_verification.md: per-reference DOI/publisher verification log with all 24 rows ticked after recheck.
- paper/venue_guide_notes.md, experiments/LIVE_SMOKE_TEST.md, experiments/SPOKEN_IO_EXAMPLE.template.md, experiments/USER_STUDY_PROTOCOL.md, experiments/ethics_inquiry_receipt.md, experiments/session_manifest.template.json, experiments/user_study_worksheet.template.csv, experiments/multi_session_replay.py, experiments/user_study.py, scripts/live_smoke_test.py, scripts/check_arxiv_metadata.py, and scripts/final_release_checklist.py: venue, live-evidence, three-policy, ethics, and final-release preparation artifacts.
- trinexis_core.py, trinexis_telemetry.py, trinexis_language.py, CITATION.cff, codemeta.json, README.md, LICENSE, requirements.txt, and THIRD_PARTY_LICENSES.md: repository metadata and software artifacts.