

# Depth-first search

## COMS20017 (Algorithms and Data)

John Lapinskas, University of Bristol

# Path-finding

One of the most basic problems in graph theory: Given a graph  $G$  and two vertices  $x, y \in V(G)$ , is there a path from  $x$  to  $y$ ?

# Path-finding

One of the most basic problems in graph theory: Given a graph  $G$  and two vertices  $x, y \in V(G)$ , is there a path from  $x$  to  $y$ ?

E.g. can an enemy attack the base without breaking down a wall?



# Path-finding

One of the most basic problems in graph theory: Given a graph  $G$  and two vertices  $x, y \in V(G)$ , is there a path from  $x$  to  $y$ ?

E.g. can an enemy attack the base without breaking down a wall?



Often we want to know the **shortest** path from  $x$  to  $y$  — see next video!

# Component-finding

In fact, it's better to ask for something more.

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .


**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

# Component-finding

In fact, it's better to ask for something more.

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .




**Input:**  $v_1$

# Component-finding

In fact, it's better to ask for something more.

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .



**Input:**  $v_1$


**Output:**  $[v_1, v_2, v_3, v_5, v_6, v_7, v_9, v_{10}, v_{11}, v_{12}]$

# Component-finding

In fact, it's better to ask for something more.

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .



**Input:**  $v_6$




# Component-finding

In fact, it's better to ask for something more.

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .



**Input:**  $v_6$


**Output:**  $[v_1, v_2, v_3, v_5, v_6, v_7, v_9, v_{10}, v_{11}, v_{12}]$

# Component-finding

In fact, it's better to ask for something more.

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .




# Component-finding

In fact, it's better to ask for something more.

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .



**Input:**  $v_4$


**Output:**  $[v_4, v_8]$

# Component-finding

In fact, it's better to ask for something more.

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .



**Input:**  $v_4$

**Output:**  $[v_4, v_8]$


In other words, we check whether there is a path from  $x$  to  $y$  for **all**  $y$ . Turns out the worst-case running time is the same either way!

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$

**Output:**  $[v_1, v_5]$




## Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$

**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}]$




# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$

**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7]$




## Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3]$

## Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$

**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$




# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$

**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$




# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.



**Input:**  $G, v_1$


**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

# Depth-first search: The idea

**Input:** A graph  $G$  and a vertex  $x \in V(G)$ .

**Output:** A list of all vertices in the component of  $G$  containing  $x$ .

**Idea:** Think of the graph as like a **maze**: explore greedily until everything looks familiar, then backtrack.




**Input:**  $G, v_1$

**Output:**  $[v_1, v_5, v_9, v_{10}, v_{11}, v_{12}, v_6, v_7, v_3, v_2]$

The slick way to implement this is to use recursion.

## Pseudocode and example



**Input:**  $v_1$

### Algorithm: DFS

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .

2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .

### 3 Procedure helper( $v_i$ )

```

4 |   if explored[i] = 0 then

```

5	Set $\text{explored}[i] \leftarrow 1$ .
---	---

6	<b>for</b> $v_j$ <i>adjacent to</i> $v_i$ <b>do</b>
---	---

7	if explored[j] = 0 then
---	-------------------------

8				Call helper( $v_i$ ).
---	--	--	--	-----------------------


```

9 Call helper( $v$ ).

```

10 Return  $[v_i: \text{explored}[i] = 1]$  (in some order).

## Pseudocode and example



**Input:**  $v_1$

### Algorithm: DFS

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .

2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .

### 3 Procedure helper( $v_i$ )

```

4 |   if explored[i] = 0 then

```

5	Set $\text{explored}[i] \leftarrow 1$ .
---	---

6	<b>for</b> $v_j$ <i>adjacent to</i> $v_i$ <b>do</b>
---	---

7		<b>if</b> explored[j] = 0 <b>then</b>
---	--	---------------------------------------

8				Call helper( $v_i$ ).
---	--	--	--	-----------------------

```

9 Call helper( $v$ ).


```

```

10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

```

# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS

---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .


**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  *adjacent to*  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---



# Pseudocode and example



Input:  $v_1$

---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
    - 7             **if**  $\text{explored}[j] = 0$  **then**
    - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



Input:  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



Input:  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



Input:  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
      - 5         Set  $\text{explored}[i] \leftarrow 1$ .
      - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
        - 7             **if**  $\text{explored}[j] = 0$  **then**
          - 8                 Call  $\text{helper}(v_j)$ .
    - 9     Call  $\text{helper}(v)$ .
    - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-



# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
      - 5         Set  $\text{explored}[i] \leftarrow 1$ .
      - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
        - 7             **if**  $\text{explored}[j] = 0$  **then**
          - 8                 Call  $\text{helper}(v_j)$ .
    - 9     Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



Input:  $v_1$

---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
    - 7             **if**  $\text{explored}[j] = 0$  **then**
    - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
      - 5         Set  $\text{explored}[i] \leftarrow 1$ .
      - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
        - 7             **if**  $\text{explored}[j] = 0$  **then**
          - 8                 Call  $\text{helper}(v_j)$ .
    - 9     Call  $\text{helper}(v)$ .
    - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



Input:  $v_1$

---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
    - 7             **if**  $\text{explored}[j] = 0$  **then**
    - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

## Pseudocode and example



**Input:**  $V_1$

### Algorithm: DFS

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .

2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .

### 3 Procedure helper( $v_i$ )

```

4 |   if explored[i] = 0 then

```

5	Set $\text{explored}[i] \leftarrow 1$ .
---	---

6	<b>for</b> $v_j$ <i>adjacent to</i> $v_i$ <b>do</b>
---	---

7		<b>if</b> explored[j] = 0 <b>then</b>
---	--	---------------------------------------

8				Call helper( $v_i$ ).
---	--	--	--	-----------------------


```
9 Call helper( $v$ ).
```

```

10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

```

# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
    - 7             **if**  $\text{explored}[j] = 0$  **then**
    - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



---

## Algorithm: DFS

---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .


**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---



# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
      - 5         Set  $\text{explored}[i] \leftarrow 1$ .
      - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
        - 7             **if**  $\text{explored}[j] = 0$  **then**
          - 8                 Call  $\text{helper}(v_j)$ .
    - 9     Call  $\text{helper}(v)$ .
    - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



Input:  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
      - 5         Set  $\text{explored}[i] \leftarrow 1$ .
      - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
        - 7             **if**  $\text{explored}[j] = 0$  **then**
          - 8                 Call  $\text{helper}(v_j)$ .
    - 9     Call  $\text{helper}(v)$ .
    - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
      - 5         Set  $\text{explored}[i] \leftarrow 1$ .
      - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
        - 7             **if**  $\text{explored}[j] = 0$  **then**
          - 8                 Call  $\text{helper}(v_j)$ .
    - 9     Call  $\text{helper}(v)$ .
    - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
      - 5         Set  $\text{explored}[i] \leftarrow 1$ .
      - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
        - 7             **if**  $\text{explored}[j] = 0$  **then**
          - 8                 Call  $\text{helper}(v_j)$ .
    - 9     Call  $\text{helper}(v)$ .
    - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-



# Pseudocode and example



Input:  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
      - 5         Set  $\text{explored}[i] \leftarrow 1$ .
      - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
        - 7             **if**  $\text{explored}[j] = 0$  **then**
          - 8                 Call  $\text{helper}(v_j)$ .
    - 9     Call  $\text{helper}(v)$ .
    - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS

---


**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---

# Pseudocode and example



Input:  $v_1$

---

## Algorithm: DFS

---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .


**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
- 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
- 3 **Procedure**  $\text{helper}(v_i)$ 
  - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
      - 7             **if**  $\text{explored}[j] = 0$  **then**
        - 8                 Call  $\text{helper}(v_j)$ .
  - 9     Call  $\text{helper}(v)$ .
  - 10    Return  $[v_i : \text{explored}[i] = 1]$  (in some order).

---



# Pseudocode and example



---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
    - 7             **if**  $\text{explored}[j] = 0$  **then**
    - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
    - 7             **if**  $\text{explored}[j] = 0$  **then**
    - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
    - 7             **if**  $\text{explored}[j] = 0$  **then**
    - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



---

## Algorithm: DFS


---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .

**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  adjacent to  $v_i$  **do**
    - 7             **if**  $\text{explored}[j] = 0$  **then**
    - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
-

# Pseudocode and example



**Input:**  $v_1$

---

## Algorithm: DFS

---

**Input** : Graph  $G = (V, E)$ , vertex  $v \in V$ .


**Output** : List of vertices in  $v$ 's component.

- 1 Number the vertices of  $G$  as  $v_1, \dots, v_n$ .
  - 2 Let  $\text{explored}[i] \leftarrow 0$  for all  $i \in [n]$ .
  - 3 **Procedure**  $\text{helper}(v_i)$ 
    - 4     **if**  $\text{explored}[i] = 0$  **then**
    - 5         Set  $\text{explored}[i] \leftarrow 1$ .
    - 6         **for**  $v_j$  *adjacent to*  $v_i$  **do**
    - 7             **if**  $\text{explored}[j] = 0$  **then**
    - 8                 Call  $\text{helper}(v_j)$ .
  - 9 Call  $\text{helper}(v)$ .
  - 10 Return  $[v_i : \text{explored}[i] = 1]$  (in some order).
- 


We assume  $G$  is in adjacency list form.

**Time analysis:** In total there are  $\sum_{v \in V} d(v) = O(|E|)$  calls to  $\text{helper}$  (each vertex only runs lines 5–7 once), and there is  $O(1)$  time between calls. So the running time is  $O(|V| + |E|)$ .

## Correctness I: Output is contained in $v$ 's component $C$




## Correctness I: Output is contained in $v$ 's component $C$



**Invariant:** “When `helper` is called, if `explored[i] = 1` then  $v_i \in V(C)$ .”

## Correctness I: Output is contained in $v$ 's component $C$




**Invariant:** “When helper is called, if  $\text{explored}[i] = 1$  then  $v_i \in V(C)$ .”

Proof by induction. Vacuously true for initial call and second call. ✓




## Correctness I: Output is contained in $v$ 's component $C$



**Invariant:** “When `helper` is called, if `explored[i] = 1` then  $v_i \in V(C)$ .”

Proof by induction. Vacuously true for initial call and second call. ✓

## Correctness I: Output is contained in $v$ 's component $C$




**Invariant:** “When `helper` is called, if `explored[i] = 1` then  $v_i \in V(C)$ .”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper( $v_j$ )` from `helper( $v_i$ )`.  
If  $v_j$  is already explored, we're done.

## Correctness I: Output is contained in $v$ 's component $C$




**Invariant:** “When `helper` is called, if `explored[i] = 1` then  $v_i \in V(C)$ .”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper( $v_j$ )` from `helper( $v_i$ )`.  
If  $v_j$  is already explored, we're done.

# Correctness I: Output is contained in $v$ 's component $C$




**Invariant:** “When `helper` is called, if `explored[i] = 1` then  $v_i \in V(C)$ .”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper( $v_j$ )` from `helper( $v_i$ )`.  
If  $v_j$  is already explored, we’re done.

# Correctness I: Output is contained in $v$ 's component $C$




**Invariant:** “When `helper` is called, if `explored[i] = 1` then  $v_i \in V(C)$ .”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper( $v_j$ )` from `helper( $v_i$ )`. If  $v_j$  is already explored, we’re done. If not, we must show  $v_j \in V(C)$ .

## Correctness I: Output is contained in $v$ 's component $C$




**Invariant:** “When helper is called, if  $\text{explored}[i] = 1$  then  $v_i \in V(C)$ .”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper( $v_j$ )` from `helper( $v_i$ )`. If  $v_j$  is already explored, we're done. If not, we must show  $v_j \in V(C)$ .

## Correctness I: Output is contained in $v$ 's component $C$




**Invariant:** “When `helper` is called, if `explored[i] = 1` then  $v_i \in V(C)$ .”

Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper( $v_j$ )` from `helper( $v_i$ )`.  
If  $v_j$  is already explored, we’re done. If not, we must show  $v_j \in V(C)$ .

Since we called from `helper( $v_i$ )`,  $\{v_i, v_j\} \in E$  and  $v_i$  is explored.

Correctness I: Output is contained in  $v$ 's component  $C$



**Invariant:** “When helper is called, if  $\text{explored}[i] = 1$  then  $v_i \in V(C)$ .”


Proof by induction. Vacuously true for initial call and second call. ✓

Suppose it holds at the start of some call `helper( $v_j$ )` from `helper( $v_i$ )`. If  $v_j$  is already explored, we're done. If not, we must show  $v_j \in V(C)$ .

Since we called from `helper( $v_i$ )`,  $\{v_i, v_j\} \in E$  and  $v_i$  is explored. By induction there is a path  $P$  from  $v$  to  $v_i$ . Then  $Pv_iv_j$  is a walk from  $v$  to  $v_j$ , which contains a path, so  $v_j \in V(C)$ .  $\square$




## Correctness II: Output contains $v$ 's component $C$




Let  $w \in V(C)$ . Then there is a path  $P = x_1 \dots x_t$  from  $v$  to  $w$ .

## Correctness II: Output contains $v$ 's component $C$



Let  $w \in V(C)$ . Then there is a path  $P = x_1 \dots x_t$  from  $v$  to  $w$ .

## Correctness II: Output contains $v$ 's component $C$




Let  $w \in V(C)$ . Then there is a path  $P = x_1 \dots x_t$  from  $v$  to  $w$ .

**Claim:** Every vertex in  $P$  is explored.

**Proof by induction:** We prove  $x_1, \dots, x_i$  are explored for all  $i \leq t$ .

$x_1$  is explored.

## Correctness II: Output contains $v$ 's component $C$



Let  $w \in V(C)$ . Then there is a path  $P = x_1 \dots x_t$  from  $v$  to  $w$ .


**Claim:** Every vertex in  $P$  is explored.

**Proof by induction:** We prove  $x_1, \dots, x_i$  are explored for all  $i \leq t$ .

$x_1$  is explored.



## Correctness II: Output contains $v$ 's component $C$



Let  $w \in V(C)$ . Then there is a path  $P = x_1 \dots x_t$  from  $v$  to  $w$ .


**Claim:** Every vertex in  $P$  is explored.

**Proof by induction:** We prove  $x_1, \dots, x_i$  are explored for all  $i \leq t$ .

$x_1$  is explored. ✓

If  $x_i$  is explored, then  $\text{helper}(x_{i+1})$  will be called from  $\text{helper}(x_i)$ , so  $x_{i+1}$  will also be explored (either then or earlier).

## Correctness II: Output contains $v$ 's component $C$



Let  $w \in V(C)$ . Then there is a path  $P = x_1 \dots x_t$  from  $v$  to  $w$ .

**Claim:** Every vertex in  $P$  is explored.


**Proof by induction:** We prove  $x_1, \dots, x_i$  are explored for all  $i \leq t$ .

$x_1$  is explored. ✓

If  $x_i$  is explored, then  $\text{helper}(x_{i+1})$  will be called from  $\text{helper}(x_i)$ , so  $x_{i+1}$  will also be explored (either then or earlier).



## Correctness II: Output contains $v$ 's component $C$



Let  $w \in V(C)$ . Then there is a path  $P = x_1 \dots x_t$  from  $v$  to  $w$ .

**Claim:** Every vertex in  $P$  is explored.

**Proof by induction:** We prove  $x_1, \dots, x_i$  are explored for all  $i \leq t$ .

$x_1$  is explored.

✓


If  $x_i$  is explored, then  $\text{helper}(x_{i+1})$  will be called from  $\text{helper}(x_i)$ , so  $x_{i+1}$  will also be explored (either then or earlier).

7



# Depth-first search trees


Consider the subgraph formed by the edges **traversed** in DFS:



This is an example of a **DFS tree** rooted at  $v$ .

# Depth-first search trees

Consider the subgraph formed by the edges **traversed** in DFS:



This is an example of a **DFS tree** rooted at  $v$ .


**Definition:** A **DFS tree**  $T$  of  $G$  is a rooted tree satisfying:

- $V(T)$  is the vertex set of a component of  $G$ ;
- If  $\{x, y\} \in E(G)$ , then  $x$  is an ancestor of  $y$  in  $T$  or vice versa.

**Theorem:** DFS always gives a DFS tree. (See problem sheet.)

# Depth-first search trees

Consider the subgraph formed by the edges **traversed** in DFS:



This is an example of a **DFS tree** rooted at  $v$ .

**Definition:** A **DFS tree**  $T$  of  $G$  is a rooted tree satisfying:


- $V(T)$  is the vertex set of a component of  $G$ ;
- If  $\{x, y\} \in E(G)$ , then  $x$  is an ancestor of  $y$  in  $T$  or vice versa.

**Theorem:** DFS always gives a DFS tree. (See problem sheet.)

DFS trees can be independently useful! (See problem sheet.)

# Depth-first search trees

Consider the subgraph formed by the edges **traversed** in DFS:



This is an example of a **DFS tree** rooted at  $v$ .

**Definition:** A **DFS tree**  $T$  of  $G$  is a rooted tree satisfying:

- $V(T)$  is the vertex set of a component of  $G$ ;
- If  $\{x, y\} \in E(G)$ , then  $x$  is an ancestor of  $y$  in  $T$  or vice versa.

**Theorem:** DFS always gives a DFS tree. (See problem sheet.)

DFS trees can be independently useful! (See problem sheet.)

Depth-first search works for directed graphs too, in exactly the same way. But paths **between**  $v$  and  $w$  are replaced by paths **from**  $v$  **to**  $w$ .