



This document describes the files in the skin directories changed from 8.1.0 to 8.1.1 as well as what has been changed within the skin files. It is meant to be used when planning for the best way to carry your skin-level customizations from a previous version of WebVoyage forward to version 8.1.1. If you have not altered a file, you can copy the new 8.1.1 version over the existing file in whatever skin you would like. If you have customized a file, we recommend that you review the changes below but recommit your customizations to the *new* file. Test your skin after each customization is reapplied to the new files.

If you are upgrading from a version of Voyager prior to 8.0.0, please note that there is not a Changed Skin Files document. Since the process for upgrading to Voyager 8.0.0 requires that you begin with the Voyager 8.0.0 version of all skin files, no list of changed files is necessary.

Please see the Voyager 8.1.1 Release Notes for specific bug fixes that affect skin files. The Release Notes can be found on the Documentation Center under Documentation Center under Home > Documentation Center > Ex Libris Documentation Center > Voyager > Upgrade Release Planning > 8.1.1.

## Changed skin files from 8.1.0 to 8.1.1

The following skin files changed in 8.1.1.

*The files below are all in the directory, /m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\_default/ (e.g. the first one is /m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\_default/htdocs/help/index.html):*

```
.../htdocs/help/index.html  
.../webvoyage.properties.tml  
.../webvoyage.properties  
.../xsl/contentLayout/cl_exportRecordDialog.xsl  
.../xsl/contentLayout/cl_printRecordDialog.xsl  
.../xsl/contentLayout/configs/displaycfg.xml  
.../xsl/contentLayout/configs/emailcfg.xml  
.../xsl/contentLayout/configs/print/briefRecordConfig.xml  
.../xsl/contentLayout/configs/print/fullRecordConfig.xml  
.../xsl/contentLayout/display/display_text.xsl  
.../xsl/contentLayout/display/display.xsl  
.../xsl/resultsMyList.xsl  
.../xsl/resultsTitles.xsl
```

Also:

/m1/voyager/xxxdb/tomcat/vxws/context/vxws/ui/exl\_default/vxws.properties  
/m1/voyager/xxxdb/tomcat/vxws/context/vxws/ui/exl\_default/vxws.properties.tml

The upgrade to 8.1.1 will overwrite your exl\_default directory with all of the new files listed above, as well as the default versions of all other WebVoyage skin files.

# Skin file content changes 8.1.0 to 8.1.1

Below contains exactly what has been changed in each exl\_default changed skin file for 8.1.1.

[/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\\_default/htdocs/help/index.html](/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl_default/htdocs/help/index.html)

#### Action: Add the following snippet at starting at line 151 ####  
++++++ Snippet Start +++++++

++++++ Snippet End +++++++

#### Action: Change lines 147 to 149 to the following snippet ####  
++++++ Snippet Start +++++++

    </div>  
  </body>  
  </html>  
++++++ Snippet End +++++++

#### Action: Change line 145 to the following snippet ####

++++++ Snippet Start +++++++

    </div>

++++++ Snippet End +++++++

#### Action: Change lines 142 to 143 to the following snippet ####

++++++ Snippet Start +++++++

    <span id="copySymbol">&copy;</span> <span>2011 Ex Libris Group. All rights  
    reserved.</span>

++++++ Snippet End +++++++

#### Action: Change lines 137 to 139 to the following snippet ####

++++++ Snippet Start +++++++

    <!-- end mainContent -->  
    </div>

++++++ Snippet End +++++++

#### Action: Add the following snippet at starting at line 134 ####

++++++ Snippet Start +++++++

    <li>  
        <a href="patronRequest.html">Request Selection</a>  
    </li>  
    <li>  
        <a href="hdlrcl.html">Hold/Recall Request</a>  
    </li>  
    <li>  
        <a href="callslip.html">Call Slip Request</a>  
    </li>  
    <li>  
        <a href="purchase.html">Purchase Request</a>  
    </li>

++++++ Snippet End +++++++

#### Action: Change lines 129 to 131 to the following snippet ####

++++++ Snippet Start +++++++

    </ul>  
    <h2>Requesting Materials</h2>  
    <ul>

++++++ Snippet End +++++++

```

##### Action: Change lines 116 to 119 to the following snippet #####
++++++ Snippet Start ++++++
<li>
    <a href="editPreferences.html">Personal Search Preferences</a>
</li>
<!-- remove this, if your library does not use PINs -->
++++++ Snippet End ++++++

```

```

##### Action: Change lines 69 to 70 to the following snippet #####
++++++ Snippet Start ++++++
<!-- remove this entry, if you haven't set up remote databases for searching -->
<li>
++++++ Snippet End ++++++

```

```

##### Action: Change line 65 to the following snippet #####
++++++ Snippet Start ++++++
<!-- remove this entry, if you haven't set up remote databases for searching -->
++++++ Snippet End ++++++

```

```

##### Action: Change line 60 to the following snippet #####
++++++ Snippet Start ++++++
-->
++++++ Snippet End ++++++

```

```

##### Action: Change line 56 to the following snippet #####
++++++ Snippet Start ++++++
<!--
++++++ Snippet End ++++++

```

```

##### Action: Change lines 51 to 52 to the following snippet #####
++++++ Snippet Start ++++++
<!-- only one course reserve navigation type can be active at a time -->
<!-- remove one of these entries bases upon the settings in webvoyage.properties -->
++++++ Snippet End ++++++

```

```

##### Action: Change lines 17 to 18 to the following snippet #####
++++++ Snippet Start ++++++
<title>WebVoyage Help Contents</title>
</head>
++++++ Snippet End ++++++

```

```

##### Action: Change line 14 to the following snippet #####
++++++ Snippet Start ++++++
<link rel="stylesheet" href="../css/header.css" type="text/css">
++++++ Snippet End ++++++

```

```

##### Action: Change line 5 to the following snippet #####
++++++ Snippet Start ++++++
#(c) Copyright 2007-2012 Ex Libris (USA) Inc.
++++++ Snippet End ++++++

```

```

##### Action: Change line 2 to the following snippet #####
++++++ Snippet Start ++++++
<!--
++++++ Snippet End ++++++

```

[/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\\_default/webvoyage.properties](/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl_default/webvoyage.properties)

#### Action: Add the following snippet at starting at line 2174 ####

++++++ Snippet Start ++++++

++++++ Snippet End ++++++

#### Action: Change lines 1630 to 1632 to the following snippet ####

++++++ Snippet Start ++++++

page.myAccount.chargedItem.item.status.2=Charged (Requests: \\c)

page.myAccount.chargedItem.item.status.3=Renewed (Requests: \\c)

page.myAccount.chargedItem.item.status.4=Overdue (Requests: \\c)

++++++ Snippet End ++++++

#### Action: Change line 1572 to the following snippet ####

++++++ Snippet Start ++++++

page.myAccount.borrowingBlocks.item.reason.address\_invalid\_patron=The address in your patron record is invalid.

++++++ Snippet End ++++++

#### Action: Change line 3 to the following snippet ####

++++++ Snippet Start ++++++

#(c)# Copyright 2007-2012 Ex Libris Group

++++++ Snippet End ++++++

[/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\\_default/webvoyage.properties.tml](/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl_default/webvoyage.properties.tml)

#### Action: Add the following snippet at starting at line 2174 ####

++++++ Snippet Start ++++++

++++++ Snippet End ++++++

#### Action: Change lines 1630 to 1632 to the following snippet ####

++++++ Snippet Start ++++++

page.myAccount.chargedItem.item.status.2=Charged (Requests: \\c)

page.myAccount.chargedItem.item.status.3=Renewed (Requests: \\c)

page.myAccount.chargedItem.item.status.4=Overdue (Requests: \\c)

++++++ Snippet End ++++++

#### Action: Change line 1572 to the following snippet ####

++++++ Snippet Start ++++++

page.myAccount.borrowingBlocks.item.reason.address\_invalid\_patron=The address in your patron record is invalid.

++++++ Snippet End ++++++

#### Action: Change line 3 to the following snippet ####

++++++ Snippet Start ++++++

#(c)# Copyright 2007-2012 Ex Libris Group

++++++ Snippet End ++++++

[/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\\_default/xsl/contentLayout/cl\\_exportRecordDialog.xsl](/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl_default/xsl/contentLayout/cl_exportRecordDialog.xsl)

#### Action: Add the following snippet at starting at line 74 ####

++++++ Snippet Start ++++++

++++++ Snippet End ++++++

#### Action: Add the following snippet at starting at line 73 ####

++++++ Snippet Start ++++++

```

<xsl:template name="cl_exportRecordDialog.exportRecordDialogForm">
  <xsl:for-each select="/page:page/page:pageBody" >
    <form id="exportRecordDialogForm" method="POST" action="exportRecord.do" class="formBackground">
>
  <div class="formLabel" >
    <span class="formLabel"><xsl:value-of
select="//page:element[@nameId='page.exportDialog.export.instructions']/page:label" /></span>
  </div>
  <br/>
  <xsl:call-template name="contentLayout.cl_commonDialog.hiddenSearchOrBib" />
  <div class="formLabel" >
    <xsl:call-template name="buildFormDropDown">
      <xsl:with-param name="eleName" select=" 'format'" />
    </xsl:call-template>
  </div>
  <br/>
  <br/>
  <xsl:call-template name="renderButtons">
    <xsl:with-param name="submitBtn" select="page.exportDialog.export.button"/>
    <xsl:with-param name="submitBtnName" select="butExport"/>
    <xsl:with-param name="cancelBtn" select="page.return.button"/>
    <xsl:with-param name="cancelBtnName" select="butCancel"/>
  </xsl:call-template>
  <br/>
<xsl:if test="page:element[@nameId='recordsGroup']">
  <div class="selectedRecords">
    <xsl:for-each select="page:element[@nameId='recordsGroup']/page:element" >
      <xsl:call-template name="display_dialogDisplay_buildRecord"/>
    </xsl:for-each>
    <div class="moreRecords">
      <xsl:for-each select="page:element[@nameId='page.exportDialog.export.moreRecords']" >
        <xsl:value-of select="page:label" />
      </xsl:for-each>
    </div>
  </div>
</xsl:if>
</form>
<br/>
</xsl:for-each>
</xsl:template>

```

++++++ Snippet End ++++++

#### Action: Delete lines 33 - 72 ####

#### Action: Change lines 22 to 30 to the following snippet ####

++++++ Snippet Start ++++++

```

exclude-result-prefixes="xsi fo page"
xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
xmlns:page="http://www.exlibrisgroup.com/voyager/webvoyage/page"
xmlns:fo="http://www.w3.org/1999/XSL/Format">

<!-- External imports -->
<xsl:include href=".//cl_commonDialog.xsl"/>
<xsl:include href=".//display/dialog_display.xsl"/>

```

++++++ Snippet End ++++++

#### Action: Change line 13 to the following snippet ####

++++++ Snippet Start ++++++

\*\* Product : WebVoyage  
++++++ Snippet End ++++++

#### Action: Change line 6 to the following snippet ####  
++++++ Snippet Start ++++++  
#(c)# Copyright 2007-2012 Ex Libris (USA) Inc.  
++++++ Snippet End ++++++

[/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\\_default/xsl/contentLayout/cl\\_printRecor dDialog.xsl](/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl_default/xsl/contentLayout/cl_printRecor dDialog.xsl)

#### Action: Add the following snippet at starting at line 73 ####  
++++++ Snippet Start ++++++

++++++ Snippet End ++++++

#### Action: Change lines 71 to 72 to the following snippet ####  
++++++ Snippet Start ++++++

++++++ Snippet End ++++++

#### Action: Change lines 56 to 65 to the following snippet ####  
++++++ Snippet Start ++++++

```
<div class="selectedRecords">
    <xsl:for-each select="page:element[@nameId='recordsGroup']/page:element" >
        <xsl:call-template name="display_dialogDisplay_buildRecord"/>
    </xsl:for-each>
    <div class="moreRecords">
        <xsl:for-each select="page:element[@nameId='page.printDialog.print.moreRecords']" >
            <xsl:value-of select="page:label" />
        </xsl:for-each>
    </div>
</div>
```

++++++ Snippet End ++++++

#### Action: Change line 40 to the following snippet ####  
++++++ Snippet Start ++++++

++++++ Snippet End ++++++

#### Action: Change line 37 to the following snippet ####

```
++++++ Snippet Start ++++++
<form id="printRecordDialogForm" method="POST" action="printResults.do" class="formBackground" >
++++++ Snippet End ++++++
```

#### Action: Change line 33 to the following snippet ####  
++++++ Snippet Start ++++++

++++++ Snippet End ++++++

#### Action: Change line 30 to the following snippet ####  
++++++ Snippet Start ++++++

++++++ Snippet End ++++++

#### Action: Change line 26 to the following snippet ####  
++++++ Snippet Start ++++++

```
++++++ Snippet End ++++++
#### Action: Change line 23 to the following snippet ####
++++++ Snippet Start ++++++
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
++++++ Snippet End ++++++
#### Action: Change line 13 to the following snippet ####
++++++ Snippet Start ++++++
**      Product : WebVoyage
++++++ Snippet End ++++++
#### Action: Change line 6 to the following snippet ####
++++++ Snippet Start ++++++
#(c)#    Copyright 2007-2012 Ex Libris (USA) Inc.
++++++ Snippet End ++++++
```

[/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\\_default/xsl/contentLayout/configs/displaycfg.xml](/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl_default/xsl/contentLayout/configs/displaycfg.xml)

```
#### Action: Add the following snippet at starting at line 270 ####
++++++ Snippet Start ++++++
++++++ Snippet End ++++++
#### Action: Delete line 267 ####
#### Action: Change line 253 to the following snippet ####
++++++ Snippet Start ++++++
<!--
  <displayTags label="Control Number:>
    <displayTag field="001"/>
  </displayTags>
-->
  <displayTags label="Holdings Information" notFound="No holdings available - check at the Circulation Desk.">
++++++ Snippet End ++++++
#### Action: Add the following snippet at starting at line 157 ####
++++++ Snippet Start ++++++
++++++ Snippet End ++++++
#### Action: Add the following snippet at starting at line 40 ####
++++++ Snippet Start ++++++
<!--
++++++ Snippet End ++++++
#### Action: Add the following snippet at starting at line 39 ####
++++++ Snippet Start ++++++
-->
++++++ Snippet End ++++++
#### Action: Delete line 19 ####
#### Action: Change line 5 to the following snippet ####
++++++ Snippet Start ++++++
#(c)#    Copyright 2007-2012 Ex Libris (USA) Inc.
++++++ Snippet End ++++++
```

/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\_default/xsl/contentLayout/configs/ema ilcfg.xml

#### Action: Change line 84 to the following snippet ####

++++++ Snippet Start +++++  
    </display>

++++++ Snippet End +++++

#### Action: Change lines 80 to 82 to the following snippet ####

++++++ Snippet Start +++++  
    <holdingsTags label="Holdings Information" notFound="No holdings available - check at the Circulation Desk.">  
        <displayTag field="9000" />  
    </holdingsTags>  
++++++ Snippet End +++++

#### Action: Change lines 76 to 78 to the following snippet ####

++++++ Snippet Start +++++  
    <displayTags label="Links:">  
        <displayTag field="3000"/>  
    </displayTags>  
++++++ Snippet End +++++

#### Action: Change lines 72 to 74 to the following snippet ####

++++++ Snippet Start +++++  
    <displayTags label="Subjects:">  
        <displayTag field="600" indicator1="X" indicator2="X" subfield="abcdefghijklmnopqrstuvwxyz"/>  
    </displayTags>  
++++++ Snippet End +++++

#### Action: Change lines 68 to 70 to the following snippet ####

++++++ Snippet Start +++++  
    <displayTags label="Series:">  
        <displayTag field="400" indicator1="X" indicator2="X" subfield="abdfklnptv"/>  
    </displayTags>  
++++++ Snippet End +++++

#### Action: Change lines 64 to 66 to the following snippet ####

++++++ Snippet Start +++++  
    <displayTags label="Contents:">  
        <displayTag field="2000"/>  
    </displayTags>  
++++++ Snippet End +++++

#### Action: Change line 55 to the following snippet ####

++++++ Snippet Start +++++  
    </display>

++++++ Snippet End +++++

#### Action: Change lines 47 to 49 to the following snippet ####

++++++ Snippet Start +++++  
    <displayTags label="Description:">  
        <displayTag field="250" indicator1="X" indicator2="X" subfield="ab"/>  
    </displayTags>  
++++++ Snippet End +++++

#### Action: Change lines 43 to 45 to the following snippet ####

```

++++++ Snippet Start ++++++
<displayTags label="ISSN:">
  <displayTag field="022" indicator1="X" indicator2="X" subfield="a"/>
</displayTags>
++++++ Snippet End ++++++

```

#### Action: Change lines 39 to 41 to the following snippet ####

```

++++++ Snippet Start ++++++
<displayTags label="ISBN:">
  <displayTag field="020" indicator1="X" indicator2="X" subfield="a"/>
</displayTags>
++++++ Snippet End ++++++

```

#### Action: Change lines 35 to 37 to the following snippet ####

```

++++++ Snippet Start ++++++
<displayTags label="Publisher:">
  <displayTag field="260" indicator1="X" indicator2="X" subfield="abc"/>
</displayTags>
++++++ Snippet End ++++++

```

#### Action: Change lines 30 to 33 to the following snippet ####

```

++++++ Snippet Start ++++++
<displayTags label="Author:">
  <displayTag field="100" indicator1="X" indicator2="X" subfield="aq"/>
  <displayTag field="110" indicator1="X" indicator2="X" subfield="ab"/>
</displayTags>
++++++ Snippet End ++++++

```

#### Action: Change lines 24 to 28 to the following snippet ####

```

++++++ Snippet Start ++++++
<displayTags label="Title:">
  <displayTag field="130" indicator1="X" indicator2="X" subfield="aplskf"/>
  <displayTag field="240" indicator1="X" indicator2="X" subfield="aplskf"/>
  <displayTag field="245" indicator1="X" indicator2="X" subfield="ab"/>
</displayTags>
++++++ Snippet End ++++++

```

#### Action: Change line 22 to the following snippet ####

```

++++++ Snippet Start ++++++
<display>
++++++ Snippet End ++++++

```

#### Action: Change line 20 to the following snippet ####

```

++++++ Snippet Start ++++++
-->
++++++ Snippet End ++++++

```

#### Action: Change line 18 to the following snippet ####

```

++++++ Snippet Start ++++++
** Notes This is a config for the xsl that creates
++++++ Snippet End ++++++

```

#### Action: Change line 5 to the following snippet ####

```

++++++ Snippet Start ++++++
#(c)#
Copyright 2007-2012 Ex Libris (USA) Inc.
++++++ Snippet End ++++++

```

#### Action: Change line 2 to the following snippet ####

```

++++++ Snippet Start ++++++
<!--
++++++ Snippet End ++++++

```

/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\_default/xsl/contentLayout/configs/print  
/briefRecordConfig.xml

#### Action: Add the following snippet at starting at line 69 ####  
++++++ Snippet Start +++++++

++++++ Snippet End +++++++

#### Action: Change lines 57 to 68 to the following snippet ####  
++++++ Snippet Start +++++++

```
<displayTags label="Publisher:>
  <displayTag field="260" indicator1="X" indicator2="X" subfield="abc" />
</displayTags>
<displayTags label="Link:>
  <displayTag field="856" indicator1="4" indicator2="X" subfield="z" />
</displayTags>
<displayTags label="URL:>
  <displayTag field="856" indicator1="4" indicator2="X" subfield="u" />
</displayTags>
<!--
  <displayTags label="Control Number:>
    <displayTag field="001"/>
  </displayTags>
-->
<displayTags label="Holdings Information: " notFound="No Data Available--Ask at Reference">
  <displayTag field="9000" />  </displayTags>
++++++ Snippet End +++++++
```

#### Action: Change line 49 to the following snippet ####  
++++++ Snippet Start +++++++

++++++ Snippet End +++++++

#### Action: Change lines 33 to 44 to the following snippet ####

++++++ Snippet Start +++++++

```
<displayTags label="Main Author:>
  <displayTag field="100" indicator1="X" indicator2="X" subfield="aq" />
  <displayTag field="110" indicator1="X" indicator2="X" subfield="ab" />
</displayTags>
<displayTags label="Conference:>
  <displayTag field="111" indicator1="X" indicator2="X" subfield="acnd" />
</displayTags>
<displayTags label="Title:>
  <displayTag field="130" indicator1="X" indicator2="X" subfield="aplskf" />
  <displayTag field="240" indicator1="X" indicator2="X" subfield="aplskf" preText="[" postText="]" />
  <displayTag field="245" indicator1="X" indicator2="X" subfield="ab" />
</displayTags>
```

++++++ Snippet End +++++++

#### Action: Change lines 30 to 31 to the following snippet ####

++++++ Snippet Start +++++++

```
<!-- <displayTags label="Database: " notFound="No information available">
  <displayTag field="5000" />  </displayTags>
++++++ Snippet End +++++++
```

#### Action: Delete lines 23 - 28 ####

```

##### Action: Add the following snippet at starting at line 21 #####
++++++ Snippet Start ++++++
<titleTags>
  <displayTag field="130" indicator1="X" indicator2="X" subfield="aplskf"/>
  <displayTag field="240" indicator1="X" indicator2="X" subfield="aplskf"/>
  <displayTag field="245" indicator1="X" indicator2="X" subfield="ab"/>
</titleTags>
++++++ Snippet End ++++++
##### Action: Change line 19 to the following snippet #####
++++++ Snippet Start ++++++
-->
++++++ Snippet End ++++++
##### Action: Change line 5 to the following snippet #####
++++++ Snippet Start ++++++
#(c) Copyright 2007-2012 Ex Libris (USA) Inc.
++++++ Snippet End ++++++
##### Action: Change line 2 to the following snippet #####
++++++ Snippet Start ++++++
<!--
++++++ Snippet End ++++++

```

[/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\\_default/xsl/contentLayout/configs/print  
/fullRecordConfig.xml](/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl_default/xsl/contentLayout/configs/print/fullRecordConfig.xml)

```

##### Action: Add the following snippet at starting at line 216 #####
++++++ Snippet Start ++++++
++++++ Snippet End ++++++
##### Action: Add the following snippet at starting at line 215 #####
++++++ Snippet Start ++++++
<displayTags label="Subject(s):">
  <displayTag field="600" indicator1="X" indicator2="X" subfield="abcdefghijklmnopqrstuvwxyz" >
    <subfield value="v" preText="--" />
    <subfield value="x" preText="--" />
    <subfield value="y" preText="--" />
    <subfield value="z" preText="--" />
  </displayTag>
  <displayTag field="610" indicator1="X" indicator2="X" subfield="abcdefghijklmnopqrstuvwxyz" >
    <subfield value="v" preText="--" />
    <subfield value="x" preText="--" />
    <subfield value="y" preText="--" />
    <subfield value="z" preText="--" />
  </displayTag>
  <displayTag field="611" indicator1="X" indicator2="X" subfield="abcdefghijklmnopqrstuvwxyz" >
    <subfield value="v" preText="--" />
    <subfield value="x" preText="--" />
    <subfield value="y" preText="--" />
    <subfield value="z" preText="--" />
  </displayTag>
  <displayTag field="630" indicator1="X" indicator2="X" subfield="abcdefghijklmnopqrstuvwxyz" >
    <subfield value="v" preText="--" />
    <subfield value="x" preText="--" />
    <subfield value="y" preText="--" />
    <subfield value="z" preText="--" />

```

```

</displayTag>
<displayTag field="650" indicator1="X" indicator2="X" subfield="abcdvxzy" >
  <subfield value="v" preText="--" />
  <subfield value="x" preText="--" />
  <subfield value="z" preText="--" />
  <subfield value="y" preText="--" />
</displayTag>
<displayTag field="651" indicator1="X" indicator2="X" subfield="avxyz" >
  <subfield value="v" preText="--" />
  <subfield value="x" preText="--" />
  <subfield value="y" preText="--" />
  <subfield value="z" preText="--" />
</displayTag>
<displayTag field="655" indicator1="|" indicator2="7" subfield="avxyz" >
  <subfield value="v" preText="--" />
  <subfield value="x" preText="--" />
  <subfield value="y" preText="--" />
  <subfield value="z" preText="--" />
</displayTag>
<displayTag field="690" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="691" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="692" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="693" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="694" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="695" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="696" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="697" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="698" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="699" indicator1="X" indicator2="X" subfield="a" />
</displayTags>
<displayTags label="Publisher:>
  <displayTag field="260" indicator1="X" indicator2="X" subfield="abc" />
</displayTags>
<displayTags label="Description:>
  <displayTag field="250" indicator1="X" indicator2="X" subfield="ab" />
  <displayTag field="254" indicator1="X" indicator2="X" subfield="a" />
  <displayTag field="255" indicator1="X" indicator2="X" subfield="abcde" />
  <displayTag field="507" indicator1="X" indicator2="X" subfield="ab" />
  <displayTag field="256" indicator1="X" indicator2="X" subfield="a" />
  <displayTag field="516" indicator1="X" indicator2="X" subfield="a" />
  <displayTag field="753" indicator1="X" indicator2="X" subfield="abc" />
  <displayTag field="755" indicator1="X" indicator2="X" subfield="axyz" />
  <displayTag field="300" indicator1="X" indicator2="X" subfield="abcefg" />
  <displayTag field="306" indicator1="X" indicator2="X" subfield="a" />
  <displayTag field="310" indicator1="X" indicator2="X" subfield="a" />
  <displayTag field="515" indicator1="X" indicator2="X" subfield="a" />
  <displayTag field="340" indicator1="X" indicator2="X" subfield="abcdefh" />
  <displayTag field="351" indicator1="X" indicator2="X" subfield="abc" />
  <displayTag field="362" indicator1="X" indicator2="X" subfield="a" />
</displayTags>
<displayTags label="Series:>
  <displayTag field="400" indicator1="X" indicator2="X" subfield="abdfklnptv" />
  <displayTag field="410" indicator1="X" indicator2="X" subfield="abdfklnptv" />
  <displayTag field="411" indicator1="X" indicator2="X" subfield="acdefklnpt" />
  <displayTag field="440" indicator1="X" indicator2="X" subfield="anpv" />
  <displayTag field="490" indicator1="X" indicator2="X" subfield="av" />
</displayTags>
<displayTags label="Notes:>
  <displayTag field="500" indicator1="X" indicator2="X" subfield="a" />
  <displayTag field="501" indicator1="X" indicator2="X" subfield="a" />
  <displayTag field="502" indicator1="X" indicator2="X" subfield="a" />

```

```

<displayTag field="504" indicator1="X" indicator2="X" subfield="ab" />
<displayTag field="506" indicator1="X" indicator2="X" subfield="abcde" />
<displayTag field="520" indicator1="X" indicator2="X" subfield="ab" />
<displayTag field="525" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="530" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="533" indicator1="X" indicator2="X" subfield="ae" />
<displayTag field="538" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="540" indicator1="X" indicator2="X" subfield="abcd" />
<displayTag field="545" indicator1="X" indicator2="X" subfield="ab" />
<displayTag field="546" indicator1="X" indicator2="X" subfield="ab" />
<displayTag field="555" indicator1="X" indicator2="X" subfield="ab" />
<displayTag field="590" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="591" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="592" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="593" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="594" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="595" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="596" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="597" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="598" indicator1="X" indicator2="X" subfield="a" />
<displayTag field="599" indicator1="X" indicator2="X" subfield="a" />
</displayTags>
<displayTags label="Indexed In:">
    <displayTag field="510" indicator1="X" indicator2="X" subfield="ab" />
</displayTags>
<displayTags label="Original Language:">
    <displayTag field="880" indicator1="X" indicator2="X" subfield="abc" />
</displayTags>
<displayTags label="Link:">
    <displayTag field="856" indicator1="4" indicator2="X" subfield="z" />
</displayTags>
<displayTags label="URL:">
    <displayTag field="856" indicator1="4" indicator2="X" subfield="u" />
</displayTags>
<!--
    <displayTags label="Control Number:">
        <displayTag field="001"/>
    </displayTags>
-->
    <displayTags label="Holdings Information: " notFound="No Data Available--Ask at Reference">
        <displayTag field="9000" />    </displayTags>

```

++++++ Snippet End ++++++

#### Action: Delete lines 93 - 214 ####

#### Action: Change line 85 to the following snippet ####

++++++ Snippet Start ++++++

++++++ Snippet End ++++++

#### Action: Change lines 33 to 80 to the following snippet ####

++++++ Snippet Start ++++++

```

<displayTags label="Main Author:">
    <displayTag field="100" indicator1="X" indicator2="X" subfield="aqd" />
    <displayTag field="110" indicator1="X" indicator2="X" subfield="ab" />
</displayTags>
<displayTags label="Other Author(s):">
    <displayTag field="700" indicator1="X" indicator2="X" subfield="aqd" />
    <displayTag field="710" indicator1="X" indicator2="X" subfield="ab" />
</displayTags>

```

```

<displayTags label="Conference Name:>
  <displayTag field="111" indicator1="X" indicator2="X" subfield="acnd" />
  <displayTag field="711" indicator1="X" indicator2="X" subfield="acnd" />
</displayTags>
<displayTags label="Title:>
  <displayTag field="130" indicator1="X" indicator2="X" subfield="aplskfmnor" />
  <displayTag field="240" indicator1="X" indicator2="X" subfield="aplskfmnor" preText="[" postText="]" />
  <displayTag field="730" indicator1="X" indicator2="X" subfield="aplskfmnor" />
  <displayTag field="245" indicator1="X" indicator2="X" subfield="abcfknps" />
</displayTags>

<displayTags label="Variant Title:>
  <displayTag field="246" indicator1="X" indicator2="X" subfield="abfnp" />
</displayTags>
<displayTags label="Continues:>
  <displayTag field="780" indicator1="0" indicator2="0" subfield="at" />
  <displayTag field="780" indicator1="0" indicator2="1" subfield="at" />
</displayTags>
<displayTags label="Supersedes:>
  <displayTag field="780" indicator1="0" indicator2="2" subfield="at" />
  <displayTag field="780" indicator1="0" indicator2="3" subfield="at" />
</displayTags>
<displayTags label="Absorbed:>
  <displayTag field="780" indicator1="0" indicator2="5" subfield="at" />
  <displayTag field="780" indicator1="0" indicator2="6" subfield="at" />
</displayTags>
<displayTags label="Continued by:>
  <displayTag field="785" indicator1="0" indicator2="0" subfield="at" />
  <displayTag field="785" indicator1="0" indicator2="1" subfield="at" />
</displayTags>
<displayTags label="Superseded by:>
  <displayTag field="785" indicator1="0" indicator2="2" subfield="at" />
  <displayTag field="785" indicator1="0" indicator2="3" subfield="at" />
</displayTags>
<displayTags label="Absorbed by:>
  <displayTag field="785" indicator1="0" indicator2="4" subfield="at" />
  <displayTag field="785" indicator1="0" indicator2="5" subfield="at" />
</displayTags>
<displayTags label="Split into:>
  <displayTag field="785" indicator1="0" indicator2="6" subfield="at" />
</displayTags>
++++++ Snippet End ++++++

```

#### Action: Change lines 30 to 31 to the following snippet ####

++++++ Snippet Start ++++++

```

<!-- <displayTags label="Database: " notFound="No information available">
  <displayTag field="5000" /> </displayTags>
++++++ Snippet End ++++++

```

#### Action: Change lines 23 to 28 to the following snippet ####

++++++ Snippet Start ++++++

```

<titleTags>
  <displayTag field="130" indicator1="X" indicator2="X" subfield="aplskf"/>
  <displayTag field="240" indicator1="X" indicator2="X" subfield="aplskf"/>
  <displayTag field="245" indicator1="X" indicator2="X" subfield="ab"/>
</titleTags>
++++++ Snippet End ++++++

```

#### Action: Change line 19 to the following snippet ####

++++++ Snippet Start ++++++

```
-->
++++++ Snippet End +++++++

##### Action: Change line 5 to the following snippet #####
++++++ Snippet Start ++++++
#(c) Copyright 2007-2012 Ex Libris (USA) Inc.
++++++ Snippet End +++++

##### Action: Change line 2 to the following snippet #####
++++++ Snippet Start ++++++
<!--
++++++ Snippet End ++++++
```

[/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\\_default/xsl/contentLayout/display/display\\_text.xsl](/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl_default/xsl/contentLayout/display/display_text.xsl)

```
##### Action: Add the following snippet at starting at line 1061 #####
++++++ Snippet Start ++++++

++++++ Snippet End +++++

##### Action: Add the following snippet at starting at line 878 #####
++++++ Snippet Start ++++++
<xsl:when test="string-length($pathToFile)>0">
    <xsl:value-of select="$pathToFile"/>
</xsl:when>
++++++ Snippet End ++++++
```

```
##### Action: Add the following snippet at starting at line 831 #####
++++++ Snippet Start ++++++
```

```
<!-- Get local link-to-file information. -->
<xsl:variable name="path">
    <xsl:if test="slim:subfield[@code='d']">
        <xsl:value-of select="slim:subfield[@code='d']"/>
    </xsl:if>
</xsl:variable>
<xsl:variable name="fileName">
    <xsl:for-each select="slim:subfield[@code='f']">
        <xsl:value-of select="."/>
    </xsl:for-each>
</xsl:variable>
<xsl:variable name="operSys">
    <xsl:if test="slim:subfield[@code='o']">
        <xsl:value-of select="slim:subfield[@code='o']"/>
    </xsl:if>
</xsl:variable>

<!-- Set path and file. -->
<xsl:variable name="pathToFile">
    <xsl:if test="string-length($fileName)>0">
        <xsl:value-of select="file:///"/>
        <xsl:copy-of select="$path"/>
    <xsl:choose>
        <xsl:when test="$operSys='DOS'">
            <xsl:value-of select="\\"/>
        </xsl:when>
        <xsl:when test="$operSys='UNIX'">
            <xsl:value-of select="/" />
        </xsl:when>
```

```

<xsl:otherwise>
    <xsl:value-of select="/" />
</xsl:otherwise>
</xsl:choose>
<xsl:copy-of select="$fileName"/>
</xsl:if>
</xsl:variable>

++++++ Snippet End +++++++

#### Action: Add the following snippet at starting at line 514 #####
++++++ Snippet Start +++++++
<xsl:template name="BMDDisplayControlfield">
<xsl:param name="controlfield"/>

<xsl:if test="contains($controlfield, @tag)">
    <xsl:value-of select="." />
</xsl:if>

</xsl:template>

<!--#####
-->

++++++ Snippet End +++++++

#### Action: Add the following snippet at starting at line 472 #####
++++++ Snippet Start +++++++
<xsl:for-each select="$bibRecord/hol:marcRecord/slim:controlfield[@tag=$field]">
    <xsl:call-template name="BMDDisplayControlfield">
        <xsl:with-param name="controlfield" select="$field"/>
    </xsl:call-template>
</xsl:for-each>

++++++ Snippet End +++++++

#### Action: Change line 6 to the following snippet #####
++++++ Snippet Start +++++++
#(c)#
Copyright 2007-2012 Ex Libris (USA) Inc.
++++++ Snippet End +++++++

/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\_default/xsl/contentLayout/display/display.xsl

#### Action: Add the following snippet at starting at line 1903 #####
++++++ Snippet Start +++++++

++++++ Snippet End +++++++

#### Action: Add the following snippet at starting at line 1566 #####
++++++ Snippet Start +++++++

++++++ Snippet End +++++++

#### Action: Add the following snippet at starting at line 1507 #####
++++++ Snippet Start +++++++

++++++ Snippet End +++++++

#### Action: Add the following snippet at starting at line 1502 #####

```

```

++++++ Snippet Start ++++++
<xsl:when test="string-length($pathToFile)>0">
    <xsl:value-of select="$pathToFile"/>
</xsl:when>
++++++ Snippet End ++++++
##### Action: Delete line 1452 #####
##### Action: Add the following snippet at starting at line 1420 #####
++++++ Snippet Start ++++++
<!-- Get local link-to-file information. -->
<xsl:variable name="path">
    <xsl:if test="slim:subfield[@code='d']">
        <xsl:value-of select="slim:subfield[@code='d']"/>
    </xsl:if>
</xsl:variable>
<xsl:variable name="fileName">
    <xsl:for-each select="slim:subfield[@code='f']">
        <xsl:value-of select="."/>
    </xsl:for-each>
</xsl:variable>
<xsl:variable name="operSys">
    <xsl:if test="slim:subfield[@code='o']">
        <xsl:value-of select="slim:subfield[@code='o']"/>
    </xsl:if>
</xsl:variable>

<!-- Set path and filename for link. -->
<xsl:variable name="pathToFile">
    <xsl:if test="string-length($fileName)>0">

        <xsl:value-of select="file:///"/>
        <xsl:copy-of select="$path"/>
        <xsl:choose>
            <xsl:when test="$operSys='DOS'">
                <xsl:value-of select="\\"/>
            </xsl:when>
            <xsl:when test="$operSys='UNIX'">
                <xsl:value-of select="/">
            </xsl:when>
            <xsl:otherwise>
                <xsl:value-of select="/">
            </xsl:otherwise>
        </xsl:choose>
        <xsl:copy-of select="$fileName"/>
    </xsl:if>
</xsl:variable>

```

++++++ Snippet End ++++++

##### Action: Add the following snippet at starting at line 1016 #####
++++++ Snippet Start ++++++

++++++ Snippet End ++++++

##### Action: Add the following snippet at starting at line 956 #####
++++++ Snippet Start ++++++

```

<xsl:template name="BMDDisplayControlfield">
<xsl:param name="controlfield"/>

    <xsl:if test="contains($controlfield,@tag)">

```

```

<xsl:value-of select=". "/>
</xsl:if>

</xsl:template>

<!--#####
----- -->

++++++ Snippet End +++++++

##### Action: Change line 937 to the following snippet #####
++++++ Snippet Start +++++++
    <xsl:if test="string-length($displayTag/@postText)">
        <xsl:value-of select="$displayTag/@postText"/>
    </xsl:if>
++++++ Snippet End +++++++

##### Action: Change line 935 to the following snippet #####
++++++ Snippet Start +++++++
    <xsl:if test="string-length($displayTag/@preText)">
        <xsl:value-of select="$displayTag/@preText"/>
    </xsl:if>
++++++ Snippet End +++++++

##### Action: Change lines 927 to 931 to the following snippet #####
++++++ Snippet Start +++++++
    <xsl:choose>
        <xsl:when test="string-length($link)>0">
            <a href="{{$link}}>
                <xsl:if test="string-length($displayTag/@preText)">
                    <xsl:value-of select="$displayTag/@preText"/>
                </xsl:if>
                <xsl:copy-of select="$subfieldData"/>
                <xsl:if test="string-length($displayTag/@postText)">
                    <xsl:value-of select="$displayTag/@postText"/>
                </xsl:if>
            </a>
            <br/>
        </xsl:when>
        <xsl:otherwise>
            <xsl:if test="string-length($displayTag/@preText)">
                <xsl:value-of select="$displayTag/@preText"/>
            </xsl:if>
            <xsl:copy-of select="$subfieldData"/>
            <xsl:if test="string-length($displayTag/@postText)">
                <xsl:value-of select="$displayTag/@postText"/>
            </xsl:if>
            <br/>
        </xsl:otherwise>
    </xsl:choose>
++++++ Snippet End +++++++

##### Action: Change line 920 to the following snippet #####
++++++ Snippet Start ++++++
    <xsl:if test="string-length($redirectSearchData)>0">
        <xsl:value-of select="$searchParameter"/><xsl:value-of
select="$searchArgParameter"/>=<xsl:value-of select="normalize-
space(substring($redirectSearchData,$redirectNonFilingIndicator))"/>&#x26amp;<xsl:value-of
select="$searchCodeParameter"/>=<xsl:value-of select="$redirectSearchCode"/>&#x26amp;<xsl:value-of
select="$searchTypeParameter"/>=<xsl:value-of select="$redirectSearchType"/>
    </xsl:if>
++++++ Snippet End ++++++

```

```

##### Action: Add the following snippet at starting at line 892 #####
++++++ Snippet Start ++++++
    <xsl:with-param name="displayTag" select="$displayTag"/>
++++++ Snippet End +++++

##### Action: Change lines 884 to 888 to the following snippet #####
++++++ Snippet Start ++++++
    <xsl:variable name="redirectSearchType">
        <xsl:choose>
            <xsl:when test="$mfhdSearchRedirect='callnumber'">
                <xsl:value-of
select="$searchTypeCallNumber/page:element[@nameId='searchType']/page:label"/>
                </xsl:when>
            </xsl:choose>
        </xsl:variable>
++++++ Snippet End +++++

##### Action: Change lines 878 to 882 to the following snippet #####
++++++ Snippet Start ++++++
    <xsl:variable name="redirectSearchCode">
        <xsl:choose>
            <xsl:when test="$mfhdSearchRedirect='callnumber'">
                <xsl:value-of
select="$searchTypeCallNumber/page:element[@nameId='searchCode']/page:label"/>
                <xsl:value-of select="$browse"/>
            </xsl:when>
        </xsl:choose>
    </xsl:variable>
++++++ Snippet End +++++

##### Action: Change lines 874 to 876 to the following snippet #####
++++++ Snippet Start ++++++
    <xsl:variable name="mfhdSearchRedirect">
        <xsl:value-of select="translate($displayTag/@redirect, $uppercase, $lowercase)">
        </xsl:value-of>
++++++ Snippet End +++++

##### Action: Add the following snippet at starting at line 872 #####
++++++ Snippet Start ++++++
    <!-- Snippet End +++++

##### Action: Change line 870 to the following snippet #####
++++++ Snippet Start ++++++
    <xsl:if test="position()>1">
        <xsl:text> </xsl:text>
    </xsl:if>
++++++ Snippet End +++++

##### Action: Change lines 837 to 841 to the following snippet #####
++++++ Snippet Start ++++++
    <xsl:choose>
        <xsl:when test="string-length($link)>0">
            <a href="{{$link}}>
                <xsl:if test="string-length($displayTag/@preText)">
                    <xsl:value-of select="$displayTag/@preText"/>
                </xsl:if>
                <xsl:copy-of select="$subfieldData"/>
                <xsl:if test="string-length($displayTag/@postText)">
                    <xsl:value-of select="$displayTag/@postText"/>
                </xsl:if>
            </a>
        </xsl:when>
    </xsl:choose>

```

```

        </xsl:if>
    </a>
    <br/>
</xsl:when>
<xsl:otherwise>
    <xsl:if test="string-length($displayTag/@preText)">
        <xsl:value-of select="$displayTag/@preText"/>
    </xsl:if>
    <xsl:copy-of select="$subfieldData"/>
    <xsl:if test="string-length($displayTag/@postText)">
        <xsl:value-of select="$displayTag/@postText"/>
    </xsl:if>
    <br/>
</xsl:otherwise>
</xsl:choose>
++++++ Snippet End ++++++

```

#### Action: Change lines 830 to 831 to the following snippet ####

++++++ Snippet Start ++++++

```

<xsl:if test="string-length($cleanedRedirectSearchData)>0">
    <xsl:value-of select="$searchParameter"/><xsl:value-of
select="$searchArgParameter"/>=<xsl:value-of
select="substring($cleanedRedirectSearchData,$redirectNonFilingIndicator)"/>&lt;xsl:value-of
select="$searchCodeParameter"/>=<xsl:value-of select="$redirectSearchCode"/>&lt;xsl:value-of
select="$searchTypeParameter"/>=<xsl:value-of select="$redirectSearchType"/>
    </xsl:if>
</xsl:variable>
++++++ Snippet End ++++++

```

#### Action: Delete line 761 ####

#### Action: Add the following snippet at starting at line 714 ####

++++++ Snippet Start ++++++

```

<xsl:for-each select="$bibRecord/hol:marcRecord/slim:controlfield[@tag=$field]">
    <xsl:call-template name="BMDDisplayControlfield">
        <xsl:with-param name="controlfield" select="$field"/>
    </xsl:call-template>
</xsl:for-each>

```

++++++ Snippet End ++++++

#### Action: Change line 6 to the following snippet ####

++++++ Snippet Start ++++++

#(c) Copyright 2007-2012 Ex Libris (USA) Inc.

++++++ Snippet End ++++++

[/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\\_default/xsl/resultsMyList.xsl](/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl_default/xsl/resultsMyList.xsl)

#### Action: Add the following snippet at starting at line 66 ####

++++++ Snippet Start ++++++

++++++ Snippet End ++++++

#### Action: Change line 57 to the following snippet ####

++++++ Snippet Start ++++++

```

<form action="{!!page:element[@nameId='page.form.action']/page:value}" method="POST" id="resultsForm">
++++++ Snippet End ++++++

```

#### Action: Change line 6 to the following snippet ####

```
++++++ Snippet Start ++++++
#(c) Copyright 2007-2012 Ex Libris (USA) Inc.
++++++ Snippet End ++++++
```

[/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl\\_default/xsl/resultsTitles.xsl](/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/exl_default/xsl/resultsTitles.xsl)

```
#### Action: Add the following snippet at starting at line 71 #####
++++++ Snippet Start ++++++
```

```
++++++ Snippet End ++++++
```

```
#### Action: Change lines 63 to 64 to the following snippet #####
++++++ Snippet Start ++++++
```

```
    <xsl:call-template name="buildResultsForm"/>
    <!-- ## Remove Update Button ## -->
++++++ Snippet End ++++++
```

```
#### Action: Change lines 51 to 54 to the following snippet #####
++++++ Snippet Start ++++++
```

```
    <xsl:call-template name="buildHtmlPage">
        <xsl:with-param name="myCSS" select="$resultsTitlesCSS"/>
        <xsl:with-param name="myJavascripts" select="$myJavascripts"/>
    </xsl:call-template>
++++++ Snippet End ++++++
```

```
#### Action: Change lines 22 to 25 to the following snippet #####
++++++ Snippet Start ++++++
```

```
    exclude-result-prefixes="xsl fo page"
    xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
    xmlns:page="http://www.exlibrisgroup.com/voyager/webvoyage/page"
    xmlns:fo="http://www.w3.org/1999/XSL/Format">
++++++ Snippet End ++++++
```

```
#### Action: Change line 6 to the following snippet #####
++++++ Snippet Start ++++++
```

```
#(c) Copyright 2007-2012 Ex Libris (USA) Inc.
++++++ Snippet End ++++++
```

For both

[/m1/voyager/xxxdb/tomcat/vxws/context/vxws/ui/exl\\_default/vxws.properties](/m1/voyager/xxxdb/tomcat/vxws/context/vxws/ui/exl_default/vxws.properties)  
and

[/m1/voyager/xxxdb/tomcat/vxws/context/vxws/ui/exl\\_default/vxws.properties.tml](/m1/voyager/xxxdb/tomcat/vxws/context/vxws/ui/exl_default/vxws.properties.tml)

```
#### Action: Add the following snippet at starting at line 166 #####
++++++ Snippet Start ++++++
```

```
#####
# Item information substitution tokens to display the codes' corresponding
# information in the Item column on the Charged Item section of My Account page
# \t -> the item's title
# \i -> the item's enumeration, chronology and year
# \n -> the item's copy number
# \c -> the item's call number
# \b -> the item's barcode
# \l -> the item's location
# \a -> the item's author
#####
page.myAccount.chargedItem.itemInfo=\t
```

```

#####
# Item title substitution tokens to display the item's title, enum, chron, year
# and copy number information in the item title field of patron requestItem
# elements of the circulation actions services
# \t -> the item's title
# \i -> the items's enumeration, chronology and year
# \n -> the item's copy number
#####
page.myAccount.reqPending.itemInfo=\t \i

#####
# Item due date substitution tokens to display the codes' corresponding
# information in the Due Date column on the Charged Item section of My Account page
# \d -> the item's due date
# \e -> the items's due date, if the due date is not today
# \t -> the item's due time
# \u -> the item's due time, if the due date is today
#####
page.myAccount.chargedItem.dueDate=\d \t

++++++ Snippet End +++++++

#### Action: Change lines 107 to 108 to the following snippet #####
++++++ Snippet Start ++++++
page.myAccount.chargedItem.item.status.3=Renewed (Requests: \c)
page.myAccount.chargedItem.item.status.4=Overdue (Requests: \c)
++++++ Snippet End +++++++

#### Action: Change line 100 to the following snippet #####
++++++ Snippet Start ++++++
page.myAccount.chargedItem.item.status.2=Charged (Requests: \c)
++++++ Snippet End +++++++

#### Action: Change line 62 to the following snippet #####
++++++ Snippet Start ++++++
page.myAccount.borrowingBlocks.item.reason.address_invalid_patron=The address in your patron record is
invalid.
++++++ Snippet End ++++++

```