



# **Voyager<sup>®</sup> 7.0 WebVoyage<sup>®</sup> Architecture and Configuration User's Guide**

April 2008  
Draft

**Ex Libris (USA) Inc.**

This document contains proprietary information of  
Ex Libris (USA) Inc. and is not to be disclosed or used  
except in accordance with applicable agreements.

Copyright © 2008 Ex Libris (USA) Inc.  
Unpublished and Not for Publication  
All Rights Reserved

## **Copyright © 2008 Ex Libris (USA) Inc.**

This material is protected by the copyright laws of the United States and other countries. It may not be reproduced, distributed, or altered in any fashion by any entity (either internal or external to Ex Libris (USA) Inc.), except in accordance with applicable agreements, contracts or licensing.

## **CONFIDENTIAL INFORMATION**

The information herein is the property of Ex Libris (USA) Inc. or its affiliates and any misuse or abuse will result in economic loss.

This document is provided for limited and restricted purposes in accordance with a binding contract with Ex Libris (USA) Inc. or an affiliate. The information herein includes trade secrets and is confidential.

## **Notice**

Every effort was made to ensure that the information in this document was complete and accurate at the time of printing. However, information is subject to change.

## **Trademarks**

Voyager is a registered trademark of Ex Libris (USA) Inc.

WebVoyage is a trademark of Ex Libris (USA) Inc.

UNIX is a registered trademark in the United States and other countries, licensed exclusively through X/Open Company Ltd.

Microsoft, the Microsoft logo, MS, MS-DOS, Microsoft PowerPoint, Visual Basic, Visual C++, Win32, Microsoft Windows, the Windows logo, Microsoft Notepad, Microsoft Windows Explorer, Microsoft Internet Explorer, and Windows NT are registered trademarks and ActiveX is a trademark of the Microsoft corporation in the United States and/or other countries.

Sun, Sun Microsystems, the Sun logo, Solaris, ONC+, NFS, SunVTS, VIS, JumpStart, Sun Fire, StorEdge, Sun Fireplane Interconnect, WebNFS, Java, Solstice, Solstice AdminSuite, Sun Management Center, Sun Cluster, JVM, ShowMeHow, ShowMe TV, Solaris Webstart, Sun Remote Systems Control, Solaris PC Netlink, and Open Windows are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and other countries.

The Mozilla trademarks include, among others, the names Mozilla®, mozilla.org®, Firefox®, Thunderbird™, Bugzilla™, Camino®, Sunbird®, Seamonkey®, Foxkeh™ and XUL™, as well as the Firefox logo, Thunderbird logo, SeaMonkey logo, Camino logo, Foxkeh logo and the Mozilla red lizard logo.

Unicode and the Unicode logo are registered trademarks of Unicode, Inc.

Google is a trademark of Google Inc.

WorldCat is a registered trademark provided by OCLC Online Computer Library Center, Inc. on behalf of its member libraries.

Amazon.com is a registered trademark of Amazon.com, Inc.

Other products and corporate names mentioned herein which are trademarks of a third party are used only for explanation and for the owners' benefit and with no intent to infringe.

Use of third party products or information referred to herein is at the user's risk.

---

# Contents

---

## About This Document

- Purpose xvii
- Intended Audience xvii
- Reason for Reissue xvii
- Document Summary xviii
- Conventions Used in This Document xix
- Document Reproduction/Photocopying xx
- Comment on This Document xx
  - To Submit Comments by E-mail xxi

---

## 1 Getting Started

- Purpose of this Chapter 1-1
- Prerequisite Skills and Knowledge 1-1
- Before You Begin 1-2

---

## 2 Architecture

- WebVoyage Architecture Overview 2-1
- Flowchart Example - myAccount Page 2-2
  - Flowchart Example Description 2-2
  - .css Processing 2-4
- Page Components Example - Basic Search 2-5

---

## 3 How Do I Build A Separate Display For Serials?

- Description For “How Do I Build A Separate Display For Serials?” Example 3-1
- Files 3-1
- Instructions 3-1

**Ex Libris (USA) Inc.**  
See notice on first page

---

## Contents

---

### **4            How Do I Add Static Links To The Header Or Footer?**

- Description For “How Do I Add Static Links To The Header Or Footer?” Example 4-1
- Files 4-1
- Instructions 4-1

---

### **5            How Do I Remove Information From A Page?**

- Description For “How Do I Remove Information From A Page?” Example 5-1
- Files 5-1
- Instructions 5-1

---

### **6            How Do I Add A Map Or Other Information To A Location?**

- Description For “How Do I Add A Map Or Other Information To A Location?” Example 6-1
- Files 6-1
- Instructions 6-1

---

### **7            How Do I Create An External Search From A Bibliographic Record Display?**

- Description For “How Do I Create An External Search From A Bibliographic Record Display?” Example 7-1
- Files 7-1
- Instructions 7-2

---

### **8            How Do I Dynamically Disable Limits And Change Search Tips Based On The Selected Search Index?**

- Description For “How Do I Dynamically Disable

Ex Libris (USA) Inc.  
See notice on first page

---

## Contents

	Limits And Change Search Tips Based On The Selected Search Index?" Example	8-1
•	Files	8-1
•	Instructions	8-2

---

### 9 How Do I Disable AutoComplete?

•	Description For "How Do I Disable AutoComplete?" Example	9-1
•	Files	9-1
•	Instructions	9-1

---

### 10 How Do I Display A Favicon?

•	Description For "How Do I Display A Favicon?" Example	10-1
•	Files	10-1
•	Instructions	10-2

---

### 11 How Do I Hide Limits On The Advanced Search Page?

•	Description For "How Do I Hide Limits On The Advanced Search Page?" Example	11-1
•	Files	11-1
•	Instructions	11-1

---

### 12 How Do I Build And Display A Persistent Link To A Bibliographic Record?

•	Description For "How Do I Build And Display A Persistent Link To A Bibliographic Record?" Example	12-1
•	Files	12-1
•	Instructions	12-1

---

## Contents

---

### 13      **How Do I Change The Format Of The Record Display Page?**

- Description For “How Do I Change The Format Of The Record Display Page?” Example 13-1
- Files 13-1
- Instructions 13-2

---

### 14      **How Do I Add Tracking Codes?**

- Description For “How Do I Add Tracking Codes?” Example 14-1
- Files 14-1
- Instructions 14-2

---

### 15      **How Do I Implement Google Book Search?**

- Description For “How Do I Implement Google Book Search?” 15-1
- Files 15-1
- Google Book Search Implementation 15-2
  - googleBooksAvail.js 15-2
  - local\_googleBooksAvail.xsl 15-2
  - displayFacets.xsl 15-3
  - displayGoogleBooks.css 15-3
- Disable Google Book Search 15-3

---

### 16      **How Do I Display Cover Images From Services Like Amazon.com and Syndetics Solutions?**

- Description For “How Do I Display Cover Images From Services Like Amazon.com and Syndetics Solutions?” 16-1
- Files 16-1
- Syndetics Solutions Implementation 16-2
  - pageProperties.xml 16-2
  - resultsFacets.xsl 16-3

**Ex Libris (USA) Inc.**  
See notice on first page

---

## Contents

resultsTitles.xsl	16-5
imageUtils.js	16-5
displaycfg.xml	16-6
display.xsl	16-6
displayRecord.xsl	16-7

---

IN

Index

IN-1

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page



---

## Figures

---

<b>2</b>	<b>Architecture</b>	
2-1.	Display page build overview	2-2
2-2.	Flowchart example for myAccount page	2-4
2-3.	Page components	2-6

---

<b>3</b>	<b>How Do I Build A Separate Display For Serials?</b>	
3-1.	Sample line of code for sdisplaycfg.xml	3-2
3-2.	Preceding lines of code	3-4
3-3.	Document holders declaration to add	3-5
3-4.	Lines to be replaced	3-5
3-5.	Replacement lines of code	3-5

---

<b>4</b>	<b>How Do I Add Static Links To The Header Or Footer?</b>	
4-1.	Header links template	4-2
4-2.	Call instruction	4-3
4-3.	Footer tab code example	4-4

---

<b>5</b>	<b>How Do I Remove Information From A Page?</b>	
5-1.	Section comment to locate	5-2
5-2.	Table heading example	5-2
5-3.	Table cell example	5-3

---

<b>6</b>	<b>How Do I Add A Map Or Other Information To A Location?</b>	
6-1.	Example code for building hyperlink	6-2
6-2.	Example code for adding path statement	6-4
6-3.	Example of call for locMapLink	6-4

---

---

## Figures

---

### 7      **How Do I Create An External Search From A Bibliographic Record Display?**

- |      |   |     |
|------|---|-----|
| 7-1. | Sample code to extract ISBN from bibliographic record | 7-2 |
| 7-2. | Define isbnSearch.xsl location example                | 7-4 |
| 7-3. | Call for isbnSearch.xsl in displayFacets.xsl          | 7-4 |

---

### 8      **How Do I Dynamically Disable Limits And Change Search Tips Based On The Selected Search Index?**

- |      |                                  |     |
|------|----------------------------------|-----|
| 8-1. | Example code for searchBasic.js  | 8-2 |
| 8-2. | Example <div> element            | 8-6 |
| 8-3. | Locate buildBasicSearch template | 8-7 |

---

### 9      **How Do I Disable AutoComplete?**

- |      |   |     |
|------|---|-----|
| 9-1. | Example of autocomplete="off" code            | 9-2 |
| 9-2. | Additional example of autocomplete="off" code | 9-3 |

---

### 10      **How Do I Display A Favicon?**

- |       |  |      |
|-------|--|------|
| 10-1. | Example favicon code for frameWork.xsl | 10-2 |
|-------|--|------|

---

### 11      **How Do I Hide Limits On The Advanced Search Page?**

- |       |   |      |
|-------|---|------|
| 11-1. | Example code for searchAdvanced.js                | 11-2 |
| 11-2. | Example code for searchAdvanced.css               | 11-4 |
| 11-3. | Example coding change for cl_searchAdvanced.xsl   | 11-5 |
| 11-4. | Additional coding change to cl_searchAdvanced.xsl | 11-5 |

---

## Figures

---

### **12      How Do I Build And Display A Persistent Link To A Bibliographic Record?**

- |   |      |
|---|------|
| 12-1. Sample code for local_PersistentLink.xsl                    | 12-2 |
| 12-2. Include file reference example                              | 12-3 |
| 12-3. Persistent link template call in Bibliographic Data section | 12-4 |

---

### **13      How Do I Change The Format Of The Record Display Page?**

- |   |      |
|---|------|
| 13-1. Class attribute creation example        | 13-2 |
| 13-2. Example code to add to buildMarcDisplay | 13-3 |
| 13-3. Example code for displayRecord.css      | 13-4 |

---

### **14      How Do I Add Tracking Codes?**

- |   |      |
|---|------|
| 14-1. Example of script snippet add to buildFooter template | 14-2 |
|---|------|

---

### **15      How Do I Implement Google Book Search?**

- |  |      |
|--|------|
| 15-1. Action Box text                                | 15-2 |
| 15-2. Line of code to locate                         | 15-4 |
| 15-3. Comment out code to disable Google Book Search | 15-4 |

---

### **16      How Do I Display Cover Images From Services Like Amazon.com and Syndetics Solutions?**

- |  |      |
|--|------|
| 16-1. Example of pageProperties.xml              | 16-2 |
| 16-2. Example of buildResultsCoverImage template | 16-3 |
| 16-3. Example of trimData template               | 16-4 |
| 16-4. Example of imageUtils.js                   | 16-5 |
| 16-5. Example displaycfg.xml code                | 16-6 |

---

## Figures

**DRAFT**

---

## Procedures

- 
- |          |   |     |
|----------|---|-----|
| <b>3</b> | <b>How Do I Build A Separate Display For Serials?</b> |     |
|          | 3-1. Building Separate Display for Serials            | 3-2 |
- 
- |          |   |     |
|----------|---|-----|
| <b>4</b> | <b>How Do I Add Static Links To The Header Or Footer?</b> |     |
|          | 4-1. Creating Header Links                                | 4-2 |
|          | 4-2. Creating Footer Tabs                                 | 4-3 |
- 
- |          |   |     |
|----------|---|-----|
| <b>5</b> | <b>How Do I Remove Information From A Page?</b> |     |
|          | 5-1. Removing Information From a Page           | 5-2 |
- 
- |          |   |     |
|----------|---|-----|
| <b>6</b> | <b>How Do I Add A Map Or Other Information To A Location?</b>       |     |
|          | 6-1. Adding a Map to a Location and/or Other Applicable Information | 6-2 |
- 
- |          |  |     |
|----------|--|-----|
| <b>7</b> | <b>How Do I Create An External Search From A Bibliographic Record Display?</b> |     |
|          | 7-1. Create External Search From Bibliographic Record Display                  | 7-2 |
- 
- |          |   |     |
|----------|---|-----|
| <b>8</b> | <b>How Do I Dynamically Disable Limits And Change Search Tips Based On The Selected Search Index?</b> |     |
|          | 8-1. Disable Limits and Change Search Tips  | 8-2 |
-

---

## Procedures

- 
- |          |                                       |     |
|----------|---------------------------------------|-----|
| <b>9</b> | <b>How Do I Disable AutoComplete?</b> |     |
|          | 9-1. Disable AutoComplete             | 9-2 |
- 
- |           |                                    |      |
|-----------|------------------------------------|------|
| <b>10</b> | <b>How Do I Display A Favicon?</b> |      |
|           | 10-1. Display favicon              | 10-2 |
- 
- |           |  |      |
|-----------|--|------|
| <b>11</b> | <b>How Do I Hide Limits On The Advanced Search Page?</b> |      |
|           | 11-1. Hide Limits on the Advanced Search Page            | 11-2 |
- 
- |           |  |      |
|-----------|--|------|
| <b>12</b> | <b>How Do I Build And Display A Persistent Link To A Bibliographic Record?</b> |      |
|           | 12-1. Building Persistent Link to Bibliographic Record                         | 12-2 |
- 
- |           |   |      |
|-----------|---|------|
| <b>13</b> | <b>How Do I Change The Format Of The Record Display Page?</b> |      |
|           | 13-1. Add Class Attributes For Formatting                     | 13-2 |
- 
- |           |                                     |      |
|-----------|-------------------------------------|------|
| <b>14</b> | <b>How Do I Add Tracking Codes?</b> |      |
|           | 14-1. Add tracking codes            | 14-2 |
-

---

## Procedures

---

### 15      **How Do I Implement Google Book Search?**

15-1. Disable Google Book Search Feature

15-3

**DRAFT**

---

## Procedures

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page



---

## About This Document

---

### Purpose

The purpose of the *WebVoyage Architecture and Configuration User's Guide* is to describe WebVoyage files, their relationship, and configuration options by example.

Given the programming design used for the new user interface, there is considerable flexibility in customizing the online public access catalog (OPAC) to your preferences. Key to this customization is experience with coding cascading style sheets (CSS), XSL, XML, and/or JavaScript.

The design of this user's guide is intended for learn by example. As a result, the *WebVoyage Architecture and Configuration User's Guide* incorporates several chapters of specific "how to" instructions.

---

### Intended Audience

This document is intended for programmers who are customizing WebVoyage in CSS, XSL, XML, and/or JavaScript.

---

### Reason for Reissue

This is the first release of the *WebVoyage Architecture and Configuration User's Guide*.

Ex Libris (USA) Inc.  
See notice on first page

---

## Document Summary

---

- Chapter 1     [“Getting Started”](#)  
Chapter 1 describes the prerequisites for working with and customizing Voyager WebVoyage 7.0.
- Chapter 2     [“Architecture”](#)  
Chapter 2 provides an overview of the WebVoyage architecture.
- Chapter 3     [“How Do I Build A Separate Display For Serials?”](#)  
Chapter 3 describes how to build a separate display for serials.
- Chapter 4     [“How Do I Add Static Links To The Header Or Footer?”](#)  
Chapter 4 describes how to add static links to the header/footer area.
- Chapter 5     [“How Do I Remove Information From A Page?”](#)  
Chapter 5 describes how to remove information from a page.
- Chapter 6     [“How Do I Add A Map Or Other Information To A Location?”](#)  
Chapter 6 describes how to add a map or other information to a location.
- Chapter 7     [“How Do I Create An External Search From A Bibliographic Record Display?”](#)  
Chapter 7 describes how to create an external search.
- Chapter 8     [“How Do I Dynamically Disable Limits And Change Search Tips Based On The Selected Search Index?”](#)  
Chapter 8 describes how to dynamically disable limits and change search tips based on the selected search index.
- Chapter 9     [“How Do I Disable AutoComplete?”](#)  
Chapter 9 describes how to disable AutoComplete.
- Chapter 10    [“How Do I Display A Favicon?”](#)  
Chapter 10 describes how to create an icon for a browser tab or title bar display.
- Chapter 11    [“How Do I Hide Limits On The Advanced Search Page?”](#)  
Chapter 11 describes how to hide the limit options on an advanced search while, optionally, a user may click to see them.
- Chapter 12    [“How Do I Build And Display A Persistent Link To A Bibliographic Record?”](#)  
Chapter 12 describes how to dynamically build and display a persistent link to a bibliographic record.
- Chapter 13    [“How Do I Change The Format Of The Record Display Page?”](#)  
Chapter 13 describes how to add class attributes to the Detailed Display Page for improved formatting control.

Chapter 14	<a href="#">“How Do I Add Tracking Codes?”</a> Chapter 14 describes how to add tracking codes.
Chapter 15	<a href="#">“How Do I Implement Google Book Search?”</a> Chapter 15 provides instructions regarding the implementation of Google Book Search.
Chapter 16	<a href="#">“How Do I Display Cover Images From Services Like Amazon.com and Syndetics Solutions?”</a> Chapter 16 provides instructions for implementing Syndetics enhancements.
Index	The <a href="#">Index</a> is an alphabetical, detailed cross-reference of topics.

## **Conventions Used in This Document**

---

The following conventions are used throughout this document:

- Names of commands, variables, stanzas, files, and paths (such as `/dev/tmp`), as well as selectors and typed user input, are displayed in `constant width` type.
- Commands or other keyboard input that must be typed exactly as presented are displayed in **`constant width bold`** type.
- Commands or other keyboard input that must be supplied by the user are displayed in ***constant width bold italic*** type.
- System-generated responses such as error messages are displayed in `constant width` type.
- Variable portions of system-generated responses are displayed in *constant width italic* type.
- Keyboard commands (such as **Ctrl** and **Enter**) are displayed in **bold**.
- Required keyboard input such as “Enter **vi**” is displayed in **`constant width bold`** type.
- Place holders for variable portions of user-defined input such as ***ls -l filename*** are displayed in ***italicized constant width bold*** type.
- The names of menus or status display pages and required selections from menus or status display pages such as “From the **Applications** drop-down menu, select **System-wide**,” are displayed in **bold** type.
- Object names on a window's interface, such as the **Description** field, the **OK** button, and the **Metadata** tab, are displayed in **bold** type.
- The titles of documents such as *Acquisitions User's Guide* are displayed in *italic* type.

- 
- Caution, and important notices are displayed with a distinctive label such as the following:

**NOTE:**

Extra information pertinent to the topic.



**IMPORTANT:**

*Information you should consider before making a decision or configuration.*



**CAUTION:**

*Information you must consider before making a decision, due to potential loss of data or system malfunction involved.*



**TIP:**

*Helpful hints you might want to consider before making a decision.*

**RECOMMENDED:**

*Preferred course of action.*

**OPTIONAL:**

*Indicates course of action which is not required, but may be taken to suit your library's preferences or requirements.*

## **Document Reproduction/Photocopying**

---

Photocopying the documentation is allowed under your contract with Ex Libris (USA) Inc. It is stated below:

All documentation is subject to U.S. copyright protection. CUSTOMER may copy the printed documentation only in reasonable quantities to aid the employees in their use of the SOFTWARE. Limited portions of documentation, relating only to the public access catalog, may be copied for use in patron instruction.

## **Comment on This Document**

---

Please contact Customer Support to provide us with your feedback. For Customer Support contact information, see SupportWeb at:

**Ex Libris (USA) Inc.**  
See notice on first page

[http://www.exlibrisgroup.com/support\\_center.htm](http://www.exlibrisgroup.com/support_center.htm).

### **To Submit Comments by E-mail**

---

To submit comments by e-mail, please send your message to:  
[docmanager@exlibrisgroup.com](mailto:docmanager@exlibrisgroup.com)

**DRAFT**

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

**Contents**

<b>Purpose of this Chapter</b>	<b>1-1</b>
<b>Prerequisite Skills and Knowledge</b>	<b>1-1</b>
<b>Before You Begin</b>	<b>1-2</b>

**DRAFT**

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page



---

### Purpose of this Chapter

The purpose of this chapter is to describe what you need to get started to effectively work with/customize WebVoyage and use this guide.

---

### Prerequisite Skills and Knowledge

To use this document effectively, you should have a working knowledge of the following:

- Microsoft Windows operating environment.
- CSS.
- XML.
- XSL.
- JavaScript.
- Text editor(s) for working with CSS, XML, XSL, and so on.
- UNIX operating system commands and file system (depending on your environment).
- Basic MARC records formats.
- Local procedures.

---

## Before You Begin

---

Before you can begin, you need to do the following:

- Have the Voyager WebVoyage 7.0 and corresponding Voyager 7.0 integrated library system software installed.
- Have access to an internet browser on your PC.
- Obtain the URL and/or the IP and port address for accessing your instance of Voyager WebVoyage 7.0.
- Obtain your user ID and password for logging in to Voyager WebVoyage 7.0. For login steps, refer to the *WebVoyage Basic User's Guide*.
- Set up your PC to display Unicode-specific data as needed. See the *WebVoyage Basic User's Guide* for instructions.

DRAFT

---

## Contents

<b>WebVoyage Architecture Overview</b>	<b>2-1</b>
<b>Flowchart Example - myAccount Page</b>	<b>2-2</b>
• Flowchart Example Description	2-2
• .css Processing	2-4
<b>Page Components Example - Basic Search</b>	<b>2-5</b>

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

### WebVoyage Architecture Overview

---


The purpose of this section is to provide an overview description of the architecture of WebVoyage for displaying information.

WebVoyage has a modular design to control formatting for the broadest number of page displays.

To display search results, patron information, and other dynamically generated information, WebVoyage combines information from the Voyager database (or from an outside resource like Google<sup>TM</sup> Book Search) with formatting properties from the WebVoyage .css, .xsl, and .xml files to render a display page in HTML. See [Figure 2-1](#) on [page 2-2](#).

For a flowchart example of how these files work together, see [Flowchart Example - myAccount Page](#) on [page 2-2](#).

For an example and description of the HTML page components, see [Page Components Example - Basic Search](#) on [page 2-5](#).



---

**Figure 2-1. Display page build overview**

## **Flowchart Example - myAccount Page**

---

The purpose of this section is to describe and illustrate the relationship of the WebVoyage files used for building and displaying content using the myAccount page as an example.

### **Flowchart Example Description**

---

The content of this section describes the the flowchart example highlighted in [Figure 2-2 on page 2-4](#).

To build the display page for myAccount page, the primary .xsl file is used. For this example, it is the myAccount.xsl file that is used. The name of the .xsl file used for this process generally represents the page being built such as displayRecord.xsl. See the .xsl files located in /ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/.

#### **NOTE:**

Directory path references to xxxdb implies that you need to substitute your database path name; and where [skin] is referenced, substitute the path name

that is used at your site. The default skin path provided is en\_US as in the following:

```
/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/
```

The `myAccount.xsl` imports the following:

- `stdImports.xsl`.  
This is an important part of the page processing. Every page uses it. It imports `frameWork.xsl`.
- `cl_myAccount.xsl`.  
This is a key component. The `cl` stands for **content** layout.
- `myAccountLinks.xsl`.
- `myAccount.css`.

**NOTE:**

The file naming convention used is intentional to show relationships between files used to build the HTML page as with `myAccount.xsl`, `myAccountLinks.xsl`, `cl_myAccount.xsl`, and `myAccount.css`.

The `myAccount.xsl` calls the following templates which are used to construct every page:

- `buildHtmlPage`.
- `buildContent`.

The `frameWork.xsl` takes input from the following components:

- `.xml` files.
- `.js` files.
- `.css` files.
- `buildHtmlPage` template.
- Timeout mechanism.

And subsequently, the `frameWork.xsl` generates HTML output with the following page components:

- Header.
- Main content based on the `buildContent` template.
- Footer.

For more information regarding page components, see [Page Components Example - Basic Search](#) on [page 2-5](#).




Figure 2-2. Flowchart example for myAccount page

## .css Processing

Cascading Style Sheets (CSS) is a stylesheet language used to describe the presentation of a document. CSS is commonly used to apply style to web pages or more specifically colors, fonts, layout, and other aspects of document presentation. These are processed in a specified priority scheme or hierarchy that determines which style rules apply. As a result, pieces of one stylesheet may be overridden by another stylesheet.



In WebVoyage, the baseline defaults are provided by the following `.css` files that are used by almost every page that is generated:

1. `frameWork.css`.
2. `header.css`.
3. `quickSearchBar.css`.
4. `pageProperties.css`.

In the above hierarchy, the items #1 through #3 have a higher priority scheme and take precedence while `pageProperties.css` provides overriding characteristics to #1 through #3. Specific page `.css` files like `myAccount.css` always override the baseline defaults.

Variations in a specific page `.css` file only applies to that page. For more global changes like a font change for all pages, the files controlling the baseline defaults need to be modified.



**TIP:**

*A tool like Mozilla® Firebug enables you to view these variations/interactions and edit/debug CSS, JavaScript, and so on live in any web page.*


## Page Components Example - Basic Search

---

As described, each page includes the following major components:

- Header.
- Footer.
- Main content.

See [Figure 2-3](#).



**Figure 2-3. Page components**

Any element of WebVoyage that is used by multiple pages such as the footer component, the search navigation bar, or the login link is defined independently of the pages on which they appear. An independent definition allows the element to be called by any and every page. This provides greater flexibility; but as a result, there isn't a single .xsl stylesheet for each page that WebVoyage renders.

The page shown in [Figure 2-3](#) is built with the following files that are used by all pages.

- `frameWork.xsl`.
- `constants.xsl`.
- `tools.xsl`.
- `formInput.xsl`.
- `constantStrings.xsl`.
- `frameWork.css`.
- `header.css`.
- `quickSearchBar.css`.
- `pageProperties.css`.

In addition, the **Basic Search** page uses the following:

- `cl_searchBasic.xsl`.

- `searchFacets.xsl`.
- `searchPages.css`.
- `searchBasic.css`.
- `pageInputFocus.js`.

Specific to the **Basic** tab, it uses the following:

- The font family is from `frameWork.css`.
- The font size, color, weight, and alignment of the tab label are from the `searchPages.css`.
- The font size, color, weight, and alignment of the tab contents such as Limit To are from `frameWork.css`.
- The font family, size, color, weight, and alignment of the search tips are from `pageProperties.css`.
- The text values are from `webvoyage.properties`.
- The images that make up the **Basic** tab are from the `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/images/` directory.
- The cursor placement is determined by `pageInputFocus.js`.

In summary, this example illustrates the hierarchy described in [Flowchart Example - myAccount Page](#) on [page 2-2](#) where baseline defaults are used in combination with page-specific, overriding controls for formatting that includes the following:

- Fonts.
- Color.
- Images.
- Content placement on the page.
- And so on.

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Build A Separate Display For Serials?

# 3

---

### Contents

Description For “How Do I Build A Separate Display For Serials?” Example	3-1
Files	3-1
Instructions	3-1

**DRAFT**

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Build A Separate Display For Serials?

# 3

---

### Description For “How Do I Build A Separate Display For Serials?” Example

By default, WebVoyage uses a single `displaycfg.xml` file to display all MARC bibliographic records.

The instructions for this example allow you to create and use a separate configuration file for serials based on the MARC leader value.

This model can also be used to create different MARC views for any material type.

### Files

The example in this chapter uses the following files:

- `sdisplaycfg.xml` (new for this example).
- `cl_displayRecord.xml`.

### Instructions

This section provides the instructions for creating the example described in this chapter.



### Procedure 3-1. Building Separate Display for Serials

Use the following procedure to build a separate display for serials.

**NOTE:**

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

`/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/`

1. Create and save a new file in the `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/contentLayout/configs/` directory named `sdisplaycfg.xml` to be used to specify the display fields for your serials records. Use the sample lines of code shown in [Figure 3-1](#) for this example.

```
#(c)#####
#(c)#
#(c)#      Copyright 2008 ExLibris Group
#(c)#      All Rights Reserved
#(c)#
#(c)#####
-->
<!--
**      Product : WebOpac : displaycfg
**      Version : 7.0
**      Created : 17-OCT-2007
**      Orig Author : David Sellers
**      Last Modified : 11-APR-2008
**Last Modified By: ASP

-->
<display>

      <titleTags>
```

**Figure 3-1. Sample line of code for sdisplaycfg.xml**



```
<displayTag field="245" indicator1="X" indicator2="X"
  subfield="ab" />
</titleTags>

<displayTags label="Title:">
  <displayTag field="245" indicator1="X" indicator2="X"
    subfield="abcfknps" />
</displayTags >

<displayTags label="Also Called:">
  <displayTag field="246" indicator1="X" indicator2="X"
    subfield="abfnp" />
</displayTags >

<displayTags label="Continues:">
  <displayTag field="780" indicator1="0" indicator2="0"
    subfield="at" />
  <displayTag field="780" indicator1="0" indicator2="1"
    subfield="at" />
</displayTags >

<displayTags label="Supersedes:">
  <displayTag field="780" indicator1="0" indicator2="2"
    subfield="at" />
  <displayTag field="780" indicator1="0" indicator2="3"
    subfield="at" />
</displayTags >

<displayTags label="Publisher:">
  <displayTag field="260" indicator1="X" indicator2="X"
    subfield="abc" />
</displayTags>

<displayTags label="ISSN:">
  <displayTag field="022" indicator1="X" indicator2="X"
    subfield="a" />
</displayTags>

<displayTags label="Format:">
  <displayTag field="000" indicator1="0" indicator2="6"
    subfield="2" />
</displayTags>
```

**Figure 3-1. Sample line of code for sdisplaycfg.xml (Continued)**

---

```

<displayTags label="Subjects:">
  <displayTag field="600" indicator1="X" indicator2="X"
    subfield="abcdefghijklmnopqrstuvxyz">
    <subfield value="v" preText="--"/>
    <subfield value="x" preText="--"/>
    <subfield value="y" preText="--"/>
    <subfield value="z" preText="--"/>
  </displayTag>
</displayTags>

<displayTags label="Online Journal:">
  <displayTag field="3000"/>
</displayTags>

<displayTags label="Holdings Information" notFound="No holdings available -
- check at the Circulation Desk.">
  <displayTag field="9000"/>
</displayTags>

</display>

```

**Figure 3-1. Sample line of code for `sdisplaycfg.xml` (Continued)**

2. Make a backup copy of `cl_displayRecord.xsl` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/contentLayout/`.
3. Edit `cl_displayRecord.xsl`.
  - a. Add a document holders declaration (see [Figure 3-3](#)) after the lines of code shown in [Figure 3-2](#).

---

```

<!-- ## Our Document Holders ## -->
<xsl:variable name="MConfig" select="document('./configs/displaycfg.xml')"/>

```

**Figure 3-2. Preceding lines of code**

```
<!-- added for serial config display -->
<xsl:variable name="SConfig" select="document('./configs/sdisplaycfg.xml')"/>
<xsl:variable name="recType" select="substring($bibRecord/hol:marcRecord/
slim:leader,8,1)" />
```

**Figure 3-3. Document holders declaration to add**

- b. Add logic for looking at the record leader by replacing the lines of code seen in [Figure 3-4](#) with the example lines of code in [Figure 3-5](#).

```
<!-- ## Bibliographic Data ## -->
<xsl:for-each select="$Config">
  <div
    class="bibliographicData">
      <xsl:call-template
        name="buildMarcDisplay">
          <xsl:with-
            param name="recordType" select="'bib'"/>
        </xsl:call-template>
      </div>
    </xsl:for-each>
```

**Figure 3-4. Lines to be replaced**

```
<!-- ## Bibliographic Data ## -->
<xsl:choose>
  <xsl:when test="$recType='s'">
    <xsl:for-each select="$SConfig">
      <div class="bibliographicData">
        <xsl:call-template name="buildMarcDisplay">
          <xsl:with-param name="recordType"
            select="'bib'"/>
        </xsl:call-template>
      </div>
    </xsl:for-each>
  </xsl:when>
</xsl:choose>
```

**Figure 3-5. Replacement lines of code**

---

```

        <br />Record type:&#160;<xsl:value-of
select="$recType" />

    </div>
</xsl:for-each>
</xsl:when>

<xsl:otherwise >
    <xsl:for-each select="$MConfig">
        <div class="bibliographicData">
            <xsl:call-template name="buildMarcDisplay">
                <xsl:with-param name="recordType"
select="'bib'" />
            </xsl:call-template>

            <br />Record type:&#160;<xsl:value-of
select="$recType" />

        </div>
    </xsl:for-each>

</xsl:otherwise>
</xsl:choose>

```

**Figure 3-5. Replacement lines of code (Continued)**

4. Save and test the changes you made to `cl_displayRecord.xml`.

**OPTIONAL:**

5. *Back out your changes, if necessary, by deploying your backup copy of `cl_displayRecord.xml`.*
-

---

# How Do I Add Static Links To The Header Or Footer?

4

---

## Contents

Description For “How Do I Add Static Links To The Header Or Footer?” Example	4-1
Files	4-1
Instructions	4-1

DRAFT

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Add Static Links To The Header Or Footer?

# 4

---

### Description For “How Do I Add Static Links To The Header Or Footer?” Example

---

Both the header and footer page elements can accommodate links to external web sites, web applications, and so forth.

In this chapter, the header example demonstrates hyperlinks; and the footer example demonstrates adding a new tab.

### Files

---

The examples in this chapter use the following files:

- header.xml.
- footer.xml.

### Instructions

---

This section provides the instructions for creating the examples described in this chapter.



## Procedure 4-1. Creating Header Links

Use the following procedure to create header links.

### NOTE:

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

```
/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/
```

1. Make a backup copy of the `header.xml` file that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xml/pageFacets/`.
2. Edit the `header.xml` file to add a new template.
  - a. Add your template (see [Figure 4-1](#)) immediately before the `<xsl:stylesheet>` element at the bottom of the file.

```
<!-- #####  
-->  
<!-- ## buildHeaderLinks ##  
-->  
<!-- #####-->  
<xsl:template name="localHeaderLinks">  
  <div id="headerLinks" style="font-family:Arial;font-size:.70em;">  
    <span style="color:#9F175E;padding: 0 .20em;margin:0 .2em;">University  
      Library Catalog</span>  
    <a href="#" style="padding: 0 .20em;margin:0 .2em;">My library</a>  
    <a href="#" style="padding: 0 .20em;margin:0 .2em;">SFX</a>  
    <a href="#" style="padding: 0 .20em;margin:0 .2em;">Primo</a>  
    <a href="#" style="padding: 0 .20em;margin:0 .2em;">Chat with a librarian</a>
```

Figure 4-1. Header links template



```

</div>
</xsl:template>
<!-- ##### -->
<!-- ##### -->

```

**Figure 4-1. Header links template (Continued)**

- b. Call the template that you created in Step [a](#) by adding the instruction (see [Figure 4-2](#), line 7) to the buildHeader section located at the top of the header.xsl file.

Line#	
1	<!-- ##### -->
2	<!-- ## buildHeader ## -->
3	<!-- ##### -->
4	
5	<xsl:template name="buildHeader">
6	<xsl:for-each select="/page:page/page:pageHeader">
7	<xsl:call-template name="localHeaderLinks" />
8	<div id="headerRow">
9	<div id="logo" title="{ \$headerText/logo} ">

**Figure 4-2. Call instruction**

3. Save and test your changes to header.xsl.

**OPTIONAL:**

4. Back out your changes, if necessary, by deploying your backup copy of header.xsl.



**Procedure 4-2. Creating Footer Tabs**

Use the following procedure to create a footer tab.

**NOTE:**

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

`/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/`

1. Make a backup copy of the `footer.xml` file that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xml/pageFacets/`.
2. Edit the `footer.xml` file to add a new tab by adding the new tab code (see [Figure 4-3](#), lines 15 -19) after the `<ul class="navbar">` in the `buildFooter` section in the file.

Line#

```
1 <!-- ##### -->
2 <!-- ## buildFooter ## -->
3 <!-- ##### -->
4
5 <xsl:template name="buildFooter">
6
7     <xsl:for-each select="/page:page/page:pageFooter">
8         <div id="pageFooter">
9             <xsl:for-each
10                select="page:tabs[@nameId='page.footer.buttons']">
11
12                 <div id="footerTabs" title="{ $footerText/footerTabs }">
13                     <a name="navFooter"></a>
14                     <h2 class="navFooter"><xsl:value-of select="$footerText/
15 footerTabs"/></h2>
16                     <ul class="navbar">
17 <!-- extra footer tabs -->
18 <li>
19 <a href="http://www.exlibrisgroup.com/" target="_newWin">Ex Libris<
20 a>
21 </li>
22 <!-- end extra footer tabs -->
23
24                     <xsl:for-each select="$Configs/pageConfigs/
25 footerTabDisplayOrder/tab">
```

**Figure 4-3. Footer tab code example**

3. Save and test your changes to `footer.xml`.

**OPTIONAL:**

4. *Back out your changes, if necessary, by deploying your backup copy of `footer.xml`.*
- 

**DRAFT**

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

# How Do I Remove Information From A Page?

5

---

## Contents

Description For “How Do I Remove Information From A Page?” Example	5-1
Files	5-1
Instructions	5-1

DRAFT

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Remove Information From A Page?

# 5

---

### Description For “How Do I Remove Information From A Page?” Example

There may be some page elements you want to disable or prevent from displaying. This example describes how to remove the **Item Type** column from the **Charged Items** table on the **My Account** page.

#### NOTE:

It's important to remove all the relevant pieces of a page element. In this example, the instructions comment out both the heading and table cell pieces of the **Item Type** column. Commenting out only one isn't sufficient.

### Files

The example in this chapter uses the `cl_myAccount.xml` file.

### Instructions

This section provides the instructions for completing the example described in this chapter.



## Procedure 5-1. Removing Information From a Page

Use the following procedure to remove information from a page.

### NOTE:

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

```
/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/
```

1. Make a backup copy of `cl_myAccount.xsl` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/contentLayout/`.
2. Edit `cl_myAccount.xsl`.
  - a. Find the `displayChargedItems` template section marked by the comment shown in [Figure 5-1](#).

```
<!-- ##### -->
<!-- ## displayChargedItems ## -->
<!-- ##### -->
<xsl:template name="displayChargedItems">
```

**Figure 5-1. Section comment to locate**

- b. Comment out the table heading and table cell lines of code relevant to item type. See [Figure 5-2](#) and [Figure 5-3](#).

```
<!-- <th id="cellChargedType"><xsl:value-of select="page:element/
      page:heading[@nameId='type']"/></th> -->
```

**Figure 5-2. Table heading example**



```
<!-- <td id="tableCell" headers="cellChargedType"><xsl:value-of  
      select="page:itemType"/>&#160;</td> -->
```

---

**Figure 5-3. Table cell example**

---

3. Save and test your changes.

**OPTIONAL:**

4. *Back out your changes, if necessary, by deploying your backup copy of*  
`cl_myAccount.xsl`.

**DRAFT**

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

**How Do I Add A Map Or Other  
Information To A Location?**

**6**

---

**Contents**

<b>Description For “How Do I Add A Map Or Other Information To A Location?” Example</b>	<b>6-1</b>
<b>Files</b>	<b>6-1</b>
<b>Instructions</b>	<b>6-1</b>

**DRAFT**

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Add A Map Or Other Information To A Location?

# 6

---

### Description For “How Do I Add A Map Or Other Information To A Location?” Example

---

This example allows you to direct your patrons to add a map to a location and/or other applicable information like the hours of the reading room. The information offered is based on the MFHD location (852 |b).

### Files

---

The example in this chapter uses the following files:

- local\_locMapLink.xml (new for this example).
- display.xml.

### Instructions

---

This section provides the instructions for creating the example described in this chapter.



---

## Procedure 6-1. Adding a Map to a Location and/or Other Applicable Information

---

Use the following procedure to add a map to a location and/or other applicable information.

### NOTE:

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

```
/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/
```

1. Create and save a new file in the `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/contentLayout/` directory named `local_locMapLink.xsl` to define how to build the hyperlink. Use the sample lines of code shown in [Figure 6-1](#) for this example.

### NOTE:

Notice the template name `locMapLink` in this example.

```
<!--
**          Note: sample link to map based on loc code
**          Version : 1.0
**          Created : 16-Nov-2007
**          Created By : EJW
-->

<xsl:stylesheet version="1.0"
    xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
    xmlns:page="http://www.exlibrisgroup.com/voyager/webvoyage/
        page"
    xmlns:fo="http://www.w3.org/1999/XSL/Format">

<!-- ##### --
>
```

---

**Figure 6-1. Example code for building hyperlink**

---

```
<xsl:template name="locMapLink">
<xsl:param name="mfhd"/>
  <xsl:variable name="locCode">
    <xsl:call-template name="BMDProcessMarcTags">
      <xsl:with-param name="field" select="'852'"/>
      <xsl:with-param name="indicator1" select="'X'"/>
      <xsl:with-param name="indicator2" select="'X'"/>
      <xsl:with-param name="subfield" select="'b'"/>
      <xsl:with-param name="mfhdID" select="$mfhd"/>
      <xsl:with-param name="recordType" select="'mfhd'"/>
    </xsl:call-template>
  </xsl:variable>

  <!-- you must create your web site to display maps -->
  <xsl:variable name="baseURL">http://www.exlibrisgroup.com/
?loc=</xsl:variable>

  <div class="locationMap">
    Show me a<#160;<a id="locMap"
href="{ $baseURL } { $locCode }" target="_new">map</a>.
  </div>

</xsl:template>

<!-- ##### -->
</xsl:stylesheet>
```

**Figure 6-1. Example code for building hyperlink (Continued)**

2. Make a backup copy of display.xsl that is located in /ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/contentLayout/display/.


---

3. Edit `display.xsl`.

- a. Add a statement at the top of the `display.xsl` file that contains the path to the `local_locMapLink.xsl` file. See [Figure 6-2](#).

---

```
<xsl:import href="../display/marc21slim.xsl"/>
<xsl:import href="../configs/104X_display.xsl"/>
<xsl:import href="../local_locMapLink.xsl"/>
```



**Figure 6-2.** Example code for adding path statement

- b. Call the `locMapLink` template from within the `BMD100` template. See [Figure 6-3](#).

---

```
<!--##### -->

<xsl:template name="BMD100">
<xsl:param name="mfhdID"/>

  <xsl:for-each select="$HoldXML/holdingsRecord/holdings/mfhdCollection/
mfhd:mfhdRecord[@mfhdID = $mfhdID]/
mfhd:mfhdData[@name='locationDisplayName']">
    <xsl:if test="string-length(.)">
      <xsl:value-of select="."/>
      <!-- ## add a map link ## -->
      <xsl:call-template name="locMapLink" >
        <xsl:with-param name="mfhd" select="$mfhdID"/>
      </xsl:call-template>
      <br/>
    </xsl:if>
  </xsl:for-each>
</xsl:template>

<!-- ##### -->
```



**Figure 6-3.** Example of call for `locMapLink`

4. Save and test your changes.



**OPTIONAL:**

5. *Back out your changes, if necessary, by deploying your backup copy of display.xml.*
- 

**DRAFT**

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

# **How Do I Create An External Search From A Bibliographic Record Display?**

# 7

---

## **Contents**

<b>Description For “How Do I Create An External Search From A Bibliographic Record Display?” Example</b>	<b>7-1</b>
<b>Files</b>	<b>7-1</b>
<b>Instructions</b>	<b>7-2</b>

**DRAFT**

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

# How Do I Create An External Search From A Bibliographic Record Display?

# 7

---

## Description For “How Do I Create An External Search From A Bibliographic Record Display?” Example

It is common to use the ISBN as a parameter to a new search in a different application such as Amazon.com<sup>®</sup>, WorldCat<sup>®</sup>, and so on.

The instructions in this chapter describe how to parse out the ISBN from a bibliographic record display and insert it into a URL.

The URL is displayed in the Action Box on the item display page.

This model can also be used to extract different pieces of the MARC record and construct different or multiple URLs.

## Files

The example in this chapter uses the following files:

- isbnSearch.xsl (new for this example).
- displayFacets.xsl.

---

## Instructions

---

This section provides the instructions for creating the example described in this chapter.



### Procedure 7-1. Create External Search From Bibliographic Record Display

---

Use the following procedure to create an external search from a bibliographic record display.

**NOTE:**

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

```
/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/
```

1. Create and save a new file in the `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/pageFacets/` directory named `isbnSearch.xsl` to be used to specify how to extract the ISBN from the bibliographic record. Use the sample lines of code shown in [Figure 7-1](#) for this example.

**NOTE:**

Notice the template name `recordIsbnSearch` in this example.

```
<?xml version="1.0" encoding="UTF-8"?>

<!--
**          Note: Creates a link to WorldCat using the ISBN
**          Version : 1.0
**          Created : 15-APR-08
**          Created By : ASP
-->
```

---

**Figure 7-1. Sample code to extract ISBN from bibliographic record**

---

```

<xsl:stylesheet version="1.0"
    xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
    xmlns:page="http://www.exlibrisgroup.com/voyager/webvoyage/
page"
    xmlns:fo="http://www.w3.org/1999/XSL/Format">

<!-- ##### --
>

<xsl:template name="recordIsbnSearch">
    <xsl:variable name="isbn">
        <xsl:call-template name="BMDProcessMarcTags">
            <xsl:with-param name="field" select="'020'"/>
            <xsl:with-param name="indicator1" select="'X'"/>
            <xsl:with-param name="indicator2" select="'X'"/>
            <xsl:with-param name="subfield" select="'a'"/>
            <xsl:with-param name="mfhdID" select="$bibID"/>
            <xsl:with-param name="recordType" select="'bib'"/>
        </xsl:call-template>
    </xsl:variable>

    <a target="_blank">
        <xsl:attribute name="href">http://worldcatlibraries.org/XXXX/isbn/
        <xsl:value-of select="$isbn"/>&amp;loc=united+states</
        xsl:attribute>
        Check Other Local Libraries</a>

    </xsl:template>
</xsl:stylesheet>

```

**Figure 7-1. Sample code to extract ISBN from bibliographic record (Continued)**

2. Make a backup copy of displayFacets.xsl that is located in /ml/voyager/xxxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/pageFacets/.
3. Edit displayFacets.xsl.
  - a. Define where the isbnSearch.xsl can be found with a line of code immediately after the namespace declarations. See [Figure 7-2](#).

---

```

<xsl:stylesheet version="1.0"
    xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
    xmlns:page="http://www.exlibrisgroup.com/voyager/webvoyage/
page"
    xmlns:fo="http://www.w3.org/1999/XSL/Format">

    <xsl:include href="./isbnSearch.xsl"/>

```



**Figure 7-2. Define isbnSearch.xsl location example**

- b. Call the template defined in isbnSearch.xsl.

For this example, it is added to the bottom of the Action Box.

Working from the end of the file, add the call before the final </div>. See [Figure 7-3](#).

---

```

<!--/ul-->
<!-- ## add the other libraries search ## -->
    <xsl:call-template name="recordIsbnSearch" />


</div>
</xsl:for-each>

</xsl:template>

<!-- ##### -->

</xsl:stylesheet>

```



**Figure 7-3. Call for isbnSearch.xsl in displayFacets.xsl**

4. Save and test your changes.



**OPTIONAL:**

5. *Back out your changes, if necessary, by deploying your backup copy of displayFacets.xsl.*
- 

**DRAFT**

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

# How Do I Dynamically Disable Limits And Change Search Tips Based On The Selected Search Index?

# 8

---

## Contents

Description For “How Do I Dynamically Disable Limits And Change Search Tips Based On The Selected Search Index?” Example	8-1
Files	8-1
Instructions	8-2

**DRAFT**

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Dynamically Disable Limits And Change Search Tips Based On The Selected Search Index?

# 8

---

### Description For “How Do I Dynamically Disable Limits And Change Search Tips Based On The Selected Search Index?”

#### Example

---

The **Basic Search** page includes a **Limit To** dropdown list that is compatible with keyword searches. The instructions in this chapter explain how to install a JavaScript that disables the **Limit To** dropdown list when you select an index that is incompatible with limits such as headings and call number.

The JavaScript also changes the search tips displayed to the user based on the index selected. This provides you with the option to offer hints on improving search strategies.

#### Files

---

The example in this chapter uses the following files:

- `searchBasic.js` (new for this example).
- `cl_searchBasic.xsl`.
- `pageProperties.xml`.

---

## Instructions

---

This section provides the instructions for creating the example described in this chapter.



### Procedure 8-1. Disable Limits and Change Search Tips

---

Use the following procedure to disable limits and change search tips dynamically based on the selected search index.

**NOTE:**

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

```
/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/
```

1. Create and save a new JavaScript file in the `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/js/scripts/` directory named `searchBasic.js` to be used to disable the quick limits dropdown list. Use the sample lines of code shown in [Figure 8-1](#) for this example.

```
/*
#(c)#=====
#(c)#
#(c)# Copyright 2007 ExLibris Group
#(c)# All Rights Reserved
#(c)#
#(c)#=====
** Product : WebVoyage :: disable/enable limits on basic search, adjust search
           tips
** Version : 7.0
** Created : 23-JAN-2008
** Orig Author : EJW
```

---

**Figure 8-1.** Example code for `searchBasic.js`

---

```
** Last Modified : 18-APR-2008
** Last Modified By : ASP
*/

////////////////////////////////////
function updateSearchTip ()
{
    // added to searchCode.onchange to customize search tip based on
    index

    // save the default search tip the first time through
    defaultTip = window.defaultTip ||
    document.getElementById('customSearchTip').innerHTML;

    currentSearchCode = document.getElementById('searchCode').value

    switch (currentSearchCode)
    {
    case 'CMD':
    case 'CMD*':
        document.getElementById('customSearchTip').innerHTML =
        "build a simple Boolean search: <span class=\"example\">(cats or
        dogs) and therapy</span>"
        break;

    case 'NAME+':
    case 'AUTH+':
        document.getElementById('customSearchTip').innerHTML =
        "search by personal or corporate author: last name first <span
        class=\"example\">pessl marisha</span>, or company name <span
        class=\"example\">jung seed</span>"
        break;

    case 'CALL+':
        document.getElementById('customSearchTip').innerHTML =
        "enter as much of the call number that you know: <span
        class=\"example\">PR 1297</span>"
        break;

    default:
```

**Figure 8-1. Example code for searchBasic.js (Continued)**

```

        // use the default tip if not otherwise overridden
        document.getElementById('customSearchTip').innerHTML =
        defaultTip;
    }

}

function searchCodeChanged ()
{
    /*
    ** Disable the limits drop for searches that do not support it.
    */

    currentSearchCode =
        document.getElementById('searchCode').value.substring(0,4);

    if (!document.getElementById('limitTo').disabled) {
        currentLimit = document.getElementById('limitTo').value;
    }

    switch(currentSearchCode)
    {
        {
            // OPAC HEADING INDEXES
            case 'SUBJ':
            case 'TITL':
            case 'NAME':
            case 'AUTH':
            // MAIN CALL NUMBER INDEX
            case 'CALL':
            // JOURNAL INDEX WITH PRELIMITS
            case 'JKEY':
            case 'JALL':

            document.getElementById('limitTo').value="none";
            document.getElementById('limitTo').disabled=true;
            break;

```

**Figure 8-1. Example code for searchBasic.js (Continued)**



```
default:
    document.getElementById('limitTo').disabled=false;
    document.getElementById('limitTo').value=currentLimit;
}

}

function addSearchCodeChanged ()
{
    document.getElementById('searchCode').onchange = function()
    {searchCodeChanged(); updateSearchTip();}

    // run the script to catch default index doesn't support limits
    or edit search
    searchCodeChanged ();
    updateSearchTip();
}

function addLoadEvent(func) {
    var oldonload = window.onload;
    if (typeof window.onload != 'function') {
        window.onload = func;
    } else {
        window.onload = function() {
            if (oldonload) {
                oldonload();
            }
            func();
        }
    }
}

addLoadEvent (addSearchCodeChanged);
```

**Figure 8-1. Example code for searchBasic.js (Continued)**

2. Make a backup copy of `pageProperties.xml` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/userTextConfigs/`.
3. Edit `pageProperties.xml`.

---

Locate the comment `<!-- ## Start Search Tips ## -->` and identify the `<page name="page.searchBasic" position="belowContent">` element.

Add a `<div>` element as in [Figure 8-2](#).

```
<page name="page.searchBasic" position="belowContent">
  <div class="searchTip">
    <span class="label">Search Tips: </span>
    <!-- special div to enable javascript to swap out help text -->
    <div id="customSearchTip" style="display:inline">
      enter words relating to your topic, use quotes to search
      phrases: <span class="example">"world wide web"</span>,
      use + to mark essential terms: <span
      class="example">+explorer</span>,
      use * to mark important terms: <span
      class="example">*internet</span>,
      use ? to truncate: <span class="example">browser?</span>
    </div>
  </div>
</page>
```

---

**Figure 8-2. Example `<div>` element**

4. Save your changes.
5. Make a backup copy of `cl_searchBasic.xml` that is located in `/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xml/contentLayout/`.
6. Edit `cl_searchBasic.xml`.

At the end of the `buildBasicSearch` template (see [Figure 8-3](#)), load the `searchBasic.js` JavaScript file you created.

```
<!-- ##### -->
<!-- ## buildSearchForm ## -->
<!-- ##### -->

<xsl:template name="buildBasicSearch">

  <div id="searchParams">
    <div id="searchInputs">
      <xsl:call-template name="buildFormInput">
        <xsl:with-param name="eleName" select="'searchArg'"/>
        <xsl:with-param name="size" select="'51'"/>
        <xsl:with-param name="accesskey" select="'s'"/>
      </xsl:call-template>
      <xsl:call-template name="buildFormDropDown">
        <xsl:with-param name="eleName" select="'searchCode'"/>
      </xsl:call-template>
    </div>
    <div id="quickLimits">
      <xsl:call-template name="buildFormDropDown">
        <xsl:with-param name="eleName" select="'limitTo'"/>
      </xsl:call-template>
    </div>

    <!-- load javascript file for handling limits enable/disable -->
    <script type="text/javascript" src="{ $jscript-loc }searchBasic.js"/>
  </div>

  <xsl:call-template name="buildSearchButtons"/>
</xsl:template>

<!-- ##### -->
```

**Figure 8-3. Locate buildBasicSearch template**

7. Save and test your changes.

---

**OPTIONAL:**

8. *Back out your changes, if necessary, by deploying your backup copies of `pageProperties.xml` and `cl_searchBasic.xml`.*
- 

**DRAFT**

**Contents**

<b>Description For “How Do I Disable AutoComplete?”</b>	
<b>Example</b>	<b>9-1</b>
<b>Files</b>	<b>9-1</b>
<b>Instructions</b>	<b>9-1</b>

DRAFT

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Disable AutoComplete?

# 9

---

### Description For “How Do I Disable AutoComplete?” Example

---

AutoComplete is a feature of certain web browsers that stores information on the computer's hard drive that a user types into web page forms. When you begin filling in another form, the browser suggests possible answers from information stored on the hard drive.

Particularly at public workstations, you may want to disable the browser's AutoComplete capability. This is a feature of both Internet Explorer® and Firefox®.

### Files

---

The example in this chapter uses the following files:

- login.xml.
- searchFacets.xml.

### Instructions

---

This section provides the instructions for creating the example described in this chapter.



## Procedure 9-1. Disable AutoComplete

Use the following procedure to disable AutoComplete.

### NOTE:

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

`/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/`

1. Make a backup copy of `searchFacets.xml` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xml/pageFacets/`.
2. Edit `searchFacets.xml`.
  - a. Locate the `buildTheSearchForm` section near the top of the file.
  - b. Add `autocomplete="off"` to the `<form action>` element. See [Figure 9-1](#).

```
<form action="{ $formAction }" method="GET" accept-charset="UTF-8"
      id="{ $formName }" autocomplete="off">
```

**Figure 9-1. Example of `autocomplete="off"` code**

3. Save your changes.
4. Make a backup copy of `login.xml` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xml/`.
5. Edit `login.xml`.
  - a. Locate the `buildContent` section.
  - b. Add `autocomplete="off"` to the `<form action>` element. See [Figure 9-2](#).



```
<form action="{/page:page//page:element[@nameId='page.logIn.logIn.button']/  
page:buttonAction}" method="GET" accept-charset="UTF-8"  
name="selectDatabases" autocomplete="off">
```

---

**Figure 9-2. Additional example of autocomplete="off" code**

6. Save and test your changes.

**OPTIONAL:**

7. *Back out your changes, if necessary, by deploying your backup copies of `searchFacets.xsl` and/or `login.xsl`.*

**DRAFT**

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Display A Favicon?

# 10

---

### Contents

Description For “How Do I Display A Favicon?” Example	10-1
Files	10-1
Instructions	10-2

**DRAFT**

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

### Description For “How Do I Display A Favicon?” Example

---

In Internet Explorer and Firefox, a favicon (favorite icon) displays in the address bar, the favorites menu, bookmarks, and page tabs.

A favicon is a way to brand your catalog for your patrons.

#### **NOTE:**

There are multiple methods for installing a favicon. The method described in this chapter is specific to WebVoyage and allows you to use any type of image files such as .jpg, .gif, or .png in addition to favicon .ico files.

For further information regarding favicons, see the following sites:

- <http://msdn2.microsoft.com/en-us/library/ms537656.aspx>.
- [http://en.wikipedia.org/wiki/Shortcut\\_icon](http://en.wikipedia.org/wiki/Shortcut_icon).

### **Files**

---

The example in this chapter uses the `frameWork.xsl` file.

---

## Instructions

---

This section provides the instructions for creating the example described in this chapter.



### Procedure 10-1. Display favicon

---

Use the following procedure to display your favicon.

**NOTE:**

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

```
/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/
```

1. Create a 16x16 pixel icon.
2. Save the icon to the `/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/images/` directory.
3. Make a backup copy of `frameWork.xml` that is located in `/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xml/pageTools/`.
4. Edit `frameWork.xml`.
  - a. Locate the `buildHtmlPage` template.
  - b. Insert the example code shown in [Figure 10-1](#) after the `<head>` element.

```
<link rel="shortcut icon" href="{ $image-loc }favicon.ico" type="image/x-icon" />
<link rel="icon" href="{ $image-loc }favicon.ico" type="image/x-icon " />
```

---

**Figure 10-1. Example favicon code for frameWork.xml**

---

- c. Replace `favicon.ico` with the name of the icon file that you created at the beginning of this procedure and saved in `.../images/`.

**NOTE:**

By default, the `{ $image-loc }` notation is a path to the `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/images/` directory. This path is defined in `constants.xml`.

5. Save and test your changes.

**OPTIONAL:**

6. *Back out your changes, if necessary, by deploying your backup copy of `framework.xml`.*

---

**DRAFT**

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page



---

## How Do I Hide Limits On The Advanced Search Page?

# 11

---

### Contents

Description For “How Do I Hide Limits On The Advanced Search Page?” Example	11-1
Files	11-1
Instructions	11-1

**DRAFT**

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Hide Limits On The Advanced Search Page?

# 11

---

### Description For “How Do I Hide Limits On The Advanced Search Page?” Example

---

This chapter describes how to hide the various limits options on the **Advanced Search** page until a user clicks a **More** link to display them.

### Files

---

The example in this chapter uses the following files:

- `searchAdvanced.js` (new for this example).
- `searchAdvanced.css`.
- `cl_searchAdvanced.xsl`.

### Instructions

---

This section provides the instructions for creating the example described in this chapter.



## Procedure 11-1. Hide Limits on the Advanced Search Page

Use the following procedure to hide limits on the **Advanced Search** page.

### NOTE:

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

```
/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/
```

1. Create and save a new JavaScript file in the `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/jscripts/` directory named `searchAdvanced.js` to be used to hide limits on the **Advanced Search** page. Use the sample lines of code shown in [Figure 11-1](#) for this example.

```
/*
#(c)#=====
#(c)#
#(c)# Copyright 2007 ExLibris Group
#(c)# All Rights Reserved
#(c)#
#(c)#=====

** Product : WebVoyage :: disable/enable limits on advanced search
** not an accessible technique
** Version : 7.0
** Created : 23-JAN-2008
** Orig Author : EJW
** Last Modified : 23-JAN-2008
** Last Modified By : EJW
*/

// hide the limitList div
```

**Figure 11-1.** Example code for `searchAdvanced.js`

```
function hideLimits() {
    document.getElementById('limitList').style.display='none';
}

// display the limitList div
function showLimits() {
    document.getElementById('limitList').style.display='';
}

// toggle the limitList div
// we'll check the class of the toggle switch
function toggleLimits () {
    showLimits();
    document.getElementById('limitToggle').style.display='none';
}

function addLoadEvent(func) {
    var oldonload = window.onload;
    if (typeof window.onload != 'function') {
        window.onload = func;
    } else {
        window.onload = function() {
            if (oldonload) {
                oldonload();
            }
            func();
        }
    }
}

addLoadEvent(
    function () {
        // hide the the limits on page load and show the toggle
        switch
            hideLimits();
            document.getElementById('limitToggle').style.display='';
    });
```

**Figure 11-1. Example code for searchAdvanced.js (Continued)**

- 
2. Make a backup copy of `searchAdvanced.css` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/css/`.
  3. Edit `searchAdvanced.css`.

Go to the end of the file and add the example code shown in [Figure 11-2](#).

```
/* display link to show limits */
#limitToggle {
    font-size: smaller;
    font-family: Verdana;
    margin: 10px 10px 0.5em;
}
```

**Figure 11-2. Example code for `searchAdvanced.css`**

4. Save your changes.
5. Make a backup copy of `cl_searchAdvanced.xml` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xml/contentLayout/`.
6. Edit `cl_searchAdvanced.xml`.
  - a. Locate the `buildSearchForm` section.
  - b. Add a call to the `searchAdvanced.js` file immediately before the `<!-- line 6 - year label, radio button & selection box -->` comment. See [Figure 11-3](#).

```
<!-- add java script to hide/show limits on page -->

    <script type="text/javascript" src="{$_script-
loc}searchAdvanced.js"/>

    <div id="limitToggle" class="limitsOff"
style="display:none"><a href="javascript:toggleLimits();">more</
a></div>

    <div id="limitList">

    <!-- end - other end of limitList div was added below -->
```

**Figure 11-3. Example coding change for cl\_searchAdvanced.xml**

- c. Add the closing `<div>` element above the `buildSearchButtons` template at the bottom of the file. See [Figure 11-4](#).

```
    </xsl:for-each>
  </div>

  <xsl:call-template name="buildSearchButtons"/>

</div>
<!-- search advanced form - end -->
</xsl:template>
</xsl:stylesheet>
```

**Figure 11-4. Additional coding change to cl\_searchAdvanced.xml**

7. Save your changes and test.
8. Back out your changes, if necessary, by deploying your backup copies of `searchAdvanced.css` and `cl_searchAdvanced.xml`.

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page



---

## **How Do I Build And Display A Persistent Link To A Bibliographic Record?**

# 12

---

### **Contents**

<b>Description For “How Do I Build And Display A Persistent Link To A Bibliographic Record?” Example</b>	<b>12-1</b>
<b>Files</b>	<b>12-1</b>
<b>Instructions</b>	<b>12-1</b>

**DRAFT**

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

# How Do I Build And Display A Persistent Link To A Bibliographic Record?

# 12

---

## Description For “How Do I Build And Display A Persistent Link To A Bibliographic Record?” Example

---

Patrons can use the persistent link to bibliographic records for bookmarking, tagging, emailing, blogging, and so forth.

### Files

---

The example in this chapter uses the following files:

- `local_PersistentLink.xsl` (new for this example).
- `cl_displayRecord.xsl`.

### Instructions

---

This section provides the instructions for creating the example described in this chapter.



## Procedure 12-1. Building Persistent Link to Bibliographic Record

Use the following procedure to create a persistent link to a bibliographic record.

### NOTE:

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

`/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/`

1. Create and save a new file in the `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/pageFacets/` directory named `local_PersistentLink.xsl` to store the template that defines how to build the hyperlink. Use the sample lines of code shown in [Figure 12-1](#) for this example.

```
<?xml version="1.0" encoding="UTF-8"?>

<!--
**          Note: create persistent link based on bib ID
**          Version : 1.0
**          Created : 16-Nov-2007
**          Created By : EJJW
**          Last Modified : 14-Apr-2008
**          Last Modified By : ASP
-->

<xsl:stylesheet version="1.0"
xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
xmlns:page="http://www.exlibrisgroup.com/voyager/webvoyage/
page"
xmlns:fo="http://www.w3.org/1999/XSL/Format">

<!-- ##### -->
```

Figure 12-1. Sample code for `local_PersistentLink.xsl`

```
<xsl:template name="persistentLink">
<xsl:param name="bibID"/>

  <!-- :doc: you must set this to match your public URL -->
  <xsl:variable name="baseURL">http://xxx.xxx.xxx.xxx:7008/vwebv/
    holdingsInfo?bibId=</xsl:variable>

    <a id="persistentLink" href="{ $baseURL } { $bibID }" target="_new" >
      Persistent Link
    </a>

</xsl:template>

<!-- ##### -->

</xsl:stylesheet>
```

**Figure 12-1. Sample code for local\_PersistentLink.xml (Continued)**

2. Make a backup copy of `cl_displayRecord.xml` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/contentLayout/`.
3. Edit `cl_displayRecord.xml`.
  - a. Locate the namespace declarations at the top of the file and include a reference to the `local_PersistentLink.xml` file after the `<xsl:stylesheet>` element. See [Figure 12-2](#).

```
<xsl:stylesheet version="1.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:page="http://www.exlibrisgroup.com/voyager/webvoyage/
    page"
  xmlns:fo="http://www.w3.org/1999/XSL/Format">

  <xsl:include href="../../pageFacets/local_PersistentLink.xml"/>
```

**Figure 12-2. Include file reference example**

- 
- b. Call the persistent link template from the Bibliographic Data section.  
See [Figure 12-3](#).

```
<!-- ## Bibliographic Data ## -->
    <xsl:for-each select="$Config">
        <div class="bibliographicData">
            <xsl:call-template name="buildMarcDisplay">
                <xsl:with-param name="recordType"
select="'bib'"/>
            </xsl:call-template>
            <!-- add a persistent link -->
            <xsl:call-template name="persistentLink" >
                <xsl:with-param name="bibID" select="$bibID"/>
            </xsl:call-template>

        </div>
    </xsl:for-each>
```

**Figure 12-3. Persistent link template call in Bibliographic Data section**

4. Save and test your changes.

**OPTIONAL:**

5. *Back out your changes, if necessary, by deploying your backup copy of cl\_displayRecord.xsl.*

---

## How Do I Change The Format Of The Record Display Page?

# 13

---

### Contents

Description For “How Do I Change The Format Of The Record Display Page?” Example	13-1
Files	13-1
Instructions	13-2

**DRAFT**

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page



---

## How Do I Change The Format Of The Record Display Page?

# 13

---

### Description For “How Do I Change The Format Of The Record Display Page?” Example

---

For greater formatting control of elements on the record display page, class attributes may be added to the XML and subsequently adjusted in the appropriate style sheet. This allows you, for example, to change the font characteristics of the Title and Author lines without affecting other data on the page.

See [Procedure 13-1, Add Class Attributes For Formatting.](#) on page [13-2](#) for instructions regarding class attributes.

### Files

---

The example in this chapter uses the following files:

- displaycfg.xml.
- display.xsl.
- displayRecord.css.

---

## Instructions

---

This section provides the instructions for creating the example described in this chapter.



### Procedure 13-1. Add Class Attributes For Formatting

---

Use the following procedure to implement class attributes for formatting.

**NOTE:**

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

```
/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/
```

1. Make a backup copy of `displaycfg.xml` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/contentLayout/configs/`.
2. Edit `displaycfg.xml`.
  - a. Locate the `displayTag` to which you want to apply formatting.
  - b. Add a class attribute after the `label=` string. Use a name of your own choosing. See [Figure 13-1](#) for examples.

```
<displayTags label="Title:" localcssclass="tagTitle">  
<displayTags label="Author:" localcssclass="tagAuthor">
```

---

**Figure 13-1. Class attribute creation example**

---

3. Save your changes to the `displaycfg.xml`.
4. Make a backup copy of `display.xsl` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/contentLayout/display/`.
5. Edit `display.xsl`.

- a. Locate the template for buildMarcDisplay.
- b. Add the lines shown in [Figure 13-2](#) to assign one of two classes to the bibliographic tag data.

```

                                </a><br/>

                                </xsl:for-each>
                                </div>
                                </li>
                                </xsl:if>
                                </xsl:if>

<!-- assign class-->
                                <li>
                                    <xsl:attribute name="class">
                                        <xsl:choose>
                                            <xsl:when test="string-
length(@localcssclass)">
                                                <xsl:value-of select="@localcssclass" />
                                            </xsl:when>
                                            <xsl:otherwise>bibTag</xsl:otherwise>
                                        </xsl:choose>
                                    </xsl:attribute>
                                    <xsl:copy-of select="$bibTag"/>
                                </li>

<!-- assign class dinking -->

<!-- comment out these lines if using localcssclass
                                <li class="bibTag">
                                    <xsl:copy-of select="$bibTag"/>
                                </li>
-->

                                </xsl:if>
```

**Figure 13-2.** Example code to add to buildMarcDisplay

---

```
</xsl:for-each>

</ul>
</div>
</xsl:when>
```

**Figure 13-2. Example code to add to buildMarcDisplay (Continued)**

6. Save your changes to `display.xml`.
7. Make a backup copy of `displayRecord.css` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/css/`.
8. Add style directives to the `localcssclass` tags that you defined in `displaycfg.xml` and place at the bottom of the `displayRecord.css` file.

See example code in [Figure 13-3](#).

---

```
.tagTitle, .tagAuthor
{
    margin-bottom: .75em;
    font-size: larger;
    color: #ff0000;
}
```

**Figure 13-3. Example code for displayRecord.css**

9. Save and test your changes.
  10. Back out your changes, if necessary, by deploying your backup copies of `displaycfg.xml`, `displayRecord.xml`, and `displayRecord.css`.
-

---

## How Do I Add Tracking Codes?

# 14

---

### Contents

Description For “How Do I Add Tracking Codes?” Example	14-1
Files	14-1
Instructions	14-2

**DRAFT**

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

### Description For “How Do I Add Tracking Codes?” Example

---

Various companies offer web page tracking/analytic services such as Google Analytics. The general practice is to include tagging on all the pages you want tracked.

The instructions in this chapter may be use to add the relevant code to one of two .xsl files that are called by all WebVoyage pages.

**NOTE:**

You must establish a relationship with the tracking service first and consider use of such a tool in relationship to your institution's privacy policy.

### Files

---

The example in this chapter can apply to either of the following files:

- frameWork.xsl.
- footer.xsl.

---

## Instructions

---

This section provides the instructions for creating the example described in this chapter.



### Procedure 14-1. Add tracking codes

---

Use the following procedure to add tracking codes (in coordination with an outside service).

Specifically, this example inserts the Google Analytics tracking code into the `footer.xsl`. Coordinate with other services regarding their specific instructions.

**NOTE:**

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

```
/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/
```

1. Make a backup copy of `footer.xsl` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/[skin]/xsl/pageFacets/`.
2. Edit `footer.xsl`.
  - a. Copy the script snippet the third-party vendor generated for you upon signup. This example uses a Google Analytics script snippet.
  - b. Paste the script snippet into the `buildFooter` template. See [Figure 14-1](#).

```
<!-- ##### -->
<!-- ## buildFooter ## -->
<!-- ##### -->

<xsl:template name="buildFooter">

    <xsl:for-each select="/page:page/page:pageFooter">
```

---

**Figure 14-1. Example of script snippet add to buildFooter template**



```

<div id="pageFooter">
  <xsl:for-each select="page:tabs[@nameId='page.footer.buttons']">

    <div id="footerTabs" title="{ $footerText/footerTabs}">
      <a name="navFooter"></a>
      <h2 class="navFooter"><xsl:value-of select="$footerText/
        footerTabs" /></h2>
      <ul class="navbar">
        <xsl:for-each select="$Configs/pageConfigs/
          footerTabDisplayOrder/tab">
          <xsl:variable name="tempName" select="@name" />
          <xsl:variable name="newWin" select="@clickOpensNewWindow" />
          <xsl:call-template name="buildFooterTab">
            <xsl:with-param name="displayTab" select="$tempName" />
            <xsl:with-param name="newWin" select="$newWin" />
          </xsl:call-template>
        </xsl:for-each>
      </ul>
    </div>

  </xsl:for-each>

  <div id="libraryLink">
    <span>
      <xsl:call-template name="buildLinkType">
        <xsl:with-param name="eleName"
          select="'page.footer.library.link'" />
      </xsl:call-template>
    </span>
  </div>

  <div id="copyright" title="{ $footerText/copyright}"><span><xsl:value-
    of select="page:element[@nameId='page.footer.copyright.message'] /
    page:messageText" /></span></div>

</div>
</xsl:for-each>

<!-- Google Analytics snippet -->

```

**Figure 14-1. Example of script snippet add to buildFooter template (Continued)**

---

```
<script type="text/javascript">
var gaJsHost = (("https:" == document.location.protocol) ? "https://ssl." :
"http://www.");
document.write(unescape("%3Cscript src='" + gaJsHost + "google-analytics.com/
ga.js' type='text/javascript'%3E%3C/script%3E"));
</script>
<script type="text/javascript">
var pageTracker = _gat._getTracker("UA-xxxxxx-x");
pageTracker._initData();
pageTracker._trackPageview();
</script>
</xsl:template>
```

**Figure 14-1. Example of script snippet add to buildFooter template (Continued)**

3. Save and test your changes.

**OPTIONAL:**

4. *Back out your changes, if necessary, by deploying your backup copy of footer.xsl.*

---

## How Do I Implement Google Book Search?

# 15

---

### Contents

<b>Description For “How Do I Implement Google Book Search?”</b>	<b>15-1</b>
<b>Files</b>	<b>15-1</b>
<b>Google Book Search Implementation</b>	<b>15-2</b>
• googleBooksAvail.js	15-2
• local_googleBooksAvail.xsl	15-2
• displayFacets.xsl	15-3
• displayGoogleBooks.css	15-3
<b>Disable Google Book Search</b>	<b>15-3</b>

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Implement Google Book Search?

# 15

---

### Description For “How Do I Implement Google Book Search?”

---

The Voyager 7.0 version of WebVoyage provides code to interface with the Google Book Search API. This enables users of WebVoyage to display Google Book Search information.

This feature is enabled at installation. To disable it, see [Procedure 15-1, Disable Google Book Search Feature](#), on page [15-3](#).

### Files

---

The Google Book Search feature uses the following files:

- googleBooksAvail.js.
- local\_googleBooksAvail.xsl.
- displayFacets.xsl.
- displayGoogleBooks.css.

---

## Google Book Search Implementation

---

This section describes the WebVoyage implementation for displaying Google Book Search information in Voyager 7.0.

### NOTE:

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

```
/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/.
```

### googleBooksAvail.js

---

The `googleBooksAvail.js` script in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/jscripts/` executes the call to the Google Book Search service. (This service is transparent to the user.)

The lines shown in [Figure 15-1](#) define the text that displays in the Action Box.

```
function listBookEntries(booksInfo)
{
    var bookPreviewFull = 'Full text available';
    var bookPreviewPartial = 'Limited Preview';
    var bookPreviewNoView = '"About This Book"';
```

---

**Figure 15-1. Action Box text**

---

### local\_googleBooksAvail.xsl

---

The `local_googleBooksAvail.xsl` file in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/xsl/` defines a template named `googleBooksAvail`. This template describes how to identify the ISBN, LCCN, or OCLC numbers which are the standard numbers used to do the lookup executed with `googleBooksAvail.js`.

### **displayFacets.xml**

---

The `displayFacets.xml` file in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/xsl/pageFacets/` calls the `googleBooksAvail` template. See [local googleBooksAvail.xsl](#) on [page 15-2](#).

### **displayGoogleBooks.css**

---

The `displayGoogleBooks.css` file in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/css/` manages the display of the Google information within the Action Box.

## **Disable Google Book Search**

---

This section provides the instructions for disabling Google Book Search described in this chapter.



### **Procedure 15-1. Disable Google Book Search Feature**

---

Use the following procedure to disable Google Book Search.

**NOTE:**

Directory path references to `xxxdb` implies that you need to substitute your database path name; and where `[skin]` is referenced, substitute the path name that is used at your site. The default skin path provided is `en_US` as in the following:

`/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/.`

1. Make a backup copy of `displayFacets.xml` that is located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/xsl/pageFacets/`.
2. Edit `displayFacets.xml`.
  - a. Locate the line of code near the bottom of the file as shown in [Figure 15-2](#).

---

```
## mdp add the google book template ##
```

---

**Figure 15-2. Line of code to locate**

- b. Comment out the lines of code as shown in [Figure 15-3](#).

---

```
<!-- ## mdp add the google book template ##  
    <div id="googleBooksRow">  
        <xsl:call-template name="googleBooksAvail"/>  
    </div>  
-->
```

---

**Figure 15-3. Comment out code to disable Google Book Search**

3. Save and test your changes.

**OPTIONAL:**

4. *Back out your changes, if necessary, by deploying your backup copy of displayFacets.xsl.*
-



---

# How Do I Display Cover Images From Services Like Amazon.com and Syndetics Solutions?

# 16

---

## Contents

<b>Description For “How Do I Display Cover Images From Services Like Amazon.com and Syndetics Solutions?”</b>	<b>16-1</b>
<b>Files</b>	<b>16-1</b>
<b>Syndetics Solutions Implementation</b>	<b>16-2</b>
• pageProperties.xml	16-2
• resultsFacets.xsl	16-3
• resultsTitles.xsl	16-5
• imageUtils.js	16-5
• displaycfg.xml	16-6
• display.xsl	16-6
• displayRecord.xsl	16-7

---

## Contents

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

---

## How Do I Display Cover Images From Services Like Amazon.com and Syndetics Solutions?

# 16

---

### Description For “How Do I Display Cover Images From Services Like Amazon.com and Syndetics Solutions?”

---

WebVoyage is preconfigured with the capability to display cover images on the results and holdings pages.

The ISBN or ISSN is generally used to do the lookup at the remote service.

**NOTE:**

You must have a pre-existing relationship or agreement with a service that provides this cover art.

### Files

---

The Syndetics example described in this chapter uses the following files:

- `pageProperties.xml`.
- `resultsFacets.xsl`.
- `resultsTitles.xsl`.
- `imageUtils.js`.
- `displaycfg.xml`.

Ex Libris (USA) Inc.  
See notice on first page

- display.xml.
- displayRecord.xml.

## Syndetics Solutions Implementation

This section describes as an example the WebVoyage implementation of displaying Syndetics Solutions cover images for results and holdings pages in Voyager 7.0.

### NOTE:

Directory path references to xxxdb implies that you need to substitute your database path name; and where [skin] is referenced, substitute the path name that is used at your site. The default skin path provided is en\_US as in the following:

```
/m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/en_US/.
```

### pageProperties.xml

The pageProperties.xml file located in /m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/xsl/userTextConfigs/ defines how the URL to the cover image for the titles results page is built to include the pre- and post-link text and the alternate name for the image. See [Figure 16-1](#).

```
<!-- each library is responsible for creating a relationship with a provider of
cover images -->

<!-- these options should not be enabled by default -->

<!-- <resultsCoverTag nameIdMatch="page.searchResults.item.type.isbn"
      linkPRE_TEXT="http://images.sample.com/images/"
      linkPOST_TEXT=".jpg" altText="Cover Image"/> -->

<!--resultsCoverTag nameIdMatch="page.searchResults.item.type.isbn"
      linkPRE_TEXT="http://www.syndetics.com/hw7.pl?isbn="
      linkPOST_TEXT="/SC.jpg" altText="Cover Image"/ -->
```

**Figure 16-1.** Example of pageProperties.xml

The /SC.jpg in [Figure 16-1](#) is the Syndetics Solutions syntax for small cover (SC). If you prefer a medium or large cover image, use MC or LC, respectively.

**resultsFacets.xsl**

The resultsFacets.xsl file located in /ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/xsl/userTextConfigs/ defines a template named buildResultsCoverImage. This template builds on the URL components defined in pageProperties.xml. See [Figure 16-2](#).

```
<!-- ##### -->
<!-- ## buildResultsCoverImage ## -->
<!--
#####
##### -->
<xsl:template name="buildResultsCoverImage">
<xsl:param name="tag"/>
<xsl:param name="tagType"/>

    <xsl:for-each select="$Configs/pageConfigs/
resultsCoverTag[@nameIdMatch=$tagType]">
        <div class="resultListCoverImageCell">
            
        </div>
    </xsl:for-each>
</xsl:template>
```

**Figure 16-2. Example of buildResultsCoverImage template**

The template is used later in the file for constructing the URL with an ISBN or ISSN.

The trimData template strips parenthetical references from the standard numbers. See [Figure 16-3](#).

```

<!-- ## cover image ## --
<xsl:choose>

  <xsl:when test="string-length(page:option/
page:element[@nameId='page.searchResults.item.type.isbn']/
page:value)">

    <!-- ## cover image from isbn ## -->

    <xsl:call-template name="buildResultsCoverImage">
      <xsl:with-param name="tag">
        <xsl:call-template name="trimData">
          <xsl:with-param name="sData"
select="page:option/
page:element[@nameId='page.searchResults.item.type.isbn']/
page:value"/>
        </xsl:call-template>
      </xsl:with-param>
      <xsl:with-param name="tagType"
select="'page.searchResults.item.type.isbn'"/>
      </xsl:call-template>
    </xsl:when>

    <xsl:when test="string-length(page:option/
page:element[@nameId='page.searchResults.item.type.issn']/
page:value)">

      <!-- ## cover image from issn ## -->

      <xsl:call-template name="buildResultsCoverImage">
        <xsl:with-param name="tag">
          <xsl:call-template name="trimData">
            <xsl:with-param name="sData"
select="page:option/
page:element[@nameId='page.searchResults.item.type.issn']/
page:value"/>
          </xsl:call-template>
        </xsl:with-param>
        <xsl:with-param name="tagType"
select="'page.searchResults.item.type.isbn'"/>
        </xsl:call-template>
      </xsl:when>
    </xsl:choose>

```

**Figure 16-3. Example of trimData template**

## **resultsTitles.xsl**

---

The resultsTitles.xsl file located in /m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/xsl/ builds the titles results page. It uses a JavaScript file named imageUtils.js.

## **imageUtils.js**

---

The imageUtils.js file located in /m1/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/jscripts/ performs the functions shown in [Figure 16-4](#).

```
var setDefaultErrImg=""; // Default image to be displayed on error
var setDefaultErrTxt=""; // Default text to be displayed on error

////////////////////////////////////

function checkImage(obj)
{
    if(obj.complete==true)
    {
        if(obj.width==0)
        {
            obj.src=setDefaultErrImg;
            obj.setAttribute("alt",setDefaultErrTxt);
        }
        else
        {
            obj.setAttribute("style","display:block");
        }
    }
}

////////////////////////////////////
```

---

**Figure 16-4. Example of imageUtils.js**

---

The Syndetics service (and possibly other remote cover services) does not allow you to pre-check whether an image exists before you build the link. Therefore, `imageUtils.js` checks to see if the image has been retrieved and loaded. If not, it displays a default **no image available** image or **no image available** text of your choice.

## displaycfg.xml

The `displaycfg.xml` file located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/xsl/contentLayout/configs/` defines how the URL to the cover image for the record display page is built that includes the pre- and post-link text and the bib field used to build the link. See [Figure 16-5](#).

```
<!--
  <coverTags altText="Cover Image" linkPRE_TEXT="http://www.syndetics.com/
    hw7.pl?isbn=" linkPOST_TEXT="/MC.jpg" singleInstance="true">
    <displayTag field="020" indicator1="X" indicator2="X" subfield="a"/>
  </coverTags>
-->
```

**Figure 16-5. Example displaycfg.xml code**

The `singleInstance="true"` syntax indicates that the first ISBN or ISSN found is used for building the link.

## display.xsl

The `display.xsl` file located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/xsl/contentLayout/display/` defines the following templates for retrieving cover images:

- `buildCoverImage`.
- `buildCoverImageLinks`.

These templates provide function similar to the templates described in [resultsFacets.xsl](#) on [page 16-3](#).



### **displayRecord.xsl**

---

The `displayRecord.xsl` file located in `/ml/voyager/xxxdb/tomcat/vwebv/context/vwebv/ui/{skin}/xsl/` uses a JavaScript file named `imageUtils.js` to build the record display page.

**DRAFT**

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page

## Index

---

### A

architecture overview, [2-1](#)  
auto complete  
    disable, [9-1](#)

---

### B

buildBasicSearch, [8-6](#)  
buildContent, [2-3](#)  
buildCoverImage, [16-6](#)  
buildCoverImageLinks, [16-6](#)  
buildHtmlPage, [2-3](#), [10-2](#)  
buildMarcDisplay, [13-3](#)  
buildResultsCoverImage, [16-3](#)  
buildSearchButtons, [11-5](#)

---

### C

cl\_displayRecord.xsl, [3-1](#), [3-4](#), [3-6](#), [12-1](#), [12-3](#), [12-4](#)  
cl\_myAccount.xsl, [2-3](#), [5-1](#), [5-2](#), [5-3](#)  
cl\_searchAdvanced.xsl, [11-1](#), [11-4](#), [11-5](#)  
cl\_searchBasic.xsl, [2-6](#), [8-1](#), [8-6](#), [8-8](#)  
constants.xsl, [2-6](#)  
constantStrings.xsl, [2-6](#)  
CSS files  
    displayGoogleBooks.css, [15-1](#), [15-3](#)  
    displayRecord.css, [13-4](#)  
    frameWork.css, [2-5](#), [2-6](#), [2-7](#)  
    header.css, [2-5](#), [2-6](#)  
    myAccount.css, [2-3](#), [2-5](#)  
    pageProperties.css, [2-5](#), [2-6](#), [2-7](#)  
    quickSearchBar.css, [2-5](#), [2-6](#)  
    searchAdvanced.css, [11-1](#), [11-4](#), [11-5](#)  
    searchBasic.css, [2-7](#)  
    searchPages.css, [2-7](#)

---

---

### D

display cover images  
    Syndetics Solutions, [16-1](#)  
display.xsl, [6-1](#), [6-3](#), [6-4](#), [6-5](#), [13-1](#), [13-2](#), [13-4](#), [16-2](#),  
    [16-6](#)  
displaycfg.xml, [3-1](#), [13-1](#), [13-2](#), [13-4](#), [16-1](#), [16-6](#)  
displayChargedItems, [5-2](#)  
displayFacets.xsl, [7-1](#), [7-3](#), [7-5](#), [15-1](#), [15-3](#), [15-4](#)  
displayGoogleBooks.css, [15-1](#), [15-3](#)  
displayRecord.css, [13-4](#)  
displayRecord.xsl, [2-2](#), [16-2](#), [16-7](#)

---

### F

favicon, [10-1](#)  
flowchart, [2-4](#)  
footer static links, [4-1](#)  
footer.xsl, [4-1](#), [4-4](#), [4-5](#), [14-1](#), [14-2](#), [14-4](#)  
formInput.xsl, [2-6](#)  
frameWork.css, [2-5](#), [2-6](#), [2-7](#)  
frameWork.xsl, [2-3](#), [2-6](#), [10-1](#), [10-2](#), [10-3](#)

---

### G

Getting Started, [1-1](#)  
    prerequisite skills and knowledge, [1-1](#)  
Google Book Search, [15-1](#)  
googleBooksAvail, [15-2](#), [15-3](#)  
googleBooksAvail.js, [15-1](#), [15-2](#)

---

### H

header static links, [4-1](#)  
header.css, [2-5](#), [2-6](#)  
header.xsl, [4-1](#), [4-2](#), [4-3](#)

---

---

## I

imageUtils.js, [16-1](#), [16-5](#), [16-6](#), [16-7](#)

---

## J

JavaScript files

  googleBooksAvail.js, [15-1](#), [15-2](#)  
  imageUtils.js, [16-1](#), [16-5](#), [16-6](#), [16-7](#)  
  pageInputFocus.js, [2-7](#)

---

## L

limits

  dynamically disable, [8-1](#)  
  hide on Advanced Search page, [11-1](#)  
local\_googleBooksAvail.xml, [15-1](#), [15-2](#)  
login.xml, [9-1](#), [9-2](#), [9-3](#)

---

## M

myAccount.css, [2-3](#), [2-5](#)  
myAccount.xml, [2-2](#), [2-3](#)  
myAccountLinks.xml, [2-3](#)

---

## P

page

  remove information, [5-1](#)  
page components, [2-5](#)  
pageInputFocus.js, [2-7](#)  
pageProperties.css, [2-5](#), [2-6](#), [2-7](#)  
pageProperties.xml, [8-1](#), [8-5](#), [16-1](#), [16-2](#), [16-3](#)  
persistent link, [12-1](#)  
prerequisites, [1-1](#)

---

## Q

quickSearchBar.css, [2-5](#), [2-6](#)

---

## R

record display page

  change format, [13-1](#)  
resultsFacets.xml, [16-1](#), [16-3](#)  
resultsTitles.xml, [16-1](#), [16-5](#)

---

## S

search tips

  dynamically change, [8-1](#)  
searchAdvanced.css, [11-1](#), [11-4](#), [11-5](#)  
searchBasic.css, [2-7](#)  
searchFacets.xml, [2-7](#), [9-1](#), [9-2](#), [9-3](#)  
searchPages.css, [2-7](#)  
serials  
  separate display for, [3-1](#)  
stdImports.xml, [2-3](#)  
Syndetics Solutions, [16-1](#)

---

## T

templates

  buildBasicSearch, [8-6](#)  
  buildContent, [2-3](#)  
  buildCoverImage, [16-6](#)  
  buildCoverImageLinks, [16-6](#)  
  buildHtmlPage, [2-3](#), [10-2](#)  
  buildMarcDisplay, [13-3](#)  
  buildResultsCoverImage, [16-3](#)  
  buildSearchButtons, [11-5](#)  
  displayChargedItems, [5-2](#)  
  googleBooksAvail, [15-2](#), [15-3](#)  
  trimData, [16-3](#)  
tools.xml, [2-6](#)  
tracking codes

add, [14-1](#)  
trimData, [16-3](#)

---

## W

webvoyage.properties, [2-7](#)

---

## X

### XML files

displaycfg.xml, [3-1](#), [13-1](#), [13-2](#), [13-4](#), [16-1](#), [16-6](#)  
pageProperties.xml, [8-1](#), [8-5](#), [16-1](#), [16-2](#), [16-3](#)

### XSL files

cl\_displayRecord.xsl, [3-1](#), [3-4](#), [3-6](#), [12-1](#), [12-3](#),  
[12-4](#)  
cl\_myAccount.xsl, [2-3](#), [5-1](#), [5-2](#), [5-3](#)  
cl\_searchAdvanced.xsl, [11-1](#), [11-4](#), [11-5](#)  
cl\_searchBasic.xsl, [2-6](#), [8-1](#), [8-6](#), [8-8](#)  
constants.xsl, [2-6](#)  
constantStrings.xsl, [2-6](#)  
display.xsl, [6-1](#), [6-3](#), [6-4](#), [6-5](#), [13-1](#), [13-2](#), [13-4](#),  
[16-2](#), [16-6](#)  
displayFacets.xsl, [7-1](#), [7-3](#), [7-5](#), [15-1](#), [15-3](#), [15-4](#)  
displayRecord.xsl, [2-2](#), [16-2](#), [16-7](#)  
footer.xsl, [4-1](#), [4-4](#), [4-5](#), [14-1](#), [14-2](#), [14-4](#)  
formInput.xsl, [2-6](#)  
frameWork.xsl, [2-3](#), [2-6](#), [10-1](#), [10-2](#), [10-3](#)  
header.xsl, [4-1](#), [4-2](#), [4-3](#)  
local\_googleBooksAvail.xsl, [15-1](#), [15-2](#)  
login.xsl, [9-1](#), [9-2](#), [9-3](#)  
myAccount.xsl, [2-2](#), [2-3](#)  
myAccountLinks.xsl, [2-3](#)  
resultsFacets.xsl, [16-1](#), [16-3](#)  
resultsTitles, [16-1](#), [16-5](#)  
searchFacets.xsl, [2-7](#), [9-1](#), [9-2](#), [9-3](#)  
stdImports.xsl, [2-3](#)  
tools.xsl, [2-6](#)

---

**DRAFT**

**Ex Libris (USA) Inc.**  
See notice on first page