



CHAPEL BASICS



Chapel Team, edited by Michelle Strout

April 3, 2025

HANDS ON: HOW TO DO THE HANDS ON



01-hello.chpl

Example codes for Chapel tutorial slides

- <https://github.com/UofA-CSc-372-Spring-2025/CSc372Spring2025-CourseMaterials/tree/main/Sandboxes/ChapelTutorialExamples>

Using a container on your laptop

- First, install docker for your machine and start it up (see the README.md for more info)
- Then, use the chapel-gasnet docker container

```
docker pull docker.io/chapel/chapel-gasnet      # takes about 5 minutes
cd CSc372Spring2025-CourseMaterials/Sandboxes/ChapelTutorial/
docker run --rm -it -v "$PWD":/workspace chapel/chapel-gasnet
root@589405d07f6a:/opt/chapel# cd /workspace
root@xxxxxxxx:/myapp# chpl 01-hello.chpl
root@xxxxxxxx:/myapp# ./01-hello -nl 1
```



PLAN

- **Announcements**

- Final project assignments coming out ASAP
- SA7 will be posted Friday April 4th, a couple of days late

- **Last time**

- TopHat questions about ChapelCon tutorial and last class, aka ICA10 prep
- Kmer counting example: file IO, maps, strings
- Parallel processing of files
- Overview of GPU programming support

- **Today**

- TopHat Questions
- ICA10 Quiz
- Chapel Programming Basics in the context of an Nbody simulation, part I

ICA10: QUIZ ON CHAPEL SO FAR

- Read the instructions on the quiz

OUTLINE: OVERVIEW OF PROGRAMMING IN CHAPEL

- Running Example: n-body computation (Hands On)
- Variables, Constants, and Operators
- Records and Classes
- Tuples
- Arrays
- Writing out Tuples, Records, and Arrays (Hands On)



RUNNING EXAMPLE: N-BODY COMPUTATION (HANDS ON)

N-BODY IN CHAPEL (WHERE $N == 5$)

- A serial computation
- From the Computer Language Benchmarks Game
 - Chapel implementation in release under `examples/benchmarks/shootout/nbody.chpl`
- Computes the influence of 5 bodies on one another
 - The Sun, Jupiter, Saturn, Uranus, Neptune
- Executes for a user-specifiable number of timesteps




Image source: <http://spaceplace.nasa.gov/review/ice-dwarf/solar-system-lrg.png>

HANDS ON: COMPILING AND RUNNING N-BODY



nbody.chpl

Things to try

```
chpl nbody.chpl
time ./nbody -nl 1
time ./nbody -nl 1 -n=100000

chpl --fast nbody.chpl
time ./nbody -nl 1
time ./nbody -nl 1 -n=100000
```

```
// number of timesteps to simulate
config const n = 10000;
...
```

Key concepts

- *nix 'time' command is an easy way to see how long a program takes to run
- Compile with '--fast' to have 'chpl' compiler generate faster code



VARIABLES, CONSTANTS, AND OPERATORS

5-BODY IN CHAPEL: VARIABLE AND RECORD DECLARATIONS



nbody.chpl

```
const pi = 3.141592653589793,  
      solarMass = 4 * pi**2,  
      daysPerYear = 365.24;
```

Variable declarations

```
config const numsteps = 10000;
```

```
record body {  
  var pos: 3*real;  
  var v: 3*real;  
  var mass: real;  
}
```

```
...
```



VARIABLES, CONSTANTS, AND PARAMETERS

Basic syntax

declaration:

```
var    identifier [: type] [= init-expr];  
const identifier [: type] [= init-expr];  
param identifier [: type] [= init-expr];
```

Examples

```
const pi: real = 3.14159;  
var count: int;           // initialized to 0  
param debug = true;      // inferred to be bool
```

Meaning

- var/const: execution-time variable/constant
- param: compile-time constant
- No init-expr \Rightarrow initial value is the type's default
- No type \Rightarrow type is taken from init-expr



PRIMITIVE TYPES

Syntax

| Type | Description | Default Value | Currently-Supported Bit Widths | Default Bit Width |
|---------|--------------------------|---------------|--------------------------------|-------------------|
| bool | logical value | false | | impl. dep. |
| int | signed integer | 0 | 8, 16, 32, 64 | 64 |
| uint | unsigned integer | 0 | 8, 16, 32, 64 | 64 |
| real | real floating point | 0.0 | 32, 64 | 64 |
| imag | imaginary floating point | 0.0i | 32, 64 | 64 |
| complex | complex floating points | 0.0 + 0.0i | 64, 128 | 128 |
| string | character string | "" | N/A | N/A |

Examples

```
primitive-type:
  type-name [( bit-width )]
```

```
int(16)    // 16-bit int
real(32)   // 32-bit real
uint       // 64-bit uint
```



CHAPEL'S STATIC TYPE INFERENCE



nbody.chpl

```
const pi = 3.14,           // pi is a real
      coord = 1.2 + 3.4i,  // coord is a complex...
      coord2 = pi*coord,   // ...as is coord2
      name = "brad",       // name is a string
      verbose = false;     // verbose is boolean

proc addem(x, y) {          // addem() has generic arguments
  return x + y;             // and an inferred return type
}

var sum = addem(1, pi),      // sum is a real
    fullname = addem(name, "ford"); // fullname is a string

writeln((sum, fullname));
```

(4.14, bradford)



BASIC OPERATORS AND PRECEDENCE

| Operator | Description | Associativity | Overloadable |
|-------------|--------------------------------------|---------------|--------------|
| : | cast | left | yes |
| ** | exponentiation | right | yes |
| ! ~ | logical and bitwise negation | right | yes |
| * / % | multiplication, division and modulus | left | yes |
| (unary) + - | positive identity and negation | right | yes |
| << >> | shift left and shift right | left | yes |
| & | bitwise/logical and | left | yes |
| ^ | bitwise/logical xor | left | yes |
| | bitwise/logical or | left | yes |
| + - | addition and subtraction | left | yes |
| <= >= < > | ordered comparison | left | yes |
| == != | equality comparison | left | yes |
| && | short-circuiting logical and | left | via isTrue |
| | short-circuiting logical or | left | via isTrue |

5-BODY IN CHAPEL: DECLARATIONS



nbody.chpl

```
const pi = 3.141592653589793,  
      solarMass = 4 * pi**2,  
      daysPerYear = 365.24;
```

Variable declarations

```
config const numsteps = 10000;
```

```
record body {  
  var pos: 3*real;  
  var v: 3*real;  
  var mass: real;  
}
```

...

5-BODY IN CHAPEL: DECLARATIONS



nbody.chpl

```
const pi = 3.141592653589793,  
      solarMass = 4 * pi**2,  
      daysPerYear = 365.24;
```

```
config const numsteps = 10000;
```

```
record body {  
  var pos: 3*real;  
  var v: 3*real;  
  var mass: real;  
}
```

```
...
```

Configuration Variable

5-BODY IN CHAPEL: DECLARATIONS



nbody.chpl

```
const pi = 3.141592653589793,  
      solarMass = 4 * pi**2,  
      daysPerYear = 365.24;
```

```
config const numsteps = 10000;
```

```
record body {  
  var pos: 3*real;  
  var v: 3*real;  
  var mass: real;  
}
```

...

Configuration Variable

```
$ ./nbody --numsteps=100
```

CONFIGS

 02-configs.chpl

```
param intSize = 32;  
type elementType = real(32);  
const epsilon = 0.01:elementType;  
var start = 1:int(intSize);
```

```
config param intSize = 32;  
config type elementType = real(32);  
config const epsilon = 0.01:elementType;  
config var start = 1:int(intSize);
```

```
$ chpl 02-configs.chpl -sintSize=64 -selementType=real  
$ ./02-configs-start=2 -nl 1 --epsilon=0.00001
```

Experiment some with 02-configs.chpl

1. Which of the above can be changed at compile time?
2. Which can be changed at runtime?



OUTLINE: OVERVIEW OF PROGRAMMING IN CHAPEL

- Running Example: n-body computation (Hands On)
- Variables, Constants, and Operators
- Records and Classes
- Tuples
- Arrays
- Writing out Tuples, Records, and Arrays (Hands On)



5-BODY IN CHAPEL: DECLARATIONS



nbody.chpl

```
const pi = 3.141592653589793,  
      solarMass = 4 * pi**2,  
      daysPerYear = 365.24;
```

```
config const numsteps = 10000;
```

```
record body {  
  var pos: 3*real;  
  var v: 3*real;  
  var mass: real;  
}
```

```
...
```

Configuration Variable

5-BODY IN CHAPEL: DECLARATIONS



nbody.chpl

```
const pi = 3.141592653589793,  
      solarMass = 4 * pi**2,  
      daysPerYear = 365.24;  
  
config const numsteps = 10000;  
  
record body {  
  var pos: 3*real;  
  var v: 3*real;  
  var mass: real;  
}  
  
...
```

Record declaration

RECORDS AND CLASSES

RECORDS AND CLASSES

 02-records-and-classes.chpl

Chapel's object types

- Contain variable definitions (fields)
- Contain procedure & iterator definitions (methods)
- Records: value-based (e.g., assignment copies fields)
- Classes: reference-based (e.g., assignment aliases object)

Example

```
use Math;
record circle {
  var radius: real;
  proc area() {
    return pi*radius**2;
  }
}
```

```
var c1 = new circle(radius=1.0);
var c2 = c1;    // copies c1
c1.radius = 5.0;
writeln(c2.radius); // prints 1.0
```


RECORDS AND CLASSES

 02-records-and-classes.chpl

Chapel's object types

- Contain variable definitions (fields)
- Contain procedure & iterator definitions (methods)
- Records: value-based (e.g., assignment copies fields)
- Classes: reference-based (e.g., assignment aliases object)

Experiment some with 02-records-and-classes.chpl

Example

1. What happens if you take away the '?'?
2. What happens if you take away the '!' ?

```
use Math;
class Circle {
  var radius: real;
  proc area() {
    return pi*radius**2;
  }
}
```

```
// c1 is a nilable class
var c1: Circle? = new shared Circle(radius=1.0);
var c2 = c1;           // aliases c1's circle
c1!.radius = 5.0;
writeln(c2!.radius); // prints 5.0
```

CLASSES VS. RECORDS

Classes

- heap-allocated
 - Variables point to objects
 - Support mem. mgmt. policies
- 'reference' semantics
 - compiler will only copy pointers
- support inheritance
- support dynamic dispatch
- identity matters most
- similar to Java classes

Records

- allocated in-place
 - Variables are the objects
 - Always freed at end of scope
- 'value' semantics
 - compiler may introduce copies
- no inheritance
- no dynamic dispatch
- value matters most
- similar to C++ structs
 - (sans pointers)



5-BODY IN CHAPEL: DECLARATIONS



nbody.chpl

```
const pi = 3.141592653589793,  
      solarMass = 4 * pi**2,  
      daysPerYear = 365.24;  
  
config const numsteps = 10000;  
  
record body {  
  var pos: 3*real;  
  var v: 3*real;  
  var mass: real;  
}  
...
```

Tuple type

TUPLES

TUPLES

Use

- support lightweight grouping of values
 - e.g., passing/returning multiple procedure arguments at once
 - short vectors
 - multidimensional array indices
- support heterogeneous data types

Examples

```
var coord: (int, int, int) = (1, 2, 3);  
var coordCopy: 3*int = coord;  
var (i1, i2, i3) = coord;  
var triple: (int, string, real) = (7, "eight", 9.0);
```

5-BODY IN CHAPEL: DECLARATIONS

 nbody.chpl

```
const pi = 3.141592653589793,  
      solarMass = 4 * pi**2,  
      daysPerYear = 365.24;
```

Variable declarations

```
config const numsteps = 10000;
```

Configuration Variable

```
record body {  
  var pos: 3*real;  
  var v: 3*real;  
  var mass: real;  
}
```

Record declaration

Tuple type

...

5-BODY IN CHAPEL: THE BODIES



nbody.chpl

```
var bodies =
  [ /* sun */
    new body(mass = solarMass),

    /* jupiter */
    new body(pos = ( 4.84143144246472090e+00,
                    -1.16032004402742839e+00,
                    -1.03622044471123109e-01),
              v = ( 1.66007664274403694e-03 * daysPerYear,
                    7.69901118419740425e-03 * daysPerYear,
                    -6.90460016972063023e-05 * daysPerYear),
              mass = 9.54791938424326609e-04 * solarMass),

    /* saturn */
    new body(...),

    /* uranus */
    new body(...),

    /* neptune */
    new body(...)
  ];
```

5-BODY IN CHAPEL: THE BODIES



nbody.chpl

```
var bodies =  
[ /* sun */  
  new body(mass = solarMass),  
  
  /* jupiter */  
  new body(pos = ( 4.84143144246472090e+00,  
                  -1.16032004402742839e+00,  
                  -1.03622044471123109e-01),  
            v = ( 1.66007664274403694e-03 * daysPerYear,  
                  7.69901118419740425e-03 * daysPerYear,  
                  -6.90460016972063023e-05 * daysPerYear),  
            mass = 9.54791938424326609e-04 * solarMass),  
  
  /* saturn */  
  new body(...),  
  
  /* uranus */  
  new body(...),  
  
  /* neptune */  
  new body(...)  
];
```

Create a record object

5-BODY IN CHAPEL: THE BODIES



nbody.chpl

```
var bodies =  
[ /* sun */  
  new body(mass = solarMass),  
  
  /* jupiter */  
  new body(pos = ( 4.84143144246472090e+00,  
                  -1.16032004402742839e+00,  
                  -1.03622044471123109e-01),  
            v = ( 1.66007664274403694e-03 * daysPerYear,  
                  7.69901118419740425e-03 * daysPerYear,  
                  -6.90460016972063023e-05 * daysPerYear),  
            mass = 9.54791938424326609e-04 * solarMass),  
  
  /* saturn */  
  new body(...),  
  
  /* uranus */  
  new body(...),  
  
  /* neptune */  
  new body(...)  
];
```

Tuple values



5-BODY IN CHAPEL: THE BODIES



nbody.chpl

```
var bodies =  
  [ /* sun */  
    new body(mass = solarMass),  
  
    /* jupiter */  
    new body(pos = ( 4.84143144246472090e+00,  
                    -1.16032004402742839e+00,  
                    -1.03622044471123109e-01),  
              v = ( 1.66007664274403694e-03 * daysPerYear,  
                    7.69901118419740425e-03 * daysPerYear,  
                    -6.90460016972063023e-05 * daysPerYear),  
              mass = 9.54791938424326609e-04 * solarMass),  
  
    /* saturn */  
    new body(...),  
  
    /* uranus */  
    new body(...),  
  
    /* neptune */  
    new body(...)  
  ];
```

Array
value

ARRAYS

ARRAY TYPES

Syntax

```
array-type:  
  [ domain-expr ] elt-type  
array-value:  
  [elt1, elt2, elt3, ... eltn]
```

Meaning

- array-type: stores an element of elt-type for each index
- array-value: represent the array with these values

Examples

```
var A: [1..3] int,           // A stores 0, 0, 0  
    B = [5, 3, 9],          // B stores 5, 3, 9  
    C: [1..m, 1..n] real,    // 2D m by n array of reals  
    D: [1..m][1..n] real;    // array of arrays of reals
```

More on arrays in data parallelism section later...

5-BODY IN CHAPEL: THE BODIES



nbody.chpl

```
var bodies =  
[ /* sun */  
  new body(mass = solarMass),  
  
  /* jupiter */  
  new body(pos = ( 4.84143144246472090e+00,  
                  -1.16032004402742839e+00,  
                  -1.03622044471123109e-01),  
            v = ( 1.66007664274403694e-03 * daysPerYear,  
                  7.69901118419740425e-03 * daysPerYear,  
                  -6.90460016972063023e-05 * daysPerYear),  
            mass = 9.54791938424326609e-04 * solarMass),  
  
  /* saturn */  
  new body(...),  
  
  /* uranus */  
  new body(...),  
  
  /* neptune */  
  new body(...)  
];
```

Create a record object

Tuple values

Array
value

HANDS ON: WRITING TUPLES, RECORDS, AND ARRAYS



nbody.chpl

Put a `writeln("bodies = ", bodies);` into program

```
chpl nbody.chpl
./nbody -nl 1
bodies = (pos = (0.0, 0.0, 0.0), vel = (0.0, 0.0, 0.0),
mass = 39.4784) (pos = (4.84143, -1.16032, -0.103622), vel
= (0.606326, 2.81199, -0.0252184), mass = 0.0376937) (pos
= (8.34337, 4.1248, -0.403523), vel = (-1.01077, 1.82566,
0.00841576), mass = 0.0112863) (pos = (12.8944, -15.1112,
-0.223308), vel = (1.08279, 0.868713, -0.0108326), mass =
0.00172372) (pos = (15.3797, -25.9193, 0.179259), vel =
(0.979091, 0.594699, -0.034756), mass = 0.00203369)
-0.169075164
-0.169016441
```