

# Types of attributes and methods of the class TransactionAnalyzer

## Notation

- $I$  denotes the number of items.
- $C$  denotes the number of separate categories associated with the items.
- $V_c$  denotes the number of separate values in the category  $c$ .
- $N$  denotes the number of nodes.
- $P$  denotes the number of patterns.
- $Y$  denotes the number of years for which transactions exist.
- $J$  denotes the number of itemsets.
- $+$  denotes public attributes and methods (i.e., exported attributes and methods).
- $-$  denotes private attributes and methods (i.e., non-exported attributes and methods).

## Class attributes

- ***STATUS\_PERSISTENT***: character
- ***STATUS\_DECLINING***: character
- ***STATUS\_EMERGENT***: character
- ***STATUS\_LATENT***: character
  
- ***TRANSACTIONS***: character
- ***NODES***: character
- ***PATTERNS***: character
- ***RULES***: character
  
- ***NODES\_OR\_PATTERNS***: character
- ***NODES\_PATTERNS\_OR\_RULES***: character
- ***NODES\_PATTERNS\_OR\_TRANSACTIONS***: character
- ***ANY\_ITEMSETS***: character
  
- ***NODE\_LINKS***: character
- ***PATTERN\_LINKS***: character

# Attributes

- + **transactions**: TransactionSet
- + **items**: named vector(character) or named vector(numeric)
- + **items\_categories**: data.frame

	category 1	category 2	...	category $C$
item 1	factor	factor	...	factor
item 2	factor	factor	...	factor
...	...	...	...	...
item $I$	factor	factor	...	factor

- + **categories\_colors**: list(named vector(character))

\$category1

value 1	character
value 2	character
...	...
value $V_1$	character

\$category2

value 1	character
value 2	character
...	...
value $V_2$	character

...

\$categoryC

value 1	character
value 2	character
...	...
value $V_C$	character

- + **status\_colors**: vector(character)
- + **parameters**: list(**target**: character,  
**count**: numeric,  
**min\_length**: numeric,  
**max\_length**: numeric,  
**status\_limit**: numeric)

- + **nodes**: data.frame

node	length	frequency
vector(character)	integer	numeric

- + **nodes\_per\_year**: matrix

	year 1	year 2	...	year $Y$
node 1	integer	integer	...	integer
node 2	integer	integer	...	integer
...	...	...	...	...
node $N$	integer	integer	...	integer

- + **n\_links**: matrix

	node 1	node 2	...	node $N$
node 1	integer	integer	...	integer
node 2	integer	integer	...	integer
...	...	...	...	...
node $N$	integer	integer	...	integer

+ **node\_links**: data.frame

endpoint.1	endpoint.2	items	weight
integer	integer	character	integer

+ **nodes\_patterns**: matrix

	pattern 1	pattern 2	...	pattern $P$
node 1	logical	logical	...	logical
node 2	logical	logical	...	logical
...	...	...	...	...
node $N$	logical	logical	...	logical

+ **patterns**: data.frame

pattern	year	length	support	frequency	weight	specificity	status
vector(character)	numeric	integer	numeric	integer	integer	numeric	character

+ **patterns\_per\_year**: matrix

	year 1	year 2	...	year $Y$
pattern 1	integer	integer	...	integer
pattern 2	integer	integer	...	integer
...	...	...	...	...
pattern $P$	integer	integer	...	integer

+ **p\_links**: matrix

	pattern 1	pattern 2	...	pattern $P$
pattern 1	integer	integer	...	integer
pattern 2	integer	integer	...	integer
...	...	...	...	...
pattern $P$	integer	integer	...	integer

+ **pattern\_links**: data.frame

endpoint.1	endpoint.2	items	weight	year
integer	integer	character	integer	integer

# Methods

- + **transaction.analyzer**(**transactions**: TransactionSet, **items**: see data.frame below,  
**target**: character, **count**: numeric, **min\_length**: numeric,  
**max\_length**: numeric, **status\_limit**: numeric, **init**: logical, **verbose**: logical):  
TransactionAnalyzer

item	name	category 1	category 2	...	category C
character	character	factor	factor	...	factor

- + **reset**(**object**: TransactionAnalyzer, **from**: numeric, **verbose**: logical)
- + **init**(**part**: character, **verbose**: logical): itemsets (class object from arules package) or NULL
- **init\_nodes**(**verbose**: logical)
- **init\_node\_links**(**verbose**: logical)
- **init\_patterns**(**verbose**: logical): itemsets (class object from arules package) or NULL
- **init\_pattern\_links**(**verbose**: logical)
- + **is\_init**(**part**: character): logical or vector(logical)
- **is\_init\_nodes**(): logical
- **is\_init\_node\_links**(): logical
- **is\_init\_patterns**(): logical
- **is\_init\_pattern\_links**(): logical
- **check\_init**(**part**: character or vector(character), **stop**: logical, **prefix**: character, **suffix**: character):  
logical or vector(logical)
- **list\_trx\_per\_year**(): see attribute **nodes\_per\_year**
- **list\_separate\_trx**(): see attribute **nodes**
- **count\_links**(**entities**: character): see attributes **n\_links** and **p\_links**
- **search\_links**(**entities**: character): see attributes **node\_links** and **pattern\_links**
- **list\_separate\_patterns**(**target**: character, **count**: numeric, **min\_length**: numeric,  
**max\_length**: numeric, **arules**: logical): itemsets (class object from arules  
package) or data.frame

pattern	support	frequency
vector(character)	numeric	integer

- **list\_patterns\_by\_trx**(): see attribute **nodes\_patterns**
- **list\_patterns\_per\_year**(): see attribute **patterns\_per\_year**
- **compute\_patterns\_characteristics**(): see attribute **patterns**
- **compute\_specificity**(**patterns**: list(vector(character)), **frequencies**: vector(numeric),  
**weights**: vector(numeric)): vector(numeric)

- **check\_RI\_params**(end: numeric, period: numeric): list

end	numeric
period	numeric

- **compute\_reporting\_indexes**(patterns: list(vector(character)), end: numeric, period: numeric):  
vector(numeric)

- **compute\_reporting\_indexes\_limits**(patterns: list(vector(character)), end: numeric,  
overall\_period: numeric, recent\_period: numeric): matrix

RI.overall	RI.recent
numeric	numeric

- **compute\_xi\_threshold**(reporting\_indexes: vector(numeric)): numeric
- **compute\_ri\_threshold**(reporting\_indexes: vector(numeric), xi: numeric): numeric
- + **dynamic\_status**(patterns: list(vector(character)), end: numeric, overall\_period: numeric,  
recent\_period: numeric): list

[[ "res" ]]: data.frame

RI.overall	is.above.threshold.1	RI.recent	is.above.threshold.2	status
numeric	logical	numeric	logical	character

[[ "thresholds" ]]: matrix

	threshold.1	threshold.2
xi	numeric	numeric
RI	numeric	numeric

- + **spectrum\_chart**(pc: character or see attribute **patterns**, identifiers: character, sort: logical,  
title: character, path: character, name: character): data.frame

ID	pattern	year	length	support	frequency	f.complex	f.simple	weight	specificity	status
numeric	vector	numeric	integer	numeric	integer	numeric	numeric	integer	numeric	character

- **plot\_spectrum\_chart**(pc: see attribute **patterns**,  
frequencies: see method **frequency\_by\_node\_complexity**, title: character)

- **pattern\_node\_characteristics**(patterns: list(vector(character))): list

[[ "frequencies" ]]:

1	vector(numeric)
2	vector(numeric)
...	...
P	vector(numeric)

[[ "lengths" ]]:

1	vector(integer)
2	vector(integer)
...	...
P	vector(integer)

+ **frequency\_by\_complexity**(patterns: list(vector(character))): matrix

complex	simple
numeric	numeric

+ **spectrosome\_chart**(nopc: character or see attribute **nodes** or **patterns**, identifiers: character, nb\_graphs: numeric, min\_link\_weight: numeric, vertex\_size: character or numeric or vector(numeric), size\_range: vector(numeric), vertex\_col: character or vector(character), clusters: numeric, highlight: numeric, use\_names: logical, n.cutoff: numeric, c.cutoff: numeric, display\_mixt: logical, title: character, path: character, name: character, ...): list

[["vertices"]]: data.frame

ID	node	length	frequency	degree
integer	vector(character)	integer	numeric	integer

or (depends on the type of entities contained in **nopc**)

ID	pattern	year	length	support	frequency	weight	specificity	status	degree
integer	vector(character)	numeric	integer	numeric	integer	integer	numeric	character	integer

[["edges"]]: data.frame

ID	endpoint.1	endpoint.2	items	weight
integer	integer	integer	character	integer

or (depends on the type of entities contained in **nopc**)

ID	endpoint.1	endpoint.2	items	weight	year
integer	integer	integer	character	integer	integer

[["coords"]]: list(matrix)

	x	y
vertex 1	numeric	numeric
vertex 2	numeric	numeric
...	...	...
vertex <i>N</i> or <i>P</i>	numeric	numeric

– **cluster\_text**(graph: see matrix below, links: see attributes **node\_links** and **pattern\_links**, display: numeric, highlight: numeric, use\_names: logical, cutoff: numeric)

	x	y
vertex 1	numeric	numeric
vertex 2	numeric	numeric
...	...	...
vertex <i>N</i> or <i>P</i>	numeric	numeric

+ **network\_density**(links: see attribute **node\_links** or **pattern\_links**): numeric

+ **degree**(ID: numeric, links: see attribute **node\_links** or **pattern\_links**): integer

+ **itemset\_chart**(**tnpc**: character or TransactionSet or see attribute **nodes** or **patterns**,  
**identifiers**: character, **length\_one**: logical, **jitter**: logical, **under**: character,  
**over**: character, **use\_names**: logical, **n.cutoff**: numeric,  
**category**: character or numeric, **c.cutoff**: numeric, **sort\_by**: character,  
**title**: character, **path**: character, **name**: character): TransactionSet or data.frame

ID	node	length	frequency
numeric	vector(character)	integer	numeric

or (depends on the type of entities contained in **nopc**)

ID	pattern	year	length	support	frequency	weight	specificity	status
numeric	vector(character)	numeric	integer	numeric	integer	integer	numeric	character

+ **category\_tree\_chart**(**category**: character or numeric, **items**: see attribute **items**,  
**use\_names**: logical, **n.cutoff**: numeric, **c.cutoff**: numeric,  
**vertex\_size**: numeric, **vertex\_alpha**: numeric, **leaf\_size**: numeric,  
**leaf\_alpha**: numeric, **leaf\_margin**: numeric, **label\_size**: numeric,  
**label\_margin**: numeric): ggplot2 graph

+ **co\_occurrence\_chart**(**items**: see attribute **items**, **category**: character or numeric,  
**co\_occ**: matrix(numeric), **proportions**: logical, **min\_occ**: numeric,  
**max\_occ**: numeric, **use\_names**: logical, **n.cutoff**: numeric, **c.cutoff**: numeric,  
**sort\_by**: character, **vertex\_size**: numeric, **vertex\_alpha**: numeric,  
**vertex\_margin**: numeric, **label\_size**: numeric, **label\_margin**: numeric,  
**edge\_looseness**: numeric, **edge\_alpha**: numeric, **palette**: character or  
numeric, **palette\_direction**: numeric): ggplot2 graph

+ **extract\_rules**(**itemsets**: character or list, **pruning**: logical, **arules**: logical, **as\_sets**: logical, ...): rules  
(class object from arules package) or data.frame

antecedent		consequent	support	confidence	lift	count
vector(character)	=>	character	numeric	numeric	numeric	integer

or (**antecedent** and **consequent** types depend on the value of **as\_sets**. Presence of **count** or **itemset** depends on the value of **itemsets**)

antecedent		consequent	support	confidence	lift	itemset
factor	=>	factor	numeric	numeric	numeric	integer

+ **rules\_chart**(**rules**: see method **extract\_rules**, **items**: see attribute **items**, **parameter**: list,  
**display**: character, **threshold**: numeric, **direction**: logical, **use\_names**: logical,  
**n.cutoff**: numeric, **category**: character or numeric, **c.cutoff**: numeric,  
**sort\_by**: character, **vertex\_size**: numeric, **vertex\_alpha**: numeric,  
**vertex\_margin**: numeric, **label\_size**: numeric, **label\_margin**: numeric,  
**edge\_looseness**: numeric, **edge\_alpha**: numeric, **palette**: character,  
**palette\_direction**: numeric, **plot**: logical): list

[["graph"]]: ggplot2 graph

[["rules"]]: see method **extract\_rules**

- + **export(nporc**: see attribute **nodes** or **patterns** or return of function **extract\_rules**, ...)
  
- + **get\_trx\_from\_category**(**trx**: character or TransactionSet, **category**: character or numeric, **value**: character, **as\_indices**: logical): TransactionSet or named vector(integer)
  
- + **get\_nodes**(**nc**: character or see attribute **nodes**, **element**: character or numeric, **value**: numeric or vector(numeric) or character or vector(character), **condition**: character): see attribute **nodes**
- **get\_nodes\_from\_items**(**nc**: character or see attribute **nodes**, **items**: vector(numeric), **condition**: character): see attribute **nodes**
- **get\_nodes\_from\_characteristic**(**nc**: character or see attribute **nodes**, **characteristic**: character, **value**: numeric, **condition**: character): see attribute **nodes**
- **get\_nodes\_from\_category**(**nc**: character or see attribute **nodes**, **category**: character or numeric, **value**: character, **condition**: character): see attribute **nodes**
  
- + **get\_patterns**(**pc**: character or see attribute **patterns**, **element**: character or numeric, **value**: numeric or vector(numeric) or character or vector(character), **condition**: character): see attribute **patterns**
- **get\_patterns\_from\_items**(**pc**: character or see attribute **patterns**, **items**: vector(numeric), **condition**: character): see attribute **patterns**
- **get\_patterns\_from\_characteristic**(**pc**: character or see attribute **patterns**, **characteristic**: character, **value**: numeric, **condition**: character): see attribute **patterns**
- **get\_patterns\_from\_status**(**pc**: character or see attribute **patterns**, **value**: vector(character), **condition**: character): see attribute **patterns**
- **get\_patterns\_from\_category**(**pc**: character or see attribute **patterns**, **category**: character or numeric, **value**: character, **condition**: character): see attribute **patterns**
  
- + **get\_links**(**nopc**: character or see attribute **nodes** or **patterns**): see attribute **node\_links** or **pattern\_links**
- + **get\_isolates**(**nopc**: character or see attribute **nodes** or **patterns**): see attribute **nodes** or **patterns**
- + **get\_non\_isolates**(**nopc**: character or see attribute **nodes** or **patterns**): see attribute **nodes** or **patterns**
- + **get\_complexes**(**nopc**: character or see attribute **nodes** or **patterns**, **category**: character or numeric, **condition**: character, **min\_nb\_values**: numeric): see attribute **nodes** or **patterns**
  
- + **get\_item\_names**(**items**: vector(character) or vector(numeric) according to the attribute **items**): vector(character)



+ **get\_item\_colors(category: character or numeric,**  
**items: vector(character) or vector(numeric) according to the attribute items):**  
vector(character)

+ **category\_values(itemsets: list(vector(character)), as\_character: logical, unique: logical):**

list(list(factor))

\$category1

itemset 1	factor
itemset 2	factor
...	...
itemset <i>J</i>	factor

\$category2

itemset 1	factor
itemset 2	factor
...	...
itemset <i>J</i>	factor

...

\$categoryC

itemset 1	factor
itemset 2	factor
...	...
itemset <i>J</i>	factor

or data.frame (according to the value of **as\_character**)

	category 1	category 2	...	category <i>C</i>
itemset 1	vector(character)	vector(character)	...	vector(character)
itemset 2	vector(character)	vector(character)	...	vector(character)
...	...	...	...	...
itemset <i>J</i>	vector(character)	vector(character)	...	vector(character)

- **check\_access\_for\_category(category: character or numeric, value: character, stop: logical):**  
logical
- **has\_item\_names():** logical
- **get\_items(items: vector(character) or vector(numeric) according to the attribute items):**  
see attribute **items**
- **get\_items\_from\_category(category: character or numeric, value: character,**  
**force\_character: logical):** vector(character) or vector(numeric)
- **get\_tnp(tnp: character or TransactionSet or see attribute nodes or patterns, entities: character):**  
TransactionSet or see attribute **nodes** or **patterns**
- **get\_tnp\_itemsets(tnp: character or list(vector(character)), entities: character):**  
list(vector(character))
- **which\_entities(npr: see attribute nodes or patterns or return of function extract\_rules,**  
**entities: character):** character
- **which\_associated\_links(name: character):** character
- **which\_name(name: character or vector(character)):** character or vector(character)