Types of attributes and methods of the class TransactionSet

Notation

- *T* denotes the number of transactions.
- ullet N denotes the number of names associated with the transactions.
- + denotes public attributes and methods (i.e., exported attributes and methods).
- — denotes private attributes and methods (i.e., non-exported attributes and methods).

Attributes

+ data: list(named list)

Stransaction1

name 1	vector
name 2	vector
name N	vector

\$transaction2

name 1	vector
name 2	vector
:	
name N	vector

StransactionT

name 1	vector
name 2	vector
•••	
name N	vector

+ names: vector(character)+ item_key: character

+ year_key: character

Methods

+ transaction.set(data: see attribute data, item_key: see attribute item_key,

year_key: see attribute year_key, names: see attribute names): TransactionSet

+ as(Class: "data.frame"): data.frame

+ as(Class: "transactions"): transactions (class from the package arules)

+ **subset(indices**: vector(numeric) or vector(logical), **keep_names**: logical): TransactionSet

+ reorder(permutation: vector(numeric) or vector(character)): TransactionSet

+ export(...)

+ get_all_items(): vector

+ get_all_years(): vector

- + get_itemsets(): list(vector)
- + **get_items_from_info(info**: named list, **presence**: character, **additional**: vector(character)): vector or named list
- + **get_info_from_items(items**: vector, **info_names**: vector(character), **presence**: character): vector or named list
- + **get_complex_trx(as_indices**: logical): TransactionSet or named vector(numeric)
- + **get_simple_trx(as_indices**: logical): TransactionSet or named vector(numeric)
- + **get_trx_from_items(items**: vector, **presence**: character, **as_indices**: logical**)**: TransactionSet or named vector(numeric)
- + **get_trx_from_info(info**: named list, **presence**: character, **as_indices**: logical**)**: TransactionSet or named vector(numeric)
- + complexity_ratio(items: vector): named vector(numeric)
- + complexity_index(items: vector): named vector(numeric)
- + co_occurrence_matrix(items: vector, proportions: logical): named matrix(numeric)
- + itemset_chart(identifiers: character, length_one: logical, jitter: logical, under: character, over: character, title: character, path: character, name: character): TransactionSet
- prepare_itemset_chart(identifiers: character, length_one: logical, under: character,

order: character): list

[["transactions"]]: TransactionSet

[["itemsets"]]: list(vector)

[["items"]]: data.frame

item	label
character or numeric	character or numeric

[["under"]]: vector(character)
[["over"]]: vector(character)

+ co_occurrence_chart(items: vector, co_occ: matrix(numeric), proportions: logical,

min_occ: numeric, max_occ: numeric, vertex_size: numeric,

vertex_alpha: numeric, vertex_margin: numeric, label_size: numeric,

label_margin: numeric, edge_looseness: numeric, edge_alpha: numeric,
palette: character or numeric, palette_direction: numeric): ggplot2 graph

- has_temporal_data(): logical
- get_items(items: character or vector): vector

Last update: 2022-01-06 2