Attribute and method types of the SpectralAnalyzer class

Notation:

- *I* designates the number of items.
- *C* designates the number of separate categories associated with the items.
- *N* designates the number of nodes.
- *P* designates the number of patterns.
- *Y* designates the number of years for which observations exist.

Attributes

observations: list

CODE	vector(character)	NAME	vector(character)	YEAR	numeric	•••	
CODE	vector(character)	NAME	vector(character)	YEAR	numeric		
•••		•••				•••	
CODE	vector(character)	NAME	vector(character)	YEAR	numeric	•••	

items: vector(character)
items_categories: data.frame

	category 1	category 2	 category C
item 1	factor	factor	 factor
item 2	factor	factor	 factor
•••	•••	•••	 •••
item I	factor	factor	 factor

target: character count: numeric min_length: numeric max_length: numeric status_limit: numeric

nodes_per_year: data.frame

node	year	weight	length
vector(character)	numeric	numeric	numeric

nodes: data.frame

node	length	weigth
vector(character)	numeric	numeric

n_links: matrix

	node 1	node 2	•••	node N
node 1	numeric	numeric		numeric
node 2	numeric	numeric		numeric
•••				•••
node N	numeric	numeric		numeric

nodes_links: data.frame

	Source	Target	ID	items	weight
ſ	numeric	numeric	numeric	character	numeric

obs_patterns: matrix

	pattern 1	pattern 2		pattern P
node 1	logical	logical		logical
node 2	logical	logical		logical
•••				•••
node N	logical	logical	•••	logical

patterns_per_year: matrix

	year 1	year 2	•••	year Y
pattern 1	numeric	numeric	•••	numeric
pattern 2	numeric	numeric		numeric
pattern P	numeric	numeric		numeric

patterns: data.frame

pattern	year	frequency	weight	order	specificity	status
vector(character)	numeric	numeric	numeric	numeric	numeric	character

p_links: matrix

	pattern 1	pattern 2		pattern P
pattern 1	numeric	numeric		numeric
pattern 2	numeric	numeric		numeric
pattern P	numeric	numeric	•••	numeric

patterns_links: data.frame

Source	Target	ID	items	weight	year
numeric	numeric	numeric	character	numeric	numeric

Methods

spectral.analyzer(observations: see attribute observations, items: see data.frame below,

target: character, count: numeric, min_length: numeric, max_length: numeric,

status_limit: numeric)

item	category 1	category 2	 category C
character	factor	factor	 factor

list_obs_per_year(): see attribute nodes_per_year

list_separate_obs(): see attribute nodes

count_links(entities: character): see attributes n_links and p_links

search_links(entities: character): see attributes nodes_links and patterns_links

list_separate_patterns(target: character, count: numeric, min_length: numeric,

max_length: numeric): data.frame

pattern	weight
vector(character)	numeric

list_patterns_by_obs(): see attribute obs_patterns

list_patterns_per_year(): see attribute patterns_per_year
compute_patterns_characteristics(): see attribute patterns

compute_specificity(patterns: list(vector(numeric)), frequencies: vector(numeric),

weights: vector(numeric)): vector(numeric)

compute_ksi_threshold(reporting_indexes: vector(numeric)): numeric

compute_ri_threshold(reporting_indexes: vector(numeric), ksi: numeric): numeric

compute_reporting_indexes(patterns: list(vector(numeric)), t: numeric, period: numeric):
data.frame

pattern	ri	
vector(character)	numeric	

check_params_for_RI(t: numeric, period: numeric): list

t	numeric
period	numeric

compute_reporting_indexes_limits(patterns: list(vector(numeric)), first_limit: numeric, t: numeric,

period: numeric): data.frame

pattern	ri_2	ri_period
vector(character)	numeric	numeric

define_dynamic_status(patterns: list(vector(numeric)), status_limit: numeric, t: numeric,

period: numeric): data.frame

pattern	Status
vector(character)	character

spectrum_chart(patterns_characteristics: see attribute patterns, path: character, name: character,

title: character): data.frame

ID	pattern	frequency	weight	order	specificity	status
numeric	vector(character)	numeric	numeric	numeric	numeric	character

create_spectrum_chart(patterns_characteristics: see attribute patterns,

weights_by_node_type: see data.frame below, title: character)

numeric	numeric
complex nodes	simple node

compute_pattern_distribution_in_nodes(patterns: list(vector(numeric))): list

[["weight_distribution"]]:

1	vector(numeric)
2	vector(numeric)
•••	•••
Р	vector(numeric)

[["length_distribution"]]:

1	vector(numeric)
2	vector(numeric)
•••	•••
Р	vector(numeric)

spectrosome_chart(entities : character, characteristics: see attribute nodes or patterns,

nb_graph: numeric, vertex_size: character, path: character, name: character,

title: character): list

[["vertices"]]:

ID	node	length	weight
numeric	vector(character)	numeric	numeric

or

ID	pattern	frequency	weight	order	specificity	status
numeric	vector(character)	numeric	numeric	numeric	numeric	character

[["edges"]]: see attribute **nodes_links** or **patterns_links**

cluster_text(graph: see matrix below, links: see attribute patterns_links)

	Х	У
vertex 1	numeric	numeric
vertex 2	numeric	numeric
•••		
vertex P	numeric	numeric

cluster_chart(entities: character, item: numeric, vertex_size: character, path: character,

name: character, title: character): list

[["vertices"]]:

ID	node	length	weight	
numeric	vector(character)	numeric	numeric	

or

ID	pattern	frequency	weight	order	specificity	status
numeric	vector(character)	numeric	numeric	numeric	numeric	character

[["edges"]]: see attribute nodes_links or patterns_links

save_characteristics(entities: character, characteristics: see attribute nodes or patterns, ...)

extract_patterns_from_items(patterns_characteristics: see attribute patterns,

items: vector(numeric), target: character): see attribute patterns

extract_patterns_from_characteristic(patterns_characteristics: see attribute patterns,

characteristic: character, value: numeric,

condition: character): see attribute patterns

extract_patterns_from_status(patterns_characteristics: see attribute patterns,

value: vector(character), condition: character): see attribute patterns

extract_nodes_from_items(nodes_characteristics: see attribute nodes, items: vector(numeric),

target: character): see attribute nodes

extract_nodes_from_characteristic(nodes_characteristics: see attribute nodes,

characteristic: character, value: numeric,
condition: character): see attribute nodes

check_access_for_category(category: character | numeric, value: character)

extract_patterns_from_category(category: character | numeric, value: character,

target: character): see attribute patterns

extract_nodes_from_category(category: character | numeric, value: character,

target: character): see attribute nodes