

SPECIFICATIONS:

- A. 22 AWG 19X34BC STRAND O.D. .029±.001
- B. 8 MIL POLYPROPYLENE INSULATION 6.5 MIL MINIMUM MIN PP INSULATION AWM STYLE 10152 80C 300V O.D. .047±.002
- C. 22 AWG 19X.0058TC DRAIN WIRE O.D. .029±.001
- D. POLY FILLER AS REQUIRED
- E. ALUMINUM MYLAR FOIL WRAP (FOIL IN)
- F. 30 MIL PRESSURED POLYURETHANE JACKET 27 MIL MINIMUM PRESSURED POLYURETHANE JACKET

CABLE JACKET: BLACK

WIRE COLORS: BLUE, RED, BLACK, VIOLET, WHITE, BROWN,

GREEN, YELLOW, GRAY, PINK, GRAY W/ PINK, RED W/ BLUE, BROWN W/ GREEN, WHITE W/

GREEN

LEGEND: WHITE INK PRINT

PRINT: P14C-22GBK RU AWM E54661 80C 300V CSA AWM

LL54185 I/II A/B 80C 300V FT1

PRODUCT IS UL AND CSA RECOGNIZED.

DRAIN POSITION MAY VARY.

PRODUCT IS MANUFACTURED USING ROHS COMPLIANT

MATERIALS.



PA	RT NO:	P14C-	22GBK			•			
DES	DESCRIPTION: CBL 22G 14C FD BLK PU JKT UL CSA 0.285							Electronic Supply Ltd	
REV	2.0	SIZE	SHEET NO.	-	OF	-		Electronic Parts Sales and Custom Cable Manufacturin	
	THIS INFORMATION IS CONFIDENTIAL AND DISCLOSED TO YOU ON CONDITION THAT NO							2240 Pegasus Rd NE, Calgary, AB T2E 8G8 Ph: 403-291-0500 Toll Free: 1-800-882-930 www.mroelectronics.com	

FURTHER DISCLOSURE IS MADE WITHOUT AUTHORIZATION FROM MRO

 2.0
 NEW FORMAT
 AR
 06-04-18

 REV NO.
 DESCRIPTION
 DRN
 DATE