

epiworld

0.0-1

Generated by Doxygen 1.9.1

1 Main Page	1
1.1 epiworld	1
1.2 Hello world	1
1.2.1 Tools	2
1.2.2 Contagion	2
2 Class Index	3
2.1 Class List	3
3 Class Documentation	5
3.1 Action< TSeq > Struct Template Reference	5
3.1.1 Detailed Description	6
3.1.2 Constructor & Destructor Documentation	6
3.1.2.1 Action()	6
3.2 AdjList Class Reference	7
3.2.1 Constructor & Destructor Documentation	7
3.2.1.1 AdjList()	7
3.3 DataBase< TSeq > Class Template Reference	8
3.3.1 Detailed Description	9
3.3.2 Member Function Documentation	9
3.3.2.1 record_variant()	9
3.4 LFMCMC< TData > Class Template Reference	9
3.4.1 Detailed Description	10
3.5 Location< TSeq > Class Template Reference	11
3.6 Model< TSeq > Class Template Reference	11
3.6.1 Detailed Description	17
3.6.2 Member Function Documentation	17
3.6.2.1 add_global_action()	17
3.6.2.2 reset()	17
3.6.2.3 run_multiple()	18
3.6.2.4 write_data()	18
3.7 Person< TSeq > Class Template Reference	19
3.7.1 Detailed Description	20
3.8 PersonTools< TSeq > Class Template Reference	20
3.8.1 Detailed Description	21
3.9 PersonViruses< TSeq > Class Template Reference	21
3.9.1 Detailed Description	22
3.10 Progress Class Reference	22
3.10.1 Detailed Description	23
3.11 Queue< TSeq > Class Template Reference	23
3.11.1 Detailed Description	23
3.12 RandGraph Class Reference	23
3.13 Tool< TSeq > Class Template Reference	24

3.13.1 Detailed Description	25
3.14 UserData< TSeq > Class Template Reference	25
3.14.1 Detailed Description	26
3.14.2 Constructor & Destructor Documentation	27
3.14.2.1 UserData()	27
3.15 vecHasher< T > Struct Template Reference	27
3.15.1 Detailed Description	27
3.16 Virus< TSeq > Class Template Reference	28
3.16.1 Detailed Description	29
Index	31

Chapter 1

Main Page

1.1 epiworld

This C++ template-header-only library provides a general framework for epidemiologic simulation. The main features of the library are:

1. Four key classes: `Model`, `Person`, `Tool`, and `Virus`.
2. The model features a social networks of `Persons`.
3. `Persons` can have multiple `Tools` as a defense system.
4. `Tools` can reduce contagion rate, transmissibility, death rates, and improve recovery rates.
5. `Viruses` can mutate (generating new variants).
6. `Models` can feature multiple states, e.g., `HEALTHY`, `SUSCEPTIBLE`, etc.
7. `Models` can have an arbitrary number of parameters.
8. **REALLY FAST** About 6.5 Million person/day simulations per second.

1.2 Hello world

Here is a simple SIRS model implemented with

```
#include "../include/epiworld/epiworld.hpp"
using namespace epiworld;
int main()
{
    // Creating a model
    Model<> model;
    // Adding the tool and virus
    Virus<> virus("covid 19");
    virus.set_post_immunity(1.0);
    model.add_virus_n(virus, 5);

    Tool<> tool("vaccine");
    model.add_tool(tool, .5);
    // Generating a random pop
    model.population_smallworld(100000);
    // Initializing setting days and seed
    model.init(100, 123);
}
```

```
// Running the model
model.run();
model.print();

}
```

And you should get something like the following:

Running the model...

```
||||| done.

SIMULATION STUDY
Population size      : 100000
Days (duration)     : 100 (of 100)
Number of variants  : 1
Last run elapsed t   : 280.00ms
Rewiring             : off
Virus(es):
- covid 19 (baseline prevalence: 5 seeds)
Tool(s):
- vaccine (baseline prevalence: 50.00%)
Model parameters:
Distribution of the population at time 100:
- Total healthy (S)   : 99995 -> 97390
- Total recovered (S) : 0 -> 2554
- Total infected (I)  : 5 -> 56
- Total removed (R)   : 0 -> 0
(S): Susceptible, (I): Infected, (R): Recovered
```

Which took about 0.280 seconds.

1.2.1 Tools

1.2.2 Contagion

Susceptible individuals can acquire a virus from any of their infected connections. The probability that susceptible individual i gets the virus v from individual j depends on how three things:

1. The transmissibility of the virus, τ_v ,
2. The contagion reduction factor of i , ρ_i , and
3. The host's transmission reduction factor, ρ_j .

The last two are computed from ρ and τ 's tools. Ultimately, the probability of getting virus v from j equals:

Nonetheless, the default behavior of the simulation model is to assume that individuals can acquire only one disease at a time, if any. This way, the actual probability is:

The latter is calculated using Bayes' rule

Where

This way, viruses with higher transmissibility will be more likely to be acquired when competing with other variants.

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Action< TSeq >	
Action data for update an agent	5
AdjList	7
DataBase< TSeq >	
Statistical data about the process	8
LFMCMC< TData >	
Likelihood-Free Markov Chain Monte Carlo	9
Location< TSeq >	11
Model< TSeq >	
Core class of epiworld	11
Person< TSeq >	
Person (agents)	19
PersonTools< TSeq >	
List of tools available for the individual to	20
PersonViruses< TSeq >	
Set of viruses in host	21
Progress	
A simple progress bar	22
Queue< TSeq >	
Controls which agents are verified at each step	23
RandGraph	23
Tool< TSeq >	
Tools for defending the host against the virus	24
UserData< TSeq >	
Personalized data by the user	25
vecHasher< T >	
Vector hasher	27
Virus< TSeq >	
Virus	28

Chapter 3


Class Documentation

3.1 Action< TSeq > Struct Template Reference

[Action](#) data for update an agent.

```
#include <config.hpp>
```

Collaboration diagram for Action< TSeq >:



Public Member Functions

- [Action](#) ([Person](#)< TSeq > ***person**_, VirusPtr< TSeq > **virus**_, ToolPtr< TSeq > **tool**_, epiworld_fast_uint **virus_idx**_, epiworld_fast_uint **tool_idx**_, epiworld_fast_int **new_status**_, epiworld_fast_int **queue**_, ActionFun< TSeq > **call**_)

Construct a new [Action](#) object.

Public Attributes

- [Person](#)< TSeq > * **person**
- VirusPtr< TSeq > **virus**
- ToolPtr< TSeq > **tool**
- epiworld_fast_uint **virus_idx**
- epiworld_fast_uint **tool_idx**
- epiworld_fast_int **new_status**
- epiworld_fast_int **queue**
- ActionFun< TSeq > **call**

3.1.1 Detailed Description

```
template<typename TSeq>
struct Action< TSeq >
```

[Action](#) data for update an agent.

Template Parameters

<i>TSeq</i>	
-------------	--

3.1.2 Constructor & Destructor Documentation

3.1.2.1 Action()

```
template<typename TSeq >
Action< TSeq >::Action (
    Person< TSeq > * person_,
    VirusPtr< TSeq > virus_,
    ToolPtr< TSeq > tool_,
    epiworld_fast_uint virus_idx_,
    epiworld_fast_uint tool_idx_,
    epiworld_fast_int new_status_,
    epiworld_fast_int queue_,
    ActionFun< TSeq > call_ ) [inline]
```

Construct a new [Action](#) object.

All the parameters are rather optional.

Parameters

<i>person_</i>	Person over who the action will happen
<i>virus_</i>	Virus to add
<i>tool_</i>	Tool to add
<i>virus_idx</i>	Index of virus to be removed (if needed)
<i>tool_idx</i>	Index of tool to be removed (if needed)
<i>new_↔ status_</i>	Next status
<i>queue_</i>	Effect on the queue
<i>call_</i>	The action call (if needed)

The documentation for this struct was generated from the following file:

- include/epiworld/config.hpp

3.2 AdjList Class Reference

Public Member Functions

- [AdjList](#) (const std::vector< unsigned int > &source, const std::vector< unsigned int > &target, bool directed, int min_id=-1, int max_id=-1)
Construct a new Adj List object.
- void **read_edgelist** (std::string fn, int skip=0, bool directed=true, int min_id=-1, int max_id=-1)
- std::map< unsigned int, unsigned int > **operator()** (unsigned int i) const
- void **print** (unsigned int limit=20u) const
- unsigned int **get_id_max** () const
- unsigned int **get_id_min** () const
- size_t **vcount** () const
- size_t **ecount** () const
- std::map< unsigned int, std::map< unsigned int, unsigned int > > & **get_dat** ()
- bool **is_directed** () const

3.2.1 Constructor & Destructor Documentation

3.2.1.1 AdjList()

```
AdjList::AdjList (
    const std::vector< unsigned int > & source,
    const std::vector< unsigned int > & target,
    bool directed,
    int min_id = -1,
    int max_id = -1 ) [inline]
```

Construct a new Adj List object.

It will create an adjacency list object with `maxid - minid + 1` nodes. If `min_id` and `max_id` are not specified (both < 0), then the program will try to figure them out automatically by looking at the range of the observed ids.

Parameters

<i>source</i>	Unsigned int vector with the source
<i>target</i>	Unsigned int vector with the target
<i>directed</i>	Bool true if the network is directed
<i>min_id</i>	int min id.
<i>max_id</i>	int max id.

The documentation for this class was generated from the following files:

- include/epiworld/adjlist-bones.hpp
- include/epiworld/adjlist-meat.hpp

3.3 DataBase< TSeq > Class Template Reference

Statistical data about the process.

```
#include <database-bones.hpp>
```

Public Member Functions

- **DataBase** (int freq=1)
- void **record_variant** ([Virus](#)< TSeq > &v)
Registering a new variant.
- void **record_tool** ([Tool](#)< TSeq > &t)
- void **set_seq_hasher** (std::function< std::vector< int >(TSeq)> fun)
- void **set_model** ([Model](#)< TSeq > &m)
- [Model](#)< TSeq > * **get_model** ()
- void **record** ()
- const std::vector< TSeq > & **get_sequence** () const
- const std::vector< int > & **get_nexposed** () const
- size_t **size** () const
- void **write_data** (std::string fn_variant_info, std::string fn_variant_hist, std::string fn_tool_info, std::string fn_tool_hist, std::string fn_total_hist, std::string fn_transmission, std::string fn_transition) const
- void **record_transmission** (int i, int j, int variant)
- size_t **get_nvariants** () const
- void **reset** ()
- void **set_user_data** (std::vector< std::string > names)
- void **add_user_data** (std::vector< epiworld_double > x)
- void **add_user_data** (unsigned int j, epiworld_double x)
- [UserData](#)< TSeq > & **get_user_data** ()

Get recorded information from the model

Parameters

what	<i>std::string, The status, e.g., 0, 1, 2, ...</i>
------	--

Returns

*In **get_today_total**, the current counts of what.*

*In **get_today_variant**, the current counts of what for each variant.*

*In **get_hist_total**, the time series of what*

*In **get_hist_variant**, the time series of what for each variant.*

*In **get_hist_total_date** and **get_hist_variant_date** the corresponding dates*

- int **get_today_total** (std::string what) const
- int **get_today_total** (epiworld_fast_uint what) const
- void **get_today_total** (std::vector< std::string > *status=nullptr, std::vector< int > *counts=nullptr) const
- void **get_today_variant** (std::vector< std::string > &status, std::vector< int > &id, std::vector< int > &counts) const
- void **get_hist_total** (std::vector< int > *date, std::vector< std::string > *status, std::vector< int > *counts) const
- void **get_hist_variant** (std::vector< int > &date, std::vector< int > &id, std::vector< std::string > &status, std::vector< int > &counts) const

Friends

- class **Model**< TSeq >
- void **default_add_virus** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)
- void **default_add_tool** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)
- void **default_rm_virus** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)
- void **default_rm_tool** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)

3.3.1 Detailed Description

```
template<typename TSeq>
class DataBase< TSeq >
```

Statistical data about the process.

Template Parameters

<i>TSeq</i>	
-------------	--

3.3.2 Member Function Documentation

3.3.2.1 record_variant()

```
template<typename TSeq >
void DataBase< TSeq >::record_variant (
    Virus< TSeq > & v ) [inline]
```

Registering a new variant.

Parameters

<i>v</i>	Pointer to the new variant. Since variants are originated in the host, the numbers simply move around. From the parent variant to the new variant. And the total number of infected does not change.
----------	--

The documentation for this class was generated from the following files:

- include/epiworld/database-bones.hpp
- include/epiworld/database-meat.hpp

3.4 LFMCMC< TData > Class Template Reference

Likelihood-Free Markov Chain Monte Carlo.

```
#include <lfmcmc.hpp>
```

Public Member Functions

- void **run** (VEC(epiworld_double) param_init, size_t n_samples_, epiworld_double epsilon_)
- **LFMCMC** (TData &observed_data_)
- void **set_observed_data** (TData &observed_data_)
- void **set_proposal_fun** (FUN< void(VEC(epiworld_double)&, LFMCMC< TData > *)> fun)
- void **set_simulation_fun** (FUN< TData(VEC(epiworld_double)&, LFMCMC< TData > *)> fun)
- void **set_summary_fun** (FUN< VEC(epiworld_double)(TData &, LFMCMC< TData > *)> fun)
- void **set_kernel_fun** (FUN< epiworld_double(VEC(epiworld_double)&, epiworld_double, LFMCMC< TData > *)> fun)
- const size_t **get_n_samples** ()
- const size_t **get_n_statistics** ()
- const size_t **get_n_parameters** ()
- const epiworld_double **get_epsilon** ()
- const **VEC** (epiworld_double) &get_params_now()
- const **VEC** (epiworld_double) &get_params_prev()
- const **VEC** (epiworld_double) &get_params_init()
- const **VEC** (epiworld_double) &get_statistics_obs()
- const **VEC** (epiworld_double) &get_statistics_hist()
- const **VEC** (bool) &get_statistics_accepted()
- const **VEC** (epiworld_double) &get_posterior_if_prob()
- const **VEC** (epiworld_double) &get_acceptance_prob()
- const **VEC** (epiworld_double) &get_drawn_prob()
- **VEC** (TData) *get_sampled_data()

Random number generation

Parameters

eng	
-----	--

- void **set_rand_engine** (std::mt19937 &eng)
- std::mt19937 * **get_rand_engine** ()
- void **seed** (unsigned int s)
- void **set_rand_gamma** (epiworld_double alpha, epiworld_double beta)
- epiworld_double **runif** ()
- epiworld_double **rnorm** ()
- epiworld_double **rnorm** (epiworld_double mean, epiworld_double sd)
- epiworld_double **rgamma** ()
- epiworld_double **rgamma** (epiworld_double alpha, epiworld_double beta)

3.4.1 Detailed Description

```
template<typename TData>
class LFMCMC< TData >
```

Likelihood-Free Markov Chain Monte Carlo.

Template Parameters

<i>TData</i>	Type of data that is generated
--------------	--------------------------------

The documentation for this class was generated from the following file:

- include/epiworld/math/lfmcmc.hpp

3.5 Location< TSeq > Class Template Reference

Public Member Functions

- **add_person** ([Person](#)< TSeq > &p)
- **add_person** ([Person](#)< TSeq > *p)
- **size_t count** () const
- **void reset** ()

The documentation for this class was generated from the following file:

- include/epiworld/location-bones.hpp

3.6 Model< TSeq > Class Template Reference

Core class of epiworld.

```
#include <model-bones.hpp>
```

Public Member Functions

- [DataBase](#)< TSeq > & **get_db** ()
- epiworld_double & **operator()** (std::string pname)
- **size_t size** () const
- **void record_variant** ([Virus](#)< TSeq > &v)
- **void record_tool** ([Tool](#)< TSeq > &t)
- **int get_nvariants** () const
- **unsigned int get_ndays** () const
- **unsigned int get_n_replicates** () const
- **void set_ndays** (unsigned int ndays)
- **bool get_verbose** () const
- **void verbose_off** ()
- **void verbose_on** ()
- **int today** () const
- *The current time of the model.*
- **void write_data** (std::string fn_variant_info, std::string fn_variant_hist, std::string fn_tool_info, std::string fn_tool_hist, std::string fn_total_hist, std::string fn_transmission, std::string fn_transition) const
- *Wrapper of DataBase::write_data*
- **std::map< std::string, epiworld_double > & params** ()
- **void reset** ()
- *Reset the model.*
- **void print** () const
- [Model](#)< TSeq > && **clone** () const

- void **get_elapsed** (std::string unit="auto", epiworld_double *last_elapsed=nullptr, epiworld_double *total_elapsed=nullptr, std::string *unit_abbr=nullptr, bool print=true) const
- void **add_global_action** (std::function< void([Model](#)< TSeq > *)> fun, int date)
Set a global action.
- void **run_global_actions** ()
- void **clear_status_set** ()
- const std::vector< VirusPtr< TSeq > > & **get_viruses** () const
- const std::vector< ToolPtr< TSeq > > & **get_tools** () const

Set the backup object

backup can be used to restore the entire object after a run. This can be useful if the user wishes to have individuals start with the same network from the beginning.

- void **set_backup** ()
- void **restore_backup** ()

Random number generation

Parameters

eng	Random number generator
s	Seed

- void **set_rand_engine** (std::mt19937 &eng)
- std::mt19937 * **get_rand_engine** ()
- void **seed** (unsigned int s)
- void **set_rand_gamma** (epiworld_double alpha, epiworld_double beta)
- epiworld_double **runif** ()
- epiworld_double **rnorm** ()
- epiworld_double **rnorm** (epiworld_double mean, epiworld_double sd)
- epiworld_double **rgamma** ()
- epiworld_double **rgamma** (epiworld_double alpha, epiworld_double beta)

Add Virus/Tool to the model

This is done before the model has been initialized.

Parameters

v	Virus to be added
t	Tool to be added
preval	Initial prevalence (initial state.) It can be specified as a proportion (between zero and one,) or an integer indicating number of individuals.

- void **add_virus** ([Virus](#)< TSeq > v, epiworld_double preval)
- void **add_virus_n** ([Virus](#)< TSeq > v, unsigned int preval)
- void **add_tool** ([Tool](#)< TSeq > t, epiworld_double preval)
- void **add_tool_n** ([Tool](#)< TSeq > t, unsigned int preval)

Accessing population of the model

Parameters

fn	std::string Filename of the edgelist file.
----	--

Parameters

skip	<i>int</i> Number of lines to skip in <i>fn</i> .
directed	<i>bool</i> Whether the graph is directed or not.
min_id	<i>int</i> Minimum id number (if negative, the program will try to guess from the data.)
max_id	<i>int</i> Maximum id number (if negative, the program will try to guess from the data.)
al	AdjList to read into the model.

- void **population_from_adjlist** (std::string fn, int skip=0, bool directed=false, int min_id=-1, int max_id=-1)
- void **population_from_adjlist** ([AdjList](#) al)
- bool **is_directed** () const
- std::vector< [Person](#)< TSeq > > * **get_population** ()
- void **population_smallworld** (unsigned int n=1000, unsigned int k=5, bool d=false, epiworld_double p=.↵01)

Functions to run the model*Parameters*

seed	<i>Seed to be used for Pseudo-RNG.</i>
ndays	<i>Number of days (steps) of the simulation.</i>
fun	<i>In the case of <code>run_multiple</code>, a function that is called after each experiment.</i>

- void **init** (unsigned int ndays, unsigned int seed)
- void **update_status** ()
- void **mutate_variant** ()
- void **next** ()
- void **run** ()
- *Runs the simulation (after initialization)*
- void **run_multiple** (unsigned int nexperiments, std::function< void([Model](#)< TSeq > *)> fun, bool [reset](#), bool verbose)

Rewire the network preserving the degree sequence.

This implementation assumes an undirected network, thus if $\{(i,j), (k,l)\} \rightarrow \{(i,l), (k,j)\}$, the reciprocal is also true, i.e., $\{(j,i), (l,k)\} \rightarrow \{(j,k), (l,i)\}$.

Parameters

proportion	<i>Proportion of ties to be rewired.</i>
------------	--

Returns

A rewired version of the network.

- void **set_rewire_fun** (std::function< void(std::vector< [Person](#)< TSeq > > *, [Model](#)< TSeq > *, epiworld_double)> fun)
- void **set_rewire_prop** (epiworld_double prop)
- epiworld_double **get_rewire_prop** () const
- void **rewire** ()

Export the network data in edgelist form

Parameters

fn	<i>std::string</i> . File name.
source	<i>Integer vector</i>
target	<i>Integer vector</i>

When passing the source and target, the function will write the edgelist on those.

- void **write_edgelist** (std::string fn) const
- void **write_edgelist** (std::vector< unsigned int > &source, std::vector< unsigned int > &target) const

Manage status (states) in the model

The functions *get_status* return the current values for the statuses included in the model.

Parameters

lab	<i>std::string</i> Name of the status.
-----	--

Returns

*add_status** returns nothing.

*get_status_** returns a vector of pairs with the statuses and their labels.

- void **add_status** (std::string lab, UpdateFun< TSeq > fun=nullptr)
- const std::vector< std::string > & **get_status** () const
- const std::vector< UpdateFun< TSeq > > & **get_status_fun** () const
- void **print_status_codes** () const

Set the user data object*Parameters*

names	<i>string vector with the names of the variables.</i>
-------	---

- void **set_user_data** (std::vector< std::string > names)
- void **add_user_data** (unsigned int j, epiworld_double x)
- void **add_user_data** (std::vector< epiworld_double > x)
- **UserData**< TSeq > & **get_user_data** ()

Queuing system

When queueing is on, the model will keep track of which agents are either in risk of exposure or exposed. This then is used at each step to act only on the aforementioned agents.

- void **queueing_on** ()
Activates the queueing system (default.)
- void **queueing_off** ()
Deactivates the queueing system.
- bool **is_queueing_on** () const
Query if the queueing system is on.
- **Queue**< TSeq > & **get_queue** ()
Retrieve the *Queue* object.

Get the susceptibility reduction object

Parameters

v	
---	--

Returns

epiworld_double

- void **set_susceptibility_reduction_mixer** (MixerFun< TSeq > fun)
- void **set_transmission_reduction_mixer** (MixerFun< TSeq > fun)
- void **set_recovery_enhancer_mixer** (MixerFun< TSeq > fun)
- void **set_death_reduction_mixer** (MixerFun< TSeq > fun)

Friends

- class **Person**< TSeq >
- class **DataBase**< TSeq >
- class **Queue**< TSeq >

Tool Mixers

These functions combine the effects tools have to deliver a single effect. For example, wearing a mask, been vaccinated, and the immune system combine together to jointly reduce the susceptibility for a given virus.

- std::vector< epiworld_double > **array_double_tmp**
- std::vector< VirusPtr< TSeq > * > **array_virus_tmp**
- **Model** ()
- **Model** (const [Model](#)< TSeq > &m)
- **Model** ([Model](#)< TSeq > &&m)
- [Model](#)< TSeq > & **operator=** (const [Model](#)< TSeq > &m)
- void **clone_population** (std::vector< [Person](#)< TSeq > > &p, std::map< int, int > &p_ids, bool &d, [Model](#)< TSeq > *m=nullptr) const
- void **clone_population** (const [Model](#)< TSeq > &m)

Setting and accessing parameters from the model

Tools can incorporate parameters included in the model. Internally, parameters in the tool are stored as pointers to an std::map<> of parameters in the model. Using the `unsigned int` method directly fetches the parameters in the order these were added to the tool. Accessing parameters via the `std::string` method involves searching the parameter directly in the std::map<> member of the model (so it is not recommended.)

The function `set_param()` can be used when the parameter already exists in the model.

The `par()` function members are aliases for `get_param()`.

Parameters

<i>initial_val</i>	
<i>pname</i>	Name of the parameter to add or to fetch

Returns

The current value of the parameter in the model.

- `epiworld_double * p0`
- `epiworld_double * p1`
- `epiworld_double * p2`
- `epiworld_double * p3`
- `epiworld_double * p4`
- `epiworld_double * p5`
- `epiworld_double * p6`
- `epiworld_double * p7`
- `epiworld_double * p8`
- `epiworld_double * p9`
- `epiworld_double * p10`
- `epiworld_double * p11`
- `epiworld_double * p12`
- `epiworld_double * p13`
- `epiworld_double * p14`
- `epiworld_double * p15`
- `epiworld_double * p16`
- `epiworld_double * p17`
- `epiworld_double * p18`
- `epiworld_double * p19`
- `epiworld_double * p20`
- `epiworld_double * p21`
- `epiworld_double * p22`
- `epiworld_double * p23`
- `epiworld_double * p24`
- `epiworld_double * p25`
- `epiworld_double * p26`
- `epiworld_double * p27`
- `epiworld_double * p28`
- `epiworld_double * p29`
- `epiworld_double * p30`
- `epiworld_double * p31`
- `epiworld_double * p32`
- `epiworld_double * p33`
- `epiworld_double * p34`
- `epiworld_double * p35`
- `epiworld_double * p36`
- `epiworld_double * p37`
- `epiworld_double * p38`
- `epiworld_double * p39`
- `unsigned int npar_used = 0u`
- `epiworld_double add_param (epiworld_double initial_val, std::string pname)`
- `epiworld_double set_param (std::string pname)`
- `epiworld_double get_param (unsigned int k)`
- `epiworld_double get_param (std::string pname)`
- `epiworld_double par (unsigned int k)`
- `epiworld_double par (std::string pname)`

3.6.1 Detailed Description

```
template<typename TSeq = int>
class Model< TSeq >
```

Core class of epiworld.

The model class provides the wrapper that puts together [Person](#), [Virus](#), and [Tools](#).

Template Parameters

<i>TSeq</i>	Type of sequence. In principle, users can build models in which virus and human sequence is represented as numeric vectors (if needed.)
-------------	---

3.6.2 Member Function Documentation

3.6.2.1 add_global_action()

```
template<typename TSeq = int>
void Model< TSeq >::add_global_action (
    std::function< void (Model< TSeq > *)> fun,
    int date )
```

Set a global action.

Parameters

<i>fun</i>	A function to be called on the prescribed dates
<i>date</i>	Integer indicating when the function is called (see details)

When date is less than zero, then the function is called at the end of every day. Otherwise, the function will be called only at the end of the indicated date.

3.6.2.2 reset()

```
template<typename TSeq = int>
void Model< TSeq >::reset ( )
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)

- re-distribute tools
- re-distribute viruses
- set the date to 0

3.6.2.3 run_multiple()

```
template<typename TSeq = int>
void Model< TSeq >::run_multiple (
    unsigned int n_experiments,
    std::function< void(Model< TSeq > *)> fun,
    bool reset,
    bool verbose )
```

Parameters

<i>n_experiments</i>	Multiple runs of the simulation
----------------------	---------------------------------

3.6.2.4 write_data()

```
template<typename TSeq = int>
void Model< TSeq >::write_data (
    std::string fn_variant_info,
    std::string fn_variant_hist,
    std::string fn_tool_info,
    std::string fn_tool_hist,
    std::string fn_total_hist,
    std::string fn_transmission,
    std::string fn_transition ) const
```

Wrapper of DataBase::write_data

Parameters

<i>fn_variant_info</i>	Filename. Information about the variant.
<i>fn_variant_hist</i>	Filename. History of the variant.
<i>fn_tool_info</i>	Filename. Information about the tool.
<i>fn_tool_hist</i>	Filename. History of the tool.
<i>fn_total_hist</i>	Filename. Aggregated history (status)
<i>fn_transmission</i>	Filename. Transmission history.
<i>fn_transition</i>	Filename. Markov transition history.

The documentation for this class was generated from the following files:

- include/epiworld/config.hpp
- include/epiworld/model-bones.hpp

3.7 Person< TSeq > Class Template Reference

Person (agents)

```
#include <person-bones.hpp>
```

Public Member Functions

- **Person** (const Person< TSeq > &p)
- int **get_id** () const
Id of the individual.
- unsigned int **get_index** () const
Location (0, ..., n-1).
- std::mt19937 * **get_rand_engine** ()
- Model< TSeq > * **get_model** ()
- VirusPtr< TSeq > & **get_virus** (int i)
- std::vector< VirusPtr< TSeq > > & **get_viruses** ()
- size_t **get_n_viruses** () const noexcept
- ToolPtr< TSeq > & **get_tool** (int i)
- std::vector< ToolPtr< TSeq > > & **get_tools** ()
- size_t **get_n_tools** () const noexcept
- void **mutate_variant** ()
- void **add_neighbor** (Person< TSeq > *p, bool check_source=true, bool check_target=true)
- std::vector< Person< TSeq > * > & **get_neighbors** ()
- void **change_status** (epiworld_fast_uint new_status, epiworld_fast_int queue=0)
- const epiworld_fast_uint & **get_status** () const
- void **reset** ()
- bool **has_tool** (unsigned int t) const
- bool **has_tool** (std::string name) const
- bool **has_virus** (unsigned int t) const
- bool **has_virus** (std::string name) const
- bool **is_locked** () const noexcept

Add/Remove Virus/Tool

Calling any of these functions will lock the agent (person) until the action is applied at the end of the iteration.
Calling any of this functions when the agent is locked will cause an error.

Parameters

tool	<i>Tool to add</i>
virus	<i>Virus to add</i>
status_new	<i>Status after the change</i>
queue	

- void **add_tool** (ToolPtr< TSeq > tool, epiworld_fast_int status_new=-99, epiworld_fast_int queue=-99)
- void **add_tool** (Tool< TSeq > tool, epiworld_fast_int status_new=-99, epiworld_fast_int queue=-99)
- void **add_virus** (VirusPtr< TSeq > virus, epiworld_fast_int status_new=-99, epiworld_fast_int queue=-99)
- void **add_virus** (Virus< TSeq > virus, epiworld_fast_int status_new=-99, epiworld_fast_int queue=-99)
- void **rm_tool** (epiworld_fast_uint tool_idx, epiworld_fast_int status_new=-99, epiworld_fast_int queue=-99)

- void **rm_virus** (epiworld_fast_uint virus_idx, epiworld_fast_int status_new=-99, epiworld_fast_int queue=-99)

Get the rates (multipliers) for the agent

Parameters

v	A pointer to a virus.
---	-----------------------

Returns

epiworld_double

- epiworld_double **get_susceptibility_reduction** (VirusPtr< TSeq > v)
- epiworld_double **get_transmission_reduction** (VirusPtr< TSeq > v)
- epiworld_double **get_recovery_enhancer** (VirusPtr< TSeq > v)
- epiworld_double **get_death_reduction** (VirusPtr< TSeq > v)

Friends

- class **Model**< TSeq >
- class **Tool**< TSeq >
- class **Queue**< TSeq >
- void **default_add_virus** (Action< TSeq > &a, Model< TSeq > *m)
- void **default_add_tool** (Action< TSeq > &a, Model< TSeq > *m)
- void **default_rm_virus** (Action< TSeq > &a, Model< TSeq > *m)
- void **default_rm_tool** (Action< TSeq > &a, Model< TSeq > *m)

3.7.1 Detailed Description

```
template<typename TSeq = int>
class Person< TSeq >
```

[Person](#) (agents)

Template Parameters

<i>TSeq</i>	Sequence type (should match TSeq across the model)
-------------	--

The documentation for this class was generated from the following files:

- include/epiworld/config.hpp
- include/epiworld/person-bones.hpp

3.8 PersonTools< TSeq > Class Template Reference

List of tools available for the individual to.

```
#include <persontools-bones.hpp>
```


Public Member Functions

- void **add_tool** (int date, [Tool](#)< TSeq > tool)
- `epiworld_double` **get_susceptibility_reduction** (VirusPtr< TSeq > v)
- `epiworld_double` **get_transmission_reduction** (VirusPtr< TSeq > v)
- `epiworld_double` **get_recovery_enhancer** (VirusPtr< TSeq > v)
- `epiworld_double` **get_death_reduction** (VirusPtr< TSeq > v)
- void **set_susceptibility_reduction_mixer** (MixerFun< TSeq > fun)
- void **set_transmission_reduction_mixer** (MixerFun< TSeq > fun)
- void **set_recovery_enhancer_mixer** (MixerFun< TSeq > fun)
- void **set_death_reduction_mixer** (MixerFun< TSeq > fun)
- `size_t` **size** () const
- [Tool](#)< TSeq > & **operator()** (int i)
- [Person](#)< TSeq > * **get_person** ()
- [Model](#)< TSeq > * **get_model** ()
- void **reset** ()
- bool **has_tool** (unsigned int t) const
- bool **has_tool** (std::string name) const

Friends

- class [Person](#)< TSeq >
- class [Model](#)< TSeq >

3.8.1 Detailed Description

```
template<typename TSeq = int>
class PersonTools< TSeq >
```

List of tools available for the individual to.

Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following files:

- include/epiworld/config.hpp
- include/epiworld/persontools-bones.hpp
- include/epiworld/persontools-meat.hpp

3.9 PersonViruses< TSeq > Class Template Reference

Set of viruses in host.

```
#include <personviruses-bones.hpp>
```

Public Member Functions

- void **add_virus** (epiworld_fast_uint new_status, [Virus](#)< TSeq > v)
- size_t **size** () const
- int **size_active** () const
- [Virus](#)< TSeq > & **operator()** (int i)
- void **mutate** ()
- void **reset** ()
- void **deactivate** ([Virus](#)< TSeq > &v)
- [Person](#)< TSeq > * **get_host** ()
- bool **has_virus** (unsigned int v) const
- bool **has_virus** (std::string vname) const

Friends

- class [Person](#)< TSeq >
- class [Model](#)< TSeq >

3.9.1 Detailed Description

```
template<typename TSeq = int>
class PersonViruses< TSeq >
```

Set of viruses in host.

Template Parameters

<i>TSeq</i>	Type of sequence
-------------	------------------

The documentation for this class was generated from the following files:

- include/epiworld/personviruses-bones.hpp
- include/epiworld/personviruses-meat.hpp

3.10 Progress Class Reference

A simple progress bar.

```
#include <progress.hpp>
```

Public Member Functions

- **Progress** (int n_, int width_)
- void **start** ()
- void **next** ()
- void **end** ()

3.10.1 Detailed Description

A simple progress bar.

The documentation for this class was generated from the following file:

- include/epiworld/progress.hpp

3.11 Queue< TSeq > Class Template Reference

Controls which agents are verified at each step.

```
#include <queue-bones.hpp>
```

Public Member Functions

- void **operator+=** ([Person](#)< TSeq > *p)
- void **operator-=** ([Person](#)< TSeq > *p)
- epiworld_fast_int **operator[]** (unsigned int i) const
- void **set_model** ([Model](#)< TSeq > *m)

3.11.1 Detailed Description

```
template<typename TSeq = int>
class Queue< TSeq >
```

Controls which agents are verified at each step.

The idea is that only agents who are either in an infected state or have an infected neighbor should be checked. Otherwise it makes no sense (no chance to recover or capture the disease).

Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following files:

- include/epiworld/model-bones.hpp
- include/epiworld/queue-bones.hpp

3.12 RandGraph Class Reference

Public Member Functions

- **RandGraph** (int N_)

- void **init** (int s)
- void **set_rand_engine** (std::mt19937 &e)
- epiworld_double **runif** ()

The documentation for this class was generated from the following file:

- include/epiworld/random_graph.hpp

3.13 Tool< TSeq > Class Template Reference

Tools for defending the host against the virus.

```
#include <tools-bones.hpp>
```

Public Member Functions

- **Tool** (std::string name="unknown tool")
- void **set_sequence** (TSeq d)
- void **set_sequence_unique** (TSeq d)
- void **set_sequence** (std::shared_ptr< TSeq > d)
- std::shared_ptr< TSeq > **get_sequence** ()
- TSeq & **get_sequence_unique** ()
- void **set_name** (std::string name)
- std::string **get_name** () const
- [Person](#)< TSeq > * **get_person** ()
- void **set_person** ([Person](#)< TSeq > *p)
- int **get_id** () const
- void **set_id** (int id)
- void **set_date** (int d)
- void **set_status** (epiworld_fast_int init, epiworld_fast_int post)
- void **set_queue** (epiworld_fast_int init, epiworld_fast_int post)
- void **get_status** (epiworld_fast_int *init, epiworld_fast_int *post)
- void **get_queue** (epiworld_fast_int *init, epiworld_fast_int *post)

Get and set the tool functions

Parameters

v	<i>The virus over which to operate</i>
fun	<i>the function to be used</i>

Returns

epiworld_double

- epiworld_double **get_susceptibility_reduction** (VirusPtr< TSeq > v)
- epiworld_double **get_transmission_reduction** (VirusPtr< TSeq > v)
- epiworld_double **get_recovery_enhancer** (VirusPtr< TSeq > v)
- epiworld_double **get_death_reduction** (VirusPtr< TSeq > v)
- void **set_susceptibility_reduction_fun** (ToolFun< TSeq > fun)

- void **set_transmission_reduction_fun** (ToolFun< TSeq > fun)
- void **set_recovery_enhancer_fun** (ToolFun< TSeq > fun)
- void **set_death_reduction_fun** (ToolFun< TSeq > fun)
- void **set_susceptibility_reduction** (epiworld_double *prob)
- void **set_transmission_reduction** (epiworld_double *prob)
- void **set_recovery_enhancer** (epiworld_double *prob)
- void **set_death_reduction** (epiworld_double *prob)
- void **set_susceptibility_reduction** (epiworld_double prob)
- void **set_transmission_reduction** (epiworld_double prob)
- void **set_recovery_enhancer** (epiworld_double prob)
- void **set_death_reduction** (epiworld_double prob)

Friends

- class **PersonTools**< TSeq >
- class **Person**< TSeq >
- class **Model**< TSeq >
- void **default_add_virus** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)
- void **default_add_tool** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)
- void **default_rm_virus** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)
- void **default_rm_tool** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)

3.13.1 Detailed Description

```
template<typename TSeq = int>
class Tool< TSeq >
```

Tools for defending the host against the virus.

Template Parameters

<i>TSeq</i>	Type of sequence
-------------	------------------

The documentation for this class was generated from the following files:

- include/epiworld/config.hpp
- include/epiworld/tools-bones.hpp
- include/epiworld/tools-meat.hpp

3.14 UserData< TSeq > Class Template Reference

Personalized data by the user.

```
#include <userdata-bones.hpp>
```

Public Member Functions

- [UserData](#) (std::vector< std::string > names)
Construct a new User Data object.
- std::vector< std::string > & **get_names** ()
- std::vector< int > & **get_dates** ()
- std::vector< epiworld_double > & **get_data** ()
- void **get_all** (std::vector< std::string > *names=nullptr, std::vector< int > *date=nullptr, std::vector< epiworld_double > *data=nullptr)
- unsigned int **nrow** () const
- unsigned int **ncol** () const
- void **write** (std::string fn)
- void **print** () const

Append data

Parameters

x	A vector of length <code>ncol()</code> (if vector), otherwise a <code>epiworld_double</code> .
j	Index of the data point, from 0 to <code>ncol() - 1</code> .

- void **add** (std::vector< epiworld_double > x)
- void **add** (unsigned int j, epiworld_double x)

Access data

Parameters

i	Row (0 through <code>ndays - 1</code> .)
j	Column (0 through <code>ncols()</code>).

Returns

`epiworld_double&`

- `epiworld_double & operator()` (unsigned int i, unsigned int j)
- `epiworld_double & operator()` (unsigned int i, std::string name)

Friends

- class **Model**< TSeq >
- class **DataBase**< TSeq >

3.14.1 Detailed Description

```
template<typename TSeq>
class UserData< TSeq >
```

Personalized data by the user.

Template Parameters

<i>TSeq</i>	
-------------	--

3.14.2 Constructor & Destructor Documentation

3.14.2.1 UserData()

```
template<typename TSeq >
UserData< TSeq >::UserData (
    std::vector< std::string > names ) [inline]
```

Construct a new User Data object.

Parameters

<i>names</i>	A vector of names. The length of the vector sets the number of columns to record.
--------------	---

The documentation for this class was generated from the following files:

- include/epiworld/database-bones.hpp
- include/epiworld/userdata-bones.hpp
- include/epiworld/userdata-meat.hpp

3.15 vecHasher< T > Struct Template Reference

Vector hasher.

```
#include <misc.hpp>
```

Public Member Functions

- `std::size_t operator() (std::vector< T > const &dat) const` noexcept

3.15.1 Detailed Description

```
template<typename T>
struct vecHasher< T >
```

Vector hasher.

Template Parameters

<i>T</i>	
----------	--

The documentation for this struct was generated from the following file:

- include/epiworld/misc.hpp

3.16 Virus< TSeq > Class Template Reference

[Virus.](#)

```
#include <virus-bones.hpp>
```

Public Member Functions

- **Virus** (std::string name="unknown virus")
- void **mutate** ()
- void **set_mutation** (MutFun< TSeq > fun)
- const TSeq * **get_sequence** ()
- void **set_sequence** (TSeq sequence)
- [Person](#)< TSeq > * **get_host** ()
- void **set_host** ([Person](#)< TSeq > *p)
- [Model](#)< TSeq > * **get_model** ()
- void **set_date** (int d)
- int **get_date** () const
- void **set_id** (int idx)
- int **get_id** () const
- void **set_name** (std::string name)
- std::string **get_name** () const
- std::vector< epiworld_double > & **get_data** ()

Get and set the tool functions

Parameters

v	<i>The virus over which to operate</i>
fun	<i>the function to be used</i>

Returns

epiworld_double

- epiworld_double **get_prob_infecting** ()
- epiworld_double **get_prob_recovery** ()
- epiworld_double **get_prob_death** ()
- void **post_recovery** ()
- void **set_post_recovery** (PostRecoveryFun< TSeq > fun)
- void **set_post_immunity** (epiworld_double prob)
- void **set_post_immunity** (epiworld_double *prob)

- void **set_prob_infecting_fun** (VirusFun< TSeq > fun)
- void **set_prob_recovery_fun** (VirusFun< TSeq > fun)
- void **set_prob_death_fun** (VirusFun< TSeq > fun)
- void **set_prob_infecting** (epiworld_double *prob)
- void **set_prob_recovery** (epiworld_double *prob)
- void **set_prob_death** (epiworld_double *prob)
- void **set_prob_infecting** (epiworld_double prob)
- void **set_prob_recovery** (epiworld_double prob)
- void **set_prob_death** (epiworld_double prob)

Get and set the status and queue

After applied, viruses can change the status and affect the queue of agents. These function sets the default values, which are retrieved when adding or removing a virus does not specify a change in status or in queue.

Parameters

init	After the virus/tool is added to the host.
end	After the virus/tool is removed.
removed	After the host (Person) is removed.

- void **set_status** (epiworld_fast_int init, epiworld_fast_int end, epiworld_fast_int removed)
- void **set_queue** (epiworld_fast_int init, epiworld_fast_int end, epiworld_fast_int removed)
- void **get_status** (epiworld_fast_int *init, epiworld_fast_int *end, epiworld_fast_int *removed)
- void **get_queue** (epiworld_fast_int *init, epiworld_fast_int *end, epiworld_fast_int *removed)

Friends

- class **Person**< TSeq >
- class **Model**< TSeq >
- class **PersonViruses**< TSeq >
- class **DataBase**< TSeq >
- void **default_add_virus** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)
- void **default_add_tool** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)
- void **default_rm_virus** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)
- void **default_rm_tool** ([Action](#)< TSeq > &a, [Model](#)< TSeq > *m)

3.16.1 Detailed Description

```
template<typename TSeq = int>
class Virus< TSeq >
```

[Virus](#).

Template Parameters

<i>TSeq</i>	
-------------	--

Raw transmissibility of a virus should be a function of its genetic sequence. Nonetheless, transmissibility can be reduced as a result of having one or more tools to fight the virus. Because of this, transmissibility should be a function of the host.

The documentation for this class was generated from the following files:

- include/epiworld/config.hpp
- include/epiworld/virus-bones.hpp
- include/epiworld/virus-meat.hpp

Index

Action

Action< TSeq >, [6](#)

Action< TSeq >, [5](#)

Action, [6](#)

add_global_action

Model< TSeq >, [17](#)

AdjList, [7](#)

AdjList, [7](#)

DataBase< TSeq >, [8](#)

record_variant, [9](#)

LFMCMC< TData >, [9](#)

Location< TSeq >, [11](#)

Model< TSeq >, [11](#)

add_global_action, [17](#)

reset, [17](#)

run_multiple, [18](#)

write_data, [18](#)

Person< TSeq >, [19](#)

PersonTools< TSeq >, [20](#)

PersonViruses< TSeq >, [21](#)

Progress, [22](#)

Queue< TSeq >, [23](#)

RandGraph, [23](#)

record_variant

DataBase< TSeq >, [9](#)

reset

Model< TSeq >, [17](#)

run_multiple

Model< TSeq >, [18](#)

Tool< TSeq >, [24](#)

UserData

UserData< TSeq >, [27](#)

UserData< TSeq >, [25](#)

UserData, [27](#)

vecHasher< T >, [27](#)

Virus< TSeq >, [28](#)

write_data

Model< TSeq >, [18](#)