

epiworld

0.8.2

Generated by Doxygen 1.9.1

1 Example: 00-hello-world	1
2 Benchmarking	3
3 Contributor Code of Conduct	5
4 ModelMeaslesMixing	7
4.1 Overview	7
4.2 Disease States	7
4.3 Key Features	8
4.3.1 Disease Progression	8
4.3.2 Population Mixing	8
4.3.3 Public Health Measures	8
4.4 Parameters	8
4.4.1 Disease Parameters	8
4.4.2 Detection and Isolation	9
4.4.3 Contact Tracing and Quarantine	9
4.4.4 Vaccination	9
4.5 Usage Example	9
4.6 Differences from Other Models	10
4.6.1 vs. ModelMeaslesSchool	10
4.6.2 vs. ModelSEIRMixingQuarantine	10
4.7 Testing	10
5 ModelMeaslesMixingRiskQuarantine	11
5.1 Overview	11
5.1.1 Key Features	11
5.2 Disease States	11
5.3 Risk Classification System	12
5.3.1 High Risk	12
5.3.2 Medium Risk	12
5.3.3 Low Risk	12
5.4 Enhanced Detection	13
5.5 Parameters	13
5.5.1 Disease Parameters	13
5.5.2 Detection and Isolation	13
5.5.3 Risk-based Quarantine	13
5.5.4 Contact Tracing	14
5.5.5 Vaccination	14
5.6 Usage Example	14
5.7 Differences from Other Models	14
5.7.1 vs. ModelMeaslesMixing	14
5.7.2 vs. ModelMeaslesSchool	15
5.8 Testing	15

5.9 Applications	15
5.10 Implementation Notes	15
6 epiworld c++ template library	17
6.1 Main features	17
6.2 Algorithm	17
6.3 Hello world (C++)	18
6.4 Surveillance simulation	18
6.4.1 Preliminary results	19
6.4.2 Cases detected	20
7 General parameters	21
7.1 Compartmental Models	21
7.1.1 SIR Model	21
7.1.2 SEIR Model	22
7.2 Agent-Based Model Approach	22
7.2.1 Mathematical preliminaries	23
7.2.2 Simulation study	23
7.3 Comparing ABM with Compartmental Models	23
7.3.1 SIR	23
7.3.2 SEIR	24
7.3.3 Rates	24
8 MIT License	25
9 model1	27
10 Mixing probabilities in connected model	29
10.1 Case 1: No grouping	29
10.2 Case 2: Grouping	30
11 EPI Simulator	31
11.1 Disease dynamics	31
11.2 Network dynamics	31
11.3 Contagion dynamics	31
11.4 Time dynamics	31
11.5 Updating agent's status	32
11.5.1 Other parameters	32
12 Namespace Index	33
12.1 Namespace List	33
13 Hierarchical Index	35
13.1 Class Hierarchy	35
14 Class Index	39

14.1 Class List	39
15 File Index	43
15.1 File List	43
16 Namespace Documentation	45
16.1 epiworld::sampler Namespace Reference	45
16.1.1 Detailed Description	45
16.1.2 Function Documentation	45
16.1.2.1 make_sample_virus_neighbors()	45
16.1.2.2 make_update_susceptible()	46
16.1.2.3 sample_virus_single()	46
16.2 sampler Namespace Reference	48
16.2.1 Detailed Description	48
16.2.2 Function Documentation	48
16.2.2.1 make_sample_virus_neighbors()	48
16.2.2.2 make_update_susceptible()	49
16.2.2.3 sample_virus_single()	49
17 Class Documentation	53
17.1 AdjList Class Reference	53
17.1.1 Constructor & Destructor Documentation	53
17.1.1.1 AdjList()	53
17.1.2 Member Function Documentation	54
17.1.2.1 read_edgelist()	54
17.2 epiworld::AdjList Class Reference	54
17.2.1 Constructor & Destructor Documentation	55
17.2.1.1 AdjList()	55
17.2.2 Member Function Documentation	55
17.2.2.1 read_edgelist()	55
17.3 Agent< TSeq > Class Template Reference	56
17.3.1 Detailed Description	58
17.3.2 Member Function Documentation	58
17.3.2.1 operator>()	58
17.3.2.2 swap_neighbors()	60
17.3.3 Friends And Related Function Documentation	60
17.3.3.1 default_rm_entity	60
17.4 epiworld::Agent< TSeq > Class Template Reference	61
17.4.1 Detailed Description	63
17.4.2 Member Function Documentation	63
17.4.2.1 operator>()	63
17.4.2.2 swap_neighbors()	64
17.4.3 Friends And Related Function Documentation	64

17.4.3.1 default_rm_entity	64
17.5 AgentsSample< TSeq > Class Template Reference	64
17.5.1 Detailed Description	65
17.5.2 Constructor & Destructor Documentation	65
17.5.2.1 AgentsSample()	65
17.6 epiworld::AgentsSample< TSeq > Class Template Reference	66
17.6.1 Detailed Description	66
17.6.2 Constructor & Destructor Documentation	67
17.6.2.1 AgentsSample()	67
17.7 ContactTracing Class Reference	67
17.7.1 Detailed Description	68
17.7.2 Constructor & Destructor Documentation	68
17.7.2.1 ContactTracing()	68
17.7.3 Member Function Documentation	68
17.7.3.1 add_contact()	69
17.7.3.2 get_contact()	69
17.7.3.3 get_n_contacts()	69
17.7.3.4 print()	70
17.7.3.5 reset()	70
17.8 epiworld::ContactTracing Class Reference	70
17.8.1 Detailed Description	71
17.8.2 Constructor & Destructor Documentation	71
17.8.2.1 ContactTracing()	71
17.8.3 Member Function Documentation	71
17.8.3.1 add_contact()	72
17.8.3.2 get_contact()	72
17.8.3.3 get_n_contacts()	72
17.8.3.4 print()	73
17.8.3.5 reset()	73
17.9 DataBase< TSeq > Class Template Reference	73
17.9.1 Detailed Description	75
17.9.2 Member Function Documentation	76
17.9.2.1 get_generation_time()	76
17.9.2.2 get_reproductive_number()	76
17.9.2.3 get_transition_probability()	77
17.9.2.4 get_transmissions()	77
17.9.2.5 operator==() [1/3]	77
17.9.2.6 operator==() [2/3]	78
17.9.2.7 operator==() [3/3]	78
17.9.2.8 record_virus()	78
17.10 epiworld::DataBase< TSeq > Class Template Reference	79
17.10.1 Detailed Description	81

17.10.2 Member Function Documentation	81
17.10.2.1 get_generation_time()	81
17.10.2.2 get_reproductive_number()	81
17.10.2.3 get_transition_probability()	82
17.10.2.4 get_transmissions()	82
17.10.2.5 operator==()	83
17.10.2.6 record_virus()	83
17.11 Entities< TSeq > Class Template Reference	83
17.11.1 Detailed Description	84
17.12 epiworld::Entities< TSeq > Class Template Reference	84
17.12.1 Detailed Description	85
17.13 Entities_const< TSeq > Class Template Reference	85
17.13.1 Detailed Description	85
17.14 epiworld::Entities_const< TSeq > Class Template Reference	86
17.14.1 Detailed Description	86
17.15 Entity< TSeq > Class Template Reference	87
17.15.1 Constructor & Destructor Documentation	87
17.15.1.1 Entity()	87
17.15.2 Friends And Related Function Documentation	88
17.15.2.1 default_rm_entity	88
17.16 epiworld::Entity< TSeq > Class Template Reference	88
17.16.1 Constructor & Destructor Documentation	89
17.16.1.1 Entity()	89
17.16.2 Friends And Related Function Documentation	89
17.16.2.1 default_rm_entity	90
17.17 epiworld::Event< TSeq > Struct Template Reference	90
17.17.1 Detailed Description	90
17.17.2 Constructor & Destructor Documentation	91
17.17.2.1 Event()	91
17.18 Event< TSeq > Struct Template Reference	91
17.18.1 Detailed Description	92
17.18.2 Constructor & Destructor Documentation	93
17.18.2.1 Event()	93
17.19 epiworld::GlobalEvent< TSeq > Class Template Reference	93
17.19.1 Detailed Description	94
17.19.2 Constructor & Destructor Documentation	94
17.19.2.1 GlobalEvent()	94
17.20 GlobalEvent< TSeq > Class Template Reference	95
17.20.1 Detailed Description	95
17.20.2 Constructor & Destructor Documentation	95
17.20.2.1 GlobalEvent()	95
17.21 epiworld::LFMCMC< TData > Class Template Reference	96

17.21.1 Detailed Description	97
17.22 LFMCMC< TData > Class Template Reference	97
17.22.1 Detailed Description	98
17.23 epiworld::Model< TSeq > Class Template Reference	99
17.23.1 Detailed Description	107
17.23.2 Member Function Documentation	107
17.23.2.1 add_globalevent()	107
17.23.2.2 clone_ptr()	108
17.23.2.3 draw()	108
17.23.2.4 events_add()	108
17.23.2.5 events_run()	109
17.23.2.6 load_agents_entities_ties()	109
17.23.2.7 reset()	110
17.23.2.8 run_multiple()	110
17.23.2.9 set_agents_data()	110
17.23.2.10 set_name()	111
17.23.2.11 write_data()	111
17.23.3 Member Data Documentation	112
17.23.3.1 initial_states_fun	112
17.23.3.2 rbinomd	112
17.23.3.3 rexp	112
17.23.3.4 rgammad	113
17.23.3.5 rgeomd	113
17.23.3.6 rlognormald	113
17.23.3.7 rnbino	113
17.23.3.8 rnormd	113
17.23.3.9 rpoissd	114
17.23.3.10 runifd	114
17.23.3.11 time_elapsed	114
17.24 Model< TSeq > Class Template Reference	114
17.24.1 Detailed Description	122
17.24.2 Member Function Documentation	123
17.24.2.1 add_globalevent()	123
17.24.2.2 clone_ptr()	123
17.24.2.3 draw()	123
17.24.2.4 events_add()	124
17.24.2.5 events_run()	124
17.24.2.6 load_agents_entities_ties()	126
17.24.2.7 reset()	126
17.24.2.8 run_multiple()	127
17.24.2.9 set_agents_data()	127
17.24.2.10 set_name()	127

17.24.2.11 write_data()	128
17.24.3 Member Data Documentation	128
17.24.3.1 initial_states_fun	128
17.24.3.2 rbinomd	128
17.24.3.3 rexp	129
17.24.3.4 rgammad	129
17.24.3.5 rgeomd	129
17.24.3.6 rlognormald	129
17.24.3.7 rnbino	129
17.24.3.8 rnormd	130
17.24.3.9 rpoissd	130
17.24.3.10 runifd	130
17.24.3.11 time_elapsed	130
17.25 epiworld::ModelDiagram Class Reference	131
17.26 ModelDiagram Class Reference	131
17.27 epiworld::epimodels::ModelDiffNet< TSeq > Class Template Reference	131
17.27.1 Detailed Description	132
17.28 ModelDiffNet< TSeq > Class Template Reference	133
17.28.1 Detailed Description	134
17.29 epiworld::epimodels::ModelMeaslesMixing< TSeq > Class Template Reference	134
17.29.1 Detailed Description	136
17.29.2 Constructor & Destructor Documentation	137
17.29.2.1 ModelMeaslesMixing() [1/2]	137
17.29.2.2 ModelMeaslesMixing() [2/2]	139
17.29.3 Member Function Documentation	140
17.29.3.1 clone_ptr()	140
17.29.3.2 get_agent_quarantine_triggered()	140
17.29.3.3 get_contact_matrix()	141
17.29.3.4 get_isolation_willingness()	141
17.29.3.5 get_quarantine_willingness()	141
17.29.3.6 initial_states()	141
17.29.3.7 run()	142
17.29.3.8 set_contact_matrix()	142
17.30 ModelMeaslesMixing< TSeq > Class Template Reference	143
17.30.1 Detailed Description	145
17.30.2 Constructor & Destructor Documentation	146
17.30.2.1 ModelMeaslesMixing() [1/2]	146
17.30.2.2 ModelMeaslesMixing() [2/2]	147
17.30.3 Member Function Documentation	148
17.30.3.1 clone_ptr()	148
17.30.3.2 get_agent_quarantine_triggered()	149
17.30.3.3 get_contact_matrix()	149

17.30.3.4	get_isolation_willingness()	149
17.30.3.5	get_quarantine_willingness()	150
17.30.3.6	initial_states()	150
17.30.3.7	run()	150
17.30.3.8	set_contact_matrix()	151
17.31	epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq > Class Template Reference	151
17.31.1	Detailed Description	153
17.31.2	Constructor & Destructor Documentation	154
17.31.2.1	ModelMeaslesMixingRiskQuarantine() [1/2]	154
17.31.2.2	ModelMeaslesMixingRiskQuarantine() [2/2]	155
17.31.3	Member Function Documentation	156
17.31.3.1	clone_ptr()	156
17.31.3.2	get_contact_matrix()	156
17.31.3.3	get_days_quarantine_triggered()	157
17.31.3.4	get_isolation_willingness()	157
17.31.3.5	get_quarantine_risk_level()	157
17.31.3.6	get_quarantine_willingness()	157
17.31.3.7	initial_states()	158
17.31.3.8	run()	158
17.31.3.9	set_contact_matrix()	158
17.32	ModelMeaslesMixingRiskQuarantine< TSeq > Class Template Reference	159
17.32.1	Detailed Description	161
17.32.2	Constructor & Destructor Documentation	161
17.32.2.1	ModelMeaslesMixingRiskQuarantine() [1/2]	161
17.32.2.2	ModelMeaslesMixingRiskQuarantine() [2/2]	163
17.32.3	Member Function Documentation	164
17.32.3.1	clone_ptr()	164
17.32.3.2	get_contact_matrix()	164
17.32.3.3	get_days_quarantine_triggered()	164
17.32.3.4	get_isolation_willingness()	165
17.32.3.5	get_quarantine_risk_level()	165
17.32.3.6	get_quarantine_willingness()	165
17.32.3.7	initial_states()	165
17.32.3.8	run()	166
17.32.3.9	set_contact_matrix()	166
17.33	epiworld::epimodels::ModelMeaslesSchool< TSeq > Class Template Reference	167
17.33.1	Detailed Description	168
17.33.2	Constructor & Destructor Documentation	169
17.33.2.1	ModelMeaslesSchool()	169
17.33.3	Member Function Documentation	170
17.33.3.1	clone_ptr()	170
17.33.3.2	quarantine_agents()	170

17.33.3.3 reset()	171
17.34 ModelMeaslesSchool< TSeq > Class Template Reference	171
17.34.1 Detailed Description	173
17.34.2 Constructor & Destructor Documentation	173
17.34.2.1 ModelMeaslesSchool()	173
17.34.3 Member Function Documentation	174
17.34.3.1 clone_ptr()	174
17.34.3.2 quarantine_agents()	175
17.34.3.3 reset()	175
17.35 epiworld::epimodels::ModelSEIR< TSeq > Class Template Reference	176
17.35.1 Detailed Description	177
17.35.2 Member Function Documentation	177
17.35.2.1 initial_states()	177
17.35.3 Member Data Documentation	178
17.35.3.1 update_exposed_seir	178
17.35.3.2 update_infected_seir	178
17.36 ModelSEIR< TSeq > Class Template Reference	179
17.36.1 Detailed Description	180
17.36.2 Member Function Documentation	180
17.36.2.1 initial_states()	180
17.36.3 Member Data Documentation	181
17.36.3.1 update_exposed_seir	181
17.36.3.2 update_infected_seir	181
17.37 epiworld::epimodels::ModelSEIRCONN< TSeq > Class Template Reference	181
17.37.1 Constructor & Destructor Documentation	182
17.37.1.1 ModelSEIRCONN()	183
17.37.2 Member Function Documentation	183
17.37.2.1 clone_ptr()	183
17.37.2.2 initial_states()	183
17.37.2.3 reset()	184
17.38 ModelSEIRCONN< TSeq > Class Template Reference	184
17.38.1 Constructor & Destructor Documentation	185
17.38.1.1 ModelSEIRCONN()	186
17.38.2 Member Function Documentation	186
17.38.2.1 clone_ptr()	186
17.38.2.2 initial_states()	186
17.38.2.3 reset()	187
17.39 epiworld::epimodels::ModelSEIRD< TSeq > Class Template Reference	187
17.39.1 Detailed Description	189
17.39.2 Constructor & Destructor Documentation	189
17.39.2.1 ModelSEIRD() [1/2]	189
17.39.2.2 ModelSEIRD() [2/2]	190

17.39.3 Member Data Documentation	190
17.39.3.1 update_exposed_seir	190
17.40 ModelSEIRD< TSeq > Class Template Reference	191
17.40.1 Detailed Description	192
17.40.2 Constructor & Destructor Documentation	192
17.40.2.1 ModelSEIRD() [1/2]	192
17.40.2.2 ModelSEIRD() [2/2]	193
17.40.3 Member Data Documentation	193
17.40.3.1 update_exposed_seir	193
17.41 epiworld::epimodels::ModelSEIRDCONN< TSeq > Class Template Reference	194
17.41.1 Constructor & Destructor Documentation	195
17.41.1.1 ModelSEIRDCONN()	195
17.41.2 Member Function Documentation	196
17.41.2.1 clone_ptr()	196
17.41.2.2 initial_states()	196
17.41.2.3 reset()	196
17.42 ModelSEIRDCONN< TSeq > Class Template Reference	197
17.42.1 Constructor & Destructor Documentation	198
17.42.1.1 ModelSEIRDCONN()	198
17.42.2 Member Function Documentation	199
17.42.2.1 clone_ptr()	199
17.42.2.2 initial_states()	199
17.42.2.3 reset()	200
17.43 epiworld::epimodels::ModelSEIRMixing< TSeq > Class Template Reference	200
17.43.1 Constructor & Destructor Documentation	201
17.43.1.1 ModelSEIRMixing() [1/2]	202
17.43.1.2 ModelSEIRMixing() [2/2]	202
17.43.2 Member Function Documentation	203
17.43.2.1 clone_ptr()	203
17.43.2.2 initial_states()	203
17.43.2.3 reset()	204
17.44 ModelSEIRMixing< TSeq > Class Template Reference	204
17.44.1 Constructor & Destructor Documentation	205
17.44.1.1 ModelSEIRMixing() [1/2]	205
17.44.1.2 ModelSEIRMixing() [2/2]	206
17.44.2 Member Function Documentation	206
17.44.2.1 clone_ptr()	207
17.44.2.2 initial_states()	207
17.44.2.3 reset()	207
17.45 epiworld::epimodels::ModelSEIRMixingQuarantine< TSeq > Class Template Reference	208
17.45.1 Constructor & Destructor Documentation	209
17.45.1.1 ModelSEIRMixingQuarantine() [1/2]	210

17.45.1.2 ModelSEIRMixingQuarantine() [2/2]	210
17.45.2 Member Function Documentation	211
17.45.2.1 clone_ptr()	211
17.45.2.2 initial_states()	211
17.45.2.3 reset()	212
17.46 ModelSEIRMixingQuarantine< TSeq > Class Template Reference	213
17.46.1 Constructor & Destructor Documentation	214
17.46.1.1 ModelSEIRMixingQuarantine() [1/2]	214
17.46.1.2 ModelSEIRMixingQuarantine() [2/2]	215
17.46.2 Member Function Documentation	217
17.46.2.1 clone_ptr()	217
17.46.2.2 initial_states()	217
17.46.2.3 reset()	218
17.47 epiworld::epimodels::ModelSIR< TSeq > Class Template Reference	218
17.47.1 Detailed Description	219
17.47.2 Member Function Documentation	219
17.47.2.1 initial_states()	220
17.48 ModelSIR< TSeq > Class Template Reference	220
17.48.1 Detailed Description	221
17.48.2 Member Function Documentation	221
17.48.2.1 initial_states()	222
17.49 epiworld::epimodels::ModelSIRCONN< TSeq > Class Template Reference	222
17.49.1 Constructor & Destructor Documentation	223
17.49.1.1 ModelSIRCONN()	224
17.49.2 Member Function Documentation	224
17.49.2.1 clone_ptr()	224
17.49.2.2 get_n_infected()	224
17.49.2.3 initial_states()	225
17.49.2.4 reset()	225
17.50 ModelSIRCONN< TSeq > Class Template Reference	226
17.50.1 Constructor & Destructor Documentation	227
17.50.1.1 ModelSIRCONN()	227
17.50.2 Member Function Documentation	227
17.50.2.1 clone_ptr()	227
17.50.2.2 get_n_infected()	228
17.50.2.3 initial_states()	228
17.50.2.4 reset()	228
17.51 epiworld::epimodels::ModelSIRD< TSeq > Class Template Reference	229
17.51.1 Detailed Description	230
17.51.2 Constructor & Destructor Documentation	230
17.51.2.1 ModelSIRD()	230
17.51.3 Member Function Documentation	231

17.51.3.1 initial_states()	231
17.52 ModelSIRD< TSeq > Class Template Reference	231
17.52.1 Detailed Description	232
17.52.2 Constructor & Destructor Documentation	232
17.52.2.1 ModelSIRD()	232
17.52.3 Member Function Documentation	233
17.52.3.1 initial_states()	233
17.53 epiworld::epimodels::ModelSIRDCONN< TSeq > Class Template Reference	234
17.53.1 Constructor & Destructor Documentation	235
17.53.1.1 ModelSIRDCONN()	235
17.53.2 Member Function Documentation	235
17.53.2.1 clone_ptr()	235
17.53.2.2 reset()	236
17.54 ModelSIRDCONN< TSeq > Class Template Reference	236
17.54.1 Constructor & Destructor Documentation	237
17.54.1.1 ModelSIRDCONN()	238
17.54.2 Member Function Documentation	238
17.54.2.1 clone_ptr()	238
17.54.2.2 reset()	238
17.55 epiworld::epimodels::ModelSIRLogit< TSeq > Class Template Reference	239
17.55.1 Detailed Description	240
17.55.2 Constructor & Destructor Documentation	241
17.55.2.1 ModelSIRLogit()	241
17.55.3 Member Function Documentation	242
17.55.3.1 clone_ptr()	242
17.55.3.2 reset()	242
17.56 ModelSIRLogit< TSeq > Class Template Reference	243
17.56.1 Detailed Description	244
17.56.2 Constructor & Destructor Documentation	244
17.56.2.1 ModelSIRLogit()	244
17.56.3 Member Function Documentation	245
17.56.3.1 clone_ptr()	245
17.56.3.2 reset()	245
17.57 epiworld::epimodels::ModelSIRMixing< TSeq > Class Template Reference	246
17.57.1 Constructor & Destructor Documentation	247
17.57.1.1 ModelSIRMixing() [1/2]	247
17.57.1.2 ModelSIRMixing() [2/2]	248
17.57.2 Member Function Documentation	248
17.57.2.1 clone_ptr()	249
17.57.2.2 initial_states()	249
17.57.2.3 reset()	249
17.58 ModelSIRMixing< TSeq > Class Template Reference	250

17.58.1 Constructor & Destructor Documentation	251
17.58.1.1 ModelSIRMixing() [1/2]	251
17.58.1.2 ModelSIRMixing() [2/2]	252
17.58.2 Member Function Documentation	252
17.58.2.1 clone_ptr()	252
17.58.2.2 initial_states()	252
17.58.2.3 reset()	253
17.59 epiworld::epimodels::ModelSIS< TSeq > Class Template Reference	253
17.59.1 Detailed Description	255
17.60 ModelSIS< TSeq > Class Template Reference	256
17.60.1 Detailed Description	257
17.61 epiworld::epimodels::ModelSISD< TSeq > Class Template Reference	257
17.61.1 Detailed Description	258
17.62 ModelSISD< TSeq > Class Template Reference	259
17.62.1 Detailed Description	260
17.63 epiworld::epimodels::ModelSURV< TSeq > Class Template Reference	260
17.63.1 Member Function Documentation	262
17.63.1.1 reset()	262
17.64 ModelSURV< TSeq > Class Template Reference	263
17.64.1 Member Function Documentation	264
17.64.1.1 reset()	265
17.65 Network< Nettype, Nodetype, Edgetype > Class Template Reference	265
17.66 epiworld::PersonTools< TSeq > Class Template Reference	265
17.67 PersonTools< TSeq > Class Template Reference	266
17.68 epiworld::Progress Class Reference	266
17.68.1 Detailed Description	266
17.69 Progress Class Reference	266
17.69.1 Detailed Description	266
17.70 epiworld::Queue< TSeq > Class Template Reference	267
17.70.1 Detailed Description	267
17.71 Queue< TSeq > Class Template Reference	267
17.71.1 Detailed Description	268
17.72 RandGraph Class Reference	268
17.73 epiworld::SAMPLETYPE Class Reference	269
17.74 SAMPLETYPE Class Reference	269
17.75 TestResults Struct Reference	269
17.76 epiworld::Tool< TSeq > Class Template Reference	269
17.76.1 Detailed Description	271
17.77 Tool< TSeq > Class Template Reference	271
17.77.1 Detailed Description	272
17.78 epiworld::ToolFunctions< TSeq > Class Template Reference	272
17.78.1 Detailed Description	273

17.79 ToolFunctions< TSeq > Class Template Reference	273
17.79.1 Detailed Description	273
17.80 epiworld::Tools< TSeq > Class Template Reference	274
17.80.1 Detailed Description	274
17.81 Tools< TSeq > Class Template Reference	274
17.81.1 Detailed Description	275
17.82 epiworld::Tools_const< TSeq > Class Template Reference	275
17.82.1 Detailed Description	276
17.83 Tools_const< TSeq > Class Template Reference	276
17.83.1 Detailed Description	276
17.84 epiworld::UserData< TSeq > Class Template Reference	277
17.84.1 Detailed Description	278
17.84.2 Constructor & Destructor Documentation	278
17.84.2.1 UserData()	278
17.85 UserData< TSeq > Class Template Reference	278
17.85.1 Detailed Description	279
17.85.2 Constructor & Destructor Documentation	280
17.85.2.1 UserData()	280
17.86 epiworld::vecHasher< T > Struct Template Reference	280
17.86.1 Detailed Description	280
17.87 vecHasher< T > Struct Template Reference	281
17.87.1 Detailed Description	281
17.88 epiworld::Virus< TSeq > Class Template Reference	281
17.88.1 Detailed Description	283
17.89 Virus< TSeq > Class Template Reference	283
17.89.1 Detailed Description	285
17.90 epiworld::Viruses< TSeq > Class Template Reference	286
17.90.1 Detailed Description	286
17.91 Viruses< TSeq > Class Template Reference	286
17.91.1 Detailed Description	287
17.92 epiworld::Viruses_const< TSeq > Class Template Reference	287
17.92.1 Detailed Description	288
17.93 Viruses_const< TSeq > Class Template Reference	288
17.93.1 Detailed Description	288
17.94 epiworld::VirusFunctions< TSeq > Class Template Reference	289
17.95 VirusFunctions< TSeq > Class Template Reference	289
18 File Documentation	291
18.1 include/epiworld/agent-meat-state.hpp File Reference	291
18.1.1 Detailed Description	292
18.2 include/epiworld/models/measlesmixing.hpp File Reference	293
18.2.1 Detailed Description	293

18.2.2 Macro Definition Documentation	293
18.2.2.1 GET_MODEL	294
18.2.2.2 SAMPLE_FROM_PROBS	294
18.3 include/epiworld/models/measlesmixingriskquarantine.hpp File Reference	294
18.3.1 Detailed Description	295
18.3.2 Macro Definition Documentation	295
18.3.2.1 GET_MODEL	295
18.3.2.2 SAMPLE_FROM_PROBS	295
Index	297

Chapter 1

Example: 00-hello-world

Output from the program:

```
Running the model...
|||||
SIMULATION STUDY
Name of the model      : (none)
Population size        : 10000
Agents' data           : (none)
Number of entities     : 0
Days (duration)        : 100 (of 100)
Number of viruses      : 1
Last run elapsed t     : 17.00ms
Last run speed         : 56.33 million agents x day / second
Rewiring               : off
Global events:
  (none)
Virus(es):
  - covid 19
Tool(s):
  - vaccine
Model parameters:
  (none)
Distribution of the population at time 100:
  - (0) Susceptible : 9950 -> 0
  - (1) Exposed     : 50 -> 0
  - (2) Recovered   : 0 -> 9399
  - (3) Removed     : 0 -> 601
Transition Probabilities:
  - Susceptible 0.92 0.08 - -
  - Exposed - 0.85 0.14 0.01
  - Recovered - - 1.00 -
  - Removed - - - 1.00
```

Chapter 2

Benchmarking

Here we keep a list of scenarios where we compare epiworld with other ABM simulation engines. Although the comparison is made at the speed level, we also list features of capabilities and main differences between the engines.

Chapter 3

Contributor Code of Conduct

As contributors and maintainers of this project, we pledge to respect all people who contribute through reporting issues, posting feature requests, updating documentation, submitting pull requests or patches, and other activities.

We are committed to making participation in this project a harassment-free experience for everyone, regardless of level of experience, gender, gender identity and expression, sexual orientation, disability, personal appearance, body size, race, ethnicity, age, or religion.

Examples of unacceptable behavior by participants include the use of sexual language or imagery, derogatory comments or personal attacks, trolling, public or private harassment, insults, or other unprofessional conduct.

Project maintainers have the right and responsibility to remove, edit, or reject comments, commits, code, wiki edits, issues, and other contributions that are not aligned to this Code of Conduct. Project maintainers who do not follow the Code of Conduct may be removed from the project team.

Instances of abusive, harassing, or otherwise unacceptable behavior may be reported by opening an issue or contacting one or more of the project maintainers.

This Code of Conduct is adapted from the Contributor Covenant (<http://contributor-covenant.org>), version 1.0.0, available at <http://contributor-covenant.org/version/1/0/0/>

Chapter 4

ModelMeaslesMixing

A comprehensive epidemiological model that combines measles-specific disease progression with population mixing and quarantine measures.

4.1 Overview

`ModelMeaslesMixing` implements a measles transmission model that extends the SEIR framework with:

- **Measles-specific disease progression:** Susceptible → Exposed → Prodromal → Rash → Recovered
- **Population mixing:** Uses contact matrices to model heterogeneous mixing between population groups
- **Infectious period:** Agents are infectious during the Prodromal state
- **Detection and isolation:** Detection occurs during the Rash state when symptoms become visible
- **Contact tracing:** Comprehensive contact tracing with configurable success rates
- **Quarantine measures:** Multiple quarantine states for exposed contacts
- **Vaccination:** Vaccine distribution with configurable efficacy and recovery enhancement

4.2 Disease States

The model includes 13 distinct states:

1. **Susceptible** - Can become infected
2. **Exposed** - Infected but not yet infectious (incubation period)
3. **Prodromal** - Infectious individuals (replaces "Infected" in standard SEIR)
4. **Rash** - Non-infectious with visible symptoms (detection occurs here)
5. **Isolated** - Detected individuals in self-isolation
6. **Isolated Recovered** - Recovered individuals still in isolation

7. **Detected Hospitalized** - Hospitalized individuals who were contact-traced
8. **Quarantined Exposed** - Exposed individuals in quarantine
9. **Quarantined Susceptible** - Susceptible individuals in quarantine
10. **Quarantined Prodromal** - Prodromal individuals in quarantine
11. **Quarantined Recovered** - Recovered individuals in quarantine
12. **Hospitalized** - Individuals requiring hospital care
13. **Recovered** - Immune individuals

4.3 Key Features

4.3.1 Disease Progression

- **Incubation Period:** Time from exposure to becoming infectious
- **Prodromal Period:** Duration of infectiousness before rash appears
- **Rash Period:** Duration of visible symptoms (detection window)
- **Detection:** Probabilistic detection during rash period
- **Hospitalization:** Some individuals require hospitalization

4.3.2 Population Mixing

- **Contact Matrices:** Define mixing patterns between population groups
- **Heterogeneous Mixing:** Different contact rates between groups
- **Scalable:** Supports multiple population entities

4.3.3 Public Health Measures

- **Contact Tracing:** Trace contacts of detected individuals
- **Quarantine:** Quarantine exposed contacts with configurable compliance
- **Isolation:** Isolate detected cases with configurable willingness
- **Vaccination:** Reduce susceptibility and enhance recovery

4.4 Parameters

4.4.1 Disease Parameters

- `contact_rate`: Average number of contacts per day
- `transmission_rate`: Probability of transmission per contact
- `incubation_period`: Average incubation period (days)
- `prodromal_period`: Average prodromal period (days)
- `rash_period`: Average rash period (days)
- `hospitalization_rate`: Probability of hospitalization
- `hospitalization_period`: Average hospitalization duration (days)

4.4.2 Detection and Isolation

- `days_undetected`: Average time until detection during rash period
- `isolation_period`: Duration of isolation for detected cases
- `isolation_willingness`: Proportion willing to self-isolate

4.4.3 Contact Tracing and Quarantine

- `contact_tracing_success_rate`: Probability of successfully tracing a contact
- `contact_tracing_days_prior`: Number of days to trace back
- `quarantine_period`: Duration of quarantine for contacts
- `quarantine_willingness`: Proportion willing to quarantine

4.4.4 Vaccination

- `prop_vaccinated`: Proportion of population vaccinated
- `vax_efficacy`: Vaccine efficacy (reduction in susceptibility)
- `vax_reduction_recovery_rate`: Recovery enhancement from vaccination

4.5 Usage Example

```
#include "epiworld.hpp"
// Contact matrix for single homogeneous population
std::vector<double> contact_matrix = {1.0};
// Create the model
epimodels::ModelMeaslesMixing<> model(
    "Measles",           // Virus name
    1000,                // Population size
    0.005,               // Initial prevalence
    4.0,                 // Contact rate
    0.9,                 // Transmission rate
    0.95,                // Vaccine efficacy
    0.5,                 // Vaccine recovery enhancement
    10.0,                // Incubation period
    4.0,                 // Prodromal period
    5.0,                 // Rash period
    contact_matrix,      // Contact matrix
    0.1,                 // Hospitalization rate
    7.0,                 // Hospitalization period
    2.0,                 // Days undetected
    14,                  // Quarantine period
    0.8,                 // Quarantine willingness
    0.9,                 // Isolation willingness
    10,                  // Isolation period
    0.7,                 // Vaccination rate
    0.8,                 // Contact tracing success rate
    3u,                  // Contact tracing days prior
);
// Add population entity
model.add_entity(Entity<>("Population", dist_factory<>(0, 1000)));
// Run simulation
model.run(60, 123);
model.print();
```

4.6 Differences from Other Models

4.6.1 vs. ModelMeaslesSchool

- **Population Mixing:** Adds contact matrices for heterogeneous mixing
- **Contact Tracing:** Enhanced contact tracing with configurable success rates
- **Scalability:** Supports multiple population entities

4.6.2 vs. ModelSEIRMixingQuarantine

- **Disease-Specific States:** Uses Prodromal/Rash instead of generic Infected
- **Detection Timing:** Detection occurs during Rash state, not Infected state
- **Infectious Period:** Only Prodromal individuals are infectious
- **Vaccination:** Includes vaccine distribution and efficacy

4.7 Testing

The model includes comprehensive tests that verify:

- Correct transition probabilities between states
- Proper detection and quarantine mechanics
- Population mixing functionality
- Reproductive number calculations
- All quarantine states function correctly

See `tests/19-measles-mixing.cpp` for test examples.

Chapter 5

ModelMeaslesMixingRiskQuarantine

A comprehensive epidemiological model that extends measles transmission modeling with risk-stratified quarantine strategies.

5.1 Overview

`ModelMeaslesMixingRiskQuarantine` implements a measles transmission model based on the `ModelMeaslesMixing` framework, with enhanced quarantine policies that vary based on exposure risk levels. This allows for targeted public health interventions that can optimize resource allocation and epidemic control.

5.1.1 Key Features

- **Measles-specific disease progression:** Susceptible → Exposed → Prodromal → Rash → Recovered
- **Population mixing:** Uses contact matrices to model heterogeneous mixing between population groups
- **Risk-stratified quarantine:** Three-tier system (high/medium/low risk) with customizable durations
- **Enhanced detection:** Detection rate parameter that activates during quarantine periods
- **Contact tracing:** Comprehensive contact tracing with configurable success rates
- **Entity-based risk assessment:** Risk levels determined by shared entity membership
- **Vaccination effects:** Vaccine distribution with configurable efficacy

5.2 Disease States

The model includes 13 distinct states:

1. **Susceptible** - Can become infected
2. **Exposed** - Infected but not yet infectious (incubation period)

3. **Prodromal** - Infectious individuals (replaces "Infected" in standard SEIR)
4. **Rash** - Non-infectious with visible symptoms (detection occurs here)
5. **Isolated** - Detected individuals in self-isolation
6. **Isolated Recovered** - Recovered individuals still in isolation
7. **Detected Hospitalized** - Hospitalized individuals who were contact-traced
8. **Quarantined Exposed** - Exposed individuals in quarantine
9. **Quarantined Susceptible** - Susceptible individuals in quarantine
10. **Quarantined Prodromal** - Prodromal individuals in quarantine
11. **Quarantined Recovered** - Recovered individuals in quarantine
12. **Hospitalized** - Individuals requiring hospital care
13. **Recovered** - Individuals who have recovered and gained immunity

5.3 Risk Classification System

When the quarantine process is triggered by a detected case, contacts are classified into three risk levels:

5.3.1 High Risk

- **Definition:** Unvaccinated agents who share entity membership with the case that triggered quarantine
- **Rationale:** Highest transmission risk due to close, prolonged contact within same household/workplace/school
- **Default quarantine duration:** 21 days (configurable)

5.3.2 Medium Risk

- **Definition:** Unvaccinated agents who had contact with infected individuals but don't share entity membership
- **Rationale:** Moderate transmission risk from community contact
- **Default quarantine duration:** 14 days (configurable)

5.3.3 Low Risk

- **Definition:** All other unvaccinated agents
- **Rationale:** Lowest transmission risk, potential for community spread
- **Default quarantine duration:** 7 days (configurable)

Note: Vaccinated agents (those with tools) are not subject to quarantine regardless of contact patterns.

5.4 Enhanced Detection

The model includes an enhanced detection mechanism that operates during active quarantine periods:

- **Detection rate quarantine:** Additional parameter specifying detection probability for prodromal individuals during active quarantine
- **Mechanism:** When any quarantine process is active, prodromal individuals have an additional chance of being detected and moved to quarantined prodromal state
- **Purpose:** Models increased surveillance and testing during outbreak response

5.5 Parameters

5.5.1 Disease Parameters

- **Contact rate:** Average number of contacts per step
- **Transmission rate:** Probability of transmission per contact
- **Incubation period:** Average time from exposure to becoming infectious
- **Prodromal period:** Average duration of infectious period
- **Rash period:** Average duration of rash symptoms
- **Hospitalization rate:** Probability of requiring hospitalization
- **Hospitalization period:** Average duration of hospital stay

5.5.2 Detection and Isolation

- **Days undetected:** Average time before rash cases are detected
- **Isolation period:** Duration of isolation for detected cases
- **Isolation willingness:** Proportion willing to self-isolate when detected
- **Detection rate quarantine:** Detection rate during active quarantine periods

5.5.3 Risk-based Quarantine

- **Quarantine period high:** Duration for high-risk contacts (days)
- **Quarantine period medium:** Duration for medium-risk contacts (days)
- **Quarantine period low:** Duration for low-risk contacts (days)
- **Quarantine willingness:** Proportion willing to comply with quarantine

5.5.4 Contact Tracing

- **Contact tracing success rate:** Probability of successfully identifying contacts
- **Contact tracing days prior:** Number of days prior to detection for tracing

5.5.5 Vaccination

- **Vaccination rate:** Proportion of agents initially vaccinated
- **Vax efficacy:** Vaccine effectiveness in preventing infection
- **Vax improved recovery:** Enhanced recovery rate for vaccinated individuals

5.6 Usage Example

```
#include <epiworld/epiworld.hpp>
// Contact matrix for 3 population groups
std::vector<double> contact_matrix = {
    0.8, 0.1, 0.1, // Group 1 mixing
    0.1, 0.8, 0.1, // Group 2 mixing
    0.1, 0.1, 0.8 // Group 3 mixing
};
// Create model with risk-based quarantine
epimodels::ModelMeaslesMixingRiskQuarantine<> model(
    1000, // Population size
    0.01, // Initial prevalence
    2.0, // Contact rate
    0.2, // Transmission rate
    0.9, // Vaccination efficacy
    0.3, // Vaccine recovery enhancement
    7.0, // Incubation period
    4.0, // Prodromal period
    5.0, // Rash period
    contact_matrix, // Contact matrix
    0.2, // Hospitalization rate
    7.0, // Hospitalization duration
    3.0, // Days undetected
    21, // Quarantine period high risk
    14, // Quarantine period medium risk
    7, // Quarantine period low risk
    0.8, // Quarantine willingness
    0.8, // Isolation willingness
    4, // Isolation period
    0.1, // Proportion vaccinated
    0.15, // Detection rate during quarantine
    1.0, // Contact tracing success rate
    4u // Contact tracing days prior
);
// Add population entities
model.add_entity(Entity<>("Households", dist_factory<>(0, 400)));
model.add_entity(Entity<>("Schools", dist_factory<>(400, 700)));
model.add_entity(Entity<>("Workplaces", dist_factory<>(700, 1000)));
// Set initial conditions
model.initial_states({1.0, 0.0}); // All infected start as exposed
// Run simulation
model.run(60, 123);
model.print();
```

5.7 Differences from Other Models

5.7.1 vs. ModelMeaslesMixing

- **Risk-stratified quarantine:** Three different quarantine durations based on exposure risk
- **Enhanced detection:** Additional detection during active quarantine periods
- **Entity-based risk assessment:** Risk levels determined by shared entity membership
- **Flexible quarantine policies:** Each risk level can have different quarantine duration or be disabled

5.7.2 vs. ModelMeaslesSchool

- **Population mixing:** Supports contact matrices for heterogeneous mixing
- **Risk stratification:** Multiple quarantine strategies rather than uniform approach
- **Enhanced contact tracing:** Risk-based contact management
- **Scalability:** Supports multiple population entities with different mixing patterns

5.8 Testing

The model includes comprehensive tests that verify:

- Correct transition probabilities between all 13 states
- Proper risk level assignment (high/medium/low)
- Enhanced detection mechanism during quarantine periods
- Different quarantine durations for different risk levels
- Comparison of uniform vs. risk-stratified quarantine strategies
- Population mixing functionality with multiple entities

See `tests/20a-measles-mixing-risk-quarantine.cpp` for test examples.

5.9 Applications

This model is particularly useful for:

1. **Outbreak response planning:** Comparing different quarantine strategies
2. **Resource optimization:** Allocating quarantine resources based on transmission risk
3. **Policy evaluation:** Assessing effectiveness of risk-stratified interventions
4. **Contact tracing optimization:** Understanding impact of enhanced detection during outbreaks
5. **Vaccination strategy:** Evaluating how vaccination coverage affects quarantine effectiveness

5.10 Implementation Notes

- Risk levels are assigned dynamically when quarantine is triggered
- Vaccinated agents are excluded from quarantine regardless of contact patterns
- Enhanced detection only operates when at least one quarantine process is active
- Quarantine durations can be set to -1 to disable quarantine for specific risk levels
- The model maintains backward compatibility with uniform quarantine by setting all periods equal

Chapter 6

epiworld c++ template library

6.1 Main features

This C++ template-header-only library provides a general framework for epidemiologic simulation. The main features of the library are:

1. Four key classes: `Model`, `Person`, `Tool`, and `Virus`.
2. The model features a social networks of `Persons`.
3. `Persons` can have multiple `Tools` as a defense system.
4. `Tools` can reduce contagion rate, transmissibility, death rates, and improve recovery rates.
5. `Viruses` can mutate (generating new variants).
6. `Models` can feature multiple states, e.g., `HEALTHY`, `SUSCEPTIBLE`, etc.
7. `Models` can have an arbitrary number of parameters.
8. **REALLY FAST** About 6.5 Million person/day simulations per second.

6.2 Algorithm

Setup

- Create viruses.
- Create tools (arbitrary).
- Set model parameters (arbitrary).
- Create global events (e.g., surveillance).
- Set up the population: small world network (default).
- Set up rewiring (optional).
- Set states (arbitrary number of them).

Run

1. Distribute the tool(s) and virus(es)
2. For each t in 1 -> Duration:
 - Update state for susceptible/infected/removed(?)
 - Mutate virus(es) (each individual)
 - Run Global events (e.g., surveillance)
 - Run rewiring algorithm

Along update:

- Contagion events are applied recorded.
- New variants are recorded.
- Optional user data is recorded.

6.3 Hello world (C++)

```
#include "include/epiworld/epiworld.hpp"
int main()
{
    // Creating a virus
    epiworld::Virus<> covid19("covid 19", .01, true);
    covid19.set_infectiousness(.8);

    // Creating a tool
    epiworld::Tool<> vax("vaccine", .5, true);
    vax.set_contagion_reduction(.95);
    // Creating a model
    epiworld::Model<> model;
    // Adding the tool and virus
    model.add_virus(covid19);
    model.add_tool(vax);
    // Generating a random pop
    model.population_from_adjlist(
        epiworld::rgraph_smallworld(1000, 5, .2)
    );
    // Initializing setting days and seed
    model.init(60, 123123);
    // Running the model
    model.run();
    model.print();
    return;
}
```

6.4 Surveillance simulation

- Incubation time of the disease $\sim \text{Gamma}(3, 1)$
- Duration of the disease $\sim \text{Gamma}(12, 1)$
- Probability of becoming symptomatic: 0.9
- Prob. of transmission: 1.0.
- Vaccinated population: 25%
- Vaccine efficacy: .9.
- Vaccine reduction on transmission: 0.5.
- Surveillance program of x% of the population at random.
- Individuals who test positive become isolated.

6.4.1 Preliminary results

```
# With low surveillance
pop_size <- 20e3
pop_seed <- pop_size * .01
s_levels <- c(0.0001, 0.002)
system(sprintf("./07-surveillance.o %i %i 100 %.04f 2>&1", pop_seed, pop_size, s_levels[1]), intern = TRUE)
|>
cat(sep = "\n")

## Running the model...
##
## | done.
##
##
## SIMULATION STUDY
##
## Population size      : 20000
## Days (duration)     : 200 (of 200)
## Number of variants  : 1
## Last run elapsed t   : 505.00ms
## Rewiring             : off
##
## Virus(es):
## - Covid19 (baseline prevalence: 100 seeds)
## Tool(s):
## - Vaccine (baseline prevalence: 25.00%)
##
## Model parameters:
## - Infect period      : 12.0000
## - Latent period      : 3.0000
## - Prob of symptoms   : 0.7000
## - Prob of transmission : 1.0000
## - Prob. death        : 0.0010
## - Prob. reinfect     : 0.1000
## - Surveillance prob. : 1.0e-04
## - Vax efficacy       : 0.9000
## - Vax redux transmission : 0.5000
##
## Distribution of the population at time 200:
## - Total susceptible (S) : 19900 -> 2106
## - Total recovered (S)   : 0 -> 17369
## - Total latent (I)      : 100 -> 109
## - Total symptomatic (I) : 0 -> 155
## - Total symptomatic isolated (I) : 0 -> 2
## - Total asymptomatic (I) : 0 -> 72
## - Total asymptomatic isolated (I) : 0 -> 0
## - Total removed (R)    : 0 -> 187
##
## (S): Susceptible, (I): Infected, (R): Recovered
##
hist1 <- read.csv("07-surveillance_hist.txt", sep = " ")
surv1 <- read.csv("07-surveillance_user_data.txt", sep = " ")
# With high surveillance
system(sprintf("./07-surveillance.o %i %i 100 %.04f 2>&1", pop_seed, pop_size, s_levels[2]), intern = TRUE)
|>
cat(sep = "\n")

## Running the model...
##
## | done.
##
##
## SIMULATION STUDY
##
## Population size      : 20000
## Days (duration)     : 200 (of 200)
## Number of variants  : 1
## Last run elapsed t   : 530.00ms
## Rewiring             : off
##
## Virus(es):
```

```
## - Covid19 (baseline prevalence: 100 seeds)
## Tool(s):
## - Vaccine (baseline prevalence: 25.00%)
##
## Model parameters:
## - Infect period      : 12.0000
## - Latent period      : 3.0000
## - Prob of symptoms   : 0.7000
## - Prob of transmission : 1.0000
## - Prob. death        : 0.0010
## - Prob. reinfect     : 0.1000
## - Surveillance prob. : 0.0020
## - Vax efficacy       : 0.9000
## - Vax redux transmission : 0.5000
##
## Distribution of the population at time 200:
## - Total susceptible (S)      : 19900 -> 2125
## - Total recovered (S)       : 0 -> 17325
## - Total latent (I)          : 100 -> 109
## - Total symptomatic (I)     : 0 -> 155
## - Total symptomatic isolated (I) : 0 -> 8
## - Total asymptomatic (I)    : 0 -> 76
## - Total asymptomatic isolated (I) : 0 -> 1
## - Total removed (R)        : 0 -> 201
##
## (S): Susceptible, (I): Infected, (R): Recovered
##
hist2 <- read.csv("07-surveillance_hist.txt", sep = " ")
surv2 <- read.csv("07-surveillance_user_data.txt", sep = " ")
hist_comb <- rbind(
  cbind(sim = as.character(s_levels[1]), hist1),
  cbind(sim = as.character(s_levels[2]), hist2)
)
ggplot(hist_comb, aes(x = date, y = counts + 1, colour = state, linetype=sim)) +
  geom_line() +
  # scale_y_log10() +
  labs(y = "Counts (log)")
```

6.4.2 Cases detected

```
survdat <- rbind(
  with(surv1, rbind(
    data.frame(Id = as.character(s_levels[1]), Date = date, Type = "N Sampled", n = nsampled),
    data.frame(Id = as.character(s_levels[1]), Date = date, Type = "N detected", n = ndetected),
    data.frame(Id = as.character(s_levels[1]), Date = date, Type = "N detected Asymp", n =
      ndetected_asymp),
    data.frame(Id = as.character(s_levels[1]), Date = date, Type = "N Asymp", n = nasymptomatic)
  )),
  with(surv2, rbind(
    data.frame(Id = as.character(s_levels[2]), Date = date, Type = "N Sampled", n = nsampled),
    data.frame(Id = as.character(s_levels[2]), Date = date, Type = "N detected", n = ndetected),
    data.frame(Id = as.character(s_levels[2]), Date = date, Type = "N detected Asymp", n =
      ndetected_asymp),
    data.frame(Id = as.character(s_levels[2]), Date = date, Type = "N Asymp", n = nasymptomatic)
  ))
)
ggplot(survdat, aes(x = Date, y = n + 1, colour = Type)) +
  geom_line() +
  facet_wrap(~Id) +
  scale_y_log10() +
  labs(y = "Counts (log)")
```

Chapter 7

General parameters

The following are parameters used for both ABM and Compartmental models.

```
EPI_BETA <- 0.75
EPI_GAMMA <- 0.33
EPI_LATENCY <- 1/0.33
EPI_N <- 10000
EPI_0 <- 0.01
EPI_NDAYS <- 50
Sys.setenv( # nolint
  EPI_BETA = EPI_BETA,
  EPI_GAMMA = EPI_GAMMA,
  EPI_LATENCY = EPI_LATENCY,
  EPI_N = EPI_N,
  EPI_0 = EPI_0,
  EPI_NDAYS = EPI_NDAYS
)
```

7.1 Compartmental Models

7.1.1 SIR Model

```
library(deSolve)
library(ggplot2)
library(data.table)
# Code from
# Chapter 2: SIR
# Book "Epidemics: Models and Data using R."
# By: Ottar N. Bjørnstad
sirmod <- function(t, y, parms) {
  # Pull state variables from the vector y
  S = y[1]
  I = y[2]
  R = y[3]

  # Pull parameter values from parms vector
  beta = parms["beta"]
  mu = parms["mu"]
  gamma = parms["gamma"]
  N = parms["N"]

  # Define equations
  dS = mu * (N - S) - beta * S * I/N
  dI = beta * S * I/N - (mu + gamma) * I
  dR = gamma * I - mu * R
  res = c(dS, dI, dR)

  # Return list of gradients
  list(res)
}
# Initial parameters
times <- seq(0, EPI_NDAYS, by = 1)
parms <- c(mu = 0, N = EPI_N, beta = EPI_BETA, gamma = EPI_GAMMA)
start <- c(S = EPI_N * (1 - EPI_0), I = EPI_N * EPI_0, R = 0)
out <- ode(y = start, times = times, func = sirmod, parms = parms)
out <- as.data.frame(out)
out <- rbind(
```

```

with(out, data.table(date = time, state = "Susceptible", counts = S)),
with(out, data.table(date = time, state = "Infected", counts = I)),
with(out, data.table(date = time, state = "Recovered", counts = R))
)

```

Now we visualize the model

```

ggplot(out, aes(x = date, y = counts)) +
  geom_line(aes(colour = state)) +
  labs(title = "Compartmental SIR")

```

7.1.2 SEIR Model

```

# Code adapted from
# Chapter 2: SIR
# Book "Epidemics: Models and Data using R"
# By: Ottar N. Bjørnstad
seirmod <- function(t, y, parms) {
  # Pull state variables from y vector
  S = y[1]
  E = y[2]
  I = y[3]
  R = y[4]

  # Pull parameter values from parms vector
  beta = parms["beta"]
  mu = parms["mu"]
  alpha = parms["alpha"]
  gamma = parms["gamma"]
  N = parms["N"]

  # Define equations
  dS = mu * (N - S) - beta * S * I/N - mu * S
  dE = beta * S * I/N - (mu + alpha) * E
  dI = alpha * E - (mu + gamma) * I
  dR = gamma * I - mu * R
  res = c(dS, dE, dI, dR)

  # Return list of gradients
  list(res)
}

# Initial parameters
parms <- c(
  mu = 0, N = EPI_N, beta = EPI_BETA,
  alpha = 1/EPI_LATENCY, gamma = EPI_GAMMA
)

start <- c(S = EPI_N * (1 - EPI_0), E = EPI_N * EPI_0, I = 0, R = 0)
out_seir <- ode(y = start, times = times, func = seirmod, parms = parms)
out_seir <- as.data.frame(out_seir)
out_seir <- rbind(
  with(out_seir, data.table(date = time, state = "Susceptible", counts = S)),
  with(out_seir, data.table(date = time, state = "Exposed", counts = E)),
  with(out_seir, data.table(date = time, state = "Infected", counts = I)),
  with(out_seir, data.table(date = time, state = "Recovered", counts = R))
)

```

Now we visualize the model

```

ggplot(out_seir, aes(x = date, y = counts)) +
  geom_line(aes(colour = state)) +
  labs(title = "Compartmental SEIR")

```

7.2 Agent-Based Model Approach

Calculation of the expected number of days in state S when prob of changing state equals α is $1/\alpha$

```

set.seed(712)
a <- .3
R <- matrix(runif(2e5 * 50), ncol = 50)
dat <- apply(R, 1, \x) {
  which.max(x < a)
})
mean(dat) - 1 / a

```

```
[1] -0.01049333
```


7.2.1 Mathematical preliminaries

That agent i becomes infected can be computed as follows:

At the same time, the probability of not becoming infected equals to the probability of no infected agent transmitting the infection. The probability that agent j infects i equals

In this case, β is parametrized such that its values are within $(0,1)$. Since transmission from the i infected agents happens independently, we finally have the following:

With the above equation, we can now calculate the change in the number of susceptible agents. In this case, it equals the expected number of new infections:

With the same parametrization in the canonical SIR model (Kermack and McKendrick), the instantaneous change in the number of susceptible agents equals $\frac{dS}{dt} = -S \beta I$. Given S and I , we can show that, as $\beta \rightarrow 0$, i.e., the population grows, both rates converge to the same number. Formally:

The same can be shown for the change in the number recovered.

7.2.2 Simulation study

Now, what happens with `epiworld`.

```
system("./09-sir-connected.o -n $EPI_N -b $EPI_BETA -d $EPI_NDAYS -p $EPI_0 -r $EPI_GAMMA -i 1.0 -s555599")
library(ggplot2)
epiworld <- data.table::fread("total_hist.txt")
ggplot(epiworld, aes(x = date, y = counts)) +
  geom_line(aes(colour = state)) +
  labs(title = "ABM SIR")
system("./09-seir-connected.o -n $EPI_N -b $EPI_BETA -d $EPI_NDAYS -p $EPI_0 -r $EPI_GAMMA -i 1.0 -s555599
-l $EPI_LATENCY")
library(ggplot2)
epiworld <- data.table::fread("total_hist.txt")
ggplot(epiworld, aes(x = date, y = counts)) +
  geom_line(aes(colour = state)) +
  labs(title = "ABM SEIR")
```

7.3 Comparing ABM with Compartmental Models

To this end, we will compare the results of the first run of the Compartmental model with 100 runs of the ABM, compute the confidence interval, and see how likely is the compartmental model to fall within the trajectory of the ABM simulation.

7.3.1 SIR

```
system("./09-sir-connected.o -n $EPI_N -b $EPI_BETA -d $EPI_NDAYS -p $EPI_0 -r $EPI_GAMMA -i 1.0 -s555599 -e
100")
library(ggplot2)
library(data.table)
epiworld <- data.table::fread("09-sir-connected-experiments.csv")
epiworld <- epiworld[, .(
  min = quantile(counts, probs = .025),
  mean = mean(counts),
  max = quantile(counts, probs = .975)), by = .(date, state)]
# Merging Compartmental
epiworld <- merge(
  epiworld,
  out[, .(date = date, state = state, compartmental = counts)],
  by = c("date", "state")
)
setorder(epiworld, state, date)
ggplot(epiworld, aes(x = date, y = mean)) +
  geom_ribbon(aes(ymin = min, ymax = max, colour = state), alpha = 0.1) +
  geom_line(aes(x = date, y = compartmental, colour = sprintf("%s (compt)", state)))
```

It seems that, although both yield the same equilibria, compartmental models reach the highest point of the simulation earlier. This makes sense as within a single day of the ABM simulation, compartmental models have more events taking place. Nonetheless, as predicted, as $\beta \rightarrow 0$, the differences become lesser. Furthermore, we could use the fact that the transition rates are known to compute an adjustment.

7.3.2 SEIR

```
system("./09-seir-connected.o -n $EPI_N -b $EPI_BETA -d $EPI_NDAYS -p $EPI_0 -r $EPI_GAMMA -i 1.0 -s555599
-e 100 -l $EPI_LATENCY")
library(ggplot2)
library(data.table)
epiworld_seir <- data.table::fread("09-seir-connected-experiments.csv")
epiworld_seir <- epiworld_seir[, .(
  min = quantile(counts, probs = .025),
  mean = mean(counts),
  max = quantile(counts, probs = .975)), by = .(date, state)]
# Merging Compartmental
epiworld_seir <- merge(
  epiworld_seir,
  out_seir[, .(date = date, state = state, compartmental = counts)],
  by = c("date", "state")
)
setorder(epiworld_seir, state, date)
ggplot(epiworld_seir, aes(x = date, y = mean)) +
  geom_ribbon(aes(ymin = min, ymax = max, colour = state), alpha = 0.1) +
  geom_line(aes(x = date, y = compartmental, colour = sprintf("%s (compt)", state)))
```

7.3.3 Rates

```
S <- 1000
rate_comp <- function(I,B) S * B * I
rate_abm <- function(I,B) S * (1 - (1 - B)^I)
op <- par(mfrow = c(3, 2))
for (i in c(1, 10, 100)) {
  curve(rate_comp(i, x), from = .01, to = 0.05)
  curve(rate_abm(i, x), from = .01, to = 0.05, add = FALSE, lty = 2)
}
par(op)
```

Chapter 8

MIT License

Copyright (c) 2021 George G. Vega Yon

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Chapter 9

model1

The dynamics of the simulation process are:

1. Discrete Markov process.

2. The simulation has the following parameters:

a. New variant emergence at rate X . b. For each variant k :

- Unvaccinated individuals become sick rate $C(k)$,
- Mortality rate $D(k)$,
- Recovery rate $H(k)$,
- Vaccines have an efficacy rate $E(v, k)$ and pseudo vaccines (recovered) have efficacy rate $E(r, k) < E(v, k)$. In general, the probability of i acquiring the disease k from j will be equal to

```  $P(i \text{ gets the disease from } j \mid \text{their states}) = C(k) * (1 - E(i, k)) * (1 - E(j, k))$  ```

where  $(i, j) \in (u, v, r)$ . Efficacy rate for unvaccinated is zero.

- Vaccinated individuals have a reduced mortality rate  $D(k, v) > D(k)$ , and recovered individuals  $D(k, r) \in (D(k, v), D(k))$
- Vaccinated individuals have an increased recovery rate  $H(k, v) > H(k)$ , whereas recovered's rate  $H(k, r) \in [H(k), H(k, v))$ .

The sum of mortality and recovery rates is less than one since the difference represents no change.

c. Each country vaccinates citizens at rate  $V$  function of  $A$  (availability) and  $B$  (citizens' acceptance rate.) d. In each country  $i$ , the entire population  $N(i)$  distributes between the following states:

- Healthy unvaccinated ( $N(i, t, u)$ ),
- Healthy vaccinated ( $N(i, t, v)$ ),
- Deceased ( $N(i, t, d)$ ),
- Recovered ( $N(i, t, r)$ ),
- Unvaccinated and sick with variant ( $N(i, t, s, k|u)$ )  $k$ ., and
- Vaccinated and sick with variant ( $N(i, t, s, k|v)$ )  $k$ .

Total sick are  $N(i, t, k, s) = \sum_{g \in \{u, v\}} N(i, t, k, s|g)$

Globally, we keep track of the prevalence of new variants. Variants can disappear if no more individuals port the variant, i.e., the prevalence rate  $P(k, t) = \sum_i N(i, s, k)$  equals zero.

d. Vaccines are manufactured at each country at rates  $M(i)$  and uniformly shared with other countries at rate  $S(i)$ . c. Population flows between each country pair  $(i, j)$  at a rate  $F(i, j)$ . Flows between countries do not change Population and are symmetric.

3. The simulation process is as follows:

- (a) Countries are initialized with a total population  $N(i)$ .
- (b) Variant zero initializes at a random location  $i$ , with an initial prevalence  $P(k, t) = N(i, t, k)$ .
- (c) For time  $t$  in  $(0, T)$  do:
  - a. Unvaccinated individuals can become sick of variant  $k$  with probability:  

$$\Pr(h \rightarrow s | i, t, k, u) \sim \sum(g \in \{u, v\}) (N(i, t-1, s, k | g) + \sum(j \neq i) F(i, j) * N(j, t-1, s, k | g)) * C(k) / (N(i) + \sum(j \neq i) N(j))$$
  - b. Vaccinated individuals can become sick of variant  $k$  with probability:  $\Pr(v \rightarrow s | i, t, k, v) \sim \Pr(h \rightarrow s | i, t, k) * (1 - E(v, k))$ .
  - b. Recovered individuals can become sick of variant  $k$  with probability:  $\Pr(v \rightarrow s | i, t, k, r) \sim \Pr(h \rightarrow s | i, t, k) * (1 - E(r, k))$ .
  - c. Sick individuals with variant  $k$  die with probability  $D(k)$  or recover with probability  $H(k)$ , otherwise they stay infected; with the rates depending on their vaccination status  $v$  or  $n$ .
  - d. Unvaccinated individuals vaccinate in country  $i$  with probability  $P(u \rightarrow v) \sim V(A(i, t), B(i))$ .
  - e. The country vaccine supply changes.

## Chapter 10

# Mixing probabilities in connected model

George G. Vega Yon, Ph.D. 2024-04-25

### 10.1 Case 1: No grouping

We will look into the probability of drawing infected individuals to simplify the algorithm. There are  $I$  infected individuals at any time in the simulation; thus, instead of drawing from  $\text{Bern}(c/N, N)$ , we will be drawing from  $\text{Bern}(c/N, I)$ . The next step is to check which infected individuals should be drawn. Let's compare the distributions using the hypergeometric as an example:

```
set.seed(132)
nsims <- 1e4
N <- 400
rate <- 5
p <- rate/N
I <- 10
sim_complex <- parallel::mclapply(1:nsims, \(i) {
 nsamples <- rbinom(N, N, p)
 sum(rbinom(N, size = nsamples, prob = I/N) > 0)
}, mc.cores = 4L) |> unlist()
sim_simple <- parallel::mclapply(1:nsims, \(i) {
 sum(rbinom(N, I, p) > 0)
}, mc.cores = 4L) |> unlist()
op <- par(mfrow = c(1,2))
MASS::truehist(sim_complex)
MASS::truehist(sim_simple)
par(op)
quantile(sim_complex)
```

0%	25%	50%	75%	100%
27	43	47	51	71

```
quantile(sim_simple)
```

0%	25%	50%	75%	100%
23	43	47	51	71

```
plotter(sim_complex, sim_simple)
```

These two approaches are equivalent, but the second one is more efficient from the computational perspective.

## 10.2 Case 2: Grouping

This explores the case when we have mixing across groups. The question is if we can replicate the effect at the group level.

```
set.seed(123133)
ngroups <- 3
mixing <- matrix(
 c(0.1, 0.2, 0.3, 0.2, 0.1, 0.2, 0.3, 0.2, 0.1),
 nrow = ngroups,
 ncol = ngroups
)
mixing <- mixing/rowSums(mixing)
mixing

 [,1] [,2] [,3]
[1,] 0.1666667 0.3333333 0.5000000
[2,] 0.4000000 0.2000000 0.4000000
[3,] 0.5000000 0.3333333 0.1666667

N <- 500
sizes <- c(100, 150, 250)
rate <- 5
p <- rate/N
I <- c(10, 30, 20)
ids <- rep.int(1:ngroups, times = sizes)
nsims <- 1e4
sim_complex <- parallel::mclapply(1:nsims, \(i) {
 # Sampling group first
 sapply(1:ngroups, \(g) {
 # How many each individual will sample from the groups
 ans <- rbinom(
 n = N, size = sizes[g], prob = mixing[ids,][,g] * p
) |> sum()
 # Sampling with replacement
 rbinom(ans, size = 1, prob = I[g]/sizes[g]) |> sum()
 }) |> sum()
}, mc.cores = 4L) |> unlist()
```

Using the alternative method in which we directly weight the probabilities:

```
sim_simple <- parallel::mclapply(1:nsims, \(i) {
 # Sampling group first
 sapply(1:ngroups, \(g) {
 rbinom(
 n = N, size = I[g], prob = mixing[cbind(ids,g)] * p
) |> sum()
 }) |> sum()
}, mc.cores = 4L) |> unlist()
op <- par(mfrow = c(1,2))
MASS::truehist(sim_complex)
MASS::truehist(sim_simple)
par(op)
quantile(sim_complex)
```

```
0% 25% 50% 75% 100%
57 88 94 101 131
```

```
quantile(sim_simple)
```

```
0% 25% 50% 75% 100%
58 87 94 101 135
```

```
plotter(sim_complex, sim_simple)
```



# Chapter 11

## EPI Simulator

### 11.1 Disease dynamics

Diseases continuously evolve in time. Changes in their genetic sequence make them more or less resistant to the particular version of the vaccine. Mutations also affect the transmissibility level and mortality rate of the disease. Using this approach allows making vaccination efficacy a function of compatibility between the variant and the vaccine.

When an individual becomes infected, the disease accumulates mutations in the new host. Ultimately, there is no single version of the disease present in the model, but rather an infinite number of them, each slightly different from the other.

### 11.2 Network dynamics

We can assume that the Population is organized in fully connected blocks for the first version of the model. Block sizes and the number of connections between blocks are Poisson random variables. Individuals interact with all the members of their blocks, and bridging individuals allow the disease to move across blocks.

### 11.3 Contagion dynamics

The transmission of the disease will be governed by the number of vaccinated, infected, and recovered within each block. Transmission between blocks will be treated in the same way, although individuals bridging the block will only interact with others within the block and their direct connections across the blocks.

### 11.4 Time dynamics

Time dynamics has two components, how biology evolves and how agents react.

The model develops as a continuous-time Markov process. Each block of individuals takes action at rates  $L(i|N(i))$  function of the local number of infections. This way, if

## 11.5 Updating agent's status

Like most other components, updating agents' states can be personalized. A naive approach allows agents to get infected with a single virus or stay as-is. The probability of this event is conditional on acquiring at most one virus. Since these are independent events, the conditional probability is computed as follows:

$$\begin{aligned} P(\text{Variant } k | \text{at most 1}) &= P(\text{at most 1} | \text{Variant } k) * P(\text{Variant } k) / P(\text{at most 1}) \\ &= P(\text{only variant } k) / P(\text{variant } k) * P(\text{Variant } k) / P(\text{at most 1}) \\ &= P(\text{only variant } k) / P(\text{at most 1}) \end{aligned}$$

Where

$$\begin{aligned} P(\text{only variant } k) &= P(k) * \text{Prod}(m \neq v) (1 - P(m)) \\ P(\text{at most 1}) &= P(\text{None}) + \text{Sum}(v \text{ in variants}) P(v) * \text{Prod}(m \neq v) (1 - P(m)) \\ P(\text{None}) &= \text{Prod}(v \text{ in variants}) (1 - P(v)) \end{aligned}$$

Furthermore, the (Variant, Person) pairs are treated independently.

### 11.5.1 Other parameters

- Who did you get the infection from.
- Omicron is 1.5 more infectious than delta.
- Surveillance:
  - Pull people to be tested at random.
  - Or at symptoms.
  - A mix of the two.
- Define a class for passing extra functions and datasets, for example, testing surveillance.
- Exposed people become infectious after k days.
- [Network](#) changes the can be a function of an ERGM. Apply K steps throughout time.
- Add progress bar.

## Chapter 12

# Namespace Index

### 12.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

<a href="#">epiworld::sampler</a>	Functions for sampling viruses . . . . .	<a href="#">45</a>
<a href="#">sampler</a>	Functions for sampling viruses . . . . .	<a href="#">48</a>



## Chapter 13

# Hierarchical Index

### 13.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

AdjList . . . . .	53
epiworld::AdjList . . . . .	54
Agent< TSeq > . . . . .	56
epiworld::Agent< TSeq > . . . . .	61
Agent< EPI_DEFAULT_TSEQ > . . . . .	56
AgentsSample< TSeq > . . . . .	64
epiworld::AgentsSample< TSeq > . . . . .	66
ContactTracing . . . . .	67
epiworld::ContactTracing . . . . .	70
DataBase< TSeq > . . . . .	73
epiworld::DataBase< TSeq > . . . . .	79
Entities< TSeq > . . . . .	83
epiworld::Entities< TSeq > . . . . .	84
Entities_const< TSeq > . . . . .	85
epiworld::Entities_const< TSeq > . . . . .	86
Entity< TSeq > . . . . .	87
epiworld::Entity< TSeq > . . . . .	88
Entity< EPI_DEFAULT_TSEQ > . . . . .	87
epiworld::Event< TSeq > . . . . .	90
Event< TSeq > . . . . .	91
epiworld::GlobalEvent< TSeq > . . . . .	93
GlobalEvent< TSeq > . . . . .	95
epiworld::LFMCMC< TData > . . . . .	96
LFMCMC< TData > . . . . .	97
epiworld::Model< TSeq > . . . . .	99
Model< TSeq > . . . . .	114
ModelMeaslesMixingRiskQuarantine< TSeq > . . . . .	159
ModelMeaslesSchool< TSeq > . . . . .	171
epiworld::Model< EPI_DEFAULT_TSEQ > . . . . .	99
ModelDiffNet< TSeq > . . . . .	133
ModelMeaslesMixing< TSeq > . . . . .	143
ModelSEIR< TSeq > . . . . .	179
ModelSEIRCONN< TSeq > . . . . .	184
ModelSEIRD< TSeq > . . . . .	191
ModelSEIRDCONN< TSeq > . . . . .	197

ModelSEIRMixing< TSeq > . . . . .	204
ModelSEIRMixingQuarantine< TSeq > . . . . .	213
ModelSIR< TSeq > . . . . .	220
ModelSIRCONN< TSeq > . . . . .	226
ModelSIRD< TSeq > . . . . .	231
ModelSIRDCONN< TSeq > . . . . .	236
ModelSIRLogit< TSeq > . . . . .	243
ModelSIRMixing< TSeq > . . . . .	250
ModelSIS< TSeq > . . . . .	256
ModelSISD< TSeq > . . . . .	259
ModelSURV< TSeq > . . . . .	263
epiworld::epimodels::ModelDiffNet< TSeq > . . . . .	131
epiworld::epimodels::ModelMeaslesMixing< TSeq > . . . . .	134
epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq > . . . . .	151
epiworld::epimodels::ModelMeaslesSchool< TSeq > . . . . .	167
epiworld::epimodels::ModelSEIR< TSeq > . . . . .	176
epiworld::epimodels::ModelSEIRCONN< TSeq > . . . . .	181
epiworld::epimodels::ModelSEIRD< TSeq > . . . . .	187
epiworld::epimodels::ModelSEIRDCONN< TSeq > . . . . .	194
epiworld::epimodels::ModelSEIRMixing< TSeq > . . . . .	200
epiworld::epimodels::ModelSEIRMixingQuarantine< TSeq > . . . . .	208
epiworld::epimodels::ModelSIR< TSeq > . . . . .	218
epiworld::epimodels::ModelSIRCONN< TSeq > . . . . .	222
epiworld::epimodels::ModelSIRD< TSeq > . . . . .	229
epiworld::epimodels::ModelSIRDCONN< TSeq > . . . . .	234
epiworld::epimodels::ModelSIRLogit< TSeq > . . . . .	239
epiworld::epimodels::ModelSIRMixing< TSeq > . . . . .	246
epiworld::epimodels::ModelSIS< TSeq > . . . . .	253
epiworld::epimodels::ModelSISD< TSeq > . . . . .	257
epiworld::epimodels::ModelSURV< TSeq > . . . . .	260
epiworld::ModelDiagram . . . . .	131
ModelDiagram . . . . .	131
Network< Nettype, Nodetype, Edgetype > . . . . .	265
epiworld::PersonTools< TSeq > . . . . .	265
PersonTools< TSeq > . . . . .	266
epiworld::Progress . . . . .	266
Progress . . . . .	266
epiworld::Queue< TSeq > . . . . .	267
Queue< TSeq > . . . . .	267
RandGraph . . . . .	268
epiworld::SAMPLETYPE . . . . .	269
SAMPLETYPE . . . . .	269
TestResults . . . . .	269
epiworld::Tool< TSeq > . . . . .	269
Tool< TSeq > . . . . .	271
epiworld::ToolFunctions< TSeq > . . . . .	272
ToolFunctions< TSeq > . . . . .	273
epiworld::Tools< TSeq > . . . . .	274
Tools< TSeq > . . . . .	274
epiworld::Tools_const< TSeq > . . . . .	275
Tools_const< TSeq > . . . . .	276
epiworld::UserData< TSeq > . . . . .	277
UserData< TSeq > . . . . .	278
epiworld::vecHasher< T > . . . . .	280
vecHasher< T > . . . . .	281
epiworld::Virus< TSeq > . . . . .	281
Virus< TSeq > . . . . .	283
epiworld::Viruses< TSeq > . . . . .	286

Viruses< TSeq > . . . . .	286
epiworld::Viruses_const< TSeq > . . . . .	287
Viruses_const< TSeq > . . . . .	288
epiworld::VirusFunctions< TSeq > . . . . .	289
VirusFunctions< TSeq > . . . . .	289





## Chapter 14

# Class Index

### 14.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">AdjList</a> . . . . .	53
<a href="#">epiworld::AdjList</a> . . . . .	54
<a href="#">Agent&lt; TSeq &gt;</a>	
<a href="#">Agent</a> (agents) . . . . .	56
<a href="#">epiworld::Agent&lt; TSeq &gt;</a>	
<a href="#">Agent</a> (agents) . . . . .	61
<a href="#">AgentsSample&lt; TSeq &gt;</a>	
Sample of agents . . . . .	64
<a href="#">epiworld::AgentsSample&lt; TSeq &gt;</a>	
Sample of agents . . . . .	66
<a href="#">ContactTracing</a>	
Class for tracing contacts between agents . . . . .	67
<a href="#">epiworld::ContactTracing</a>	
Class for tracing contacts between agents . . . . .	70
<a href="#">DataBase&lt; TSeq &gt;</a>	
Statistical data about the process . . . . .	73
<a href="#">epiworld::DataBase&lt; TSeq &gt;</a>	
Statistical data about the process . . . . .	79
<a href="#">Entities&lt; TSeq &gt;</a>	
Set of <a href="#">Entities</a> (useful for building iterators) . . . . .	83
<a href="#">epiworld::Entities&lt; TSeq &gt;</a>	
Set of <a href="#">Entities</a> (useful for building iterators) . . . . .	84
<a href="#">Entities_const&lt; TSeq &gt;</a>	
Set of <a href="#">Entities</a> (const) (useful for iterators) . . . . .	85
<a href="#">epiworld::Entities_const&lt; TSeq &gt;</a>	
Set of <a href="#">Entities</a> (const) (useful for iterators) . . . . .	86
<a href="#">Entity&lt; TSeq &gt;</a> . . . . .	87
<a href="#">epiworld::Entity&lt; TSeq &gt;</a> . . . . .	88
<a href="#">epiworld::Event&lt; TSeq &gt;</a>	
<a href="#">Event</a> data for update an agent . . . . .	90
<a href="#">Event&lt; TSeq &gt;</a>	
<a href="#">Event</a> data for update an agent . . . . .	91
<a href="#">epiworld::GlobalEvent&lt; TSeq &gt;</a>	
Template for a Global <a href="#">Event</a> . . . . .	93
<a href="#">GlobalEvent&lt; TSeq &gt;</a>	
Template for a Global <a href="#">Event</a> . . . . .	95

<a href="#">epiworld::LFMCMC&lt; TData &gt;</a>	
Likelihood-Free Markov Chain Monte Carlo	96
<a href="#">LFMCMC&lt; TData &gt;</a>	
Likelihood-Free Markov Chain Monte Carlo	97
<a href="#">epiworld::Model&lt; TSeq &gt;</a>	
Core class of epiworld	99
<a href="#">Model&lt; TSeq &gt;</a>	
Core class of epiworld	114
<a href="#">epiworld::ModelDiagram</a>	131
<a href="#">ModelDiagram</a>	131
<a href="#">epiworld::epimodels::ModelDiffNet&lt; TSeq &gt;</a>	
Template for a <a href="#">Network</a> Diffusion <a href="#">Model</a>	131
<a href="#">ModelDiffNet&lt; TSeq &gt;</a>	
Template for a <a href="#">Network</a> Diffusion <a href="#">Model</a>	133
<a href="#">epiworld::epimodels::ModelMeaslesMixing&lt; TSeq &gt;</a>	
Measles model with population mixing, quarantine, and contact tracing	134
<a href="#">ModelMeaslesMixing&lt; TSeq &gt;</a>	
Measles model with population mixing, quarantine, and contact tracing	143
<a href="#">epiworld::epimodels::ModelMeaslesMixingRiskQuarantine&lt; TSeq &gt;</a>	
Measles model with population mixing and risk-based quarantine strategies	151
<a href="#">ModelMeaslesMixingRiskQuarantine&lt; TSeq &gt;</a>	
Measles model with population mixing and risk-based quarantine strategies	159
<a href="#">epiworld::epimodels::ModelMeaslesSchool&lt; TSeq &gt;</a>	
Template for a Measles model with quarantine	167
<a href="#">ModelMeaslesSchool&lt; TSeq &gt;</a>	
Template for a Measles model with quarantine	171
<a href="#">epiworld::epimodels::ModelSEIR&lt; TSeq &gt;</a>	
Template for a Susceptible-Exposed-Infected-Removed (SEIR) model	176
<a href="#">ModelSEIR&lt; TSeq &gt;</a>	
Template for a Susceptible-Exposed-Infected-Removed (SEIR) model	179
<a href="#">epiworld::epimodels::ModelSEIRCONN&lt; TSeq &gt;</a>	181
<a href="#">ModelSEIRCONN&lt; TSeq &gt;</a>	184
<a href="#">epiworld::epimodels::ModelSEIRD&lt; TSeq &gt;</a>	
Template for a Susceptible-Exposed-Infected-Removed-Deceased (SEIRD) model	187
<a href="#">ModelSEIRD&lt; TSeq &gt;</a>	
Template for a Susceptible-Exposed-Infected-Removed-Deceased (SEIRD) model	191
<a href="#">epiworld::epimodels::ModelSEIRDCONN&lt; TSeq &gt;</a>	194
<a href="#">ModelSEIRDCONN&lt; TSeq &gt;</a>	197
<a href="#">epiworld::epimodels::ModelSEIRMixing&lt; TSeq &gt;</a>	200
<a href="#">ModelSEIRMixing&lt; TSeq &gt;</a>	204
<a href="#">epiworld::epimodels::ModelSEIRMixingQuarantine&lt; TSeq &gt;</a>	208
<a href="#">ModelSEIRMixingQuarantine&lt; TSeq &gt;</a>	213
<a href="#">epiworld::epimodels::ModelSIR&lt; TSeq &gt;</a>	
Template for a Susceptible-Infected-Removed (SIR) model	218
<a href="#">ModelSIR&lt; TSeq &gt;</a>	
Template for a Susceptible-Infected-Removed (SIR) model	220
<a href="#">epiworld::epimodels::ModelSIRCONN&lt; TSeq &gt;</a>	222
<a href="#">ModelSIRCONN&lt; TSeq &gt;</a>	226
<a href="#">epiworld::epimodels::ModelSIRD&lt; TSeq &gt;</a>	
Template for a Susceptible-Infected-Removed-Deceased (SIRD) model	229
<a href="#">ModelSIRD&lt; TSeq &gt;</a>	
Template for a Susceptible-Infected-Removed-Deceased (SIRD) model	231
<a href="#">epiworld::epimodels::ModelSIRDCONN&lt; TSeq &gt;</a>	234
<a href="#">ModelSIRDCONN&lt; TSeq &gt;</a>	236
<a href="#">epiworld::epimodels::ModelSIRLogit&lt; TSeq &gt;</a>	
Template for a Susceptible-Infected-Removed (SIR) model	239
<a href="#">ModelSIRLogit&lt; TSeq &gt;</a>	
Template for a Susceptible-Infected-Removed (SIR) model	243

<a href="#">epiworld::epimodels::ModelSIRMixing&lt; TSeq &gt;</a>	246
<a href="#">ModelSIRMixing&lt; TSeq &gt;</a>	250
<a href="#">epiworld::epimodels::ModelSIS&lt; TSeq &gt;</a>	
Template for a Susceptible-Infected-Susceptible (SIS) model	253
<a href="#">ModelSIS&lt; TSeq &gt;</a>	
Template for a Susceptible-Infected-Susceptible (SIS) model	256
<a href="#">epiworld::epimodels::ModelSISD&lt; TSeq &gt;</a>	
Template for a Susceptible-Infected-Susceptible-Deceased (SISD) model	257
<a href="#">ModelSISD&lt; TSeq &gt;</a>	
Template for a Susceptible-Infected-Susceptible-Deceased (SISD) model	259
<a href="#">epiworld::epimodels::ModelSURV&lt; TSeq &gt;</a>	260
<a href="#">ModelSURV&lt; TSeq &gt;</a>	263
<a href="#">Network&lt; Nettype, Nodetype, Edgetype &gt;</a>	265
<a href="#">epiworld::PersonTools&lt; TSeq &gt;</a>	265
<a href="#">PersonTools&lt; TSeq &gt;</a>	266
<a href="#">epiworld::Progress</a>	
A simple progress bar	266
<a href="#">Progress</a>	
A simple progress bar	266
<a href="#">epiworld::Queue&lt; TSeq &gt;</a>	
Controls which agents are verified at each step	267
<a href="#">Queue&lt; TSeq &gt;</a>	
Controls which agents are verified at each step	267
<a href="#">RandGraph</a>	268
<a href="#">epiworld::SAMPLETYPE</a>	269
<a href="#">SAMPLETYPE</a>	269
<a href="#">TestResults</a>	269
<a href="#">epiworld::Tool&lt; TSeq &gt;</a>	
Tools for defending the agent against the virus	269
<a href="#">Tool&lt; TSeq &gt;</a>	
Tools for defending the agent against the virus	271
<a href="#">epiworld::ToolFunctions&lt; TSeq &gt;</a>	
Helper class to store the functions avoiding multiple shared_pointers (we have only one for the four of these)	272
<a href="#">ToolFunctions&lt; TSeq &gt;</a>	
Helper class to store the functions avoiding multiple shared_pointers (we have only one for the four of these)	273
<a href="#">epiworld::Tools&lt; TSeq &gt;</a>	
Set of tools (useful for building iterators)	274
<a href="#">Tools&lt; TSeq &gt;</a>	
Set of tools (useful for building iterators)	274
<a href="#">epiworld::Tools_const&lt; TSeq &gt;</a>	
Set of <a href="#">Tools</a> (const) (useful for iterators)	275
<a href="#">Tools_const&lt; TSeq &gt;</a>	
Set of <a href="#">Tools</a> (const) (useful for iterators)	276
<a href="#">epiworld::UserData&lt; TSeq &gt;</a>	
Personalized data by the user	277
<a href="#">UserData&lt; TSeq &gt;</a>	
Personalized data by the user	278
<a href="#">epiworld::vecHasher&lt; T &gt;</a>	
Vector hasher	280
<a href="#">vecHasher&lt; T &gt;</a>	
Vector hasher	281
<a href="#">epiworld::Virus&lt; TSeq &gt;</a>	
Virus	281
<a href="#">Virus&lt; TSeq &gt;</a>	
Virus	283

<a href="#">epiworld::Viruses&lt; TSeq &gt;</a>	
Set of viruses (useful for building iterators) . . . . .	286
<a href="#">Viruses&lt; TSeq &gt;</a>	
Set of viruses (useful for building iterators) . . . . .	286
<a href="#">epiworld::Viruses_const&lt; TSeq &gt;</a>	
Set of <a href="#">Viruses</a> (const) (useful for iterators) . . . . .	287
<a href="#">Viruses_const&lt; TSeq &gt;</a>	
Set of <a href="#">Viruses</a> (const) (useful for iterators) . . . . .	288
<a href="#">epiworld::VirusFunctions&lt; TSeq &gt;</a>	289
<a href="#">VirusFunctions&lt; TSeq &gt;</a>	289

# Chapter 15

## File Index

### 15.1 File List

Here is a list of all documented files with brief descriptions:

<b>epiworld.hpp</b>	??
include/epiworld/ <b>adjlist-bones.hpp</b>	??
include/epiworld/ <b>adjlist-meat.hpp</b>	??
include/epiworld/ <b>agent-bones.hpp</b>	??
include/epiworld/ <b>agent-events-meat.hpp</b>	??
include/epiworld/ <b>agent-meat-state.hpp</b>	??
Sampling functions are getting big, so we keep them in a separate file	291
include/epiworld/ <b>agent-meat-virus-sampling.hpp</b>	??
include/epiworld/ <b>agent-meat.hpp</b>	??
include/epiworld/ <b>agentssample-bones.hpp</b>	??
include/epiworld/ <b>config.hpp</b>	??
include/epiworld/ <b>contacttracing-bones.hpp</b>	??
include/epiworld/ <b>database-bones.hpp</b>	??
include/epiworld/ <b>database-meat.hpp</b>	??
include/epiworld/ <b>entities-bones.hpp</b>	??
include/epiworld/ <b>entity-bones.hpp</b>	??
include/epiworld/ <b>entity-distribute-meat.hpp</b>	??
include/epiworld/ <b>entity-meat.hpp</b>	??
include/epiworld/ <b>epiworld-macros.hpp</b>	??
include/epiworld/ <b>epiworld.hpp</b>	??
include/epiworld/ <b>globalevent-bones.hpp</b>	??
include/epiworld/ <b>globalevent-meat.hpp</b>	??
include/epiworld/ <b>misc.hpp</b>	??
include/epiworld/ <b>model-bones.hpp</b>	??
include/epiworld/ <b>model-meat-print.hpp</b>	??
include/epiworld/ <b>model-meat.hpp</b>	??
include/epiworld/ <b>modeldiagram-bones.hpp</b>	??
include/epiworld/ <b>modeldiagram-meat.hpp</b>	??
include/epiworld/ <b>network-bones.hpp</b>	??
include/epiworld/ <b>progress.hpp</b>	??
include/epiworld/ <b>queue-bones.hpp</b>	??
include/epiworld/ <b>randgraph.hpp</b>	??
include/epiworld/ <b>random_graph.hpp</b>	??
include/epiworld/ <b>seq_processing.hpp</b>	??
include/epiworld/ <b>tool-bones.hpp</b>	??

include/epiworld/ <b>tool-distribute-meat.hpp</b>	??
include/epiworld/ <b>tool-meat.hpp</b>	??
include/epiworld/ <b>tools-bones.hpp</b>	??
include/epiworld/ <b>userdata-bones.hpp</b>	??
include/epiworld/ <b>userdata-meat.hpp</b>	??
include/epiworld/ <b>virus-bones.hpp</b>	??
include/epiworld/ <b>virus-distribute-meat.hpp</b>	??
include/epiworld/ <b>virus-meat.hpp</b>	??
include/epiworld/ <b>viruses-bones.hpp</b>	??
include/epiworld/math/ <b>distributions.hpp</b>	??
include/epiworld/math/ <b>lfmcmc.hpp</b>	??
include/epiworld/math/lfmcmc/ <b>lfmcmc-bones.hpp</b>	??
include/epiworld/math/lfmcmc/ <b>lfmcmc-meat-print.hpp</b>	??
include/epiworld/math/lfmcmc/ <b>lfmcmc-meat.hpp</b>	??
include/epiworld/models/ <b>diffnet.hpp</b>	??
include/epiworld/models/ <b>globalevents.hpp</b>	??
include/epiworld/models/ <b>init-functions.hpp</b>	??
include/epiworld/models/ <a href="#">measlesmixing.hpp</a>	
Template for a Measles model with population mixing, quarantine, and contact tracing	293
include/epiworld/models/ <a href="#">measlesmixingriskquarantine.hpp</a>	
Template for a Measles model with population mixing and risk-based quarantine	294
include/epiworld/models/ <b>measlesquarantine.hpp</b>	??
include/epiworld/models/ <b>models.hpp</b>	??
include/epiworld/models/ <b>seir.hpp</b>	??
include/epiworld/models/ <b>seirconnected.hpp</b>	??
include/epiworld/models/ <b>seird.hpp</b>	??
include/epiworld/models/ <b>seirdconnected.hpp</b>	??
include/epiworld/models/ <b>seirmixing.hpp</b>	??
include/epiworld/models/ <b>seirmixingquarantine.hpp</b>	??
include/epiworld/models/ <b>sir.hpp</b>	??
include/epiworld/models/ <b>sirconnected.hpp</b>	??
include/epiworld/models/ <b>sird.hpp</b>	??
include/epiworld/models/ <b>sirdconnected.hpp</b>	??
include/epiworld/models/ <b>sirlogit.hpp</b>	??
include/epiworld/models/ <b>sirmixing.hpp</b>	??
include/epiworld/models/ <b>sis.hpp</b>	??
include/epiworld/models/ <b>sisd.hpp</b>	??
include/epiworld/models/ <b>surveillance.hpp</b>	??
tests/ <b>tests.hpp</b>	??

## Chapter 16

# Namespace Documentation

### 16.1 epiworld::sampler Namespace Reference

Functions for sampling viruses.

#### Functions

- `template<typename TSeq = EPI_DEFAULT_TSEQ>`  
`std::function< void(Agent< TSeq > *, Model< TSeq > *)> make\_update\_susceptible (std::vector< epiworld_fast_uint > exclude={})`  
*Make a function to sample from neighbors.*
- `template<typename TSeq = EPI_DEFAULT_TSEQ>`  
`std::function< Virus< TSeq > *(Agent< TSeq > *, Model< TSeq > *)> make\_sample\_virus\_neighbors (std::vector< epiworld_fast_uint > exclude={})`  
*Make a function to sample from neighbors.*
- `template<typename TSeq = EPI_DEFAULT_TSEQ>`  
`Virus< TSeq > * sample\_virus\_single (Agent< TSeq > *p, Model< TSeq > *m)`  
*Sample from neighbors pool of viruses (at most one)*

#### 16.1.1 Detailed Description

Functions for sampling viruses.

#### 16.1.2 Function Documentation

##### 16.1.2.1 `make_sample_virus_neighbors()`

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::function<Virus<TSeq>*(Agent<TSeq>*,Model<TSeq>*)> epiworld::sampler::make_sample_virus_neighbors (
 std::vector< epiworld_fast_uint > exclude = {}) [inline]
```

Make a function to sample from neighbors.

This is akin to the function `default_update_susceptible`, with the difference that it will create a function that supports excluding states from the sampling frame. For example, individuals who have acquired a virus can be excluded if in incubation state.

## Template Parameters

<i>TSeq</i>	
-------------	--

## Parameters

<i>exclude</i>	unsigned vector of states that need to be excluded from the sampling
----------------	----------------------------------------------------------------------

## Returns

Virus<TSeq>\* of the selected virus. If none selected (or none available,) returns a nullptr;

**16.1.2.2 make\_update\_susceptible()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::function<void (Agent<TSeq>*, Model<TSeq>*)> epiworld::sampler::make_update_susceptible (
 std::vector< epiworld_fast_uint > exclude = {}) [inline]
```

Make a function to sample from neighbors.

This is akin to the function `default_update_susceptible`, with the difference that it will create a function that supports excluding states from the sampling frame. For example, individuals who have acquired a virus can be excluded if in incubation state.

## Template Parameters

<i>TSeq</i>	
-------------	--

## Parameters

<i>exclude</i>	unsigned vector of states that need to be excluded from the sampling
----------------	----------------------------------------------------------------------

## Returns

Virus<TSeq>\* of the selected virus. If none selected (or none available,) returns a nullptr;

**16.1.2.3 sample\_virus\_single()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
Virus<TSeq>* epiworld::sampler::sample_virus_single (
 Agent< TSeq > * p,
 Model< TSeq > * m) [inline]
```

Sample from neighbors pool of viruses (at most one)



This function samples at most one virus from the pool of viruses from its neighbors. If no virus is selected, the function returns a `nullptr`, otherwise it returns a pointer to the selected virus.

This can be used to build a new update function (EPI\_NEW\_UPDATEFUN.)

## Template Parameters

<i>TSeq</i>	
-------------	--

## Parameters

<i>p</i>	Pointer to person
<i>m</i>	Pointer to the model

## Returns

Virus<TSeq>\* of the selected virus. If none selected (or none available,) returns a nullptr;

## 16.2 sampler Namespace Reference

Functions for sampling viruses.

### Functions

- `template<typename TSeq = EPI_DEFAULT_TSEQ>`  
`std::function< void(Agent< TSeq > *, Model< TSeq > *)> make\_update\_susceptible (std::vector< epiworld_fast_uint > exclude={})`  
*Make a function to sample from neighbors.*
- `template<typename TSeq = EPI_DEFAULT_TSEQ>`  
`std::function< Virus< TSeq > *(Agent< TSeq > *, Model< TSeq > *)> make\_sample\_virus\_neighbors (std::vector< epiworld_fast_uint > exclude={})`  
*Make a function to sample from neighbors.*
- `template<typename TSeq = EPI_DEFAULT_TSEQ>`  
`Virus< TSeq > * sample\_virus\_single (Agent< TSeq > *p, Model< TSeq > *m)`  
*Sample from neighbors pool of viruses (at most one)*

### 16.2.1 Detailed Description

Functions for sampling viruses.

### 16.2.2 Function Documentation

#### 16.2.2.1 `make_sample_virus_neighbors()`

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::function<Virus<TSeq>*(Agent<TSeq>*,Model<TSeq>*)> sampler::make_sample_virus_neighbors
(
 std::vector< epiworld_fast_uint > exclude = {}) [inline]
```

Make a function to sample from neighbors.

This is akin to the function `default_update_susceptible`, with the difference that it will create a function that supports excluding states from the sampling frame. For example, individuals who have acquired a virus can be excluded if in incubation state.

## Template Parameters

<i>TSeq</i>	
-------------	--

## Parameters

<i>exclude</i>	unsigned vector of states that need to be excluded from the sampling
----------------	----------------------------------------------------------------------

## Returns

Virus<TSeq>\* of the selected virus. If none selected (or none available,) returns a nullptr;

## 16.2.2.2 make\_update\_susceptible()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::function<void (Agent<TSeq>*, Model<TSeq>*)> sampler::make_update_susceptible (
 std::vector< epiworld_fast_uint > exclude = {}) [inline]
```

Make a function to sample from neighbors.

This is akin to the function `default_update_susceptible`, with the difference that it will create a function that supports excluding states from the sampling frame. For example, individuals who have acquired a virus can be excluded if in incubation state.

## Template Parameters

<i>TSeq</i>	
-------------	--

## Parameters

<i>exclude</i>	unsigned vector of states that need to be excluded from the sampling
----------------	----------------------------------------------------------------------

## Returns

Virus<TSeq>\* of the selected virus. If none selected (or none available,) returns a nullptr;

## 16.2.2.3 sample\_virus\_single()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
Virus<TSeq>* sampler::sample_virus_single (
 Agent< TSeq > * p,
 Model< TSeq > * m) [inline]
```

Sample from neighbors pool of viruses (at most one)

This function samples at most one virus from the pool of viruses from its neighbors. If no virus is selected, the function returns a `nullptr`, otherwise it returns a pointer to the selected virus.

This can be used to build a new update function (`EPI_NEW_UPDATEFUN.`)

## Template Parameters

<i>TSeq</i>	
-------------	--

## Parameters

<i>p</i>	Pointer to person
<i>m</i>	Pointer to the model

## Returns

Virus<TSeq>\* of the selected virus. If none selected (or none available,) returns a nullptr;



## Chapter 17

# Class Documentation

### 17.1 AdjList Class Reference

#### Public Member Functions

- [AdjList](#) (const std::vector< int > &source, const std::vector< int > &target, int size, bool directed)  
*Construct a new Adj List object.*
- **AdjList** ([AdjList](#) &&a)
- **AdjList** (const [AdjList](#) &a)
- [AdjList](#) & **operator=** (const [AdjList](#) &a)
- void [read\\_edgelist](#) (std::string fn, int size, int skip=0, bool directed=true)  
*Read an edgelist.*
- std::map< int, int > **operator()** (epiworld\_fast\_uint i) const
- void **print** (epiworld\_fast\_uint limit=20u) const
- size\_t [vcount](#) () const  
*Number of vertices/nodes in the network.*
- size\_t [ecount](#) () const  
*Number of edges/arcs/ties in the network.*
- std::vector< std::map< int, int > > & **get\_dat** ()
- bool [is\\_directed](#) () const  
*true if the network is directed.*

#### 17.1.1 Constructor & Destructor Documentation

##### 17.1.1.1 AdjList()

```
AdjList::AdjList (
 const std::vector< int > & source,
 const std::vector< int > & target,
 int size,
 bool directed) [inline]
```

Construct a new Adj List object.

Ids in the network are assume to range from 0 to size - 1.

## Parameters

<i>source</i>	Unsigned int vector with the source
<i>target</i>	Unsigned int vector with the target
<i>size</i>	Number of vertices in the network.
<i>directed</i>	Bool true if the network is directed

## 17.1.2 Member Function Documentation

### 17.1.2.1 read\_edgelist()

```
void AdjList::read_edgelist (
 std::string fn,
 int size,
 int skip = 0,
 bool directed = true) [inline]
```

Read an edgelist.

Ids in the network are assume to range from 0 to `size - 1`.

## Parameters

<i>fn</i>	Path to the file
<i>skip</i>	Number of lines to skip (e.g., 1 if there's a header)
<i>directed</i>	true if the network is directed
<i>size</i>	Number of vertices in the network.

The documentation for this class was generated from the following files:

- include/epiworld/adjlist-bones.hpp
- include/epiworld/adjlist-meat.hpp

## 17.2 epiworld::AdjList Class Reference

### Public Member Functions

- [AdjList](#) (const std::vector< int > &source, const std::vector< int > &target, int size, bool directed)  
*Construct a new Adj List object.*
- [AdjList](#) ([AdjList](#) &&a)
- [AdjList](#) (const [AdjList](#) &a)
- [AdjList](#) & [operator=](#) (const [AdjList](#) &a)
- void [read\\_edgelist](#) (std::string fn, int size, int skip=0, bool directed=true)  
*Read an edgelist.*



- `std::map< int, int > operator()` (`epiworld_fast_uint i`) `const`
- `void print` (`epiworld_fast_uint limit=20u`) `const`
- `size_t vcount` () `const`  
*Number of vertices/nodes in the network.*
- `size_t ecount` () `const`  
*Number of edges/arcs/ties in the network.*
- `std::vector< std::map< int, int > > & get_dat` ()
- `bool is_directed` () `const`  
*true if the network is directed.*

## 17.2.1 Constructor & Destructor Documentation

### 17.2.1.1 AdjList()

```
AdjList::AdjList (
 const std::vector< int > & source,
 const std::vector< int > & target,
 int size,
 bool directed) [inline]
```

Construct a new Adj List object.

Ids in the network are assume to range from 0 to `size - 1`.

#### Parameters

<i>source</i>	Unsigned int vector with the source
<i>target</i>	Unsigned int vector with the target
<i>size</i>	Number of vertices in the network.
<i>directed</i>	Bool true if the network is directed

## 17.2.2 Member Function Documentation

### 17.2.2.1 read\_edgelist()

```
void AdjList::read_edgelist (
 std::string fn,
 int size,
 int skip = 0,
 bool directed = true) [inline]
```

Read an edgelist.

Ids in the network are assume to range from 0 to `size - 1`.

## Parameters

<i>fn</i>	Path to the file
<i>skip</i>	Number of lines to skip (e.g., 1 if there's a header)
<i>directed</i>	<code>true</code> if the network is directed
<i>size</i>	Number of vertices in the network.

The documentation for this class was generated from the following file:

- `epiworld.hpp`

## 17.3 `Agent< TSeq >` Class Template Reference

`Agent` (agents)

```
#include <agent-bones.hpp>
```

### Public Member Functions

- **Agent** (`Agent< TSeq > &&p`)
- **Agent** (const `Agent< TSeq > &p`)
- `Agent< TSeq > & operator=` (const `Agent< TSeq > &other_agent`)
- int `get_id` () const  
*Id of the individual.*
- `VirusPtr< TSeq > & get_virus` ()
- const `VirusPtr< TSeq > & get_virus` () const
- `ToolPtr< TSeq > & get_tool` (int i)
- `Tools< TSeq > get_tools` ()
- const `Tools_const< TSeq > get_tools` () const
- size\_t `get_n_tools` () const noexcept
- void `mutate_virus` ()
- void `add_neighbor` (`Agent< TSeq > &p`, bool check\_source=true, bool check\_target=true)
- void `swap_neighbors` (`Agent< TSeq > &other`, size\_t n\_this, size\_t n\_other)  
*Swaps neighbors between the current agent and agent other*
- std::vector< `Agent< TSeq > *` > `get_neighbors` ()
- size\_t `get_n_neighbors` () const
- void `change_state` (`Model< TSeq > *model`, epiworld\_fast\_uint new\_state, epiworld\_fast\_int queue=0)
- const unsigned int & `get_state` () const
- void `reset` ()
- bool `has_tool` (epiworld\_fast\_uint t) const
- bool `has_tool` (std::string name) const
- bool `has_tool` (const `Tool< TSeq > &t`) const
- bool `has_virus` (epiworld\_fast\_uint t) const
- bool `has_virus` (std::string name) const
- bool `has_virus` (const `Virus< TSeq > &v`) const
- bool `has_entity` (epiworld\_fast\_uint t) const
- bool `has_entity` (std::string name) const
- void `print` (bool compressed=false) const
- `Entities< TSeq > get_entities` ()
- const `Entities_const< TSeq > get_entities` () const

- const [Entity](#)< TSeq > & **get\_entity** (size\_t i) const
- [Entity](#)< TSeq > & **get\_entity** (size\_t i)
- size\_t **get\_n\_entities** () const
- bool **operator==** (const [Agent](#)< TSeq > &other) const
- bool **operator!=** (const [Agent](#)< TSeq > &other) const

### Add/Remove Virus/Tool

Any of these is ultimately reflected at the end of the iteration.

#### Parameters

tool	<a href="#">Tool</a> to add
virus	<a href="#">Virus</a> to add
state_new	state after the change
queue	

- void **add\_tool** (ToolPtr< TSeq > &tool, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **add\_tool** (const [Tool](#)< TSeq > &tool, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **set\_virus** (VirusPtr< TSeq > &virus, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **set\_virus** (const [Virus](#)< TSeq > &virus, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **add\_entity** ([Entity](#)< TSeq > &entity, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_tool** (epiworld\_fast\_uint tool\_idx, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_tool** (ToolPtr< TSeq > &tool, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_virus** ([Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_entity** (epiworld\_fast\_uint entity\_idx, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_entity** ([Entity](#)< TSeq > &entity, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_agent\_by\_virus** ([Model](#)< TSeq > \*model)  
*[Agent](#) removed by virus.*

### Get the rates (multipliers) for the agent

#### Parameters

v	A pointer to a virus.
---	-----------------------

#### Returns

[epiworld\\_double](#)

- epiworld\_double **get\_susceptibility\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- epiworld\_double **get\_transmission\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- epiworld\_double **get\_recovery\_enhancer** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- epiworld\_double **get\_death\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)

- double & [operator\(\)](#) (size\_t j)  
Access the j-th column of the agent.
- double & **operator[]** (size\_t j)
- double **operator()** (size\_t j) const
- double **operator[]** (size\_t j) const

## Friends

- class **Model**< TSeq >
- class **Virus**< TSeq >
- class **Tool**< TSeq >
- class **Tools**< TSeq >
- class **Tools\_const**< TSeq >
- class **Queue**< TSeq >
- class **Entities**< TSeq >
- class **AgentsSample**< TSeq >
- void **default\_add\_virus** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_add\_tool** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_add\_entity** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_virus** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_tool** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void [default\\_rm\\_entity](#) ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_change\_state** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)

## 17.3.1 Detailed Description

```
template<typename TSeq>
class Agent< TSeq >
```

[Agent](#) (agents)

Template Parameters

<a href="#">TSeq</a>	Sequence type (should match TSeq across the model)
----------------------	----------------------------------------------------

## 17.3.2 Member Function Documentation

### 17.3.2.1 operator()()

```
template<typename TSeq >
double & Agent< TSeq >::operator() (
 size_t j) [inline]
```

Access the j-th column of the agent.

If an external array has been specified, then these two functions can be used to access additional agent's features not included in the model.

The `operator[]` method is with no boundary check, whereas the `operator()` method checks boundaries. The former can result in a segfault.

**Parameters**

<i>j</i>	
----------	--

**Returns**

double&amp;

**17.3.2.2 swap\_neighbors()**

```
template<typename TSeq >
void Agent< TSeq >::swap_neighbors (
 Agent< TSeq > & other,
 size_t n_this,
 size_t n_other) [inline]
```

Swaps neighbors between the current agent and agent *other*

**Parameters**

<i>other</i>	
<i>n_this</i>	
<i>n_other</i>	

**17.3.3 Friends And Related Function Documentation****17.3.3.1 default\_rm\_entity**

```
template<typename TSeq >
void default_rm_entity (
 Event< TSeq > & a,
 Model< TSeq > * m) [friend]
```

< Last entity of the agent

< Last agent of the entity

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/agent-meat.hpp

## 17.4 epiworld::Agent< TSeq > Class Template Reference

[Agent](#) (agents)

```
#include <epiworld.hpp>
```

### Public Member Functions

- **Agent** ([Agent](#)< TSeq > &&p)
- **Agent** (const [Agent](#)< TSeq > &p)
- [Agent](#)< TSeq > & **operator=** (const [Agent](#)< TSeq > &other\_agent)
- int **get\_id** () const  
*Id of the individual.*
- VirusPtr< TSeq > & **get\_virus** ()
- const VirusPtr< TSeq > & **get\_virus** () const
- ToolPtr< TSeq > & **get\_tool** (int i)
- [Tools](#)< TSeq > **get\_tools** ()
- const [Tools\\_const](#)< TSeq > **get\_tools** () const
- size\_t **get\_n\_tools** () const noexcept
- void **mutate\_virus** ()
- void **add\_neighbor** ([Agent](#)< TSeq > &p, bool check\_source=true, bool check\_target=true)
- void **swap\_neighbors** ([Agent](#)< TSeq > &other, size\_t n\_this, size\_t n\_other)  
*Swaps neighbors between the current agent and agent other*
- std::vector< [Agent](#)< TSeq > \* > **get\_neighbors** ()
- size\_t **get\_n\_neighbors** () const
- void **change\_state** ([Model](#)< TSeq > \*model, epiworld\_fast\_uint new\_state, epiworld\_fast\_int queue=0)
- const unsigned int & **get\_state** () const
- void **reset** ()
- bool **has\_tool** (epiworld\_fast\_uint t) const
- bool **has\_tool** (std::string name) const
- bool **has\_tool** (const [Tool](#)< TSeq > &t) const
- bool **has\_virus** (epiworld\_fast\_uint t) const
- bool **has\_virus** (std::string name) const
- bool **has\_virus** (const [Virus](#)< TSeq > &v) const
- bool **has\_entity** (epiworld\_fast\_uint t) const
- bool **has\_entity** (std::string name) const
- void **print** (bool compressed=false) const
- [Entities](#)< TSeq > **get\_entities** ()
- const [Entities\\_const](#)< TSeq > **get\_entities** () const
- const [Entity](#)< TSeq > & **get\_entity** (size\_t i) const
- [Entity](#)< TSeq > & **get\_entity** (size\_t i)
- size\_t **get\_n\_entities** () const
- bool **operator==** (const [Agent](#)< TSeq > &other) const
- bool **operator!=** (const [Agent](#)< TSeq > &other) const

### Add/Remove Virus/Tool

*Any of these is ultimately reflected at the end of the iteration.*

#### Parameters

tool	<i><a href="#">Tool</a> to add</i>
virus	<i><a href="#">Virus</a> to add</i>
state_new	<i>state after the change</i>
Generated by Doxygen	

- void **add\_tool** (ToolPtr< TSeq > &tool, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **add\_tool** (const [Tool](#)< TSeq > &tool, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **set\_virus** (VirusPtr< TSeq > &virus, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **set\_virus** (const [Virus](#)< TSeq > &virus, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **add\_entity** ([Entity](#)< TSeq > &entity, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_tool** (epiworld\_fast\_uint tool\_idx, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_tool** (ToolPtr< TSeq > &tool, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_virus** ([Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_entity** (epiworld\_fast\_uint entity\_idx, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_entity** ([Entity](#)< TSeq > &entity, [Model](#)< TSeq > \*model, epiworld\_fast\_int state\_new=-99, epiworld\_fast\_int queue=-99)
- void **rm\_agent\_by\_virus** ([Model](#)< TSeq > \*model)  
*[Agent](#) removed by virus.*

### Get the rates (multipliers) for the agent

#### Parameters

v	A pointer to a virus.
---	-----------------------

#### Returns

*epiworld\_double*

- epiworld\_double **get\_susceptibility\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- epiworld\_double **get\_transmission\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- epiworld\_double **get\_recovery\_enhancer** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- epiworld\_double **get\_death\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)

- double & **operator()** (size\_t j)

*Access the j-th column of the agent.*

- double & **operator[]** (size\_t j)
- double **operator()** (size\_t j) const
- double **operator[]** (size\_t j) const

### Friends

- class **Model**< TSeq >
- class **Virus**< TSeq >
- class **Tool**< TSeq >
- class **Tools**< TSeq >
- class **Tools\_const**< TSeq >
- class **Queue**< TSeq >
- class **Entities**< TSeq >
- class **AgentsSample**< TSeq >



- void **default\_add\_virus** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_add\_tool** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_add\_entity** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_virus** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_tool** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_entity** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_change\_state** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)

### 17.4.1 Detailed Description

```
template<typename TSeq>
class epiworld::Agent< TSeq >
```

[Agent](#) (agents)

Template Parameters

<i>TSeq</i>	Sequence type (should match TSeq across the model)
-------------	----------------------------------------------------

### 17.4.2 Member Function Documentation

#### 17.4.2.1 operator()()

```
template<typename TSeq >
double & Agent< TSeq >::operator() (
 size_t j) [inline]
```

Access the j-th column of the agent.

If an external array has been specified, then these two functions can be used to access additional agent's features not included in the model.

The `operator[]` method is with no boundary check, whereas the `operator()` method checks boundaries. The former can result in a segfault.

Parameters

<i>j</i>	
----------	--

Returns

double&

### 17.4.2.2 swap\_neighbors()

```
template<typename TSeq >
void Agent< TSeq >::swap_neighbors (
 Agent< TSeq > & other,
 size_t n_this,
 size_t n_other) [inline]
```

Swaps neighbors between the current agent and agent `other`

#### Parameters

<i>other</i>	
<i>n_this</i>	
<i>n_other</i>	

## 17.4.3 Friends And Related Function Documentation

### 17.4.3.1 default\_rm\_entity

```
template<typename TSeq >
void default_rm_entity (
 Event< TSeq > & a,
 Model< TSeq > * m) [friend]
```

< Last entity of the agent

< Last agent of the entity

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.5 AgentsSample< TSeq > Class Template Reference

Sample of agents.

```
#include <agentssample-bones.hpp>
```

## Public Member Functions

- [AgentsSample](#) ()=delete  
*Default constructor.*
- [AgentsSample](#) (const [AgentsSample](#)< TSeq > &a)=delete  
*Copy constructor.*
- [AgentsSample](#) ([AgentsSample](#)< TSeq > &&a)=delete  
*Move constructor.*
- **AgentsSample** ([Model](#)< TSeq > &model\_, size\_t n, std::vector< size\_t > states\_={}, bool truncate=false)
- **AgentsSample** ([Model](#)< TSeq > \*model, [Entity](#)< TSeq > &entity\_, size\_t n, std::vector< size\_t > states\_←\_={}, bool truncate=false)
- [AgentsSample](#) ([Model](#)< TSeq > \*model, [Agent](#)< TSeq > &agent\_, size\_t n, std::vector< size\_t > states\_←\_={}, bool truncate=false)  
*Sample from the agent's entities.*
- std::vector< [Agent](#)< TSeq > \* >::iterator **begin** ()
- std::vector< [Agent](#)< TSeq > \* >::iterator **end** ()
- [Agent](#)< TSeq > \* **operator[]** (size\_t n)
- [Agent](#)< TSeq > \* **operator()** (size\_t n)
- size\_t **size** () const noexcept

### 17.5.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class AgentsSample< TSeq >
```

Sample of agents.

This class allows sampling agents from Entity<TSeq> and Model<TSeq>.

Template Parameters

<i>TSeq</i>	
-------------	--

### 17.5.2 Constructor & Destructor Documentation

#### 17.5.2.1 AgentsSample()

```
template<typename TSeq >
AgentsSample< TSeq >::AgentsSample (
 Model< TSeq > * model,
 Agent< TSeq > & agent_,
 size_t n,
 std::vector< size_t > states_ = {},
 bool truncate = false) [inline]
```

Sample from the agent's entities.

For example, how many individuals the agent contacts in a given point in time.

## Template Parameters

<i>TSeq</i>	
-------------	--

## Parameters

<i>agent</i> ↔	
—	
<i>n</i>	Sample size
<i>truncate</i>	If the agent has fewer than <i>n</i> connections, then <i>truncate</i> = true will automatically reduce the number of possible samples. Otherwise, if false, then it returns an error.

The documentation for this class was generated from the following file:

- include/epiworld/agentssample-bones.hpp

## 17.6 epiworld::AgentsSample< TSeq > Class Template Reference

Sample of agents.

```
#include <epiworld.hpp>
```

### Public Member Functions

- [AgentsSample](#) ()=delete  
*Default constructor.*
- [AgentsSample](#) (const [AgentsSample](#)< TSeq > &a)=delete  
*Copy constructor.*
- [AgentsSample](#) ([AgentsSample](#)< TSeq > &&a)=delete  
*Move constructor.*
- [AgentsSample](#) ([Model](#)< TSeq > &model\_, size\_t n, std::vector< size\_t > states\_={}, bool truncate=false)
- [AgentsSample](#) ([Model](#)< TSeq > \*model, [Entity](#)< TSeq > &entity\_, size\_t n, std::vector< size\_t > states\_↔\_={}, bool truncate=false)
- [AgentsSample](#) ([Model](#)< TSeq > \*model, [Agent](#)< TSeq > &agent\_, size\_t n, std::vector< size\_t > states\_↔\_={}, bool truncate=false)  
*Sample from the agent's entities.*
- std::vector< [Agent](#)< TSeq > \* >::iterator **begin** ()
- std::vector< [Agent](#)< TSeq > \* >::iterator **end** ()
- [Agent](#)< TSeq > \* **operator[]** (size\_t n)
- [Agent](#)< TSeq > \* **operator()** (size\_t n)
- size\_t **size** () const noexcept

### 17.6.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::AgentsSample< TSeq >
```

Sample of agents.

This class allows sampling agents from [Entity](#)<TSeq> and [Model](#)<TSeq>.

## Template Parameters

<i>TSeq</i>	
-------------	--

## 17.6.2 Constructor & Destructor Documentation

### 17.6.2.1 AgentsSample()

```
template<typename TSeq >
AgentsSample< TSeq >::AgentsSample (
 Model< TSeq > * model,
 Agent< TSeq > & agent_,
 size_t n,
 std::vector< size_t > states_ = {},
 bool truncate = false) [inline]
```

Sample from the agent's entities.

For example, how many individuals the agent contacts in a given point in time.

## Template Parameters

<i>TSeq</i>	
-------------	--

## Parameters

<i>agent</i> ↔	
<i>n</i>	Sample size
<i>truncate</i>	If the agent has fewer than <i>n</i> connections, then <i>truncate</i> = true will automatically reduce the number of possible samples. Otherwise, if false, then it returns an error.

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.7 ContactTracing Class Reference

Class for tracing contacts between agents.

```
#include <contacttracing-bones.hpp>
```

## Public Member Functions

- [ContactTracing](#) (size\_t n\_agents, size\_t max\_contacts)  
*Construct a new Contact Tracing object.*
- void [add\\_contact](#) (size\_t agent\_a, size\_t agent\_b, size\_t day)  
*Add a contact between two agents at a given day.*
- size\_t [get\\_n\\_contacts](#) (size\_t agent)  
*Get the number of contacts for an agent.*
- std::pair< size\_t, size\_t > [get\\_contact](#) (size\_t agent, size\_t idx)  
*Get the contact object.*
- void [reset](#) (size\_t n\_agents, size\_t max\_contacts)  
*Reset the contact tracing data.*
- void [print](#) (size\_t agent)  
*Print the contacts of an agent.*

### 17.7.1 Detailed Description

Class for tracing contacts between agents.

The class assumes that contacts are stored in a matrix-like structure, where rows are agents and columns are contacts in a column-major format. Each entry stores the id of the contact and the day of the contact is stored in a parallel array.

The maximum number of contacts per agent is fixed at initialization time. If more contacts are added, they will overwrite previous contacts in a circular buffer fashion.

### 17.7.2 Constructor & Destructor Documentation

#### 17.7.2.1 ContactTracing()

```
ContactTracing::ContactTracing (
 size_t n_agents,
 size_t max_contacts) [inline]
```

Construct a new Contact Tracing object.

#### Parameters

<i>n_agents</i>	Agents in the system, usually <code>Model&lt;TSeq&gt;::size()</code> .
<i>max_contacts</i>	Maximum number of contacts to track per agent.

### 17.7.3 Member Function Documentation

### 17.7.3.1 add\_contact()

```
void ContactTracing::add_contact (
 size_t agent_a,
 size_t agent_b,
 size_t day) [inline]
```

Add a contact between two agents at a given day.

#### Parameters

<i>agent</i> ↔ <i>_a</i>	Agent id (usually infectious agent)
<i>agent</i> ↔ <i>_b</i>	Agent id (usually susceptible agent)
<i>day</i>	Day of the contact (usually <code>Model&lt;TSeq&gt;::today()</code> ).

### 17.7.3.2 get\_contact()

```
std::pair< size_t, size_t > ContactTracing::get_contact (
 size_t agent,
 size_t idx) [inline]
```

Get the contact object.

#### Parameters

<i>agent</i>	Source agent (id)
<i>idx</i>	Index of the contact (0 to <code>get_n_contacts(agent)-1</code> )

#### Returns

`std::pair<size_t, size_t>` with (contact\_id, contact\_day)

#### Exceptions

<code>std::out_of_range</code>	if idx is out of range.
--------------------------------	-------------------------

### 17.7.3.3 get\_n\_contacts()

```
size_t ContactTracing::get_n_contacts (
 size_t agent) [inline]
```

Get the number of contacts for an agent.

**Parameters**

<i>agent</i>	<a href="#">Agent</a> id
--------------	--------------------------

**Returns**

size\_t Number of contacts recorded for that agent (can be more than max\_contacts)

**17.7.3.4 print()**

```
void ContactTracing::print (
 size_t agent) [inline]
```

Print the contacts of an agent.

**Parameters**

<i>agent</i>	<a href="#">Agent</a> id
--------------	--------------------------

**17.7.3.5 reset()**

```
void ContactTracing::reset (
 size_t n_agents,
 size_t max_contacts) [inline]
```

Reset the contact tracing data.

Usually called by [Model<TSeq>::reset\(\)](#).

**Parameters**

<i>n_agents</i>	Number of agents
<i>max_contacts</i>	Maximum number of contacts to track per agent

The documentation for this class was generated from the following file:

- include/epiworld/contacttracing-bones.hpp

**17.8 epiworld::ContactTracing Class Reference**

Class for tracing contacts between agents.

```
#include <epiworld.hpp>
```



## Public Member Functions

- [ContactTracing](#) (size\_t n\_agents, size\_t max\_contacts)  
*Construct a new Contact Tracing object.*
- void [add\\_contact](#) (size\_t agent\_a, size\_t agent\_b, size\_t day)  
*Add a contact between two agents at a given day.*
- size\_t [get\\_n\\_contacts](#) (size\_t agent)  
*Get the number of contacts for an agent.*
- std::pair< size\_t, size\_t > [get\\_contact](#) (size\_t agent, size\_t idx)  
*Get the contact object.*
- void [reset](#) (size\_t n\_agents, size\_t max\_contacts)  
*Reset the contact tracing data.*
- void [print](#) (size\_t agent)  
*Print the contacts of an agent.*

### 17.8.1 Detailed Description

Class for tracing contacts between agents.

The class assumes that contacts are stored in a matrix-like structure, where rows are agents and columns are contacts in a column-major format. Each entry stores the id of the contact and the day of the contact is stored in a parallel array.

The maximum number of contacts per agent is fixed at initialization time. If more contacts are added, they will overwrite previous contacts in a circular buffer fashion.

### 17.8.2 Constructor & Destructor Documentation

#### 17.8.2.1 ContactTracing()

```
ContactTracing::ContactTracing (
 size_t n_agents,
 size_t max_contacts) [inline]
```

Construct a new Contact Tracing object.

#### Parameters

<i>n_agents</i>	Agents in the system, usually <code>Model&lt;TSeq&gt;::size()</code> .
<i>max_contacts</i>	Maximum number of contacts to track per agent.

### 17.8.3 Member Function Documentation

### 17.8.3.1 add\_contact()

```
void ContactTracing::add_contact (
 size_t agent_a,
 size_t agent_b,
 size_t day) [inline]
```

Add a contact between two agents at a given day.

#### Parameters

<i>agent</i> ↔ <i>_a</i>	Agent id (usually infectious agent)
<i>agent</i> ↔ <i>_b</i>	Agent id (usually susceptible agent)
<i>day</i>	Day of the contact (usually <code>Model&lt;TSeq&gt;::today()</code> ).

### 17.8.3.2 get\_contact()

```
std::pair< size_t, size_t > ContactTracing::get_contact (
 size_t agent,
 size_t idx) [inline]
```

Get the contact object.

#### Parameters

<i>agent</i>	Source agent (id)
<i>idx</i>	Index of the contact (0 to <code>get_n_contacts(agent)-1</code> )

#### Returns

`std::pair<size_t, size_t>` with (contact\_id, contact\_day)

#### Exceptions

<code>std::out_of_range</code>	if idx is out of range.
--------------------------------	-------------------------

### 17.8.3.3 get\_n\_contacts()

```
size_t ContactTracing::get_n_contacts (
 size_t agent) [inline]
```

Get the number of contacts for an agent.

## Parameters

<i>agent</i>	<a href="#">Agent</a> id
--------------	--------------------------

## Returns

size\_t Number of contacts recorded for that agent (can be more than max\_contacts)

**17.8.3.4 print()**

```
void ContactTracing::print (
 size_t agent) [inline]
```

Print the contacts of an agent.

## Parameters

<i>agent</i>	<a href="#">Agent</a> id
--------------	--------------------------

**17.8.3.5 reset()**

```
void ContactTracing::reset (
 size_t n_agents,
 size_t max_contacts) [inline]
```

Reset the contact tracing data.

Usually called by [Model<TSeq>::reset\(\)](#).

## Parameters

<i>n_agents</i>	Number of agents
<i>max_contacts</i>	Maximum number of contacts to track per agent

The documentation for this class was generated from the following file:

- [epiworld.hpp](#)

**17.9 DataBase< TSeq > Class Template Reference**

Statistical data about the process.

```
#include <database-bones.hpp>
```

## Public Member Functions

- **DataBase** ([Model](#)< TSeq > &m)
- **DataBase** (const [DataBase](#)< TSeq > &db)
- void [record\\_virus](#) ([Virus](#)< TSeq > &v)
  - Registering a new variant.*
- void [record\\_tool](#) ([Tool](#)< TSeq > &t)
- void [set\\_seq\\_hasher](#) (std::function< std::vector< int >(TSeq)> fun)
- void [reset](#) ()
- [Model](#)< TSeq > \* [get\\_model](#) ()
- void [record](#) ()
- const std::vector< TSeq > & [get\\_sequence](#) () const
- const std::vector< int > & [get\\_nexposed](#) () const
- size\_t [size](#) () const
- void [write\\_data](#) (std::string fn\_virus\_info, std::string fn\_virus\_hist, std::string fn\_tool\_info, std::string fn\_tool\_hist, std::string fn\_total\_hist, std::string fn\_transmission, std::string fn\_transition, std::string fn\_reproductive\_number, std::string fn\_generation\_time) const
- void [record\\_transmission](#) (int i, int j, int virus, int i\_expo\_date)
- size\_t [get\\_n\\_viruses](#) () const
  - Get the number of viruses.*
- size\_t [get\\_n\\_tools](#) () const
  - Get the number of tools.*
- void [set\\_user\\_data](#) (std::vector< std::string > names)
- void [add\\_user\\_data](#) (std::vector< epiworld\_double > x)
- void [add\\_user\\_data](#) (epiworld\_fast\_uint j, epiworld\_double x)
- [UserData](#)< TSeq > & [get\\_user\\_data](#) ()
- std::vector< epiworld\_double > [get\\_transition\\_probability](#) (bool print=true, bool normalize=true) const
  - Calculates the transition probabilities.*
- bool [operator==](#) (const [DataBase](#)< TSeq > &other) const
- bool [operator!=](#) (const [DataBase](#)< TSeq > &other) const
- bool [operator==](#) (const [DataBase](#)< std::vector< int >> &other) const
- bool [operator==](#) (const [DataBase](#)< std::vector< int >> &other) const

### Get recorded information from the model

#### Parameters

what	<i>std::string, The state, e.g., 0, 1, 2, ...</i>
------	---------------------------------------------------

#### Returns

*In [get\\_today\\_total](#), the current counts of what.*

*In [get\\_today\\_virus](#), the current counts of what for each virus.*

*In [get\\_hist\\_total](#), the time series of what*

*In [get\\_hist\\_virus](#), the time series of what for each virus.*

*In [get\\_hist\\_total\\_date](#) and [get\\_hist\\_virus\\_date](#) the corresponding date*

- int [get\\_today\\_total](#) (const std::string &what) const
- int [get\\_today\\_total](#) (const epiworld\_fast\_uint &what) const
- void [get\\_today\\_total](#) (std::vector< std::string > \*state=nullptr, std::vector< int > \*counts=nullptr) const
- void [get\\_today\\_virus](#) (std::vector< std::string > &state, std::vector< int > &id, std::vector< int > &counts) const
- void [get\\_today\\_transition\\_matrix](#) (std::vector< int > &counts) const
- void [get\\_hist\\_total](#) (std::vector< int > \*date, std::vector< std::string > \*state, std::vector< int > \*counts) const

- void **get\_hist\_virus** (std::vector< int > &date, std::vector< int > &id, std::vector< std::string > &state, std::vector< int > &counts) const
  - void **get\_hist\_tool** (std::vector< int > &date, std::vector< int > &id, std::vector< std::string > &state, std::vector< int > &counts) const
  - void **get\_hist\_transition\_matrix** (std::vector< std::string > &state\_from, std::vector< std::string > &state\_to, std::vector< int > &date, std::vector< int > &counts, bool skip\_zeros) const
- 
- void **get\_transmissions** (std::vector< int > &date, std::vector< int > &source, std::vector< int > &target, std::vector< int > &virus, std::vector< int > &source\_exposure\_date) const  
*Get the transmissions object.*
  - void **get\_transmissions** (int \*date, int \*source, int \*target, int \*virus, int \*source\_exposure\_date) const
- 
- MapVec\_type< int, int > **get\_reproductive\_number** () const  
*Computes the reproductive number of each case.*
  - void **get\_reproductive\_number** (std::string fn) const
- 
- void **get\_generation\_time** (std::vector< int > &agent\_id, std::vector< int > &virus\_id, std::vector< int > &time, std::vector< int > &gentime) const  
*Get the generation time.*
  - void **get\_generation\_time** (std::string fn) const  
*Write the generation time to a file.*

## Friends

- class **Model**< TSeq >
- void **default\_add\_virus** (Event< TSeq > &a, Model< TSeq > \*m)
- void **default\_add\_tool** (Event< TSeq > &a, Model< TSeq > \*m)
- void **default\_rm\_virus** (Event< TSeq > &a, Model< TSeq > \*m)
- void **default\_rm\_tool** (Event< TSeq > &a, Model< TSeq > \*m)
- void **default\_change\_state** (Event< TSeq > &a, Model< TSeq > \*m)

### 17.9.1 Detailed Description

```
template<typename TSeq>
class DataBase< TSeq >
```

Statistical data about the process.

#### Template Parameters

<i>TSeq</i>	
-------------	--

## 17.9.2 Member Function Documentation

### 17.9.2.1 `get_generation_time()`

```
template<typename TSeq >
void DataBase< TSeq >::get_generation_time (
 std::vector< int > & agent_id,
 std::vector< int > & virus_id,
 std::vector< int > & time,
 std::vector< int > & gentime) const [inline]
```

Get the generation time.

Calculates the generating time

#### Parameters

<i>agent_id, virus_id, time, gentime</i>	vectors where to save the values
------------------------------------------	----------------------------------

The generation time is the time between the infection of the source and the infection of the target.

### 17.9.2.2 `get_reproductive_number()`

```
template<typename TSeq >
MapVec_type< int, int > DataBase< TSeq >::get_reproductive_number [inline]
```

Computes the reproductive number of each case.

By definition, whereas it computes R0 (basic reproductive number) or Rt/R (the effective reproductive number) will depend on whether the virus is allowed to circulate naïvely or not, respectively.

#### Parameters

<i>fn</i>	File where to write out the reproductive number.
-----------	--------------------------------------------------

In the case of `MapVec_type<int, int>`, the key is a vector of 3 integers:

- **Virus** id
- Source id
- Date when the source was infected

### 17.9.2.3 get\_transition\_probability()

```
template<typename TSeq >
std::vector< epiworld_double > DataBase< TSeq >::get_transition_probability (
 bool print = true,
 bool normalize = true) const [inline]
```

Calculates the transition probabilities.

#### Parameters

<i>print</i>	Print the transition matrix.
<i>normalize</i>	Normalize the transition matrix. Otherwise, it returns raw counts.

The transition matrix is the matrix of the counts of transitions from one state to another. So the ij-th element of the matrix is the number of transitions from state i to state j (when not normalized), or the probability of transitioning from state i to state j (when normalized).

#### Returns

std::vector< epiworld\_double >

### 17.9.2.4 get\_transmissions()

```
template<typename TSeq >
void DataBase< TSeq >::get_transmissions (
 std::vector< int > & date,
 std::vector< int > & source,
 std::vector< int > & target,
 std::vector< int > & virus,
 std::vector< int > & source_exposure_date) const [inline]
```

Get the transmissions object.

#### Parameters

<i>date</i>	
<i>source</i>	
<i>target</i>	
<i>virus</i>	
<i>source_exposure_date</i>	

### 17.9.2.5 operator==( ) [1/3]

```
bool DataBase< std::vector< int > >::operator== (
 const DataBase< std::vector< int >> & other) const [inline]
```

< Date of the transmission eve,

< Id of the sour,

< Id of the targ,

< Id of the varia,

< Date when the source acquired the varia,

#### 17.9.2.6 operator==( ) [2/3]

```
bool DataBase< std::vector< int > >::operator== (
 const DataBase< std::vector< int >> & other) const [inline]
```

< Date of the transmission eve,

< Id of the sour,

< Id of the targ,

< Id of the varia,

< Date when the source acquired the varia,

#### 17.9.2.7 operator==( ) [3/3]

```
template<typename TSeq >
bool DataBase< TSeq >::operator== (
 const DataBase< TSeq > & other) const [inline]
```

< Date of the transmission eve

< Id of the sour

< Id of the targ

< Id of the varia

< Date when the source acquired the varia

#### 17.9.2.8 record\_virus()

```
template<typename TSeq >
void DataBase< TSeq >::record_virus (
 Virus< TSeq > & v) [inline]
```

Registering a new variant.



## Parameters

v	Pointer to the new virus. Since viruses are originated in the agent, the numbers simply move around. From the parent virus to the new virus. And the total number of infected does not change.
---	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

The documentation for this class was generated from the following files:

- include/epiworld/database-bones.hpp
- include/epiworld/database-meat.hpp

## 17.10 epiworld::DataBase< TSeq > Class Template Reference

Statistical data about the process.

```
#include <epiworld.hpp>
```

### Public Member Functions

- **DataBase** ([Model](#)< TSeq > &m)
- **DataBase** (const [DataBase](#)< TSeq > &db)
- void **record\_virus** ([Virus](#)< TSeq > &v)  
*Registering a new variant.*
- void **record\_tool** ([Tool](#)< TSeq > &t)
- void **set\_seq\_hasher** (std::function< std::vector< int >(TSeq)> fun)
- void **reset** ()
- [Model](#)< TSeq > \* **get\_model** ()
- void **record** ()
- const std::vector< TSeq > & **get\_sequence** () const
- const std::vector< int > & **get\_nexposed** () const
- [size\\_t](#) **size** () const
- void **write\_data** (std::string fn\_virus\_info, std::string fn\_virus\_hist, std::string fn\_tool\_info, std::string fn\_tool\_hist, std::string fn\_total\_hist, std::string fn\_transmission, std::string fn\_transition, std::string fn\_reproductive\_number, std::string fn\_generation\_time) const
- void **record\_transmission** (int i, int j, int virus, int i\_expo\_date)
- [size\\_t](#) **get\_n\_viruses** () const  
*Get the number of viruses.*
- [size\\_t](#) **get\_n\_tools** () const  
*Get the number of tools.*
- void **set\_user\_data** (std::vector< std::string > names)
- void **add\_user\_data** (std::vector< [epiworld\\_double](#) > x)
- void **add\_user\_data** ([epiworld\\_fast\\_uint](#) j, [epiworld\\_double](#) x)
- [UserData](#)< TSeq > & **get\_user\_data** ()
- std::vector< [epiworld\\_double](#) > **get\_transition\_probability** (bool print=true, bool normalize=true) const  
*Calculates the transition probabilities.*
- bool **operator==** (const [DataBase](#)< TSeq > &other) const
- bool **operator!=** (const [DataBase](#)< TSeq > &other) const

**Get recorded information from the model**

### Parameters

what	<i>std::string, The state, e.g., 0, 1, 2, ...</i>
------	---------------------------------------------------

### Returns

*In `get_today_total`, the current counts of what.*

*In `get_today_virus`, the current counts of what for each virus.*

*In `get_hist_total`, the time series of what*

*In `get_hist_virus`, the time series of what for each virus.*

*In `get_hist_total_date` and `get_hist_virus_date` the corresponding date*

- int **get\_today\_total** (const std::string &what) const
  - int **get\_today\_total** (const epiworld\_fast\_uint &what) const
  - void **get\_today\_total** (std::vector< std::string > \*state=nullptr, std::vector< int > \*counts=nullptr) const
  - void **get\_today\_virus** (std::vector< std::string > &state, std::vector< int > &id, std::vector< int > &counts) const
  - void **get\_today\_transition\_matrix** (std::vector< int > &counts) const
  - void **get\_hist\_total** (std::vector< int > \*date, std::vector< std::string > \*state, std::vector< int > \*counts) const
  - void **get\_hist\_virus** (std::vector< int > &date, std::vector< int > &id, std::vector< std::string > &state, std::vector< int > &counts) const
  - void **get\_hist\_tool** (std::vector< int > &date, std::vector< int > &id, std::vector< std::string > &state, std::vector< int > &counts) const
  - void **get\_hist\_transition\_matrix** (std::vector< std::string > &state\_from, std::vector< std::string > &state\_to, std::vector< int > &date, std::vector< int > &counts, bool skip\_zeros) const
- 
- void **get\_transmissions** (std::vector< int > &date, std::vector< int > &source, std::vector< int > &target, std::vector< int > &virus, std::vector< int > &source\_exposure\_date) const  
*Get the transmissions object.*
  - void **get\_transmissions** (int \*date, int \*source, int \*target, int \*virus, int \*source\_exposure\_date) const
- 
- MapVec\_type< int, int > **get\_reproductive\_number** () const  
*Computes the reproductive number of each case.*
  - void **get\_reproductive\_number** (std::string fn) const
- 
- void **get\_generation\_time** (std::vector< int > &agent\_id, std::vector< int > &virus\_id, std::vector< int > &time, std::vector< int > &gentime) const  
*Get the generation time.*
  - void **get\_generation\_time** (std::string fn) const  
*Write the generation time to a file.*

## Friends

- class **Model**< TSeq >
- void **default\_add\_virus** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_add\_tool** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_virus** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_tool** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_change\_state** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)

## 17.10.1 Detailed Description

```
template<typename TSeq>
class epiworld::DataBase< TSeq >
```

Statistical data about the process.

### Template Parameters

<i>TSeq</i>	
-------------	--

## 17.10.2 Member Function Documentation

### 17.10.2.1 `get_generation_time()`

```
template<typename TSeq >
void DataBase< TSeq >::get_generation_time (
 std::vector< int > & agent_id,
 std::vector< int > & virus_id,
 std::vector< int > & time,
 std::vector< int > & gentime) const [inline]
```

Get the generation time.

Calculates the generating time

### Parameters

<i>agent_id, virus_id, time, gentime</i>	vectors where to save the values
------------------------------------------	----------------------------------

The generation time is the time between the infection of the source and the infection of the target.

### 17.10.2.2 `get_reproductive_number()`

```
template<typename TSeq >
MapVec_type< int, int > DataBase< TSeq >::get_reproductive_number [inline]
```

Computes the reproductive number of each case.

By definition, whereas it computes  $R_0$  (basic reproductive number) or  $R_t/R$  (the effective reproductive number) will depend on whether the virus is allowed to circulate naïvely or not, respectively.

#### Parameters

<i>fn</i>	File where to write out the reproductive number.
-----------	--------------------------------------------------

In the case of `MapVec_type<int, int>`, the key is a vector of 3 integers:

- [Virus](#) id
- Source id
- Date when the source was infected

#### 17.10.2.3 `get_transition_probability()`

```
template<typename TSeq >
std::vector< epiworld_double > DataBase< TSeq >::get_transition_probability (
 bool print = true,
 bool normalize = true) const [inline]
```

Calculates the transition probabilities.

#### Parameters

<i>print</i>	Print the transition matrix.
<i>normalize</i>	Normalize the transition matrix. Otherwise, it returns raw counts.

The transition matrix is the matrix of the counts of transitions from one state to another. So the  $ij$ -th element of the matrix is the number of transitions from state  $i$  to state  $j$  (when not normalized), or the probability of transitioning from state  $i$  to state  $j$  (when normalized).

#### Returns

`std::vector< epiworld_double >`

#### 17.10.2.4 `get_transmissions()`

```
template<typename TSeq >
void DataBase< TSeq >::get_transmissions (
 std::vector< int > & date,
 std::vector< int > & source,
 std::vector< int > & target,
 std::vector< int > & virus,
 std::vector< int > & source_exposure_date) const [inline]
```

Get the transmissions object.

## Parameters

<i>date</i>	
<i>source</i>	
<i>target</i>	
<i>virus</i>	
<i>source_exposure_date</i>	

**17.10.2.5 operator==()**

```
template<typename TSeq >
bool DataBase< TSeq >::operator== (
 const DataBase< TSeq > & other) const [inline]
```

&lt; Date of the transmission eve

&lt; Id of the sour

&lt; Id of the targ

&lt; Id of the varia

&lt; Date when the source acquired the varia

**17.10.2.6 record\_virus()**

```
template<typename TSeq >
void DataBase< TSeq >::record_virus (
 Virus< TSeq > & v) [inline]
```

Registering a new variant.

## Parameters

<i>v</i>	Pointer to the new virus. Since viruses are originated in the agent, the numbers simply move around. From the parent virus to the new virus. And the total number of infected does not change.
----------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

The documentation for this class was generated from the following file:

- epiworld.hpp

**17.11 Entities< TSeq > Class Template Reference**Set of [Entities](#) (useful for building iterators)

#include &lt;entities-bones.hpp&gt;

## Public Member Functions

- **Entities** ([Agent](#)< TSeq > &p)
- std::vector< [Entity](#)< TSeq > \* >::iterator **begin** ()
- std::vector< [Entity](#)< TSeq > \* >::iterator **end** ()
- [Entity](#)< TSeq > & **operator**() (size\_t i)
- [Entity](#)< TSeq > & **operator**[] (size\_t i)
- size\_t **size** () const noexcept
- bool **operator==** (const [Entities](#)< TSeq > &other) const

## Friends

- class **Entity**< TSeq >
- class **Agent**< TSeq >

### 17.11.1 Detailed Description

```
template<typename TSeq>
class Entities< TSeq >
```

Set of [Entities](#) (useful for building iterators)

#### Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/entities-bones.hpp

## 17.12 epiworld::Entities< TSeq > Class Template Reference

Set of [Entities](#) (useful for building iterators)

```
#include <epiworld.hpp>
```

## Public Member Functions

- **Entities** ([Agent](#)< TSeq > &p)
- std::vector< [Entity](#)< TSeq > \* >::iterator **begin** ()
- std::vector< [Entity](#)< TSeq > \* >::iterator **end** ()
- [Entity](#)< TSeq > & **operator**() (size\_t i)
- [Entity](#)< TSeq > & **operator**[] (size\_t i)
- size\_t **size** () const noexcept
- bool **operator==** (const [Entities](#)< TSeq > &other) const

## Friends

- class **Entity**< TSeq >
- class **Agent**< TSeq >

### 17.12.1 Detailed Description

```
template<typename TSeq>
class epiworld::Entities< TSeq >
```

Set of [Entities](#) (useful for building iterators)

Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.13 Entities\_const< TSeq > Class Template Reference

Set of [Entities](#) (const) (useful for iterators)

```
#include <entities-bones.hpp>
```

## Public Member Functions

- **Entities\_const** (const [Agent](#)< TSeq > &p)
- std::vector< [Entity](#)< TSeq > \* >::const\_iterator **begin** ()
- std::vector< [Entity](#)< TSeq > \* >::const\_iterator **end** ()
- const [Entity](#)< TSeq > & **operator()** (size\_t i)
- const [Entity](#)< TSeq > & **operator[]** (size\_t i)
- size\_t **size** () const noexcept
- bool **operator==** (const [Entities\\_const](#)< TSeq > &other) const

## Friends

- class **Virus**< TSeq >
- class **Agent**< TSeq >

### 17.13.1 Detailed Description

```
template<typename TSeq>
class Entities_const< TSeq >
```

Set of [Entities](#) (const) (useful for iterators)

## Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following file:

- include/epiworld/entities-bones.hpp

## 17.14 epiworld::Entities\_const< TSeq > Class Template Reference

Set of [Entities](#) (const) (useful for iterators)

```
#include <epiworld.hpp>
```

### Public Member Functions

- **Entities\_const** (const [Agent](#)< TSeq > &p)
- std::vector< [Entity](#)< TSeq > \* >::const\_iterator **begin** ()
- std::vector< [Entity](#)< TSeq > \* >::const\_iterator **end** ()
- const [Entity](#)< TSeq > & **operator()** (size\_t i)
- const [Entity](#)< TSeq > & **operator[]** (size\_t i)
- size\_t **size** () const noexcept
- bool **operator==** (const [Entities\\_const](#)< TSeq > &other) const

### Friends

- class **Virus**< TSeq >
- class **Agent**< TSeq >

#### 17.14.1 Detailed Description

```
template<typename TSeq>
class epiworld::Entities_const< TSeq >
```

Set of [Entities](#) (const) (useful for iterators)

## Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following file:

- epiworld.hpp



## 17.15 Entity< TSeq > Class Template Reference

### Public Member Functions

- [Entity](#) (std::string name, EntityToAgentFun< TSeq > fun=nullptr)  
Constructs an [Entity](#) object.
- void **add\_agent** ([Agent](#)< TSeq > &p, [Model](#)< TSeq > \*model)
- void **add\_agent** ([Agent](#)< TSeq > \*p, [Model](#)< TSeq > \*model)
- void **rm\_agent** (size\_t idx, [Model](#)< TSeq > \*model)
- size\_t **size** () const noexcept
- void **set\_location** (std::vector< epiworld\_double > loc)
- std::vector< epiworld\_double > & **get\_location** ()
- std::vector< size\_t >::iterator **begin** ()
- std::vector< size\_t >::iterator **end** ()
- std::vector< size\_t >::const\_iterator **begin** () const
- std::vector< size\_t >::const\_iterator **end** () const
- size\_t **operator[]** (size\_t i)
- int **get\_id** () const noexcept
- const std::string & **get\_name** () const noexcept
- void **set\_state** (epiworld\_fast\_int init, epiworld\_fast\_int post)
- void **set\_queue** (epiworld\_fast\_int init, epiworld\_fast\_int post)
- void **get\_state** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*post)
- void **get\_queue** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*post)
- void **reset** ()
- bool **operator==** (const [Entity](#)< TSeq > &other) const
- bool **operator!=** (const [Entity](#)< TSeq > &other) const

### Entity distribution

*These functions are used for distributing agents among entities. The idea is to have a flexible way of distributing agents among entities.*

- void **distribute** ([Model](#)< TSeq > \*model)
- std::vector< size\_t > & **get\_agents** ()
- void **print** () const
- void **set\_distribution** (EntityToAgentFun< TSeq > fun)

### Friends

- class **Agent**< TSeq >
- class **AgentsSample**< TSeq >
- class **Model**< TSeq >
- void **default\_add\_entity** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_entity** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)

## 17.15.1 Constructor & Destructor Documentation

### 17.15.1.1 Entity()

```
template<typename TSeq >
Entity< TSeq >::Entity (
 std::string name,
 EntityToAgentFun< TSeq > fun = nullptr) [inline]
```

Constructs an [Entity](#) object.

This constructor initializes an [Entity](#) object with the specified parameters.

## Parameters

<i>name</i>	The name of the entity.
<i>fun</i>	A function pointer to a function that maps the entity to an agent.

## 17.15.2 Friends And Related Function Documentation

### 17.15.2.1 default\_rm\_entity

```
template<typename TSeq >
void default_rm_entity (
 Event< TSeq > & a,
 Model< TSeq > * m) [friend]
```

< Last entity of the agent

< Last agent of the entity

< Last entity of the agent

< Last agent of the entity

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/entity-bones.hpp
- include/epiworld/entity-meat.hpp

## 17.16 epiworld::Entity< TSeq > Class Template Reference

### Public Member Functions

- [Entity](#) (std::string name, EntityToAgentFun< TSeq > fun=nullptr)  
*Constructs an [Entity](#) object.*
- void **add\_agent** ([Agent](#)< TSeq > &p, [Model](#)< TSeq > \*model)
- void **add\_agent** ([Agent](#)< TSeq > \*p, [Model](#)< TSeq > \*model)
- void **rm\_agent** (size\_t idx, [Model](#)< TSeq > \*model)
- size\_t **size** () const noexcept
- void **set\_location** (std::vector< epiworld\_double > loc)
- std::vector< epiworld\_double > & **get\_location** ()
- std::vector< size\_t >::iterator **begin** ()
- std::vector< size\_t >::iterator **end** ()
- std::vector< size\_t >::const\_iterator **begin** () const
- std::vector< size\_t >::const\_iterator **end** () const
- size\_t **operator[]** (size\_t i)
- int **get\_id** () const noexcept
- const std::string & **get\_name** () const noexcept

- void **set\_state** (epiworld\_fast\_int init, epiworld\_fast\_int post)
- void **set\_queue** (epiworld\_fast\_int init, epiworld\_fast\_int post)
- void **get\_state** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*post)
- void **get\_queue** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*post)
- void **reset** ()
- bool **operator==** (const Entity< TSeq > &other) const
- bool **operator!=** (const Entity< TSeq > &other) const

### Entity distribution

*These functions are used for distributing agents among entities. The idea is to have a flexible way of distributing agents among entities.*

- void **distribute** (Model< TSeq > \*model)
- std::vector< size\_t > & **get\_agents** ()
- void **print** () const
- void **set\_distribution** (EntityToAgentFun< TSeq > fun)

## Friends

- class **Agent**< TSeq >
- class **AgentsSample**< TSeq >
- class **Model**< TSeq >
- void **default\_add\_entity** (Event< TSeq > &a, Model< TSeq > \*m)
- void **default\_rm\_entity** (Event< TSeq > &a, Model< TSeq > \*m)

## 17.16.1 Constructor & Destructor Documentation

### 17.16.1.1 Entity()

```
template<typename TSeq >
epiworld::Entity< TSeq >::Entity (
 std::string name,
 EntityToAgentFun< TSeq > fun = nullptr) [inline]
```

Constructs an Entity object.

This constructor initializes an Entity object with the specified parameters.

#### Parameters

<i>name</i>	The name of the entity.
<i>fun</i>	A function pointer to a function that maps the entity to an agent.

## 17.16.2 Friends And Related Function Documentation

### 17.16.2.1 default\_rm\_entity

```
template<typename TSeq >
void default_rm_entity (
 Event< TSeq > & a,
 Model< TSeq > * m) [friend]
```

< Last entity of the agent

< Last agent of the entity

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.17 epiworld::Event< TSeq > Struct Template Reference

Event data for update an agent.

```
#include <epiworld.hpp>
```

### Public Member Functions

- **Event** (**Agent**< TSeq > \*agent\_, VirusPtr< TSeq > &virus\_, ToolPtr< TSeq > &tool\_, **Entity**< TSeq > \*entity\_, epiworld\_fast\_int new\_state\_, epiworld\_fast\_int queue\_, EventFun< TSeq > &call\_, int idx\_agent\_, int idx\_object\_)↵

*Construct a new Event object.*

### Public Attributes

- **Agent**< TSeq > \* **agent**
- VirusPtr< TSeq > **virus**
- ToolPtr< TSeq > **tool**
- **Entity**< TSeq > \* **entity**
- epiworld\_fast\_int **new\_state**
- epiworld\_fast\_int **queue**
- EventFun< TSeq > **call**
- int **idx\_agent**
- int **idx\_object**

### 17.17.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
struct epiworld::Event< TSeq >
```

Event data for update an agent.

## Template Parameters

<i>TSeq</i>	
-------------	--

## 17.17.2 Constructor &amp; Destructor Documentation

## 17.17.2.1 Event()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
epiworld::Event< TSeq >::Event (
 Agent< TSeq > * agent_,
 VirusPtr< TSeq > & virus_,
 ToolPtr< TSeq > & tool_,
 Entity< TSeq > * entity_,
 epiworld_fast_int new_state_,
 epiworld_fast_int queue_,
 EventFun< TSeq > & call_,
 int idx_agent_,
 int idx_object_) [inline]
```

Construct a new [Event](#) object.

All the parameters are rather optional.

## Parameters

<i>agent_</i>	<a href="#">Agent</a> over who the action will happen
<i>virus_</i>	<a href="#">Virus</a> to add
<i>tool_</i>	<a href="#">Tool</a> to add
<i>virus_idx</i>	Index of virus to be removed (if needed)
<i>tool_idx</i>	Index of tool to be removed (if needed)
<i>new_↔ state_</i>	Next state
<i>queue_</i>	Effect on the queue
<i>call_</i>	The action call (if needed)
<i>idx_↔ agent_</i>	Location of agent in object.
<i>idx_↔ object_</i>	Location of object in agent.

The documentation for this struct was generated from the following file:


- epiworld.hpp

## 17.18 Event&lt; TSeq &gt; Struct Template Reference

[Event](#) data for update an agent.

```
#include <config.hpp>
```

Collaboration diagram for Event< TSeq >:



## Public Member Functions

- [Event](#) ([Agent](#)< TSeq > \*agent\_, VirusPtr< TSeq > &virus\_, ToolPtr< TSeq > &tool\_, [Entity](#)< TSeq > \*entity\_, epiworld\_fast\_int new\_state\_, epiworld\_fast\_int queue\_, EventFun< TSeq > &call\_, int idx\_agent←\_, int idx\_object\_)

Construct a new [Event](#) object.

## Public Attributes

- [Agent](#)< TSeq > \* **agent**
- VirusPtr< TSeq > **virus**
- ToolPtr< TSeq > **tool**
- [Entity](#)< TSeq > \* **entity**
- epiworld\_fast\_int **new\_state**
- epiworld\_fast\_int **queue**
- EventFun< TSeq > **call**
- int **idx\_agent**
- int **idx\_object**

### 17.18.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
struct Event< TSeq >
```

[Event](#) data for update an agent.

Template Parameters

<i>TSeq</i>	
-------------	--

## 17.18.2 Constructor & Destructor Documentation

### 17.18.2.1 Event()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
Event< TSeq >::Event (
 Agent< TSeq > * agent_,
 VirusPtr< TSeq > & virus_,
 ToolPtr< TSeq > & tool_,
 Entity< TSeq > * entity_,
 epiworld_fast_int new_state_,
 epiworld_fast_int queue_,
 EventFun< TSeq > & call_,
 int idx_agent_,
 int idx_object_) [inline]
```

Construct a new [Event](#) object.

All the parameters are rather optional.

#### Parameters

<i>agent_</i>	<a href="#">Agent</a> over who the action will happen
<i>virus_</i>	<a href="#">Virus</a> to add
<i>tool_</i>	<a href="#">Tool</a> to add
<i>virus_idx</i>	Index of virus to be removed (if needed)
<i>tool_idx</i>	Index of tool to be removed (if needed)
<i>new_↔ state_</i>	Next state
<i>queue_</i>	Effect on the queue
<i>call_</i>	The action call (if needed)
<i>idx_↔ agent_</i>	Location of agent in object.
<i>idx_↔ object_</i>	Location of object in agent.

The documentation for this struct was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/config.hpp

## 17.19 epiworld::GlobalEvent< TSeq > Class Template Reference

Template for a Global [Event](#).

```
#include <epiworld.hpp>
```

## Public Member Functions

- [GlobalEvent](#) (GlobalFun< TSeq > fun, std::string name, int day=-99)  
Construct a new Global [Event](#) object.
- void **operator()** ([Model](#)< TSeq > \*m, int day)
- void **set\_name** (std::string name)
- std::string **get\_name** () const
- void **set\_day** (int day)
- int **get\_day** () const
- void **print** () const
- bool **operator==** (const [GlobalEvent](#)< TSeq > &other) const
- bool **operator!=** (const [GlobalEvent](#)< TSeq > &other) const

### 17.19.1 Detailed Description

```
template<typename TSeq>
class epiworld::GlobalEvent< TSeq >
```

Template for a Global [Event](#).

Global events are functions that `Model<TSeq>` executes at the end of a day.

### 17.19.2 Constructor & Destructor Documentation

#### 17.19.2.1 GlobalEvent()

```
template<typename TSeq >
GlobalEvent< TSeq >::GlobalEvent (
 GlobalFun< TSeq > fun,
 std::string name,
 int day = -99) [inline]
```

Construct a new Global [Event](#) object.

#### Parameters

<i>fun</i>	A function that takes a <code>Model&lt;TSeq&gt; *</code> as argument and returns void.
<i>name</i>	A descriptive name for the action.
<i>day</i>	The day when the action will be executed. If negative, it will be executed every day.

The documentation for this class was generated from the following file:

- epiworld.hpp



## 17.20 GlobalEvent< TSeq > Class Template Reference

Template for a Global [Event](#).

```
#include <globalevent-bones.hpp>
```

### Public Member Functions

- [GlobalEvent](#) (GlobalFun< TSeq > fun, std::string name, int day=-99)  
*Construct a new Global [Event](#) object.*
- void **operator()** ([Model](#)< TSeq > \*m, int day)
- void **set\_name** (std::string name)
- std::string **get\_name** () const
- void **set\_day** (int day)
- int **get\_day** () const
- void **print** () const
- bool **operator==** (const [GlobalEvent](#)< TSeq > &other) const
- bool **operator!=** (const [GlobalEvent](#)< TSeq > &other) const

### 17.20.1 Detailed Description

```
template<typename TSeq>
class GlobalEvent< TSeq >
```

Template for a Global [Event](#).

Global events are functions that [Model](#)<TSeq> executes at the end of a day.

### 17.20.2 Constructor & Destructor Documentation

#### 17.20.2.1 GlobalEvent()

```
template<typename TSeq >
GlobalEvent< TSeq >::GlobalEvent (
 GlobalFun< TSeq > fun,
 std::string name,
 int day = -99) [inline]
```

Construct a new Global [Event](#) object.

#### Parameters

<i>fun</i>	A function that takes a <a href="#">Model</a> <TSeq> * as argument and returns void.
<i>name</i>	A descriptive name for the action.
<i>day</i>	The day when the action will be executed. If negative, it will be executed every day.

The documentation for this class was generated from the following files:

- include/epiworld/globalevent-bones.hpp
- include/epiworld/globalevent-meat.hpp

## 17.21 epiworld::LFMCMC< TData > Class Template Reference

Likelihood-Free Markov Chain Monte Carlo.

```
#include <epiworld.hpp>
```

### Public Member Functions

- void **run** (std::vector< epiworld\_double > params\_init\_, size\_t n\_samples\_, epiworld\_double epsilon\_, int seed=-1)
- **LFMCMC** (const TData &observed\_data\_)
- void **set\_observed\_data** (const TData &observed\_data\_)
- void **set\_proposal\_fun** (LFMCMCProposalFun< TData > fun)
- void **set\_simulation\_fun** (LFMCMCSimFun< TData > fun)
- void **set\_summary\_fun** (LFMCMCSummaryFun< TData > fun)
- void **set\_kernel\_fun** (LFMCMCKernelFun< TData > fun)
- void **set\_params\_names** (std::vector< std::string > names)
- void **set\_stats\_names** (std::vector< std::string > names)
- size\_t **get\_n\_samples** () const
- size\_t **get\_n\_stats** () const
- size\_t **get\_n\_params** () const
- epiworld\_double **get\_epsilon** () const
- const std::vector< epiworld\_double > & **get\_initial\_params** () const
- const std::vector< epiworld\_double > & **get\_current\_proposed\_params** () const
- const std::vector< epiworld\_double > & **get\_current\_accepted\_params** () const
- const std::vector< epiworld\_double > & **get\_current\_proposed\_stats** () const
- const std::vector< epiworld\_double > & **get\_current\_accepted\_stats** () const
- const std::vector< epiworld\_double > & **get\_observed\_stats** () const
- const std::vector< epiworld\_double > & **get\_all\_sample\_params** () const
- const std::vector< epiworld\_double > & **get\_all\_sample\_stats** () const
- const std::vector< bool > & **get\_all\_sample\_acceptance** () const
- const std::vector< epiworld\_double > & **get\_all\_sample\_drawn\_prob** () const
- const std::vector< epiworld\_double > & **get\_all\_sample\_kernel\_scores** () const
- const std::vector< epiworld\_double > & **get\_all\_accepted\_params** () const
- const std::vector< epiworld\_double > & **get\_all\_accepted\_stats** () const
- const std::vector< epiworld\_double > & **get\_all\_accepted\_kernel\_scores** () const
- std::vector< TData > \* **get\_simulated\_data** () const
- std::vector< epiworld\_double > **get\_mean\_params** ()
- std::vector< epiworld\_double > **get\_mean\_stats** ()
- **LFMCMC**< TData > & **verbose\_off** ()
- **LFMCMC**< TData > & **verbose\_on** ()
- void **print** (size\_t burnin=0u) const

### Random number generation

*Parameters*

eng	
-----	--

- void **set\_rand\_engine** (std::shared\_ptr< std::mt19937 > &eng)
- std::shared\_ptr< std::mt19937 > & **get\_rand\_engine** ()
- void **seed** (epiworld\_fast\_uint s)
- void **set\_rand\_gamma** (epiworld\_double alpha, epiworld\_double beta)
- epiworld\_double **runif** ()
- epiworld\_double **rnorm** ()
- epiworld\_double **rgamma** ()
- epiworld\_double **runif** (epiworld\_double lb, epiworld\_double ub)
- epiworld\_double **rnorm** (epiworld\_double mean, epiworld\_double sd)
- epiworld\_double **rgamma** (epiworld\_double alpha, epiworld\_double beta)

**17.21.1 Detailed Description**

```
template<typename TData>
class epiworld::LFMCMC< TData >
```

Likelihood-Free Markov Chain Monte Carlo.

**Template Parameters**

<i>TData</i>	Type of data that is generated
--------------	--------------------------------

The documentation for this class was generated from the following file:

- epiworld.hpp

**17.22 LFMCMC< TData > Class Template Reference**

Likelihood-Free Markov Chain Monte Carlo.

```
#include <lfmcmc-bones.hpp>
```

**Public Member Functions**

- void **run** (std::vector< epiworld\_double > params\_init\_, size\_t n\_samples\_, epiworld\_double epsilon\_, int seed=-1)
- **LFMCMC** (const TData &observed\_data\_)
- void **set\_observed\_data** (const TData &observed\_data\_)
- void **set\_proposal\_fun** (LFMCMCProposalFun< TData > fun)
- void **set\_simulation\_fun** (LFMCMCSimFun< TData > fun)
- void **set\_summary\_fun** (LFMCMCSummaryFun< TData > fun)
- void **set\_kernel\_fun** (LFMCMCKernelFun< TData > fun)
- void **set\_params\_names** (std::vector< std::string > names)
- void **set\_stats\_names** (std::vector< std::string > names)
- size\_t **get\_n\_samples** () const

- `size_t` **get\_n\_stats** () const
- `size_t` **get\_n\_params** () const
- `epiworld_double` **get\_epsilon** () const
- `const std::vector< epiworld_double >` & **get\_initial\_params** () const
- `const std::vector< epiworld_double >` & **get\_current\_proposed\_params** () const
- `const std::vector< epiworld_double >` & **get\_current\_accepted\_params** () const
- `const std::vector< epiworld_double >` & **get\_current\_proposed\_stats** () const
- `const std::vector< epiworld_double >` & **get\_current\_accepted\_stats** () const
- `const std::vector< epiworld_double >` & **get\_observed\_stats** () const
- `const std::vector< epiworld_double >` & **get\_all\_sample\_params** () const
- `const std::vector< epiworld_double >` & **get\_all\_sample\_stats** () const
- `const std::vector< bool >` & **get\_all\_sample\_acceptance** () const
- `const std::vector< epiworld_double >` & **get\_all\_sample\_drawn\_prob** () const
- `const std::vector< epiworld_double >` & **get\_all\_sample\_kernel\_scores** () const
- `const std::vector< epiworld_double >` & **get\_all\_accepted\_params** () const
- `const std::vector< epiworld_double >` & **get\_all\_accepted\_stats** () const
- `const std::vector< epiworld_double >` & **get\_all\_accepted\_kernel\_scores** () const
- `std::vector< TData >` \* **get\_simulated\_data** () const
- `std::vector< epiworld_double >` **get\_mean\_params** ()
- `std::vector< epiworld_double >` **get\_mean\_stats** ()
- `LFMCMC< TData >` & **verbose\_off** ()
- `LFMCMC< TData >` & **verbose\_on** ()
- `void` **print** (`size_t` burnin=0u) const

### Random number generation

#### Parameters

eng	
-----	--

- `void` **set\_rand\_engine** (`std::shared_ptr< std::mt19937 >` &eng)
- `std::shared_ptr< std::mt19937 >` & **get\_rand\_engine** ()
- `void` **seed** (`epiworld_fast_uint` s)
- `void` **set\_rand\_gamma** (`epiworld_double` alpha, `epiworld_double` beta)
- `epiworld_double` **runif** ()
- `epiworld_double` **rnorm** ()
- `epiworld_double` **rgamma** ()
- `epiworld_double` **runif** (`epiworld_double` lb, `epiworld_double` ub)
- `epiworld_double` **rnorm** (`epiworld_double` mean, `epiworld_double` sd)
- `epiworld_double` **rgamma** (`epiworld_double` alpha, `epiworld_double` beta)

## 17.22.1 Detailed Description

```
template<typename TData>
class LFMCMC< TData >
```

Likelihood-Free Markov Chain Monte Carlo.

#### Template Parameters

<i>TData</i>	Type of data that is generated
--------------	--------------------------------

The documentation for this class was generated from the following files:

- include/epiworld/math/lfmcmc/lfmcmc-bones.hpp
- include/epiworld/math/lfmcmc/lfmcmc-meat-print.hpp
- include/epiworld/math/lfmcmc/lfmcmc-meat.hpp

## 17.23 epiworld::Model< TSeq > Class Template Reference

Core class of epiworld.

```
#include <epiworld.hpp>
```

Collaboration diagram for epiworld::Model< TSeq >:



### Public Member Functions

- `DataBase< TSeq > & get_db ()`
- `const DataBase< TSeq > & get_db () const`
- `epiworld_double & operator() (std::string pname)`
- `size_t size () const`
- `void load_agents_entities_ties (std::string fn, int skip)`  
*Associate agents-entities from a file.*
- `void load_agents_entities_ties (const std::vector< int > &agents_ids, const std::vector< int > &entities_ids)`  
*Associate agents-entities from data.*
- `void load_agents_entities_ties (const int *agents_id, const int *entities_id, size_t n)`
- `size_t get_n_viruses () const`  
*Number of viruses in the model.*
- `size_t get_n_tools () const`  
*Number of tools in the model.*
- `epiworld_fast_uint get_ndays () const`
- `epiworld_fast_uint get_n_replicates () const`
- `size_t get_n_entities () const`
- `void set_ndays (epiworld_fast_uint ndays)`
- `bool get_verbose () const`
- `Model< TSeq > & verbose_off ()`
- `Model< TSeq > & verbose_on ()`

- int **today** () const  
*The current time of the model.*
- void **write\_data** (std::string fn\_virus\_info, std::string fn\_virus\_hist, std::string fn\_tool\_info, std::string fn\_tool\_hist, std::string fn\_total\_hist, std::string fn\_transmission, std::string fn\_transition, std::string fn\_reproductive\_number, std::string fn\_generation\_time) const  
*Wrapper of DataBase::write\_data*
- std::map< std::string, epiworld\_double > & **params** ()
- virtual void **reset** ()  
*Reset the model.*
- const **Model**< TSeq > & **print** (bool lite=false) const
- void **get\_elapsed** (std::string unit="auto", epiworld\_double \*last\_elapsed=nullptr, epiworld\_double \*total\_elapsed=nullptr, std::string \*unit\_abbr=nullptr, bool print=true) const
- void **add\_globalevent** (std::function< void(**Model**< TSeq > \*)> fun, std::string name="A global action", int date=-99)  
*Set a global action.*
- void **add\_globalevent** (**GlobalEvent**< TSeq > action)
- **GlobalEvent**< TSeq > & **get\_globalevent** (std::string name)  
*Retrieve a global action by name.*
- **GlobalEvent**< TSeq > & **get\_globalevent** (size\_t i)  
*Retrieve a global action by index.*
- void **rm\_globalevent** (std::string name)  
*Remove a global action by name.*
- void **rm\_globalevent** (size\_t i)  
*Remove a global action by index.*
- void **run\_globalevents** ()
- void **clear\_state\_set** ()
- const std::vector< VirusPtr< TSeq > > & **get\_viruses** () const
- const std::vector< ToolPtr< TSeq > > & **get\_tools** () const
- **Virus**< TSeq > & **get\_virus** (size\_t id)
- **Tool**< TSeq > & **get\_tool** (size\_t id)
- void **set\_agents\_data** (double \*data\_, size\_t ncols\_)  
*Set the agents data object.*
- double \* **get\_agents\_data** ()
- size\_t **get\_agents\_data\_ncols** () const
- void **set\_name** (std::string name)  
*Set the name object.*
- std::string **get\_name** () const
- bool **operator==** (const **Model**< TSeq > &other) const
- bool **operator!=** (const **Model**< TSeq > &other) const
- void **events\_run** ()  
*Executes the stored action.*
- void **draw** (DiagramType diagram\_type=DiagramType::Mermaid, const std::string &fn\_output="", bool self=false)  
*Draws a mermaid diagram of the model.*

### Set the backup object

*backup* can be used to restore the entire object after a run. This can be useful if the user wishes to have individuals start with the same network from the beginning.

- void **set\_backup** ()

### Random number generation

*Parameters*

eng	<i>Random number generator</i>
s	<i>Seed</i>

- void **set\_rand\_engine** (std::shared\_ptr< std::mt19937 > &eng)
- std::shared\_ptr< std::mt19937 > & **get\_rand\_engine** ()
- void **seed** (size\_t s)
- void **set\_rand\_norm** (epiworld\_double mean, epiworld\_double sd)
- void **set\_rand\_unif** (epiworld\_double a, epiworld\_double b)
- void **set\_rand\_exp** (epiworld\_double lambda)
- void **set\_rand\_gamma** (epiworld\_double alpha, epiworld\_double beta)
- void **set\_rand\_lognormal** (epiworld\_double mean, epiworld\_double shape)
- void **set\_rand\_binom** (int n, epiworld\_double p)
- void **set\_rand\_nbinom** (int n, epiworld\_double p)
- void **set\_rand\_geom** (epiworld\_double p)
- void **set\_rand\_pois** (epiworld\_double lambda)
- epiworld\_double **runif** ()
- epiworld\_double **runif** (epiworld\_double a, epiworld\_double b)
- epiworld\_double **rnorm** ()
- epiworld\_double **rnorm** (epiworld\_double mean, epiworld\_double sd)
- epiworld\_double **rgamma** ()
- epiworld\_double **rgamma** (epiworld\_double alpha, epiworld\_double beta)
- epiworld\_double **rexp** ()
- epiworld\_double **rexp** (epiworld\_double lambda)
- epiworld\_double **rlognormal** ()
- epiworld\_double **rlognormal** (epiworld\_double mean, epiworld\_double shape)
- int **rbinom** ()
- int **rbinom** (int n, epiworld\_double p)
- int **rnbinom** ()
- int **rnbinom** (int n, epiworld\_double p)
- int **rgeom** ()
- int **rgeom** (epiworld\_double p)
- int **rpoiss** ()
- int **rpoiss** (epiworld\_double lambda)

**Add Virus/Tool to the model**

*This is done before the model has been initialized.*

*Parameters*

v	<i><a href="#">Virus</a> to be added</i>
t	<i><a href="#">Tool</a> to be added</i>
preval	<i>Initial prevalence (initial state.) It can be specified as a proportion (between zero and one,) or an integer indicating number of individuals.</i>

- void **add\_virus** ([Virus](#)< TSeq > &v)
- void **add\_tool** ([Tool](#)< TSeq > &t)
- void **add\_entity** ([Entity](#)< TSeq > e)
- void **rm\_virus** (size\_t virus\_pos)
- void **rm\_tool** (size\_t tool\_pos)
- void **rm\_entity** (size\_t entity\_id)

**Accessing population of the model**

*Parameters*

fn	<i>std::string Filename of the edgelist file.</i>
skip	<i>int Number of lines to skip in fn.</i>
directed	<i>bool Whether the graph is directed or not.</i>
size	<i>Size of the network.</i>
al	<i><a href="#">AdjList</a> to read into the model.</i>

- void **agents\_from\_adjlist** (std::string fn, int size, int skip=0, bool directed=false)
- void **agents\_from\_edgelist** (const std::vector< int > &source, const std::vector< int > &target, int size, bool directed)
- void **agents\_from\_adjlist** ([AdjList](#) al)
- bool **is\_directed** () const
- std::vector< [Agent](#)< TSeq > > &**get\_agents** ()  
*Returns a reference to the vector of agents.*
- [Agent](#)< TSeq > &**get\_agent** (size\_t i)
- std::vector< epiworld\_fast\_uint > **get\_agents\_states** () const  
*Returns a vector with the states of the agents.*
- std::vector< [Viruses\\_const](#)< TSeq > > **get\_agents\_viruses** () const  
*Returns a const vector with the viruses of the agents.*
- std::vector< [Viruses](#)< TSeq > > **get\_agents\_viruses** ()  
*Returns a vector with the viruses of the agents.*
- std::vector< [Entity](#)< TSeq > > &**get\_entities** ()
- [Entity](#)< TSeq > &**get\_entity** (size\_t entity\_id, int \*entity\_pos=nullptr)
- [Model](#)< TSeq > &**agents\_smallworld** (epiworld\_fast\_uint n=1000, epiworld\_fast\_uint k=5, bool d=false, epiworld\_double p=.01)
- void **agents\_empty\_graph** (epiworld\_fast\_uint n=1000)

**Functions to run the model***Parameters*

seed	<i>Seed to be used for Pseudo-RNG.</i>
ndays	<i>Number of days (steps) of the simulation.</i>
fun	<i>In the case of <code>run_multiple</code>, a function that is called after each experiment.</i>

- void **update\_state** ()
- void **mutate\_virus** ()
- void **next** ()
- virtual [Model](#)< TSeq > &**run** (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void **run\_multiple** (epiworld\_fast\_uint ndays, epiworld\_fast\_uint nexperiments, int seed\_=-1, std::function< void(size\_t, [Model](#)< TSeq > \*)> fun=make\_save\_run< TSeq >(), bool **reset**=true, bool verbose=true, int nthreads=1)

**Rewire the network preserving the degree sequence.**

*This implementation assumes an undirected network, thus if  $\{(i,j), (k,l)\} \rightarrow \{(i,l), (k,j)\}$ , the reciprocal is also true, i.e.,  $\{(j,i), (l,k)\} \rightarrow \{(j,k), (l,i)\}$ .*

*Parameters*

proportion	<i>Proportion of ties to be rewired.</i>
------------	------------------------------------------



**Returns**

*A rewired version of the network.*

- void **set\_rewire\_fun** (std::function< void(std::vector< [Agent](#)< TSeq >> \*, [Model](#)< TSeq > \*, epiworld\_double)> fun)
- void **set\_rewire\_prop** (epiworld\_double prop)
- epiworld\_double **get\_rewire\_prop** () const
- void **rewire** ()

**Export the network data in edgelist form****Parameters**

fn	<i>std::string. File name.</i>
source	<i>Integer vector</i>
target	<i>Integer vector</i>

*When passing the source and target, the function will write the edgelist on those.*

- void **write\_edgelist** (std::string fn) const
- void **write\_edgelist** (std::vector< int > &source, std::vector< int > &target) const

**Manage state (states) in the model**

*The functions `get_state` return the current values for the states included in the model.*

**Parameters**

lab	<i>std::string Name of the state.</i>
-----	---------------------------------------

**Returns**

*add\_state\* returns nothing.*

*get\_state\_\* returns a vector of pairs with the states and their labels.*

- void **add\_state** (std::string lab, UpdateFun< TSeq > fun=nullptr)
- const std::vector< std::string > & **get\_states** () const
- size\_t **get\_n\_states** () const
- const std::vector< UpdateFun< TSeq > > & **get\_state\_fun** () const
- void **print\_state\_codes** () const

**Initial states**

*These functions are called before the simulation starts.*

**Parameters**

proportions↔	<i>Vector of proportions for each state.</i>
—	
queue_	<i>Vector of queue for each state.</i>

- virtual [Model](#)< TSeq > & **initial\_states** (std::vector< double >, std::vector< int >)

**Setting and accessing parameters from the model**

*Tools* can incorporate parameters included in the model. Internally, parameters in the tool are stored as pointers to an `std::map<>` of parameters in the model. Using the `epiworld_fast_uint` method directly fetches the parameters in the order these were added to the tool. Accessing parameters via the `std::string` method involves searching the parameter directly in the `std::map<>` member of the model (so it is not recommended.)

The `par()` function members are aliases for `get_param()`.

In the case of the function `read_params`, users can pass a file listing parameters to be included in the model. Each line in the file should have the following structure:

```
[name of parameter 1]: [value in double]
[name of parameter 2]: [value in double]
...
```

The only condition for parameter names is that these do not include a colon.

#### Parameters

initial_val	
pname	Name of the parameter to add or to fetch
fn	Path to the file containing parameters

#### Returns

The current value of the parameter in the model.

- `epiworld_double add_param` (`epiworld_double initial_val`, `std::string pname`, `bool overwrite=false`)
- `Model< TSeq > & read_params` (`std::string fn`, `bool overwrite=false`)
- `epiworld_double get_param` (`epiworld_fast_uint k`)
- `epiworld_double get_param` (`std::string pname`)
- `void set_param` (`std::string pname`, `epiworld_double val`)
- `epiworld_double par` (`std::string pname`) `const`

#### Set the user data object

##### Parameters

names	string vector with the names of the variables.
-------	------------------------------------------------

- `void set_user_data` (`std::vector< std::string > names`)  
[@
- `void add_user_data` (`epiworld_fast_uint j`, `epiworld_double x`)
- `void add_user_data` (`std::vector< epiworld_double > x`)
- `UserData< TSeq > & get_user_data` ()

#### Queuing system

When queueing is on, the model will keep track of which agents are either in risk of exposure or exposed. This then is used at each step to act only on the aforementioned agents.

- `void queuing_on` ()  
Activates the queuing system (default.)
- `Model< TSeq > & queuing_off` ()  
Deactivates the queuing system.
- `bool is_queuing_on` () `const`  
Query if the queuing system is on.
- `Queue< TSeq > & get_queue` ()  
Retrieve the `Queue` object.

#### Get the susceptibility reduction object

### Parameters

v	
---	--

### Returns

*epiworld\_double*

- void **set\_susceptibility\_reduction\_mixer** (MixerFun< TSeq > fun)
- void **set\_transmission\_reduction\_mixer** (MixerFun< TSeq > fun)
- void **set\_recovery\_enhancer\_mixer** (MixerFun< TSeq > fun)
- void **set\_death\_reduction\_mixer** (MixerFun< TSeq > fun)

## Protected Member Functions

- void **dist\_tools** ()
- void **dist\_virus** ()
- void **dist\_entities** ()
- void **chrono\_start** ()
- void **chrono\_end** ()
- void **events\_add** (Agent< TSeq > \*agent\_, VirusPtr< TSeq > virus\_, ToolPtr< TSeq > tool\_, Entity< TSeq > \*entity\_, epiworld\_fast\_int new\_state\_, epiworld\_fast\_int queue\_, EventFun< TSeq > call\_, int idx\_↵ agent\_, int idx\_object\_)

*Construct a new [Event](#) object.*

## Protected Attributes

- std::string **name** = ""  
*Name of the model.*
- DataBase< TSeq > **db** = DataBase<TSeq>(\*this)
- std::vector< Agent< TSeq > > **population** = {}
- bool **using\_backup** = true
- std::vector< Agent< TSeq > > **population\_backup** = {}
- bool **directed** = false
- std::vector< VirusPtr< TSeq > > **viruses** = {}
- std::vector< ToolPtr< TSeq > > **tools** = {}
- std::vector< Entity< TSeq > > **entities** = {}
- std::vector< Entity< TSeq > > **entities\_backup** = {}
- std::shared\_ptr< std::mt19937 > **engine** = std::make\_shared< std::mt19937 >()
- std::uniform\_real\_distribution **runifd**
- std::normal\_distribution **rnormd**
- std::gamma\_distribution **rgammad**
- std::lognormal\_distribution **rlognormald**
- std::exponential\_distribution **rexp**
- std::binomial\_distribution **rbinomd**
- std::negative\_binomial\_distribution **rnbinomd**
- std::geometric\_distribution **rgeomd**
- std::poisson\_distribution **rpoissd**
- std::function< void(std::vector< Agent< TSeq > > \*, Model< TSeq > \*, epiworld\_double)> **rewire\_fun**
- epiworld\_double **rewire\_prop** = 0.0
- std::map< std::string, epiworld\_double > **parameters**
- epiworld\_fast\_uint **ndays** = 0
- [Progress](#) **pb**

- `std::vector< UpdateFun< TSeq > > state_fun = {}`  
*Functions to update states.*
- `std::vector< std::string > states_labels = {}`  
*Labels of the states.*
- `std::function< void(Model< TSeq > *)> initial_states_fun`
- `epiworld_fast_uint nstates = 0u`
- `bool verbose = true`
- `int current_date = 0`
- `std::chrono::time_point< std::chrono::steady_clock > time_start`
- `std::chrono::time_point< std::chrono::steady_clock > time_end`
- `std::chrono::duration< epiworld_double, std::micro > time_elapsed`
- `epiworld_fast_uint n_replicates = 0u`
- `std::vector< GlobalEvent< TSeq > > globalevents`
- `Queue< TSeq > queue`
- `bool use_queueing = true`
- `std::vector< Event< TSeq > > events = {}`  
*Variables used to keep track of the events to be made regarding viruses.*
- `epiworld_fast_uint nactions = 0u`

#### Auxiliary variables for AgentsSample<TSeq> iterators

*These variables+objects are used by the AgentsSample<TSeq> class for building efficient iterators over agents. The idea is to reduce the memory allocation, so only during the first call of AgentsSample<TSeq>::AgentsSample(Model<TSeq>) these vectors are allocated.*

- `std::vector< Agent< TSeq > * > sampled_population`
- `size_t sampled_population_n = 0u`
- `std::vector< size_t > population_left`
- `size_t population_left_n = 0u`

#### Agents features

*Optionally, a model can include an external data source pointing to agents information. The data can then be access through the Agent::operator() method.*

- `double * agents_data = nullptr`
- `size_t agents_data_ncols = 0u`

#### Friends

- `class Agent< TSeq >`
- `class AgentsSample< TSeq >`
- `class DataBase< TSeq >`
- `class Queue< TSeq >`

#### Tool Mixers

These functions combine the effects tools have to deliver a single effect. For example, wearing a mask, been vaccinated, and the immune system combine together to jointly reduce the susceptibility for a given virus.

- `MixerFun< TSeq > susceptibility_reduction_mixer = susceptibility_reduction_mixer_default<TSeq>`
- `MixerFun< TSeq > transmission_reduction_mixer = transmission_reduction_mixer_default<TSeq>`
- `MixerFun< TSeq > recovery_enhancer_mixer = recovery_enhancer_mixer_default<TSeq>`

- MixerFun< TSeq > **death\_reduction\_mixer** = death\_reduction\_mixer\_default<TSeq>
- std::vector< epiworld\_double > **array\_double\_tmp**
- std::vector< [Virus](#)< TSeq > \* > **array\_virus\_tmp**
- virtual [Model](#)< TSeq > \* **clone\_ptr** ()

*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*

- **Model** ()
- **Model** (const [Model](#)< TSeq > &m)
- **Model** ([Model](#)< TSeq > &m)
- **Model** ([Model](#)< TSeq > &&m)
- [Model](#)< TSeq > & **operator=** (const [Model](#)< TSeq > &m)
- virtual ~**Model** ()

### 17.23.1 Detailed Description

```
template<typename TSeq>
class epiworld::Model< TSeq >
```

Core class of epiworld.

The model class provides the wrapper that puts together [Agent](#), [Virus](#), and [Tools](#).

#### Template Parameters

<i>TSeq</i>	Type of sequence. In principle, users can build models in which virus and human sequence is represented as numeric vectors (if needed.)
-------------	-----------------------------------------------------------------------------------------------------------------------------------------

### 17.23.2 Member Function Documentation

#### 17.23.2.1 add\_globalevent()

```
template<typename TSeq >
void Model< TSeq >::add_globalevent (
 std::function< void(Model< TSeq > *)> fun,
 std::string name = "A global action",
 int date = -99) [inline]
```

Set a global action.

#### Parameters

<i>fun</i>	A function to be called on the prescribed date
<i>name</i>	Name of the action.
<i>date</i>	Integer indicating when the function is called (see details)

When date is less than zero, then the function is called at the end of every day. Otherwise, the function will be called only at the end of the indicated date.



```
int idx_agent_,
int idx_object_) [inline], [protected]
```

Construct a new [Event](#) object.

#### Parameters

<i>agent_</i>	<a href="#">Agent</a> over which the action will be called
<i>virus_</i>	<a href="#">Virus</a> pointer included in the action
<i>tool_</i>	<a href="#">Tool</a> pointer included in the action
<i>entity_</i>	<a href="#">Entity</a> pointer included in the action
<i>new_↔ state_</i>	New state of the agent
<i>call_</i>	Function the action will call
<i>queue_</i>	Change in the queue
<i>idx_↔ agent_</i>	Location of agent in object.
<i>idx_↔ object_</i>	Location of object in agent.

#### 17.23.2.5 events\_run()

```
template<typename TSeq >
void Model< TSeq >::events_run [inline]
```

Executes the stored action.

#### Parameters

<i>model_↔ _</i>	<a href="#">Model</a> over which it will be executed.
----------------------	-------------------------------------------------------

#### 17.23.2.6 load\_agents\_entities\_ties()

```
template<typename TSeq >
void Model< TSeq >::load_agents_entities_ties (
 std::string fn,
 int skip) [inline]
```

Associate agents-entities from a file.

The structure of the file should be two columns separated by space. The first column indexing between 0 and nagents-1, and the second column between 0 and nentities - 1.

#### Parameters

<i>fn</i>	Path to the file.
<i>skip</i>	How many rows to skip.

### 17.23.2.7 reset()

```
template<typename TSeq >
void Model< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented in `ModelSURV< TSeq >`, `ModelSIRMixing< TSeq >`, `ModelSIRLogit< TSeq >`, `ModelSIRDCONN< TSeq >`, `ModelSIRCONN< TSeq >`, `ModelSEIRMixingQuarantine< TSeq >`, `ModelSEIRMixing< TSeq >`, `ModelSEIRDCONN< TSeq >`, `ModelSEIRCONN< TSeq >`, `ModelMeaslesMixing< TSeq >`, `epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >`, `epiworld::epimodels::ModelMeaslesMixing< TSeq >`, `epiworld::epimodels::ModelSEIRMixingQuarantine< TSeq >`, `epiworld::epimodels::ModelMeaslesSchool< TSeq >`, `epiworld::epimodels::ModelSIRMixing< TSeq >`, `epiworld::epimodels::ModelSIRLogit< TSeq >`, `epiworld::epimodels::ModelSEIRDCONN< TSeq >`, `epiworld::epimodels::ModelSIRCONN< TSeq >`, `epiworld::epimodels::ModelSEIRCONN< TSeq >`, `epiworld::epimodels::ModelSIRCONN< TSeq >`, and `epiworld::epimodels::ModelSIRCONN< TSeq >`.

### 17.23.2.8 run\_multiple()

```
template<typename TSeq >
void Model< TSeq >::run_multiple (
 epiworld_fast_uint ndays,
 epiworld_fast_uint nexperiments,
 int seed_ = -1,
 std::function< void(size_t, Model< TSeq > *)> fun = make_save_run<TSeq>(),
 bool reset = true,
 bool verbose = true,
 int nthreads = 1) [inline]
```

#### Parameters

<code>ndays</code>	Multiple runs of the simulation
--------------------	---------------------------------

### 17.23.2.9 set\_agents\_data()

```
template<typename TSeq >
void Model< TSeq >::set_agents_data (
```



```
double * data_,
size_t ncols_) [inline]
```

Set the agents data object.

The data should be an array with the data stored in a column major order, i.e., by column.

#### Parameters

<i>data</i> ↔ _	Pointer to the first element of an array of size <code>size() * ncols_</code> .
<i>ncols</i> ↔ _	Number of features included in the data.

#### 17.23.2.10 set\_name()

```
template<typename TSeq >
void Model< TSeq >::set_name (
 std::string name) [inline]
```

Set the name object.

#### Parameters

<i>name</i>	
-------------	--

#### 17.23.2.11 write\_data()

```
template<typename TSeq >
void Model< TSeq >::write_data (
 std::string fn_virus_info,
 std::string fn_virus_hist,
 std::string fn_tool_info,
 std::string fn_tool_hist,
 std::string fn_total_hist,
 std::string fn_transmission,
 std::string fn_transition,
 std::string fn_reproductive_number,
 std::string fn_generation_time) const [inline]
```

Wrapper of `DataBase::write_data`

#### Parameters

<i>fn_virus_info</i>	Filename. Information about the virus.
<i>fn_virus_hist</i>	Filename. History of the virus.
<i>fn_tool_info</i>	Filename. Information about the tool.

## Parameters

<i>fn_tool_hist</i>	Filename. History of the tool.
<i>fn_total_hist</i>	Filename. Aggregated history (state)
<i>fn_transmission</i>	Filename. Transmission history.
<i>fn_transition</i>	Filename. Markov transition history.
<i>fn_reproductive_number</i>	Filename. Case by case reproductive number

### 17.23.3 Member Data Documentation

#### 17.23.3.1 initial\_states\_fun

```
template<typename TSeq >
std::function<void (Model<TSeq>*)> epiworld::Model< TSeq >::initial_states_fun [protected]
```

## Initial value:

```
= [] (Model<TSeq> *)
 -> void {}
```

Function to distribute states. Goes along with the function

#### 17.23.3.2 rbinomd

```
template<typename TSeq >
std::binomial_distribution epiworld::Model< TSeq >::rbinomd [protected]
```

## Initial value:

```
=
 std::binomial_distribution<>()
```

#### 17.23.3.3 rexp

```
template<typename TSeq >
std::exponential_distribution epiworld::Model< TSeq >::rexp [protected]
```

## Initial value:

```
=
 std::exponential_distribution<>()
```

### 17.23.3.4 `rgammad`

```
template<typename TSeq >
std::gamma_distribution epiworld::Model< TSeq >::rgammad [protected]
```

**Initial value:**

```
=
 std::gamma_distribution<>()
```

### 17.23.3.5 `rgeomd`

```
template<typename TSeq >
std::geometric_distribution epiworld::Model< TSeq >::rgeomd [protected]
```

**Initial value:**

```
=
 std::geometric_distribution<>()
```

### 17.23.3.6 `rlognormald`

```
template<typename TSeq >
std::lognormal_distribution epiworld::Model< TSeq >::rlognormald [protected]
```

**Initial value:**

```
=
 std::lognormal_distribution<>()
```

### 17.23.3.7 `rnbinomd`

```
template<typename TSeq >
std::negative_binomial_distribution epiworld::Model< TSeq >::rnbinomd [protected]
```

**Initial value:**

```
=
 std::negative_binomial_distribution<>()
```

### 17.23.3.8 `rnormd`

```
template<typename TSeq >
std::normal_distribution epiworld::Model< TSeq >::rnormd [protected]
```

**Initial value:**

```
=
 std::normal_distribution<>(0.0)
```

### 17.23.3.9 rpoissd

```
template<typename TSeq >
std::poisson_distribution epiworld::Model< TSeq >::rpoissd [protected]
```

#### Initial value:

```
=
 std::poisson_distribution<>()
```

### 17.23.3.10 runifd

```
template<typename TSeq >
std::uniform_real_distribution epiworld::Model< TSeq >::runifd [protected]
```

#### Initial value:

```
=
 std::uniform_real_distribution<> (0.0, 1.0)
```

### 17.23.3.11 time\_elapsed

```
template<typename TSeq >
std::chrono::duration<epiworld_double, std::micro> epiworld::Model< TSeq >::time_elapsed [protected]
```

#### Initial value:

```
=
 std::chrono::duration<epiworld_double, std::micro>::zero()
```

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.24 Model< TSeq > Class Template Reference

Core class of epiworld.

```
#include <model-bones.hpp>
```

Inheritance diagram for Model< TSeq >:



Collaboration diagram for Model< TSeq >:



## Public Member Functions

- [DataBase< TSeq >](#) & **get\_db** ()
- const [DataBase< TSeq >](#) & **get\_db** () const
- [epiworld\\_double](#) & **operator()** (std::string pname)
- [size\\_t](#) **size** () const
- void [load\\_agents\\_entities\\_ties](#) (std::string fn, int skip)
  - Associate agents-entities from a file.*
- void [load\\_agents\\_entities\\_ties](#) (const std::vector< int > &agents\_ids, const std::vector< int > &entities\_ids)
  - Associate agents-entities from data.*
- void **load\_agents\_entities\_ties** (const int \*agents\_id, const int \*entities\_id, [size\\_t](#) n)
- [size\\_t](#) [get\\_n\\_viruses](#) () const
  - Number of viruses in the model.*
- [size\\_t](#) [get\\_n\\_tools](#) () const
  - Number of tools in the model.*
- [epiworld\\_fast\\_uint](#) **get\_ndays** () const
- [epiworld\\_fast\\_uint](#) **get\_n\_replicates** () const
- [size\\_t](#) **get\_n\_entities** () const
- void **set\_ndays** ([epiworld\\_fast\\_uint](#) ndays)
- bool **get\_verbose** () const
- [Model< TSeq >](#) & **verbose\_off** ()
- [Model< TSeq >](#) & **verbose\_on** ()
- int [today](#) () const
  - The current time of the model.*
- void [write\\_data](#) (std::string fn\_virus\_info, std::string fn\_virus\_hist, std::string fn\_tool\_info, std::string fn\_↵  
\_tool\_hist, std::string fn\_total\_hist, std::string fn\_transmission, std::string fn\_transition, std::string fn\_↵  
reproductive\_number, std::string fn\_generation\_time) const
  - Wrapper of DataBase::write\_data*
- std::map< std::string, [epiworld\\_double](#) > & **params** ()
- virtual void [reset](#) ()
  - Reset the model.*
- const [Model< TSeq >](#) & **print** (bool lite=false) const
- void **get\_elapsed** (std::string unit="auto", [epiworld\\_double](#) \*last\_elapsed=nullptr, [epiworld\\_double](#) \*total\_↵  
elapsed=nullptr, std::string \*unit\_abbr=nullptr, bool print=true) const
- void [add\\_globalevent](#) (std::function< void([Model< TSeq >](#) \*)> fun, std::string name="A global action", int date=-99)

*Set a global action.*

- void **add\_globlevent** ([GlobalEvent](#)< TSeq > action)
- [GlobalEvent](#)< TSeq > & **get\_globlevent** (std::string name)

*Retrieve a global action by name.*

- [GlobalEvent](#)< TSeq > & **get\_globlevent** (size\_t i)

*Retrieve a global action by index.*

- void **rm\_globlevent** (std::string name)

*Remove a global action by name.*

- void **rm\_globlevent** (size\_t i)

*Remove a global action by index.*

- void **run\_globlevents** ()
- void **clear\_state\_set** ()
- const std::vector< [VirusPtr](#)< TSeq > > & **get\_viruses** () const
- const std::vector< [ToolPtr](#)< TSeq > > & **get\_tools** () const
- [Virus](#)< TSeq > & **get\_virus** (size\_t id)
- [Tool](#)< TSeq > & **get\_tool** (size\_t id)
- void **set\_agents\_data** (double \*data\_, size\_t ncols\_)

*Set the agents data object.*

- double \* **get\_agents\_data** ()
- size\_t **get\_agents\_data\_ncols** () const
- void **set\_name** (std::string name)

*Set the name object.*

- std::string **get\_name** () const
- bool **operator==** (const [Model](#)< TSeq > &other) const
- bool **operator!=** (const [Model](#)< TSeq > &other) const
- void **events\_run** ()

*Executes the stored action.*

- void **draw** ([DiagramType](#) diagram\_type=[DiagramType::Mermaid](#), const std::string &fn\_output="", bool self=false)

*Draws a mermaid diagram of the model.*

### Set the backup object

*backup* can be used to restore the entire object after a run. This can be useful if the user wishes to have individuals start with the same network from the beginning.

- void **set\_backup** ()

### Random number generation

#### Parameters

eng	<i>Random number generator</i>
s	<i>Seed</i>

- void **set\_rand\_engine** (std::shared\_ptr< std::mt19937 > &eng)
- std::shared\_ptr< std::mt19937 > & **get\_rand\_endgine** ()
- void **seed** (size\_t s)
- void **set\_rand\_norm** (epiworld\_double mean, epiworld\_double sd)
- void **set\_rand\_unif** (epiworld\_double a, epiworld\_double b)
- void **set\_rand\_exp** (epiworld\_double lambda)
- void **set\_rand\_gamma** (epiworld\_double alpha, epiworld\_double beta)
- void **set\_rand\_lognormal** (epiworld\_double mean, epiworld\_double shape)
- void **set\_rand\_binom** (int n, epiworld\_double p)

- void **set\_rand\_nbinom** (int n, epiworld\_double p)
- void **set\_rand\_geom** (epiworld\_double p)
- void **set\_rand\_pois** (epiworld\_double lambda)
- epiworld\_double **runif** ()
- epiworld\_double **runif** (epiworld\_double a, epiworld\_double b)
- epiworld\_double **rnorm** ()
- epiworld\_double **rnorm** (epiworld\_double mean, epiworld\_double sd)
- epiworld\_double **rgamma** ()
- epiworld\_double **rgamma** (epiworld\_double alpha, epiworld\_double beta)
- epiworld\_double **rexp** ()
- epiworld\_double **rexp** (epiworld\_double lambda)
- epiworld\_double **rlognormal** ()
- epiworld\_double **rlognormal** (epiworld\_double mean, epiworld\_double shape)
- int **rbinom** ()
- int **rbinom** (int n, epiworld\_double p)
- int **rnbinom** ()
- int **rnbinom** (int n, epiworld\_double p)
- int **rgeom** ()
- int **rgeom** (epiworld\_double p)
- int **rpoiss** ()
- int **rpoiss** (epiworld\_double lambda)

### Add Virus/Tool to the model

*This is done before the model has been initialized.*

#### Parameters

v	<i>Virus to be added</i>
t	<i>Tool to be added</i>
preval	<i>Initial prevalence (initial state.) It can be specified as a proportion (between zero and one,) or an integer indicating number of individuals.</i>

- void **add\_virus** ([Virus](#)< TSeq > &v)
- void **add\_tool** ([Tool](#)< TSeq > &t)
- void **add\_entity** ([Entity](#)< TSeq > e)
- void **rm\_virus** (size\_t virus\_pos)
- void **rm\_tool** (size\_t tool\_pos)
- void **rm\_entity** (size\_t entity\_id)

### Accessing population of the model

#### Parameters

fn	<i>std::string Filename of the edgelist file.</i>
skip	<i>int Number of lines to skip in fn.</i>
directed	<i>bool Whether the graph is directed or not.</i>
size	<i>Size of the network.</i>
al	<i><a href="#">AdjList</a> to read into the model.</i>

- void **agents\_from\_adjlist** (std::string fn, int size, int skip=0, bool directed=false)
- void **agents\_from\_edgelist** (const std::vector< int > &source, const std::vector< int > &target, int size, bool directed)
- void **agents\_from\_adjlist** ([AdjList](#) al)
- bool **is\_directed** () const
- std::vector< [Agent](#)< TSeq > > & **get\_agents** ()  
*Returns a reference to the vector of agents.*

- [Agent](#)< TSeq > & **get\_agent** (size\_t i)
- std::vector< [epiworld\\_fast\\_uint](#) > [get\\_agents\\_states](#) () const  
Returns a vector with the states of the agents.
- std::vector< [Viruses\\_const](#)< TSeq > > [get\\_agents\\_viruses](#) () const  
Returns a const vector with the viruses of the agents.
- std::vector< [Viruses](#)< TSeq > > [get\\_agents\\_viruses](#) ()  
Returns a vector with the viruses of the agents.
- std::vector< [Entity](#)< TSeq > > & **get\_entities** ()
- [Entity](#)< TSeq > & **get\_entity** (size\_t entity\_id, int \*entity\_pos=nullptr)
- [Model](#)< TSeq > & **agents\_smallworld** ([epiworld\\_fast\\_uint](#) n=1000, [epiworld\\_fast\\_uint](#) k=5, bool d=false, [epiworld\\_double](#) p=.01)
- void **agents\_empty\_graph** ([epiworld\\_fast\\_uint](#) n=1000)

### Functions to run the model

#### Parameters

seed	Seed to be used for Pseudo-RNG.
ndays	Number of days (steps) of the simulation.
fun	In the case of <i>run_multiple</i> , a function that is called after each experiment.

- void **update\_state** ()
- void **mutate\_virus** ()
- void **next** ()
- virtual [Model](#)< TSeq > & **run** ([epiworld\\_fast\\_uint](#) ndays, int seed=-1)  
Runs the simulation (after initialization)
- void **run\_multiple** ([epiworld\\_fast\\_uint](#) ndays, [epiworld\\_fast\\_uint](#) nexperiments, int seed\_=-1, std::function< void(size\_t, [Model](#)< TSeq > \*)> fun=make\_save\_run< TSeq >(), bool **reset**=true, bool verbose=true, int nthreads=1)

### Rewire the network preserving the degree sequence.

This implementation assumes an undirected network, thus if  $\{(i,j), (k,l)\} \rightarrow \{(i,l), (k,j)\}$ , the reciprocal is also true, i.e.,  $\{(j,i), (l,k)\} \rightarrow \{(j,k), (l,i)\}$ .

#### Parameters

proportion	Proportion of ties to be rewired.
------------	-----------------------------------

#### Returns

A rewired version of the network.

- void **set\_rewire\_fun** (std::function< void(std::vector< [Agent](#)< TSeq > > \*, [Model](#)< TSeq > \*, [epiworld\\_double](#))> fun)
- void **set\_rewire\_prop** ([epiworld\\_double](#) prop)
- [epiworld\\_double](#) **get\_rewire\_prop** () const
- void **rewire** ()

### Export the network data in edgelist form

#### Parameters

fn	std::string. File name.
source	Integer vector
target	Integer vector



When passing the source and target, the function will write the edgelist on those.

- void **write\_edgelist** (std::string fn) const
- void **write\_edgelist** (std::vector< int > &source, std::vector< int > &target) const

### Manage state (states) in the model

The functions `get_state` return the current values for the states included in the model.

#### Parameters

lab	<code>std::string</code> Name of the state.
-----	---------------------------------------------

#### Returns

`add_state*` returns nothing.

`get_state_*` returns a vector of pairs with the states and their labels.

- void **add\_state** (std::string lab, UpdateFun< TSeq > fun=nullptr)
- const std::vector< std::string > & **get\_states** () const
- size\_t **get\_n\_states** () const
- const std::vector< UpdateFun< TSeq > > & **get\_state\_fun** () const
- void **print\_state\_codes** () const

### Initial states

These functions are called before the simulation starts.

#### Parameters

proportions↔	Vector of proportions for each state.
—	
queue_	Vector of queue for each state.

- virtual `Model< TSeq > & initial_states` (std::vector< double >, std::vector< int >)

### Setting and accessing parameters from the model

`Tools` can incorporate parameters included in the model. Internally, parameters in the tool are stored as pointers to an `std::map<>` of parameters in the model. Using the `epiworld_fast_uint` method directly fetches the parameters in the order these were added to the tool. Accessing parameters via the `std::string` method involves searching the parameter directly in the `std::map<>` member of the model (so it is not recommended.)

The `par()` function members are aliases for `get_param()`.

In the case of the function `read_params`, users can pass a file listing parameters to be included in the model.

Each line in the file should have the following structure:

```
[name of parameter 1]: [value in double]
[name of parameter 2]: [value in double]
...
```

The only condition for parameter names is that these do not include a colon.

#### Parameters

initial_val	
pname	Name of the parameter to add or to fetch
fn	Path to the file containing parameters

### Returns

*The current value of the parameter in the model.*

- `epiworld_double` **add\_param** (`epiworld_double` initial\_val, `std::string` pname, `bool` overwrite=false)
- `Model`< `TSeq` > & **read\_params** (`std::string` fn, `bool` overwrite=false)
- `epiworld_double` **get\_param** (`epiworld_fast_uint` k)
- `epiworld_double` **get\_param** (`std::string` pname)
- `void` **set\_param** (`std::string` pname, `epiworld_double` val)
- `epiworld_double` **par** (`std::string` pname) `const`

### Set the user data object

#### Parameters

names	<i>string vector with the names of the variables.</i>
-------	-------------------------------------------------------

- `void` **set\_user\_data** (`std::vector`< `std::string` > names)
- `[@`
- `void` **add\_user\_data** (`epiworld_fast_uint` j, `epiworld_double` x)
- `void` **add\_user\_data** (`std::vector`< `epiworld_double` > x)
- `UserData`< `TSeq` > & **get\_user\_data** ()

### Queuing system

*When queueing is on, the model will keep track of which agents are either in risk of exposure or exposed. This then is used at each step to act only on the aforementioned agents.*

- `void` **queueing\_on** ()
- *Activates the queueing system (default.)*
- `Model`< `TSeq` > & **queueing\_off** ()
- *Deactivates the queueing system.*
- `bool` **is\_queueing\_on** () `const`
- *Query if the queueing system is on.*
- `Queue`< `TSeq` > & **get\_queue** ()
- *Retrieve the `Queue` object.*

### Get the susceptibility reduction object

#### Parameters

v	
---	--

### Returns

*epiworld\_double*

- `void` **set\_susceptibility\_reduction\_mixer** (`MixerFun`< `TSeq` > fun)
- `void` **set\_transmission\_reduction\_mixer** (`MixerFun`< `TSeq` > fun)
- `void` **set\_recovery\_enhancer\_mixer** (`MixerFun`< `TSeq` > fun)
- `void` **set\_death\_reduction\_mixer** (`MixerFun`< `TSeq` > fun)

### Protected Member Functions

- `void` **dist\_tools** ()
- `void` **dist\_virus** ()

- void **dist\_entities** ()
- void **chrono\_start** ()
- void **chrono\_end** ()
- void **events\_add** (Agent< TSeq > \*agent\_, VirusPtr< TSeq > virus\_, ToolPtr< TSeq > tool\_, Entity< TSeq > \*entity\_, epiworld\_fast\_int new\_state\_, epiworld\_fast\_int queue\_, EventFun< TSeq > call\_, int idx\_↵ agent\_, int idx\_object\_)

Construct a new *Event* object.

## Protected Attributes

- std::string **name** = ""  
Name of the model.
- DataBase< TSeq > **db** = DataBase<TSeq>(\*this)
- std::vector< Agent< TSeq > > **population** = {}
- bool **using\_backup** = true
- std::vector< Agent< TSeq > > **population\_backup** = {}
- bool **directed** = false
- std::vector< VirusPtr< TSeq > > **viruses** = {}
- std::vector< ToolPtr< TSeq > > **tools** = {}
- std::vector< Entity< TSeq > > **entities** = {}
- std::vector< Entity< TSeq > > **entities\_backup** = {}
- std::shared\_ptr< std::mt19937 > **engine** = std::make\_shared< std::mt19937 >()
- std::uniform\_real\_distribution **runifd**
- std::normal\_distribution **rnormd**
- std::gamma\_distribution **rgammad**
- std::lognormal\_distribution **rlognormald**
- std::exponential\_distribution **rexp**
- std::binomial\_distribution **rbinomd**
- std::negative\_binomial\_distribution **rnbinomd**
- std::geometric\_distribution **rgeomd**
- std::poisson\_distribution **rpoissd**
- std::function< void(std::vector< Agent< TSeq > > \*, Model< TSeq > \*, epiworld\_double)> **rewire\_fun**
- epiworld\_double **rewire\_prop** = 0.0
- std::map< std::string, epiworld\_double > **parameters**
- epiworld\_fast\_uint **ndays** = 0
- **Progress pb**
- std::vector< UpdateFun< TSeq > > **state\_fun** = {}  
Functions to update states.
- std::vector< std::string > **states\_labels** = {}  
Labels of the states.
- std::function< void(Model< TSeq > \*)> **initial\_states\_fun**
- epiworld\_fast\_uint **nstates** = 0u
- bool **verbose** = true
- int **current\_date** = 0
- std::chrono::time\_point< std::chrono::steady\_clock > **time\_start**
- std::chrono::time\_point< std::chrono::steady\_clock > **time\_end**
- std::chrono::duration< epiworld\_double, std::micro > **time\_elapsed**
- epiworld\_fast\_uint **n\_replicates** = 0u
- std::vector< GlobalEvent< TSeq > > **globalevents**
- **Queue**< TSeq > **queue**
- bool **use\_queuing** = true
- std::vector< Event< TSeq > > **events** = {}  
Variables used to keep track of the events to be made regarding viruses.

- `epiworld_fast_uint nactions = 0u`

#### Auxiliary variables for `AgentsSample<TSeq>` iterators

These variables+objects are used by the `AgentsSample<TSeq>` class for building efficient iterators over agents. The idea is to reduce the memory allocation, so only during the first call of `AgentsSample<TSeq>::AgentsSample(Model<TSeq>)` these vectors are allocated.

- `std::vector< Agent< TSeq > * > sampled_population`
- `size_t sampled_population_n = 0u`
- `std::vector< size_t > population_left`
- `size_t population_left_n = 0u`

#### Agents features

Optionally, a model can include an external data source pointing to agents information. The data can then be access through the `Agent::operator()` method.

- `double * agents_data = nullptr`
- `size_t agents_data_ncols = 0u`

#### Friends

- `class Agent< TSeq >`
- `class AgentsSample< TSeq >`
- `class DataBase< TSeq >`
- `class Queue< TSeq >`

#### Tool Mixers

These functions combine the effects tools have to deliver a single effect. For example, wearing a mask, been vaccinated, and the immune system combine together to jointly reduce the susceptibility for a given virus.

- `MixerFun< TSeq > susceptibility_reduction_mixer = susceptibility_reduction_mixer_default<TSeq>`
- `MixerFun< TSeq > transmission_reduction_mixer = transmission_reduction_mixer_default<TSeq>`
- `MixerFun< TSeq > recovery_enhancer_mixer = recovery_enhancer_mixer_default<TSeq>`
- `MixerFun< TSeq > death_reduction_mixer = death_reduction_mixer_default<TSeq>`
- `std::vector< epiworld_double > array_double_tmp`
- `std::vector< Virus< TSeq > * > array_virus_tmp`
- `virtual Model< TSeq > * clone_ptr ()`

*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*

- `Model ()`
- `Model (const Model< TSeq > &m)`
- `Model (Model< TSeq > &m)`
- `Model (Model< TSeq > &&m)`
- `Model< TSeq > & operator= (const Model< TSeq > &m)`
- `virtual ~Model ()`

### 17.24.1 Detailed Description

```
template<typename TSeq>
class Model< TSeq >
```

Core class of epiworld.

The model class provides the wrapper that puts together `Agent`, `Virus`, and `Tools`.

## Template Parameters

<i>TSeq</i>	Type of sequence. In principle, users can build models in which virus and human sequence is represented as numeric vectors (if needed.)
-------------	-----------------------------------------------------------------------------------------------------------------------------------------

## 17.24.2 Member Function Documentation

## 17.24.2.1 add\_globalevent()

```
template<typename TSeq >
void Model< TSeq >::add_globalevent (
 std::function< void(Model< TSeq > *)> fun,
 std::string name = "A global action",
 int date = -99) [inline]
```

Set a global action.

## Parameters

<i>fun</i>	A function to be called on the prescribed date
<i>name</i>	Name of the action.
<i>date</i>	Integer indicating when the function is called (see details)

When date is less than zero, then the function is called at the end of every day. Otherwise, the function will be called only at the end of the indicated date.

## 17.24.2.2 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * Model< TSeq >::clone_ptr [inline], [protected], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

## Parameters

<i>copy</i>	
-------------	--

Reimplemented in [ModelMeaslesSchool< TSeq >](#), and [ModelMeaslesMixingRiskQuarantine< TSeq >](#).

## 17.24.2.3 draw()

```
template<typename TSeq >
void Model< TSeq >::draw (
```

```
DiagramType diagram_type = DiagramType::Mermaid,
const std::string & fn_output = "",
bool self = false) [inline]
```

Draws a mermaid diagram of the model.

#### Parameters

<i>model</i>	The model to draw.
<i>fn_output</i>	The name of the file to write the diagram. If empty, the diagram will be printed to the standard output.
<i>self</i>	Whether to allow self-transitions.

#### 17.24.2.4 events\_add()

```
template<typename TSeq >
void Model< TSeq >::events_add (
 Agent< TSeq > * agent_,
 VirusPtr< TSeq > virus_,
 ToolPtr< TSeq > tool_,
 Entity< TSeq > * entity_,
 epiworld_fast_int new_state_,
 epiworld_fast_int queue_,
 EventFun< TSeq > call_,
 int idx_agent_,
 int idx_object_) [inline], [protected]
```

Construct a new [Event](#) object.

#### Parameters

<i>agent_</i>	<a href="#">Agent</a> over which the action will be called
<i>virus_</i>	<a href="#">Virus</a> pointer included in the action
<i>tool_</i>	<a href="#">Tool</a> pointer included in the action
<i>entity_</i>	<a href="#">Entity</a> pointer included in the action
<i>new_↔ state_</i>	New state of the agent
<i>call_</i>	Function the action will call
<i>queue_</i>	Change in the queue
<i>idx_↔ agent_</i>	Location of agent in object.
<i>idx_↔ object_</i>	Location of object in agent.

#### 17.24.2.5 events\_run()

```
template<typename TSeq >
void Model< TSeq >::events_run [inline]
```

Executes the stored action.

## Parameters

<i>model</i> ↔	<a href="#">Model</a> over which it will be executed.
—	

**17.24.2.6 load\_agents\_entities\_ties()**

```
template<typename TSeq >
void Model< TSeq >::load_agents_entities_ties (
 std::string fn,
 int skip) [inline]
```

Associate agents-entities from a file.

The structure of the file should be two columns separated by space. The first column indexing between 0 and *nagents*-1, and the second column between 0 and *nentities* - 1.

## Parameters

<i>fn</i>	Path to the file.
<i>skip</i>	How many rows to skip.

**17.24.2.7 reset()**

```
template<typename TSeq >
void Model< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented in [ModelMeaslesSchool< TSeq >](#), and [ModelMeaslesMixingRiskQuarantine< TSeq >](#).



**17.24.2.8 run\_multiple()**

```
template<typename TSeq >
void Model< TSeq >::run_multiple (
 epiworld_fast_uint ndays,
 epiworld_fast_uint nexperiments,
 int seed_ = -1,
 std::function< void(size_t, Model< TSeq > *)> fun = make_save_run<TSeq>(),
 bool reset = true,
 bool verbose = true,
 int nthreads = 1) [inline]
```

**Parameters**

<i>ndays</i>	Multiple runs of the simulation
--------------	---------------------------------

**17.24.2.9 set\_agents\_data()**

```
template<typename TSeq >
void Model< TSeq >::set_agents_data (
 double * data_,
 size_t ncols_) [inline]
```

Set the agents data object.

The data should be an array with the data stored in a column major order, i.e., by column.

**Parameters**

<i>data</i> ↔ —	Pointer to the first element of an array of size <code>size() * ncols_</code> .
<i>ncols</i> ↔ —	Number of features included in the data.

**17.24.2.10 set\_name()**

```
template<typename TSeq >
void Model< TSeq >::set_name (
 std::string name) [inline]
```

Set the name object.

**Parameters**

<i>name</i>	
-------------	--

### 17.24.2.11 write\_data()

```
template<typename TSeq >
void Model< TSeq >::write_data (
 std::string fn_virus_info,
 std::string fn_virus_hist,
 std::string fn_tool_info,
 std::string fn_tool_hist,
 std::string fn_total_hist,
 std::string fn_transmission,
 std::string fn_transition,
 std::string fn_reproductive_number,
 std::string fn_generation_time) const [inline]
```

Wrapper of DataBase::write\_data

#### Parameters

<i>fn_virus_info</i>	Filename. Information about the virus.
<i>fn_virus_hist</i>	Filename. History of the virus.
<i>fn_tool_info</i>	Filename. Information about the tool.
<i>fn_tool_hist</i>	Filename. History of the tool.
<i>fn_total_hist</i>	Filename. Aggregated history (state)
<i>fn_transmission</i>	Filename. Transmission history.
<i>fn_transition</i>	Filename. Markov transition history.
<i>fn_reproductive_number</i>	Filename. Case by case reproductive number

## 17.24.3 Member Data Documentation

### 17.24.3.1 initial\_states\_fun

```
template<typename TSeq >
std::function<void (Model<TSeq>*)> Model< TSeq >::initial_states_fun [protected]
```

#### Initial value:

```
= [] (Model<TSeq> *)
 -> void {}
```

Function to distribute states. Goes along with the function

### 17.24.3.2 rbinomd

```
template<typename TSeq >
std::binomial_distribution Model< TSeq >::rbinomd [protected]
```

#### Initial value:

```
=
 std::binomial_distribution<>()
```

### 17.24.3.3 rexp

```
template<typename TSeq >
std::exponential_distribution Model< TSeq >::rexp [protected]
```

**Initial value:**

```
=
 std::exponential_distribution<>()
```

### 17.24.3.4 rgammad

```
template<typename TSeq >
std::gamma_distribution Model< TSeq >::rgammad [protected]
```

**Initial value:**

```
=
 std::gamma_distribution<>()
```

### 17.24.3.5 rgeomd

```
template<typename TSeq >
std::geometric_distribution Model< TSeq >::rgeomd [protected]
```

**Initial value:**

```
=
 std::geometric_distribution<>()
```

### 17.24.3.6 rlognormald

```
template<typename TSeq >
std::lognormal_distribution Model< TSeq >::rlognormald [protected]
```

**Initial value:**

```
=
 std::lognormal_distribution<>()
```

### 17.24.3.7 rnbinomd

```
template<typename TSeq >
std::negative_binomial_distribution Model< TSeq >::rnbinomd [protected]
```

**Initial value:**

```
=
 std::negative_binomial_distribution<>()
```

### 17.24.3.8 rnormd

```
template<typename TSeq >
std::normal_distribution Model< TSeq >::rnormd [protected]
```

**Initial value:**

```
=
 std::normal_distribution<>(0.0)
```

### 17.24.3.9 rpoissd

```
template<typename TSeq >
std::poisson_distribution Model< TSeq >::rpoissd [protected]
```

**Initial value:**

```
=
 std::poisson_distribution<>()
```

### 17.24.3.10 runifd

```
template<typename TSeq >
std::uniform_real_distribution Model< TSeq >::runifd [protected]
```

**Initial value:**

```
=
 std::uniform_real_distribution<>(0.0, 1.0)
```

### 17.24.3.11 time\_elapsed

```
template<typename TSeq >
std::chrono::duration<epiworld_double, std::micro> Model< TSeq >::time_elapsed [protected]
```

**Initial value:**

```
=
 std::chrono::duration<epiworld_double, std::micro>::zero()
```

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/model-bones.hpp
- include/epiworld/model-meat-print.hpp
- include/epiworld/model-meat.hpp

## 17.25 epiworld::ModelDiagram Class Reference

### Public Member Functions

- void **draw\_from\_data** (DiagramType diagram\_type, const std::vector< std::string > &states, const std::vector< epiworld\_double > &tprob, const std::string &fn\_output="", bool self=false)
- void **draw\_from\_file** (DiagramType diagram\_type, const std::string &fn\_transition, const std::string &fn\_output="", bool self=false)
- void **draw\_from\_files** (DiagramType diagram\_type, const std::vector< std::string > &fns\_transition, const std::string &fn\_output="", bool self=false)

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.26 ModelDiagram Class Reference

### Public Member Functions

- void **draw\_from\_data** (DiagramType diagram\_type, const std::vector< std::string > &states, const std::vector< epiworld\_double > &tprob, const std::string &fn\_output="", bool self=false)
- void **draw\_from\_file** (DiagramType diagram\_type, const std::string &fn\_transition, const std::string &fn\_output="", bool self=false)
- void **draw\_from\_files** (DiagramType diagram\_type, const std::vector< std::string > &fns\_transition, const std::string &fn\_output="", bool self=false)

The documentation for this class was generated from the following files:

- include/epiworld/modeldiagram-bones.hpp
- include/epiworld/modeldiagram-meat.hpp

## 17.27 epiworld::epimodels::ModelDiffNet< TSeq > Class Template Reference

Template for a [Network](#) Diffusion [Model](#).

```
#include <epiworld.hpp>
```

Inheritance diagram for epiworld::epimodels::ModelDiffNet< TSeq >:



Collaboration diagram for `epiworld::epimodels::ModelDiffNet< TSeq >`:



## Public Member Functions

- **ModelDiffNet** ([ModelDiffNet](#)< TSeq > &model, const std::string &innovation\_name, epiworld\_double prevalence, epiworld\_double prob\_adopt, bool normalize\_exposure=true, double \*agents\_data=nullptr, size\_t data\_ncols=0u, std::vector< size\_t > data\_cols={}, std::vector< double > params={})
- **ModelDiffNet** (const std::string &innovation\_name, epiworld\_double prevalence, epiworld\_double prob\_adopt, bool normalize\_exposure=true, double \*agents\_data=nullptr, size\_t data\_ncols=0u, std::vector< size\_t > data\_cols={}, std::vector< double > params={})

## Public Attributes

- bool **normalize\_exposure** = true
- std::vector< size\_t > **data\_cols**
- std::vector< double > **params**

## Static Public Attributes

- static const int **NONADOPTER** = 0
- static const int **ADOPTER** = 1

## Additional Inherited Members

### 17.27.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelDiffNet< TSeq >
```

Template for a [Network](#) Diffusion [Model](#).

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>initial_prevalence</i>	epiworld_double Initial prevalence
<i>initial_efficacy</i>	epiworld_double Initial susceptibility_reduction of the immune system
<i>initial_recovery</i>	epiworld_double Initial recovery rate of the immune system

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.28 ModelDiffNet< TSeq > Class Template Reference

Template for a [Network](#) Diffusion [Model](#).

```
#include <diffnet.hpp>
```

Inheritance diagram for ModelDiffNet< TSeq >:



Collaboration diagram for ModelDiffNet< TSeq >:



### Public Member Functions

- **ModelDiffNet** ([ModelDiffNet](#)< TSeq > &model, const std::string &innovation\_name, epiworld\_double prevalence, epiworld\_double prob\_adopt, bool normalize\_exposure=true, double \*agents\_data=nullptr, size\_t data\_ncols=0u, std::vector< size\_t > data\_cols={}, std::vector< double > params={})
- **ModelDiffNet** (const std::string &innovation\_name, epiworld\_double prevalence, epiworld\_double prob\_adopt, bool normalize\_exposure=true, double \*agents\_data=nullptr, size\_t data\_ncols=0u, std::vector< size\_t > data\_cols={}, std::vector< double > params={})

## Public Attributes

- bool **normalize\_exposure** = true
- std::vector< size\_t > **data\_cols**
- std::vector< double > **params**

## Static Public Attributes

- static const int **NONADOPTER** = 0
- static const int **ADOPTER** = 1

## Additional Inherited Members

### 17.28.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelDiffNet< TSeq >
```

Template for a [Network](#) Diffusion [Model](#).

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>initial_prevalence</i>	epiworld_double Initial prevalence
<i>initial_efficiency</i>	epiworld_double Initial susceptibility_reduction of the immune system
<i>initial_recovery</i>	epiworld_double Initial recovery rate of the immune system

The documentation for this class was generated from the following file:

- include/epiworld/models/diffnet.hpp


## 17.29 epiworld::epimodels::ModelMeaslesMixing< TSeq > Class Template Reference

Measles model with population mixing, quarantine, and contact tracing.


```
#include <epiworld.hpp>
```



Inheritance diagram for epiworld::epimodels::ModelMeaslesMixing< TSeq >:



Collaboration diagram for epiworld::epimodels::ModelMeaslesMixing< TSeq >:



## Public Member Functions

- [ModelMeaslesMixing](#) ([ModelMeaslesMixing](#)< TSeq > &model, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double vax\_↔ efficacy, epiworld\_double vax\_reduction\_recovery\_rate, epiworld\_double incubation\_period, epiworld\_double prodromal\_period, epiworld\_double rash\_period, std::vector< double > contact\_matrix, epiworld\_double hospitalization\_rate, epiworld\_double hospitalization\_period, epiworld\_double days\_undetected, epiworld\_↔ \_fast\_int quarantine\_period, epiworld\_double quarantine\_willingness, epiworld\_double isolation\_willingness, epiworld\_fast\_int isolation\_period, epiworld\_double prop\_vaccinated, epiworld\_double contact\_tracing\_↔ success\_rate=1.0, epiworld\_fast\_uint contact\_tracing\_days\_prior=4u)  
Constructs a [ModelMeaslesMixing](#) object.
- [ModelMeaslesMixing](#) (epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double vax\_efficacy, epiworld\_double vax\_reduction\_↔ recovery\_rate, epiworld\_double incubation\_period, epiworld\_double prodromal\_period, epiworld\_double rash\_period, std::vector< double > contact\_matrix, epiworld\_double hospitalization\_rate, epiworld\_double hospitalization\_period, epiworld\_double days\_undetected, epiworld\_fast\_int quarantine\_period, epiworld\_↔ \_double quarantine\_willingness, epiworld\_double isolation\_willingness, epiworld\_fast\_int isolation\_period,

epiworld\_double prop\_vaccinated, epiworld\_double contact\_tracing\_success\_rate=1.0, epiworld\_fast\_uint contact\_tracing\_days\_prior=4u)

*Constructs a [ModelMeaslesMixing](#) object.*

- [ModelMeaslesMixing](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)

*Run the model simulation.*

- void [reset](#) ()

*Reset the model to initial state.*

- [Model](#)< TSeq > \* [clone\\_ptr](#) ()

*Create a clone of this model.*

- [ModelMeaslesMixing](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})

*Set the initial states of the model.*

- void [set\\_contact\\_matrix](#) (std::vector< double > cmat)

*Set the contact matrix for population mixing.*

- std::vector< double > [get\\_contact\\_matrix](#) () const

*Get the current contact matrix.*

- std::vector< size\_t > [get\\_agent\\_quarantine\\_triggered](#) () const

*Get the quarantine trigger status for all agents.*

- std::vector< bool > [get\\_quarantine\\_willingness](#) () const

*Get the quarantine willingness for all agents.*

- std::vector< bool > [get\\_isolation\\_willingness](#) () const

*Get the isolation willingness for all agents.*

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **PRODROMAL** = 2
- static const int **RASH** = 3
- static const int **ISOLATED** = 4
- static const int **ISOLATED\_RECOVERED** = 5
- static const int **DETECTED\_HOSPITALIZED** = 6
- static const int **QUARANTINED\_EXPOSED** = 7
- static const int **QUARANTINED\_SUSCEPTIBLE** = 8
- static const int **QUARANTINED\_PRODROMAL** = 9
- static const int **QUARANTINED\_RECOVERED** = 10
- static const int **HOSPITALIZED** = 11
- static const int **RECOVERED** = 12
- static const size\_t **QUARANTINE\_PROCESS\_INACTIVE** = 0u
- static const size\_t **QUARANTINE\_PROCESS\_ACTIVE** = 1u
- static const size\_t **QUARANTINE\_PROCESS\_DONE** = 2u

## Additional Inherited Members

### 17.29.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelMeaslesMixing< TSeq >
```

Measles model with population mixing, quarantine, and contact tracing.

This class implements a Measles epidemiological model based on the SEIR framework with additional features including:

- Population mixing based on contact matrices
- Measles-specific disease progression: Susceptible → Exposed → Prodromal → Rash
- Prodromal individuals are infectious (replace the "Infected" state in SEIR)
- Rash individuals are no longer infectious but can be detected for isolation
- Quarantine measures for exposed contacts during contact tracing
- Isolation policies for detected individuals during the rash state
- Contact tracing with configurable success rates
- Hospitalization of severe cases
- Individual willingness to comply with public health measures

The model supports 13 distinct states:

- Susceptible: Individuals who can become infected
- Exposed: Infected but not yet infectious (incubation period)
- Prodromal: Infectious individuals in the community (replaces "Infected" in SEIR)
- Rash: Non-infectious individuals with visible symptoms (detection occurs here)
- Isolated: Detected individuals in self-isolation
- Isolated Recovered: Recovered individuals still in isolation
- Detected Hospitalized: Hospitalized individuals who were contact-traced
- Quarantined Exposed: Exposed individuals in quarantine due to contact tracing
- Quarantined Susceptible: Susceptible individuals in quarantine due to contact tracing
- Quarantined Prodromal: Prodromal individuals in quarantine due to contact tracing
- Quarantined Recovered: Recovered individuals in quarantine due to contact tracing
- Hospitalized: Individuals requiring hospital care
- Recovered: Individuals who have recovered and gained immunity

#### Template Parameters

<code>TSeq</code>	Type for genetic sequences (default: <code>EPI_DEFAULT_TSEQ</code> )
-------------------	----------------------------------------------------------------------

## 17.29.2 Constructor & Destructor Documentation

### 17.29.2.1 `ModelMeaslesMixing()` [1/2]

```
template<typename TSeq >
ModelMeaslesMixing< TSeq >::ModelMeaslesMixing (
```

```

ModelMeaslesMixing< TSeq > & model,
epiworld_fast_uint n,
epiworld_double prevalence,
epiworld_double contact_rate,
epiworld_double transmission_rate,
epiworld_double vax_efficacy,
epiworld_double vax_reduction_recovery_rate,
epiworld_double incubation_period,
epiworld_double prodromal_period,
epiworld_double rash_period,
std::vector< double > contact_matrix,
epiworld_double hospitalization_rate,
epiworld_double hospitalization_period,
epiworld_double days_undetected,
epiworld_fast_int quarantine_period,
epiworld_double quarantine_willingness,
epiworld_double isolation_willingness,
epiworld_fast_int isolation_period,
epiworld_double prop_vaccinated,
epiworld_double contact_tracing_success_rate = 1.0,
epiworld_fast_uint contact_tracing_days_prior = 4u) [inline]

```

Constructs a [ModelMeaslesMixing](#) object.

Template for a Measles model with population mixing, quarantine, and contact tracing.

#### Parameters

<i>model</i>	A reference to an existing <a href="#">ModelMeaslesMixing</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>vax_efficacy</i>	The efficacy of the vaccine.
<i>vax_reduction_recovery_rate</i>	The reduction in recovery rate due to the vaccine.
<i>incubation_period</i>	The incubation period of the disease in the model.
<i>prodromal_period</i>	The prodromal period of the disease in the model.
<i>rash_period</i>	The rash period of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model. Specified in column-major order.
<i>hospitalization_rate</i>	The rate at which infected individuals are hospitalized.
<i>hospitalization_period</i>	The average duration of hospitalization in days.
<i>days_undetected</i>	The average number of days an infected individual remains undetected.
<i>quarantine_period</i>	The duration of quarantine in days for exposed contacts.
<i>quarantine_willingness</i>	The proportion of individuals willing to comply with quarantine measures.
<i>isolation_willingness</i>	The proportion of individuals willing to self-isolate when detected.
<i>isolation_period</i>	The duration of isolation in days for detected infected individuals.
<i>prop_vaccinated</i>	The proportion of vaccinated agents.
<i>contact_tracing_success_rate</i>	The probability of successfully identifying and tracing contacts (default: 1.0).
<i>contact_tracing_days_prior</i>	The number of days prior to detection for which contacts are traced (default: 4).
<i>model</i>	A <a href="#">ModelMeaslesMixing&lt;TSeq&gt;</a> object where to set up the model.
<i>n</i>	Number of agents in the population
<i>prevalence</i>	Initial prevalence (proportion of infected individuals)

## Parameters

<i>contact_rate</i>	Average number of contacts (interactions) per step
<i>transmission_rate</i>	Probability of transmission per contact
<i>vax_efficacy</i>	The efficacy of the vaccine
<i>vax_reduction_recovery_rate</i>	The reduction in recovery rate due to the vaccine
<i>incubation_period</i>	Average incubation period in days
<i>prodromal_period</i>	Average prodromal period in days
<i>rash_period</i>	Average rash period in days
<i>contact_matrix</i>	Contact matrix specifying mixing patterns between population groups
<i>hospitalization_rate</i>	Rate at which infected individuals are hospitalized
<i>hospitalization_period</i>	Average duration of hospitalization in days
<i>days_undetected</i>	Average number of days an infected individual remains undetected
<i>quarantine_period</i>	Duration of quarantine in days for exposed contacts
<i>quarantine_willingness</i>	Proportion of individuals willing to comply with quarantine
<i>isolation_willingness</i>	Proportion of individuals willing to self-isolate when detected
<i>isolation_period</i>	Duration of isolation in days for detected infected individuals
<i>prop_vaccinated</i>	Proportion of vaccinated agents
<i>contact_tracing_success_rate</i>	Probability of successfully identifying contacts during tracing
<i>contact_tracing_days_prior</i>	Number of days prior to detection for contact tracing

17.29.2.2 `ModelMeaslesMixing()` [2/2]

```
template<typename TSeq >
ModelMeaslesMixing< TSeq >::ModelMeaslesMixing (
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double vax_efficacy,
 epiworld_double vax_reduction_recovery_rate,
 epiworld_double incubation_period,
 epiworld_double prodromal_period,
 epiworld_double rash_period,
 std::vector< double > contact_matrix,
 epiworld_double hospitalization_rate,
 epiworld_double hospitalization_period,
 epiworld_double days_undetected,
 epiworld_fast_int quarantine_period,
 epiworld_double quarantine_willingness,
 epiworld_double isolation_willingness,
 epiworld_fast_int isolation_period,
 epiworld_double prop_vaccinated,
 epiworld_double contact_tracing_success_rate = 1.0,
 epiworld_fast_uint contact_tracing_days_prior = 4u) [inline]
```

Constructs a `ModelMeaslesMixing` object.

## Parameters

<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>vax_efficacy</i>	The efficacy of the vaccine.
<i>vax_reduction_recovery_rate</i>	The reduction in recovery rate due to the vaccine.
<i>incubation_period</i>	The incubation period of the disease in the model.
<i>prodromal_period</i>	The prodromal period of the disease in the model.
<i>rash_period</i>	The rash period of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.
<i>hospitalization_rate</i>	The rate at which infected individuals are hospitalized.
<i>hospitalization_period</i>	The average duration of hospitalization in days.
<i>days_undetected</i>	The average number of days an infected individual remains undetected.
<i>quarantine_period</i>	The duration of quarantine in days for exposed contacts.
<i>quarantine_willingness</i>	The proportion of individuals willing to comply with quarantine measures.
<i>isolation_willingness</i>	The proportion of individuals willing to self-isolate when detected.
<i>isolation_period</i>	The duration of isolation in days for detected infected individuals.
<i>prop_vaccinated</i>	The proportion of vaccinated agents.
<i>contact_tracing_success_rate</i>	The probability of successfully identifying and tracing contacts (default: 1.0).
<i>contact_tracing_days_prior</i>	The number of days prior to detection for which contacts are traced (default: 4).

## 17.29.3 Member Function Documentation

### 17.29.3.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelMeaslesMixing< TSeq >::clone_ptr [inline], [virtual]
```

Create a clone of this model.

#### Returns

Pointer to a new model instance with the same configuration

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.29.3.2 get\_agent\_quarantine\_triggered()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::vector< size_t > epiworld::epimodels::ModelMeaslesMixing< TSeq >::get_agent_quarantine↔
_triggered () const [inline]
```

Get the quarantine trigger status for all agents.

#### Returns

Vector indicating quarantine process status for each agent

### 17.29.3.3 get\_contact\_matrix()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::vector< double > epiworld::epimodels::ModelMeaslesMixing< TSeq >::get_contact_matrix ()
const [inline]
```

Get the current contact matrix.

#### Returns

Vector representing the contact matrix

### 17.29.3.4 get\_isolation\_willingness()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::vector< bool > epiworld::epimodels::ModelMeaslesMixing< TSeq >::get_isolation_willingness
() const [inline]
```

Get the isolation willingness for all agents.

#### Returns

Vector of boolean values indicating each agent's willingness to self-isolate

### 17.29.3.5 get\_quarantine\_willingness()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::vector< bool > epiworld::epimodels::ModelMeaslesMixing< TSeq >::get_quarantine_willingness
() const [inline]
```

Get the quarantine willingness for all agents.

#### Returns

Vector of boolean values indicating each agent's willingness to quarantine

### 17.29.3.6 initial\_states()

```
template<typename TSeq >
ModelMeaslesMixing< TSeq > & ModelMeaslesMixing< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

## Parameters

<i>proportions</i> ↔ —	Double vector with two elements: <ul style="list-style-type: none"> <li>• [0]: The proportion of initially infected individuals who start in the exposed state.</li> <li>• [1]: The proportion of initially non-infected individuals who have recovered (immune).</li> </ul>
<i>queue_</i>	Optional vector for queuing specifications (default: empty).

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

**17.29.3.7 run()**

```
template<typename TSeq >
ModelMeaslesMixing< TSeq > & ModelMeaslesMixing< TSeq >::run (
 epiworld_fast_uint ndays,
 int seed = -1) [inline], [virtual]
```

Run the model simulation.

## Parameters

<i>ndays</i>	Number of days to simulate
<i>seed</i>	Random seed for reproducibility (default: -1 for random seed)

## Returns

Reference to this model instance

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

**17.29.3.8 set\_contact\_matrix()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
void epiworld::epimodels::ModelMeaslesMixing< TSeq >::set_contact_matrix (
 std::vector< double > cmat) [inline]
```

Set the contact matrix for population mixing.

## Parameters

<i>cmat</i>	Contact matrix specifying interaction rates between groups
-------------	------------------------------------------------------------

The documentation for this class was generated from the following file:

- epiworld.hpp



## 17.30 ModelMeaslesMixing< TSeq > Class Template Reference

Measles model with population mixing, quarantine, and contact tracing.

```
#include <measlesmixing.hpp>
```

Inheritance diagram for ModelMeaslesMixing< TSeq >:



Collaboration diagram for ModelMeaslesMixing< TSeq >:



### Public Member Functions

- [ModelMeaslesMixing](#) ([ModelMeaslesMixing](#)< TSeq > &model, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double vax\_↵ efficacy, epiworld\_double vax\_reduction\_recovery\_rate, epiworld\_double incubation\_period, epiworld\_double prodromal\_period, epiworld\_double rash\_period, std::vector< double > contact\_matrix, epiworld\_double hospitalization\_rate, epiworld\_double hospitalization\_period, epiworld\_double days\_undetected, epiworld\_↵ \_fast\_int quarantine\_period, epiworld\_double quarantine\_willingness, epiworld\_double isolation\_willingness, epiworld\_fast\_int isolation\_period, epiworld\_double prop\_vaccinated, epiworld\_double contact\_tracing\_↵ success\_rate=1.0, epiworld\_fast\_uint contact\_tracing\_days\_prior=4u)

Constructs a [ModelMeaslesMixing](#) object.

- [ModelMeaslesMixing](#) (epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double vax\_efficacy, epiworld\_double vax\_reduction\_recovery\_rate, epiworld\_double incubation\_period, epiworld\_double prodromal\_period, epiworld\_double rash\_period, std::vector< double > contact\_matrix, epiworld\_double hospitalization\_rate, epiworld\_double hospitalization\_period, epiworld\_double days\_undetected, epiworld\_fast\_int quarantine\_period, epiworld\_double quarantine\_willingness, epiworld\_double isolation\_willingness, epiworld\_fast\_int isolation\_period, epiworld\_double prop\_vaccinated, epiworld\_double contact\_tracing\_success\_rate=1.0, epiworld\_fast\_int contact\_tracing\_days\_prior=4u)  
*Constructs a [ModelMeaslesMixing](#) object.*
- [ModelMeaslesMixing](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Run the model simulation.*
- void [reset](#) ()  
*Reset the model to initial state.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Create a clone of this model.*
- [ModelMeaslesMixing](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})  
*Set the initial states of the model.*
- void [set\\_contact\\_matrix](#) (std::vector< double > cmat)  
*Set the contact matrix for population mixing.*
- std::vector< double > [get\\_contact\\_matrix](#) () const  
*Get the current contact matrix.*
- std::vector< size\_t > [get\\_agent\\_quarantine\\_triggered](#) () const  
*Get the quarantine trigger status for all agents.*
- std::vector< bool > [get\\_quarantine\\_willingness](#) () const  
*Get the quarantine willingness for all agents.*
- std::vector< bool > [get\\_isolation\\_willingness](#) () const  
*Get the isolation willingness for all agents.*

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **PRODROMAL** = 2
- static const int **RASH** = 3
- static const int **ISOLATED** = 4
- static const int **ISOLATED\_RECOVERED** = 5
- static const int **DETECTED\_HOSPITALIZED** = 6
- static const int **QUARANTINED\_EXPOSED** = 7
- static const int **QUARANTINED\_SUSCEPTIBLE** = 8
- static const int **QUARANTINED\_PRODROMAL** = 9
- static const int **QUARANTINED\_RECOVERED** = 10
- static const int **HOSPITALIZED** = 11
- static const int **RECOVERED** = 12
- static const size\_t **QUARANTINE\_PROCESS\_INACTIVE** = 0u
- static const size\_t **QUARANTINE\_PROCESS\_ACTIVE** = 1u
- static const size\_t **QUARANTINE\_PROCESS\_DONE** = 2u

## Additional Inherited Members

### 17.30.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelMeaslesMixing< TSeq >
```

Measles model with population mixing, quarantine, and contact tracing.

This class implements a Measles epidemiological model based on the SEIR framework with additional features including:

- Population mixing based on contact matrices
- Measles-specific disease progression: Susceptible → Exposed → Prodromal → Rash
- Prodromal individuals are infectious (replace the "Infected" state in SEIR)
- Rash individuals are no longer infectious but can be detected for isolation
- Quarantine measures for exposed contacts during contact tracing
- Isolation policies for detected individuals during the rash state
- Contact tracing with configurable success rates
- Hospitalization of severe cases
- Individual willingness to comply with public health measures

The model supports 13 distinct states:

- Susceptible: Individuals who can become infected
- Exposed: Infected but not yet infectious (incubation period)
- Prodromal: Infectious individuals in the community (replaces "Infected" in SEIR)
- Rash: Non-infectious individuals with visible symptoms (detection occurs here)
- Isolated: Detected individuals in self-isolation
- Isolated Recovered: Recovered individuals still in isolation
- Detected Hospitalized: Hospitalized individuals who were contact-traced
- Quarantined Exposed: Exposed individuals in quarantine due to contact tracing
- Quarantined Susceptible: Susceptible individuals in quarantine due to contact tracing
- Quarantined Prodromal: Prodromal individuals in quarantine due to contact tracing
- Quarantined Recovered: Recovered individuals in quarantine due to contact tracing
- Hospitalized: Individuals requiring hospital care
- Recovered: Individuals who have recovered and gained immunity

## Template Parameters

<i>TSeq</i>	Type for genetic sequences (default: EPI_DEFAULT_TSEQ)
-------------	--------------------------------------------------------

## 17.30.2 Constructor &amp; Destructor Documentation

## 17.30.2.1 ModelMeaslesMixing() [1/2]

```
template<typename TSeq >
ModelMeaslesMixing< TSeq >::ModelMeaslesMixing (
 ModelMeaslesMixing< TSeq > & model,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double vax_efficacy,
 epiworld_double vax_reduction_recovery_rate,
 epiworld_double incubation_period,
 epiworld_double prodromal_period,
 epiworld_double rash_period,
 std::vector< double > contact_matrix,
 epiworld_double hospitalization_rate,
 epiworld_double hospitalization_period,
 epiworld_double days_undetected,
 epiworld_fast_int quarantine_period,
 epiworld_double quarantine_willingness,
 epiworld_double isolation_willingness,
 epiworld_fast_int isolation_period,
 epiworld_double prop_vaccinated,
 epiworld_double contact_tracing_success_rate = 1.0,
 epiworld_fast_uint contact_tracing_days_prior = 4u) [inline]
```

Constructs a [ModelMeaslesMixing](#) object.

Template for a Measles model with population mixing, quarantine, and contact tracing.

## Parameters

<i>model</i>	A reference to an existing <a href="#">ModelMeaslesMixing</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>vax_efficacy</i>	The efficacy of the vaccine.
<i>vax_reduction_recovery_rate</i>	The reduction in recovery rate due to the vaccine.
<i>incubation_period</i>	The incubation period of the disease in the model.
<i>prodromal_period</i>	The prodromal period of the disease in the model.
<i>rash_period</i>	The rash period of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model. Specified in column-major order.

## Parameters

<i>hospitalization_rate</i>	The rate at which infected individuals are hospitalized.
<i>hospitalization_period</i>	The average duration of hospitalization in days.
<i>days_undetected</i>	The average number of days an infected individual remains undetected.
<i>quarantine_period</i>	The duration of quarantine in days for exposed contacts.
<i>quarantine_willingness</i>	The proportion of individuals willing to comply with quarantine measures.
<i>isolation_willingness</i>	The proportion of individuals willing to self-isolate when detected.
<i>isolation_period</i>	The duration of isolation in days for detected infected individuals.
<i>prop_vaccinated</i>	The proportion of vaccinated agents.
<i>contact_tracing_success_rate</i>	The probability of successfully identifying and tracing contacts (default: 1.0).
<i>contact_tracing_days_prior</i>	The number of days prior to detection for which contacts are traced (default: 4).
<i>model</i>	A ModelMeaslesMixing<TSeq> object where to set up the model.
<i>n</i>	Number of agents in the population
<i>prevalence</i>	Initial prevalence (proportion of infected individuals)
<i>contact_rate</i>	Average number of contacts (interactions) per step
<i>transmission_rate</i>	Probability of transmission per contact
<i>vax_efficacy</i>	The efficacy of the vaccine
<i>vax_reduction_recovery_rate</i>	The reduction in recovery rate due to the vaccine
<i>incubation_period</i>	Average incubation period in days
<i>prodromal_period</i>	Average prodromal period in days
<i>rash_period</i>	Average rash period in days
<i>contact_matrix</i>	Contact matrix specifying mixing patterns between population groups
<i>hospitalization_rate</i>	Rate at which infected individuals are hospitalized
<i>hospitalization_period</i>	Average duration of hospitalization in days
<i>days_undetected</i>	Average number of days an infected individual remains undetected
<i>quarantine_period</i>	Duration of quarantine in days for exposed contacts
<i>quarantine_willingness</i>	Proportion of individuals willing to comply with quarantine
<i>isolation_willingness</i>	Proportion of individuals willing to self-isolate when detected
<i>isolation_period</i>	Duration of isolation in days for detected infected individuals
<i>prop_vaccinated</i>	Proportion of vaccinated agents
<i>contact_tracing_success_rate</i>	Probability of successfully identifying contacts during tracing
<i>contact_tracing_days_prior</i>	Number of days prior to detection for contact tracing

## 17.30.2.2 ModelMeaslesMixing() [2/2]

```
template<typename TSeq >
ModelMeaslesMixing< TSeq >::ModelMeaslesMixing (
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double vax_efficacy,
 epiworld_double vax_reduction_recovery_rate,
 epiworld_double incubation_period,
 epiworld_double prodromal_period,
```

```

epiworld_double rash_period,
std::vector< double > contact_matrix,
epiworld_double hospitalization_rate,
epiworld_double hospitalization_period,
epiworld_double days_undetected,
epiworld_fast_int quarantine_period,
epiworld_double quarantine_willingness,
epiworld_double isolation_willingness,
epiworld_fast_int isolation_period,
epiworld_double prop_vaccinated,
epiworld_double contact_tracing_success_rate = 1.0,
epiworld_fast_uint contact_tracing_days_prior = 4u) [inline]

```

Constructs a [ModelMeaslesMixing](#) object.

#### Parameters

<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>vax_efficacy</i>	The efficacy of the vaccine.
<i>vax_reduction_recovery_rate</i>	The reduction in recovery rate due to the vaccine.
<i>incubation_period</i>	The incubation period of the disease in the model.
<i>prodromal_period</i>	The prodromal period of the disease in the model.
<i>rash_period</i>	The rash period of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.
<i>hospitalization_rate</i>	The rate at which infected individuals are hospitalized.
<i>hospitalization_period</i>	The average duration of hospitalization in days.
<i>days_undetected</i>	The average number of days an infected individual remains undetected.
<i>quarantine_period</i>	The duration of quarantine in days for exposed contacts.
<i>quarantine_willingness</i>	The proportion of individuals willing to comply with quarantine measures.
<i>isolation_willingness</i>	The proportion of individuals willing to self-isolate when detected.
<i>isolation_period</i>	The duration of isolation in days for detected infected individuals.
<i>prop_vaccinated</i>	The proportion of vaccinated agents.
<i>contact_tracing_success_rate</i>	The probability of successfully identifying and tracing contacts (default: 1.0).
<i>contact_tracing_days_prior</i>	The number of days prior to detection for which contacts are traced (default: 4).

## 17.30.3 Member Function Documentation

### 17.30.3.1 clone\_ptr()

```

template<typename TSeq >
Model< TSeq > * ModelMeaslesMixing< TSeq >::clone_ptr [inline], [virtual]

```

Create a clone of this model.

**Returns**

Pointer to a new model instance with the same configuration

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

**17.30.3.2 get\_agent\_quarantine\_triggered()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::vector< size_t > ModelMeaslesMixing< TSeq >::get_agent_quarantine_triggered () const
[inline]
```

Get the quarantine trigger status for all agents.

**Returns**

Vector indicating quarantine process status for each agent

**17.30.3.3 get\_contact\_matrix()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::vector< double > ModelMeaslesMixing< TSeq >::get_contact_matrix () const [inline]
```

Get the current contact matrix.

**Returns**

Vector representing the contact matrix

**17.30.3.4 get\_isolation\_willingness()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::vector< bool > ModelMeaslesMixing< TSeq >::get_isolation_willingness () const [inline]
```

Get the isolation willingness for all agents.

**Returns**

Vector of boolean values indicating each agent's willingness to self-isolate

### 17.30.3.5 get\_quarantine\_willingness()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
std::vector< bool > ModelMeaslesMixing< TSeq >::get_quarantine_willingness () const [inline]
```

Get the quarantine willingness for all agents.

#### Returns

Vector of boolean values indicating each agent's willingness to quarantine

### 17.30.3.6 initial\_states()

```
template<typename TSeq >
ModelMeaslesMixing< TSeq > & ModelMeaslesMixing< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

#### Parameters

<i>proportions_</i>	Double vector with two elements: <ul style="list-style-type: none"> <li>[0]: The proportion of initially infected individuals who start in the exposed state.</li> <li>[1]: The proportion of initially non-infected individuals who have recovered (immune).</li> </ul>
<i>queue_</i>	Optional vector for queuing specifications (default: empty).

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.30.3.7 run()

```
template<typename TSeq >
ModelMeaslesMixing< TSeq > & ModelMeaslesMixing< TSeq >::run (
 epiworld_fast_uint ndays,
 int seed = -1) [inline], [virtual]
```

Run the model simulation.

#### Parameters

<i>ndays</i>	Number of days to simulate
<i>seed</i>	Random seed for reproducibility (default: -1 for random seed)



**Returns**

Reference to this model instance

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

**17.30.3.8 set\_contact\_matrix()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
void ModelMeaslesMixing< TSeq >::set_contact_matrix (
 std::vector< double > cmat) [inline]
```

Set the contact matrix for population mixing.

**Parameters**

<i>cmat</i>	Contact matrix specifying interaction rates between groups
-------------	------------------------------------------------------------

The documentation for this class was generated from the following file:

- [include/epiworld/models/measlesmixing.hpp](#)

## 17.31 epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq > Class Template Reference

Measles model with population mixing and risk-based quarantine strategies.

```
#include <epiworld.hpp>
```

Inheritance diagram for epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >:



Collaboration diagram for `epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >`:



## Public Member Functions

- [ModelMeaslesMixingRiskQuarantine](#) ([ModelMeaslesMixingRiskQuarantine](#)< TSeq > &model, epiworld\_↵  
\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_↵  
rate, epiworld\_double vax\_efficacy, epiworld\_double incubation\_period, epiworld\_double prodromal\_period,  
epiworld\_double rash\_period, std::vector< double > contact\_matrix, epiworld\_double hospitalization\_rate,  
epiworld\_double hospitalization\_period, epiworld\_double days\_undetected, epiworld\_fast\_int quarantine\_↵  
\_period\_high, epiworld\_fast\_int quarantine\_period\_medium, epiworld\_fast\_int quarantine\_period\_low,  
epiworld\_double quarantine\_willingness, epiworld\_double isolation\_willingness, epiworld\_fast\_int isolation\_↵  
\_period, epiworld\_double prop\_vaccinated, epiworld\_double detection\_rate\_quarantine, epiworld\_double  
contact\_tracing\_success\_rate=1.0, epiworld\_fast\_uint contact\_tracing\_days\_prior=4u)  
*Constructs a [ModelMeaslesMixingRiskQuarantine](#) object.*
- [ModelMeaslesMixingRiskQuarantine](#) (epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_↵  
double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double vax\_efficacy, epiworld\_double  
incubation\_period, epiworld\_double prodromal\_period, epiworld\_double rash\_period, std::vector< double >  
contact\_matrix, epiworld\_double hospitalization\_rate, epiworld\_double hospitalization\_period, epiworld\_↵  
double days\_undetected, epiworld\_fast\_int quarantine\_period\_high, epiworld\_fast\_int quarantine\_period\_↵  
medium, epiworld\_fast\_int quarantine\_period\_low, epiworld\_double quarantine\_willingness, epiworld\_double  
isolation\_willingness, epiworld\_fast\_int isolation\_period, epiworld\_double prop\_vaccinated, epiworld\_↵  
double detection\_rate\_quarantine, epiworld\_double contact\_tracing\_success\_rate=1.0, epiworld\_fast\_uint  
contact\_tracing\_days\_prior=4u)  
*Constructs a [ModelMeaslesMixingRiskQuarantine](#) object.*
- [ModelMeaslesMixingRiskQuarantine](#)< TSeq > &run (epiworld\_fast\_uint ndays, int seed=-1)  
*Run the model simulation.*
- void [reset](#) ()  
*Reset the model to initial state.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Create a clone of this model.*
- [ModelMeaslesMixingRiskQuarantine](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std\_↵  
::vector< int > queue\_={})  
*Set the initial states of the model.*
- void [set\\_contact\\_matrix](#) (std::vector< double > cmat)  
*Set the contact matrix for population mixing.*
- auto [get\\_contact\\_matrix](#) () const  
*Get the current contact matrix.*

- auto [get\\_quarantine\\_willingness](#) () const  
*Get the quarantine willingness for all agents.*
- auto [get\\_isolation\\_willingness](#) () const  
*Get the isolation willingness for all agents.*
- const auto & [get\\_quarantine\\_risk\\_level](#) () const  
*Get the risk level assigned to each agent for quarantine purposes.*
- auto [get\\_days\\_quarantine\\_triggered](#) () const  
*Get the total number of quarantines that have occurred.*

## Static Public Attributes

- static constexpr int **SUSCEPTIBLE** = 0
- static constexpr int **EXPOSED** = 1
- static constexpr int **PRODROMAL** = 2
- static constexpr int **RASH** = 3
- static constexpr int **ISOLATED** = 4
- static constexpr int **ISOLATED\_RECOVERED** = 5
- static constexpr int **DETECTED\_HOSPITALIZED** = 6
- static constexpr int **QUARANTINED\_EXPOSED** = 7
- static constexpr int **QUARANTINED\_SUSCEPTIBLE** = 8
- static constexpr int **QUARANTINED\_PRODROMAL** = 9
- static constexpr int **QUARANTINED\_RECOVERED** = 10
- static constexpr int **HOSPITALIZED** = 11
- static constexpr int **RECOVERED** = 12
- static constexpr size\_t **QUARANTINE\_PROCESS\_INACTIVE** = 0u
- static constexpr size\_t **QUARANTINE\_PROCESS\_ACTIVE** = 1u
- static constexpr size\_t **QUARANTINE\_PROCESS\_DONE** = 2u
- static constexpr int **RISK\_LOW** = 0
- static constexpr int **RISK\_MEDIUM** = 1
- static constexpr int **RISK\_HIGH** = 2

## Additional Inherited Members

### 17.31.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >
```

Measles model with population mixing and risk-based quarantine strategies.

This class extends the Measles epidemiological model to support different quarantine strategies based on exposure risk levels:

- **High Risk:** Unvaccinated agents who share entity membership with the case
- **Medium Risk:** Unvaccinated agents who contacted an infected individual but don't share entity membership
- **Low Risk:** Other unvaccinated agents

Each risk level can have different quarantine durations, allowing for targeted public health interventions. The model also includes enhanced detection during active quarantine periods.

Disease progression follows the same states as [ModelMeaslesMixing](#): Susceptible → Exposed → Prodromal → Rash → Recovered

## Template Parameters

<i>TSeq</i>	Type for genetic sequences (default: EPI_DEFAULT_TSEQ)
-------------	--------------------------------------------------------

## 17.31.2 Constructor &amp; Destructor Documentation

## 17.31.2.1 ModelMeaslesMixingRiskQuarantine() [1/2]

```
template<typename TSeq >
ModelMeaslesMixingRiskQuarantine< TSeq >::ModelMeaslesMixingRiskQuarantine (
 ModelMeaslesMixingRiskQuarantine< TSeq > & model,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double vax_efficacy,
 epiworld_double incubation_period,
 epiworld_double prodromal_period,
 epiworld_double rash_period,
 std::vector< double > contact_matrix,
 epiworld_double hospitalization_rate,
 epiworld_double hospitalization_period,
 epiworld_double days_undetected,
 epiworld_fast_int quarantine_period_high,
 epiworld_fast_int quarantine_period_medium,
 epiworld_fast_int quarantine_period_low,
 epiworld_double quarantine_willingness,
 epiworld_double isolation_willingness,
 epiworld_fast_int isolation_period,
 epiworld_double prop_vaccinated,
 epiworld_double detection_rate_quarantine,
 epiworld_double contact_tracing_success_rate = 1.0,
 epiworld_fast_uint contact_tracing_days_prior = 4u) [inline]
```

Constructs a [ModelMeaslesMixingRiskQuarantine](#) object.

## Parameters

<i>model</i>	A reference to an existing <a href="#">ModelMeaslesMixingRiskQuarantine</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>vax_efficacy</i>	The efficacy of the vaccine.
<i>incubation_period</i>	The incubation period of the disease in the model.
<i>prodromal_period</i>	The prodromal period of the disease in the model.
<i>rash_period</i>	The rash period of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model. Specified in column-major order.
<i>hospitalization_rate</i>	The rate at which infected individuals are hospitalized.

## Parameters

<i>hospitalization_period</i>	The average duration of hospitalization in days.
<i>days_undetected</i>	The average number of days an infected individual remains undetected.
<i>quarantine_period_high</i>	The duration of quarantine in days for high-risk contacts.
<i>quarantine_period_medium</i>	The duration of quarantine in days for medium-risk contacts.
<i>quarantine_period_low</i>	The duration of quarantine in days for low-risk contacts.
<i>quarantine_willingness</i>	The proportion of individuals willing to comply with quarantine measures.
<i>isolation_willingness</i>	The proportion of individuals willing to self-isolate when detected.
<i>isolation_period</i>	The duration of isolation in days for detected infected individuals.
<i>prop_vaccinated</i>	The proportion of vaccinated agents.
<i>detection_rate_quarantine</i>	The detection rate during active quarantine periods.
<i>contact_tracing_success_rate</i>	The probability of successfully identifying and tracing contacts (default: 1.0).
<i>contact_tracing_days_prior</i>	The number of days prior to detection for which contacts are traced (default: 4).

17.31.2.2 `ModelMeaslesMixingRiskQuarantine()` [2/2]

```
template<typename TSeq >
ModelMeaslesMixingRiskQuarantine< TSeq >::ModelMeaslesMixingRiskQuarantine (
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double vax_efficacy,
 epiworld_double incubation_period,
 epiworld_double prodromal_period,
 epiworld_double rash_period,
 std::vector< double > contact_matrix,
 epiworld_double hospitalization_rate,
 epiworld_double hospitalization_period,
 epiworld_double days_undetected,
 epiworld_fast_int quarantine_period_high,
 epiworld_fast_int quarantine_period_medium,
 epiworld_fast_int quarantine_period_low,
 epiworld_double quarantine_willingness,
 epiworld_double isolation_willingness,
 epiworld_fast_int isolation_period,
 epiworld_double prop_vaccinated,
 epiworld_double detection_rate_quarantine,
 epiworld_double contact_tracing_success_rate = 1.0,
 epiworld_fast_uint contact_tracing_days_prior = 4u) [inline]
```

Constructs a `ModelMeaslesMixingRiskQuarantine` object.

## Parameters

<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.

## Parameters

<i>vax_efficacy</i>	The efficacy of the vaccine.
<i>incubation_period</i>	The incubation period of the disease in the model.
<i>prodromal_period</i>	The prodromal period of the disease in the model.
<i>rash_period</i>	The rash period of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.
<i>hospitalization_rate</i>	The rate at which infected individuals are hospitalized.
<i>hospitalization_period</i>	The average duration of hospitalization in days.
<i>days_undetected</i>	The average number of days an infected individual remains undetected.
<i>quarantine_period_high</i>	The duration of quarantine in days for high-risk contacts.
<i>quarantine_period_medium</i>	The duration of quarantine in days for medium-risk contacts.
<i>quarantine_period_low</i>	The duration of quarantine in days for low-risk contacts.
<i>quarantine_willingness</i>	The proportion of individuals willing to comply with quarantine measures.
<i>isolation_willingness</i>	The proportion of individuals willing to self-isolate when detected.
<i>isolation_period</i>	The duration of isolation in days for detected infected individuals.
<i>prop_vaccinated</i>	The proportion of vaccinated agents.
<i>detection_rate_quarantine</i>	The detection rate during active quarantine periods.
<i>contact_tracing_success_rate</i>	The probability of successfully identifying and tracing contacts (default: 1.0).
<i>contact_tracing_days_prior</i>	The number of days prior to detection for which contacts are traced (default: 4).

### 17.31.3 Member Function Documentation

#### 17.31.3.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelMeaslesMixingRiskQuarantine< TSeq >::clone_ptr [inline], [virtual]
```

Create a clone of this model.

##### Returns

Pointer to a new model instance with the same configuration

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

#### 17.31.3.2 get\_contact\_matrix()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
auto epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >::get_contact_matrix ()
const [inline]
```

Get the current contact matrix.

##### Returns

Vector representing the contact matrix

### 17.31.3.3 get\_days\_quarantine\_triggered()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
auto epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >::get_days_quarantine_triggered () const [inline]
```

Get the total number of quarantines that have occurred.

#### Returns

The number of quarantines

### 17.31.3.4 get\_isolation\_willingness()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
auto epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >::get_isolation_willingness () const [inline]
```

Get the isolation willingness for all agents.

#### Returns

Vector of boolean values indicating each agent's willingness to self-isolate

### 17.31.3.5 get\_quarantine\_risk\_level()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
const auto& epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >::get_quarantine_risk_level () const [inline]
```

Get the risk level assigned to each agent for quarantine purposes.

#### Returns

Vector of integers representing risk levels (0=low, 1=medium, 2=high)

### 17.31.3.6 get\_quarantine\_willingness()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
auto epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >::get_quarantine_willingness () const [inline]
```

Get the quarantine willingness for all agents.

#### Returns

Vector of boolean values indicating each agent's willingness to quarantine

### 17.31.3.7 initial\_states()

```
template<typename TSeq >
ModelMeaslesMixingRiskQuarantine< TSeq > & ModelMeaslesMixingRiskQuarantine< TSeq >::initial←
_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

#### Parameters

<i>proportions_</i>	Double vector with two elements:
—	<ul style="list-style-type: none"> <li>• [0]: The proportion of initially infected individuals who start in the exposed state.</li> <li>• [1]: The proportion of initially non-infected individuals who have recovered (immune).</li> </ul>
<i>queue_</i>	Optional vector for queuing specifications (default: empty).

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.31.3.8 run()

```
template<typename TSeq >
ModelMeaslesMixingRiskQuarantine< TSeq > & ModelMeaslesMixingRiskQuarantine< TSeq >::run (
 epiworld_fast_uint ndays,
 int seed = -1) [inline], [virtual]
```

Run the model simulation.

#### Parameters

<i>ndays</i>	Number of days to simulate
<i>seed</i>	Random seed for reproducibility (default: -1 for random seed)

#### Returns

Reference to this model instance

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.31.3.9 set\_contact\_matrix()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
void epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >::set_contact_matrix (
 std::vector< double > cmat) [inline]
```

Set the contact matrix for population mixing.



## Parameters

<i>cmat</i>	Contact matrix specifying interaction rates between groups
-------------	------------------------------------------------------------

The documentation for this class was generated from the following file:


- `epiworld.hpp`

## 17.32 ModelMeaslesMixingRiskQuarantine< TSeq > Class Template Reference


Measles model with population mixing and risk-based quarantine strategies.

```
#include <measlesmixingriskquarantine.hpp>
```

Inheritance diagram for ModelMeaslesMixingRiskQuarantine< TSeq >:



Collaboration diagram for ModelMeaslesMixingRiskQuarantine< TSeq >:



## Public Member Functions

- [ModelMeaslesMixingRiskQuarantine](#) ([ModelMeaslesMixingRiskQuarantine](#)< TSeq > &model, [epiworld](#)↔\_fast\_uint n, [epiworld\\_double](#) prevalence, [epiworld\\_double](#) contact\_rate, [epiworld\\_double](#) transmission\_↔rate, [epiworld\\_double](#) vax\_efficacy, [epiworld\\_double](#) incubation\_period, [epiworld\\_double](#) prodromal\_period, [epiworld\\_double](#) rash\_period, [std::vector](#)< [double](#) > contact\_matrix, [epiworld\\_double](#) hospitalization\_rate, [epiworld\\_double](#) hospitalization\_period, [epiworld\\_double](#) days\_undetected, [epiworld\\_fast\\_int](#) quarantine↔\_period\_high, [epiworld\\_fast\\_int](#) quarantine\_period\_medium, [epiworld\\_fast\\_int](#) quarantine\_period\_low, [epiworld\\_double](#) quarantine\_willingness, [epiworld\\_double](#) isolation\_willingness, [epiworld\\_fast\\_int](#) isolation↔\_period, [epiworld\\_double](#) prop\_vaccinated, [epiworld\\_double](#) detection\_rate\_quarantine, [epiworld\\_double](#) contact\_tracing\_success\_rate=1.0, [epiworld\\_fast\\_uint](#) contact\_tracing\_days\_prior=4u)

Constructs a [ModelMeaslesMixingRiskQuarantine](#) object.

- [ModelMeaslesMixingRiskQuarantine](#) ([epiworld\\_fast\\_uint](#) n, [epiworld\\_double](#) prevalence, [epiworld\\_double](#) contact\_rate, [epiworld\\_double](#) transmission\_rate, [epiworld\\_double](#) vax\_efficacy, [epiworld\\_double](#) incubation\_period, [epiworld\\_double](#) prodromal\_period, [epiworld\\_double](#) rash\_period, [std::vector](#)< [double](#) > contact\_matrix, [epiworld\\_double](#) hospitalization\_rate, [epiworld\\_double](#) hospitalization\_period, [epiworld\\_double](#) days\_undetected, [epiworld\\_fast\\_int](#) quarantine\_period\_high, [epiworld\\_fast\\_int](#) quarantine\_period↔medium, [epiworld\\_fast\\_int](#) quarantine\_period\_low, [epiworld\\_double](#) quarantine\_willingness, [epiworld\\_double](#) isolation\_willingness, [epiworld\\_fast\\_int](#) isolation\_period, [epiworld\\_double](#) prop\_vaccinated, [epiworld\\_double](#) detection\_rate\_quarantine, [epiworld\\_double](#) contact\_tracing\_success\_rate=1.0, [epiworld\\_fast\\_uint](#) contact\_tracing\_days\_prior=4u)

Constructs a [ModelMeaslesMixingRiskQuarantine](#) object.

- [ModelMeaslesMixingRiskQuarantine](#)< TSeq > & [run](#) ([epiworld\\_fast\\_uint](#) ndays, [int](#) seed=-1)

Run the model simulation.

- [void](#) [reset](#) ()

Reset the model to initial state.

- [Model](#)< TSeq > \* [clone\\_ptr](#) ()

Create a clone of this model.

- [ModelMeaslesMixingRiskQuarantine](#)< TSeq > & [initial\\_states](#) ([std::vector](#)< [double](#) > proportions\_, [std::vector](#)< [int](#) > queue\_={})

Set the initial states of the model.

- [void](#) [set\\_contact\\_matrix](#) ([std::vector](#)< [double](#) > cmat)

Set the contact matrix for population mixing.

- [auto](#) [get\\_contact\\_matrix](#) () const

Get the current contact matrix.

- [auto](#) [get\\_quarantine\\_willingness](#) () const

Get the quarantine willingness for all agents.

- [auto](#) [get\\_isolation\\_willingness](#) () const

Get the isolation willingness for all agents.

- [const auto](#) & [get\\_quarantine\\_risk\\_level](#) () const

Get the risk level assigned to each agent for quarantine purposes.

- [auto](#) [get\\_days\\_quarantine\\_triggered](#) () const

Get the total number of quarantines that have occurred.

## Static Public Attributes

- [static constexpr int](#) **SUSCEPTIBLE** = 0
- [static constexpr int](#) **EXPOSED** = 1
- [static constexpr int](#) **PRODROMAL** = 2
- [static constexpr int](#) **RASH** = 3
- [static constexpr int](#) **ISOLATED** = 4
- [static constexpr int](#) **ISOLATED\_RECOVERED** = 5
- [static constexpr int](#) **DETECTED\_HOSPITALIZED** = 6

- static constexpr int **QUARANTINED\_EXPOSED** = 7
- static constexpr int **QUARANTINED\_SUSCEPTIBLE** = 8
- static constexpr int **QUARANTINED\_PRODROMAL** = 9
- static constexpr int **QUARANTINED\_RECOVERED** = 10
- static constexpr int **HOSPITALIZED** = 11
- static constexpr int **RECOVERED** = 12
- static constexpr size\_t **QUARANTINE\_PROCESS\_INACTIVE** = 0u
- static constexpr size\_t **QUARANTINE\_PROCESS\_ACTIVE** = 1u
- static constexpr size\_t **QUARANTINE\_PROCESS\_DONE** = 2u
- static constexpr int **RISK\_LOW** = 0
- static constexpr int **RISK\_MEDIUM** = 1
- static constexpr int **RISK\_HIGH** = 2

## Additional Inherited Members

### 17.32.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelMeaslesMixingRiskQuarantine< TSeq >
```

Measles model with population mixing and risk-based quarantine strategies.

This class extends the Measles epidemiological model to support different quarantine strategies based on exposure risk levels:

- **High Risk:** Unvaccinated agents who share entity membership with the case
- **Medium Risk:** Unvaccinated agents who contacted an infected individual but don't share entity membership
- **Low Risk:** Other unvaccinated agents

Each risk level can have different quarantine durations, allowing for targeted public health interventions. The model also includes enhanced detection during active quarantine periods.

Disease progression follows the same states as [ModelMeaslesMixing](#): Susceptible → Exposed → Prodromal → Rash → Recovered

#### Template Parameters

<i>TSeq</i>	Type for genetic sequences (default: EPI_DEFAULT_TSEQ)
-------------	--------------------------------------------------------

### 17.32.2 Constructor & Destructor Documentation

#### 17.32.2.1 ModelMeaslesMixingRiskQuarantine() [1/2]

```
template<typename TSeq >
ModelMeaslesMixingRiskQuarantine< TSeq >::ModelMeaslesMixingRiskQuarantine (
```

```

ModelMeaslesMixingRiskQuarantine< TSeq > & model,
epiworld_fast_uint n,
epiworld_double prevalence,
epiworld_double contact_rate,
epiworld_double transmission_rate,
epiworld_double vax_efficacy,
epiworld_double incubation_period,
epiworld_double prodromal_period,
epiworld_double rash_period,
std::vector< double > contact_matrix,
epiworld_double hospitalization_rate,
epiworld_double hospitalization_period,
epiworld_double days_undetected,
epiworld_fast_int quarantine_period_high,
epiworld_fast_int quarantine_period_medium,
epiworld_fast_int quarantine_period_low,
epiworld_double quarantine_willingness,
epiworld_double isolation_willingness,
epiworld_fast_int isolation_period,
epiworld_double prop_vaccinated,
epiworld_double detection_rate_quarantine,
epiworld_double contact_tracing_success_rate = 1.0,
epiworld_fast_uint contact_tracing_days_prior = 4u) [inline]

```

Constructs a [ModelMeaslesMixingRiskQuarantine](#) object.

#### Parameters

<i>model</i>	A reference to an existing <a href="#">ModelMeaslesMixingRiskQuarantine</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>vax_efficacy</i>	The efficacy of the vaccine.
<i>incubation_period</i>	The incubation period of the disease in the model.
<i>prodromal_period</i>	The prodromal period of the disease in the model.
<i>rash_period</i>	The rash period of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model. Specified in column-major order.
<i>hospitalization_rate</i>	The rate at which infected individuals are hospitalized.
<i>hospitalization_period</i>	The average duration of hospitalization in days.
<i>days_undetected</i>	The average number of days an infected individual remains undetected.
<i>quarantine_period_high</i>	The duration of quarantine in days for high-risk contacts.
<i>quarantine_period_medium</i>	The duration of quarantine in days for medium-risk contacts.
<i>quarantine_period_low</i>	The duration of quarantine in days for low-risk contacts.
<i>quarantine_willingness</i>	The proportion of individuals willing to comply with quarantine measures.
<i>isolation_willingness</i>	The proportion of individuals willing to self-isolate when detected.
<i>isolation_period</i>	The duration of isolation in days for detected infected individuals.
<i>prop_vaccinated</i>	The proportion of vaccinated agents.
<i>detection_rate_quarantine</i>	The detection rate during active quarantine periods.
<i>contact_tracing_success_rate</i>	The probability of successfully identifying and tracing contacts (default: 1.0).
<i>contact_tracing_days_prior</i>	The number of days prior to detection for which contacts are traced (default: 4).

## 17.32.2.2 ModelMeaslesMixingRiskQuarantine() [2/2]

```

template<typename TSeq >
ModelMeaslesMixingRiskQuarantine< TSeq >::ModelMeaslesMixingRiskQuarantine (
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double vax_efficacy,
 epiworld_double incubation_period,
 epiworld_double prodromal_period,
 epiworld_double rash_period,
 std::vector< double > contact_matrix,
 epiworld_double hospitalization_rate,
 epiworld_double hospitalization_period,
 epiworld_double days_undetected,
 epiworld_fast_int quarantine_period_high,
 epiworld_fast_int quarantine_period_medium,
 epiworld_fast_int quarantine_period_low,
 epiworld_double quarantine_willingness,
 epiworld_double isolation_willingness,
 epiworld_fast_int isolation_period,
 epiworld_double prop_vaccinated,
 epiworld_double detection_rate_quarantine,
 epiworld_double contact_tracing_success_rate = 1.0,
 epiworld_fast_uint contact_tracing_days_prior = 4u) [inline]

```

Constructs a [ModelMeaslesMixingRiskQuarantine](#) object.

## Parameters

<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>vax_efficacy</i>	The efficacy of the vaccine.
<i>incubation_period</i>	The incubation period of the disease in the model.
<i>prodromal_period</i>	The prodromal period of the disease in the model.
<i>rash_period</i>	The rash period of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.
<i>hospitalization_rate</i>	The rate at which infected individuals are hospitalized.
<i>hospitalization_period</i>	The average duration of hospitalization in days.
<i>days_undetected</i>	The average number of days an infected individual remains undetected.
<i>quarantine_period_high</i>	The duration of quarantine in days for high-risk contacts.
<i>quarantine_period_medium</i>	The duration of quarantine in days for medium-risk contacts.
<i>quarantine_period_low</i>	The duration of quarantine in days for low-risk contacts.
<i>quarantine_willingness</i>	The proportion of individuals willing to comply with quarantine measures.
<i>isolation_willingness</i>	The proportion of individuals willing to self-isolate when detected.
<i>isolation_period</i>	The duration of isolation in days for detected infected individuals.
<i>prop_vaccinated</i>	The proportion of vaccinated agents.
<i>detection_rate_quarantine</i>	The detection rate during active quarantine periods.
<i>contact_tracing_success_rate</i>	The probability of successfully identifying and tracing contacts (default: 1.0).
<i>contact_tracing_days_prior</i>	The number of days prior to detection for which contacts are traced (default: 4).

## 17.32.3 Member Function Documentation

### 17.32.3.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelMeaslesMixingRiskQuarantine< TSeq >::clone_ptr [inline], [virtual]
```

Create a clone of this model.

#### Returns

Pointer to a new model instance with the same configuration

Reimplemented from [Model< TSeq >](#).

### 17.32.3.2 get\_contact\_matrix()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
auto ModelMeaslesMixingRiskQuarantine< TSeq >::get_contact_matrix () const [inline]
```

Get the current contact matrix.

#### Returns

Vector representing the contact matrix

### 17.32.3.3 get\_days\_quarantine\_triggered()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
auto ModelMeaslesMixingRiskQuarantine< TSeq >::get_days_quarantine_triggered () const [inline]
```

Get the total number of quarantines that have occurred.

#### Returns

The number of quarantines

**17.32.3.4 get\_isolation\_willingness()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
auto ModelMeaslesMixingRiskQuarantine< TSeq >::get_isolation_willingness () const [inline]
```

Get the isolation willingness for all agents.

**Returns**

Vector of boolean values indicating each agent's willingness to self-isolate

**17.32.3.5 get\_quarantine\_risk\_level()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
const auto& ModelMeaslesMixingRiskQuarantine< TSeq >::get_quarantine_risk_level () const
[inline]
```

Get the risk level assigned to each agent for quarantine purposes.

**Returns**

Vector of integers representing risk levels (0=low, 1=medium, 2=high)

**17.32.3.6 get\_quarantine\_willingness()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
auto ModelMeaslesMixingRiskQuarantine< TSeq >::get_quarantine_willingness () const [inline]
```

Get the quarantine willingness for all agents.

**Returns**

Vector of boolean values indicating each agent's willingness to quarantine

**17.32.3.7 initial\_states()**

```
template<typename TSeq >
ModelMeaslesMixingRiskQuarantine< TSeq > & ModelMeaslesMixingRiskQuarantine< TSeq >::initial←
_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

## Parameters

<i>proportions</i> ↔ —	Double vector with two elements: <ul style="list-style-type: none"> <li>• [0]: The proportion of initially infected individuals who start in the exposed state.</li> <li>• [1]: The proportion of initially non-infected individuals who have recovered (immune).</li> </ul>
<i>queue_</i>	Optional vector for queuing specifications (default: empty).

Reimplemented from [Model< TSeq >](#).

**17.32.3.8 run()**

```
template<typename TSeq >
ModelMeaslesMixingRiskQuarantine< TSeq > & ModelMeaslesMixingRiskQuarantine< TSeq >::run (
 epiworld_fast_uint ndays,
 int seed = -1) [inline], [virtual]
```

Run the model simulation.

## Parameters

<i>ndays</i>	Number of days to simulate
<i>seed</i>	Random seed for reproducibility (default: -1 for random seed)

## Returns

Reference to this model instance

Reimplemented from [Model< TSeq >](#).

**17.32.3.9 set\_contact\_matrix()**

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
void ModelMeaslesMixingRiskQuarantine< TSeq >::set_contact_matrix (
 std::vector< double > cmat) [inline]
```

Set the contact matrix for population mixing.

## Parameters

<i>cmat</i>	Contact matrix specifying interaction rates between groups
-------------	------------------------------------------------------------

The documentation for this class was generated from the following file:

- include/epiworld/models/[measlesmixingriskquarantine.hpp](#)



## 17.33 epiworld::epimodels::ModelMeaslesSchool< TSeq > Class Template Reference

Template for a Measles model with quarantine.

```
#include <epiworld.hpp>
```

Inheritance diagram for epiworld::epimodels::ModelMeaslesSchool< TSeq >:



Collaboration diagram for epiworld::epimodels::ModelMeaslesSchool< TSeq >:



### Public Member Functions

- void [quarantine\\_agents](#) ()  
*Quarantine agents that are in the system.*
- void [reset](#) ()  
*Reset the model.*
- void [update\\_infectious](#) ()

- [Model](#)< TSeq > \* [clone\\_ptr](#) ()

*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*

- [ModelMeaslesSchool](#) ([ModelMeaslesSchool](#)< TSeq > &model, [epiworld\\_fast\\_uint](#) n, [epiworld\\_fast\\_uint](#) n\_exposed, [epiworld\\_double](#) contact\_rate, [epiworld\\_double](#) transmission\_rate, [epiworld\\_double](#) vax\_↵\_efficacy, [epiworld\\_double](#) vax\_reduction\_recovery\_rate, [epiworld\\_double](#) incubation\_period, [epiworld\\_↵\\_double](#) prodromal\_period, [epiworld\\_double](#) rash\_period, [epiworld\\_double](#) days\_undetected, [epiworld\\_double](#) hospitalization\_rate, [epiworld\\_double](#) hospitalization\_period, [epiworld\\_double](#) prop\_vaccinated, [epiworld\\_↵\\_fast\\_int](#) quarantine\_period, [epiworld\\_double](#) quarantine\_willingness, [epiworld\\_fast\\_int](#) isolation\_period)
- **ModelMeaslesSchool** ([epiworld\\_fast\\_uint](#) n, [epiworld\\_fast\\_uint](#) n\_exposed, [epiworld\\_double](#) contact\_↵\_rate, [epiworld\\_double](#) transmission\_rate, [epiworld\\_double](#) vax\_efficacy, [epiworld\\_double](#) vax\_reduction\_↵\_recovery\_rate, [epiworld\\_double](#) incubation\_period, [epiworld\\_double](#) prodromal\_period, [epiworld\\_double](#) rash\_period, [epiworld\\_double](#) days\_undetected, [epiworld\\_double](#) hospitalization\_rate, [epiworld\\_double](#) hospitalization\_period, [epiworld\\_double](#) prop\_vaccinated, [epiworld\\_fast\\_int](#) quarantine\_period, [epiworld\\_↵\\_double](#) quarantine\_willingness, [epiworld\\_fast\\_int](#) isolation\_period)

## Public Attributes

- [std::vector](#)< [Agent](#)< TSeq > \* > [infectious](#)  
*Agents infectious for contact.*
- [bool](#) **system\_quarantine\_triggered** = false
- [std::vector](#)< [int](#) > [day\\_flagged](#)  
*Either detected or started quarantine.*
- [std::vector](#)< [int](#) > [day\\_rash\\_onset](#)  
*Day of rash onset.*

## Static Public Attributes

- [static constexpr](#) [epiworld\\_fast\\_uint](#) **SUSCEPTIBLE** = 0u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **EXPOSED** = 1u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **PRODROMAL** = 2u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **RASH** = 3u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **ISOLATED** = 4u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **ISOLATED\_RECOVERED** = 5u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **DETECTED\_HOSPITALIZED** = 6u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **QUARANTINED\_EXPOSED** = 7u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **QUARANTINED\_SUSCEPTIBLE** = 8u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **QUARANTINED\_PRODROMAL** = 9u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **QUARANTINED\_RECOVERED** = 10u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **HOSPITALIZED** = 11u
- [static constexpr](#) [epiworld\\_fast\\_uint](#) **RECOVERED** = 12u

## Additional Inherited Members

### 17.33.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelMeaslesSchool< TSeq >
```

Template for a Measles model with quarantine.

## Parameters

<i>TSeq</i>	The type of the sequence to be used.
-------------	--------------------------------------

This model can be described as a SEIHR model with isolation and quarantine. The infectious state is divided into prodromal and rash phases. Furthermore, the quarantine state includes exposed, susceptible, prodromal, and recovered states.

The quarantine process is triggered any time that an agent with rash is detected. The agent is then isolated and all agents who are unvaccinated are quarantined. Isolated agents then may be moved out of the isolation in `isolation_↵_period` days.

## 17.33.2 Constructor & Destructor Documentation

### 17.33.2.1 ModelMeaslesSchool()

```
template<typename TSeq >
ModelMeaslesSchool< TSeq >::ModelMeaslesSchool (
 ModelMeaslesSchool< TSeq > & model,
 epiworld_fast_uint n,
 epiworld_fast_uint n_exposed,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double vax_efficacy,
 epiworld_double vax_reduction_recovery_rate,
 epiworld_double incubation_period,
 epiworld_double prodromal_period,
 epiworld_double rash_period,
 epiworld_double days_undetected,
 epiworld_double hospitalization_rate,
 epiworld_double hospitalization_period,
 epiworld_double prop_vaccinated,
 epiworld_fast_int quarantine_period,
 epiworld_double quarantine_willingness,
 epiworld_fast_int isolation_period) [inline]
```

## Parameters

<i>n</i>	The number of agents in the system.
<i>n_exposed</i>	The number of exposed agents in the system.
<i>contact_rate</i>	The rate of contact between agents.
<i>transmission_rate</i>	The rate of transmission of the virus.
<i>vax_efficacy</i>	The efficacy of the vaccine.
<i>vax_reduction_recovery_rate</i>	The reduction in recovery rate due to the vaccine.
<i>incubation_period</i>	The incubation period of the virus.
<i>prodromal_period</i>	The prodromal period of the virus.
<i>rash_period</i>	The rash period of the virus.
<i>days_undetected</i>	The number of days the virus goes undetected.
<i>hospitalization_rate</i>	The rate of hospitalization.

## Parameters

<i>hospitalization_period</i>	The duration of hospitalization.
<i>prop_vaccinated</i>	The proportion of vaccinated agents.
<i>quarantine_period</i>	The number of days for quarantine.
<i>quarantine_willingness</i>	The willingness to be quarantined.
<i>isolation_period</i>	The number of days for isolation.

### 17.33.3 Member Function Documentation

#### 17.33.3.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelMeaslesSchool< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

## Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

#### 17.33.3.2 quarantine\_agents()

```
template<typename TSeq >
void ModelMeaslesSchool< TSeq >::quarantine_agents [inline]
```

Quarantine agents that are in the system.

The flow should be:

- The function only runs if the quarantine status is active.
- Agents who are in quarantine, isolation, removed, or hospitalized are ignored.
- Agents who are in the RASH state are isolated.
- Vaccinated agents are ignored.
- Susceptible, Exposed, and Prodromal agents are moved to the QUARANTINED\_\* state.
- At the end of the function, the quarantine status is set false.

### 17.33.3.3 reset()

```
template<typename TSeq >
void ModelMeaslesSchool< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- `epiworld.hpp`

## 17.34 ModelMeaslesSchool< TSeq > Class Template Reference

Template for a Measles model with quarantine.

```
#include <measlesquarantine.hpp>
```

Inheritance diagram for ModelMeaslesSchool< TSeq >:



Collaboration diagram for ModelMeaslesSchool< TSeq >:



## Public Member Functions

- void [quarantine\\_agents](#) ()  
*Quarantine agents that are in the system.*
- void [reset](#) ()  
*Reset the model.*
- void **update\_infectious** ()
- [Model< TSeq > \\* clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- [ModelMeaslesSchool](#) ([ModelMeaslesSchool< TSeq > &model](#), [epiworld\\_fast\\_uint n](#), [epiworld\\_fast\\_uint n\\_exposed](#), [epiworld\\_double contact\\_rate](#), [epiworld\\_double transmission\\_rate](#), [epiworld\\_double vax\\_↔\\_efficacy](#), [epiworld\\_double vax\\_reduction\\_recovery\\_rate](#), [epiworld\\_double incubation\\_period](#), [epiworld\\_↔\\_double prodromal\\_period](#), [epiworld\\_double rash\\_period](#), [epiworld\\_double days\\_undetected](#), [epiworld\\_double hospitalization\\_rate](#), [epiworld\\_double hospitalization\\_period](#), [epiworld\\_double prop\\_vaccinated](#), [epiworld\\_↔\\_fast\\_int quarantine\\_period](#), [epiworld\\_double quarantine\\_willingness](#), [epiworld\\_fast\\_int isolation\\_period](#))
- **ModelMeaslesSchool** ([epiworld\\_fast\\_uint n](#), [epiworld\\_fast\\_uint n\\_exposed](#), [epiworld\\_double contact\\_↔\\_rate](#), [epiworld\\_double transmission\\_rate](#), [epiworld\\_double vax\\_↔\\_efficacy](#), [epiworld\\_double vax\\_reduction\\_↔\\_recovery\\_rate](#), [epiworld\\_double incubation\\_period](#), [epiworld\\_double prodromal\\_period](#), [epiworld\\_double rash\\_period](#), [epiworld\\_double days\\_undetected](#), [epiworld\\_double hospitalization\\_rate](#), [epiworld\\_double hospitalization\\_period](#), [epiworld\\_double prop\\_vaccinated](#), [epiworld\\_fast\\_int quarantine\\_period](#), [epiworld\\_↔\\_double quarantine\\_willingness](#), [epiworld\\_fast\\_int isolation\\_period](#))

## Public Attributes

- [std::vector< Agent< TSeq > \\* > infectious](#)  
*Agents infectious for contact.*
- bool **system\_quarantine\_triggered** = false
- [std::vector< int > day\\_flagged](#)  
*Either detected or started quarantine.*
- [std::vector< int > day\\_rash\\_onset](#)  
*Day of rash onset.*

## Static Public Attributes

- static constexpr epiworld\_fast\_uint **SUSCEPTIBLE** = 0u
- static constexpr epiworld\_fast\_uint **EXPOSED** = 1u
- static constexpr epiworld\_fast\_uint **PRODROMAL** = 2u
- static constexpr epiworld\_fast\_uint **RASH** = 3u
- static constexpr epiworld\_fast\_uint **ISOLATED** = 4u
- static constexpr epiworld\_fast\_uint **ISOLATED\_RECOVERED** = 5u
- static constexpr epiworld\_fast\_uint **DETECTED\_HOSPITALIZED** = 6u
- static constexpr epiworld\_fast\_uint **QUARANTINED\_EXPOSED** = 7u
- static constexpr epiworld\_fast\_uint **QUARANTINED\_SUSCEPTIBLE** = 8u
- static constexpr epiworld\_fast\_uint **QUARANTINED\_PRODROMAL** = 9u
- static constexpr epiworld\_fast\_uint **QUARANTINED\_RECOVERED** = 10u
- static constexpr epiworld\_fast\_uint **HOSPITALIZED** = 11u
- static constexpr epiworld\_fast\_uint **RECOVERED** = 12u

## Additional Inherited Members

### 17.34.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelMeaslesSchool< TSeq >
```

Template for a Measles model with quarantine.

#### Parameters

<i>TSeq</i>	The type of the sequence to be used.
-------------	--------------------------------------

This model can be described as a SEIHR model with isolation and quarantine. The infectious state is divided into prodromal and rash phases. Furthermore, the quarantine state includes exposed, susceptible, prodromal, and recovered states.

The quarantine process is triggered any time that an agent with rash is detected. The agent is then isolated and all agents who are unvaccinated are quarantined. Isolated agents then may be moved out of the isolation in isolation↔\_period days.

### 17.34.2 Constructor & Destructor Documentation

#### 17.34.2.1 ModelMeaslesSchool()

```
template<typename TSeq >
ModelMeaslesSchool< TSeq >::ModelMeaslesSchool (
 ModelMeaslesSchool< TSeq > & model,
 epiworld_fast_uint n,
 epiworld_fast_uint n_exposed,
 epiworld_double contact_rate,
```

```

epiworld_double transmission_rate,
epiworld_double vax_efficacy,
epiworld_double vax_reduction_recovery_rate,
epiworld_double incubation_period,
epiworld_double prodromal_period,
epiworld_double rash_period,
epiworld_double days_undetected,
epiworld_double hospitalization_rate,
epiworld_double hospitalization_period,
epiworld_double prop_vaccinated,
epiworld_fast_int quarantine_period,
epiworld_double quarantine_willingness,
epiworld_fast_int isolation_period) [inline]

```

#### Parameters

<i>n</i>	The number of agents in the system.
<i>n_exposed</i>	The number of exposed agents in the system.
<i>contact_rate</i>	The rate of contact between agents.
<i>transmission_rate</i>	The rate of transmission of the virus.
<i>vax_efficacy</i>	The efficacy of the vaccine.
<i>vax_reduction_recovery_rate</i>	The reduction in recovery rate due to the vaccine.
<i>incubation_period</i>	The incubation period of the virus.
<i>prodromal_period</i>	The prodromal period of the virus.
<i>rash_period</i>	The rash period of the virus.
<i>days_undetected</i>	The number of days the virus goes undetected.
<i>hospitalization_rate</i>	The rate of hospitalization.
<i>hospitalization_period</i>	The duration of hospitalization.
<i>prop_vaccinated</i>	The proportion of vaccinated agents.
<i>quarantine_period</i>	The number of days for quarantine.
<i>quarantine_willingness</i>	The willingness to be quarantined.
<i>isolation_period</i>	The number of days for isolation.

## 17.34.3 Member Function Documentation

### 17.34.3.1 clone\_ptr()

```

template<typename TSeq >
Model< TSeq > * ModelMeaslesSchool< TSeq >::clone_ptr [inline], [virtual]

```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from [Model< TSeq >](#).



### 17.34.3.2 quarantine\_agents()

```
template<typename TSeq >
void ModelMeaslesSchool< TSeq >::quarantine_agents [inline]
```

Quarantine agents that are in the system.

The flow should be:

- The function only runs if the quarantine status is active.
- Agents who are in quarantine, isolation, removed, or hospitalized are ignored.
- Agents who are in the RASH state are isolated.
- Vaccinated agents are ignored.
- Susceptible, Exposed, and Prodromal agents are moved to the QUARANTINED\_\* state.
- At the end of the function, the quarantine status is set false.

### 17.34.3.3 reset()

```
template<typename TSeq >
void ModelMeaslesSchool< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [Model< TSeq >](#).

The documentation for this class was generated from the following file:

- `include/epiworld/models/measlesquarantine.hpp`

## 17.35 epiworld::epimodels::ModelSEIR< TSeq > Class Template Reference

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

```
#include <epiworld.hpp>
```

Inheritance diagram for epiworld::epimodels::ModelSEIR< TSeq >:



Collaboration diagram for epiworld::epimodels::ModelSEIR< TSeq >:



### Public Member Functions

- **ModelSEIR** ([ModelSEIR](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate↵rate)
- **ModelSEIR** (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate)
- [ModelSEIR](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})

*Set up the initial states of the model.*

## Public Attributes

- epiworld::UpdateFun< TSeq > **update\_exposed\_seir**
- epiworld::UpdateFun< TSeq > **update\_infected\_seir**

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **REMOVED** = 3

## Additional Inherited Members

### 17.35.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelSEIR< TSeq >
```

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	epiworld_double Initial prevalence the immune system
<i>transmission_rate</i>	epiworld_double Transmission rate of the virus
<i>avg_incubation_days</i>	epiworld_double Average incubation days of the virus.
<i>recovery_rate</i>	epiworld_double Recovery rate of the virus.

### 17.35.2 Member Function Documentation

#### 17.35.2.1 initial\_states()

```
template<typename TSeq >
ModelSEIR< TSeq > & ModelSEIR< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set up the initial states of the model.

## Parameters

<i>proportions</i> ↔	Double vector with the following values:
—	<ul style="list-style-type: none"> <li>• 0: Proportion of non-infected agents who are removed.</li> <li>• 1: Proportion of exposed agents to be set as infected.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

## 17.35.3 Member Data Documentation

### 17.35.3.1 update\_exposed\_seir

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
epiworld::UpdateFun<TSeq> epiworld::epimodels::ModelSEIR< TSeq >::update_exposed_seir
```

**Initial value:**

```
= [] (
 epiworld::Agent<TSeq> * p,
 epiworld::Model<TSeq> * m
) -> void {
 auto v = p->get_virus();
 if (m->runif() < 1.0/(v->get_incubation(m)))
 p->change_state(m, ModelSEIR<TSeq>::INFECTED);
 return;
}
```

### 17.35.3.2 update\_infected\_seir

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
epiworld::UpdateFun<TSeq> epiworld::epimodels::ModelSEIR< TSeq >::update_infected_seir
```

**Initial value:**

```
= [] (
 epiworld::Agent<TSeq> * p,
 epiworld::Model<TSeq> * m
) -> void {
 if (m->runif() < (m->par("Recovery rate")))
 p->rm_virus(m);
 return;
}
```

The documentation for this class was generated from the following file:

- [epiworld.hpp](#)

## 17.36 ModelSEIR< TSeq > Class Template Reference

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

```
#include <seir.hpp>
```

Inheritance diagram for ModelSEIR< TSeq >:



Collaboration diagram for ModelSEIR< TSeq >:



### Public Member Functions

- **ModelSEIR** ([ModelSEIR](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate↵rate)
- **ModelSEIR** (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate)
- [ModelSEIR](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})  
*Set up the initial states of the model.*

### Public Attributes

- epiworld::UpdateFun< TSeq > **update\_exposed\_seir**
- epiworld::UpdateFun< TSeq > **update\_infected\_seir**

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **REMOVED** = 3

## Additional Inherited Members

### 17.36.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelSEIR< TSeq >
```

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	epiworld_double Initial prevalence the immune system
<i>transmission_rate</i>	epiworld_double Transmission rate of the virus
<i>avg_incubation_days</i>	epiworld_double Average incubation days of the virus.
<i>recovery_rate</i>	epiworld_double Recovery rate of the virus.

### 17.36.2 Member Function Documentation

#### 17.36.2.1 initial\_states()

```
template<typename TSeq >
ModelSEIR< TSeq > & ModelSEIR< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set up the initial states of the model.

#### Parameters

<i>proportions_</i>	Double vector with the following values:
—	<ul style="list-style-type: none"> <li>• 0: Proportion of non-infected agents who are removed.</li> <li>• 1: Proportion of exposed agents to be set as infected.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.36.3 Member Data Documentation

#### 17.36.3.1 update\_exposed\_seir

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
epiworld::UpdateFun<TSeq> ModelSEIR< TSeq >::update_exposed_seir
```

**Initial value:**

```
= [] (
 epiworld::Agent<TSeq> * p,
 epiworld::Model<TSeq> * m
) -> void {
 auto v = p->get_virus();
 if (m->runif() < 1.0/(v->get_incubation(m)))
 p->change_state(m, ModelSEIR<TSeq>::INFECTED);
 return;
}
```

#### 17.36.3.2 update\_infected\_seir

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
epiworld::UpdateFun<TSeq> ModelSEIR< TSeq >::update_infected_seir
```

**Initial value:**

```
= [] (
 epiworld::Agent<TSeq> * p,
 epiworld::Model<TSeq> * m
) -> void {
 if (m->runif() < (m->par("Recovery rate")))
 p->rm_virus(m);
 return;
}
```

The documentation for this class was generated from the following file:

- include/epiworld/models/seir.hpp

## 17.37 epiworld::epimodels::ModelSEIRCONN< TSeq > Class Template Reference

Inheritance diagram for epiworld::epimodels::ModelSEIRCONN< TSeq >:



Collaboration diagram for `epiworld::epimodels::ModelSEIRCONN< TSeq >`:



## Public Member Functions

- [ModelSEIRCONN](#) ([ModelSEIRCONN](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate)  
*Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.*
- **ModelSEIRCONN** (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate)
- [ModelSEIRCONN](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- [ModelSEIRCONN](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})  
*Set the initial states of the model.*
- size\_t **get\_n\_infected** () const
- std::vector< double > **generation\_time\_expected** (int max\_days=200, int max\_contacts=200) const

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **RECOVERED** = 3

## Additional Inherited Members

### 17.37.1 Constructor & Destructor Documentation



### 17.37.1.1 `ModelSEIRCONN()`

```
template<typename TSeq >
ModelSEIRCONN< TSeq >::ModelSEIRCONN (
 ModelSEIRCONN< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate) [inline]
```

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

#### Parameters

<i>model</i>	A <code>Model&lt;TSeq&gt;</code> object where to set up the SIR.
<i>vname</i>	<code>std::string</code> Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery

## 17.37.2 Member Function Documentation

### 17.37.2.1 `clone_ptr()`

```
template<typename TSeq >
Model< TSeq > * ModelSEIRCONN< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from `epiworld::Model< EPI_DEFAULT_TSEQ >`.

### 17.37.2.2 `initial_states()`

```
template<typename TSeq >
ModelSEIRCONN< TSeq > & ModelSEIRCONN< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

## Parameters

<i>proportions</i> ↔	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

**17.37.2.3 reset()**

```
template<typename TSeq >
void ModelSEIRCONN< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0


Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:

- `epiworld.hpp`

**17.38 ModelSEIRCONN< TSeq > Class Template Reference**

Inheritance diagram for `ModelSEIRCONN< TSeq >`:



Collaboration diagram for ModelSEIRCONN< TSeq >:



## Public Member Functions

- [ModelSEIRCONN](#) ([ModelSEIRCONN](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate)  
*Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.*
- **ModelSEIRCONN** (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate)
- [ModelSEIRCONN](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- [ModelSEIRCONN](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_=  
\_={})  
*Set the initial states of the model.*
- size\_t [get\\_n\\_infected](#) () const
- std::vector< double > [generation\\_time\\_expected](#) (int max\_days=200, int max\_contacts=200) const

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **RECOVERED** = 3

## Additional Inherited Members

### 17.38.1 Constructor & Destructor Documentation

### 17.38.1.1 ModelSEIRCONN()

```
template<typename TSeq >
ModelSEIRCONN< TSeq >::ModelSEIRCONN (
 ModelSEIRCONN< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate) [inline]
```

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery

## 17.38.2 Member Function Documentation

### 17.38.2.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSEIRCONN< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.38.2.2 initial\_states()

```
template<typename TSeq >
ModelSEIRCONN< TSeq > & ModelSEIRCONN< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

## Parameters

<code>proportions</code> ↔	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

**17.38.2.3 reset()**

```
template<typename TSeq >
void ModelSEIRCONN< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:

- `include/epiworld/models/seirconnected.hpp`

**17.39 epiworld::epimodels::ModelSEIRD< TSeq > Class Template Reference**

Template for a Susceptible-Exposed-Infected-Removed-Deceased (SEIRD) model.

```
#include <epiworld.hpp>
```

Inheritance diagram for `epiworld::epimodels::ModelSEIRD< TSeq >`:



Collaboration diagram for `epiworld::epimodels::ModelSEIRD< TSeq >`:



## Public Member Functions

- [ModelSEIRD](#) ([ModelSEIRD](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, epiworld\_double death\_rate)  
*Constructor for the SEIRD model.*
- [ModelSEIRD](#) (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, epiworld\_double death\_rate)  
*Constructor for the SEIRD model.*
- [ModelSEIRD](#)< TSeq > & **initial\_states** (std::vector< double > proportions\_, std::vector< int > queue\_={})

## Public Attributes

- epiworld::UpdateFun< TSeq > **update\_exposed\_seir**
- epiworld::UpdateFun< TSeq > **update\_infected**

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **REMOVED** = 3
- static const int **DECEASED** = 4

## Additional Inherited Members

### 17.39.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelSEIRD< TSeq >
```

Template for a Susceptible-Exposed-Infected-Removed-Deceased (SEIRD) model.

### 17.39.2 Constructor & Destructor Documentation

#### 17.39.2.1 ModelSEIRD() [1/2]

```
template<typename TSeq >
ModelSEIRD< TSeq >::ModelSEIRD (
 ModelSEIRD< TSeq > & model,
 const std::string & vname,
 epiworld_double prevalence,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 epiworld_double death_rate) [inline]
```

Constructor for the SEIRD model.

#### Template Parameters

<i>TSeq</i>	Type of the sequence used in the model.
-------------	-----------------------------------------

#### Parameters

<i>model</i>	Reference to the SEIRD model.
<i>vname</i>	Name of the model.
<i>prevalence</i>	Prevalence of the disease.
<i>transmission_rate</i>	Transmission rate of the disease.
<i>avg_incubation_days</i>	Average incubation period of the disease.
<i>recovery_rate</i>	Recovery rate of the disease.
<i>death_rate</i>	Death rate of the disease.

### 17.39.2.2 ModelSEIRD() [2/2]

```
template<typename TSeq >
ModelSEIRD< TSeq >::ModelSEIRD (
 const std::string & vname,
 epiworld_double prevalence,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 epiworld_double death_rate) [inline]
```

Constructor for the SEIRD model.

#### Parameters

<i>vname</i>	Name of the model.
<i>prevalence</i>	Initial prevalence of the disease.
<i>transmission_rate</i>	Transmission rate of the disease.
<i>avg_incubation_days</i>	Average incubation period of the disease.
<i>recovery_rate</i>	Recovery rate of the disease.
<i>death_rate</i>	Death rate of the disease.

## 17.39.3 Member Data Documentation

### 17.39.3.1 update\_exposed\_seir

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
epiworld::UpdateFun<TSeq> epiworld::epimodels::ModelSEIRD< TSeq >::update_exposed_seir
```

#### Initial value:

```
= [] (
 epiworld::Agent<TSeq> * p,
 epiworld::Model<TSeq> * m
) -> void {

 auto v = p->get_virus();

 if (m->runif() < 1.0/(v->get_incubation(m)))
 p->change_state(m, ModelSEIRD<TSeq>::INFECTED);
 return;
}
```

The documentation for this class was generated from the following file:

- epiworld.hpp




## 17.40 ModelSEIRD< TSeq > Class Template Reference


Template for a Susceptible-Exposed-Infected-Removed-Deceased (SEIRD) model.

```
#include <seird.hpp>
```

Inheritance diagram for ModelSEIRD< TSeq >:



Collaboration diagram for ModelSEIRD< TSeq >:



### Public Member Functions

- [ModelSEIRD](#) ([ModelSEIRD](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, epiworld\_double death\_rate)  
*Constructor for the SEIRD model.*
- [ModelSEIRD](#) (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, epiworld\_double death\_rate)  
*Constructor for the SEIRD model.*
- [ModelSEIRD](#)< TSeq > & **initial\_states** (std::vector< double > proportions\_, std::vector< int > queue\_={})

## Public Attributes

- `epiworld::UpdateFun< TSeq >` **update\_exposed\_seir**
- `epiworld::UpdateFun< TSeq >` **update\_infected**

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **REMOVED** = 3
- static const int **DECEASED** = 4

## Additional Inherited Members

### 17.40.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelSEIRD< TSeq >
```

Template for a Susceptible-Exposed-Infected-Removed-Deceased (SEIRD) model.

### 17.40.2 Constructor & Destructor Documentation

#### 17.40.2.1 ModelSEIRD() [1/2]

```
template<typename TSeq >
ModelSEIRD< TSeq >::ModelSEIRD (
 ModelSEIRD< TSeq > & model,
 const std::string & vname,
 epiworld_double prevalence,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 epiworld_double death_rate) [inline]
```

Constructor for the SEIRD model.

#### Template Parameters

<i>TSeq</i>	Type of the sequence used in the model.
-------------	-----------------------------------------

#### Parameters

<i>model</i>	Reference to the SEIRD model.
<i>vname</i>	Name of the model.

## Parameters

<i>prevalence</i>	Prevalence of the disease.
<i>transmission_rate</i>	Transmission rate of the disease.
<i>avg_incubation_days</i>	Average incubation period of the disease.
<i>recovery_rate</i>	Recovery rate of the disease.
<i>death_rate</i>	Death rate of the disease.

## 17.40.2.2 ModelSEIRD() [2/2]

```
template<typename TSeq >
ModelSEIRD< TSeq >::ModelSEIRD (
 const std::string & vname,
 epiworld_double prevalence,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 epiworld_double death_rate) [inline]
```

Constructor for the SEIRD model.

## Parameters

<i>vname</i>	Name of the model.
<i>prevalence</i>	Initial prevalence of the disease.
<i>transmission_rate</i>	Transmission rate of the disease.
<i>avg_incubation_days</i>	Average incubation period of the disease.
<i>recovery_rate</i>	Recovery rate of the disease.
<i>death_rate</i>	Death rate of the disease.

## 17.40.3 Member Data Documentation

## 17.40.3.1 update\_exposed\_seir

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
epiworld::UpdateFun<TSeq> ModelSEIRD< TSeq >::update_exposed_seir
```

## Initial value:

```
= [] (
 epiworld::Agent<TSeq> * p,
 epiworld::Model<TSeq> * m
) -> void {
 auto v = p->get_virus();
 if (m->runif() < 1.0/(v->get_incubation(m)))
 p->change_state(m, ModelSEIRD<TSeq>::INFECTED);
 return;
}
```

The documentation for this class was generated from the following file:

- `include/epiworld/models/seird.hpp`

## 17.41 `epiworld::epimodels::ModelSEIRDCONN< TSeq >` Class Template Reference

Inheritance diagram for `epiworld::epimodels::ModelSEIRDCONN< TSeq >`:



Collaboration diagram for `epiworld::epimodels::ModelSEIRDCONN< TSeq >`:



### Public Member Functions

- [ModelSEIRDCONN](#) ([ModelSEIRDCONN](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, epiworld\_double death\_rate)  
*Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.*
- **ModelSEIRDCONN** (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, epiworld\_double death\_rate)
- [ModelSEIRDCONN](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)

- Runs the simulation (after initialization)*
- `void reset ()`  
*Reset the model.*
- `Model< TSeq > * clone_ptr ()`  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- `ModelSEIRDCONN< TSeq > & initial_states (std::vector< double > proportions_, std::vector< int > queue_={})`  
*Set up the initial states of the model.*
- `size_t get_n_infected () const`

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **REMOVED** = 3
- static const int **DECEASED** = 4

## Additional Inherited Members

### 17.41.1 Constructor & Destructor Documentation

#### 17.41.1.1 `ModelSEIRDCONN()`

```
template<typename TSeq >
ModelSEIRDCONN< TSeq >::ModelSEIRDCONN (
 ModelSEIRDCONN< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 epiworld_double death_rate) [inline]
```

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

#### Parameters

<i>model</i>	A <code>Model&lt;TSeq&gt;</code> object where to set up the SIR.
<i>vname</i>	<code>std::string</code> Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery
<i>death_rate</i>	Probability of death

## 17.41.2 Member Function Documentation

### 17.41.2.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSEIRDCONN< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.41.2.2 initial\_states()

```
template<typename TSeq >
ModelSEIRDCONN< TSeq > & ModelSEIRDCONN< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set up the initial states of the model.

#### Parameters

<i>proportions_↵</i>	Double vector with the following values:
—	<ul style="list-style-type: none"> <li>• 0: Proportion of non-infected agents who are removed.</li> <li>• 1: Proportion of exposed agents to be set as infected.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.41.2.3 reset()

```
template<typename TSeq >
void ModelSEIRDCONN< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:

- `epiworld.hpp`

## 17.42 ModelSEIRDCONN< TSeq > Class Template Reference

Inheritance diagram for ModelSEIRDCONN< TSeq >:



Collaboration diagram for ModelSEIRDCONN< TSeq >:



## Public Member Functions

- [ModelSEIRDCONN](#) ([ModelSEIRDCONN](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, epiworld\_double death\_rate)  
*Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.*
- **ModelSEIRDCONN** (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, epiworld\_double death\_rate)
- [ModelSEIRDCONN](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- [ModelSEIRDCONN](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})  
*Set up the initial states of the model.*
- size\_t [get\\_n\\_infected](#) () const

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **REMOVED** = 3
- static const int **DECEASED** = 4

## Additional Inherited Members

### 17.42.1 Constructor & Destructor Documentation

#### 17.42.1.1 ModelSEIRDCONN()

```
template<typename TSeq >
ModelSEIRDCONN< TSeq >::ModelSEIRDCONN (
 ModelSEIRDCONN< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 epiworld_double death_rate) [inline]
```

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.



## Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery
<i>death_rate</i>	Probability of death

## 17.42.2 Member Function Documentation

## 17.42.2.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSEIRDCONN< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

## Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

## 17.42.2.2 initial\_states()

```
template<typename TSeq >
ModelSEIRDCONN< TSeq > & ModelSEIRDCONN< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set up the initial states of the model.

## Parameters

<i>proportions_</i>	Double vector with the following values:
—	<ul style="list-style-type: none"> <li>• 0: Proportion of non-infected agents who are removed.</li> <li>• 1: Proportion of exposed agents to be set as infected.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.42.2.3 reset()

```
template<typename TSeq >
void ModelSEIRDCONN< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from `epiworld::Model< EPI_DEFAULT_TSEQ >`.

The documentation for this class was generated from the following file:

- `include/epiworld/models/seirdconnected.hpp`

## 17.43 epiworld::epimodels::ModelSEIRMixing< TSeq > Class Template Reference

Inheritance diagram for `epiworld::epimodels::ModelSEIRMixing< TSeq >`:



Collaboration diagram for epiworld::epimodels::ModelSEIRMixing< TSeq >:



## Public Member Functions

- [ModelSEIRMixing](#) ([ModelSEIRMixing](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, std::vector< double > contact\_matrix)  
*Constructs a [ModelSEIRMixing](#) object.*
- [ModelSEIRMixing](#) (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, std::vector< double > contact\_matrix)  
*Constructs a [ModelSEIRMixing](#) object.*
- [ModelSEIRMixing](#)< TSeq > &run (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- [ModelSEIRMixing](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_ = {})  
*Set the initial states of the model.*
- void [set\\_contact\\_matrix](#) (std::vector< double > cmat)

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **RECOVERED** = 3

## Additional Inherited Members

### 17.43.1 Constructor & Destructor Documentation

### 17.43.1.1 ModelSEIRMixing() [1/2]

```
template<typename TSeq >
ModelSEIRMixing< TSeq >::ModelSEIRMixing (
 ModelSEIRMixing< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix) [inline]
```

Constructs a [ModelSEIRMixing](#) object.

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

#### Parameters

<i>model</i>	A reference to an existing <a href="#">ModelSEIRMixing</a> object.
<i>vname</i>	The name of the <a href="#">ModelSEIRMixing</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>avg_incubation_days</i>	The average incubation period of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model. Specified in column-major order.
<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery

### 17.43.1.2 ModelSEIRMixing() [2/2]

```
template<typename TSeq >
ModelSEIRMixing< TSeq >::ModelSEIRMixing (
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix) [inline]
```

Constructs a [ModelSEIRMixing](#) object.

## Parameters

<i>vname</i>	The name of the <a href="#">ModelSEIRMixing</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>avg_incubation_days</i>	The average incubation period of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.

## 17.43.2 Member Function Documentation

17.43.2.1 `clone_ptr()`

```
template<typename TSeq >
Model< TSeq > * ModelSEIRMixing< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

## Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

17.43.2.2 `initial_states()`

```
template<typename TSeq >
ModelSEIRMixing< TSeq > & ModelSEIRMixing< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

## Parameters

<i>proportions</i> ↵	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.43.2.3 reset()

```
template<typename TSeq >
void ModelSEIRMixing< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from `epiworld::Model< EPI_DEFAULT_TSEQ >`.

The documentation for this class was generated from the following file:

- `epiworld.hpp`

## 17.44 ModelSEIRMixing< TSeq > Class Template Reference

Inheritance diagram for ModelSEIRMixing< TSeq >:



Collaboration diagram for ModelSEIRMixing< TSeq >:



## Public Member Functions

- [ModelSEIRMixing](#) ([ModelSEIRMixing](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, std::vector< double > contact\_matrix)  
*Constructs a [ModelSEIRMixing](#) object.*
- [ModelSEIRMixing](#) (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, std::vector< double > contact\_matrix)  
*Constructs a [ModelSEIRMixing](#) object.*
- [ModelSEIRMixing](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- [ModelSEIRMixing](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_ = {})  
*Set the initial states of the model.*
- void [set\\_contact\\_matrix](#) (std::vector< double > cmat)

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **RECOVERED** = 3

## Additional Inherited Members

### 17.44.1 Constructor & Destructor Documentation

#### 17.44.1.1 ModelSEIRMixing() [1/2]

```
template<typename TSeq >
ModelSEIRMixing< TSeq >::ModelSEIRMixing (
 ModelSEIRMixing< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix) [inline]
```

Constructs a [ModelSEIRMixing](#) object.

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

## Parameters

<i>model</i>	A reference to an existing <a href="#">ModelSEIRMixing</a> object.
<i>vname</i>	The name of the <a href="#">ModelSEIRMixing</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>avg_incubation_days</i>	The average incubation period of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model. Specified in column-major order.
<i>model</i>	A <code>Model&lt;TSeq&gt;</code> object where to set up the SIR.
<i>vname</i>	<code>std::string</code> Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery

17.44.1.2 [ModelSEIRMixing\(\)](#) [2/2]

```
template<typename TSeq >
ModelSEIRMixing< TSeq >::ModelSEIRMixing (
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix) [inline]
```

Constructs a [ModelSEIRMixing](#) object.

## Parameters

<i>vname</i>	The name of the <a href="#">ModelSEIRMixing</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>avg_incubation_days</i>	The average incubation period of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.

## 17.44.2 Member Function Documentation



### 17.44.2.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSEIRMixing< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.44.2.2 initial\_states()

```
template<typename TSeq >
ModelSEIRMixing< TSeq > & ModelSEIRMixing< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

#### Parameters

<i>proportions_</i> ↔	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.44.2.3 reset()

```
template<typename TSeq >
void ModelSEIRMixing< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0


Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- `include/epiworld/models/seirmixing.hpp`

## 17.45 epiworld::epimodels::ModelSEIRMixingQuarantine< TSeq > Class Template Reference

Inheritance diagram for epiworld::epimodels::ModelSEIRMixingQuarantine< TSeq >:



Collaboration diagram for epiworld::epimodels::ModelSEIRMixingQuarantine< TSeq >:



### Public Member Functions

- [ModelSEIRMixingQuarantine](#) ([ModelSEIRMixingQuarantine](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, std::vector< double > contact\_matrix, std::vector< bool > entity\_can\_quarantine, epiworld\_double hospitalization\_rate, epiworld\_double hospitalization\_period, epiworld\_double days\_undetected, epiworld\_fast\_int quarantine\_↔\_period, epiworld\_double quarantine\_willingness, epiworld\_double isolation\_willingness, epiworld\_fast\_int isolation\_period)

Constructs a [ModelSEIRMixingQuarantine](#) object.

- [ModelSEIRMixingQuarantine](#) (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, std::vector< double > contact\_matrix, std::vector< bool > entity\_can\_quarantine, epiworld\_double hospitalization\_rate, epiworld\_double hospitalization\_period, epiworld\_double days\_undetected, epiworld\_fast\_int quarantine\_period, epiworld\_double quarantine\_willingness, epiworld\_double isolation\_willingness, epiworld\_fast\_int isolation\_period)  
*Constructs a [ModelSEIRMixingQuarantine](#) object.*
- [ModelSEIRMixingQuarantine< TSeq > & run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model< TSeq > \\* clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- [ModelSEIRMixingQuarantine< TSeq > & initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})  
*Set the initial states of the model.*
- void [set\\_contact\\_matrix](#) (std::vector< double > cmat)
- void [set\\_entity\\_can\\_quarantine](#) (std::vector< bool > can\_quarantine)
- std::vector< double > [get\\_contact\\_matrix](#) () const
- std::vector< bool > [get\\_entity\\_can\\_quarantine](#) () const
- std::vector< bool > [get\\_entity\\_quarantine\\_triggered](#) () const
- std::vector< bool > [get\\_quarantine\\_willingness](#) () const
- std::vector< bool > [get\\_isolation\\_willingness](#) () const

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **ISOLATED** = 3
- static const int **DETECTED\_HOSPITALIZED** = 4
- static const int **QUARANTINED\_SUSCEPTIBLE** = 5
- static const int **QUARANTINED\_EXPOSED** = 6
- static const int **ISOLATED\_RECOVERED** = 7
- static const int **HOSPITALIZED** = 8
- static const int **RECOVERED** = 9

## Additional Inherited Members

### 17.45.1 Constructor & Destructor Documentation

### 17.45.1.1 ModelSEIRMixingQuarantine() [1/2]

```
template<typename TSeq >
ModelSEIRMixingQuarantine< TSeq >::ModelSEIRMixingQuarantine (
 ModelSEIRMixingQuarantine< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix,
 std::vector< bool > entity_can_quarantine,
 epiworld_double hospitalization_rate,
 epiworld_double hospitalization_period,
 epiworld_double days_undetected,
 epiworld_fast_int quarantine_period,
 epiworld_double quarantine_willingness,
 epiworld_double isolation_willingness,
 epiworld_fast_int isolation_period) [inline]
```

Constructs a [ModelSEIRMixingQuarantine](#) object.

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

#### Parameters

<i>model</i>	A reference to an existing <a href="#">ModelSEIRMixingQuarantine</a> object.
<i>vname</i>	The name of the <a href="#">ModelSEIRMixingQuarantine</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>avg_incubation_days</i>	The average incubation period of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model. Specified in column-major order.
<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery

### 17.45.1.2 ModelSEIRMixingQuarantine() [2/2]

```
template<typename TSeq >
ModelSEIRMixingQuarantine< TSeq >::ModelSEIRMixingQuarantine (
 const std::string & vname,
 epiworld_fast_uint n,
```

```

epiworld_double prevalence,
epiworld_double contact_rate,
epiworld_double transmission_rate,
epiworld_double avg_incubation_days,
epiworld_double recovery_rate,
std::vector< double > contact_matrix,
std::vector< bool > entity_can_quarantine,
epiworld_double hospitalization_rate,
epiworld_double hospitalization_period,
epiworld_double days_undetected,
epiworld_fast_int quarantine_period,
epiworld_double quarantine_willingness,
epiworld_double isolation_willingness,
epiworld_fast_int isolation_period) [inline]

```

Constructs a [ModelSEIRMixingQuarantine](#) object.

#### Parameters

<i>vname</i>	The name of the <a href="#">ModelSEIRMixingQuarantine</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>avg_incubation_days</i>	The average incubation period of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.

## 17.45.2 Member Function Documentation

### 17.45.2.1 `clone_ptr()`

```

template<typename TSeq >
Model< TSeq > * ModelSEIRMixingQuarantine< TSeq >::clone_ptr [inline], [virtual]

```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.45.2.2 `initial_states()`

```

template<typename TSeq >
ModelSEIRMixingQuarantine< TSeq > & ModelSEIRMixingQuarantine< TSeq >::initial_states (

```

```
std::vector< double > proportions_,
std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

#### Parameters

<i>proportions_</i> ↔	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.45.2.3 reset()

```
template<typename TSeq >
void ModelSEIRMixingQuarantine< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0


Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- `epiworld.hpp`

## 17.46 ModelSEIRMixingQuarantine< TSeq > Class Template Reference

Inheritance diagram for ModelSEIRMixingQuarantine< TSeq >:



Collaboration diagram for ModelSEIRMixingQuarantine< TSeq >:



### Public Member Functions

- [ModelSEIRMixingQuarantine](#) ([ModelSEIRMixingQuarantine](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, std::vector< double > contact\_matrix, std::vector< bool > entity\_can\_quarantine, epiworld\_double hospitalization\_rate, epiworld\_double hospitalization\_period, epiworld\_double days\_undetected, epiworld\_fast\_int quarantine\_↵\_period, epiworld\_double quarantine\_willingness, epiworld\_double isolation\_willingness, epiworld\_fast\_int isolation\_period)
- Constructs a [ModelSEIRMixingQuarantine](#) object.
- [ModelSEIRMixingQuarantine](#) (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double avg\_incubation\_days, epiworld\_double recovery\_rate, std::vector< double > contact\_matrix, std::vector< bool > entity\_can\_↵\_quarantine, epiworld\_double hospitalization\_rate, epiworld\_double hospitalization\_period, epiworld\_double days\_undetected, epiworld\_fast\_int quarantine\_period, epiworld\_double quarantine\_willingness, epiworld\_↵\_double isolation\_willingness, epiworld\_fast\_int isolation\_period)

- Constructs a [ModelSEIRMixingQuarantine](#) object.*
- [ModelSEIRMixingQuarantine](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- [ModelSEIRMixingQuarantine](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})  
*Set the initial states of the model.*
- void [set\\_contact\\_matrix](#) (std::vector< double > cmat)
- void [set\\_entity\\_can\\_quarantine](#) (std::vector< bool > can\_quarantine)
- std::vector< double > [get\\_contact\\_matrix](#) () const
- std::vector< bool > [get\\_entity\\_can\\_quarantine](#) () const
- std::vector< bool > [get\\_entity\\_quarantine\\_triggered](#) () const
- std::vector< bool > [get\\_quarantine\\_willingness](#) () const
- std::vector< bool > [get\\_isolation\\_willingness](#) () const

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **EXPOSED** = 1
- static const int **INFECTED** = 2
- static const int **ISOLATED** = 3
- static const int **DETECTED\_HOSPITALIZED** = 4
- static const int **QUARANTINED\_SUSCEPTIBLE** = 5
- static const int **QUARANTINED\_EXPOSED** = 6
- static const int **ISOLATED\_RECOVERED** = 7
- static const int **HOSPITALIZED** = 8
- static const int **RECOVERED** = 9

## Additional Inherited Members

### 17.46.1 Constructor & Destructor Documentation

#### 17.46.1.1 ModelSEIRMixingQuarantine() [1/2]

```
template<typename TSeq >
ModelSEIRMixingQuarantine< TSeq >::ModelSEIRMixingQuarantine (
 ModelSEIRMixingQuarantine< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix,
```



```

std::vector< bool > entity_can_quarantine,
epiworld_double hospitalization_rate,
epiworld_double hospitalization_period,
epiworld_double days_undetected,
epiworld_fast_int quarantine_period,
epiworld_double quarantine_willingness,
epiworld_double isolation_willingness,
epiworld_fast_int isolation_period) [inline]

```

Constructs a [ModelSEIRMixingQuarantine](#) object.

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

#### Parameters

<i>model</i>	A reference to an existing <a href="#">ModelSEIRMixingQuarantine</a> object.
<i>vname</i>	The name of the <a href="#">ModelSEIRMixingQuarantine</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>avg_incubation_days</i>	The average incubation period of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model. Specified in column-major order.
<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery

#### 17.46.1.2 ModelSEIRMixingQuarantine() [2/2]

```

template<typename TSeq >
ModelSEIRMixingQuarantine< TSeq >::ModelSEIRMixingQuarantine (
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double avg_incubation_days,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix,
 std::vector< bool > entity_can_quarantine,
 epiworld_double hospitalization_rate,
 epiworld_double hospitalization_period,
 epiworld_double days_undetected,
 epiworld_fast_int quarantine_period,
 epiworld_double quarantine_willingness,
 epiworld_double isolation_willingness,
 epiworld_fast_int isolation_period) [inline]

```

Constructs a [ModelSEIRMixingQuarantine](#) object.

## Parameters

<i>vname</i>	The name of the <a href="#">ModelSEIRMixingQuarantine</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>avg_incubation_days</i>	The average incubation period of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.

## 17.46.2 Member Function Documentation

## 17.46.2.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSEIRMixingQuarantine< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

## Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

## 17.46.2.2 initial\_states()

```
template<typename TSeq >
ModelSEIRMixingQuarantine< TSeq > & ModelSEIRMixingQuarantine< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

## Parameters

<i>proportions_</i>	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.46.2.3 reset()

```
template<typename TSeq >
void ModelSEIRMixingQuarantine< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from `epiworld::Model< EPI_DEFAULT_TSEQ >`.

The documentation for this class was generated from the following file:


- `include/epiworld/models/seirmixingquarantine.hpp`

## 17.47 epiworld::epimodels::ModelSIR< TSeq > Class Template Reference


Template for a Susceptible-Infected-Removed (SIR) model.

```
#include <epiworld.hpp>
```

Inheritance diagram for `epiworld::epimodels::ModelSIR< TSeq >`:



Collaboration diagram for epiworld::epimodels::ModelSIR< TSeq >:



## Public Member Functions

- **ModelSIR** ([ModelSIR](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)
- **ModelSIR** (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)
- [ModelSIR](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})  
*Set the initial states of the model.*

## Additional Inherited Members

### 17.47.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelSIR< TSeq >
```

Template for a Susceptible-Infected-Removed (SIR) model.

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>initial_prevalence</i>	epiworld_double Initial prevalence
<i>initial_efficacy</i>	epiworld_double Initial susceptibility_reduction of the immune system
<i>initial_recovery</i>	epiworld_double Initial recovery_rate rate of the immune system

### 17.47.2 Member Function Documentation

### 17.47.2.1 initial\_states()

```
template<typename TSeq >
ModelSIR< TSeq > & ModelSIR< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

#### Parameters

<i>proportions_↔</i>	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- [epiworld.hpp](#)

## 17.48 ModelSIR< TSeq > Class Template Reference


Template for a Susceptible-Infected-Removed (SIR) model.

```
#include <sir.hpp>
```

Inheritance diagram for ModelSIR< TSeq >:



Collaboration diagram for ModelSIR< TSeq >:



## Public Member Functions

- **ModelSIR** ([ModelSIR](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)
- **ModelSIR** (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)
- [ModelSIR](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})

*Set the initial states of the model.*

## Additional Inherited Members

### 17.48.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelSIR< TSeq >
```

Template for a Susceptible-Infected-Removed (SIR) model.

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>initial_prevalence</i>	epiworld_double Initial prevalence
<i>initial_efficacy</i>	epiworld_double Initial susceptibility_reduction of the immune system
<i>initial_recovery</i>	epiworld_double Initial recovery_rate rate of the immune system

### 17.48.2 Member Function Documentation

### 17.48.2.1 initial\_states()

```
template<typename TSeq >
ModelSIR< TSeq > & ModelSIR< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

#### Parameters

<i>proportions_↔</i>	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>


Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:

- include/epiworld/models/sir.hpp


## 17.49 epiworld::epimodels::ModelSIRCONN< TSeq > Class Template Reference

Inheritance diagram for epiworld::epimodels::ModelSIRCONN< TSeq >:





Collaboration diagram for epiworld::epimodels::ModelSIRCONN< TSeq >:



## Public Member Functions

- [ModelSIRCONN](#) ([ModelSIRCONN](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)
- *Template for a Susceptible-Infected-Removed (SIR) model.*
- **ModelSIRCONN** (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)
- [ModelSIRCONN](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)
- *Runs the simulation (after initialization)*
- void [reset](#) ()
- *Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()
- *Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- [ModelSIRCONN](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_ = {})
- *Set the initial states of the model.*
- size\_t [get\\_n\\_infected](#) () const
- *Get the infected individuals.*
- std::vector< double > **generation\_time\_expected** (int max\_days=200, int max\_contacts=200) const

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **INFECTED** = 1
- static const int **RECOVERED** = 2

## Additional Inherited Members

### 17.49.1 Constructor & Destructor Documentation

### 17.49.1.1 ModelSIRCONN()

```
template<typename TSeq >
ModelSIRCONN< TSeq >::ModelSIRCONN (
 ModelSIRCONN< TSeq > & model,
 const std::string & vname,
 epiworld_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate) [inline]
```

Template for a Susceptible-Infected-Removed (SIR) model.

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery

## 17.49.2 Member Function Documentation

### 17.49.2.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSIRCONN< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.49.2.2 get\_n\_infected()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
size_t epiworld::epimodels::ModelSIRCONN< TSeq >::get_n_infected () const [inline]
```

Get the infected individuals.

## Returns

std::vector< epiworld::Agent<TSeq> \* >

## 17.49.2.3 initial\_states()

```
template<typename TSeq >
ModelSIRCONN< TSeq > & ModelSIRCONN< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

## Parameters

<i>proportions_</i> ↩	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

## 17.49.2.4 reset()

```
template<typename TSeq >
void ModelSIRCONN< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0


Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- epiworld.hpp

## 17.50 ModelSIRCONN< TSeq > Class Template Reference

Inheritance diagram for ModelSIRCONN< TSeq >:



Collaboration diagram for ModelSIRCONN< TSeq >:



### Public Member Functions

- [ModelSIRCONN](#) ([ModelSIRCONN](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)  
*Template for a Susceptible-Infected-Removed (SIR) model.*
- **ModelSIRCONN** (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)
- [ModelSIRCONN](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- [ModelSIRCONN](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_ = {})

*Set the initial states of the model.*

- `size_t` `get_n_infected` () const

*Get the infected individuals.*

- `std::vector< double >` `generation_time_expected` (int max\_days=200, int max\_contacts=200) const

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **INFECTED** = 1
- static const int **RECOVERED** = 2

## Additional Inherited Members

### 17.50.1 Constructor & Destructor Documentation

#### 17.50.1.1 ModelSIRCONN()

```
template<typename TSeq >
ModelSIRCONN< TSeq >::ModelSIRCONN (
 ModelSIRCONN< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate) [inline]
```

Template for a Susceptible-Infected-Removed (SIR) model.

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery

### 17.50.2 Member Function Documentation

#### 17.50.2.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSIRCONN< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.50.2.2 get\_n\_infected()

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
size_t ModelSIRCONN< TSeq >::get_n_infected () const [inline]
```

Get the infected individuals.

#### Returns

`std::vector< epiworld::Agent<TSeq> * >`

### 17.50.2.3 initial\_states()

```
template<typename TSeq >
ModelSIRCONN< TSeq > & ModelSIRCONN< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

#### Parameters

<i>proportions_</i>	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.50.2.4 reset()

```
template<typename TSeq >
void ModelSIRCONN< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- `include/epiworld/models/sirconnected.hpp`

## 17.51 epiworld::epimodels::ModelSIRD< TSeq > Class Template Reference


Template for a Susceptible-Infected-Removed-Deceased (SIRD) model.

```
#include <epiworld.hpp>
```

Inheritance diagram for `epiworld::epimodels::ModelSIRD< TSeq >`:



Collaboration diagram for `epiworld::epimodels::ModelSIRD< TSeq >`:



## Public Member Functions

- [ModelSIRD](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})  
*Set the initial states of the model.*
- [ModelSIRD](#) ([ModelSIRD](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)  
*Constructs a new SIRD model with the given parameters.*
- **ModelSIRD** (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)

## Additional Inherited Members

### 17.51.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelSIRD< TSeq >
```

Template for a Susceptible-Infected-Removed-Deceased (SIRD) model.

### 17.51.2 Constructor & Destructor Documentation

#### 17.51.2.1 ModelSIRD()

```
template<typename TSeq >
ModelSIRD< TSeq >::ModelSIRD (
 ModelSIRD< TSeq > & model,
 const std::string & vname,
 epiworld_double prevalence,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate,
 epiworld_double death_rate) [inline]
```

Constructs a new SIRD model with the given parameters.

#### Parameters

<i>model</i>	The SIRD model to copy from.
<i>vname</i>	The name of the vertex associated with this model.
<i>prevalence</i>	The initial prevalence of the disease in the population.
<i>transmission_rate</i>	The rate at which the disease spreads from infected to susceptible individuals.
<i>recovery_rate</i>	The rate at which infected individuals recover and become immune.
<i>death_rate</i>	The rate at which infected individuals die.



### 17.51.3 Member Function Documentation

#### 17.51.3.1 initial\_states()

```
template<typename TSeq >
ModelSIRD< TSeq > & ModelSIRD< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

##### Parameters

<i>proportions_</i>	Double vector with two elements:
—	<ul style="list-style-type: none"> <li>• The proportion of non-infected individuals who have recovered.</li> <li>• The proportion of non-infected individuals who have died.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- `epiworld.hpp`

## 17.52 ModelSIRD< TSeq > Class Template Reference


Template for a Susceptible-Infected-Removed-Deceased (SIRD) model.

```
#include <sird.hpp>
```

Inheritance diagram for ModelSIRD< TSeq >:



Collaboration diagram for ModelSIRD< TSeq >:



## Public Member Functions

- [ModelSIRD](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_={})  
*Set the initial states of the model.*
- [ModelSIRD](#) ([ModelSIRD](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)  
*Constructs a new SIRD model with the given parameters.*
- **ModelSIRD** (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)

## Additional Inherited Members

### 17.52.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelSIRD< TSeq >
```

Template for a Susceptible-Infected-Removed-Deceased (SIRD) model.

### 17.52.2 Constructor & Destructor Documentation

#### 17.52.2.1 ModelSIRD()

```
template<typename TSeq >
ModelSIRD< TSeq >::ModelSIRD (
 ModelSIRD< TSeq > & model,
 const std::string & vname,
 epiworld_double prevalence,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate,
 epiworld_double death_rate) [inline]
```

Constructs a new SIRD model with the given parameters.

## Parameters

<i>model</i>	The SIRD model to copy from.
<i>vname</i>	The name of the vertex associated with this model.
<i>prevalence</i>	The initial prevalence of the disease in the population.
<i>transmission_rate</i>	The rate at which the disease spreads from infected to susceptible individuals.
<i>recovery_rate</i>	The rate at which infected individuals recover and become immune.
<i>death_rate</i>	The rate at which infected individuals die.

## 17.52.3 Member Function Documentation

## 17.52.3.1 initial\_states()

```
template<typename TSeq >
ModelSIRD< TSeq > & ModelSIRD< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

## Parameters

<i>proportions_</i> ↔	Double vector with two elements:
—	<ul style="list-style-type: none"> <li>• The proportion of non-infected individuals who have recovered.</li> <li>• The proportion of non-infected individuals who have died.</li> </ul>


Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- `include/epiworld/models/sird.hpp`

## 17.53 epiworld::epimodels::ModelSIRDCONN< TSeq > Class Template Reference

Inheritance diagram for epiworld::epimodels::ModelSIRDCONN< TSeq >:



Collaboration diagram for epiworld::epimodels::ModelSIRDCONN< TSeq >:



### Public Member Functions

- [ModelSIRDCONN](#) ([ModelSIRDCONN](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)  
*Template for a Susceptible-Infected-Removed (SIR) model.*
- **ModelSIRDCONN** (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)
- [ModelSIRDCONN](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **INFECTED** = 1
- static const int **RECOVERED** = 2
- static const int **DECEASED** = 3

## Additional Inherited Members

### 17.53.1 Constructor & Destructor Documentation

#### 17.53.1.1 ModelSIRDCONN()

```
template<typename TSeq >
ModelSIRDCONN< TSeq >::ModelSIRDCONN (
 ModelSIRDCONN< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate,
 epiworld_double death_rate) [inline]
```

Template for a Susceptible-Infected-Removed (SIR) model.

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery
<i>death_rate</i>	Probability of death

### 17.53.2 Member Function Documentation

#### 17.53.2.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSIRDCONN< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

## Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

**17.53.2.2 reset()**

```
template<typename TSeq >
void ModelSIRDConn< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0


Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- `epiworld.hpp`

**17.54 ModelSIRDConn< TSeq > Class Template Reference**

Inheritance diagram for `ModelSIRDConn< TSeq >`:



Collaboration diagram for ModelSIRDConn< TSeq >:



## Public Member Functions

- [ModelSIRDConn](#) ([ModelSIRDConn](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)  
*Template for a Susceptible-Infected-Removed (SIR) model.*
- **ModelSIRDConn** (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)
- [ModelSIRDConn](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **INFECTED** = 1
- static const int **RECOVERED** = 2
- static const int **DECEASED** = 3

## Additional Inherited Members

### 17.54.1 Constructor & Destructor Documentation

### 17.54.1.1 ModelSIRDCONN()

```
template<typename TSeq >
ModelSIRDCONN< TSeq >::ModelSIRDCONN (
 ModelSIRDCONN< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate,
 epiworld_double death_rate) [inline]
```

Template for a Susceptible-Infected-Removed (SIR) model.

#### Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery
<i>death_rate</i>	Probability of death

## 17.54.2 Member Function Documentation

### 17.54.2.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSIRDCONN< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.54.2.2 reset()

```
template<typename TSeq >
void ModelSIRDCONN< TSeq >::reset [inline], [virtual]
```



Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- `include/epiworld/models/sirdconnected.hpp`

## 17.55 `epiworld::epimodels::ModelSIRLogit< TSeq >` Class Template Reference

Template for a Susceptible-Infected-Removed (SIR) model.

```
#include <epiworld.hpp>
```

Inheritance diagram for `epiworld::epimodels::ModelSIRLogit< TSeq >`:



Collaboration diagram for `epiworld::epimodels::ModelSIRLogit< TSeq >`:



## Public Member Functions

- [ModelSIRLogit](#) ([ModelSIRLogit](#)< TSeq > &model, const std::string &vname, double \*data, size\_t ncols, std::vector< double > coefs\_infect, std::vector< double > coefs\_recover, std::vector< size\_t > coef\_infect\_cols, std::vector< size\_t > coef\_recover\_cols, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double prevalence)

*Template for a Susceptible-Infected-Removed (SIR) model.*

- **ModelSIRLogit** (const std::string &vname, double \*data, size\_t ncols, std::vector< double > coefs\_infect, std::vector< double > coefs\_recover, std::vector< size\_t > coef\_infect\_cols, std::vector< size\_t > coef\_recover\_cols, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double prevalence)
- [ModelSIRLogit](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- void [reset](#) ()  
*Reset the model.*

## Public Attributes

- std::vector< double > **coefs\_infect**
- std::vector< double > **coefs\_recover**
- std::vector< size\_t > **coef\_infect\_cols**
- std::vector< size\_t > **coef\_recover\_cols**

## Additional Inherited Members

### 17.55.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelSIRLogit< TSeq >
```

Template for a Susceptible-Infected-Removed (SIR) model.

In this model, infection and recovery probabilities are computed using a logit model. Particularly, the probability of infection is computed as:

$$\frac{1}{1 + \exp(-(\beta_0 E_i + \sum_{i=1}^n \beta_i x_i))}$$

where  $\beta_0$  is the exposure coefficient and  $E_i$  is the exposure number,  $\beta_i$  are the coefficients for the features  $x_i$  of the agents, and  $n$  is the number of features. The probability of recovery is computed as:

$$\frac{1}{1 + \exp(-(\sum_{i=1}^n \beta_i x_i))}$$

where  $\beta_i$  are the coefficients for the features  $x_i$  of the agents, and  $n$  is the number of features.

#### Parameters

<i>TSeq</i>	Type of the sequence (e.g. <code>std::vector</code> , <code>std::deque</code> )
-------------	---------------------------------------------------------------------------------

## 17.55.2 Constructor & Destructor Documentation

### 17.55.2.1 ModelSIRLogit()

```
template<typename TSeq >
ModelSIRLogit< TSeq >::ModelSIRLogit (
 ModelSIRLogit< TSeq > & model,
 const std::string & vname,
 double * data,
 size_t ncols,
 std::vector< double > coefs_infect,
 std::vector< double > coefs_recover,
 std::vector< size_t > coef_infect_cols,
 std::vector< size_t > coef_recover_cols,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate,
 epiworld_double prevalence) [inline]
```

Template for a Susceptible-Infected-Removed (SIR) model.

#### Parameters

<i>vname</i>	Name of the virus.
<i>coefs_infect</i>	Double ptr. Infection coefficients.
<i>coefs_recover</i>	Double ptr. Recovery coefficients.
<i>ncoenf_infect</i>	Unsigned int. Number of infection coefficients.
<i>ncoenf_recover</i>	Unsigned int. Number of recovery coefficients.
<i>coef_infect_cols</i>	Vector<unsigned int>. Ids of infection vars.
<i>coef_recover_cols</i>	Vector<unsigned int>. Ids of recover vars.

## Parameters

<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>prob_transmission</i>	Probability of transmission
<i>prob_recovery</i>	Probability of recovery

### 17.55.3 Member Function Documentation

#### 17.55.3.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSIRLogit< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

## Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

#### 17.55.3.2 reset()

```
template<typename TSeq >
void ModelSIRLogit< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:


- `epiworld.hpp`

## 17.56 ModelSIRLogit< TSeq > Class Template Reference

Template for a Susceptible-Infected-Removed (SIR) model.

```
#include <sirlogit.hpp>
```

Inheritance diagram for ModelSIRLogit< TSeq >:



Collaboration diagram for ModelSIRLogit< TSeq >:



### Public Member Functions

- [ModelSIRLogit](#) ([ModelSIRLogit](#)< TSeq > &model, const std::string &vname, double \*data, size\_t ncols, std::vector< double > coefs\_infect, std::vector< double > coefs\_recover, std::vector< size\_t > coef\_infect\_cols, std::vector< size\_t > coef\_recover\_cols, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double prevalence)  
*Template for a Susceptible-Infected-Removed (SIR) model.*
- **ModelSIRLogit** (const std::string &vname, double \*data, size\_t ncols, std::vector< double > coefs\_infect, std::vector< double > coefs\_recover, std::vector< size\_t > coef\_infect\_cols, std::vector< size\_t > coef\_recover\_cols, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double prevalence)
- [ModelSIRLogit](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*
- void [reset](#) ()  
*Reset the model.*

## Public Attributes

- `std::vector< double > coefs_infect`
- `std::vector< double > coefs_recover`
- `std::vector< size_t > coef_infect_cols`
- `std::vector< size_t > coef_recover_cols`

## Additional Inherited Members

### 17.56.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelSIRLogit< TSeq >
```

Template for a Susceptible-Infected-Removed (SIR) model.

In this model, infection and recovery probabilities are computed using a logit model. Particularly, the probability of infection is computed as:

$$\frac{1}{1 + \exp(-(\beta_0 E_i + \sum_{i=1}^n \beta_i x_i))}$$

where  $\beta_0$  is the exposure coefficient and  $E_i$  is the exposure number,  $\beta_i$  are the coefficients for the features  $x_i$  of the agents, and  $n$  is the number of features. The probability of recovery is computed as:

$$\frac{1}{1 + \exp(-(\sum_{i=1}^n \beta_i x_i))}$$

where  $\beta_i$  are the coefficients for the features  $x_i$  of the agents, and  $n$  is the number of features.

#### Parameters

<i>TSeq</i>	Type of the sequence (e.g. <code>std::vector</code> , <code>std::deque</code> )
-------------	---------------------------------------------------------------------------------

### 17.56.2 Constructor & Destructor Documentation

#### 17.56.2.1 ModelSIRLogit()

```
template<typename TSeq >
ModelSIRLogit< TSeq >::ModelSIRLogit (
 ModelSIRLogit< TSeq > & model,
 const std::string & vname,
 double * data,
 size_t ncols,
```

```

std::vector< double > coefs_infect,
std::vector< double > coefs_recover,
std::vector< size_t > coef_infect_cols,
std::vector< size_t > coef_recover_cols,
epiworld_double transmission_rate,
epiworld_double recovery_rate,
epiworld_double prevalence) [inline]

```

Template for a Susceptible-Infected-Removed (SIR) model.

#### Parameters

<i>vname</i>	Name of the virus.
<i>coefs_infect</i>	Double ptr. Infection coefficients.
<i>coefs_recover</i>	Double ptr. Recovery coefficients.
<i>nccoef_infect</i>	Unsigned int. Number of infection coefficients.
<i>nccoef_recover</i>	Unsigned int. Number of recovery coefficients.
<i>coef_infect_cols</i>	Vector<unsigned int>. Ids of infection vars.
<i>coef_recover_cols</i>	Vector<unsigned int>. Ids of recover vars.
<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>prob_transmission</i>	Probability of transmission
<i>prob_recovery</i>	Probability of recovery

## 17.56.3 Member Function Documentation

### 17.56.3.1 clone\_ptr()

```

template<typename TSeq >
Model< TSeq > * ModelSIRLogit< TSeq >::clone_ptr [inline], [virtual]

```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.56.3.2 reset()

```

template<typename TSeq >
void ModelSIRLogit< TSeq >::reset [inline], [virtual]

```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:

- `include/epiworld/models/sirlogit.hpp`

## 17.57 epiworld::epimodels::ModelSIRMixing< TSeq > Class Template Reference

Inheritance diagram for `epiworld::epimodels::ModelSIRMixing< TSeq >`:



Collaboration diagram for `epiworld::epimodels::ModelSIRMixing< TSeq >`:





## Public Member Functions

- `ModelSIRMixing` (`ModelSIRMixing< TSeq > &model`, `const std::string &vname`, `epiworld_fast_uint n`, `epiworld_double prevalence`, `epiworld_double contact_rate`, `epiworld_double transmission_rate`, `epiworld_double recovery_rate`, `std::vector< double > contact_matrix`)  
Constructs a `ModelSIRMixing` object.
- `ModelSIRMixing` (`const std::string &vname`, `epiworld_fast_uint n`, `epiworld_double prevalence`, `epiworld_double contact_rate`, `epiworld_double transmission_rate`, `epiworld_double recovery_rate`, `std::vector< double > contact_matrix`)  
Constructs a `ModelSIRMixing` object.
- `ModelSIRMixing< TSeq > &run` (`epiworld_fast_uint ndays`, `int seed=-1`)  
Runs the simulation (after initialization)
- `void reset` ()  
Reset the model.
- `Model< TSeq > * clone_ptr` ()  
Advanced usage: Makes a copy of data and returns it as undeleted pointer.
- `ModelSIRMixing< TSeq > &initial_states` (`std::vector< double > proportions_`, `std::vector< int > queue_`, `_={}`)  
Set the initial states of the model.
- `size_t get_n_infected` (`size_t group`) `const`
- `void set_contact_matrix` (`std::vector< double > cmat`)

## Static Public Attributes

- `static const int SUSCEPTIBLE` = 0
- `static const int INFECTED` = 1
- `static const int RECOVERED` = 2

## Additional Inherited Members

### 17.57.1 Constructor & Destructor Documentation

#### 17.57.1.1 `ModelSIRMixing()` [1/2]

```
template<typename TSeq >
ModelSIRMixing< TSeq >::ModelSIRMixing (
 ModelSIRMixing< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix) [inline]
```

Constructs a `ModelSIRMixing` object.

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

## Parameters

<i>model</i>	A reference to an existing <a href="#">ModelSIRMixing</a> object.
<i>vname</i>	The name of the <a href="#">ModelSIRMixing</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.
<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery

17.57.1.2 [ModelSIRMixing\(\)](#) [2/2]

```
template<typename TSeq >
ModelSIRMixing< TSeq >::ModelSIRMixing (
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix) [inline]
```

Constructs a [ModelSIRMixing](#) object.

## Parameters

<i>vname</i>	The name of the <a href="#">ModelSIRMixing</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.

## 17.57.2 Member Function Documentation

### 17.57.2.1 `clone_ptr()`

```
template<typename TSeq >
Model< TSeq > * ModelSIRMixing< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from `epiworld::Model< EPI_DEFAULT_TSEQ >`.

### 17.57.2.2 `initial_states()`

```
template<typename TSeq >
ModelSIRMixing< TSeq > & ModelSIRMixing< TSeq >::initial_states (
 std::vector< double > proportions_,
 std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

#### Parameters

<i>proportions_</i> ↔	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from `epiworld::Model< EPI_DEFAULT_TSEQ >`.

### 17.57.2.3 `reset()`

```
template<typename TSeq >
void ModelSIRMixing< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0


Reimplemented from `epiworld::Model< EPI_DEFAULT_TSEQ >`.

The documentation for this class was generated from the following file:


- `epiworld.hpp`

## 17.58 ModelSIRMixing< TSeq > Class Template Reference

Inheritance diagram for ModelSIRMixing< TSeq >:



Collaboration diagram for ModelSIRMixing< TSeq >:



### Public Member Functions

- [ModelSIRMixing](#) ([ModelSIRMixing](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, std::vector< double > contact\_matrix)  
*Constructs a [ModelSIRMixing](#) object.*
- [ModelSIRMixing](#) (const std::string &vname, epiworld\_fast\_uint n, epiworld\_double prevalence, epiworld\_double contact\_rate, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, std::vector< double > contact\_matrix)  
*Constructs a [ModelSIRMixing](#) object.*
- [ModelSIRMixing](#)< TSeq > & [run](#) (epiworld\_fast\_uint ndays, int seed=-1)  
*Runs the simulation (after initialization)*
- void [reset](#) ()  
*Reset the model.*
- [Model](#)< TSeq > \* [clone\\_ptr](#) ()  
*Advanced usage: Makes a copy of data and returns it as undeleted pointer.*

- [ModelSIRMixing](#)< TSeq > & [initial\\_states](#) (std::vector< double > proportions\_, std::vector< int > queue\_ ←  
\_={})  
*Set the initial states of the model.*
- size\_t **get\_n\_infected** (size\_t group) const
- void **set\_contact\_matrix** (std::vector< double > cmat)

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **INFECTED** = 1
- static const int **RECOVERED** = 2

## Additional Inherited Members

### 17.58.1 Constructor & Destructor Documentation

#### 17.58.1.1 ModelSIRMixing() [1/2]

```
template<typename TSeq >
ModelSIRMixing< TSeq >::ModelSIRMixing (
 ModelSIRMixing< TSeq > & model,
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix) [inline]
```

Constructs a [ModelSIRMixing](#) object.

Template for a Susceptible-Exposed-Infected-Removed (SEIR) model.

#### Parameters

<i>model</i>	A reference to an existing <a href="#">ModelSIRMixing</a> object.
<i>vname</i>	The name of the <a href="#">ModelSIRMixing</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.
<i>model</i>	A Model<TSeq> object where to set up the SIR.
<i>vname</i>	std::string Name of the virus
<i>prevalence</i>	Initial prevalence (proportion)
<i>contact_rate</i>	Average number of contacts (interactions) per step.
<i>transmission_rate</i>	Probability of transmission
<i>recovery_rate</i>	Probability of recovery

### 17.58.1.2 ModelSIRMixing() [2/2]

```
template<typename TSeq >
ModelSIRMixing< TSeq >::ModelSIRMixing (
 const std::string & vname,
 epiworld_fast_uint n,
 epiworld_double prevalence,
 epiworld_double contact_rate,
 epiworld_double transmission_rate,
 epiworld_double recovery_rate,
 std::vector< double > contact_matrix) [inline]
```

Constructs a [ModelSIRMixing](#) object.

#### Parameters

<i>vname</i>	The name of the <a href="#">ModelSIRMixing</a> object.
<i>n</i>	The number of entities in the model.
<i>prevalence</i>	The initial prevalence of the disease in the model.
<i>contact_rate</i>	The contact rate between entities in the model.
<i>transmission_rate</i>	The transmission rate of the disease in the model.
<i>recovery_rate</i>	The recovery rate of the disease in the model.
<i>contact_matrix</i>	The contact matrix between entities in the model.

## 17.58.2 Member Function Documentation

### 17.58.2.1 clone\_ptr()

```
template<typename TSeq >
Model< TSeq > * ModelSIRMixing< TSeq >::clone_ptr [inline], [virtual]
```

Advanced usage: Makes a copy of data and returns it as undeleted pointer.

#### Parameters

<i>copy</i>	
-------------	--

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.58.2.2 initial\_states()

```
template<typename TSeq >
ModelSIRMixing< TSeq > & ModelSIRMixing< TSeq >::initial_states (
```

```
std::vector< double > proportions_,
std::vector< int > queue_ = {}) [inline], [virtual]
```

Set the initial states of the model.

#### Parameters

<code>proportions_</code>	Double vector with a single element:
—	<ul style="list-style-type: none"> <li>The proportion of non-infected individuals who have recovered.</li> </ul>

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

### 17.58.2.3 `reset()`

```
template<typename TSeq >
void ModelSIRMixing< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:

- `include/epiworld/models/sirmixing.hpp`

## 17.59 `epiworld::epimodels::ModelSIS< TSeq >` Class Template Reference

Template for a Susceptible-Infected-Susceptible (SIS) model.

```
#include <epiworld.hpp>
```

Inheritance diagram for `epiworld::epimodels::ModelSIS< TSeq >`:



Collaboration diagram for `epiworld::epimodels::ModelSIS< TSeq >`:



## Public Member Functions

- **ModelSIS** ([ModelSIS](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)
- **ModelSIS** (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **INFECTED** = 1



## Additional Inherited Members

### 17.59.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelSIS< TSeq >
```

Template for a Susceptible-Infected-Susceptible (SIS) model.

## Parameters

<i>vname</i>	std::string Name of the virus
<i>initial_prevalence</i>	epiworld_double Initial prevalence
<i>initial_efficacy</i>	epiworld_double Initial susceptibility_reduction of the immune system
<i>initial_recovery</i>	epiworld_double Initial recovery_rate rate of the immune system

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.60 ModelSIS< TSeq > Class Template Reference

Template for a Susceptible-Infected-Susceptible (SIS) model.

```
#include <sis.hpp>
```

Inheritance diagram for ModelSIS< TSeq >:



Collaboration diagram for ModelSIS< TSeq >:



## Public Member Functions

- **ModelSIS** ([ModelSIS](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)
- **ModelSIS** (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate)

## Static Public Attributes

- static const int **SUSCEPTIBLE** = 0
- static const int **INFECTED** = 1

## Additional Inherited Members

### 17.60.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelSIS< TSeq >
```

Template for a Susceptible-Infected-Susceptible (SIS) model.

#### Parameters

<i>vname</i>	std::string Name of the virus
<i>initial_prevalence</i>	epiworld_double Initial prevalence
<i>initial_efficiency</i>	epiworld_double Initial susceptibility_reduction of the immune system
<i>initial_recovery</i>	epiworld_double Initial recovery_rate rate of the immune system

The documentation for this class was generated from the following file:

- include/epiworld/models/sis.hpp

## 17.61 epiworld::epimodels::ModelSISD< TSeq > Class Template Reference

Template for a Susceptible-Infected-Susceptible-Deceased (SISD) model.

```
#include <epiworld.hpp>
```

Inheritance diagram for `epiworld::epimodels::ModelSISD< TSeq >`:



Collaboration diagram for `epiworld::epimodels::ModelSISD< TSeq >`:



## Public Member Functions

- **ModelSISD** ([ModelSISD](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)
- **ModelSISD** (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)

## Additional Inherited Members

### 17.61.1 Detailed Description

```

template<typename TSeq = EPI_DEFAULT_TSEQ>
class epiworld::epimodels::ModelSISD< TSeq >

```

Template for a Susceptible-Infected-Susceptible-Deceased (SISD) model.

## Parameters

<i>vname</i>	std::string Name of the virus
<i>initial_prevalence</i>	epiworld_double Initial prevalence
<i>initial_efficacy</i>	epiworld_double Initial susceptibility_reduction of the immune system
<i>initial_recovery</i>	epiworld_double Initial recovery_rate rate of the immune system
<i>inital_death</i>	epiworld_double Initial death_rate of the immune system

The documentation for this class was generated from the following file:


- epiworld.hpp

## 17.62 ModelSISD< TSeq > Class Template Reference


Template for a Susceptible-Infected-Susceptible-Deceased (SISD) model.

```
#include <sisd.hpp>
```

Inheritance diagram for ModelSISD< TSeq >:



Collaboration diagram for ModelSISD< TSeq >:



## Public Member Functions

- **ModelSISD** ([ModelSISD](#)< TSeq > &model, const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)
- **ModelSISD** (const std::string &vname, epiworld\_double prevalence, epiworld\_double transmission\_rate, epiworld\_double recovery\_rate, epiworld\_double death\_rate)

## Additional Inherited Members

### 17.62.1 Detailed Description

```
template<typename TSeq = EPI_DEFAULT_TSEQ>
class ModelSISD< TSeq >
```

Template for a Susceptible-Infected-Susceptible-Deceased (SISD) model.

#### Parameters

<i>vname</i>	std::string Name of the virus
<i>initial_prevalence</i>	epiworld_double Initial prevalence
<i>initial_efficiency</i>	epiworld_double Initial susceptibility_reduction of the immune system
<i>initial_recovery</i>	epiworld_double Initial recovery_rate rate of the immune system
<i>initial_death</i>	epiworld_double Initial death_rate of the immune system

The documentation for this class was generated from the following file:

- include/epiworld/models/sisd.hpp

## 17.63 epiworld::epimodels::ModelSURV< TSeq > Class Template Reference

Inheritance diagram for epiworld::epimodels::ModelSURV< TSeq >:



Collaboration diagram for epiworld::epimodels::ModelSURV< TSeq >:



## Public Member Functions

- void [reset](#) ()  
*Reset the model.*

### Construct a new ModelSURV object

The [ModelSURV](#) class simulates a surveillance model where agents can be isolated, even if asymptomatic.

#### Parameters

vname	String. Name of the virus
prevalence	Integer. Number of initial cases of the virus.
efficacy_vax	Double. Efficacy of the vaccine ( $1 - P(\text{acquire the disease})$ ).
latent_period	Double. Shape parameter of a <i>Gamma</i> (latent_period, 1) distribution. This coincides with the expected number of latent days.
infect_period	Double. Shape parameter of a <i>Gamma</i> (infected_period, 1) distribution. This coincides with the expected number of infectious days.
prob_symptoms	Double. Probability of generating symptoms.
prop_vaccinated	Double. Probability of vaccination. Coincides with the initial prevalence of vaccinated individuals.
prop_vax_redux_transm	Double. Factor by which the vaccine reduces transmissibility.
prop_vax_redux_infect	Double. Factor by which the vaccine reduces the chances of becoming infected.
surveillance_prob	Double. Probability of testing an agent.
prob_transmission	Double. Raw transmission probability.
prob_death	Double. Raw probability of death for symptomatic individuals.
prob_noreinfect	Double. Probability of no re-infection.

This model features the following states:

- Susceptible
- Latent
- Symptomatic
- Symptomatic isolated

- *Asymptomatic*
- *Asymptomatic isolated*
- *Recovered*
- *Removed*

#### Returns

An object of class *epiworld\_surv*

- **ModelSURV** ()
- **ModelSURV** ([ModelSURV](#)< TSeq > &model, const std::string &vname, epiworld\_fast\_uint prevalence=50, epiworld\_double efficacy\_vax=0.9, epiworld\_double latent\_period=3u, epiworld\_double infect\_↵\_period=6u, epiworld\_double prob\_symptoms=0.6, epiworld\_double prop\_vaccinated=0.25, epiworld\_↵\_double prop\_vax\_redux\_transm=0.5, epiworld\_double prop\_vax\_redux\_infect=0.5, epiworld\_double surveillance\_prob=0.001, epiworld\_double prob\_transmission=1.0, epiworld\_double prob\_death=0.001, epiworld\_double prob\_noreinfect=0.9)
- **ModelSURV** (const std::string &vname, epiworld\_fast\_uint prevalence=50, epiworld\_double efficacy\_↵\_vax=0.9, epiworld\_double latent\_period=3u, epiworld\_double infect\_period=6u, epiworld\_double prob\_↵\_symptoms=0.6, epiworld\_double prop\_vaccinated=0.25, epiworld\_double prop\_vax\_redux\_transm=0.5, epiworld\_double prop\_vax\_redux\_infect=0.5, epiworld\_double surveillance\_prob=0.001, epiworld\_double prob\_transmission=1.0, epiworld\_double prob\_death=0.001, epiworld\_double prob\_noreinfect=0.9)

### Public Attributes

- std::vector< epiworld\_double > [days\\_latent\\_and\\_infectious](#)  
Vector of days spent in latent and infectious states A row-major matrix.

### Additional Inherited Members

#### 17.63.1 Member Function Documentation

##### 17.63.1.1 reset()

```
template<typename TSeq >
void ModelSURV< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:

- epiworld.hpp



## 17.64 ModelSURV< TSeq > Class Template Reference

Inheritance diagram for ModelSURV< TSeq >:



Collaboration diagram for ModelSURV< TSeq >:



### Public Member Functions

- void [reset](#) ()  
*Reset the model.*

#### Construct a new ModelSURV object

The [ModelSURV](#) class simulates a surveillance model where agents can be isolated, even if asymptomatic.

#### Parameters

vname	String. Name of the virus
prevalence	Integer. Number of initial cases of the virus.
efficacy_vax	Double. Efficacy of the vaccine ( $1 - P(\text{acquire the disease})$ ).
latent_period	Double. Shape parameter of a Gamma ( $\text{latent\_period}, 1$ ) distribution. This coincides with the expected number of latent days.

**Parameters**

infect_period	<i>Double. Shape parameter of a Gamma (infected_period, 1) distribution. This coincides with the expected number of infectious days.</i>
prob_symptoms	<i>Double. Probability of generating symptoms.</i>
prop_vaccinated	<i>Double. Probability of vaccination. Coincides with the initial prevalence of vaccinated individuals.</i>
prop_vax_redux_transm	<i>Double. Factor by which the vaccine reduces transmissibility.</i>
prop_vax_redux_infect	<i>Double. Factor by which the vaccine reduces the chances of becoming infected.</i>
surveillance_prob	<i>Double. Probability of testing an agent.</i>
prob_transmission	<i>Double. Raw transmission probability.</i>
prob_death	<i>Double. Raw probability of death for symptomatic individuals.</i>
prob_noreinfect	<i>Double. Probability of no re-infection.</i>

*This model features the following states:*

- *Susceptible*
- *Latent*
- *Symptomatic*
- *Symptomatic isolated*
- *Asymptomatic*
- *Asymptomatic isolated*
- *Recovered*
- *Removed*

**Returns**

*An object of class `epiworld_surv`*

- **ModelSURV** ()
- **ModelSURV** ([ModelSURV](#) < TSeq > &model, const std::string &vname, epiworld\_fast\_uint prevalence=50, epiworld\_double efficacy\_vax=0.9, epiworld\_double latent\_period=3u, epiworld\_double infect\_↵\_period=6u, epiworld\_double prob\_symptoms=0.6, epiworld\_double prop\_vaccinated=0.25, epiworld\_↵\_double prop\_vax\_redux\_transm=0.5, epiworld\_double prop\_vax\_redux\_infect=0.5, epiworld\_double surveillance\_prob=0.001, epiworld\_double prob\_transmission=1.0, epiworld\_double prob\_death=0.001, epiworld\_double prob\_noreinfect=0.9)
- **ModelSURV** (const std::string &vname, epiworld\_fast\_uint prevalence=50, epiworld\_double efficacy\_↵\_vax=0.9, epiworld\_double latent\_period=3u, epiworld\_double infect\_period=6u, epiworld\_double prob\_↵\_symptoms=0.6, epiworld\_double prop\_vaccinated=0.25, epiworld\_double prop\_vax\_redux\_transm=0.5, epiworld\_double prop\_vax\_redux\_infect=0.5, epiworld\_double surveillance\_prob=0.001, epiworld\_double prob\_transmission=1.0, epiworld\_double prob\_death=0.001, epiworld\_double prob\_noreinfect=0.9)

**Public Attributes**

- std::vector< epiworld\_double > [days\\_latent\\_and\\_infectious](#)  
*Vector of days spent in latent and infectious states A row-major matrix.*

**Additional Inherited Members****17.64.1 Member Function Documentation**

### 17.64.1.1 reset()

```
template<typename TSeq >
void ModelSURV< TSeq >::reset [inline], [virtual]
```

Reset the model.

Resetting the model will:

- clear the database
- restore the population (if `set_backup()` was called before)
- re-distribute tools
- re-distribute viruses
- set the date to 0

Reimplemented from [epiworld::Model< EPI\\_DEFAULT\\_TSEQ >](#).

The documentation for this class was generated from the following file:

- `include/epiworld/models/surveillance.hpp`

## 17.65 Network< Nettype, Nodetype, Edgetype > Class Template Reference

### Public Member Functions

- **NType** ()
- Edgetype **operator()** (int i, int j)
- bool **is\_directed** () const
- size\_t **vcount** () const
- size\_t **ecount** () const
- void **add\_edge** (int i, int j)
- void **rm\_edge** (int i, int j)

The documentation for this class was generated from the following file:

- `include/epiworld/network-bones.hpp`

## 17.66 epiworld::PersonTools< TSeq > Class Template Reference

The documentation for this class was generated from the following file:

- `epiworld.hpp`

## 17.67 PersonTools< TSeq > Class Template Reference

The documentation for this class was generated from the following file:

- include/epiworld/config.hpp

## 17.68 epiworld::Progress Class Reference

A simple progress bar.

```
#include <epiworld.hpp>
```

### Public Member Functions

- **Progress** (int n\_, int width\_)
- void **start** ()
- void **next** ()

### 17.68.1 Detailed Description

A simple progress bar.

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.69 Progress Class Reference

A simple progress bar.

```
#include <progress.hpp>
```

### Public Member Functions

- **Progress** (int n\_, int width\_)
- void **start** ()
- void **next** ()

### 17.69.1 Detailed Description

A simple progress bar.

The documentation for this class was generated from the following file:

- include/epiworld/progress.hpp

## 17.70 epiworld::Queue< TSeq > Class Template Reference

Controls which agents are verified at each step.

```
#include <epiworld.hpp>
```

### Public Member Functions

- void **operator+=** ([Agent](#)< TSeq > \*p)
- void **operator-=** ([Agent](#)< TSeq > \*p)
- epiworld\_fast\_int & **operator[]** (epiworld\_fast\_uint i)
- void **reset** ()
- bool **operator==** (const [Queue](#)< TSeq > &other) const
- bool **operator!=** (const [Queue](#)< TSeq > &other) const

### Static Public Attributes

- static const int **NoOne** = 0
- static const int **OnlySelf** = 1
- static const int **Everyone** = 2

### Friends

- class **Model**< TSeq >

### 17.70.1 Detailed Description

```
template<typename TSeq>
class epiworld::Queue< TSeq >
```

Controls which agents are verified at each step.

The idea is that only agents who are either in an infected state or have an infected neighbor should be checked. Otherwise it makes no sense (no chance to recover or capture the disease).

#### Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.71 Queue< TSeq > Class Template Reference

Controls which agents are verified at each step.

```
#include <queue-bones.hpp>
```

## Public Member Functions

- void **operator+=** ([Agent](#)< TSeq > \*p)
- void **operator-=** ([Agent](#)< TSeq > \*p)
- epiworld\_fast\_int & **operator[]** (epiworld\_fast\_uint i)
- void **reset** ()
- bool **operator==** (const [Queue](#)< TSeq > &other) const
- bool **operator!=** (const [Queue](#)< TSeq > &other) const

## Static Public Attributes

- static const int **NoOne** = 0
- static const int **OnlySelf** = 1
- static const int **Everyone** = 2

## Friends

- class **Model**< TSeq >

### 17.71.1 Detailed Description

```
template<typename TSeq>
class Queue< TSeq >
```

Controls which agents are verified at each step.

The idea is that only agents who are either in an infected state or have an infected neighbor should be checked. Otherwise it makes no sense (no chance to recover or capture the disease).

#### Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/queue-bones.hpp

## 17.72 RandGraph Class Reference

### Public Member Functions

- **RandGraph** (int N\_)
- void **init** (int s)
- void **set\_rand\_engine** (std::shared\_ptr< std::mt19937 > &e)
- epiworld\_double **runif** ()

The documentation for this class was generated from the following file:

- include/epiworld/random\_graph.hpp

## 17.73 epiworld::SAMPLETYPE Class Reference

### Static Public Attributes

- static const int **MODEL** = 0
- static const int **ENTITY** = 1
- static const int **AGENT** = 2

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.74 SAMPLETYPE Class Reference

### Static Public Attributes

- static const int **MODEL** = 0
- static const int **ENTITY** = 1
- static const int **AGENT** = 2

The documentation for this class was generated from the following file:

- include/epiworld/agentssample-bones.hpp

## 17.75 TestResults Struct Reference

### Public Attributes

- epimodels::ModelMeaslesMixingRiskQuarantine **model**
- std::vector< epiworld\_double > **transitions**
- std::vector< epiworld\_double > **R0s**
- std::vector< std::vector< int > > **final\_distribution**
- std::vector< double > **sizes**

The documentation for this struct was generated from the following file:

- tests/20c-measles-mixing-risk-quarantine-durations.cpp

## 17.76 epiworld::Tool< TSeq > Class Template Reference

[Tools](#) for defending the agent against the virus.

```
#include <epiworld.hpp>
```

## Public Member Functions

- **Tool** (std::string name="unknown tool")
- **Tool** (std::string name, epiworld\_double prevalence, bool as\_proportion)
- void **set\_sequence** (TSeq d)
- void **set\_sequence** (std::shared\_ptr< TSeq > d)
- **EPI\_TYPENAME\_TRAITS** (TSeq, int) get\_sequence()
- void **set\_name** (std::string name)
- std::string **get\_name** () const
- [Agent](#)< TSeq > \* **get\_agent** ()
- int **get\_id** () const
- void **set\_id** (int id)
- void **set\_date** (int d)
- int **get\_date** () const
- void **set\_state** (epiworld\_fast\_int init, epiworld\_fast\_int post)
- void **set\_queue** (epiworld\_fast\_int init, epiworld\_fast\_int post)
- void **get\_state** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*post)
- void **get\_queue** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*post)
- bool **operator==** (const [Tool](#)< TSeq > &other) const
- bool **operator!=** (const [Tool](#)< TSeq > &other) const
- void **print** () const
- void **distribute** ([Model](#)< TSeq > \*model)
- void **set\_distribution** (ToolToAgentFun< TSeq > fun)

### Get and set the tool functions

#### Parameters

v	<i>The virus over which to operate</i>
fun	<i>the function to be used</i>

#### Returns

*epiworld\_double*

- epiworld\_double **get\_susceptibility\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- epiworld\_double **get\_transmission\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- epiworld\_double **get\_recovery\_enhancer** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- epiworld\_double **get\_death\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- void **set\_susceptibility\_reduction\_fun** (ToolFun< TSeq > fun)
- void **set\_transmission\_reduction\_fun** (ToolFun< TSeq > fun)
- void **set\_recovery\_enhancer\_fun** (ToolFun< TSeq > fun)
- void **set\_death\_reduction\_fun** (ToolFun< TSeq > fun)
- void **set\_susceptibility\_reduction** (epiworld\_double \*prob)
- void **set\_transmission\_reduction** (epiworld\_double \*prob)
- void **set\_recovery\_enhancer** (epiworld\_double \*prob)
- void **set\_death\_reduction** (epiworld\_double \*prob)
- void **set\_susceptibility\_reduction** (epiworld\_double prob)
- void **set\_transmission\_reduction** (epiworld\_double prob)
- void **set\_recovery\_enhancer** (epiworld\_double prob)
- void **set\_death\_reduction** (epiworld\_double prob)

## Friends

- class **Agent**< TSeq >
- class **Model**< TSeq >
- void **default\_add\_tool** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_tool** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)



### 17.76.1 Detailed Description

```
template<typename TSeq>
class epiworld::Tool< TSeq >
```

[Tools](#) for defending the agent against the virus.

#### Template Parameters

<i>TSeq</i>	Type of sequence
-------------	------------------

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.77 Tool< TSeq > Class Template Reference

[Tools](#) for defending the agent against the virus.

```
#include <tool-bones.hpp>
```

### Public Member Functions

- **Tool** (std::string name="unknown tool")
- **Tool** (std::string name, epiworld\_double prevalence, bool as\_proportion)
- void **set\_sequence** (TSeq d)
- void **set\_sequence** (std::shared\_ptr< TSeq > d)
- **EPI\_TYPENAME\_TRAITS** (TSeq, int) get\_sequence()
- void **set\_name** (std::string name)
- std::string **get\_name** () const
- [Agent](#)< TSeq > \* **get\_agent** ()
- int **get\_id** () const
- void **set\_id** (int id)
- void **set\_date** (int d)
- int **get\_date** () const
- void **set\_state** (epiworld\_fast\_int init, epiworld\_fast\_int post)
- void **set\_queue** (epiworld\_fast\_int init, epiworld\_fast\_int post)
- void **get\_state** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*post)
- void **get\_queue** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*post)
- bool **operator==** (const [Tool](#)< TSeq > &other) const
- bool **operator!=** (const [Tool](#)< TSeq > &other) const
- void **print** () const
- void **distribute** ([Model](#)< TSeq > \*model)
- void **set\_distribution** (ToolToAgentFun< TSeq > fun)
- void **set\_sequence** (int d)
- bool **operator==** (const [Tool](#)< std::vector< int >> &other) const
- void **set\_sequence** (int d)
- bool **operator==** (const [Tool](#)< std::vector< int >> &other) const

#### Get and set the tool functions

**Parameters**

v	<i>The virus over which to operate</i>
fun	<i>the function to be used</i>

**Returns**

*epiworld\_double*

- `epiworld_double` **get\_susceptibility\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- `epiworld_double` **get\_transmission\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- `epiworld_double` **get\_recovery\_enhancer** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- `epiworld_double` **get\_death\_reduction** (VirusPtr< TSeq > v, [Model](#)< TSeq > \*model)
- void **set\_susceptibility\_reduction\_fun** (ToolFun< TSeq > fun)
- void **set\_transmission\_reduction\_fun** (ToolFun< TSeq > fun)
- void **set\_recovery\_enhancer\_fun** (ToolFun< TSeq > fun)
- void **set\_death\_reduction\_fun** (ToolFun< TSeq > fun)
- void **set\_susceptibility\_reduction** (epiworld\_double \*prob)
- void **set\_transmission\_reduction** (epiworld\_double \*prob)
- void **set\_recovery\_enhancer** (epiworld\_double \*prob)
- void **set\_death\_reduction** (epiworld\_double \*prob)
- void **set\_susceptibility\_reduction** (epiworld\_double prob)
- void **set\_transmission\_reduction** (epiworld\_double prob)
- void **set\_recovery\_enhancer** (epiworld\_double prob)
- void **set\_death\_reduction** (epiworld\_double prob)

**Friends**

- class **Agent**< TSeq >
- class **Model**< TSeq >
- void **default\_add\_tool** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_tool** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)

**17.77.1 Detailed Description**

```
template<typename TSeq>
class Tool< TSeq >
```

[Tools](#) for defending the agent against the virus.

**Template Parameters**

<i>TSeq</i>	Type of sequence
-------------	------------------

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/tool-bones.hpp
- include/epiworld/tool-meat.hpp

**17.78 epiworld::ToolFunctions< TSeq > Class Template Reference**

Helper class to store the functions avoiding multiple shared\_pointers (we have only one for the four of these)

```
#include <epiworld.hpp>
```

## Public Attributes

- ToolFun< TSeq > **susceptibility\_reduction** = nullptr
- ToolFun< TSeq > **transmission\_reduction** = nullptr
- ToolFun< TSeq > **recovery\_enhancer** = nullptr
- ToolFun< TSeq > **death\_reduction** = nullptr
- ToolToAgentFun< TSeq > **dist** = nullptr

### 17.78.1 Detailed Description

```
template<typename TSeq>
class epiworld::ToolFunctions< TSeq >
```

Helper class to store the functions avoiding multiple shared\_pointers (we have only one for the four of these)

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.79 ToolFunctions< TSeq > Class Template Reference

Helper class to store the functions avoiding multiple shared\_pointers (we have only one for the four of these)

```
#include <tool-bones.hpp>
```

## Public Attributes

- ToolFun< TSeq > **susceptibility\_reduction** = nullptr
- ToolFun< TSeq > **transmission\_reduction** = nullptr
- ToolFun< TSeq > **recovery\_enhancer** = nullptr
- ToolFun< TSeq > **death\_reduction** = nullptr
- ToolToAgentFun< TSeq > **dist** = nullptr

### 17.79.1 Detailed Description

```
template<typename TSeq>
class ToolFunctions< TSeq >
```

Helper class to store the functions avoiding multiple shared\_pointers (we have only one for the four of these)

The documentation for this class was generated from the following file:

- include/epiworld/tool-bones.hpp

## 17.80 epiworld::Tools< TSeq > Class Template Reference

Set of tools (useful for building iterators)

```
#include <epiworld.hpp>
```

### Public Member Functions

- **Tools** ([Agent](#)< TSeq > &p)
- std::vector< ToolPtr< TSeq > >::iterator **begin** ()
- std::vector< ToolPtr< TSeq > >::iterator **end** ()
- ToolPtr< TSeq > & **operator**() (size\_t i)
- ToolPtr< TSeq > & **operator**[] (size\_t i)
- size\_t **size** () const noexcept
- void **print** () const noexcept

### Friends

- class **Tool**< TSeq >
- class **Agent**< TSeq >

### 17.80.1 Detailed Description

```
template<typename TSeq>
class epiworld::Tools< TSeq >
```

Set of tools (useful for building iterators)

#### Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.81 Tools< TSeq > Class Template Reference

Set of tools (useful for building iterators)

```
#include <tools-bones.hpp>
```

## Public Member Functions

- **Tools** ([Agent](#)< TSeq > &p)
- std::vector< ToolPtr< TSeq > >::iterator **begin** ()
- std::vector< ToolPtr< TSeq > >::iterator **end** ()
- ToolPtr< TSeq > & **operator**() (size\_t i)
- ToolPtr< TSeq > & **operator**[] (size\_t i)
- size\_t **size** () const noexcept
- void **print** () const noexcept

## Friends

- class **Tool**< TSeq >
- class **Agent**< TSeq >

### 17.81.1 Detailed Description

```
template<typename TSeq>
class Tools< TSeq >
```

Set of tools (useful for building iterators)

#### Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/tools-bones.hpp

## 17.82 epiworld::Tools\_const< TSeq > Class Template Reference

Set of [Tools](#) (const) (useful for iterators)

```
#include <epiworld.hpp>
```

## Public Member Functions

- **Tools\_const** (const [Agent](#)< TSeq > &p)
- std::vector< ToolPtr< TSeq > >::const\_iterator **begin** () const
- std::vector< ToolPtr< TSeq > >::const\_iterator **end** () const
- const ToolPtr< TSeq > & **operator**() (size\_t i)
- const ToolPtr< TSeq > & **operator**[] (size\_t i)
- size\_t **size** () const noexcept
- void **print** () const noexcept

## Friends

- class **Tool**< TSeq >
- class **Agent**< TSeq >

### 17.82.1 Detailed Description

```
template<typename TSeq>
class epiworld::Tools_const< TSeq >
```

Set of [Tools](#) (const) (useful for iterators)

#### Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.83 Tools\_const< TSeq > Class Template Reference

Set of [Tools](#) (const) (useful for iterators)

```
#include <tools-bones.hpp>
```

## Public Member Functions

- **Tools\_const** (const [Agent](#)< TSeq > &p)
- std::vector< ToolPtr< TSeq > >::const\_iterator **begin** () const
- std::vector< ToolPtr< TSeq > >::const\_iterator **end** () const
- const ToolPtr< TSeq > & **operator()** (size\_t i)
- const ToolPtr< TSeq > & **operator[]** (size\_t i)
- size\_t **size** () const noexcept
- void **print** () const noexcept

## Friends

- class **Tool**< TSeq >
- class **Agent**< TSeq >

### 17.83.1 Detailed Description

```
template<typename TSeq>
class Tools_const< TSeq >
```

Set of [Tools](#) (const) (useful for iterators)

## Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/tools-bones.hpp

## 17.84 epiworld::UserData< TSeq > Class Template Reference

Personalized data by the user.

```
#include <epiworld.hpp>
```

### Public Member Functions

- **UserData** ([Model](#)< TSeq > &m)
- **UserData** ([Model](#)< TSeq > \*m)
- **UserData** (std::vector< std::string > names)  
*Construct a new User Data object.*
- std::vector< std::string > & **get\_names** ()
- std::vector< int > & **get\_dates** ()
- std::vector< epiworld\_double > & **get\_data** ()
- void **get\_all** (std::vector< std::string > \*names=nullptr, std::vector< int > \*date=nullptr, std::vector< epiworld\_double > \*data=nullptr)
- epiworld\_fast\_uint **nrow** () const
- epiworld\_fast\_uint **ncol** () const
- void **write** (std::string fn)
- void **print** () const

### Append data

#### Parameters

x	A vector of length <code>ncol()</code> (if vector), otherwise a <code>epiworld_double</code> .
j	Index of the data point, from 0 to <code>ncol()</code> - 1.

- void **add** (std::vector< epiworld\_double > x)
- void **add** (epiworld\_fast\_uint j, epiworld\_double x)

### Access data

#### Parameters

i	Row (0 through <code>ndays</code> - 1.)
j	Column (0 through <code>ncols()</code> ).

*Returns**epiworld\_double&*

- *epiworld\_double* & **operator()** (*epiworld\_fast\_uint* i, *epiworld\_fast\_uint* j)
- *epiworld\_double* & **operator()** (*epiworld\_fast\_uint* i, *std::string* name)

**Friends**

- class **Model**< **TSeq** >
- class **DataBase**< **TSeq** >

**17.84.1 Detailed Description**

```
template<typename TSeq>
class epiworld::UserData< TSeq >
```

Personalized data by the user.

**Template Parameters**

<i>TSeq</i>	
-------------	--

**17.84.2 Constructor & Destructor Documentation****17.84.2.1 UserData()**

```
template<typename TSeq >
UserData< TSeq >::UserData (
 std::vector< std::string > names) [inline]
```

Construct a new User Data object.

**Parameters**

<i>names</i>	A vector of names. The length of the vector sets the number of columns to record.
--------------	-----------------------------------------------------------------------------------

The documentation for this class was generated from the following file:

- *epiworld.hpp*

**17.85 UserData< TSeq > Class Template Reference**

Personalized data by the user.

```
#include <userdata-bones.hpp>
```



## Public Member Functions

- **UserData** ([Model](#)< TSeq > &m)
- **UserData** ([Model](#)< TSeq > \*m)
- **UserData** (std::vector< std::string > names)  
Construct a new User Data object.
- std::vector< std::string > & **get\_names** ()
- std::vector< int > & **get\_dates** ()
- std::vector< epiworld\_double > & **get\_data** ()
- void **get\_all** (std::vector< std::string > \*names=nullptr, std::vector< int > \*date=nullptr, std::vector< epiworld\_double > \*data=nullptr)
- epiworld\_fast\_uint **nrow** () const
- epiworld\_fast\_uint **ncol** () const
- void **write** (std::string fn)
- void **print** () const

## Append data

### Parameters

x	A vector of length <code>ncol()</code> (if vector), otherwise a <code>epiworld_double</code> .
j	Index of the data point, from 0 to <code>ncol()</code> - 1.

- void **add** (std::vector< epiworld\_double > x)
- void **add** (epiworld\_fast\_uint j, epiworld\_double x)

## Access data

### Parameters

i	Row (0 through <code>ndays</code> - 1.)
j	Column (0 through <code>ncols()</code> ).

### Returns

`epiworld_double&`

- epiworld\_double & **operator()** (epiworld\_fast\_uint i, epiworld\_fast\_uint j)
- epiworld\_double & **operator()** (epiworld\_fast\_uint i, std::string name)

## Friends

- class **Model**< TSeq >
- class **DataBase**< TSeq >

## 17.85.1 Detailed Description

```
template<typename TSeq>
class UserData< TSeq >
```

Personalized data by the user.

## Template Parameters

<i>TSeq</i>	
-------------	--

## 17.85.2 Constructor & Destructor Documentation

### 17.85.2.1 UserData()

```
template<typename TSeq >
UserData< TSeq >::UserData (
 std::vector< std::string > names) [inline]
```

Construct a new User Data object.

## Parameters

<i>names</i>	A vector of names. The length of the vector sets the number of columns to record.
--------------	-----------------------------------------------------------------------------------

The documentation for this class was generated from the following files:

- include/epiworld/database-bones.hpp
- include/epiworld/userdata-bones.hpp
- include/epiworld/userdata-meat.hpp

## 17.86 epiworld::vecHasher< T > Struct Template Reference

Vector hasher.

```
#include <epiworld.hpp>
```

### Public Member Functions

- `std::size_t operator() (std::vector< T > const &dat) const` noexcept

### 17.86.1 Detailed Description

```
template<typename T>
struct epiworld::vecHasher< T >
```

Vector hasher.

## Template Parameters

<i>T</i>	
----------	--

The documentation for this struct was generated from the following file:

- epiworld.hpp

## 17.87 vecHasher< T > Struct Template Reference

Vector hasher.

```
#include <misc.hpp>
```

### Public Member Functions

- `std::size_t operator() (std::vector< T > const &dat) const` noexcept

#### 17.87.1 Detailed Description

```
template<typename T>
struct vecHasher< T >
```

Vector hasher.

## Template Parameters

<i>T</i>	
----------	--

The documentation for this struct was generated from the following file:

- include/epiworld/misc.hpp

## 17.88 epiworld::Virus< TSeq > Class Template Reference

[Virus](#).

```
#include <epiworld.hpp>
```

## Public Member Functions

- **Virus** (std::string name="unknown virus")
- **Virus** (std::string name, epiworld\_double prevalence, bool as\_proportion)
- void **mutate** (Model< TSeq > \*model)
- void **set\_mutation** (MutFun< TSeq > fun)
- **EPI\_TYPENAME\_TRAITS** (TSeq, int) get\_sequence()
- void **set\_sequence** (TSeq sequence)
- Agent< TSeq > \* **get\_agent** ()
- void **set\_agent** (Agent< TSeq > \*p)
- void **set\_date** (int d)
- int **get\_date** () const
- void **set\_id** (int idx)
- int **get\_id** () const
- void **set\_name** (std::string name)
- std::string **get\_name** () const
- bool **operator==** (const Virus< TSeq > &other) const
- bool **operator!=** (const Virus< TSeq > &other) const
- void **print** () const

### Get and set the tool functions

#### Parameters

v	<i>The virus over which to operate</i>
fun	<i>the function to be used</i>

#### Returns

*epiworld\_double*

- epiworld\_double **get\_prob\_infecting** (Model< TSeq > \*model)
- epiworld\_double **get\_prob\_recovery** (Model< TSeq > \*model)
- epiworld\_double **get\_prob\_death** (Model< TSeq > \*model)
- epiworld\_double **get\_incubation** (Model< TSeq > \*model)
- void **post\_recovery** (Model< TSeq > \*model)
- void **set\_post\_recovery** (PostRecoveryFun< TSeq > fun)
- void **set\_post\_immunity** (epiworld\_double prob)
- void **set\_post\_immunity** (epiworld\_double \*prob)
- void **set\_prob\_infecting\_fun** (VirusFun< TSeq > fun)
- void **set\_prob\_recovery\_fun** (VirusFun< TSeq > fun)
- void **set\_prob\_death\_fun** (VirusFun< TSeq > fun)
- void **set\_incubation\_fun** (VirusFun< TSeq > fun)
- void **set\_prob\_infecting** (const epiworld\_double \*prob)
- void **set\_prob\_recovery** (const epiworld\_double \*prob)
- void **set\_prob\_death** (const epiworld\_double \*prob)
- void **set\_incubation** (const epiworld\_double \*prob)
- void **set\_prob\_infecting** (epiworld\_double prob)
- void **set\_prob\_recovery** (epiworld\_double prob)
- void **set\_prob\_death** (epiworld\_double prob)
- void **set\_incubation** (epiworld\_double prob)

### Get and set the state and queue

After applied, viruses can change the state and affect the queue of agents. These function sets the default values, which are retrieved when adding or removing a virus does not specify a change in state or in queue.

*Parameters*

init	After the virus/tool is added to the agent.
end	After the virus/tool is removed.
removed	After the agent ( <a href="#">Agent</a> ) is removed.

- void **set\_state** (epiworld\_fast\_int init, epiworld\_fast\_int end, epiworld\_fast\_int removed=-99)
  - void **set\_queue** (epiworld\_fast\_int init, epiworld\_fast\_int end, epiworld\_fast\_int removed=-99)
  - void **get\_state** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*end, epiworld\_fast\_int \*removed=nullptr)
  - void **get\_queue** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*end, epiworld\_fast\_int \*removed=nullptr)
- 
- void **distribute** ([Model](#)< TSeq > \*model)  
Get information about the prevalence of the virus.
  - void **set\_distribution** (VirusToAgentFun< TSeq > fun)

**Friends**

- class **Agent**< TSeq >
- class **Model**< TSeq >
- class **DataBase**< TSeq >
- void **default\_add\_virus** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_virus** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)

**17.88.1 Detailed Description**

```
template<typename TSeq>
class epiworld::Virus< TSeq >
```

[Virus](#).

**Template Parameters**

<i>TSeq</i>	
-------------	--

Raw transmissibility of a virus should be a function of its genetic sequence. Nonetheless, transmissibility can be reduced as a result of having one or more tools to fight the virus. Because of this, transmissibility should be a function of the agent.

The documentation for this class was generated from the following file:

- epiworld.hpp

**17.89 Virus< TSeq > Class Template Reference**

[Virus](#).

```
#include <virus-bones.hpp>
```

## Public Member Functions

- **Virus** (std::string name="unknown virus")
- **Virus** (std::string name, epiworld\_double prevalence, bool as\_proportion)
- void **mutate** (Model< TSeq > \*model)
- void **set\_mutation** (MutFun< TSeq > fun)
- **EPI\_TYPENAME\_TRAITS** (TSeq, int) get\_sequence()
- void **set\_sequence** (TSeq sequence)
- Agent< TSeq > \* **get\_agent** ()
- void **set\_agent** (Agent< TSeq > \*p)
- void **set\_date** (int d)
- int **get\_date** () const
- void **set\_id** (int idx)
- int **get\_id** () const
- void **set\_name** (std::string name)
- std::string **get\_name** () const
- bool **operator==** (const Virus< TSeq > &other) const
- bool **operator!=** (const Virus< TSeq > &other) const
- void **print** () const
- void **set\_sequence** (int sequence)
- bool **operator==** (const Virus< std::vector< int >> &other) const
- void **set\_sequence** (int sequence)
- bool **operator==** (const Virus< std::vector< int >> &other) const

### Get and set the tool functions

#### Parameters

v	<i>The virus over which to operate</i>
fun	<i>the function to be used</i>

#### Returns

*epiworld\_double*

- epiworld\_double **get\_prob\_infecting** (Model< TSeq > \*model)
- epiworld\_double **get\_prob\_recovery** (Model< TSeq > \*model)
- epiworld\_double **get\_prob\_death** (Model< TSeq > \*model)
- epiworld\_double **get\_incubation** (Model< TSeq > \*model)
- void **post\_recovery** (Model< TSeq > \*model)
- void **set\_post\_recovery** (PostRecoveryFun< TSeq > fun)
- void **set\_post\_immunity** (epiworld\_double prob)
- void **set\_post\_immunity** (epiworld\_double \*prob)
- void **set\_prob\_infecting\_fun** (VirusFun< TSeq > fun)
- void **set\_prob\_recovery\_fun** (VirusFun< TSeq > fun)
- void **set\_prob\_death\_fun** (VirusFun< TSeq > fun)
- void **set\_incubation\_fun** (VirusFun< TSeq > fun)
- void **set\_prob\_infecting** (const epiworld\_double \*prob)
- void **set\_prob\_recovery** (const epiworld\_double \*prob)
- void **set\_prob\_death** (const epiworld\_double \*prob)
- void **set\_incubation** (const epiworld\_double \*prob)
- void **set\_prob\_infecting** (epiworld\_double prob)
- void **set\_prob\_recovery** (epiworld\_double prob)
- void **set\_prob\_death** (epiworld\_double prob)
- void **set\_incubation** (epiworld\_double prob)

### Get and set the state and queue

After applied, viruses can change the state and affect the queue of agents. These function sets the default values, which are retrieved when adding or removing a virus does not specify a change in state or in queue.

*Parameters*

init	<i>After the virus/tool is added to the agent.</i>
end	<i>After the virus/tool is removed.</i>
removed	<i>After the agent (<a href="#">Agent</a>) is removed.</i>

- void **set\_state** (epiworld\_fast\_int init, epiworld\_fast\_int end, epiworld\_fast\_int removed=-99)
  - void **set\_queue** (epiworld\_fast\_int init, epiworld\_fast\_int end, epiworld\_fast\_int removed=-99)
  - void **get\_state** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*end, epiworld\_fast\_int \*removed=nullptr)
  - void **get\_queue** (epiworld\_fast\_int \*init, epiworld\_fast\_int \*end, epiworld\_fast\_int \*removed=nullptr)
- 
- void **distribute** ([Model](#)< TSeq > \*model)  
*Get information about the prevalence of the virus.*
  - void **set\_distribution** (VirusToAgentFun< TSeq > fun)

**Friends**

- class **Agent**< TSeq >
- class **Model**< TSeq >
- class **DataBase**< TSeq >
- void **default\_add\_virus** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)
- void **default\_rm\_virus** ([Event](#)< TSeq > &a, [Model](#)< TSeq > \*m)

**17.89.1 Detailed Description**

```
template<typename TSeq>
class Virus< TSeq >
```

[Virus](#).

**Template Parameters**

<i>TSeq</i>	
-------------	--

Raw transmissibility of a virus should be a function of its genetic sequence. Nonetheless, transmissibility can be reduced as a result of having one or more tools to fight the virus. Because of this, transmissibility should be a function of the agent.

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/virus-bones.hpp
- include/epiworld/virus-meat.hpp

## 17.90 epiworld::Viruses< TSeq > Class Template Reference

Set of viruses (useful for building iterators)

```
#include <epiworld.hpp>
```

### Public Member Functions

- **Viruses** ([Agent](#)< TSeq > &p)
- std::vector< VirusPtr< TSeq > >::iterator **begin** ()
- std::vector< VirusPtr< TSeq > >::iterator **end** ()
- VirusPtr< TSeq > & **operator**() (size\_t i)
- VirusPtr< TSeq > & **operator**[] (size\_t i)
- size\_t **size** () const noexcept
- void **print** () const noexcept

### Friends

- class **Virus**< TSeq >
- class **Agent**< TSeq >

### 17.90.1 Detailed Description

```
template<typename TSeq>
class epiworld::Viruses< TSeq >
```

Set of viruses (useful for building iterators)

#### Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.91 Viruses< TSeq > Class Template Reference

Set of viruses (useful for building iterators)

```
#include <viruses-bones.hpp>
```



## Public Member Functions

- **Viruses** ([Agent](#)< TSeq > &p)
- std::vector< VirusPtr< TSeq > >::iterator **begin** ()
- std::vector< VirusPtr< TSeq > >::iterator **end** ()
- VirusPtr< TSeq > & **operator()** (size\_t i)
- VirusPtr< TSeq > & **operator[]** (size\_t i)
- size\_t **size** () const noexcept
- void **print** () const noexcept

## Friends

- class **Virus**< TSeq >
- class **Agent**< TSeq >

### 17.91.1 Detailed Description

```
template<typename TSeq>
class Viruses< TSeq >
```

Set of viruses (useful for building iterators)

#### Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/viruses-bones.hpp

## 17.92 epiworld::Viruses\_const< TSeq > Class Template Reference

Set of [Viruses](#) (const) (useful for iterators)

```
#include <epiworld.hpp>
```

## Public Member Functions

- **Viruses\_const** (const [Agent](#)< TSeq > &p)
- std::vector< VirusPtr< TSeq > >::const\_iterator **begin** () const
- std::vector< VirusPtr< TSeq > >::const\_iterator **end** () const
- const VirusPtr< TSeq > & **operator()** (size\_t i)
- const VirusPtr< TSeq > & **operator[]** (size\_t i)
- size\_t **size** () const noexcept
- void **print** () const noexcept

## Friends

- class **Virus**< TSeq >
- class **Agent**< TSeq >

### 17.92.1 Detailed Description

```
template<typename TSeq>
class epiworld::Viruses_const< TSeq >
```

Set of [Viruses](#) (const) (useful for iterators)

#### Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.93 Viruses\_const< TSeq > Class Template Reference

Set of [Viruses](#) (const) (useful for iterators)

```
#include <viruses-bones.hpp>
```

## Public Member Functions

- **Viruses\_const** (const [Agent](#)< TSeq > &p)
- std::vector< VirusPtr< TSeq > >::const\_iterator **begin** () const
- std::vector< VirusPtr< TSeq > >::const\_iterator **end** () const
- const VirusPtr< TSeq > & **operator()** (size\_t i)
- const VirusPtr< TSeq > & **operator[]** (size\_t i)
- size\_t **size** () const noexcept
- void **print** () const noexcept

## Friends

- class **Virus**< TSeq >
- class **Agent**< TSeq >

### 17.93.1 Detailed Description

```
template<typename TSeq>
class Viruses_const< TSeq >
```

Set of [Viruses](#) (const) (useful for iterators)

## Template Parameters

<i>TSeq</i>	
-------------	--

The documentation for this class was generated from the following files:

- include/epiworld/agent-bones.hpp
- include/epiworld/viruses-bones.hpp

## 17.94 epiworld::VirusFunctions< TSeq > Class Template Reference

### Public Attributes

- MutFun< TSeq > **mutation** = nullptr
- PostRecoveryFun< TSeq > **post\_recovery** = nullptr
- VirusFun< TSeq > **probability\_of\_infecting** = nullptr
- VirusFun< TSeq > **probability\_of\_recovery** = nullptr
- VirusFun< TSeq > **probability\_of\_death** = nullptr
- VirusFun< TSeq > **incubation** = nullptr
- VirusToAgentFun< TSeq > **dist** = nullptr

The documentation for this class was generated from the following file:

- epiworld.hpp

## 17.95 VirusFunctions< TSeq > Class Template Reference

### Public Attributes

- MutFun< TSeq > **mutation** = nullptr
- PostRecoveryFun< TSeq > **post\_recovery** = nullptr
- VirusFun< TSeq > **probability\_of\_infecting** = nullptr
- VirusFun< TSeq > **probability\_of\_recovery** = nullptr
- VirusFun< TSeq > **probability\_of\_death** = nullptr
- VirusFun< TSeq > **incubation** = nullptr
- VirusToAgentFun< TSeq > **dist** = nullptr

The documentation for this class was generated from the following file:

- include/epiworld/virus-bones.hpp



## Chapter 18

# File Documentation

### 18.1 include/epiworld/agent-meat-state.hpp File Reference

Sampling functions are getting big, so we keep them in a separate file.

```
#include "model-bones.hpp"
#include "agent-meat-virus-sampling.hpp"
#include "config.hpp"
```

Include dependency graph for agent-meat-state.hpp:



This graph shows which files directly or indirectly include this file:



## Functions

- `template<typename TSeq = EPI_DEFAULT_TSEQ>`  
`void default_update_susceptible (Agent< TSeq > *p, Model< TSeq > *m)`
- `template<typename TSeq = EPI_DEFAULT_TSEQ>`  
`void default_update_exposed (Agent< TSeq > *p, Model< TSeq > *m)`

### 18.1.1 Detailed Description

Sampling functions are getting big, so we keep them in a separate file.

#### Author

George G. Vega Yon (g.vegayon en gmail)

#### Version

0.1

#### Date

2022-06-15

#### Copyright

Copyright (c) 2022

## 18.2 include/epiworld/models/measlesmixing.hpp File Reference

Template for a Measles model with population mixing, quarantine, and contact tracing.

This graph shows which files directly or indirectly include this file:



### Classes

- class [ModelMeaslesMixing< TSeq >](#)  
*Measles model with population mixing, quarantine, and contact tracing.*

### Macros

- #define **MM**(i, j, n)  $j * n + i$
- #define **GET\_MODEL**(model, output)
- #define **SAMPLE\_FROM\_PROBS**(n, ans)

#### 18.2.1 Detailed Description

Template for a Measles model with population mixing, quarantine, and contact tracing.

#### 18.2.2 Macro Definition Documentation

### 18.2.2.1 GET\_MODEL

```
#define GET_MODEL(
 model,
 output)
```

**Value:**

```
auto * output = dynamic_cast< ModelMeaslesMixing<TSeq> * >((model)); \
assert((output) != nullptr);
```

### 18.2.2.2 SAMPLE\_FROM\_PROBS

```
#define SAMPLE_FROM_PROBS(
 n,
 ans)
```

**Value:**

```
size_t ans; \
epiworld_double p_total = m->runif(); \
for (ans = 0u; ans < n; ++ans) \
{ \
 if (p_total < m->array_double_tmp[ans]) \
 break; \
 m->array_double_tmp[ans + 1] += m->array_double_tmp[ans]; \
}
```

## 18.3 include/epiworld/models/measlesmixingriskquarantine.hpp File Reference

Template for a Measles model with population mixing and risk-based quarantine.

This graph shows which files directly or indirectly include this file:





## Classes

- class [ModelMeaslesMixingRiskQuarantine< TSeq >](#)  
*Measles model with population mixing and risk-based quarantine strategies.*

## Macros

- #define [COL\\_MAJOR\\_POS](#)(i, j, n) (j \* n + i)
- #define [GET\\_MODEL](#)(model, output)
- #define [SAMPLE\\_FROM\\_PROBS](#)(n, ans)  
*Macro to sample from a list of probabilities.*

### 18.3.1 Detailed Description

Template for a Measles model with population mixing and risk-based quarantine.

### 18.3.2 Macro Definition Documentation

#### 18.3.2.1 GET\_MODEL

```
#define GET_MODEL(
 model,
 output)
```

##### Value:

```
auto * output = dynamic_cast< ModelMeaslesMixingRiskQuarantine<TSeq> * >((model)); \
assert((output) != nullptr);
```

#### 18.3.2.2 SAMPLE\_FROM\_PROBS

```
#define SAMPLE_FROM_PROBS(
 n,
 ans)
```

##### Value:

```
int ans; \
epiworld_double p_total = m->runif(); \
for (ans = 0; ans < static_cast<int>(n); ans++) \
{ \
 if (p_total < m->array_double_tmp[ans]) \
 break; \
 m->array_double_tmp[ans + 1] += m->array_double_tmp[ans]; \
};
```

Macro to sample from a list of probabilities.

##### Returns

The index of the sampled probability; and the total length if none is found, returns n.



# Index

add\_contact  
    ContactTracing, 68  
    epiworld::ContactTracing, 71  
add\_globolevent  
    epiworld::Model< TSeq >, 107  
    Model< TSeq >, 123  
AdjList, 53  
    AdjList, 53  
    epiworld::AdjList, 55  
    read\_edgelist, 54  
Agent< TSeq >, 56  
    default\_rm\_entity, 60  
    operator(), 58  
    swap\_neighbors, 60  
AgentsSample  
    AgentsSample< TSeq >, 65  
    epiworld::AgentsSample< TSeq >, 67  
AgentsSample< TSeq >, 64  
    AgentsSample, 65  
clone\_ptr  
    epiworld::epimodels::ModelMeaslesMixing< TSeq  
        >, 140  
    epiworld::epimodels::ModelMeaslesMixingRiskQuarantine<  
        TSeq >, 156  
    epiworld::epimodels::ModelMeaslesSchool< TSeq  
        >, 170  
    epiworld::epimodels::ModelSEIRCONN< TSeq >,  
        183  
    epiworld::epimodels::ModelSEIRDCONN< TSeq  
        >, 196  
    epiworld::epimodels::ModelSEIRMixing< TSeq >,  
        203  
    epiworld::epimodels::ModelSEIRMixingQuarantine<  
        TSeq >, 211  
    epiworld::epimodels::ModelSIRCONN< TSeq >,  
        224  
    epiworld::epimodels::ModelSIRDCONN< TSeq >,  
        235  
    epiworld::epimodels::ModelSIRLogit< TSeq >,  
        242  
    epiworld::epimodels::ModelSIRMixing< TSeq >,  
        248  
    epiworld::Model< TSeq >, 107  
    Model< TSeq >, 123  
    ModelMeaslesMixing< TSeq >, 148  
    ModelMeaslesMixingRiskQuarantine< TSeq >,  
        164  
    ModelMeaslesSchool< TSeq >, 174  
    ModelSEIRCONN< TSeq >, 186  
    ModelSEIRDCONN< TSeq >, 199  
    ModelSEIRMixing< TSeq >, 206  
    ModelSEIRMixingQuarantine< TSeq >, 217  
    ModelSIRCONN< TSeq >, 227  
    ModelSIRDCONN< TSeq >, 238  
    ModelSIRLogit< TSeq >, 245  
    ModelSIRMixing< TSeq >, 252  
ContactTracing, 67  
    add\_contact, 68  
    ContactTracing, 68  
    epiworld::ContactTracing, 71  
    get\_contact, 69  
    get\_n\_contacts, 69  
    print, 70  
    reset, 70  
DataBase< TSeq >, 73  
    get\_generation\_time, 76  
    get\_reproductive\_number, 76  
    get\_transition\_probability, 76  
    get\_transmissions, 77  
    operator==, 77, 78  
    record\_virus, 78  
default\_rm\_entity  
    Agent< TSeq >, 60  
    Entity< TSeq >, 88  
    epiworld::Agent< TSeq >, 64  
    epiworld::Entity< TSeq >, 89  
draw  
    epiworld::Model< TSeq >, 108  
    Model< TSeq >, 123  
Entities< TSeq >, 83  
Entities\_const< TSeq >, 85  
Entity  
    Entity< TSeq >, 87  
    epiworld::Entity< TSeq >, 89  
Entity< TSeq >, 87  
    default\_rm\_entity, 88  
    Entity, 87  
epiworld::AdjList, 54  
    AdjList, 55  
    read\_edgelist, 55  
epiworld::Agent< TSeq >, 61  
    default\_rm\_entity, 64  
    operator(), 63  
    swap\_neighbors, 63  
epiworld::AgentsSample< TSeq >, 66  
    AgentsSample, 67  
epiworld::ContactTracing, 70

- add\_contact, 71
- ContactTracing, 71
- get\_contact, 72
- get\_n\_contacts, 72
- print, 73
- reset, 73
- epiworld::DataBase< TSeq >, 79
  - get\_generation\_time, 81
  - get\_reproductive\_number, 81
  - get\_transition\_probability, 82
  - get\_transmissions, 82
  - operator==, 83
  - record\_virus, 83
- epiworld::Entities< TSeq >, 84
- epiworld::Entities\_const< TSeq >, 86
- epiworld::Entity< TSeq >, 88
  - default\_rm\_entity, 89
  - Entity, 89
- epiworld::epimodels::ModelDiffNet< TSeq >, 131
- epiworld::epimodels::ModelMeaslesMixing< TSeq >, 134
  - clone\_ptr, 140
  - get\_agent\_quarantine\_triggered, 140
  - get\_contact\_matrix, 140
  - get\_isolation\_willingness, 141
  - get\_quarantine\_willingness, 141
  - initial\_states, 141
  - ModelMeaslesMixing, 137, 139
  - run, 142
  - set\_contact\_matrix, 142
- epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >, 151
  - clone\_ptr, 156
  - get\_contact\_matrix, 156
  - get\_days\_quarantine\_triggered, 156
  - get\_isolation\_willingness, 157
  - get\_quarantine\_risk\_level, 157
  - get\_quarantine\_willingness, 157
  - initial\_states, 157
  - ModelMeaslesMixingRiskQuarantine, 154, 155
  - run, 158
  - set\_contact\_matrix, 158
- epiworld::epimodels::ModelMeaslesSchool< TSeq >, 167
  - clone\_ptr, 170
  - ModelMeaslesSchool, 169
  - quarantine\_agents, 170
  - reset, 170
- epiworld::epimodels::ModelSEIR< TSeq >, 176
  - initial\_states, 177
  - update\_exposed\_seir, 178
  - update\_infected\_seir, 178
- epiworld::epimodels::ModelSEIRCONN< TSeq >, 181
  - clone\_ptr, 183
  - initial\_states, 183
  - ModelSEIRCONN, 182
  - reset, 184
- epiworld::epimodels::ModelSEIRD< TSeq >, 187
  - ModelSEIRD, 189, 190
  - update\_exposed\_seir, 190
- epiworld::epimodels::ModelSEIRDCONN< TSeq >, 194
  - clone\_ptr, 196
  - initial\_states, 196
  - ModelSEIRDCONN, 195
  - reset, 196
- epiworld::epimodels::ModelSEIRMixing< TSeq >, 200
  - clone\_ptr, 203
  - initial\_states, 203
  - ModelSEIRMixing, 201, 202
  - reset, 203
- epiworld::epimodels::ModelSEIRMixingQuarantine< TSeq >, 208
  - clone\_ptr, 211
  - initial\_states, 211
  - ModelSEIRMixingQuarantine, 209, 210
  - reset, 212
- epiworld::epimodels::ModelSIR< TSeq >, 218
  - initial\_states, 219
- epiworld::epimodels::ModelSIRCONN< TSeq >, 222
  - clone\_ptr, 224
  - get\_n\_infected, 224
  - initial\_states, 225
  - ModelSIRCONN, 223
  - reset, 225
- epiworld::epimodels::ModelSIRD< TSeq >, 229
  - initial\_states, 231
  - ModelSIRD, 230
- epiworld::epimodels::ModelSIRDCONN< TSeq >, 234
  - clone\_ptr, 235
  - ModelSIRDCONN, 235
  - reset, 236
- epiworld::epimodels::ModelSIRLogit< TSeq >, 239
  - clone\_ptr, 242
  - ModelSIRLogit, 241
  - reset, 242
- epiworld::epimodels::ModelSIRMixing< TSeq >, 246
  - clone\_ptr, 248
  - initial\_states, 249
  - ModelSIRMixing, 247, 248
  - reset, 249
- epiworld::epimodels::ModelSIS< TSeq >, 253
- epiworld::epimodels::ModelSISD< TSeq >, 257
- epiworld::epimodels::ModelSURV< TSeq >, 260
  - reset, 262
- epiworld::Event< TSeq >, 90
  - Event, 91
- epiworld::GlobalEvent< TSeq >, 93
  - GlobalEvent, 94
- epiworld::LFMCMC< TData >, 96
- epiworld::Model< TSeq >, 99
  - add\_globalevent, 107
  - clone\_ptr, 107
  - draw, 108
  - events\_add, 108
  - events\_run, 109

- initial\_states\_fun, 112
- load\_agents\_entities\_ties, 109
- rbinomd, 112
- reset, 110
- rexp, 112
- rgammad, 112
- rgeomd, 113
- rlognormald, 113
- rnbinomd, 113
- rnormd, 113
- rpoissd, 113
- run\_multiple, 110
- runifd, 114
- set\_agents\_data, 110
- set\_name, 111
- time\_elapsed, 114
- write\_data, 111
- epiworld::ModelDiagram, 131
- epiworld::PersonTools< TSeq >, 265
- epiworld::Progress, 266
- epiworld::Queue< TSeq >, 267
- epiworld::sampler, 45
  - make\_sample\_virus\_neighbors, 45
  - make\_update\_susceptible, 46
  - sample\_virus\_single, 46
- epiworld::SAMPLETYPE, 269
- epiworld::Tool< TSeq >, 269
- epiworld::ToolFunctions< TSeq >, 272
- epiworld::Tools< TSeq >, 274
- epiworld::Tools\_const< TSeq >, 275
- epiworld::UserData< TSeq >, 277
  - UserData, 278
- epiworld::vecHasher< T >, 280
- epiworld::Virus< TSeq >, 281
- epiworld::Viruses< TSeq >, 286
- epiworld::Viruses\_const< TSeq >, 287
- epiworld::VirusFunctions< TSeq >, 289
- Event
  - epiworld::Event< TSeq >, 91
  - Event< TSeq >, 93
- Event< TSeq >, 91
  - Event, 93
- events\_add
  - epiworld::Model< TSeq >, 108
  - Model< TSeq >, 124
- events\_run
  - epiworld::Model< TSeq >, 109
  - Model< TSeq >, 124
- get\_agent\_quarantine\_triggered
  - epiworld::epimodels::ModelMeaslesMixing< TSeq >, 140
  - ModelMeaslesMixing< TSeq >, 149
- get\_contact
  - ContactTracing, 69
  - epiworld::ContactTracing, 72
- get\_contact\_matrix
  - epiworld::epimodels::ModelMeaslesMixing< TSeq >, 140
- epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >, 156
  - ModelMeaslesMixing< TSeq >, 149
  - ModelMeaslesMixingRiskQuarantine< TSeq >, 164
- get\_days\_quarantine\_triggered
  - epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >, 156
  - ModelMeaslesMixingRiskQuarantine< TSeq >, 164
- get\_generation\_time
  - DataBase< TSeq >, 76
  - epiworld::DataBase< TSeq >, 81
- get\_isolation\_willingness
  - epiworld::epimodels::ModelMeaslesMixing< TSeq >, 141
  - epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >, 157
  - ModelMeaslesMixing< TSeq >, 149
  - ModelMeaslesMixingRiskQuarantine< TSeq >, 164
- GET\_MODEL
  - measlesmixing.hpp, 293
  - measlesmixingriskquarantine.hpp, 295
- get\_n\_contacts
  - ContactTracing, 69
  - epiworld::ContactTracing, 72
- get\_n\_infected
  - epiworld::epimodels::ModelSIRCONN< TSeq >, 224
  - ModelSIRCONN< TSeq >, 228
- get\_quarantine\_risk\_level
  - epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >, 157
  - ModelMeaslesMixingRiskQuarantine< TSeq >, 165
- get\_quarantine\_willingness
  - epiworld::epimodels::ModelMeaslesMixing< TSeq >, 141
  - epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >, 157
  - ModelMeaslesMixing< TSeq >, 149
  - ModelMeaslesMixingRiskQuarantine< TSeq >, 165
- get\_reproductive\_number
  - DataBase< TSeq >, 76
  - epiworld::DataBase< TSeq >, 81
- get\_transition\_probability
  - DataBase< TSeq >, 76
  - epiworld::DataBase< TSeq >, 82
- get\_transmissions
  - DataBase< TSeq >, 77
  - epiworld::DataBase< TSeq >, 82
- GlobalEvent
  - epiworld::GlobalEvent< TSeq >, 94
  - GlobalEvent< TSeq >, 95
- GlobalEvent< TSeq >, 95
  - GlobalEvent, 95

- include/epiworld/agent-meat-state.hpp, 291
- include/epiworld/models/measlesmixing.hpp, 293
- include/epiworld/models/measlesmixingriskquarantine.hpp, 294
- initial\_states
  - epiworld::epimodels::ModelMeaslesMixing< TSeq >, 141
  - epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >, 157
  - epiworld::epimodels::ModelSEIR< TSeq >, 177
  - epiworld::epimodels::ModelSEIRCONN< TSeq >, 183
  - epiworld::epimodels::ModelSEIRDCONN< TSeq >, 196
  - epiworld::epimodels::ModelSEIRMixing< TSeq >, 203
  - epiworld::epimodels::ModelSEIRMixingQuarantine< TSeq >, 211
  - epiworld::epimodels::ModelSIR< TSeq >, 219
  - epiworld::epimodels::ModelSIRCONN< TSeq >, 225
  - epiworld::epimodels::ModelSIRD< TSeq >, 231
  - epiworld::epimodels::ModelSIRMixing< TSeq >, 249
  - ModelMeaslesMixing< TSeq >, 150
  - ModelMeaslesMixingRiskQuarantine< TSeq >, 165
  - ModelSEIR< TSeq >, 180
  - ModelSEIRCONN< TSeq >, 186
  - ModelSEIRDCONN< TSeq >, 199
  - ModelSEIRMixing< TSeq >, 207
  - ModelSEIRMixingQuarantine< TSeq >, 217
  - ModelSIR< TSeq >, 221
  - ModelSIRCONN< TSeq >, 228
  - ModelSIRD< TSeq >, 233
  - ModelSIRMixing< TSeq >, 252
- initial\_states\_fun
  - epiworld::Model< TSeq >, 112
  - Model< TSeq >, 128
- LFMCMC< TData >, 97
- load\_agents\_entities\_ties
  - epiworld::Model< TSeq >, 109
  - Model< TSeq >, 126
- make\_sample\_virus\_neighbors
  - epiworld::sampler, 45
  - sampler, 48
- make\_update\_susceptible
  - epiworld::sampler, 46
  - sampler, 49
- measlesmixing.hpp
  - GET\_MODEL, 293
  - SAMPLE\_FROM\_PROBS, 294
- measlesmixingriskquarantine.hpp
  - GET\_MODEL, 295
  - SAMPLE\_FROM\_PROBS, 295
- Model< TSeq >, 114
  - add\_globlevent, 123
  - clone\_ptr, 123
  - draw, 123
  - events\_add, 124
  - events\_run, 124
  - initial\_states\_fun, 128
  - load\_agents\_entities\_ties, 126
  - rbinomd, 128
  - reset, 126
  - rexp, 128
  - rgammad, 129
  - rgeomd, 129
  - rlognormald, 129
  - rnbinomd, 129
  - rnormd, 129
  - rpoissd, 130
  - run\_multiple, 126
  - runifd, 130
  - set\_agents\_data, 127
  - set\_name, 127
  - time\_elapsed, 130
  - write\_data, 128
- ModelDiagram, 131
- ModelDiffNet< TSeq >, 133
- ModelMeaslesMixing
  - epiworld::epimodels::ModelMeaslesMixing< TSeq >, 137, 139
  - ModelMeaslesMixing< TSeq >, 146, 147
- ModelMeaslesMixing< TSeq >, 143
  - clone\_ptr, 148
  - get\_agent\_quarantine\_triggered, 149
  - get\_contact\_matrix, 149
  - get\_isolation\_willingness, 149
  - get\_quarantine\_willingness, 149
  - initial\_states, 150
  - ModelMeaslesMixing, 146, 147
  - run, 150
  - set\_contact\_matrix, 151
- ModelMeaslesMixingRiskQuarantine
  - epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >, 154, 155
  - ModelMeaslesMixingRiskQuarantine< TSeq >, 161, 163
- ModelMeaslesMixingRiskQuarantine< TSeq >, 159
  - clone\_ptr, 164
  - get\_contact\_matrix, 164
  - get\_days\_quarantine\_triggered, 164
  - get\_isolation\_willingness, 164
  - get\_quarantine\_risk\_level, 165
  - get\_quarantine\_willingness, 165
  - initial\_states, 165
  - ModelMeaslesMixingRiskQuarantine, 161, 163
  - run, 166
  - set\_contact\_matrix, 166
- ModelMeaslesSchool
  - epiworld::epimodels::ModelMeaslesSchool< TSeq >, 169
  - ModelMeaslesSchool< TSeq >, 173
- ModelMeaslesSchool< TSeq >, 171

- clone\_ptr, 174
- ModelMeaslesSchool, 173
- quarantine\_agents, 175
- reset, 175
- ModelSEIR< TSeq >, 179
  - initial\_states, 180
  - update\_exposed\_seir, 181
  - update\_infected\_seir, 181
- ModelSEIRCONN
  - epiworld::epimodels::ModelSEIRCONN< TSeq >, 182
  - ModelSEIRCONN< TSeq >, 185
- ModelSEIRCONN< TSeq >, 184
  - clone\_ptr, 186
  - initial\_states, 186
  - ModelSEIRCONN, 185
  - reset, 187
- ModelSEIRD
  - epiworld::epimodels::ModelSEIRD< TSeq >, 189, 190
  - ModelSEIRD< TSeq >, 192, 193
- ModelSEIRD< TSeq >, 191
  - ModelSEIRD, 192, 193
  - update\_exposed\_seir, 193
- ModelSEIRDCONN
  - epiworld::epimodels::ModelSEIRDCONN< TSeq >, 195
  - ModelSEIRDCONN< TSeq >, 198
- ModelSEIRDCONN< TSeq >, 197
  - clone\_ptr, 199
  - initial\_states, 199
  - ModelSEIRDCONN, 198
  - reset, 200
- ModelSEIRMixing
  - epiworld::epimodels::ModelSEIRMixing< TSeq >, 201, 202
  - ModelSEIRMixing< TSeq >, 205, 206
- ModelSEIRMixing< TSeq >, 204
  - clone\_ptr, 206
  - initial\_states, 207
  - ModelSEIRMixing, 205, 206
  - reset, 207
- ModelSEIRMixingQuarantine
  - epiworld::epimodels::ModelSEIRMixingQuarantine< TSeq >, 209, 210
  - ModelSEIRMixingQuarantine< TSeq >, 214, 215
- ModelSEIRMixingQuarantine< TSeq >, 213
  - clone\_ptr, 217
  - initial\_states, 217
  - ModelSEIRMixingQuarantine, 214, 215
  - reset, 217
- ModelSIR< TSeq >, 220
  - initial\_states, 221
- ModelSIRCONN
  - epiworld::epimodels::ModelSIRCONN< TSeq >, 223
  - ModelSIRCONN< TSeq >, 227
- ModelSIRCONN< TSeq >, 226
  - clone\_ptr, 227
  - get\_n\_infected, 228
  - initial\_states, 228
  - ModelSIRCONN, 227
  - reset, 228
- ModelSIRD
  - epiworld::epimodels::ModelSIRD< TSeq >, 230
  - ModelSIRD< TSeq >, 232
- ModelSIRD< TSeq >, 231
  - initial\_states, 233
  - ModelSIRD, 232
- ModelSIRDCONN
  - epiworld::epimodels::ModelSIRDCONN< TSeq >, 235
  - ModelSIRDCONN< TSeq >, 237
- ModelSIRDCONN< TSeq >, 236
  - clone\_ptr, 238
  - ModelSIRDCONN, 237
  - reset, 238
- ModelSIRLogit
  - epiworld::epimodels::ModelSIRLogit< TSeq >, 241
  - ModelSIRLogit< TSeq >, 244
- ModelSIRLogit< TSeq >, 243
  - clone\_ptr, 245
  - ModelSIRLogit, 244
  - reset, 245
- ModelSIRMixing
  - epiworld::epimodels::ModelSIRMixing< TSeq >, 247, 248
  - ModelSIRMixing< TSeq >, 251, 252
- ModelSIRMixing< TSeq >, 250
  - clone\_ptr, 252
  - initial\_states, 252
  - ModelSIRMixing, 251, 252
  - reset, 253
- ModelSIS< TSeq >, 256
- ModelSISD< TSeq >, 259
- ModelSURV< TSeq >, 263
  - reset, 264
- Network< Nettype, Nodetype, Edgetype >, 265
- operator()
  - Agent< TSeq >, 58
  - epiworld::Agent< TSeq >, 63
- operator==
  - DataBase< TSeq >, 77, 78
  - epiworld::DataBase< TSeq >, 83
- PersonTools< TSeq >, 266
- print
  - ContactTracing, 70
  - epiworld::ContactTracing, 73
- Progress, 266
- quarantine\_agents
  - epiworld::epimodels::ModelMeaslesSchool< TSeq >, 170

- ModelMeaslesSchool< TSeq >, 175
- Queue< TSeq >, 267
- RandGraph, 268
- rbinomd
  - epiworld::Model< TSeq >, 112
  - Model< TSeq >, 128
- read\_edgelist
  - AdjList, 54
  - epiworld::AdjList, 55
- record\_virus
  - DataBase< TSeq >, 78
  - epiworld::DataBase< TSeq >, 83
- reset
  - ContactTracing, 70
  - epiworld::ContactTracing, 73
  - epiworld::epimodels::ModelMeaslesSchool< TSeq >, 170
  - epiworld::epimodels::ModelSEIRCONN< TSeq >, 184
  - epiworld::epimodels::ModelSEIRDCONN< TSeq >, 196
  - epiworld::epimodels::ModelSEIRMixing< TSeq >, 203
  - epiworld::epimodels::ModelSEIRMixingQuarantine< TSeq >, 212
  - epiworld::epimodels::ModelSIRCONN< TSeq >, 225
  - epiworld::epimodels::ModelSIRDCONN< TSeq >, 236
  - epiworld::epimodels::ModelSIRLogit< TSeq >, 242
  - epiworld::epimodels::ModelSIRMixing< TSeq >, 249
  - epiworld::epimodels::ModelSURV< TSeq >, 262
  - epiworld::Model< TSeq >, 110
  - Model< TSeq >, 126
  - ModelMeaslesSchool< TSeq >, 175
  - ModelSEIRCONN< TSeq >, 187
  - ModelSEIRDCONN< TSeq >, 200
  - ModelSEIRMixing< TSeq >, 207
  - ModelSEIRMixingQuarantine< TSeq >, 217
  - ModelSIRCONN< TSeq >, 228
  - ModelSIRDCONN< TSeq >, 238
  - ModelSIRLogit< TSeq >, 245
  - ModelSIRMixing< TSeq >, 253
  - ModelSURV< TSeq >, 264
- rexp
  - epiworld::Model< TSeq >, 112
  - Model< TSeq >, 128
- rgammad
  - epiworld::Model< TSeq >, 112
  - Model< TSeq >, 129
- rgeomd
  - epiworld::Model< TSeq >, 113
  - Model< TSeq >, 129
- rlognormald
  - epiworld::Model< TSeq >, 113
  - Model< TSeq >, 129
- rnbinomd
  - epiworld::Model< TSeq >, 113
  - Model< TSeq >, 129
- rnormd
  - epiworld::Model< TSeq >, 113
  - Model< TSeq >, 129
- rpoissd
  - epiworld::Model< TSeq >, 113
  - Model< TSeq >, 130
- run
  - epiworld::epimodels::ModelMeaslesMixing< TSeq >, 142
  - epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >, 158
  - ModelMeaslesMixing< TSeq >, 150
  - ModelMeaslesMixingRiskQuarantine< TSeq >, 166
- run\_multiple
  - epiworld::Model< TSeq >, 110
  - Model< TSeq >, 126
- runifd
  - epiworld::Model< TSeq >, 114
  - Model< TSeq >, 130
- SAMPLE\_FROM\_PROBS
  - measlesmixing.hpp, 294
  - measlesmixingriskquarantine.hpp, 295
- sample\_virus\_single
  - epiworld::sampler, 46
  - sampler, 49
- sampler, 48
  - make\_sample\_virus\_neighbors, 48
  - make\_update\_susceptible, 49
  - sample\_virus\_single, 49
- SAMPLETYPE, 269
- set\_agents\_data
  - epiworld::Model< TSeq >, 110
  - Model< TSeq >, 127
- set\_contact\_matrix
  - epiworld::epimodels::ModelMeaslesMixing< TSeq >, 142
  - epiworld::epimodels::ModelMeaslesMixingRiskQuarantine< TSeq >, 158
  - ModelMeaslesMixing< TSeq >, 151
  - ModelMeaslesMixingRiskQuarantine< TSeq >, 166
- set\_name
  - epiworld::Model< TSeq >, 111
  - Model< TSeq >, 127
- swap\_neighbors
  - Agent< TSeq >, 60
  - epiworld::Agent< TSeq >, 63
- TestResults, 269
- time\_elapsed
  - epiworld::Model< TSeq >, 114
  - Model< TSeq >, 130
- Tool< TSeq >, 271
- ToolFunctions< TSeq >, 273



Tools< TSeq >, [274](#)  
Tools\_const< TSeq >, [276](#)  
  
update\_exposed\_seir  
    epiworld::epimodels::ModelSEIR< TSeq >, [178](#)  
    epiworld::epimodels::ModelSEIRD< TSeq >, [190](#)  
    ModelSEIR< TSeq >, [181](#)  
    ModelSEIRD< TSeq >, [193](#)  
update\_infected\_seir  
    epiworld::epimodels::ModelSEIR< TSeq >, [178](#)  
    ModelSEIR< TSeq >, [181](#)  
UserData  
    epiworld::UserData< TSeq >, [278](#)  
    UserData< TSeq >, [280](#)  
UserData< TSeq >, [278](#)  
    UserData, [280](#)  
  
vecHasher< T >, [281](#)  
Virus< TSeq >, [283](#)  
Viruses< TSeq >, [286](#)  
Viruses\_const< TSeq >, [288](#)  
VirusFunctions< TSeq >, [289](#)  
  
write\_data  
    epiworld::Model< TSeq >, [111](#)  
    Model< TSeq >, [128](#)