Not Reading, Not Misreading: Where Thai OCR Vision-Language Models Lose Vowel and Tone Marks

Thanakrit Samoenar
School of Information Technology
King Mongkut's Institute of Technology Ladkrabang
Bangkok, Thailand
67070060@kmitl.ac.th

Thanawat Suriya
School of Information Technology
King Mongkut's Institute of Technology Ladkrabang
Bangkok, Thailand
67070236@kmitl.ac.th

Asst. Prof. Nont Kanungsukkasem, Ph.D.
School of Information Technology
King Mongkut's Institute of Technology Ladkrabang
Bangkok, Thailand
nont@it.kmitl.ac.th

***Abstract*—Open vision-language models (VLMs) for Thai OCR now read most of a page correctly, but Thai vowels and tone marks are small, and one mark can change a word. This paper asks where the marks are lost, in addition to how many. We introduce a mark score that ignores reading order, penalizes surplus text, and gives no credit to the copies produced by a repetition loop. On the ThaiOCRBench calibration split, Typhoon OCR 1.5 (2B) writes a wrong tone mark in only 0.65% of the places where it reads the base consonant correctly. Given the correct preceding text, it chooses the right tone mark 98.8% of the time even without the image. In six open models, most of the marks are lost because lines are never read, not because marks are misread: not reading costs 7 to 12 times more marks. Among training-free decoders, stopping at a detected loop raises mark F1 for every model, by 0.8 points for Typhoon and by 10.8 to 24.4 points for models that loop often, and it changes almost no output that ended on its own. A repetition penalty lowers F1 on pages that do not loop, and subtracting the language prior removes correct tone marks. [The image test for other models and a locked-split confirmation are pending.] All results are preliminary. They come from one benchmark and a calibration split, and some rules were written after the data had been seen.**

***Index Terms*—Thai OCR, vision-language models, diacritics, repetition loops, training-free decoding**

I. Introduction

Thai is written on a line of consonants, with vowels and tone marks stacked above and below it. A single mark can change the meaning and the sound of a word, as in ข่าว (news) and ข้าว (rice). A transcription that drops or swaps a mark is therefore wrong for the reader, even when nearly every other character is correct. Thai OCR is nevertheless scored with whole-text measures such as n-gram overlap and normalized edit distance in ThaiOCRBench [1], or with character error rate in other work. These measures do not show whether the marks are the problem. Sequence-level scores also penalize a model that reads the columns of a page in a different order from the reference.

XXX-X-XXXX-XXXX-X/XX/$XX.00 ©20XX IEEE

Open vision-language models (VLMs) trained for Thai OCR are now available [2]–[4]. When one of them gets a mark wrong, there are three possible explanations. The visual evidence for a small mark may be weak. The language prior may override the evidence. Or the model may never read the mark, because it skipped the line, failed to find the text, or fell into a repetition loop. Each explanation calls for a different remedy. Weak evidence suggests re-reading or zooming, an overriding prior suggests subtracting it as contrastive decoding does [5], [6], and unread text suggests changing the decoding or locating the text.

We study this question on ThaiOCRBench with Typhoon OCR 1.5 and five other open checkpoints, using the full-page OCR and text recognition tasks. We make three contributions.

1) A mark score that ignores reading order (Section III). It scores upper vowels, lower vowels and tone marks line by line, wherever the line appears in the output. Surplus text is penalized, and copies produced by a repetition loop earn no credit.
2) A diagnosis of where marks are lost (Section V). In all six models, not reading a line costs 7 to 12 times more marks than misreading a mark after a correctly read consonant. For Typhoon, a wrong tone mark follows a correct consonant 0.65% of the time, and given the correct preceding text it chooses the right tone mark 98.8% of the time even without the image. **[The image test for the other models.]**
3) An evaluation of training-free decoding (Section VI). Stopping at a detected loop raises mark F1 for every model and changes almost no output that ended on its own. A repetition penalty lowers F1 on pages that do not loop, and subtracting the language prior removes correct tone marks. **[Confirmation on the locked split.]**

For the models we studied, the remaining mark errors of a strong Thai OCR model arise before the mark is reached. Decoding and finding the text matter more than seeing a tone mark more sharply.

II. Related Work

Thai OCR with VLMs. ThaiOCRBench [1] evaluates proprietary and open VLMs on Thai document tasks, including full-page OCR and text recognition. It uses n-gram overlap and edit-distance measures: BLEU, METEOR, F1 and normalized Levenshtein distance, with ANLS for text recognition. Its introduction names stacked diacritics as a difficulty of Thai, but no score isolates the marks. Several open Thai OCR models have appeared since. Typhoon OCR [2] is a full fine-tune of Qwen3-VL-2B [7] in version 1.5, and its authors list infographics as an area for improvement. Pathumma-llm-vision 3.0 [3] is another Qwen3-VL-2B fine-tune. wayu-paxa-ocr-zero [4] fine-tunes PaddleOCR-VL [8] on synthetic Thai pages. Each reports aggregate accuracy. We ask where the marks are lost.

Diacritics in OCR. OCR is known to be difficult for scripts with many diacritics. Post-OCR correction has been proposed for Vietnamese [9], and an evaluation of Arabic OCR treats diacritized text as a separate condition [10]. We found no work that scores Thai marks separately from reading order and surplus text.

Repetition and omission. Decoding that maximizes likelihood produces repetitive text [11], and document OCR models show the same behavior. Nougat reports pages on which the model repeats a sentence, and it stops generation when a logit-variance signal falls [12]. olmOCR retries at a higher temperature [13]. The PaddleOCR-VL pipeline truncates repetitive output after decoding [14], and the released DeepSeek-OCR code bans repeated n-grams within a window [15], [16]. CC-OCR counts repetition as a form of OCR hallucination [17]. These works treat repetition as something to detect or avoid. We measure what each remedy costs the marks on pages that do not loop. One of the remedies is the repetition penalty of CTRL [18], which some OCR packages enable by default.

Language priors and training-free decoding. Contrastive decoding reduces hallucination in VLMs by down-weighting what the model would predict without the image, or with a degraded image. Examples are VCD [5], M3ID [6] and PAI [19]. These methods assume that the language prior is the problem. For Thai tone marks we find that the prior is usually right. Our versions are reimplementations, so we call them M3ID-form and PAI-style. Speculative decoding [20] with prompt-lookup drafts [21] speeds up decoding and leaves the output unchanged in exact arithmetic.

III. Scoring Marks Without Charging Reading Order

We call the following characters marks: the six upper vowels (ั ิ ี ึ ื ็), the two lower vowels (ุ ู) and the four tone marks (่ ้ ๊ ๋). A full page has several reference lines, and a model may read its columns in a different order from the reference. A global alignment then counts correctly read marks as errors.

Definition. We take the reference lines of at least eight characters, longest first. For each line we look for the stretch of the output that matches it at under 40% character error rate, ignoring characters already claimed. We credit the marks that match and claim the stretch, so that no stretch credits two lines. The remaining lines are aligned globally, in reference order, against the output with all claimed characters removed. Without this second step, marks inside poorly read lines were lost, and our first version failed its check against the base model. Recall is the credited marks divided by the reference marks. Precision is the credited marks divided by all marks in the output, which penalizes surplus text. F1 is averaged over items by pooling counts.

Repeat-aware variant. In this variant, credit is computed after each loop run is reduced to one copy. A run is a unit of 4 to 400 characters that contains a letter and repeats exactly at least eight times, or six times for units of 50 characters or more. Precision still counts every mark in the full output, so the copies are penalized and cannot earn recall. We added the variant after a collaborator showed that the alignment matched 434 copies of one repeated unit to common syllables in the reference. When nothing loops, the two scores are identical.

Checks. Reading the same page twice in a row scores far below the better single read. The base model's recall stays within 0.3 points of the global alignment in every cell. Typhoon's full-page recall rises by 1.6 to 1.8 points when order is not charged, and charging order alone lowers its full-page mark F1 from 94.9 to 93.1 for the BQ prompt (95.3 to 93.7 for TC, both defined below). The base model is barely affected.

IV. Experimental Setup

Data. We use the test split of ThaiOCRBench [1] on two tasks, full-page OCR and text recognition. A seeded 30% calibration split, stratified by task and category, holds 69 full-page items and 109 text-recognition items. The remaining 70% is a locked split that has not been opened. We report outputs and scores for each item and do not redistribute any benchmark image.

Models. We evaluate Typhoon OCR 1.5 (2B), its base model Qwen3-VL-2B, Qwen3-VL-4B, and the 0.9B region recognizers PaddleOCR-VL-1.6 and wayu-paxa-ocr-zero (Wayu). We also apply the two region recognizers to full pages, which goes beyond their design. Each checkpoint is pinned by revision, and we use the Apache-2.0-only revision of Typhoon. Revisions, seeds and run identifiers are recorded in the project repository.

Prompts and decoding. BQ is the benchmark's own question for each item, and TC is the prompt recommended on Typhoon's model card. Paddle and Wayu use their `OCR:` prompt. Decoding is greedy with at most 3,072 new tokens, in fp16 on Kaggle T4 GPUs. Each result comes from one run. Outputs are reduced to plain text before scoring. BQ is the primary prompt and TC the secondary one.

Statistics. Intervals are 95% bootstrap intervals over items. All results are preliminary and come from the calibration split. Several decoding rules were written after that split had been seen, and we say so where it applies.




Fig. 1. Mark F1 on the calibration split, (a) full-page OCR and (b) text recognition. The prompt is BQ, except `OCR:` for the two 0.9B models and the card prompt for Pathumma.

TABLE I
MARK F1, TONE-MARK ERROR AFTER A CORRECTLY READ CONSONANT, AND SHARE OF OUTPUTS THAT REACHED THE TOKEN LIMIT (%). PATHUMMA USES ITS CARD PROMPT.

	Full-page			Text rec.	
Model	F1	tone err.	limit	F1	limit
Typhoon OCR 1.5	**94.9**	0.65	2.9	**81.7**	0.9
Pathumma 3.0	89.8	0.99	5.8	77.6	1.8
Wayu	65.2	5.27	26.1	46.0	20.2
PaddleOCR-VL-1.6	53.3	14.57	39.1	47.9	14.7
Qwen3-VL-4B	45.9	9.89	27.5	23.5	11.9
Qwen3-VL-2B	41.0	9.41	43.5	24.3	14.7

V. Where Marks Are Lost

A. Six Models

Typhoon scores a mark F1 of 94.9 on full pages and 81.7 on text recognition (Fig. 1 and Table I). Pathumma-llm-vision 3.0 [3], a second Thai fine-tune of the same base model, comes close. With its own card prompt it scores 89.8 and 77.6. Its difference from Typhoon is −5.1 points on full pages (interval −14.3 to +1.6) and −4.1 on text recognition (interval −15.1 to +8.0), so we cannot say that either model is better. Both are far above the base model, by 48.9 and 53.3 points. The remaining three checkpoints are well below Typhoon: Wayu by 29.6 points on full pages (interval 19.2 to 39.9). Doubling the size of the base model changes its full-page F1 by only +5.0 (interval −4.0 to +14.1), and its tone error stays near 9.4 to 9.9%. Typhoon's median character error rate per page is 2.8%. The models are compared as released, with different numbers of visual tokens. Typhoon is the strongest model we measured and is comparable to Pathumma. The card of Pathumma reports ThaiOCRBench scores, and its 377K training samples are not named, so we cannot rule out overlap with the benchmark.

On text recognition the two models fail differently. Pathumma finds more of the requested marks (recall higher by 14.3 points) but often transcribes the whole image instead of the requested span, which lowers its precision.

Loop copies earned recall. The repeat-aware score changes Typhoon by at most 0.2 points. It lowers the full-page F1 of the base model (BQ) from 41.0 to 34.4 and its recall from 65.0 to 54.6 (Table II). About a sixth of the marks that the order-free score credited to the base model came from loop copies. We read back every stripped run. All 126 had reached the token limit, the shortest contained 15 copies, and no ordinary text was removed.

TABLE II
RECALL (R), PRECISION (P) AND F1 (%) WITH AND WITHOUT CREDIT FOR LOOP COPIES, FULL-PAGE BQ

	Order-free			Repeat-aware		
Model	R	P	F1	R	P	F1
Typhoon	96.1	93.7	94.9	96.1	93.6	94.8
Qwen3-VL-2B	65.0	29.9	41.0	54.6	25.1	34.4

B. Most Lost Marks Are Never Read

On full pages, Typhoon gets 6.2% (BQ) and 7.1% (TC) of all reference marks wrong. We assign each error automatically to one of four causes (Fig. 2). The line may be read in another order, meaning that some stretch of the output matches it at under 20% character error rate (for lines of at least eight characters). The whole line may be absent. A span may be missing inside a line that was kept. Or the mark may be misread. Absent lines account for 2.3% (BQ) and 2.9% (TC) of the marks, missing spans for 0.7% and 0.8%, and misreads for 1.5% and 2.4%. Reading order alone accounts for 1.6% and 0.9%, and this is not an error of reading. In the raw outputs, the absent lines are mostly text inside infographics and charts, inset advertisements, and titles or page furniture, where Typhoon writes an image placeholder. This agrees with the note on infographics by its authors [2]. The attribution is automatic, and we checked page images only for the six pages that hold most of the absent marks.

The same pattern holds for the other five models (Fig. 2). We apply the attribution to outputs cut at the first loop, because a looping output is many times longer than the reference and the alignment cannot be trusted on it. Whole lines absent plus missing spans cost 3.2% of the marks for Typhoon, 9.3% for Pathumma, and 29 to 44% for the other four models. A wrong mark after a correctly read consonant costs 0.4% for Typhoon, 0.8% for Pathumma, and 2.7 to 4.3% for the others. For every model, not reading therefore costs between 7 and 12 times more marks than misreading. For the models that loop, a line that comes after a loop counts as absent, and we do not separate lines lost to the loop from lines the model would not have read anyway.

C. With the Right Context, the Prior Is Already Right

In a forced-choice test, we give the model the correct text up to a mark and let it score the legal variants of that mark with and without the image (fp32, in-context tokenization). On full pages Typhoon chooses the correct tone mark 99.7% of the time with the image and 98.8% without it. For the base model the figures are 98.1% and 98.9%. The image therefore adds 0.9 points for Typhoon and removes 0.8 for the base




Fig. 2. Where full-page marks are lost, as a share of all reference marks, for outputs cut at the first loop. The bar totals exclude the grey segment, which is a difference in reading order and not an error.




Fig. 3. (a) Gain in tone accuracy when the image is given, at the registered sites. (b) Typhoon's tone accuracy when the no-image score is subtracted with weight λ.

model (Fig. 3a). This test gives the model correct context and is not free generation. In this one pair, the specialized model gains more from the image than its base model does, and we do not generalize from it. **[The same test for Pathumma and Qwen3-VL-4B.]**

Confidence. Typhoon's own token probabilities locate its mark errors. The lowest token probability inside a character cluster separates misread marks from correct ones with an AUROC of 0.918 (BQ) and 0.935 (TC) on the model's own greedy output.

VI. Training-Free Decoding and Marks

A. Loops Are Rare but Costly

Of 356 Typhoon outputs (both prompts, both tasks), 11 contain a loop. In each cell, two to five looping pages hold 68 to 76% of all surplus marks. Without them, full-page F1 for BQ would be 97.4 instead of 94.9. This figure is a ceiling obtained by removing those pages. It is not the result of any method.

B. Three Ways to Handle a Loop

We compare three decoders for Typhoon with greedy decoding (Fig. 4, full pages, BQ).




Fig. 4. Change in full-page mark F1 against greedy decoding (Typhoon, BQ). Blue bars cover all pages, with 95% intervals. Orange bars cover pages that do not loop.

- Repetition penalty 1.1, the setting used by Typhoon's own package, which applies the penalty of CTRL [18].
- n-gram blocking as in the DeepSeek-OCR code, which forbids repeating a 30-gram within 90 tokens.
- Stopping at a detected loop. When a unit repeats eight times, or six times for units of 50 characters or more, decoding stops at the first copy. Greedy decoding is prefix-deterministic, so we compute the cut offline from complete greedy outputs. A decode-time implementation has not yet been checked against this result.

Repetition penalty. It changes nearly every output, and none of the loop-free full-page BQ outputs is identical to greedy. F1 on loop-free pages falls by 1.1 to 1.3 points. On text recognition (BQ) the tone error rises from 17.1% to 22.6%. Over all pages the effect cannot be told apart from zero (+0.89, interval −2.70 to +4.81). Thai text legitimately repeats syllables and tone marks, and a page-wide penalty may discourage them. We did not test this explanation.

n-gram blocking. It is safe where nothing loops: 92 to 100% of loop-free outputs are unchanged and the change in F1 is at most 0.05. It ends 6 of the 11 loops. In the others, the model escapes into near-repeats, for example a street name that drifts through three similar names. These near-repeats carry more marks, so surplus rises and full-page F1 ends 0.68 lower for BQ. We read a loop as an attractor of the decoder, so that banning an exact repeat moves the model to a neighboring one. This is an interpretation and has not been tested.

Stopping at a loop. It leaves every loop-free output unchanged, in every cell. Full-page mark F1 rises by 0.84 (BQ) and 0.67 (TC), and text-recognition F1 by 3.30 and 2.39. The stop also saves 11.2% of the generated tokens. Recall falls by at most 0.16 points, because stopping cannot recover text that the loop skipped. We wrote the rule after seeing the previous comparison. Each cell has only one to four looping outputs, so every interval includes zero.

C. The Stop on Other Models

The other models loop far more often than Typhoon. On full pages, 18 to 30 of 69 outputs of the base model, Qwen3-VL-4B, Paddle and Wayu loop, against 2 for Typhoon and 4 for Pathumma. Applying the same offline stop to their

TABLE III
MARK F1 WITHOUT AND WITH THE STOP AT A DETECTED LOOP (OFFLINE)

	Full-page		Text rec.	
Model	greedy	+ stop	greedy	+ stop
Typhoon OCR 1.5	94.9	95.7	81.7	85.0
Pathumma 3.0	89.8	92.8	77.6	77.7
Wayu	65.2	76.0	46.0	70.4
PaddleOCR-VL-1.6	53.3	58.4	47.9	61.8
Qwen3-VL-4B	45.9	68.8	23.5	29.9
Qwen3-VL-2B	41.0	65.4	24.3	66.9

greedy outputs raises mark F1 for every model on both tasks (Table III). No interval lies below zero, and seven of the twelve cells exclude zero. The gain is large where a model loops often, for example +24.4 for the base model and +10.8 for Wayu on full pages (interval 5.3 to 16.1), and small for Typhoon and Pathumma, which rarely loop. The gain comes from precision and costs recall, up to 10.6 points on full pages. Part of that recall was credit earned by loop copies, and the rest is text that follows the loop and is cut. Across the twelve cells the stop changed 3 of 898 outputs that had ended on their own. Two of them are Paddle outputs that left a degenerate loop by themselves, and the cut dropped real page text after it. A repetition penalty of 1.05 alone, the value in Wayu's own example, does not help (+2.8, interval −3.6 to +9.6 on full pages, and −11.3, interval −22.5 to +4.5 on text recognition). Stopping saves 34% of the generated tokens on Wayu's full pages. In this run, 72% of Wayu's full-page recall gap to Typhoon lies on the 18 pages where it loops, and no decoder we tested recovers it. We cannot say whether the loop is a cause or a symptom.

D. Subtracting the Language Prior Removes Correct Marks

In the forced-choice test, subtracting the no-image score with weight λ lowers Typhoon's tone accuracy from 99.7% to 97.3% at $\lambda = 0.5$ and to 42.3% at $\lambda = 1$ (Fig. 3b). The base model falls to 84.7% at 0.5. In free generation, on a subset of 24 items, our M3ID-form contrast ended the loops of the base model (character error rate 1.12 to 0.21). It also raised the tone error on retained items from 3.7% to 7.6%, mostly by deleting tone marks (21 to 55 on 12 items). On Typhoon the change is small and concentrated in a few items. Both results point the same way. The prior for the tone mark is right, and removing it removes correct marks.

E. Speed

Speculative decoding with prompt lookup makes Typhoon 1.14 to 1.15 times faster (base model: 1.16 to 1.21 times) on pages that do not degenerate. The output is identical except at fp16 near-ties, and 88 to 93% of items are identical. The greedy reference reproduces our main outputs character for character on all 177 timed items. **[Speed of the stop combined with speculative decoding.]**

VII. DISCUSSION AND LIMITATIONS

In all six models we studied, the mark errors arise mostly before the mark is reached, through unread lines, missing spans and loops. With the correct context the tone mark is almost certain, and methods that remove the prior pay for it in tone marks. The cheap and safe way to deal with a loop is to stop it.

The study has several limitations. It uses one benchmark and two tasks. All results come from the calibration split, and the stop rule, the repeat-aware score and the scoring were written after the data had been seen. The locked split has not been opened **[pending]**. The models are compared as released, with different numbers of visual tokens, and the two region recognizers are used on full pages beyond their design. Pathumma may have seen the benchmark in training. Few outputs loop for Typhoon and Pathumma, so most of their intervals include zero, and our claim concerns a mechanism rather than a rate. The stop sometimes cuts real text that follows a loop, and the attribution after a cut cannot tell a loop from a failure to read. The attribution of errors is automatic. The forced-choice test supplies correct context. Our contrastive variants are reimplementations tested on 24 items. Finally, we used a revision of Typhoon published under Apache-2.0 alone, while the vendor's current terms ask for written consent to competitive benchmarking.

VIII. CONCLUSION

A strong open Thai OCR model does not fail mainly at the tone mark. It fails earlier, by not reading, not finding the text, or looping. Stopping at a detected loop is a safe training-free step with a measurable gain, and removing the language prior is not. **[Final claims wait for the remaining runs.]**

ETHICAL AND LICENSING NOTES

All models are open and used under their licenses (Apache-2.0 or MIT, with Typhoon at its Apache-2.0-only revision). ThaiOCRBench is released under CC-BY-SA-4.0. We cite its paper and revision, report outputs and scores, and do not redistribute its images.

REFERENCES

[1] S. Nonesung, T. Jaknamon, S. Chaiophat, N. Nitarach, C. Wittayasakpan, W. Sirichotedumrong, A. Na-Thalang, and K. Pipatanakul, "ThaiOCRBench: A task-diverse benchmark for vision-language understanding in Thai," in *Proceedings of IJCNLP-AACL 2025 (Long Papers)*, 2025, pp. 1653–1675, arXiv:2511.04479. [Online]. Available: https://aclanthology.org/2025.ijcnlp-long.89

[2] S. Nonesung, N. Nitarach, T. Jaknamon, P. Taveekitworachai, and K. Pipatanakul, "Typhoon OCR: Open vision-language model for Thai document extraction," 2026. [Online]. Available: https://arxiv.org/abs/2601.14722

[3] NECTEC, "Pathumma-llm-vision-3.0.0-re," Hugging Face model card, 2026, revision 08bb11dcabf509ac3fa3ac0014ecd44eadb9729b. [Online]. Available: https://huggingface.co/nectec/Pathumma-llm-vision-3.0.0-re

[4] K. Pipatanakul, "How far can synthetic data take Thai OCR?" 2026. [Online]. Available: https://arxiv.org/abs/2609.03595

[5] S. Leng, H. Zhang, G. Chen, X. Li, S. Lu, C. Miao, and L. Bing, "Mitigating object hallucinations in large vision-language models through visual contrastive decoding," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024, pp. 13 872–13 882.

[6] A. Favero, L. Zancato, M. Trager, S. Choudhary, P. Perera, A. Achille, A. Swaminathan, and S. Soatto, "Multi-modal hallucination control by visual information grounding," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024, arXiv:2403.14003.

[7] S. Bai, Y. Cai, R. Chen *et al.*, "Qwen3-VL technical report," 2025. [Online]. Available: https://arxiv.org/abs/2511.21631

[8] C. Cui, T. Sun, S. Liang *et al.*, "PaddleOCR-VL: Boosting multilingual document parsing via a 0.9B ultra-compact vision-language model," 2025. [Online]. Available: https://arxiv.org/abs/2510.14528

[9] T. Do, D. P. Tran, A. Vo, and D. Kim, "Reference-based post-OCR processing with LLM for precise diacritic text in historical document recognition," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 39, no. 27, 2025, pp. 27 951–27 959.

[10] H. Elsafty, F. Aldabbas, and R. Sifa, "Arabic OCR in the age of multimodal models: A comprehensive comparative evaluation," in *2025 IEEE International Conference on Big Data*, 2025, pp. 5437–5442, lamarr Institute publication page.

[11] A. Holtzman, J. Buys, L. Du, M. Forbes, and Y. Choi, "The curious case of neural text degeneration," in *International Conference on Learning Representations (ICLR)*, 2020, arXiv:1904.09751.

[12] L. Blecher, G. Cucurull, T. Scialom, and R. Stojnic, "Nougat: Neural optical understanding for academic documents," in *International Conference on Learning Representations (ICLR)*, 2024, arXiv:2308.13418.

[13] J. Poznanski, A. Rangapur, J. Borchardt, J. Dunkelberger, R. Huff, D. Lin, C. Wilhelm, K. Lo, and L. Soldaini, "olmOCR: Unlocking trillions of tokens in PDFs with vision language models," 2025. [Online]. Available: https://arxiv.org/abs/2502.18443

[14] PaddlePaddle, "PaddleX PaddleOCR-VL pipeline: `truncate_repetitive_content`," GitHub source code, 2025. [Online]. Available: https://github.com/PaddlePaddle/PaddleX/blob/ffb64904d23708863ff5b8da312a5cbd52a7f462/paddlex/inference/pipelines/paddleocr_vl/uilts.py

[15] DeepSeek-AI, "DeepSeek-OCR source code: `NoRepeatNGramLogitsProcessor`," GitHub, 2025. [Online]. Available: https://github.com/deepseek-ai/DeepSeek-OCR

[16] H. Wei, Y. Sun, and Y. Li, "DeepSeek-OCR: Contexts optical compression," 2025. [Online]. Available: https://arxiv.org/abs/2510.18234

[17] Z. Yang, J. Tang, Z. Li, P. Wang, J. Wan, H. Zhong, X. Liu, M. Yang, P. Wang, S. Bai, L. Jin, and J. Lin, "CC-OCR: A comprehensive and challenging OCR benchmark for evaluating large multimodal models in literacy," in *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2025, pp. 21 744–21 754.

[18] N. S. Keskar, B. McCann, L. R. Varshney, C. Xiong, and R. Socher, "CTRL: A conditional transformer language model for controllable generation," 2019.

[19] S. Liu, K. Zheng, and W. Chen, "Paying more attention to images: A training-free method for alleviating hallucination in LVLMs," in *European Conference on Computer Vision (ECCV)*, 2024.

[20] Y. Leviathan, M. Kalman, and Y. Matias, "Fast inference from transformers via speculative decoding," in *International Conference on Machine Learning (ICML)*, 2023, arXiv:2211.17192.

[21] A. Saxena, "Prompt lookup decoding," GitHub, 2023. [Online]. Available: https://github.com/apoorvumang/prompt-lookup-decoding