

# Yet Another Markdown Cheatsheet

## Including MarkDown, MultiMarkdown, pandoc, GFM and LaTeX Math Syntax by MathJax

Kolen Cheung  
University of California, Berkeley  
khcheung@berkeley.edu

April 17, 2016

### Contents

<b>Contents</b>	<b>1</b>
<b>1 Introduction</b>	<b>3</b>
1.1 Organization	3
<b>2 Examples</b>	<b>4</b>
2.1 Header	4
2.1.1 Header <i>Containing <b>Styling</b></i> and a Link	4
2.1.2 Header Containing Attributes {#identifier .class1 key=value1}	4
2.1.3 Header Unnumbered {-}	4
2.1.4 Header Unnumbered 2 {.Unnumbered}	4
2.1.5 Auto Cross Reference	4
2.1.6 User defined reference	4
2.1.7 Deeper Levels of Headers	5
2.1.7.1 Header4	5
2.1.7.1.1 Header5	5
2.1.7.1.1.1 Header6	5
2.2 Backslash Escapes	5
2.3 Emphasis	5
2.3.1 CriticMarkup	5
2.4 Horizontal Rules	5
2.5 Break	6
2.6 Superscript & Subscript	6
2.7 Smarty Pants	6
2.8 Abbreviations (PHP Markdown Extra)	6
2.9 Lists	6
2.9.1 Compact vs Loose Lists	6
2.9.1.1 Compact	7
2.9.1.2 Loose	7

2.9.2	Ordered Lists . . . . .	7
2.9.3	Unordered Lists . . . . .	7
2.9.4	Nested Lists . . . . .	7
2.9.5	Cutoff a List . . . . .	8
2.9.6	List Item in a Block . . . . .	8
2.9.7	Fancy Lists . . . . .	8
<b>3</b>	<b>. one</b>	<b>8</b>
<b>4</b>	<b>. two</b>	<b>8</b>
4.1	Definition Lists . . . . .	9
4.1.1	Method 1 . . . . .	9
4.1.2	Method 2 . . . . .	9
4.2	Numbered Example Lists . . . . .	9
4.3	Code . . . . .	9
4.3.1	Fenced Code Blocks . . . . .	9
4.3.1.1	Method 1 . . . . .	9
4.3.1.2	Method 2 . . . . .	10
4.3.1.3	Method 3 . . . . .	10
4.4	Block-quotes . . . . .	10
4.4.0.1	Test . . . . .	10
4.4.1	Block-quotes Quoting Codes . . . . .	10
4.5	Line Blocks . . . . .	10
4.6	Tables . . . . .	10
4.6.1	Method 1 . . . . .	10
4.6.2	Method 2 . . . . .	11
4.6.3	Method 3 . . . . .	11
4.6.4	Method 4 . . . . .	11
4.6.5	Method 5 . . . . .	11
4.6.6	Method 6 . . . . .	12
4.7	Links . . . . .	12
4.7.1	Reference Links . . . . .	12
4.8	Footnotes . . . . .	12
4.8.1	Reference Footnotes . . . . .	12
4.8.2	Glossaries . . . . .	13
4.8.3	Citations . . . . .	13
4.8.3.1	MultiMarkdown . . . . .	13
4.8.3.2	Pandoc . . . . .	13
4.9	Images . . . . .	14
4.9.1	Reference Images . . . . .	15
4.9.2	Image with Links by Nesting Image and Link . . . . .	17
4.9.3	Block Level Images . . . . .	17
4.10	RAW . . . . .	19
4.10.1	HTML . . . . .	19
4.10.2	LaTeX . . . . .	19
<b>5</b>	<b>Other Syntaxes</b>	<b>19</b>
5.1	Metadata . . . . .	19
5.1.1	MultiMarkdown Metadata Block . . . . .	19

5.1.2	Pandoc Title Block . . . . .	19
5.1.3	YAML Metadata Block . . . . .	20
5.2	TOC . . . . .	20
5.2.1	Pandoc . . . . .	20
5.2.2	MultiMarkdown . . . . .	20
5.2.3	Kramdown . . . . .	20
5.3	Math . . . . .	21
5.3.1	Markdown . . . . .	21
5.3.2	MultiMarkdown and Pandoc . . . . .	21
	5.3.2.1 MultiMarkdown . . . . .	21
	5.3.2.2 Pandoc . . . . .	22
5.3.3	Inline Math . . . . .	22
5.3.4	Block Math . . . . .	22
5.3.5	Other Examples . . . . .	22
5.4	File Transclusion . . . . .	23
<b>6</b>	<b>References</b>	<b>23</b>
	<b>Bibliography</b>	<b>23</b>

## 1 Introduction

Examples ([chapter 2](#)) shows explicit examples for different syntaxes. Other Syntaxes ([chapter 5](#)) show the syntaxes that can't be shown explicitly.

### 1.1 Organization

- Header levels (except possibly the last header level): features in groups
- Last header level or a list: different syntaxes
- TaskPaper-styled tags to indicate in what favor of Markdown such syntax is supported
  - `@markdown`: supported by original markdown, hence understood to be supported by all variants of markdown
  - `@ghpages`: GitHub-Favored Markdown, built by kramdown with GFM option. i.e. GitHub Pages' GitHub-Favored Markdown
  - `@mmd`: MultiMarkdown
  - `@pandoc`: pandoc-favored markdown
  - `@phpextra`: PHP Markdown Extra (inspired some syntax in pandoc and mmd and gfm, not exhaustively tested here)
- TaskPaper Tags
  - `@... (partial)`: partial supports only
  - `@... (+...)`: when the extension is used
  - `@pandoc (--...)`: when the command line argument is used
  - `@pandoc (parsed)`: not verbatim, but parsed

Note:

- You might see `<!-- \begin{comment} -->...<!-- \end{comment} -->`. This is for mmd to tex to pdf use only. Ignore this.

## 2 Examples

### 2.1 Header

@markdown

See Emphasis ([section 2.3](#)) and Other Syntaxes ([chapter 5](#)) to see alternative Setext-style header styles @markdown

#### 2.1.1 Header *Containing Styling* and a [Link](#)

@markdown

#### 2.1.2 Header Containing Attributes {#identifier .class1 key=value1}

@pandoc @phpextra

#### 2.1.3 Header Unnumbered {-}

@pandoc

#### 2.1.4 Header Unnumbered 2 {.Unnumbered}

@pandoc

#### 2.1.5 Auto Cross Reference

- Link to Header ([section 2.1](#)) @pandoc @ghpages @mmd
- Link to Header ([section 2.1](#)) @pandoc @mmd
- Header ([section 2.1](#)) @mmd @pandoc
- Header ([section 2.1](#)) @mmd @pandoc

#### 2.1.6 User defined reference

- userdefinedreference ([subsection 2.1.6](#)) @mmd
- Link to userdefinedreference ([subsection 2.1.6](#)) @mmd @pandoc(+mmd\_header\_identifiers)
- Link to “Header Containing Attributes” (??) @pandoc
- another-link (??) @pandoc

## 2.1.7 Deeper Levels of Headers

### 2.1.7.1 Header4

#### 2.1.7.1.1 Header5

##### 2.1.7.1.1.1 Header6

## 2.2 Backslash Escapes

\*testing\* @markdown

## 2.3 Emphasis

- *italic* or *italic* @markdown
- **bold** or **bold** @markdown
- ***bold italic*** or ***bold italic*** @markdown
- ~~strikethrough~~ @pandoc
- Small caps @pandoc @markdown(html)

### 2.3.1 CriticMarkup

Visually it looks like emphasis. Functionally it is much more, and called Critic Markup @mmd

- Deletions from the original text: This is is a test.
- Additions: This a test.
- Substitutions: This isn't a test.
- Highlighting: This is a test.
- Comments: This is a test.

See more at [CriticMarkup—MultiMarkdown Documentation](http://fletcher.github.io/MultiMarkdown-5/criticmarkup.html)<sup>1</sup>.

## 2.4 Horizontal Rules

@markdown

---

3 or more hyphens or asterisks

---



---

<sup>1</sup><http://fletcher.github.io/MultiMarkdown-5/criticmarkup.html>

## 2.5 Break

@markdown

No break like this

Soft break

like this

Hard break

like this

## 2.6 Superscript & Subscript

- $x^2$  @mmd
- $d_o$  @mmd
- $x^{a+b}$  @mmd @pandoc
- $x_{y,z}$  @mmd @pandoc
- $P_a \setminus \text{cat} \sim$  @pandoc

## 2.7 Smarty Pants

@markdown(+smartypants) @pandoc(-smart) @ghpages

- “Example 1”
- ‘Example 2’
- en-dash
- em—dash
- ellipsis...

@mmd

- “Example 3”

## 2.8 Abbreviations (PHP Markdown Extra)

@mmd @phpextra @pandoc(+abbreviations)

Testing abbreviations: HyperText Markup Language (HTML), World Wide Web Consortium (W3C) (mouseover it to see)

## 2.9 Lists

### 2.9.1 Compact vs Loose Lists

The following effects are the same for different kind of lists @markdown

### 2.9.1.1 Compact

- test 1
- test 2
- test 3

### 2.9.1.2 Loose

- test 1
- test 2
- test 3

### 2.9.2 Ordered Lists

@markdown

1. test
2. test
3. test

### 2.9.3 Unordered Lists

@markdown

- test
- test
- test

### 2.9.4 Nested Lists

@markdown

- test
  - test
- test
  1. test
  2. test
    - test
      - a) test
      - b) test
  3. test

- test

Note about LaTeX output in mmd/pandoc:

- The Maximum nesting level of lists in LaTeX is 4. The quick hack is to mix itemize and enumerate alternatively to go beyond this.

### 2.9.5 Cutoff a List

@markdown

1. one
2. two
3. three

1. uno
2. dos
3. tres

- item one
- item two

end of list

```
{ my code block }
```

### 2.9.6 List Item in a Block

@markdown

- First paragraph.  
Continued.
- Second paragraph. With a code block, which must be indented eight spaces:

```
{ code }
```

### 2.9.7 Fancy Lists

@pandoc

**3 . one**

**4 . two**

9) Ninth 10) Tenth 11) Eleventh i. i ii. ii iii. iii (2) Two (5) Three 1. Four \* Five



## 4.1 Definition Lists

### 4.1.1 Method 1

@mmd @phpextra @pandoc @ghpages

**Physics** The Fundamental of Science

Describe the Nature

Make Prediction

### 4.1.2 Method 2

@ghpages @pandoc @mmd

**Term 1** Definition 1

**Term 2 with *inline markup*** Definition 2

{ some code, part of Definition 2 }

Third paragraph of definition 2.

## 4.2 Numbered Example Lists

@pandoc

(@) My first example will be numbered (1). (@) My second example will be numbered (2).

Explanation of examples.

(@) My third example will be numbered (3).

(@good) This is a good example.

As (@good) illustrates, ...

## 4.3 Code

- `testing` @markdown
- `\[\ket{a}\]\{.latex}` @pandoc

### 4.3.1 Fenced Code Blocks

#### 4.3.1.1 Method 1

@markdown

```
test
test
    test
    # test
```

#### 4.3.1.2 Method 2

@markdown(partial:language-not-supported) @ghpages @pandoc @mmd

$\nabla \times \mathbf{E} = - \frac{\partial \mathbf{B}}{\partial t}$

#### 4.3.1.3 Method 3

@pandoc

~~~markdown test test test # test ~~~

~~~ {#mycode .markdown .numberLines startFrom="100"} test test test # test ~~~

### 4.4 Block-quotes

@markdown

#### 4.4.0.1 Test

test

test

test

- test
- test

#### 4.4.1 Block-quotes Quoting Codes

@markdown

`\newcommand...`

### 4.5 Line Blocks

@ghpages(partial) @pandoc

| The limerick packs laughs anatomical | In space that is quite economical. | But the good  
ones I've seen | So seldom are clean | And the clean ones so seldom are comical  
| 200 Main St. | Berkeley, CA 94718

### 4.6 Tables

#### 4.6.1 Method 1

@ghpages @pandoc @mmd

| **Right** | **Left** | **Default** | **Center** |

|——:|:——|——|:——:|

| 12 | 12 | 12 | 12 |

|     |     |     |     |
|-----|-----|-----|-----|
| 123 | 123 | 123 | 123 |
|-----|-----|-----|-----|

**1 | 1 | 1 | 1 |** Notice how pandoc can have optional caption like this

### 4.6.2 Method 2

@mmmd

Table 1: Table Caption

| Left align                                      | Right align                                      | Grouping<br>Center align                          |
|---|--|---|
| This<br>column<br>will<br>be<br>left<br>aligned | This<br>column<br>will<br>be<br>right<br>aligned | This<br>column<br>will<br>be<br>center<br>aligned |
| And a big grouping is like this                 |  |   |

### 4.6.3 Method 3

@pandoc

Right Left Center Default — — — — — 12 12 12 12 123 123 123 123 1 1 1 1  
Table: Demonstration of simple table syntax.

#### 4.6.4 Method 4

@pandoc

|            | Centered | Default   | Right | Left | Header | Aligned | Aligned | Aligned | ———— | ——— | ————— |
|------------|----------|---|-------|------|--------|---------|---------|---------|------|-----|-------|
| First row  | 12.0     | Example of a row that spans multiple lines.     |       |      |        |         |         |         |      |     |       |
| Second row | 5.0      | Here's another one. Note the blank line between |       |      |        |         |         |         |      |     |       |

Table: Here's the caption. It, too, may span multiple lines.

#### 4.6.5 Method 5

@pandoc Sample grid table.

```

+-----+-----+-----+ | Fruit | Price | Advantages | +=====+=====+
| Bananas | $1.34 | - built-in wrapper | | | | - bright color | +-----+-----+-----+
-----+ | Oranges | $2.10 | - cures scurvy | | | | - tasty | +-----+-----+-----+
-----+

```

### 4.6.6 Method 6

@ghpages

See [Syntax](#) | [kramdown](#)<sup>2</sup>

## 4.7 Links

- <https://www.wikipedia.org> @pandoc(+autolink\_bare\_uris)
- <https://www.wikipedia.org> @markdown
- [Wikipedia.org](#)<sup>3</sup> @markdown
- [Wikipedia.org](#)<sup>4</sup> @markdown
- [Mail to GitHub](#)<sup>5</sup> @markdown

### 4.7.1 Reference Links

- [Search here](#)<sup>6</sup> @markdown
- A [link](#)<sup>7</sup> with attributes. @mmd
- [Another link to the link above](#)<sup>8</sup>. @mmd
- A [link](#)<sup>9</sup> with attributes. @markdown
- [Another link](#)<sup>10</sup>. @markdown
- [link3](#)<sup>11</sup>. @markdown

## 4.8 Footnotes

- Footnotes <sup>12</sup> @mmd
- Footnotes <sup>^</sup>[This is a pandoc inline footnote] @pandoc

### 4.8.1 Reference Footnotes

- Footnotes<sup>13</sup> @markdown
- Long Footnotes <sup>14</sup> @pandoc @ghpages @mmd

This paragraph won't be part of the note, because it isn't indented.

---

<sup>2</sup><http://kramdown.gettalong.org/syntax.html#tables>

<sup>3</sup><https://www.wikipedia.org>

<sup>4</sup><https://www.wikipedia.org>

<sup>5</sup><mailto:support@github.com>

<sup>6</sup><https://www.google.com>

<sup>7</sup>[image.png](#)

<sup>8</sup>[image.png](#)

<sup>9</sup>[/foo/bar.html](#)

<sup>10</sup><http://fsf.org>

<sup>11</sup>[/bar#special](#)

<sup>12</sup>This is a mmd inline footnote

<sup>13</sup>This is a footnote

<sup>14</sup>Here's one with multiple blocks.

### 4.8.2 Glossaries

A special kind of footnote . @mmd

See more at [Glossary—MultiMarkdown Documentation](#)<sup>15</sup>.

### 4.8.3 Citations

It can look like footnotes in HTML output.

#### 4.8.3.1 MultiMarkdown

@mmd

- This is a statement that should be attributed to its source (1, p. 23).

See more at [Citations—MultiMarkdown Documentation](#)<sup>16</sup>.

#### 4.8.3.2 Pandoc

@pandoc

Very powerful but complicated. See more at [Citations—Pandoc Documentation](#)<sup>17</sup>.

---

Subsequent paragraphs are indented to show that they belong to the previous footnote.

```
{ some.code }
```

The whole paragraph can be indented, or just the first line. In this way, multi-paragraph footnotes work like multi-paragraph list items.

<sup>15</sup><http://fletcher.github.io/MultiMarkdown-5/glossary.html>

<sup>16</sup><http://fletcher.github.io/MultiMarkdown-5/citations.html>


<sup>17</sup><http://pandoc.org/README.html#citations>

## 4.9 Images



•  
@markdown

## 4.9.1 Reference Images



- @markdown
-  @mmd @pandoc(+mmd\_link\_attributes)




- .class width=30 height=20px} @pandoc @phpextra(partial)
- a reference ![image][ref] with attributes. @pandoc @phpextra(partial)

[ref]: image.png “optional title” {#id .class key=val key2=“val 2”}

{#id



#### 4.9.2 Image with Links by Nesting Image and Link



- @markdown

18

#### 4.9.3 Block Level Images

- Block level: HTML `figure` element in MultiMarkdown @mmd @pandoc

---

<sup>18</sup><https://www.wikipedia.org/>



## 4.10 RAW

### 4.10.1 HTML

- This should *not* be markdown (or is it?) @markdown
- This *is* markdown @mmd @pandoc(+markdown\_attribute)

See more at [Raw—MultiMarkdown Documentation](http://fletcher.github.io/MultiMarkdown-5/raw.html)<sup>19</sup>. See test in [Babelmark 2 - Compare markdown implementations](http://johnmacfarlane.net/babelmark2/?normalize=1&text=%3Cdiv%3EThis+should

### 4.10.2 LaTeX

- @mmd
- \newcommand\rawlatex{} @pandoc(parsed)
- \begin{...} @pandoc

## 5 Other Syntaxes

### 5.1 Metadata

Note: mmd accepts capitalized metadata keys but others do not. For maximum compatibility, `author(s)`, `title`, etc. should be in lower cases.

#### 5.1.1 MultiMarkdown Metadata Block

@mmd @pandoc(+mmd\_title\_block)

```
title:      A Sample MultiMarkdown Document
author:     Fletcher T. Penney
date:       February 9, 2011
comment:    This is a comment intended to demonstrate
            metadata that spans multiple lines, yet
            is treated as a single value.
CSS:        http://example.com/standard.css
```

See more at [Metadata—MultiMarkdown Documentation](http://fletcher.github.io/MultiMarkdown-5/metadata.html)<sup>20</sup>.

#### 5.1.2 Pandoc Title Block

@pandoc

```
% title
% author(s) (separated by semicolons)
% date
```

<sup>19</sup><http://fletcher.github.io/MultiMarkdown-5/raw.html>

<sup>20</sup><http://fletcher.github.io/MultiMarkdown-5/metadata.html>

### 5.1.3 YAML Metadata Block

```
@Mmd(partial)
  @pandoc @ghpages

  ---
  title:    A Sample MultiMarkdown Document
  author:   Fletcher T. Penney
  date:     February 9, 2011
  tags: [nothing, nothingness]
  abstract: |
    This is the abstract.

    It consists of two paragraphs.
  ---
```

## 5.2 TOC

### 5.2.1 Pandoc

```
@pandoc
  Use --toc as a command argument.
```

### 5.2.2 MultiMarkdown

```
@mmd
  {{TOC}}, see beginning. It preprocess the headings and generate a ToC on its own, and
  doesn't give instruction for LaTeX to generate one. A hack is like this:
```

```
---
...
LaTeX Input:    mmd-load-toc-setcounter
LaTeX Input:    mmd-load-toc
...
---
<!-- \begin{comment} -->
{{TOC}}
<!-- \end{comment} -->
...
```

See more at [ickc/peg-multimarkdown-latex-support](https://github.com/ickc/peg-multimarkdown-latex-support): Default support files for generating LaTeX documents with MMD 3 through MMD 5<sup>21</sup>.

### 5.2.3 Kramdown

```
@ghpages
```

---

<sup>21</sup><https://github.com/ickc/peg-multimarkdown-latex-support>

```
# Contents
{:.no_toc}

* Will be replaced with the ToC, excluding the "Contents" header
{:toc}
```

### 5.3 Math

MathJax is assumed. MathJax has many configurable options. See [MathJax TeX and LaTeX Support — MathJax 2.6 documentation](#)<sup>22</sup>.

#### 5.3.1 Markdown

@markdown

Add the following at the beginning of the document:

```
<script type="text/javascript"
  src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-AMS-HTML"
</script>
```

MathJax.js is used and any codes within math delimiters are treated as raw HTML and to be processed by MathJax.

MathJax delimiter are  $$$...$$$ ,  $\backslash(\dots\backslash)$  and  $\backslash[...\backslash]$  (because an extra  $\backslash$  can be used to escape from Markdown).

Depending on the markdown parser, extra tricks might be needed to make sure nothing within the math delimiter is treated as markdown (see [TeX and LaTeX in HTML documents — MathJax 2.6 documentation](#)<sup>23</sup>).  $$. . . $$  can be used with MathJax configuration (see [TeX and LaTeX math delimiters — MathJax 2.6 documentation](#)<sup>24</sup>).

#### 5.3.2 MultiMarkdown and Pandoc

There are subtleties how math should be used in HTML+MathJax and LaTeX output from single markdown source. See more in [Testing LaTeX Environments Usage in MathJax From Markdown Conversion \(including mmd and pandoc\)](#)<sup>25</sup>.

##### 5.3.2.1 MultiMarkdown

@mmd

Add the following metadata at the beginning of the document:

```
HTML header: <script type="text/javascript"
  src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-AMS-HTML"
</script>
```

MultiMarkdown math delimiter are  $$. . . $$ ,  $$$...$$$ ,  $\backslash(\dots\backslash)$  and  $\backslash[...\backslash]$ .

<sup>22</sup><http://mathjax.readthedocs.org/en/latest/tex.html>

<sup>23</sup><http://mathjax.readthedocs.org/en/latest/tex.html#tex-and-latex-in-html-documents>

<sup>24</sup><http://mathjax.readthedocs.org/en/latest/tex.html#tex-and-latex-math-delimiters>

<sup>25</sup><https://github.com/ickc/mathjax-latex-md-mmd-pandoc>

### 5.3.2.2 Pandoc

@pandoc(-mathjax)

For pandoc, add --mathjax in the command-line argument.

Default math delimiter for pandoc is  $\$...\$, \$\$...\$\$$ . Other options are configurable. See more in [Pandoc - Pandoc User's Guide](#)<sup>26</sup>.

### 5.3.3 Inline Math

- $1 + 1$
- $1 + 1$  @pandoc(+tex\_math\_double\_backslash)

### 5.3.4 Block Math

- $$RR^T = I$$
- $$A_S^T = B$$

### 5.3.5 Other Examples

- $$x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$
- $$\begin{aligned} \dot{x} &= \sigma(y-x) \setminus \dot{y} &= \rho x - y - xz \setminus \dot{z} \\ &= -\beta z + xy \end{aligned}$$
- $$\left( \sum_{k=1}^n a_k b_k \right)^2 \leq \left( \sum_{k=1}^n a_k^2 \right) \left( \sum_{k=1}^n b_k^2 \right)$$
- $$\mathbf{V}_1 \times \mathbf{V}_2 = \begin{vmatrix} \mathbf{i} & \mathbf{j} & \mathbf{k} \\ \frac{\partial X}{\partial u} & \frac{\partial Y}{\partial u} & 0 \\ \frac{\partial X}{\partial v} & \frac{\partial Y}{\partial v} & 0 \end{vmatrix}$$
- $$P(E) = \binom{n}{k} p^k (1-p)^{n-k}$$
- $$\frac{1}{(\sqrt{\phi\sqrt{5}} - \phi)e^{\frac{2}{5}\pi}} = 1 + \frac{e^{-2\pi}}{1 + \frac{e^{-4\pi}}{1 + \frac{e^{-6\pi}}{1 + \frac{e^{-8\pi}}{1 + \dots}}}}$$
- $$\begin{aligned} \nabla \times \vec{\mathbf{B}} &= \frac{1}{c} \nabla \times \vec{\mathbf{E}} \\ \frac{1}{c} \nabla \times \vec{\mathbf{E}} &= -\frac{1}{c} \frac{\partial \mathbf{B}}{\partial t} \\ \nabla \cdot \vec{\mathbf{E}} &= \frac{\rho}{\epsilon_0} \\ \nabla \cdot \vec{\mathbf{B}} &= 0 \end{aligned}$$

<sup>26</sup><http://pandoc.org/README.html#non-pandoc-extensions>

•

$$1 + \frac{q^2}{(1-q)} + \frac{q^6}{(1-q)(1-q^2)} + \cdots = \prod_{j=0}^{\infty} \frac{1}{(1-q^{5j+2})(1-q^{5j+3})}, \quad \text{for } |q| < 1.$$

## 5.4 File Transclusion

@mmd

See more at [File Transclusion—MultiMarkdown Documentation](#)<sup>27</sup>.

## 6 References

Some examples are directly or indirectly copied from the following documentations:

1. [Pandoc - Pandoc User's Guide](#)<sup>28</sup>
2. [MultiMarkdown User's Guide](#)<sup>29</sup>
3. [Syntax | kramdown](#)<sup>30</sup>

## Bibliography

- [1] John Doe. *Some Big Fancy Book*. Vanity Press, 2006.
- [2] John Doe. *Another Big Fancy Book*. Vanity Press, 2016. [13](#)

---

<sup>27</sup><http://fletcher.github.io/MultiMarkdown-5/transclusion.html>

<sup>28</sup><http://pandoc.org/README.html>

<sup>29</sup><http://fletcher.github.io/MultiMarkdown-5/>

<sup>30</sup><http://kramdown.gettalong.org/syntax.html#tables>