

GENERAL

ALIAPT The APT3000 Series pressure transmitter for general industrial application is the ideal solution for customers with demanding measuring requirements. APT3000 is a very high quality product, which even the most adverse environmental conditions cannot affect. The APT3000 offers continuous measuring ranges between 0-0.16 and 0-1000 bar in all the major units. These measuring ranges can be combined in the standard industry output signal. Application to machine building, Hydraulics, pneumatics, pumps, chemical industry.

FEATURES

- ❑ Improved performance, increased accuracy and greater stability
- ❑ Non-linearity 0.2% of span (BFSL)
- ❑ Measuring ranges from 0-0.16~0-1000 bar
- ❑ Output signal: 4-20 mA (2-Wire)
- ❑ Zero point and span adjustable
- ❑ Electrical connections: DIN EN 175301-803A
- ❑ 4 Digits LCD display, 270° rotatable

STANDARD SPECIFICATION

- | | | | |
|------------------------|--|------------------------|---|
| ● Process Fluid | : Liquid, Gas, Vapor | ● Display Range | : -1999~9999 |
| ● Application | : Absolute Pressure, Gauge Pressure, Vacuum | ● Display Unit | : MPa, bar, kPa, psi, pa, none |
| ● Measuring Range | : 0-0.16~0-1000 bar | ● Response Time | : ≥ 1 ms |
| ● Accuracy | : $\pm 0.45\%$ of span (Standard) | ● Output Response Time | : ≤ 8 ms |
| | : $\pm 0.20\%$ of span (Option) | ● Current Output | : 4-20 mA (2-Wire) |
| ● Non-Linearity | : $\leq 0.2\%$ of span (BFSL) | | Load : $\leq (\text{VDC}-15) / 0.02\text{A}$ |
| ● Non-Repeatability | : $\leq 0.05\%$ of span | | Load : $\leq (\text{VDC}-19) / 0.02\text{A}$ (with Display) |
| ● Stability | : $\leq \pm 0.2\%$ of URL for 1 year | ● Power Supply | : 11-36 VDC |
| ● Working Temperature | : -40~85 °C (Standard) | | : 15-36 VDC (with Display) |
| | : -40~125 °C (Option) | ● Material | |
| ● Compensation Temp. | : -10~70 °C | | Connection : Stainless steel 304 |
| ● Temp. Effect of zero | | | Diaphragm : Stainless steel 316L |
| | Ranges ≤ 0.25 bar : $\leq 0.4\%$ FS / 10K | | Body : Stainless steel 304 |
| | Ranges > 0.25 bar : $\leq 0.2\%$ FS / 10K | | Fill Fluid : Silicone Oil |
| ● Temp. Effect of span | : $\leq 0.2\%$ FS / 10K | | Wetted O-ring (inside) : Viton |
| ● Vibration Resistance | : 20 g (20-2000 Hz) per IEC 60068-2-6 | | Electrical Connector : PA66+30% FV |
| ● Shock Resistance | : 100 g (10 ms) | | Display Case : PA66+30% FV |
| ● Adjustability | | ● Electrical Connector | |
| | Zero Point : $\pm 3\%$ | | Ingress Protection : IP65 |
| | Span : 65%-150% (with APP300) | | Wire Cross-section : Max. 1.5 mm ² |
| ● Process Connection | : G1/4" (Standard) | | Cable Diameter : 6-8 mm |
| | : 1/2" NPT, 1/2" BSPP, M20, 3/4" NPT | ● EMI / RFI Effect | : Follow SAMA PMC 33.1 from 20-1000 |
| | : 3/4" BSPP etc. (Option) | | MHz and for field strengths up to 30 V/m |
| ● Intrinsically Safe | : Ex ia IIC T6 (Standard) | ● Ambient Temperature | : -20~70 °C |
| | | ● Humidity Limit | : 0-95% Relative Humidity |



ALIA TECHNOLOGY LLC

633 W. 5th Street, 26th Floor, Los Angeles, CA 90071, USA
TEL : + 1 - 213 - 533 - 4139 FAX : + 1 - 213 - 223 - 2317



URL : www.alia-inc.com
E-mail : alia@alia-inc.com
APT3000V1.2.3.r3.A4.en

DIMENSIONS

Max. Temperature : -40~85 °C	Max. Temperature : -40~125 °C	Max. Temperature : -40~85 °C With display	Max. Temperature : -40~125 °C With display

MEASURING RANGE

Range Code	Pressure Range	Range Code	Pressure Range	Range Code	Pressure Range	Range Code	Pressure Range
1	0-0.16 bar	6	0-1.6 bar	B	0-16 bar	G	0-160 bar
2	0-0.25 bar	7	0-2.5 bar	C	0-25 bar	H	0-250 bar
3	0-0.40 bar	8	0-4 bar	D	0-40 bar	J	0-400 bar
4	0-0.60 bar	9	0-6 bar	E	0-60 bar	K	0-600 bar
5	0-1 bar	A	0-10 bar	F	0-100 bar	L	0-1000 bar

Overpressure Limit_Range code 1-F: 200% FS / Range code G-L: 150% FS

MODEL SELECTION GUIDE

APT3000 Series									
Example: APT3000-G9NN-D-1/2"NPT									
APT3000-	X	X	X	X	-X	-XXXXX	Description		
Type	G						Gauge Pressure Transmitter		
	A						Absolute Pressure Transmitter * Note 1		
Pressure Range	1-L						Please see MEASURING RANGE		
Max. Temperature	N						-40~85 °C		
	H						-40~125 °C		
Accuracy	N						+/-0.45% of span (Standard)		
	C						+/-0.20% of span (Option)		
Display	-N						None		
	-D						with Display		
Connection	-NNNNN						G1/4" (Standard)		
	-XXXXX						1/2" NPT, 1/2" BSPP, M20 etc. (with Adapter)		

● **Note 1: Absolute Pressure Transmitter only for range code 5-B**

● **Note 2: APP300 ALIA Pressure Transmitter Programmer is used for APT3000 calibration, range modification and 4-20 mA analog**