

Table of Contents

Quick Start	2
GeminiChatRequest Features	5
All Endpoints	15
UGemini v2 Breaking Changes	33

Quick Start

Please note that the code provided in this page is *purely* for learning purposes and is far from perfect. Remember to null-check all responses!

Setup

Add an instance of `Uralstech.UGemini.GeminiManager` to your scene, and set it up with your Gemini API key. You can get your API key from [here](#).

GeminiManager

There are only three methods in `GeminiManager`:

Method	What it does
<code>SetApiKey</code>	Sets the Gemini API key through code
<code>Request</code>	Computes a request on the Gemini API
<code>StreamRequest*</code>	Computes a streaming request on the Gemini API

*Requires [Utilities.Async](#).

All computations on the Gemini API are done through `GeminiManager.Request`, `GeminiManager.StreamRequest` and their variants.

In this page, the fields, properties and methods of each type will not be explained. Every type has been fully documented in code, so please check the code docstrings or reference documentation to learn more about each type.

Beta API

`GeminiManager` supports both the `v1` and `v1beta` Gemini API versions. As a lot of features are still unsupported in the main `v1` API, you may need to use the Beta API. You can set the `useBetaApi` boolean parameter in the request's constructor to do so.

Models

`Uralstech.UGemini.Models.GeminiModel` has multiple static model IDs:

- [Gemini1_5Flash](#)
- [Gemini1_5Pro](#)
- [Gemini1_0Pro](#)
- And so on...

You can provide these to the `model` parameter in the constructors for model-related requests. `UGemini` can also implicitly convert `string` model IDs to `GeminiModelId` objects.

QuickStart: Multi-turn Chat Request

This is a simple script that maintains the user's chat history with Gemini.

```
using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.Generation.Chat;

private List<GeminiContent> _chatHistory = new();

private async Task<string> OnChat(string text)
{
    _chatHistory.Add(GeminiContent.GetContent(text, GeminiRole.User));
    GeminiChatResponse response = await GeminiManager.Instance.Request<GeminiChatResponse>(
        new GeminiChatRequest(GeminiModel.Gemini1_5Flash)
        {
            Contents = _chatHistory.ToArray(),
        }
    );

    _chatHistory.Add(response.Candidates[0].Content);
    return response.Parts[0].Text;
}
```

Here, we simply have a list of `GeminiContent` objects, which tracks the messages of the conversation. Every time `OnChat` is called, the user's request and the model's reply are added to the list.


What Next?

You can check out more [GeminiChatRequest Features](#) like Streaming Requests, Function Calling, Code Execution and more. You can also read the documentation for [all Gemini API endpoints that UGemini supports](#) to learn more about features like File Uploads, Content Caching and Fine Tuning.

Samples

For full-fledged examples of the features of this package, check out the samples included in the package:

Multi-turn Chat

A sample scene showing a multi-turn chat system. [GitHub Source](#) 

Function Calling

A sample scene showing a function calling system. [GitHub Source](#)

Streaming Generated Content

A sample showing a system which streams Gemini's responses, including function calls. [GitHub Source](#)

Question Answering

A sample scene with a system where Gemini answers questions based only on the given context. [GitHub Source](#)

Prompting with File API

A sample scene with a system to create, delete, retrieve, list and prompt Gemini with files stored in the File/Media API endpoints. [GitHub Source](#)

JSON Response

A sample scene showing a system where Gemini responds in a specified JSON format. [GitHub Source](#)

List and Get Model Metadata

A sample scene with a system to list, get and chat with models using the models.get and models.list endpoints. [GitHub Source](#)

Token Counting

A sample scene showing a token counting system using the `countTokens` endpoint. [GitHub Source](#)

GeminiChatRequest Features

`GeminiAnswerRequest` also shares some of these features.

Streaming Responses

`GeminiChatRequest` allows you to stream Gemini's response in real-time. You can do so by using `GeminiManager.StreamRequest` and utilizing the callback in `GeminiChatRequest`.

You can even stream function calls! Check out the `Streaming Generated Content` sample included in the package.

```
using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.Generation.Chat;

[SerializeField] private Text _chatResponse;

private async Task<string> OnChat(string text)
{
    GeminiChatResponse response = await GeminiManager.Instance.StreamRequest(new
    GeminiChatRequest(GeminiModel.Gemini1_5Flash)
    {
        Contents = new GeminiContent[]
        {
            GeminiContent.GetContent(text, GeminiRole.User),
        },

        OnPartialResponseReceived = streamedResponse =>
        {
            _chatResponse.text = streamedResponse.Parts[0].Text;
            return Task.CompletedTask;
        }
    });

    return response.Parts[0].Text;
}
```

If you do not want to use the callback, you can let the `StreamRequest` task run in the background, and access the streamed data from the `GeminiChatRequest.StreamedResponse` property.

Adding Media Content to Requests

`GeminiContent.Parts` contains the actual contents of each chat request and response. You can add media content to the `Parts` array, but you must only have one type of data in each part, like one part of text, one part of an image, and so on. The following samples shows data being read from a file and into a `GeminiContent` object.

```
using Uralstech.UGemini;
using Uralstech.UGemini.Models.Content;

private async Task<GeminiContent> GetFileContent(string filePath,
GeminiContentType contentType)
{
    byte[] data;
    try
    {
        data = await File.ReadAllBytesAsync(filePath);
    }
    catch (SystemException exception)
    {
        Debug.LogError($"Failed to load file: {exception.Message}");
        return null;
    }

    return new GeminiContent()
    {
        Parts = new GeminiContentPart[]
        {
            new GeminiContentPart()
            {
                Text = "What's in this file?"
            },
            new GeminiContentPart()
            {
                InlineData = new GeminiContentBlob()
                {
                    MimeType = contentType,
                    Data = Convert.ToBase64String(data)
                }
            }
        }
    };
}
```

Now, the `GeminiContent` returned by the method can be fed into a chat request!

Utility Methods

`GeminiContent` and `GeminiContentBlob` also contain static utility methods to help create them from Unity types like `AudioClip` or `Texture2D`:

- `GeminiContent.GetContent`
 - Can convert `string` messages, `Texture2D` images, `AudioClip`* audio and `GeminiFile` data to `GeminiContent` objects.
- `GeminiContentBlob.GetContentBlob`
 - Can convert `Texture2D` images and `AudioClip`* audio to `GeminiContentBlob` objects.

*Requires [Utilities.Encoding.Wav](#)🔗.

Function Calling

First, we have to setup our tools and define our function schemas.

```
using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.Generation.Chat;
using Uralstech.UGemini.Models.Generation.Schema;
using Uralstech.UGemini.Models.Generation.Tools;
using Uralstech.UGemini.Models.Generation.Tools.Declaration;

private GeminiTool _geminiFunctions = new GeminiTool()
{
    FunctionDeclarations = new GeminiFunctionDeclaration[]
    {
        new GeminiFunctionDeclaration()
        {
            Name = "printToConsole",
            Description = "Print text to the user's console.",
            Parameters = new GeminiSchema()
            {
                Type = GeminiSchemaDataType.Object,
                Properties = new Dictionary<string, GeminiSchema>()
                {
                    {
                        "text", new GeminiSchema()
                        {
                            Type = GeminiSchemaDataType.String,
                            Description = "The text to print. e.g. \"Hello, World!\"",
                            Nullable = false,
```

```

        }
    },
    },
    Required = new string[] { "text" },
}
},

new GeminiFunctionDeclaration()
{
    Name = "changeTextColor",
    Description = "Change the color of the text.",
    Parameters = new GeminiSchema()
    {
        Type = GeminiSchemaDataType.Object,
        Properties = new Dictionary<string, GeminiSchema>()
        {
            {
                "color", new GeminiSchema()
                {
                    Type = GeminiSchemaDataType.String,
                    Description = "The color to set. e.g. \"BLUE\"",
                    Format = GeminiSchemaDataFormat.Enum,
                    Enum = new string[]
                    {
                        "RED",
                        "GREEN",
                        "BLUE",
                        "WHITE",
                    },
                    Nullable = false,
                }
            },
        },
    },
    Required = new string[] { "color" },
}
}
},
};

```

To use Gemini Tools, we need to declare each tool to use. So, we have created a declaration for function calling. Each *tool* must be declared separately but every *function* must be declared in a single *tool* declaration.

For each function, we need a declaration with a name and description. The parameters are an object of type `GeminiSchema`, which defines the schema of each of the parameters. The type is of

`GeminiSchemaDataType.Object`, and contains the dictionary of parameter schemas.

The keys of the dictionary should be the parameter name, and the values should be `GeminiSchema` objects which define the type, description, format, etc. of the parameter.

Finally, we have the `Required` property which tells Gemini which fields are absolutely required in each call. Now, we can move on to the chat.

```
[SerializeField] private Text _chatResponse;

private async Task<string> OnChat(string text)
{
    List<GeminiContent> contents = new()
    {
        GeminiContent.GetContent(text, GeminiRole.User),
    };

    GeminiChatResponse response;
    GeminiFunctionCall functionCall;
    string responseText = string.Empty;
    do
    {
        response = await GeminiManager.Instance.Request<GeminiChatResponse>(new
        GeminiChatRequest(GeminiModel.Gemini1_5Flash, true)
        {
            Contents = contents.ToArray(),
            Tools = new GeminiTool[] { _geminiFunctions },
            ToolConfig =
            GeminiToolConfiguration.GetConfiguration(GeminiFunctionCallingMode.Auto),
        });

        // Don't forget to do this! If the function call is not added to the chat
        // history, Gemini will throw an error when receiving the response!
        contents.Add(response.Candidates[0].Content);

        responseText = Array.Find(response.Parts, part =>
        !string.IsNullOrEmpty(part.Text)).Text;
        GeminiContentPart[] allFunctionCalls = Array.FindAll(response.Parts, part =>
        part.FunctionCall != null);

        functionCall = null;
        for (int i = 0; i < allFunctionCalls.Length; i++)
        {
            functionCall = allFunctionCalls[i].FunctionCall;
            JObject functionResponse = null;
        }
    }
}
```

```

        switch (functionCall.Name)
        {
            case "printToConsole":
                Debug.Log(functionCall.Arguments["text"].ToObject<string>());
                break;

            case "changeTextColor":
                if (!TryChangeTextColor(functionCall.Arguments["color"].ToObject<string>
(
)))
                {
                    functionResponse = new JObject()
                    {
                        ["result"] = "Unknown color."
                    };
                }

                break;

            default:
                functionResponse = new JObject()
                {
                    ["result"] = "Sorry, but that function does not exist."
                };

                break;
        }

        contents.Add(GeminiContent.GetContent(functionCall.GetResponse(functionResponse
?? new JObject()
    {
        ["result"] = "Completed executing function successfully."
    }
    ))));
    }
} while (functionCall != null);

_chatResponse.text = responseText;
return responseText;
}

private bool TryChangeTextColor(string color)
{
    switch (color)
    {
        case "RED":
            _chatResponse.color = Color.red; break;
    }
}

```

```

        case "GREEN":
            _chatResponse.color = Color.green; break;

        case "BLUE":
            _chatResponse.color = Color.blue; break;

        case "WHITE":
            _chatResponse.color = Color.white; break;

        default:
            return false;
    }

    Debug.Log("Changed text color!");
    return true;
}

```

Here, we are going through each response, checking if a function was called, and calling the requested function.

The response is a JSON object, which is optional, but it is recommended to include. Note the use of `GeminiToolConfiguration.GetConfiguration`, which is a utility method to create a `GeminiToolConfiguration` with the given `GeminiFunctionCallingMode`. `GeminiFunctionCallingMode.Any` means Gemini will always call at least one function in each *request*, `Auto` means the model will call the functions when it thinks it needs to, and `None` means no functions can be called.

After the function is called, we respond by adding the calls and responses to the history. We use the `GetResponse` utility method to get a `GeminiFunctionResponse` object with the response JSON.

Function calling is, as of writing, only available in the Beta API.

Code Execution

Code execution is also a Tool, so it is similar to function calling:

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.Generation.Chat;
using Uralstech.UGemini.Models.Generation.Tools.Declaration;

private GeminiTool _geminiCodeExecution = new GeminiTool()
{
    CodeExecution = new GeminiCodeExecution()
};

```

```

[SerializeField] private Text _chatResponse;

private async Task<string> OnChat(string text)
{
    List<GeminiContent> contents = new()
    {
        GeminiContent.GetContent(text, GeminiRole.User),
    };

    GeminiChatResponse response = await GeminiManager.Instance.Request<GeminiChatResponse>
(new GeminiChatRequest(GeminiModel.Gemini1_5Flash, true)
    {
        Contents = contents.ToArray(),
        Tools = new GeminiTool[] { _geminiCodeExecution },
    });

    string responseText = string.Join(", ", Array.ConvertAll(response.Parts, part => $"
(Text={part.Text}, Code={part.ExecutableCode?.Code}, ExecutionResult=
{part.CodeExecutionResult?.Output}))");

    _chatResponse.text = responseText;
    return responseText;
}

```

That's it! Now, when code execution is used, the response should be something like this:

```

> Make a simple python program to print hello world and use code execution for that.
Result: (Text=, Code=, ExecutionResult=), (Text=, Code=print("Hello world!"),
ExecutionResult=), (Text=, Code=, ExecutionResult=Hello world!),
(Text=I have created a simple Python program that prints "Hello world!". I used the
`print()` function to achieve this. The code was executed
using the `tool_code` block., Code=, ExecutionResult=)

```

Code execution is also, as of writing, only available in the Beta API.

JSON Response Mode

In JSON mode, Gemini will always respond in the specified JSON response schema.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.Generation;

```

```

using Uralstech.UGemini.Models.Generation.Chat;
using Uralstech.UGemini.Models.Generation.Schema;

private async Task<string> OnChat(string text)
{
    // Note: It seems GeminiModel.Gemini1_5Flash is not very good at JSON.
    GeminiChatResponse response = await GeminiManager.Instance.Request<GeminiChatResponse>
(new GeminiChatRequest(GeminiModel.Gemini1_5Pro, true)
    {
        Contents = new GeminiContent[]
        {
            GeminiContent.GetContent(text, GeminiRole.User),
        },
        SystemInstruction = GeminiContent.GetContent("You are a helpful math teacher who
teacher their students mathematics in the most helpful way possible."),
        GenerationConfig = new GeminiGenerationConfiguration()
        {
            ResponseMimeType = GeminiResponseType.Json,
            ResponseSchema = new GeminiSchema()
            {
                Type = GeminiSchemaDataType.Array,
                Description = "A list of mathematical expressions.",
                Items = new GeminiSchema()
                {
                    Type = GeminiSchemaDataType.Object,
                    Properties = new Dictionary<string, GeminiSchema>()
                    {
                        {
                            "expression", new GeminiSchema()
                            {
                                Type = GeminiSchemaDataType.String,
                            }
                        },
                        {
                            "explanation", new GeminiSchema()
                            {
                                Type = GeminiSchemaDataType.String,
                            }
                        },
                    },
                },
                Required = new string[] { "expression", "explanation", },
            },
        },
    });
}

```

```
    return response.Parts[0].Text;  
}
```

Here, we used a schema for an array of objects, which contain two parameters: `expression` and `explanation`. We have told Gemini to split the response into the parameters, where a mathematical expression and its explanation is given.

The `GeminiSchema` object is the same type used for function calling.

JSON mode is also only available in the Beta API.

All Supported Endpoints

CachedContents (Beta API)

Context caching allows you to save and reuse precomputed input tokens that you wish to use repeatedly, for example when asking different questions about the same media file.

Create

Creates CachedContent resource.

```
private async Task<GeminiCachedContent> RunCreateCachedContentRequest()
{
    // Content must be at least 32,768 tokens.
    StringBuilder sb = new StringBuilder();
    for (int i = 0; i < 1800; i++)
        sb.Append("(*)#$*OIJIR$U(IJT^(U$*I%O$#@");

    return await GeminiManager.Instance.Request<GeminiCachedContent>(new
        GeminiCachedContentCreateRequest(new GeminiCachedContentCreationData
        {
            Contents = new[]
            {
                GeminiContent.GetContent(sb.ToString(), GeminiRole.User),
            },
            ExpireTime = DateTime.UtcNow.AddDays(1),
            Model = "Gemini-1.5-flash-001", // Make sure the model you use supports caching!
        }));
}
```

See [GeminiCachedContent](#) and [GeminiCachedContentCreateRequest](#) for more details.

Delete

Deletes CachedContent resource.

```
private async Task RunDeleteCachedContentRequest(GeminiCachedContent content)
{
    Debug.Log("Deleting cached content...");
    await GeminiManager.Instance.Request(new
```

```
GeminiCachedContentDeleteRequest(content.Name));  
    Debug.Log("Content deleted.");  
}
```

See [GeminiCachedContentDeleteRequest](#) for more details.

Get

Reads CachedContent resource.

```
private async Task<GeminiCachedContent> RunGetCachedContentRequest(string contentName)  
{  
    return await GeminiManager.Instance.Request<GeminiCachedContent>(new  
    GeminiCachedContentGetRequest(contentName));  
}
```

See [GeminiCachedContent](#) and [GeminiCachedContentGetRequest](#) for more details.

List

Lists CachedContents.

```
private async Task<GeminiCachedContent[]> RunListCachedContentRequest()  
{  
    GeminiCachedContentListResponse response = await  
    GeminiManager.Instance.Request<GeminiCachedContentListResponse>(new  
    GeminiCachedContentListRequest());  
    return response.CachedContents;  
}
```

See [GeminiCachedContentListResponse](#) and [GeminiCachedContentListRequest](#) for more details.

Patch

Updates CachedContent resource (only expiration is updatable).

```
private async Task<GeminiCachedContent> RunPatchCachedContentRequest(string contentName)  
{  
    return await GeminiManager.Instance.Request<GeminiCachedContent>(new  
    GeminiCachedContentPatchRequest(new GeminiCachedContentPatchData
```



```

{
    ExpireTime = DateTime.UtcNow.AddYears(1),
}, contentName));
}

```

See [GeminiCachedContent](#) and [GeminiCachedContentPatchRequest](#) for more details.

Models

The Models endpoint contains methods that allow you to access and inference Gemini models.

Get

Gets information about a specific Model such as its version number, token limits, parameters and other metadata.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models;

private async Task<GeminiModel> RunGetModelRequest(string modelId)
{
    return await GeminiManager.Instance.Request<GeminiModel>(new
    GeminiModelGetRequest(modelId));
}

```

See [GeminiModel](#) and [GeminiModelGetRequest](#) for more details.

Newer models will not be recognized by the request if you're not using the Beta API.

List

Lists the Models available through the Gemini API.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models;

private async Task<GeminiModel[]> RunListModelRequest(int maxModels = 50, string pageToken
= null)
{
    GeminiModelListResponse response = await
    GeminiManager.Instance.Request<GeminiModelListResponse>(new GeminiModelListRequest()

```

```

{
    MaxResponseModels = maxModels,
    PageToken = string.IsNullOrEmpty(pageToken) ? string.Empty : pageToken,
});

return response?.Models;
}

```

See [GeminiModelListResponse](#) and [GeminiModelListRequest](#) for more details.

Newer models will not be recognized by the request if you're not using the Beta API.

EmbedContent

Generates a text embedding vector from the input Content using the specified Gemini Embedding model.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.Embedding;

private async void RunEmbedContentRequest()
{
    Debug.Log("Running embedding request.");

    GeminiEmbedContentResponse response = await
GeminiManager.Instance.Request<GeminiEmbedContentResponse>(
    new GeminiEmbedContentRequest(GeminiModel.TextEmbedding004)
    {
        Content = GeminiContent.GetContent("Hello! How are you?"),
    }
);

    Debug.Log($"Embedding values: {string.Join(", ", response.Embedding.Values)}");
}

```

See [GeminiEmbedContentResponse](#) and [GeminiEmbedContentRequest](#) for more details.

BatchEmbedContents

Generates multiple embedding vectors from the input Content which consists of a batch of strings represented as EmbedContentRequest objects.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.Embedding;

private async void RunBatchEmbedContentRequest()
{
    Debug.Log("Running batch embedding request.");

    // Make sure the model used for the batch request is the same for all included requests.
    GeminiBatchEmbedContentResponse response = await
GeminiManager.Instance.Request<GeminiBatchEmbedContentResponse>(
    new GeminiBatchEmbedContentRequest(GeminiModel.TextEmbedding004)
    {
        Requests = new GeminiEmbedContentRequest[]
        {
            new GeminiEmbedContentRequest(GeminiModel.TextEmbedding004)
            {
                Content = GeminiContent.GetContent("Hello! How are you?"),
            },
            new GeminiEmbedContentRequest(GeminiModel.TextEmbedding004)
            {
                Content = GeminiContent.GetContent("Lorem ipsum dolor sit amet,
consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore
magna aliqua."),
            }
        }
    });

    foreach (GeminiContentEmbedding embedding in response.Embeddings)
        Debug.Log($"Embedding values: {string.Join(", ", embedding.Values)}");
}

```

See [GeminiBatchEmbedContentResponse](#) and [GeminiBatchEmbedContentRequest](#) for more details.

GenerateContent

Generates a model response given an input GenerateContentRequest.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;

```

```

using Uralstech.UGemini.Models.Generation.Chat;

private async void RunChatRequest()
{
    Debug.Log("Running chat request.");

    GeminiChatResponse response = await GeminiManager.Instance.Request<GeminiChatResponse>(
        new GeminiChatRequest(GeminiModel.Gemini1_5Flash)
        {
            Contents = new GeminiContent[]
            {
                GeminiContent.GetContent("What's up?")
            },
        }
    );

    Debug.Log($"Gemini's response: {response.Parts[^1].Text}");
}

```

See [GeminiChatResponse](#) and [GeminiChatRequest](#) for more details.

StreamGenerateContent

Generates a streamed response from the model given an input GenerateContentRequest.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.Generation.Chat;

private async void RunStreamingChatRequest()
{
    Debug.Log("Running streamed chat request.");

    GeminiChatResponse response = await GeminiManager.Instance.StreamRequest(
        new GeminiChatRequest(GeminiModel.Gemini1_5Flash)
        {
            Contents = new GeminiContent[]
            {
                GeminiContent.GetContent("What's up? Tell me a story about airplanes.")
            },
            OnPartialResponseReceived = partialResponse =>
            {
                if (partialResponse.Candidates == null || partialResponse.Candidates.Length

```

```

< 0)

        return Task.CompletedTask;

        Debug.Log($"Gemini's partial response: {partialResponse.Parts[^1].Text}");
        return Task.CompletedTask;
    }
}

);

Debug.Log($"Gemini's final response: {response.Parts[^1].Text}");
}

```

See [GeminiChatResponse](#) and [GeminiChatRequest](#) for more details.

GenerateAnswer (Beta API)

Generates a grounded answer from the model given an input `GenerateAnswerRequest`.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.Content.Attribution;
using Uralstech.UGemini.Models.Generation.QuestionAnswering;
using Uralstech.UGemini.Models.Generation.QuestionAnswering.Grounding;

private async void RunQuestionAnsweringRequest()
{
    Debug.Log("Running Q/A request.");

    GeminiAnswerResponse response = await
    GeminiManager.Instance.Request<GeminiAnswerResponse>(
        new GeminiAnswerRequest(GeminiModel.Aqa)
        {
            Contents = new GeminiContent[]
            {
                GeminiContent.GetContent("What is e2zr2?")
            },

            InlinePassages = new GeminiGroundingPassages()
            {
                Passages = new GeminiGroundingPassage[]
                {
                    new GeminiGroundingPassage()
                    {

```

```

        Id = "ezrSquaredContext",
        Content = GeminiContent.GetContent(
            "ezr² is an easy to learn and practical interpreted programming
            language for beginners and experts alike made in C#." +
            "The latest version of ezr² RE has been released! ezr² RE, or
            REwrite, is the project's initiative to rewrite ezr². " +
            "The latest working version of ezr² RE has many more features
            than the latest version of ezr²! But, it is still in " +
            "development, has some essential features missing. Like the
            include expression, or any built-in object methods like " +
            "\"a string\".length or [\"a\", \"list\"].insert. If you want to
            help in testing it out and fixing bugs, feel free to" +
            " download the latest version of ezr² RE from the ezr² GitHub
            releases page and compiling it using the .NET SDK and/or" +
            " Visual Studio. The GitHub releases page is:
            https://github.com/Uralstech/ezrSquared/releases."
        )
    }
}
},

    AnswerStyle = GeminiAnswerStyle.Verbose,
}
);

if (response.Answer.Content != null)
    Debug.Log($"Gemini's answer: {response.Answer.Content.Parts[^1].Text}");

foreach (GeminiGroundingAttribution attribution in
response.Answer.GroundingAttributions)
    Debug.Log($"Attribution ID: {attribution.SourceId.GroundingPassage.PassageId} |
Content: {attribution.Content.Parts[^1].Text}");
}

```

See [GeminiAnswerResponse](#) and [GeminiAnswerRequest](#) for more details.

CountTokens

Runs a model's tokenizer on input Content and returns the token count.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.CountTokens;

```

```
private async void RunTokenCountRequest()
{
    Debug.Log("Running token counting request.");

    GeminiTokenCountResponse response = await
GeminiManager.Instance.Request<GeminiTokenCountResponse>(
    new GeminiTokenCountRequest(GeminiModel.Gemini1_5Flash)
    {
        Contents = new GeminiContent[]
        {
            GeminiContent.GetContent("Hello! How are you?"),
        }
    }
);

    Debug.Log($"Tokens: {response.TotalTokens}");
}
```

See [GeminiTokenCountResponse](#) and [GeminiTokenCountRequest](#) for more details.

TunedModels (Beta API)

The TunedModels endpoint contains methods that allow you to access and inference fine-tuned Gemini models.

You will have to use [OAuth](#) authorization to access a lot of these endpoints, with permissions like:

- <https://www.googleapis.com/auth/generative-language.tuning>
- <https://www.googleapis.com/auth/cloud-platform>

Create

Creates a tuned model. Check intermediate tuning progress (if any) through the google.longrunning.Operations service with the [UCloud.Operations](#) plugin. See [Operations Endpoints](#) for more details and code examples.

```
using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Tuning;

private async void RunTunedModelCreateRequest(string oauthAccessToken)
{

```

```

Debug.Log("Creating tuned model.");

GeminiTuningExample[] examples = new GeminiTuningExample[20];
for (int i = 0; i < examples.Length; i++)
{
    examples[i] = new GeminiTuningExample
    {
        TextInput = "What is your name?",
        Output = "My name is [insert name here].",
    };
}

GeminiTunedModelCreateResponse response = await
GeminiManager.Instance.Request<GeminiTunedModelCreateResponse>(
    new GeminiTunedModelCreateRequest(
        new GeminiTunedModelCreationData
        {
            BaseModel = GeminiModel.Gemini1_5FlashTuning,
            DisplayName = "Test Model",
            Description = "This is a test model",
            TuningTask = new GeminiInitialTuningTask
            {
                TrainingData = new GeminiTuningDataset
                {
                    Examples = new GeminiTuningExamples
                    {
                        Examples = examples,
                    },
                },
            },
        }, true)
    {
        ModelId = "tunedModels/mynameis",
        OAuthAccessToken = oauthAccessToken,
    });

Debug.Log($"Tuned model created (JSON): {JsonConvert.SerializeObject(response)}");
}

```

See [GeminiTunedModelCreateResponse](#) and [GeminiTunedModelCreateRequest](#) for more details.

Delete

Deletes a tuned model. This will also delete the operations associated with it.


```

using Uralstech.UGemini;
using Uralstech.UGemini.Models.Tuning;

private async void RunTunedModelDeleteRequest(string oauthAccessToken)
{
    Debug.Log("Deleting tuned model.");

    await GeminiManager.Instance.Request(
        new GeminiTunedModelDeleteRequest("tunedModels/mynameis")
        {
            OAuthAccessToken = oauthAccessToken
        });

    Debug.Log("Tuned model deleted.");
}

```

See [GeminiTunedModelDeleteRequest](#) for more details.

GenerateContent

Generates a model response given an input `GenerateContentRequest`.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models.Content;
using Uralstech.UGemini.Models.Generation.Chat;

private async void RunTunedModelChatRequest(string oauthAccessToken)
{
    Debug.Log("Running chat request on tuned model.");

    GeminiChatResponse response = await GeminiManager.Instance.Request<GeminiChatResponse>(
        new GeminiChatRequest("tunedModels/mynameis")
        {
            AuthMethod = GeminiAuthMethod.OAuthAccessToken,
            OAuthAccessToken = oauthAccessToken,
            Contents = new GeminiContent[]
            {
                GeminiContent.GetContent("Who are you?")
            },
        }
    );
}

```

```
    Debug.Log($"Tuned Gemini's response: {response.Parts[^1].Text}");  
}
```

See [GeminiChatResponse](#) and [GeminiChatRequest](#) for more details.

Get

Gets information about a specific TunedModel.

```
using Uralstech.UGemini;  
using Uralstech.UGemini.Models.Tuning;  
  
private async void RunTunedModelGetRequest(string oauthAccessToken)  
{  
    Debug.Log("Getting tuned model.");  
  
    GeminiTunedModel response = await GeminiManager.Instance.Request<GeminiTunedModel>(  
        new GeminiTunedModelGetRequest("tunedModels/mynameis")  
        {  
            OAuthAccessToken = oauthAccessToken  
        });  
  
    Debug.Log($"Got tuned model (JSON): {JsonConvert.SerializeObject(response)}");  
}
```

See [GeminiTunedModel](#) and [GeminiTunedModelGetRequest](#) for more details.

List

Lists created tuned models.

```
using Uralstech.UGemini;  
using Uralstech.UGemini.Models.Tuning;  
  
private async void RunTunedModelListRequest(string oauthAccessToken)  
{  
    Debug.Log("Listing tuned models.");  
  
    GeminiTunedModelListResponse response = await  
    GeminiManager.Instance.Request<GeminiTunedModelListResponse>(  
        new GeminiTunedModelListRequest()  
        {  

```

```

        OAuthAccessToken = oauthAccessToken
    });

    Debug.Log($"Got tuned models (JSON): {JsonConvert.SerializeObject(response)}");
}

```

See [GeminiTunedModelListResponse](#) and [GeminiTunedModelListRequest](#) for more details.

Patch

Updates a tuned model.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models.Tuning;

private async void RunTunedModelPatchRequest(string oauthAccessToken)
{
    Debug.Log("Patching tuned model.");

    GeminiTunedModelPatchData response = await
    GeminiManager.Instance.Request<GeminiTunedModelPatchData>(
        new GeminiTunedModelPatchRequest(
            new GeminiTunedModelPatchData
            {
                DisplayName = "This has been changed!",
            }, "tunedModels/mynameis")
            {
                OAuthAccessToken = oauthAccessToken,
            }
        ));

    Debug.Log($"Patched tuned model (JSON): {JsonConvert.SerializeObject(response)}");
}

```

See [GeminiTunedModelPatchData](#) and [GeminiTunedModelPatchRequest](#) for more details.

TransferOwnership

Transfers ownership of the tuned model. This is the only way to change ownership of the tuned model. The current owner will be downgraded to writer role.

```

using Uralstech.UGemini;
using Uralstech.UGemini.Models.Tuning;

```

```
private async void RunTunedModelTransferOwnershipRequest(string oauthAccessToken)
{
    Debug.Log("Transferring tuned model.");

    await GeminiManager.Instance.Request(new
GeminiTunedModelTransferOwnershipRequest("tunedModels/mynameis")
    {
        EmailAddress = "SomeGuy@SomeMail.com",
        OAuthAccessToken = oauthAccessToken,
    });

    Debug.Log("Tuned model transferred.");
}
```

See [GeminiTunedModelTransferOwnershipRequest](#) for more details.

Files (Beta API)

The Gemini File API can be used to store data on the cloud for future prompting with the Gemini models.

Delete

Deletes the File.

```
using Uralstech.UGemini;
using Uralstech.UGemini.FileAPI;

private async void RunDeleteFileRequest(string fileId)
{
    Debug.Log("Deleting file...");
    await GeminiManager.Instance.Request(new GeminiFileDeleteRequest(fileId));
    Debug.Log("File deleted.");
}
```

See [GeminiFileDeleteRequest](#) for more details.

Get

Gets the metadata for the given File.

```

using Uralstech.UGemini;
using Uralstech.UGemini.FileAPI;

private async Task<GeminiFile> RunGetFileRequest(string fileId)
{
    return await GeminiManager.Instance.Request<GeminiFile>
(new GeminiFileGetRequest(fileId));
}

```

See [GeminiFile](#) and [GeminiFileGetRequest](#) for more details.

List

Lists the metadata for Files owned by the requesting project.

```

using Uralstech.UGemini;
using Uralstech.UGemini.FileAPI;

private async Task<GeminiFile[]> RunListFilesRequest(int maxFiles = 10, string pageToken
= null)
{
    GeminiFileListResponse response = await
GeminiManager.Instance.Request<GeminiFileListResponse>(new GeminiFileListRequest()
{
    MaxResponseFiles = maxFiles,
    PageToken = string.IsNullOrEmpty(pageToken) ? string.Empty : pageToken,
});

    return response?.Files;
}

```

See [GeminiFileListResponse](#) and [GeminiFileListRequest](#) for more details.

Media (Beta API)

The Gemini File API can be used to store data on the cloud for future prompting with the Gemini models.

Upload

Creates a File.

```

using Uralstech.UGemini;
using Uralstech.UGemini.FileAPI;

private async Task<GeminiFile> RunUploadFileRequest(string text)
{
    GeminiFileUploadResponse response = await
GeminiManager.Instance.Request<GeminiFileUploadResponse>(new
GeminiFileUploadRequest(GeminiContentType.TextPlain.MimeType())
    {
        File = new GeminiFileUploadMetaData()
        {
            DisplayName = "I'm a File",
        },
        RawData = Encoding.UTF8.GetBytes(text)
    });

    return response.File;
}

```

See [GeminiFileUploadResponse](#) and [GeminiFileUploadRequest](#) for more details.

Operations Endpoints

The operations endpoint allows you to view the status of long-running processes.

This functionality is not part of UGemini, but its sister plugin [UCloud.Operations](#)[↗]. More general documentation about UCloud.Operations can be found [here](#)[↗]

UCloud.Operations uses OAuth authorization to access and edit running operations. The following permissions may or may not be required depending on the type of operations that you access or edit in the Gemini API:

- <https://www.googleapis.com/auth/generative-language.tuning>
- <https://www.googleapis.com/auth/cloud-platform>

List

Lists all long-running operations in the Gemini API.

```

using Uralstech.UCloud.Operations;
using Uralstech.UGemini;

```

```
private async void RunOperationsListRequest(string oauthAccessToken)
{
    Debug.Log("Listing all operations.");

    OperationsListResponse response = await
    OperationsManager.Instance.Request<OperationsListResponse>(oauthAccessToken,
        new OperationsListRequest()
        {
            BaseServiceUri = GeminiManager.ProductionApiUri,
        });

    Debug.Log($"All operations: {JsonConvert.SerializeObject(response)}");
}
```

TunedModels.Operations.Cancel

Cancels a long-running tuned model creation operation in the Gemini API.

```
using Uralstech.UCloud.Operations;
using Uralstech.UGemini;

private async void RunTunedModelOperationsCancelRequest(string oauthAccessToken,
string operationResourceName)
{
    Debug.Log("Cancelling tuned model operation.");

    await OperationsManager.Instance.Request(oauthAccessToken,
        new OperationCancelRequest(operationResourceName)
        {
            BaseServiceUri = GeminiManager.ProductionApiUri
        });

    Debug.Log("Tuned model operation cancelled.");
}
```

TunedModels.Operations.Get

Gets a long-running tuned model creation operation in the Gemini API.

```
using Uralstech.UCloud.Operations;
using Uralstech.UGemini;
using Uralstech.UGemini.Models.Tuning;
```

```

private async void RunTunedModelOperationsGetRequest(string oauthAccessToken,
string operationResourceName)
{
    Debug.Log("Getting tuned model operation.");

    GeminiTunedModelCreateResponse response = await
OperationsManager.Instance.Request<GeminiTunedModelCreateResponse>(oauthAccessToken,
    new OperationGetRequest(operationResourceName)
    {
        BaseServiceUri = GeminiManager.ProductionApiUri
    });

    Debug.Log($"Got tuned model operation: {JsonConvert.SerializeObject(response)}");
}

```

TunedModels.Operations.List

Lists all long-running operations of the specified tuned model in the Gemini API.

```

using Uralstech.UCloud.Operations;
using Uralstech.UCloud.Operations.Generic;
using Uralstech.UGemini;
using Uralstech.UGemini.Models;
using Uralstech.UGemini.Models.Tuning;

private async void RunTunedModelOperationsListRequest(string oauthAccessToken,
GeminiModelId model)
{
    Debug.Log($"Listing all operations of tuned model: {model.Name}");

    OperationsListResponse<GeminiTunedModelCreateResponse> response = await
OperationsManager.Instance.Request<OperationsListResponse<GeminiTunedModelCreateResponse>>
(oauthAccessToken,
    new OperationsListRequest()
    {
        BaseServiceUri = $"{GeminiManager.ProductionApiUri}/{model.Name}",
    });

    Debug.Log($"All operations of model \"{model.Name}\":
{JsonConvert.SerializeObject(response)}");
}

```


Breaking Changes Notice

UGemini v2.0.0 contains many breaking changes. For breaking changes in newer versions, check the release's changelogs at <https://github.com/Uralstech/UGemini/releases>. To update your code to use UGemini 2.0.0, refer to the following list and table of changes:

General Changes

- `EnumExtensions` is now `GeminiContentTypeExtensions`.
- `GeminiTimeSpanJsonConverter` is now `GeminiSecondsToTimeSpanJsonConverter` in `Uralstech.UGemini`.
- The `fileId` field in the constructors for `GeminiFileDeleteRequest` and `GeminiFileGetRequest` has been renamed to `fileNameOrId`.
- All code previously marked as "deprecated" has been removed.

Namespace Changes

Class	Old Namespace	New Namespace
<code>GeminiContent</code>	<code>Uralstech.UGemini</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiContentBlob</code>	<code>Uralstech.UGemini</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiContentPart</code>	<code>Uralstech.UGemini</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiFileData</code>	<code>Uralstech.UGemini</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiRole</code>	<code>Uralstech.UGemini</code>	<code>Uralstech.UGemini.Mode</code>
<code>UnityExtensions</code>	<code>Uralstech.UGemini</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiAttributionSourceId</code>	<code>Uralstech.UGemini.Chat</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiGroundingAttribution</code>	<code>Uralstech.UGemini.Chat</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiGroundingPassageId</code>	<code>Uralstech.UGemini.Chat</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiSemanticRetrieverChunk</code>	<code>Uralstech.UGemini.Chat</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiCitationMetadata</code>	<code>Uralstech.UGemini.Chat</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiCitationSource</code>	<code>Uralstech.UGemini.Chat</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiTokenCountRequest</code>	<code>Uralstech.UGemini.TokenCounting</code>	<code>Uralstech.UGemini.Mode</code>
<code>GeminiTokenCountResponse</code>	<code>Uralstech.UGemini.TokenCounting</code>	<code>Uralstech.UGemini.Mode</code>

Class	Old Namespace	New Namespace
GeminiBatchEmbedContentRequest	Uralstech.UGemini.Embedding	Uralstech.UGemini.Mode
GeminiBatchEmbedContentResponse	Uralstech.UGemini.Embedding	Uralstech.UGemini.Mode
GeminiContentEmbedding	Uralstech.UGemini.Embedding	Uralstech.UGemini.Mode
GeminiEmbedContentRequest	Uralstech.UGemini.Embedding	Uralstech.UGemini.Mode
GeminiEmbedContentResponse	Uralstech.UGemini.Embedding	Uralstech.UGemini.Mode
GeminiEmbedTaskType	Uralstech.UGemini.Embedding	Uralstech.UGemini.Mode
GeminiGenerationConfiguration	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiResponseType	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiCandidate	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiPromptFeedback	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiUsageMetadata	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiFinishReason	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiChatRequest	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiChatResponse	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiAnswerRequest	Uralstech.UGemini.Answer	Uralstech.UGemini.Mode
GeminiAnswerResponse	Uralstech.UGemini.Answer	Uralstech.UGemini.Mode
GeminiAnswerStyle	Uralstech.UGemini.Answer	Uralstech.UGemini.Mode
GeminiGroundingPassage	Uralstech.UGemini.Answer	Uralstech.UGemini.Mode
GeminiGroundingPassages	Uralstech.UGemini.Answer	Uralstech.UGemini.Mode
GeminiMetadataCondition	Uralstech.UGemini.Answer	Uralstech.UGemini.Mode
GeminiMetadataFilter	Uralstech.UGemini.Answer	Uralstech.UGemini.Mode
GeminiSemanticRetrieverConfig	Uralstech.UGemini.Answer	Uralstech.UGemini.Mode

Class	Old Namespace	New Namespace
GeminiMetadataConditionOperator	Uralstech.UGemini.Answer	Uralstech.UGemini.Mode
GeminiSafetyRating	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiSafetySettings	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiBlockReason	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiHarmProbability	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiSafetyHarmBlockThreshold	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiSafetyHarmCategory	Uralstech.UGemini.Chat	Uralstech.UGemini.Mode
GeminiSchema	Uralstech.UGemini.Schema	Uralstech.UGemini.Mode
GeminiSchemaDataFormat	Uralstech.UGemini.Schema	Uralstech.UGemini.Mode
GeminiSchemaDataType	Uralstech.UGemini.Schema	Uralstech.UGemini.Mode
GeminiFunctionCall	Uralstech.UGemini.Tools	Uralstech.UGemini.Mode
GeminiFunctionResponse	Uralstech.UGemini.Tools	Uralstech.UGemini.Mode
GeminiFunctionResponseContent	Uralstech.UGemini.Tools	Uralstech.UGemini.Mode
GeminiFunctionCallingConfiguration	Uralstech.UGemini.Tools.Declaration	Uralstech.UGemini.Mode
GeminiFunctionDeclaration	Uralstech.UGemini.Tools.Declaration	Uralstech.UGemini.Mode
GeminiTool	Uralstech.UGemini.Tools.Declaration	Uralstech.UGemini.Mode
GeminiToolConfiguration	Uralstech.UGemini.Tools.Declaration	Uralstech.UGemini.Mode
GeminiFunctionCallingMode	Uralstech.UGemini.Tools.Declaration	Uralstech.UGemini.Mode