

Table of Contents

- Uralstech.UShare 2
 - AdditionalShareData 3
 - AndroidPathHelper 6
 - CommonMimeTypes 9
 - IOSNativeCalls 14
 - IOSNativeCalls.ShareFileCallback 19
 - ShareSheetManager 20
- Uralstech.UShare.Editor 33
 - AndroidConfigurator 34
 - IOSConfigurator 36
 - PathUtils 37
 - UShareBuildSettings 39
 - UShareSettingsProvider 42

Namespace Uralstech.UShare

Classes

[AndroidPathHelper](#)

Path utilities for Android.

[CommonMimeTypes](#)

Contains constants for common MIME types used in sharing data.

[IOSNativeCalls](#)

An interface for the native iOS plugin.

[ShareSheetManager](#)

Class to handle the share sheet functionality.

Structs

[AdditionalShareData](#)

Additional data regarding a share event.

Delegates

[IOSNativeCalls.ShareFileCallback](#)

Called when UIActivityViewController has completed its work.

Struct AdditionalShareData

Namespace: [Uralstech.UShare](#)

Additional data regarding a share event.

```
public struct AdditionalShareData
```

Fields

AdditionalText

Additional text to be shared along with the main content.

```
public string? AdditionalText
```

Field Value

string

Remarks

You can usually get away with having text in shared content along with other data **without** having to declare it in the MIME type you provide for the request. For example, most apps will accept "image/png" share requests with additional text, but WhatsApp will send each image as individual messages with the text attached to *every* message.

AndroidFileProviderAuthority

(Android) Override the FileProvider authority for the file(s) being shared.

```
public string? AndroidFileProviderAuthority
```

Field Value

string

BasePath

Override the path to the directory containing the file(s) to share.

```
public string? BasePath
```

Field Value

string

KeepDataAfterFocusRegain

Whether to keep the file(s) after the user regains focus on the app after sharing. This only applies to share events where you provide the raw data to be shared, like with [ShareData\(string, string, byte\[\], AdditionalShareData\)](#), and not for cases where the data is already present in the app's storage.

```
public bool KeepDataAfterFocusRegain
```

Field Value

bool

Remarks

By default, the data is deleted from the app's storage when the user regains focus on the app after sharing to prevent the share directory from getting too big.

Title

Optional title for the share sheet (Android 10+, but not guaranteed to work when sharing non-text media).

```
public string? Title
```

Field Value

string

Class AndroidPathHelper

Namespace: [Uralstech.UShare](#)

Path utilities for Android.

```
public class AndroidPathHelper
```

Inheritance

object ← AndroidPathHelper

Constructors

AndroidPathHelper(AndroidJavaObject?)

```
protected AndroidPathHelper(AndroidJavaObject? pluginInstance)
```

Parameters

pluginInstance AndroidJavaObject?

The native plugin instance.

Properties

CacheDirectory

Returns the path to the application's assigned cache directory (context.cacheDir).

```
public string CacheDirectory { get; }
```

Property Value

string

ExternalCacheDirectory

Returns the path to the application's assigned external cache directory (context.externalCacheDir).

```
public String? ExternalCacheDirectory { get; }
```

Property Value

string

ExternalFilesDirectory

Returns the path to the application's assigned external files directory (from context.getExternalFilesDir).

```
public String? ExternalFilesDirectory { get; }
```

Property Value

string

FilesDirectory

Returns the path to the application's assigned files directory (context.filesDir).

```
public String FilesDirectory { get; }
```

Property Value

string

PluginInstance

The native plugin instance.

```
protected AndroidJavaObject? PluginInstance { get; }
```

Property Value

AndroidJavaObject?

Methods

Invalidate()

Invalidates this instance by setting [PluginInstance](#) to [null](#)[↗]. It is the responsibility of the creator of this object to dispose of [PluginInstance](#).

```
protected void Invalidate()
```

Class CommonMimeType

Namespace: [Uralstech.UShare](#)

Contains constants for common MIME types used in sharing data.

```
public static class CommonMimeType
```

Inheritance

object ← CommonMimeType

Fields

ApplicationPdf

PDF files.

```
public const string ApplicationPdf = "application/pdf"
```

Field Value

string

ImageGif

GIF images/videos.

```
public const string ImageGif = "image/gif"
```

Field Value

string

ImageJpg

JPG/JPEG images.

```
public const string ImageJpg = "image/jpg"
```

Field Value

string

ImageMultitype

Use this when sharing images of multiple types.

```
public const string ImageMultitype = "image/*"
```

Field Value

string

ImagePng

PNG images.

```
public const string ImagePng = "image/png"
```

Field Value

string

Multitype

Use this when sharing data of multiple unrelated types.

```
public const string Multitype = "*/*"
```

Field Value

string

TextHtml

HTML files.

```
public const string TextHtml = "text/html"
```

Field Value

string

TextJson

JSON files.

```
public const string TextJson = "text/json"
```

Field Value

string

TextMultitype

Use this when sharing text of multiple types.

```
public const string TextMultitype = "text/*"
```

Field Value

string

TextPlain

Plain text.

```
public const string TextPlain = "text/plain"
```

Field Value

string

TextRtf

RTF files.

```
public const string TextRtf = "text/rtf"
```

Field Value

string

Video3gp

3GP videos.

```
public const string Video3gp = "video/3gp"
```

Field Value

string

VideoMp4

MP4 videos.

```
public const string VideoMp4 = "video/mp4"
```

Field Value

string

VideoMultitype

Use this when sharing videos of multiple types.

```
public const string VideoMultitype = "video/*"
```

Field Value

string

Class IOSNativeCalls

Namespace: [Uralstech.UShare](#)

An interface for the native iOS plugin.

```
public static class IOSNativeCalls
```

Inheritance

object ← IOSNativeCalls

Methods

ushare_interface_share_file(long, string, string?, string?, Share FileCallback)

Shares a file using iOS's UIActivityViewController.

```
public static extern bool ushare_interface_share_file(long timestamp, string filePath, string? additionalText, string? title, IOSNativeCalls.ShareFileCallback callback)
```

Parameters

timestamp long

The timestamp of the request.

filePath string

The path of the file to share.

additionalText string

Optional text to share along with the image.

title string

An optional title for the share sheet.

callback [IOSNativeCalls.ShareFileCallback](#)

Called when UIActivityViewController has completed its work.

Returns

bool

If the share request was executed successfully.

ushare_interface_share_files(long, nint[], int, string?, string?, ShareFileCallback)

Shares multiple files using iOS's UIActivityViewController.

```
public static extern bool ushare_interface_share_files(long timestamp, nint[] filePathPtrs,
int count, string? additionalText, string? title, IOSNativeCalls.ShareFileCallback callback)
```

Parameters

timestamp long

The timestamp of the request.

filePathPtrs nint[]

The pointers to the paths of the files to share.

count int

The total number of files to share.

additionalText string

Optional text to share along with the image.

title string

An optional title for the share sheet.

callback [IOSNativeCalls.ShareFileCallback](#)

Called when UIActivityViewController has completed its work.

Returns

bool

If the share request was executed successfully.

ushare_interface_share_image(nint, int, string?, string?)

Shares an image using iOS's UIActivityViewController.

```
public static extern bool ushare_interface_share_image(nint imagePtr, int size, string? additionalText, string? title)
```

Parameters

imagePtr nint

A pointer to the image's data.

size int

The size of the image in bytes.

additionalText string

Optional text to share along with the image.

title string

An optional title for the share sheet.

Returns

bool

If the share request was executed successfully.

ushare_interface_share_images(nint[], int[], int, string?, string?)

Shares multiple images using iOS's UIActivityViewController.

```
public static extern bool ushare_interface_share_images(nint[] imagePtrs, int[] sizes, int count, string? additionalText, string? title)
```

Parameters

imagePtrs `nint[]`

An array of pointers to each image's data.

sizes `int[]`

An array of the sizes of each image's data in bytes.

count `int`

The total number of images to be shared.

additionalText `string`

Optional text to share along with the images.

title `string`

An optional title for the share sheet.

Returns

`bool`

If the share request was executed successfully.

`ushare_interface_share_text(string, string?)`

Shares text data using iOS's `UIActivityViewController`.

```
public static extern bool ushare_interface_share_text(string text, string? title)
```

Parameters

text `string`

The text to share.

title `string`

An optional title for the share sheet.

Returns

bool

If the share request was executed successfully.

Delegate IOSNativeCalls.ShareFileCallback

Namespace: [Uralstech.UShare](#)

Called when UIActivityViewController has completed its work.

```
public delegate void IOSNativeCalls.ShareFileCallback(long timestamp)
```

Parameters

timestamp long

The timestamp of the original request.

Class ShareSheetManager

Namespace: [Uralstech.UShare](#)

Class to handle the share sheet functionality.

```
public class ShareSheetManager : Singleton<ShareSheetManager>
```

Inheritance

object ← ShareSheetManager

Fields

AndroidFileProviderAuthority

The Android FileProvider URI authority the application has set in its manifest to use for share actions. If not provided, defaults to "{Application.identifier}.FileProvider".

```
public string AndroidFileProviderAuthority
```

Field Value

string

AndroidNativeClass

The fully qualified name of the native Android plugin class.

```
protected const string AndroidNativeClass = "com.uralstech.ushare.ShareHelper"
```

Field Value

string

DefaultFileProviderAuthorityFormat

Default format for the Android FileProvider URI authority.

```
protected const string DefaultFileProviderAuthorityFormat = "{0}.FileProvider"
```

Field Value

string

DefaultSaveSubDirectory

The default directory used to temporarily save data that is shared.

```
protected const string DefaultSaveSubDirectory = "ShareCache"
```

Field Value

string

_filesScheduledForDeletion

List of files scheduled for deletion after a share action has been completed.

```
protected readonly List<(long, string)> _filesScheduledForDeletion
```

Field Value

List<(long, string)>

_persistBetweenScenes

Should this object persist between scenes?

```
protected bool _persistBetweenScenes
```

Field Value

bool

_pluginInstance

(Android) The native plugin instance.

```
protected AndroidJavaObject? _pluginInstance
```

Field Value

AndroidJavaObject?

Properties

AndroidPathHelper

(Android) Utility object for Android which provides paths to where shareable data can be saved.

```
public AndroidPathHelper AndroidPathHelper { get; protected set; }
```

Property Value

[AndroidPathHelper](#)

Methods

Awake()

```
protected void Awake()
```

DeleteScheduledFiles(long, bool)

Deletes files from [_filesScheduledForDeletion](#) that match the given timestamp, unless overridden using `deleteAll`.

```
protected void DeleteScheduledFiles(long timestamp, bool deleteAll = false)
```

Parameters

timestamp long

The timestamp to match for in [_filesScheduledForDeletion](#).

deleteAll bool

Set this to true to override the timestamp check.

GetDefaultBasePath()

Gets the default shareable directory as defined in the native plugin.

```
public string GetDefaultBasePath()
```

Returns

string

GetShareableFileUri(string, string?, string?)

(Android) Gets a shareable URI for a file **located in a shareable directory** in the app's storage.

```
public AndroidJavaObject? GetShareableFileUri(string fileName, string? basePath = null, string? fileProviderAuthority = null)
```

Parameters

fileName string

The name of the file.

basePath string

The path to the file. If not given, it will expect the file in a subdirectory named "ShareCache" under the app's cache directory.

fileProviderAuthority string

The FileProvider authority for the file being shared.

Returns

AndroidJavaObject?

The native Android URI object or [null](#) if it could not create the URI.

OnApplicationFocus(bool)

```
protected void OnApplicationFocus(bool focus)
```

Parameters

focus bool

OnDestroy()

```
protected void OnDestroy()
```

ShareData(string, string, byte[], AdditionalShareData)

Shares data as a file URI to other apps using the system share sheet.

```
public bool ShareData(string contentType, string fileName, byte[] data, AdditionalShareData  
additionalData = default)
```

Parameters

contentType string

The MIME type of the content to share. See [CommonMimeType](#)s for common MIME types.

fileName string

The file name of the content to share (eg. "image.png").

data byte[]

The data to share.

additionalData [AdditionalShareData](#)

Additional data for the event.

Returns

bool

True if successful, false otherwise.

Remarks

On iOS, for images, the data is marshalled directly into the native code without any IO operations.

This method writes the data to a file in a folder that is accessible by other apps, and then shares its location as a URI. By default, this location is in the app's cache directory under a subdirectory named "ShareCache". When the user regains focus on the app after sharing, the file will be deleted to prevent the cache directory from growing too large. These settings can be overridden by setting the [AdditionalShareData](#) parameter.

ShareData(string, (string FileName, byte[] Data)[], AdditionalShareData)

Shares data as multiple file URIs to other apps using the system share sheet.

```
public bool ShareData(string contentType, (string FileName, byte[] Data)[] files,
    AdditionalShareData additionalData = default)
```

Parameters

contentType string

The MIME type of the content to share. See [CommonMimeType](#)s for common MIME types.

files (string FileName, byte[] Data)[]

An array of tuples containing file names and their corresponding data to share.

additionalData [AdditionalShareData](#)

Additional data for the event.

Returns

bool

True if successful, false otherwise.

Remarks

On iOS, for image-only requests, the data is marshalled directly into the native code without any IO operations.

This method writes the data to files in a folder that is accessible by other apps, and then shares its location as a URI. By default, this location is in the app's cache directory under a subdirectory named "ShareCache". When the user regains focus on the app after sharing, the file will be deleted to prevent the cache directory from growing too large. These settings can be overridden by setting the [AdditionalShareData](#) parameter.

ShareFile(string, string, AdditionalShareData)

Shares a file as a URI to other apps using the system share sheet.

```
public bool ShareFile(string contentType, string fileName, AdditionalShareData
additionalData = default)
```

Parameters

contentType string

The MIME type of the content to share. See [CommonMimeType](#)s for common MIME types.

fileName string

The name of the file to share.

additionalData [AdditionalShareData](#)

Additional data for the event.

Returns

bool

True if successful, false otherwise.

Remarks

By default, the file is expected to be in the app's cache directory under a subdirectory named "ShareCache". This can be overridden by setting the [AdditionalShareData](#) parameter.

ShareFileCallback(long)

Default implementation of [IOSNativeCalls.ShareFileCallback](#).

```
protected static void ShareFileCallback(long timestamp)
```

Parameters

timestamp long

The timestamp of the original request.

ShareFileImpl(long, string, string, AdditionalShareData)

Shares a file as a URI to other apps using the system share sheet.

```
protected bool ShareFileImpl(long timestamp, string contentType, string fileName,
    AdditionalShareData additionalData)
```

Parameters

timestamp long

Timestamp to be passed into the native iOS plugin.

contentType string

The MIME type of the content to share. See [CommonMimeType](#)s for common MIME types.

fileName string

The name of the file to share.

additionalData [AdditionalShareData](#)

Additional data for the event.

Returns

bool

True if successful, false otherwise.

Remarks

By default, the file is expected to be in the app's cache directory under a subdirectory named "ShareCache". This can be overridden by setting the [AdditionalShareData](#) parameter.

ShareFiles(string, string[], AdditionalShareData)

Shares multiple files as URIs to other apps using the system share sheet.

```
public bool ShareFiles(string contentType, string[] fileNames, AdditionalShareData
additionalData = default)
```

Parameters

contentType string

The MIME type of the content to share. See [CommonMimeType](#)s for common MIME types.

fileNames string[]

The names of the files to share.

additionalData [AdditionalShareData](#)

Additional data for the event.

Returns

bool

True if successful, false otherwise.

Remarks

By default, the files are expected to be in the app's cache directory under a subdirectory named "ShareCache". This can be overridden by setting the [AdditionalShareData](#) parameter.

If you want to share files that are present in different directories, you will have to get the shareable URIs for those files individually using (Android) [GetShareableFileUri\(string, string?, string?\)](#) and then share them using (Android) [ShareUri\(string, AndroidJavaObject\[\], string?, string?\)](#) method.

ShareFilesImpl(long, string, string[], AdditionalShareData)

Shares multiple files as URIs to other apps using the system share sheet.

```
protected bool ShareFilesImpl(long timestamp, string contentType, string[] fileNames,
    AdditionalShareData additionalData)
```

Parameters

timestamp long

Timestamp to be passed into the native iOS plugin.

contentType string

The MIME type of the content to share. See [CommonMimeTypes](#) for common MIME types.

fileNames string[]

The names of the files to share.

additionalData [AdditionalShareData](#)

Additional data for the event.

Returns

bool

True if successful, false otherwise.

Remarks

By default, the files are expected to be in the app's cache directory under a subdirectory named "ShareCache". This can be overridden by setting the [AdditionalShareData](#) parameter.

If you want to share files that are present in different directories, you will have to get the shareable URIs for those files individually using (Android) [GetShareableFileUri\(string, string?, string?\)](#) and then share them using (Android) [ShareUri\(string, AndroidJavaObject\[\], string?, string?\)](#) method.

ShareImageImpl(byte[], AdditionalShareData)

(iOS) Shares an image to other apps using the system share sheet.

```
protected bool ShareImageImpl(byte[] data, AdditionalShareData additionalData)
```

Parameters

data byte[]

The image to share.

additionalData [AdditionalShareData](#)

Additional data for the event.

Returns

bool

True if successful, false otherwise.

ShareImagesImpl((string, byte[] Data)[], AdditionalShareData)

(iOS) Shares images to other apps using the system share sheet.

```
protected bool ShareImagesImpl((string, byte[] Data)[] files, AdditionalShareData additionalData)
```

Parameters

files (string FileName, byte[] Data)[]

An array of tuples containing file names (ignored) and their corresponding data to share.

additionalData [AdditionalShareData](#)

Additional data for the event.

Returns

bool

True if successful, false otherwise.

ShareText(string, string?)

Shares text to other apps using the system share sheet.

```
public bool ShareText(string text, string? title = null)
```

Parameters

text string

The text to share.

title string

Optional title for the share sheet (Android 10+).

Returns

bool

If the share request was executed successfully.

ShareUri(string, AndroidJavaObject[], string?, string?)

(Android) Shares URIs, which point to files, to other apps using the system share sheet.

```
public void ShareUri(string contentType, AndroidJavaObject[] uris, string? textContent = null, string? title = null)
```

Parameters

contentType string

The MIME type of the content to share. See [CommonMimeTypes](#) for common MIME types.

uris AndroidJavaObject[]

The native file URI objects to share.

textContent string

Additional text to be shared along with the main content.

title string

Optional title for the share sheet (Android 10+, but not guaranteed to work when sharing non-text media).

Namespace Uralstech.UShare.Editor

Classes

[AndroidConfigurator](#)

Android project configurator for UShare.

[IOSConfigurator](#)

iOS project configurator for UShare.

[PathUtils](#)

Path utilities for editor scripts.

[UShareBuildSettings](#)

Project-wide settings for UShare.

[UShareSettingsProvider](#)

Project settings extension for UShare's project-wide settings.

Class AndroidConfigurator

Namespace: [Uralstech.UShare.Editor](#)

Android project configurator for UShare.

```
public class AndroidConfigurator : IPreprocessBuildWithReport
```

Inheritance

object ← AndroidConfigurator

Fields

DefaultAndroidManifestPath

```
public const string DefaultAndroidManifestPath = "Editor/Android/DefaultAndroidManifest.xml"
```

Field Value

string

DefaultFilePathsXmlPath

```
public const string DefaultFilePathsXmlPath = "Editor/Android/DefaultFileProviderPaths.xml"
```

Field Value

string

PatchFilePathsXmlPath

```
public const string PatchFilePathsXmlPath =  
"Runtime/Plugins/Android/com.uralstech.ushare.patch.androidlib/res/xml/file_provider_paths.x  
ml"
```

Field Value

string

PatchManifestPath

```
public const string PatchManifestPath =  
    "Runtime/Plugins/Android/com.uralstech.ushare.patch.androidlib/AndroidManifest.xml"
```

Field Value

string

Properties

callbackOrder

```
public int callbackOrder { get; }
```

Property Value

int

Methods

OnPreprocessBuild(BuildReport)

```
public void OnPreprocessBuild(BuildReport report)
```

Parameters

report BuildReport

Class IOSConfigurator

Namespace: [Uralstech.UShare.Editor](#)

iOS project configurator for UShare.

```
public class IOSConfigurator : IPostprocessBuildWithReport
```

Inheritance

object ← IOSConfigurator

Properties

callbackOrder

```
public int callbackOrder { get; }
```

Property Value

int

Methods

OnPostprocessBuild(BuildReport)

```
public void OnPostprocessBuild(BuildReport report)
```

Parameters

report BuildReport

Class PathUtils

Namespace: [Uralstech.UShare.Editor](#)

Path utilities for editor scripts.

```
public static class PathUtils
```

Inheritance

object ← PathUtils

Fields

PackageId

The package ID of the UShare package.

```
public const string PackageId = "com.uralstech.ushare"
```

Field Value

string

Methods

GetPackagePath()

Gets the path to the UShare package folder.

```
public static string? GetPackagePath()
```

Returns

string

The path if found.

ValidateFilePath(string)

Validates a path and logs an error if it doesn't exist.

```
public static bool ValidateFilePath(string path)
```

Parameters

path string

The path to validate.

Returns

bool

The validity of the path.

Class UShareBuildSettings

Namespace: [Uralstech.UShare.Editor](#)

Project-wide settings for UShare.

```
[Serializable]  
public class UShareBuildSettings
```

Inheritance

object ← UShareBuildSettings

Fields

CustomFileProviderPathsAndroid

Custom shareable directories for Android's FileProvider. See ["Specify shareable directories"](#) .

```
public string CustomFileProviderPathsAndroid
```

Field Value

string

PatchInfoPlistIOS

Should the exported iOS XCode project's Info.plist file be patched by the editor script?

```
public bool PatchInfoPlistIOS
```

Field Value

bool

PhotoLibraryAdditionsUsageDescriptionIOS

Usage description for sharing data to the user's gallery on iOS.

```
public string PhotoLibraryAdditionsUsageDescriptionIOS
```

Field Value

string

SavePath

Save path for project-wide UShare settings.

```
public const string SavePath = "ProjectSettings/UShareSettings.json"
```

Field Value

string

UseDefaultSettingsAndroid

Use default UShare settings for Android?

```
public bool UseDefaultSettingsAndroid
```

Field Value

bool

Methods

Get()

Gets/creates an instance of [UShareBuildSettings](#) from the Unity ProjectSettings folder.

```
public static UShareBuildSettings Get()
```

Returns

[UShareBuildSettings](#)

Save(UShareBuildSettings)

Saves the settings to the Unity ProjectSettings folder.

```
public static void Save(UShareBuildSettings settings)
```

Parameters

settings [UShareBuildSettings](#)

The settings to save.

Class UShareSettingsProvider

Namespace: [Uralstech.UShare.Editor](#)

Project settings extension for UShare's project-wide settings.

```
public static class UShareSettingsProvider
```

Inheritance

object ← UShareSettingsProvider