

Table of Contents

- Uralstech.UShare 2
 - AdditionalShareData 3
 - AndroidPathHelper 6
 - CommonMimeTypes 9
 - ShareOptions 14
 - ShareSheetManager 16
 - ShareSheetManagerV2 21
 - ShareSheetManagerV2.EventStatus 36
- Uralstech.UShare.Native 38
 - AndroidInterop 39
 - AndroidInterop.Callbacks 45
 - IOSInterop 47
 - IOSInterop.ActivityFinishedCallback 51

Namespace Uralstech.UShare

Classes

[AndroidPathHelper](#)

Utility for providing commonly used Android base paths like `cacheDir`, `filesDir`, etc.

[CommonMimeTypes](#)

Contains constants for common MIME types used in sharing data.

[ShareOptions](#)

Additional data for a share event.

[ShareSheetManager](#)

[ShareSheetManagerV2](#)

Manages the native share sheet plugins.

[ShareSheetManagerV2.EventStatus](#)

Result for QOL share methods that may generate temporary files.

Structs

[AdditionalShareData](#)

Additional data for a share event.

Struct AdditionalShareData

Namespace: [Uralstech.UShare](#)

Additional data for a share event.

```
[Obsolete("Use ShareSheetManagerV2 with ShareOptions instead.")]  
public struct AdditionalShareData
```

Fields

AdditionalText

Additional text to be shared along with the main content.

```
public string? AdditionalText
```

Field Value

string

Remarks

You can usually get away with having text in shared content along with other data **without** having to declare it in the MIME type you provide for the request. For example, most apps will accept "image/png" share requests with additional text, but WhatsApp will send each image as individual messages with the text attached to every message.

AndroidFileProviderAuthority

Overrides the Android FileProvider authority for the file(s) being shared.

```
public string? AndroidFileProviderAuthority
```

Field Value

string

BasePath

Overrides the path to the directory containing the file(s) to share.

```
public string? BasePath
```

Field Value

string

KeepDataAfterFocusRegain

```
[Obsolete("Data retention after share events is now mandatory. Deleting data when  
the source app regains focus can cause target applications to lose access to the  
shared content, particularly in windowed environments where focus returns  
immediately.", true)]  
public bool KeepDataAfterFocusRegain
```

Field Value

bool

Title

Optional title for the share sheet.

```
public string? Title
```

Field Value

string

Remarks

For Android:

Requires Android 10+ and is not guaranteed to work when sharing non-text media

Class AndroidPathHelper

Namespace: [Uralstech.UShare](#)

Utility for providing commonly used Android base paths like `cacheDir`, `filesDir`, etc.

```
public sealed class AndroidPathHelper
```

Inheritance

object ← AndroidPathHelper

Properties

CacheDirectory

The application's cache directory (`context.cacheDir`).

```
public string CacheDirectory { get; }
```

Property Value

string

Exceptions

PlatformNotSupportedException

Thrown if this property is accessed on a runtime other than Android.

ExternalCacheDirectory

The application's external cache directory (`context.externalCacheDir`).

```
public string? ExternalCacheDirectory { get; }
```

Property Value

string

Exceptions

PlatformNotSupportedException

Thrown if this property is accessed on a runtime other than Android.

ExternalFilesDirectory

The application's external directory for persistent files (from context.getExternalFilesDir).

```
public string? ExternalFilesDirectory { get; }
```

Property Value

string

Exceptions

PlatformNotSupportedException

Thrown if this property is accessed on a runtime other than Android.

FilesDirectory

The application's directory for persistent files (context.filesDir).

```
public string FilesDirectory { get; }
```

Property Value

string

Exceptions

PlatformNotSupportedException

Thrown if this property is accessed on a runtime other than Android.

Methods

GetExternalFilesDirectory(string?)

Gets the application's external directory for persistent files (from context.getExternalFilesDir).

```
public static string? GetExternalFilesDirectory(string? type = null)
```

Parameters

type string

Returns

string

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android.

Class CommonMimeType

Namespace: [Uralstech.UShare](#)

Contains constants for common MIME types used in sharing data.

```
public static class CommonMimeType
```

Inheritance

object ← CommonMimeType

Fields

ApplicationPdf

PDF files.

```
public const string ApplicationPdf = "application/pdf"
```

Field Value

string

ImageGif

GIF images/videos.

```
public const string ImageGif = "image/gif"
```

Field Value

string

ImageJpg

JPG/JPEG images.

```
public const string ImageJpg = "image/jpg"
```

Field Value

string

ImageMultitype

Use this when sharing images of multiple types.

```
public const string ImageMultitype = "image/*"
```

Field Value

string

ImagePng

PNG images.

```
public const string ImagePng = "image/png"
```

Field Value

string

Multitype

Use this when sharing data of multiple unrelated types.

```
public const string Multitype = "*/*"
```

Field Value

string

TextHtml

HTML files.

```
public const string TextHtml = "text/html"
```

Field Value

string

TextJson

JSON files.

```
public const string TextJson = "text/json"
```

Field Value

string

TextMultitype

Use this when sharing text of multiple types.

```
public const string TextMultitype = "text/*"
```

Field Value

string

TextPlain

Plain text.

```
public const string TextPlain = "text/plain"
```

Field Value

string

TextRtf

RTF files.

```
public const string TextRtf = "text/rtf"
```

Field Value

string

Video3gp

3GP videos.

```
public const string Video3gp = "video/3gp"
```

Field Value

string

VideoMp4

MP4 videos.

```
public const string VideoMp4 = "video/mp4"
```

Field Value

string

VideoMultitype

Use this when sharing videos of multiple types.

```
public const string VideoMultitype = "video/*"
```

Field Value

string

Class ShareOptions

Namespace: [Uralstech.UShare](#)

Additional data for a share event.

```
public sealed class ShareOptions
```

Inheritance

object ← ShareOptions

Fields

Authority

Overrides the Android FileProvider authority for the file(s) being shared.

```
public string? Authority
```

Field Value

string

Text

Additional text to be shared along with the main content.

```
public string? Text
```

Field Value

string

Remarks

You can usually get away with having text in shared content along with other data **without** having to declare it in the MIME type you provide for the request. For example, most apps

will accept "image/png" share requests with additional text, but WhatsApp will send each image as individual messages with the text attached to every message.

Title

Optional title for the share sheet.

```
public String? Title
```

Field Value

string

Remarks

Requires Android 10+ and is not guaranteed to work when sharing non-text media.

Class ShareSheetManager

Namespace: [Uralstech.UShare](#)

```
[Obsolete("Deprecated in favour of ShareSheetManagerV2. Subclassing  
ShareSheetManager is no longer supported.")]  
public sealed class ShareSheetManager : Singleton<ShareSheetManager>
```

Inheritance

object ← ShareSheetManager

Fields

AndroidFileProviderAuthority

The Android FileProvider URI authority the application has set in its manifest to use for share actions. If not provided, defaults to "{Application.identifier}.FileProvider".

```
public string AndroidFileProviderAuthority
```

Field Value

string

Properties

AndroidPathHelper

```
public AndroidPathHelper AndroidPathHelper { get; }
```

Property Value

[AndroidPathHelper](#)

Methods

GetDefaultBasePath()

```
public string GetDefaultBasePath()
```

Returns

string

See Also

[GetDefaultBasePath\(\)](#)

GetShareableFileUri(string, string?, string?)

```
public AndroidJavaObject? GetShareableFileUri(string fileName, string? basePath = null, string? fileProviderAuthority = null)
```

Parameters

fileName string

basePath string

fileProviderAuthority string

Returns

AndroidJavaObject?

ShareData(string, string, byte[], AdditionalShareData)

```
public bool ShareData(string contentType, string fileName, byte[] data, AdditionalShareData additionalData = default)
```

Parameters

`contentType` string

`fileName` string

`data` byte[]

`additionalData` [AdditionalShareData](#)

Returns

bool

ShareData(string, (string FileName, byte[] Data)[], AdditionalShareData)

```
public bool ShareData(string contentType, (string FileName, byte[] Data)[] files,
    AdditionalShareData additionalData = default)
```

Parameters

`contentType` string

`files` (string FileName, byte[] Data)[]

`additionalData` [AdditionalShareData](#)

Returns

bool

ShareFile(string, string, AdditionalShareData)

```
public bool ShareFile(string contentType, string fileName, AdditionalShareData
    additionalData = default)
```

Parameters

`contentType` string

`fileName` string

`additionalData` [AdditionalShareData](#)

Returns

bool

ShareFiles(string, string[], AdditionalShareData)

```
public bool ShareFiles(string contentType, string[] fileNames, AdditionalShareData additionalData = default)
```

Parameters

`contentType` string

`fileNames` string[]

`additionalData` [AdditionalShareData](#)

Returns

bool

ShareText(string, string?)

```
public bool ShareText(string text, string? title = null)
```

Parameters

`text` string

`title` string

Returns

bool

See Also

[TryShareText](#)(string, string)

ShareUri(string, AndroidJavaObject[], string?, string?)

```
public void ShareUri(string contentType, AndroidJavaObject[] uris, string?  
textContent = null, string? title = null)
```

Parameters

contentType string

uris AndroidJavaObject[]

textContent string

title string

Class ShareSheetManagerV2

Namespace: [Uralstech.UShare](#)

Manages the native share sheet plugins.

```
public sealed class ShareSheetManagerV2 : Singleton<ShareSheetManagerV2>
```

Inheritance

object ← ShareSheetManagerV2

Fields

FileProviderAuthority

The Android [FileProvider](#) authority used for sharing. Defaults to "{Application.identifier}.FileProvider", the provider defined by the Android UShare plugin.

```
public string? FileProviderAuthority
```

Field Value

string

Properties

AndroidPathHelper

Utility for providing commonly used Android base paths like `cacheDir`, `filesDir`, etc.

```
public AndroidPathHelper AndroidPathHelper { get; }
```

Property Value

[AndroidPathHelper](#)

OnResult

Invoked when the share activity has "completed", with its assigned event ID. This has different meanings in iOS and Android, see remarks for more info.

```
public UnityEvent<int> OnResult { get; }
```

Property Value

UnityEvent<int>

Remarks

On iOS, this is invoked after the completion or dismissal of the share event.

On Android, this is invoked only if the user has chosen a target to share to, and is **not** reliable for all targets.

See Also

[OnTargetChosen](#)

Methods

GetDefaultBasePath()

Returns the default shareable directory as defined in the native plugin.

```
public string GetDefaultBasePath()
```

Returns

string

Remarks

Files in this directory are not automatically deleted after sharing. Since this is a system cache location, cleanup is optional, but periodically clearing old files may help avoid unnecessary storage use.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

TryShareBytes(IReadOnlyList<ReadOnly>, IReadOnlyList<string>, string, ShareOptions?)

Shares multiple separate pieces of data to other apps using the system share sheet.

```
public ShareSheetManagerV2.EventStatus TryShareBytes(IReadOnlyList<NativeArray<byte>.ReadOnly> data, IReadOnlyList<string> fileNames, string contentType, ShareOptions? options = null)
```

Parameters

data IReadOnlyList<NativeArray<byte>.ReadOnly>

The data to share.

fileNames IReadOnlyList<string>

The names of the temporary files. Since these are displayed to the user, it's recommended to set human-readable descriptions of the data. Some platforms like iOS may even obfuscate files with non-standard extensions.

contentType string

The MIME type of the combined data; see [CommonMimeType](#)s for common MIME types.

options [ShareOptions](#)

Additional options for the event.

Returns

[ShareSheetManagerV2.EventStatus](#)

An [ShareSheetManagerV2.EventStatus](#) object with [Success](#) = [true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

This method creates a file for each byte array in a cache folder which can be accessed by the share sheet. The paths to these files are returned in [ShareSheetManagerV2.EventStatus](#). See [CreatedFiles](#) for more details.

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

ArgumentException

If `fileNames` is a different size to `data`.

TryShareBytes(IReadOnlyList<byte[]>, IReadOnlyList<string>, string, ShareOptions?)

Shares multiple separate pieces of data to other apps using the system share sheet.

```
public ShareSheetManagerV2.EventStatus TryShareBytes(IReadOnlyList<byte[]> data, IReadOnlyList<string> fileNames, string
contentType, ShareOptions? options = null)
```

Parameters

data IReadOnlyList<byte[]>

The data to share.

fileNames IReadOnlyList<string>

The names of the temporary files. Since these are displayed to the user, it's recommended to set human-readable descriptions of the data. Some platforms like iOS may even obfuscate files with non-standard extensions.

contentType string

The MIME type of the combined data; see [CommonMimeType](#)s for common MIME types.

options [ShareOptions](#)

Additional options for the event.

Returns

[ShareSheetManagerV2.EventStatus](#)

An [ShareSheetManagerV2.EventStatus](#) object with [Success](#) = [true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

This method creates a file for each byte array in a cache folder which can be accessed by the share sheet. The paths to these files are returned in [ShareSheetManagerV2.EventStatus](#). See [CreatedFiles](#) for more details.

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

ArgumentException

If `fileNames` is a different size to `data`.

TryShareBytes(int, IReadOnlyList<ReadOnly>, IReadOnlyList<string>, string, ShareOptions?)

Shares multiple separate pieces of data to other apps using the system share sheet.

```
public ShareSheetManagerV2.EventStatus TryShareBytes(int id, IReadOnlyList<NativeArray<byte>.ReadOnly> data,
IReadOnlyList<string> fileNames, string contentType, ShareOptions? options = null)
```

Parameters

id int

The ID of this share event, returned in [OnResult](#).

data IReadOnlyList<NativeArray<byte>.ReadOnly>

The data to share.

fileNames IReadOnlyList<string>

The names of the temporary files. Since these are displayed to the user, it's recommended to set human-readable descriptions of the data. Some platforms like iOS may even obfuscate files with non-standard extensions.

contentType string

The MIME type of the combined data; see [CommonMimeTypes](#) for common MIME types.

options [ShareOptions](#)

Additional options for the event.

Returns

[ShareSheetManagerV2.EventStatus](#)

An [ShareSheetManagerV2.EventStatus](#) object with [Success](#) = [true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

This method creates a file for each byte array in a cache folder which can be accessed by the share sheet. The paths to these files are returned in [ShareSheetManagerV2.EventStatus](#). See [CreatedFiles](#) for more details.

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

ArgumentException

If **fileNames** is a different size to **data**.

TryShareBytes(int, IReadOnlyList<byte[]>, IReadOnlyList<string>, string, ShareOptions?)

Shares multiple separate pieces of data to other apps using the system share sheet.

```
public ShareSheetManagerV2.EventStatus TryShareBytes(int id, IReadOnlyList<byte[]> data, IReadOnlyList<string> fileNames, string
contentType, ShareOptions? options = null)
```

Parameters

id int

The ID of this share event, returned in [OnResult](#).

data IReadOnlyList<byte[]>

The data to share.

fileNames IReadOnlyList<string>

The names of the temporary files. Since these are displayed to the user, it's recommended to set human-readable descriptions of the data. Some platforms like iOS may even obfuscate files with non-standard extensions.

contentType string

The MIME type of the combined data; see [CommonMimeTypes](#) for common MIME types.

options [ShareOptions](#)

Additional options for the event.

Returns

[ShareSheetManagerV2.EventStatus](#)

An [ShareSheetManagerV2.EventStatus](#) object with [Success](#) = [true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

This method creates a file for each byte array in a cache folder which can be accessed by the share sheet. The paths to these files are returned in [ShareSheetManagerV2.EventStatus](#). See [CreatedFiles](#) for more details.

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

ArgumentException

If **fileNames** is a different size to **data**.

TryShareBytes(int, ReadOnlySpan<byte>, string, string, ShareOptions?)

Shares data to other apps using the system share sheet.

```
public ShareSheetManagerV2.EventStatus TryShareBytes(int id, ReadOnlySpan<byte> data, string fileName, string contentType, ShareOptions? options = null)
```

Parameters

id int

The ID of this share event, returned in [OnResult](#).

data ReadOnlySpan<byte>

The data to share.

fileName string

The name of the temporary file. Since this is displayed to the user, it's recommended to set a human-readable description of the data. Some platforms like iOS may even obfuscate files with non-standard extensions.

contentType string

The MIME type of the data; see [CommonMimeTypes](#) for common MIME types.

options [ShareOptions](#)

Additional options for the event.

Returns

[ShareSheetManagerV2.EventStatus](#)

An [ShareSheetManagerV2.EventStatus](#) object with [Success](#) = [true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

This method creates a file for the data in a cache folder which can be accessed by the share sheet. The path to this file is returned in [ShareSheetManagerV2.EventStatus](#). See [CreatedFiles](#) for more details.

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

TryShareBytes(ReadOnlySpan<byte>, string, string, ShareOptions?)

Shares data to other apps using the system share sheet.

```
public ShareSheetManagerV2.EventStatus TryShareBytes(ReadOnlySpan<byte> data, string fileName, string contentType, ShareOptions? options = null)
```

Parameters

data ReadOnlySpan<byte>

The data to share.

fileName string

The name of the temporary file. Since this is displayed to the user, it's recommended to set a human-readable description of the data. Some platforms like iOS may even obfuscate files with non-standard extensions.

contentType string

The MIME type of the data; see [CommonMimeTypes](#) for common MIME types.

options [ShareOptions](#)

Additional options for the event.

Returns

[ShareSheetManagerV2.EventStatus](#)

An [ShareSheetManagerV2.EventStatus](#) object with [Success](#) = [true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

This method creates a file for the data in a cache folder which can be accessed by the share sheet. The path to this file is returned in [ShareSheetManagerV2.EventStatus](#). See [CreatedFiles](#) for more details.

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

TryShareFile(int, string, string, ShareOptions?)

Shares a file to other apps using the system share sheet.

```
public bool TryShareFile(int id, string path, string contentType, ShareOptions? options = null)
```

Parameters

id int

The ID of this share event, returned in [OnResult](#).

path string

The path to the file to share.

contentType string

The MIME type of the file's data; see [CommonMimeTypes](#) for common MIME types.

options [ShareOptions](#)

Additional options for the event.

Returns

bool

[true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

(Android) Ensure the path is under the scope of the FileProvider; see [GetDefaultBasePath\(\)](#) for this plugin's default folder for shareable data.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

TryShareFile(string, string, ShareOptions?)

Shares a file to other apps using the system share sheet.

```
public bool TryShareFile(string path, string contentType, ShareOptions? options = null)
```

Parameters

path string

The path to the file to share.

contentType string

The MIME type of the file's data; see [CommonMimeTypes](#) for common MIME types.

options [ShareOptions](#)

Additional options for the event.

Returns

bool

[true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

(Android) Ensure the path is under the scope of the FileProvider; see [GetDefaultBasePath\(\)](#) for this plugin's default folder for shareable data.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

TryShareFiles(int, string[], string, ShareOptions?)

Shares multiple files to other apps using the system share sheet.

```
public bool TryShareFiles(int id, string[] paths, string contentType, ShareOptions? options = null)
```

Parameters

id int

The ID of this share event, returned in [OnResult](#).

paths string[]

The paths to files to share.

contentType string

The MIME type of the combined data of the files; see [CommonMimeType](#)s for common MIME types.

options [ShareOptions](#)

Additional options for the event.

Returns

bool

[true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

(Android) Ensure the paths are under the scope of the FileProvider; see [GetDefaultBasePath\(\)](#) for this plugin's default folder for shareable data.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

TryShareFiles(string[], string, ShareOptions?)

Shares multiple files to other apps using the system share sheet.

```
public bool TryShareFiles(string[] paths, string contentType, ShareOptions? options = null)
```

Parameters

paths string[]

The paths to files to share.

contentType string

The MIME type of the combined data of the files; see [CommonMimeType](#) for common MIME types.

options [ShareOptions](#)

Additional options for the event.

Returns

bool

[true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

(Android) Ensure the paths are under the scope of the FileProvider; see [GetDefaultBasePath\(\)](#) for this plugin's default folder for shareable data.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

TryShareImage(int, ReadOnlySpan<byte>, string, string, ShareOptions?)

Equivalent to [TryShareBytes\(int, ReadOnlySpan<byte>, string, string, ShareOptions?\)](#), but falls back to [TryShareImageIOS\(int, ReadOnlySpan<byte>, ShareOptions?\)](#) on iOS.

```
public ShareSheetManagerV2.EventStatus TryShareImage(int id, ReadOnlySpan<byte> image, string fileName, string contentType, ShareOptions? options = null)
```

Parameters

id int

image ReadOnlySpan<byte>

fileName string

contentType string

options [ShareOptions](#)

Returns

[ShareSheetManagerV2.EventStatus](#)

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

See Also

[TryShareBytes\(int, ReadOnlySpan<byte>, string, string, ShareOptions?\)](#), [TryShareImageIOS\(int, ReadOnlySpan<byte>, ShareOptions?\)](#)

TryShareImage(ReadOnlySpan<byte>, string, string, ShareOptions?)

Equivalent to [TryShareBytes\(ReadOnlySpan<byte>, string, string, ShareOptions?\)](#), but falls back to [TryShareImageIOS\(int, ReadOnlySpan<byte>, ShareOptions?\)](#) on iOS.

```
public ShareSheetManagerV2.EventStatus TryShareImage(ReadOnlySpan<byte> image, string fileName, string contentType, ShareOptions? options = null)
```

Parameters

image ReadOnlySpan<byte>

fileName string

contentType string

options [ShareOptions](#)

Returns

[ShareSheetManagerV2.EventStatus](#)

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

See Also

[TryShareBytes\(ReadOnlySpan<byte>, string, string, ShareOptions?\)](#), [TryShareImageIOS\(int, ReadOnlySpan<byte>, ShareOptions?\)](#)

TryShareImageIOS(int, ReadOnlySpan<byte>, ShareOptions?)

Shares an image to other apps using the iOS share sheet.

```
public bool TryShareImageIOS(int id, ReadOnlySpan<byte> image, ShareOptions? options = null)
```

Parameters

id int

The ID of this share event, returned in [OnResult](#).

image ReadOnlySpan<byte>

The image to share, must be a format supported by [UIImage](#).

options [ShareOptions](#)

Additional options for the event.

Returns

bool

[true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

This is an iOS-specific method which shares the given image data directly with the native plugin. The plugin then creates a [UIImage](#) and forwards it to the share sheet.

For a multi-platform method that uses this for iOS, see [TryShareImage\(ReadOnlySpan<byte>, string, string, ShareOptions?\)](#).

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than iOS.

TryShareImages(IReadOnlyList<ReadOnly>, IReadOnlyList<string>, string, ShareOptions?)

Equivalent to

TryShareBytes(System.Collections.Generic.IReadOnlyList<Unity.Collections.NativeArray<byte>.ReadOnly>, System.Collections.Generic.IReadOnlyList<string>, string, ShareOptions?) but falls back to

TryShareImagesIOS(int, System.Collections.Generic.IReadOnlyList<Unity.Collections.NativeArray<byte>.ReadOnly>, Uralstech.UShare.ShareOptions?) on iOS.

```
public ShareSheetManagerV2.EventStatus TryShareImages(IReadOnlyList<NativeArray<byte>.ReadOnly> images, IReadOnlyList<string>
fileNames, string contentType, ShareOptions? options = null)
```

Parameters

images IReadOnlyList<NativeArray<byte>.ReadOnly>

fileNames IReadOnlyList<string>

contentType string

options [ShareOptions](#)

Returns

[ShareSheetManagerV2.EventStatus](#)

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

TryShareImages(IReadOnlyList<byte[]>, IReadOnlyList<string>, string, ShareOptions?)

Equivalent to [TryShareBytes\(IReadOnlyList<byte\[\]>, IReadOnlyList<string>, string, ShareOptions?\)](#), but falls back to [TryShareImagesIOS\(int, IReadOnlyList<byte\[\]>, ShareOptions?\)](#) on iOS.

```
public ShareSheetManagerV2.EventStatus TryShareImages(IReadOnlyList<byte[]> images, IReadOnlyList<string> fileNames, string
contentType, ShareOptions? options = null)
```

Parameters

images IReadOnlyList<byte[]>
fileNames IReadOnlyList<string>
contentType string
options [ShareOptions](#)

Returns

[ShareSheetManagerV2.EventStatus](#)

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

See Also

[TryShareBytes\(IReadOnlyList<byte\[\]>, IReadOnlyList<string>, string, ShareOptions?\)](#),
[TryShareImagesIOS\(int, IReadOnlyList<byte\[\]>, ShareOptions?\)](#).

TryShareImages(int, IReadOnlyList<ReadOnly>, IReadOnlyList<string>, string, ShareOptions?)

Equivalent to

TryShareBytes(int, System.Collections.Generic.IReadOnlyList<Unity.Collections.NativeArray<byte>.ReadOnly>, System.Collections.Generic but falls back to

TryShareImagesIOS(int, System.Collections.Generic.IReadOnlyList<Unity.Collections.NativeArray<byte>.ReadOnly>, Uralstech.UShare.Shar on iOS.

```
public ShareSheetManagerV2.EventStatus TryShareImages(int id, IReadOnlyList<NativeArray<byte>.ReadOnly> images,
IReadOnlyList<string> fileNames, string contentType, ShareOptions? options = null)
```

Parameters

id int
images IReadOnlyList<NativeArray<byte>.ReadOnly>
fileNames IReadOnlyList<string>
contentType string
options [ShareOptions](#)

Returns

[ShareSheetManagerV2.EventStatus](#)

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

TryShareImages(int, IReadOnlyList<byte[]>, IReadOnlyList<string>, string, ShareOptions?)

Equivalent to [TryShareBytes\(int, IReadOnlyList<byte\[\]>, IReadOnlyList<string>, string, ShareOptions?\)](#), but falls back to [TryShareImagesIOS\(int, IReadOnlyList<byte\[\]>, ShareOptions?\)](#) on iOS.


```
public ShareSheetManagerV2.EventStatus TryShareImages(int id, IReadOnlyList<byte[]> images, IReadOnlyList<string> fileNames, string contentType, ShareOptions? options = null)
```

Parameters

id int

images IReadOnlyList<byte[]>

fileNames IReadOnlyList<string>

contentType string

options [ShareOptions](#)

Returns

[ShareSheetManagerV2.EventStatus](#)

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

See Also

[TryShareBytes\(int, IReadOnlyList<byte\[\]>, IReadOnlyList<string>, string, ShareOptions?\)](#),
[TryShareImagesIOS\(int, IReadOnlyList<byte\[\]>, ShareOptions?\)](#)

TryShareImagesIOS(int, IReadOnlyList<ReadOnly>, ShareOptions?)

Shares multiple images to other apps using the iOS share sheet.

```
public bool TryShareImagesIOS(int id, IReadOnlyList<NativeArray<byte>.ReadOnly> images, ShareOptions? options = null)
```

Parameters

id int

The ID of this share event, returned in [OnResult](#).

images IReadOnlyList<NativeArray<byte>.ReadOnly>

The images to share, must be in formats supported by [UIImage](#).

options [ShareOptions](#)

Additional options for the event.

Returns

bool

[true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

This is an iOS-specific method which shares the given image data directly with the native plugin. The plugin then creates [UIImage](#)s and forwards them to the share sheet.

For a multi-platform method that uses this for iOS, see [TryShareImages\(int, IReadOnlyList<byte\[\]>, IReadOnlyList<string>, string, ShareOptions?\)](#).

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than iOS.

TryShareImagesIOS(int, IReadOnlyList<byte[]>, ShareOptions?)

Shares multiple images to other apps using the iOS share sheet.

```
public bool TryShareImagesIOS(int id, IReadOnlyList<byte[]> images, ShareOptions? options = null)
```

Parameters

id int

The ID of this share event, returned in [OnResult](#).

images IReadOnlyList<byte[]>

The images to share, must be in formats supported by [UIImage](#).

options [ShareOptions](#)

Additional options for the event.

Returns

bool

[true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

This is an iOS-specific method which shares the given image data directly with the native plugin. The plugin then creates [UIImage](#)s and forwards them to the share sheet.

For a multi-platform method that uses this for iOS, see [TryShareImages\(int, IReadOnlyList<byte\[\]>, IReadOnlyList<string>, string, ShareOptions?\)](#).

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than iOS.

TryShareText(int, string, string?)

Shares text to other apps using the system share sheet.

```
public bool TryShareText(int id, string text, string? title = null)
```

Parameters

id int

The ID of this share event, returned in [OnResult](#).

text string

The text to share.

title string

Optional title for the share sheet.

Returns

bool

[true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

TryShareText(string, string?)

Shares text to other apps using the system share sheet.

```
public bool TryShareText(string text, string? title = null)
```

Parameters

text string

The text to share.

title string

Optional title for the share sheet.

Returns

bool

[true](#) if the share sheet activity was presented; [false](#) otherwise.

Remarks

Duplicate IDs in successive calls may prevent reliable [OnResult](#) invocations in Android.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android or iOS.

Class ShareSheetManagerV2.EventStatus

Namespace: [Uralstech.UShare](#)

Result for QOL share methods that may generate temporary files.

```
public sealed record ShareSheetManagerV2.EventStatus
```

Inheritance

object ← ShareSheetManagerV2.EventStatus

Constructors

EventStatus(bool, IReadOnlyList<string>)

Result for QOL share methods that may generate temporary files.

```
public EventStatus(bool Success, IReadOnlyList<string> CreatedFiles)
```

Parameters

Success bool

[true](#) if the share sheet activity was presented; [false](#) otherwise.

CreatedFiles IReadOnlyList<string>

Any temporary files created for the event, regardless of [Success](#). **DO NOT** delete these immediately after the event is invoked, or even after [OnResult](#) is invoked. Delete these files later, like on subsequent app launches.

Properties

CreatedFiles

Any temporary files created for the event, regardless of [Success](#). **DO NOT** delete these immediately after the event is invoked, or even after [OnResult](#) is invoked. Delete these files later, like on subsequent app launches.

```
public IReadOnlyList<string> CreatedFiles { get; init; }
```

Property Value

IReadOnlyList<string>

Success

[true](#) if the share sheet activity was presented; [false](#) otherwise.

```
public bool Success { get; init; }
```

Property Value

bool

Namespace Uralstech.UShare.Native

Classes

[AndroidInterop](#)

Interface for the native Android plugin.

[AndroidInterop.Callbacks](#)

Handles callbacks from the native interface.

[IOSInterop](#)

Interface for the native iOS plugin.

Delegates

[IOSInterop.ActivityFinishedCallback](#)

Invoked after the completion or dismissal of a share event.

Class AndroidInterop

Namespace: [Uralstech.UShare.Native](#)

Interface for the native Android plugin.

```
public static class AndroidInterop
```

Inheritance

object ← AndroidInterop

Methods

CreateInstance(Callbacks)

Gets an instance of the native interface.

```
public static AndroidJavaObject CreateInstance(AndroidInterop.Callbacks callbacks)
```

Parameters

callbacks [AndroidInterop.Callbacks](#)

Returns

AndroidJavaObject

A new instance of the native interface.

Remarks

This method should generally be called only once during the application's lifetime, as the native object is supposed to act like a singleton. If you create a new instance of the native object while another one is active, all unfulfilled callbacks meant for the existing instance will be forwarded to the new instance's **callbacks** instead.

The returned AndroidJavaObject should be disposed when no longer needed.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android.

GetFileURI(AndroidJavaObject, string, string)

Creates a shareable `android.net.Uri` from a filepath under the given [FileProvider](#)[↗] authority's scope.

```
public static AndroidJavaObject? GetFileURI(AndroidJavaObject native, string path,
string authority)
```

Parameters

native AndroidJavaObject

The native plugin instance.

path string

The filepath.

authority string

The `FileProvider` authority which `path` is under.

Returns

AndroidJavaObject?

A shareable `android.net.Uri` object if successful; [null](#)[↗] otherwise.

Remarks

The returned `AndroidJavaObject` should be disposed when no longer needed.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android.

ShareText(AndroidJavaObject, int, string, string?)

Shares text data using ChooserActivity.

```
public static bool ShareText(AndroidJavaObject native, int id, string text, string? title)
```

Parameters

native AndroidJavaObject

The native plugin instance.

id int

The ID of this event, to be returned in [OnTargetChosen](#).

text string

The text to share.

title string

Optional title for the sharesheet.

Returns

bool

[true](#)  if the activity was started; [false](#)  otherwise.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android.

ShareURI(AndroidJavaObject, int, AndroidJavaObject, string, string?, string?)

Shares data sourced from a URI using ChooserActivity.

```
public static bool ShareURI(AndroidJavaObject native, int id, AndroidJavaObject uri,
string type, string? text, string? title)
```

Parameters

native AndroidJavaObject

The native plugin instance.

id int

The ID of this event, to be returned in [OnTargetChosen](#).

uri AndroidJavaObject

The `android.net.Uri` object to share.

type string

The MIME type of the content being shared through the `uri`.

text string

Optional additional text to share.

title string

Optional title for the sharesheet.

Returns

bool

[true](#)  if the activity was started; [false](#)  otherwise.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android.

ShareURIs(AndroidJavaObject, int, AndroidJavaObject[], string, string?, string?)

Shares multipart data sourced from URIs using ChooserActivity.

```
public static bool ShareURIs(AndroidJavaObject native, int id, AndroidJavaObject[] uris, string type, string? text, string? title)
```

Parameters

native AndroidJavaObject

The native plugin instance.

id int

The ID of this event, to be returned in [OnTargetChosen](#).

uris AndroidJavaObject[]

The array of `android.net.Uri` objects to share.

type string

The MIME type of the contents being shared through the `uris`.

text string

Optional additional text to share.

title string

Optional title for the sharesheet.

Returns

bool

[true](#) if the activity was started; [false](#) otherwise.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than Android.

Class AndroidInterop.Callbacks

Namespace: [Uralstech.UShare.Native](#)

Handles callbacks from the native interface.

```
public sealed class AndroidInterop.Callbacks : AndroidJavaProxy
```

Inheritance

object ← AndroidInterop.Callbacks

Constructors

Callbacks()

```
public Callbacks()
```

Exceptions

PlatformNotSupportedException

Thrown if this constructor is called on a runtime other than Android.

Events

OnTargetChosen

Called when the user has chosen a target to share to, along with the event ID.

```
public event Action<int>? OnTargetChosen
```

Event Type

Action<int>

Remarks

This callback indicates that a target application was selected. It does not guarantee that the shared content was successfully received or processed by the target application.

This callback is invoked from an Android BroadcastReceiver. Do not use Unity APIs unless switching back to the main thread.

This callback may not be invoked for all share targets. For example, it is not triggered by "Copy to clipboard" on Meta Quest.

Class IOSInterop

Namespace: [Uralstech.UShare.Native](#)

Interface for the native iOS plugin.

```
public static class IOSInterop
```

Inheritance

object ← IOSInterop

Methods

ushare_ios_share_files(int, string[], int, string?, string?, ActivityFinishedCallback)

Shares files using UIActivityViewController.

```
public static extern bool ushare_ios_share_files(int id, string[] paths, int count, string? text, string? title, IOSInterop.ActivityFinishedCallback callback)
```

Parameters

id int

The ID of this event, to be returned in **callback**.

paths string[]

The paths to the files being shared.

count int

Length of **paths**.

text string

Optional additional text to share.

title string

Optional title for the sharesheet.

callback [IOSInterop.ActivityFinishedCallback](#)

Callback for when the activity has finished. Note that this is **not** an indication of the operation being completed.

Returns

bool

[true](#) if the view was presented; [false](#) otherwise.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than iOS.

ushare_ios_share_images(int, nint[], int[], int, string?, string?, ActivityFinishedCallback)

Shares images using UIActivityViewController.

```
public static extern bool ushare_ios_share_images(int id, nint[] images, int[] sizes, int count, string? text, string? title, IOSInterop.ActivityFinishedCallback callback)
```

Parameters

id int

The ID of this event, to be returned in **callback**.

images nint[]

The images being shared.

sizes int[]

The size of each image in **images**, in bytes.

count int

Length of **images** **and** **sizes**.

text string

Optional additional text to share.

title string

Optional title for the sharesheet.

callback [IOSInterop.ActivityFinishedCallback](#)

Callback for when the activity has finished. Note that this is **not** an indication of the operation being completed.

Returns

bool

[true](#) if the view was presented; [false](#) otherwise.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than iOS.

ushare_ios_share_text(int, string, string?, ActivityFinishedCallback)

Shares text data using UIActivityViewController.

```
public static extern bool ushare_ios_share_text(int id, string text, string? title,
IOSInterop.ActivityFinishedCallback callback)
```

Parameters

id int

The ID of this event, to be returned in **callback**.

text string

The text to share.

title string

Optional title for the sharesheet.

callback [IOSInterop.ActivityFinishedCallback](#)

Callback for when the activity has finished. Note that this is **not** an indication of the operation being completed.

Returns

bool

[true](#) if the view was presented; [false](#) otherwise.

Exceptions

PlatformNotSupportedException

Thrown if this method is called on a runtime other than iOS.

Delegate

IOSInterop.ActivityFinishedCallback

Namespace: [Uralstech.UShare.Native](#)

Invoked after the completion or dismissal of a share event.

```
public delegate void IOSInterop.ActivityFinishedCallback(int id)
```

Parameters

id int

The ID of the event.