

Table of Contents

- Uralstech.UXR.QuestCamera 2
 - CameraDevice 3
 - CameraDevice.CaptureSessionObject 9
 - CameraDevice.CaptureTemplate 11
 - CameraDevice.ErrorCode 12
 - CameraFrameForwarder 13
 - CameraSupport 15
 - CaptureSession 17
 - NativeWrapperState 22
 - UCameraManager 23
 - YUVToRGBAConverter 26

Namespace Uralstech.UXR.QuestCamera

Classes

[CameraDevice](#)

A wrapper for a native Camera2 CameraDevice.

[CameraDevice.CaptureSessionObject](#)

Simple class for grouping capture session related GameObjects.

[CameraFrameForwarder](#)

Forwards frame callbacks from the native Kotlin plugin to Unity.

[CameraSupport](#)

Utility to check if the current Meta Quest device supports the Passthrough Camera API.

[CaptureSession](#)

A wrapper for a native Camera2 CaptureSession and ImageReader.

[UCameraManager](#)

Class for interfacing with the native Camera2 API on Android.

[YUVToRGBAConverter](#)

The default YUV 4:2:0 to RGBA converter that uses a compute shader to convert the camera texture to RGBA.

Enums

[CameraDevice.CaptureTemplate](#)

Capture template to use when recording.

[CameraDevice.ErrorCode](#)

Error codes that can be returned by the native CameraDevice wrapper.

[NativeWrapperState](#)

The current assumed state of a native wrapper.

Class CameraDevice

Namespace: [Uralstech.UXR.QuestCamera](#)

A wrapper for a native Camera2 CameraDevice.

```
public class CameraDevice : MonoBehaviour
```

Inheritance

object ← CameraDevice

Fields

OnDeviceClosed

Invoked when the CameraDevice is closed.

```
public UnityEvent OnDeviceClosed
```

Field Value

UnityEvent

OnDeviceDisconnected

Invoked when the CameraDevice is disconnected.

```
public UnityEvent OnDeviceDisconnected
```

Field Value

UnityEvent

OnDeviceErred

Invoked when the CameraDevice encounters an error.

```
public UnityEvent<CameraDevice.ErrorCode> OnDeviceErred
```

Field Value

UnityEvent<[ErrorCode](#)>

OnDeviceOpened

Invoked when the CameraDevice is opened.

```
public UnityEvent OnDeviceOpened
```

Field Value

UnityEvent

Properties

CameraId

The ID of the camera being wrapped.

```
public string CameraId { get; }
```

Property Value

string

CurrentState

The current assumed state of the native CameraDevice wrapper.

```
public NativeWrapperState CurrentState { get; }
```

Property Value

[NativeWrapperState](#)

IsActiveAndUsable

Is the native CameraDevice wrapper active and usable?

```
public bool IsActiveAndUsable { get; }
```

Property Value

bool

Methods

CreateCaptureSession(Resolution, CaptureTemplate, bool)

Creates a new capture session for use.

```
public CameraDevice.CaptureSessionObject CreateCaptureSession(Resolution resolution,  
CameraDevice.CaptureTemplate captureTemplate = CaptureTemplate.Preview, bool isContinuous  
= true)
```

Parameters

resolution Resolution

The resolution of the capture.

captureTemplate [CameraDevice.CaptureTemplate](#)

The capture template to use for the capture

isContinuous bool

Is this capture continuous (repeating) or for a single frame?

Returns

[CameraDevice.CaptureSessionObject](#)

A new capture session wrapper. May be null if the current camera device is not usable.

Remarks

Once you have finished using the capture session, either destroy its `GameObject` or call [Release\(\)](#) and [Release\(\)](#) to close the session and free up native and compute shader resources.

OnDestroy()

```
protected void OnDestroy()
```

Release()

Releases the `CameraDevice`'s native resources, and makes it unusable.

```
public void Release()
```

WaitForInitialization()

Waits until the `CameraDevice` is open or erred out.

```
public IEnumerator WaitForInitialization()
```

Returns

`IEnumerator`

WaitForInitializationAsync()

Waits until the `CameraDevice` is open or erred out.

```
public Awaitable<NativeWrapperState> WaitForInitializationAsync()
```

Returns

Awaitable<[NativeWrapperState](#)>

The current state of the CameraDevice.

Remarks

Requires Unity 6.0 or higher.

_onDeviceClosed(string)

```
public void _onDeviceClosed(string _)
```

Parameters

_ string

_onDeviceDisconnected(string)

```
public void _onDeviceDisconnected(string _)
```

Parameters

_ string

_onDeviceErred(string)

```
public void _onDeviceErred(string errorCodeStr)
```

Parameters

errorCodeStr string

_onDeviceOpened(string)

```
public void _onDeviceOpened(string _)
```

Parameters

 string

Class CameraDevice.CaptureSessionObject

Namespace: [Uralstech.UXR.QuestCamera](#)

Simple class for grouping capture session related GameObjects.

```
public class CameraDevice.CaptureSessionObject
```

Inheritance

object ← CameraDevice.CaptureSessionObject

Fields

CaptureSession

The capture session wrapper.

```
public readonly CaptureSession CaptureSession
```

Field Value

[CaptureSession](#)

GameObject

The GameObject containing the [CaptureSession](#) and [TextureConverter](#) components.

```
public readonly GameObject GameObject
```

Field Value

GameObject

TextureConverter

The YUV to RGBA texture converter.

```
public readonly YUVToRGBAConverter TextureConverter
```

Field Value

[YUVToRGBAConverter](#)

Methods

Destroy()

Destroys the GameObject to release all native resources.

```
public void Destroy()
```

Enum CameraDevice.CaptureTemplate

Namespace: [Uralstech.UXR.QuestCamera](#)

Capture template to use when recording.

```
public enum CameraDevice.CaptureTemplate
```

Fields

Default = 0

Default value, do not use.

Preview = 1

Creates a request suitable for a camera preview window.

Record = 3

Creates a request suitable for video recording.

StillCapture = 2

Creates a request suitable for still image capture.

VideoSnapshot = 4

Creates a request suitable for still image capture while recording video.

ZeroShutterLag = 5

Creates a request suitable for zero shutter lag still capture.

Enum CameraDevice.ErrorCode

Namespace: [Uralstech.UXR.QuestCamera](#)

Error codes that can be returned by the native CameraDevice wrapper.

```
public enum CameraDevice.ErrorCode
```

Fields

CameraAccessException = 1000

The native code encountered a CameraAccessException.

CameraDeviceError = 4

The camera device has encountered a fatal error.

CameraDisabled = 3

The camera device could not be opened due to a device policy.

CameraInUse = 1

The camera device is in use already.

CameraServiceError = 5

The camera service has encountered a fatal error.

MaxCamerasInUse = 2

The camera device could not be opened because there are too many other open camera devices.

SecurityException = 1001

The native code encountered a SecurityException.

Unknown = 0

Unknown error.

Class CameraFrameForwarder

Namespace: [Uralstech.UXR.QuestCamera](#)

Forwards frame callbacks from the native Kotlin plugin to Unity.

```
public class CameraFrameForwarder : AndroidJavaProxy
```

Inheritance

object ← CameraFrameForwarder

Constructors

CameraFrameForwarder()

```
public CameraFrameForwarder()
```

Fields

OnFrameReady

Callback for processing the YUV 4:2:0 frame.

```
public Action<nint, nint, nint, int, int, int, int, int, int> OnFrameReady
```

Field Value

Action<nint, nint, nint, int, int, int, int, int, int>

Remarks

Parameters	
yBuffer (IntPtr)	Pointer to the buffer containing Y (luminance) data of the frame.
uBuffer (IntPtr)	Pointer to the buffer containing U (color) data of the frame.

Parameters	
vBuffer (IntPtr)	Pointer to the buffer containing V (color) data of the frame.
ySize (int)	The size of yBuffer.
uSize (int)	The size of uBuffer.
vSize (int)	The size of vBuffer.
yRowStride (int)	The size of each row of the image in yBuffer in bytes.
uvRowStride (int)	The size of each row of the image in uBuffer and vBuffer in bytes.
uvPixelStride (int)	The size of a pixel in a row of the image in uBuffer and vBuffer in bytes.

Methods

GetBufferPointer(AndroidJavaObject)

Gets the pointer to a native buffer from a Java ByteBuffer object.

```
protected static nint GetBufferPointer(AndroidJavaObject byteBuffer)
```

Parameters

byteBuffer AndroidJavaObject

The Java ByteBuffer object.

Returns

nint

A pointer to the native buffer.

Class CameraSupport

Namespace: [Uralstech.UXR.QuestCamera](#)

Utility to check if the current Meta Quest device supports the Passthrough Camera API.

```
public static class CameraSupport
```

Inheritance

object ← CameraSupport

Remarks

Requires the Meta XR Core SDK.

Fields

MINSUPPORTOSVERSION

```
public const int MINSUPPORTOSVERSION = 74
```

Field Value

int

Properties

HorizonOSVersion

Get the Horizon OS version number on the headset

```
public static int? HorizonOSVersion { get; }
```

Property Value

int?

Remarks

Requires the Meta XR Core SDK.

IsSupported

Returns true if the current headset supports Passthrough Camera API

```
public static bool IsSupported { get; }
```

Property Value

bool

Remarks

Requires the Meta XR Core SDK.

Class CaptureSession

Namespace: [Uralstech.UXR.QuestCamera](#)

A wrapper for a native Camera2 CaptureSession and ImageReader.

```
public class CaptureSession : MonoBehaviour
```

Inheritance

object ← CaptureSession

Fields

OnSessionConfigurationFailed

Called when the session could not be configured.

```
public UnityEvent<string> OnSessionConfigurationFailed
```

Field Value

UnityEvent<string>

OnSessionConfigured

Called when the session has been configured.

```
public UnityEvent OnSessionConfigured
```

Field Value

UnityEvent

OnSessionRequestFailed

Called when the session request could not be set.

```
public UnityEvent<string> OnSessionRequestFailed
```

Field Value

UnityEvent<string>

OnSessionRequestSet

Called when the session request has been set.

```
public UnityEvent OnSessionRequestSet
```

Field Value

UnityEvent

Properties

CurrentState

The current assumed state of the native CaptureSession wrapper.

```
public NativeWrapperState CurrentState { get; }
```

Property Value

[NativeWrapperState](#)

IsActiveAndUsable

Is the native CaptureSession wrapper active and usable?

```
public bool IsActiveAndUsable { get; }
```

Property Value

bool

Methods

OnDestroy()

```
protected void OnDestroy()
```

Release()

Releases the CaptureSession's native resources, and makes it unusable.

```
public void Release()
```

WaitForInitialization()

Waits until the CaptureSession is open or erred out.

```
public IEnumerator WaitForInitialization()
```

Returns

IEnumerator

WaitForInitializationAsync()

Waits until the CaptureSession is open or erred out.

```
public Awaitable<NativeWrapperState> WaitForInitializationAsync()
```

Returns

Awaitable<[NativeWrapperState](#)>

The current state of the CaptureSession.

Remarks

Requires Unity 6.0 or higher.

_onSessionConfigurationFailed(string)

```
public void _onSessionConfigurationFailed(string reason)
```

Parameters

reason string

_onSessionConfigured(string)

```
public void _onSessionConfigured(string _)
```

Parameters

_ string

_onSessionRequestFailed(string)

```
public void _onSessionRequestFailed(string reason)
```

Parameters

reason string

_onSessionRequestSet(string)

```
public void _onSessionRequestSet(string _)
```

Parameters

 string

Enum NativeWrapperState

Namespace: [Uralstech.UXR.QuestCamera](#)

The current assumed state of a native wrapper.

```
public enum NativeWrapperState
```

Fields

Closed = 2

The native wrapper failed with an error, was disconnected or was closed normally.

Initializing = 0

The native wrapper is still initializing.

Opened = 1

The native wrapper is open and ready.

Class UCameraManager

Namespace: [Uralstech.UXR.QuestCamera](#)

Class for interfacing with the native Camera2 API on Android.

```
public class UCameraManager : DontCreateNewSingleton<UCameraManager>
```

Inheritance

object ← UCameraManager

Fields

HeadsetCameraPermission

The permission required to access the Meta Quest's cameras.

```
public const string HeadsetCameraPermission = "horizonos.permission.HEADSET_CAMERA"
```

Field Value

string

YUVToRGBAComputeShader

The compute shader to use to convert the camera's YUV 4:2:0 images to RGBA.

```
public ComputeShader YUVToRGBAComputeShader
```

Field Value

ComputeShader

Properties

CameraDevices

Gets the available camera devices. May be null.

```
public String[] CameraDevices { get; }
```

Property Value

String[]

Methods

Awake()

```
protected override void Awake()
```

GetSupportedResolutions(string)

Gets the supported resolutions for the specified camera.

```
public Resolution[] GetSupportedResolutions(string camera)
```

Parameters

camera String

The ID of the camera. You can get it from [CameraDevices](#).

Returns

Resolution[]

OnDestroy()

```
protected void OnDestroy()
```


OpenCamera(string)

Opens a camera device for use.

```
public CameraDevice OpenCamera(string camera)
```

Parameters

camera string

The ID of the camera. You can get it from [CameraDevices](#).

Returns

[CameraDevice](#)

A new camera device wrapper. May be null if the current object is disposed/unusable.

Remarks

Once you have finished using the camera, either destroy its GameObject or call [Release\(\)](#) to close the camera and free up native resources.

Class YUVToRGBAConverter

Namespace: [Uralstech.UXR.QuestCamera](#)

The default YUV 4:2:0 to RGBA converter that uses a compute shader to convert the camera texture to RGBA.

```
public class YUVToRGBAConverter : MonoBehaviour
```

Inheritance

object ← YUVToRGBAConverter

Fields

OnFrameProcessed

Called when a frame has been converted from YUV 4:2:0 to RGBA.

```
public UnityEvent<RenderTexture> OnFrameProcessed
```

Field Value

UnityEvent<RenderTexture>

Shader

The shader used to convert YUV 4:2:0 to an RGBA RenderTexture. Uses [YUVToRGBAComputeShader](#) if not specified here.

```
public ComputeShader Shader
```

Field Value

ComputeShader

`_uComputeBuffer`

Pointer to the buffer containing U (color) data of the frame being processed.

```
protected ComputeBuffer _uComputeBuffer
```

Field Value

ComputeBuffer

`_vComputeBuffer`

Pointer to the buffer containing V (color) data of the frame being processed.

```
protected ComputeBuffer _vComputeBuffer
```

Field Value

ComputeBuffer

`_yComputeBuffer`

Pointer to the buffer containing Y (luminance) data of the frame being processed.

```
protected ComputeBuffer _yComputeBuffer
```

Field Value

ComputeBuffer

Properties

CameraFrameForwarder

The native camera frame forwarder.

```
public CameraFrameForwarder CameraFrameForwarder { get; }
```

Property Value

[CameraFrameForwarder](#)

FrameRenderTexture

The RenderTexture which will contain the RGBA camera frames.

```
public RenderTexture FrameRenderTexture { get; }
```

Property Value

RenderTexture

Methods

Awake()

```
protected void Awake()
```

CopyNativeDataToComputeBuffer(ref ComputeBuffer, nint, int)

Copies native (unmanaged) byte data to a compute buffer.

```
protected static void CopyNativeDataToComputeBuffer(ref ComputeBuffer computeBuffer, nint  
nativeBufferPtr, int nativeBufferSize)
```

Parameters

computeBuffer ComputeBuffer

The buffer to copy to.

nativeBufferPtr nint

The memory to copy from.

nativeBufferSize int

The number of bytes to copy.

OnDestroy()

```
protected void OnDestroy()
```

OnFrameReady(nint, nint, nint, int, int, int, int, int, int)

Callback for [CameraFrameForwarder](#).

```
protected virtual void OnFrameReady(nint yBuffer, nint uBuffer, nint vBuffer, int ySize, int uSize, int vSize, int yRowStride, int uvRowStride, int uvPixelStride)
```

Parameters

yBuffer nint

Pointer to the buffer containing Y (luminance) data of the frame.

uBuffer nint

Pointer to the buffer containing U (color) data of the frame.

vBuffer nint

Pointer to the buffer containing V (color) data of the frame.

ySize int

The size of **yBuffer**.

uSize int

The size of **uBuffer**.

vSize int

The size of **vBuffer**.

yRowStride int

The size of each row of the image in **yBuffer** in bytes.

uvRowStride int

The size of each row of the image in **uBuffer** and **vBuffer** in bytes.

uvPixelStride int

The size of a pixel in a row of the image in **uBuffer** and **vBuffer** in bytes.

Release()

Releases the ComputeBuffers and RenderTextures associated with this converter.

```
public void Release()
```

SendFrameToComputeBuffer(int, int, int)

Sends the camera frame stored in the compute buffers to the compute shader and dispatches it.

```
protected virtual void SendFrameToComputeBuffer(int yRowStride, int uvRowStride,  
int uvPixelStride)
```

Parameters

yRowStride int

The size of each row of the image in [_yComputeBuffer](#) in bytes.

uvRowStride int

The size of each row of the image in [_uComputeBuffer](#) and [_vComputeBuffer](#) in bytes.

uvPixelStride int

The size of a pixel in a row of the image in [_uComputeBuffer](#) and [_vComputeBuffer](#) in bytes.

SetupCameraFrameForwarder(CameraFrameForwarder, Resolution)

Sets the camera frame forwarder.

```
public virtual void SetupCameraFrameForwarder(CameraFrameForwarder cameraFrameForwarder,  
Resolution textureResolution)
```

Parameters

cameraFrameForwarder [CameraFrameForwarder](#)

textureResolution Resolution