

Table of Contents

Uralstech.UXR.QuestCamera	2
CameraDevice	4
CameraDevice.ErrorCode	12
CameraDevice.Proxy	14
CameraInfo	16
CameraInfo.CameraEye	20
CameraInfo.CameraIntrinsics	21
CameraInfo.CameraSource	24
CapturePipeline<T>	25
CaptureSessionBase<TProxy>	27
CaptureSessionBase<TProxy>.ErrorCode	32
CaptureSessionBase<TProxy>.ProxyBase	33
CaptureTemplate	36
ComputeShaderKernel	37
ContinuousCaptureSession	40
ContinuousCaptureSession.OnFrameReadyCallback	42
ContinuousCaptureSession.Proxy	44
JNIExtensions	46
OnDemandCaptureSession	50
PCASupport	52
QuestCameraManager	53
ResourceState	57
StatefulResource	58
StreamUseCase	61
YUVConverter	62
Uralstech.UXR.QuestCamera.GLES	66
GLESAPI	67
GLESCaptureSession	71
GLESCaptureSession.Proxy	76
RenderJobDisposeData	77
RenderJobDisposeData.Callback	79
RenderJobEvent	80
RenderJobRunData	81
RenderJobRunData.Callback	83
RenderJobSetupData	84
RenderJobSetupData.Callback	86

Namespace Uralstech.UXR.QuestCamera

Classes

[CameraDevice](#)

Manages a camera device.

[CameraDevice.Proxy](#)

Java proxy to handle native callbacks.

[CameraInfo](#)

Information describing a camera device.

[CameraInfo.CameraIntrinsics](#)

Defines the camera's intrinsic properties. All values are in pixels.

[CapturePipeline<T>](#)

A wrapper for a complete capture-conversion pipeline.

[CaptureSessionBase<TProxy>](#)

Base class for all capture session types.

[CaptureSessionBase<TProxy>.ProxyBase](#)

Java proxy to handle native callbacks.

[ComputeShaderKernel](#)

Utility class to contain ComputeShader kernel info.

[ContinuousCaptureSession](#)

Manages a camera capture session with a continuous/repeating request.

[ContinuousCaptureSession.Proxy](#)

Java proxy to handle native callbacks.

[JNIExtensions](#)

QOL extensions for the JNI.

[OnDemandCaptureSession](#)

Manages an on-demand, explicit capture session.

[QuestCameraManager](#)

Entry point for the native Camera2 plugin.

[StatefulResource](#)

[YUVConverter](#)

Converts raw camera capture session frames to Unity-supported RGBA.

Enums

[CameraDevice.ErrorCode](#)

Error codes from the native plugin.

[CameraInfo.CameraEye](#)

The camera eye.

[CameraInfo.CameraSource](#)

The source of the camera feed.

[CaptureSessionBase<TProxy>.ErrorCode](#)

Error codes from the native plugin.

[CaptureTemplate](#)

Capture template to use when recording.

[PCASupport](#)

[ResourceState](#)

State of a Camera2 resource.

[StreamUseCase](#)

Stream Use Cases are a way to improve the performance of Camera2 capture sessions. They give the hardware device more information to tune parameters, which provides a better camera experience for your specific task.

Delegates

[ContinuousCaptureSession.OnFrameReadyCallback](#)

Processes a frame received from the native capture session.

Class CameraDevice

Namespace: [Uralstech.UXR.QuestCamera](#)

Manages a camera device.

```
public sealed class CameraDevice : StatefulResource
```

Inheritance

object ← [StatefulResource](#) ← CameraDevice

Inherited Members

[StatefulResource.State](#) , [StatefulResource.WaitForInitialization\(\)](#) ,
[StatefulResource.WaitForInitialization\(TimeSpan, Action, WaitTimeoutMode\)](#) ,
[StatefulResource.WaitForInitializationAsync\(CancellationToken\)](#).

Constructors

CameraDevice(string)

```
public CameraDevice(string cameraId)
```

Parameters

cameraId string

Fields

CameraId

The ID of the camera.

```
public readonly string CameraId
```

Field Value

string

NativeProxy

Native callback handler.

```
public readonly CameraDevice.Proxy NativeProxy
```

Field Value

[CameraDevice.Proxy](#)

Methods

CreateContinuousPipeline(Resolution, CaptureTemplate, StreamUseCase, GraphicsFormat)

Creates a continuous capture pipeline (session + linked YUV to RGBA converter) for use.

```
public CapturePipeline<ContinuousCaptureSession>? CreateContinuousPipeline(Resolution  
resolution, CaptureTemplate template = CaptureTemplate.Preview, StreamUseCase streamUseCase  
= StreamUseCase.None, GraphicsFormat textureFormat = null)
```

Parameters

resolution Resolution

template [CaptureTemplate](#)

streamUseCase [StreamUseCase](#)

textureFormat GraphicsFormat

See [YUVConverter\(Resolution, ComputeShaderKernel, GraphicsFormat\)](#) for default texture format.

Returns

[CapturePipeline](#)<[ContinuousCaptureSession](#)>

The created pipeline, or [null](#) if creation failed.

CreateContinuousSession(Resolution, CaptureTemplate, StreamUseCase)

Creates a continuous capture session for use.

```
public ContinuousCaptureSession CreateContinuousSession(Resolution resolution,  
CaptureTemplate template = CaptureTemplate.Preview, StreamUseCase streamUseCase  
= StreamUseCase.None)
```

Parameters

resolution Resolution

The capture resolution. Must be from [SupportedResolutions](#).

template [CaptureTemplate](#)

The template to use for the captures.

streamUseCase [StreamUseCase](#)

The stream use case for this session. Must be from [SupportedStreamUseCases](#) or [None](#).

Returns

[ContinuousCaptureSession](#)

Returns the session. Check [State](#) (inherited by [ContinuousCaptureSession](#)) for the state of the session.

Remarks

To shut down and dispose the session, use [DisposeAsync\(\)](#) (inherited by [ContinuousCaptureSession](#)).

Exceptions

ObjectDisposedException

CreateGLESSessionAsync(Resolution, CaptureTemplate, StreamUseCase, GraphicsFormat)

Creates a generic OpenGL-ES based capture session.

```
public ValueTask<GLESCaptureSession> CreateGLESSessionAsync(Resolution resolution,
    CaptureTemplate template = CaptureTemplate.Preview, StreamUseCase streamUseCase =
    StreamUseCase.None, GraphicsFormat textureFormat = null)
```

Parameters

resolution Resolution

The capture resolution. Must be from [SupportedResolutions](#).

template [CaptureTemplate](#)

The template to use for the captures.

streamUseCase [StreamUseCase](#)

The stream use case for this session. Must be from [SupportedStreamUseCases](#) or [None](#).

textureFormat GraphicsFormat

The output texture format for the converted frames. See [GLESCaptureSession\(Resolution, GraphicsFormat\)](#) for default.

Returns

ValueTask<[GLESCaptureSession](#)>

Returns the session. Check [State](#) (inherited by [GLESCaptureSession](#)) for the state of the session.

Remarks

This initializes a native capture session backed by a SurfaceTexture and a GLES conversion job. The returned session must be started manually (e.g., via its run loop or single-run methods) and disposed using [DisposeAsync\(\)](#).

Exceptions

ObjectDisposedException

CreateOnDemandPipeline(Resolution, StreamUseCase, GraphicsFormat)

Creates an on-demand capture pipeline (session + linked YUV to RGBA converter) for use.

```
public CapturePipeline<OnDemandCaptureSession>? CreateOnDemandPipeline(Resolution
resolution, StreamUseCase streamUseCase = StreamUseCase.None, GraphicsFormat textureFormat
= null)
```

Parameters

resolution Resolution

streamUseCase [StreamUseCase](#)

textureFormat GraphicsFormat

See [YUVConverter\(Resolution, ComputeShaderKernel, GraphicsFormat\)](#) for default texture format.

Returns

[CapturePipeline](#)<[OnDemandCaptureSession](#)>

The created pipeline, or [null](#) if creation failed.

CreateOnDemandSession(Resolution, StreamUseCase)

Creates an on-demand capture session for use.

```
public OnDemandCaptureSession CreateOnDemandSession(Resolution resolution, StreamUseCase
streamUseCase = StreamUseCase.None)
```

Parameters

resolution Resolution

The capture resolution. Must be from [SupportedResolutions](#).

streamUseCase [StreamUseCase](#)

The stream use case for this session. Must be from [SupportedStreamUseCases](#) or [None](#).

Returns

[OnDemandCaptureSession](#)

Returns the session. Check [State](#) (inherited by [OnDemandCaptureSession](#)) for the state of the session.

Remarks

To shut down and dispose the session, use [DisposeAsync\(\)](#) (inherited by [OnDemandCaptureSession](#)).

Exceptions

[ObjectDisposedException](#)

DisposeAsync()

Closes the camera (if not already closed) and releases native resources.

```
public ValueTask DisposeAsync()
```

Returns

[ValueTask](#)

~CameraDevice()

```
protected ~CameraDevice()
```

ThrowIfDisposed()

```
protected override void ThrowIfDisposed()
```

Events

OnDeviceClosed

Invoked when the camera is closed, along with the camera ID.

```
public event Action<string>? OnDeviceClosed
```

Event Type

Action<string>

OnDeviceDisconnected

Invoked when the camera is disconnected, along with the camera ID.

```
public event Action<string>? OnDeviceDisconnected
```

Event Type

Action<string>

OnDeviceErred

Invoked when the camera encounters an error, along with the camera ID.

```
public event Action<string, CameraDevice.ErrorCode>? OnDeviceErred
```

Event Type

Action<string, [CameraDevice.ErrorCode](#)>

OnDeviceOpened

Invoked when the camera is opened, along with the camera ID.

```
public event Action<string>? OnDeviceOpened
```

Event Type

Action<string>

Enum CameraDevice.ErrorCode

Namespace: [Uralstech.UXR.QuestCamera](#)

Error codes from the native plugin.

```
public enum CameraDevice.ErrorCode
```

Fields

CameraAccessError = 1001

The camera is disabled by device policy, has been disconnected, or is being used by a higher-priority camera API client.

CameraDeviceError = 4

The camera device has encountered a fatal error.

CameraDisabled = 3

The camera device could not be opened due to a device policy.

CameraInUse = 1

The camera device is in use already.

CameraServiceError = 5

The camera service has encountered a fatal error.

IllegalArgumentError = 1000

cameraId was null, or the cameraId does not match any currently or previously available camera device.

MaxCamerasInUse = 2

The camera device could not be opened because there are too many other open camera devices.

SecurityError = 1002

The application does not have permission to access the camera.

Unknown = 0

Class CameraDevice.Proxy

Namespace: [Uralstech.UXR.QuestCamera](#)

Java proxy to handle native callbacks.

```
public sealed class CameraDevice.Proxy : AndroidJavaProxy
```

Inheritance

object ← CameraDevice.Proxy

Remarks

All event callbacks will be on a Java thread, and are performance sensitive.

Constructors

Proxy()

```
public Proxy()
```

Events

OnClosed

Invoked when the camera is closed.

```
public event Action? OnClosed
```

Event Type

Action

OnDisconnected

Invoked when the camera is disconnected.

```
public event Action? OnDisconnected
```

Event Type

Action

OnErrorred

Invoked when the camera encounters an error.

```
public event Action<CameraDevice.ErrorCode>? OnErrorred
```

Event Type

Action<[CameraDevice.ErrorCode](#)>

OnOpened

Invoked when the camera is opened.

```
public event Action? OnOpened
```

Event Type

Action

Class CameraInfo

Namespace: [Uralstech.UXR.QuestCamera](#)

Information describing a camera device.

```
public sealed record CameraInfo
```

Inheritance

object ← CameraInfo

Constructors

CameraInfo(AndroidJavaObject)

```
public CameraInfo(AndroidJavaObject obj)
```

Parameters

obj AndroidJavaObject

Fields

CameraId

The device ID of the camera.

```
public readonly string CameraId
```

Field Value

string

Eye

The eye the camera is closest to.

```
public readonly CameraInfo.CameraEye Eye
```

Field Value

[CameraInfo.CameraEye](#)

Intrinsics

The intrinsic data for this camera.

```
public readonly CameraInfo.CameraIntrinsics? Intrinsics
```

Field Value

[CameraInfo.CameraIntrinsics](#)

LensPoseRotation

The orientation of the camera relative to the sensor coordinate system, converted from Android sensor rotation space to Unity rotation space.

```
public readonly Quaternion? LensPoseRotation
```

Field Value

Quaternion?

LensPoseTranslation

The position of the camera's optical center, converted from Android sensor space to Unity space.

```
public readonly Vector3? LensPoseTranslation
```

Field Value

Vector3?

Native

The native CameraCharacteristics object.

```
public readonly AndroidJavaObject Native
```

Field Value

AndroidJavaObject

Source

The source of the camera feed.

```
public readonly CameraInfo.CameraSource Source
```

Field Value

[CameraInfo.CameraSource](#)

SupportedResolutions

The resolutions supported by this camera.

```
public readonly Resolution[] SupportedResolutions
```

Field Value

Resolution[]

SupportedStreamUseCases

The stream use cases supported by this camera, if any.

```
public readonly StreamUseCase[] SupportedStreamUseCases
```

Field Value

[StreamUseCase\[\]](#)

Methods

Dispose()

Performs application-defined tasks associated with freeing, releasing, or resetting unmanaged resources.

```
public void Dispose()
```

Enum CameraInfo.CameraEye

Namespace: [Uralstech.UXR.QuestCamera](#)

The camera eye.

```
public enum CameraInfo.CameraEye
```

Fields

Left = 0

Right = 1

Unknown = -1

Class CameraInfo.CameraIntrinsics

Namespace: [Uralstech.UXR.QuestCamera](#)

Defines the camera's intrinsic properties. All values are in pixels.

```
public sealed record CameraInfo.CameraIntrinsics
```

Inheritance

object ← CameraInfo.CameraIntrinsics

Constructors

CameraIntrinsics(Vector2, Vector2, Vector2, float)

Defines the camera's intrinsic properties. All values are in pixels.

```
public CameraIntrinsics(Vector2 Resolution, Vector2 FocalLength, Vector2 PrincipalPoint,  
float Skew)
```

Parameters

Resolution Vector2

Resolution in pixels.

FocalLength Vector2

Focal length in pixels.

PrincipalPoint Vector2

Principal point in pixels from the image's top-left corner.

Skew float

Skew coefficient for axis misalignment.

Properties

FocalLength

Focal length in pixels.

```
public Vector2 FocalLength { get; init; }
```

Property Value

Vector2

PrincipalPoint

Principal point in pixels from the image's top-left corner.

```
public Vector2 PrincipalPoint { get; init; }
```

Property Value

Vector2

Resolution

Resolution in pixels.

```
public Vector2 Resolution { get; init; }
```

Property Value

Vector2

Skew

Skew coefficient for axis misalignment.

```
public float Skew { get; init; }
```

Property Value

float

Enum CameraInfo.CameraSource

Namespace: [Uralstech.UXR.QuestCamera](#)

The source of the camera feed.

```
public enum CameraInfo.CameraSource
```

Fields

PassthroughRGB = 0

Unknown = -1

Class CapturePipeline<T>

Namespace: [Uralstech.UXR.QuestCamera](#)

A wrapper for a complete capture-conversion pipeline.

```
public sealed class CapturePipeline<T> where T : ContinuousCaptureSession
```

Type Parameters

T

The capture session type.

Inheritance

object ← CapturePipeline<T>

Constructors

CapturePipeline(T, YUVConverter)

```
public CapturePipeline(T session, YUVConverter converter)
```

Parameters

session T

converter [YUVConverter](#)

Fields

Converter

The YUV to RGBA texture converter.

```
public readonly YUVConverter Converter
```

Field Value

[YUVConverter](#)

Session

The capture session.

```
public readonly T Session
```

Field Value

T

Methods

DisposeAsync()

Performs application-defined tasks associated with freeing, releasing, or resetting unmanaged resources asynchronously.

```
public ValueTask DisposeAsync()
```

Returns

ValueTask

A task that represents the asynchronous dispose operation.

Class CaptureSessionBase<TProxy>

Namespace: [Uralstech.UXR.QuestCamera](#)

Base class for all capture session types.

```
public abstract class CaptureSessionBase<TProxy> : StatefulResource where TProxy :  
CaptureSessionBase<TProxy>.ProxyBase
```

Type Parameters

TProxy

The proxy type.

Inheritance

object ← [StatefulResource](#) ← CaptureSessionBase<TProxy>

Derived

[ContinuousCaptureSession](#), [GLESCaptureSession](#)

Inherited Members

[StatefulResource.State](#) , [StatefulResource.WaitForInitialization\(\)](#) ,
[StatefulResource.WaitForInitialization\(TimeSpan, Action, WaitTimeoutMode\)](#) ,
[StatefulResource.WaitForInitializationAsync\(CancellationToken\)](#).

Constructors

CaptureSessionBase(TProxy, AndroidJavaObject)

```
protected CaptureSessionBase(TProxy proxy, AndroidJavaObject native)
```

Parameters

proxy TProxy

native AndroidJavaObject

Fields

NativeProxy

Native callback handler.

```
public readonly TProxy NativeProxy
```

Field Value

TProxy

_disposed

```
protected bool _disposed
```

Field Value

bool

_native

```
protected readonly AndroidJavaObject _native
```

Field Value

AndroidJavaObject

Methods

CloseWork()

```
protected ValueTask CloseWork()
```

Returns

ValueTask

DisposeAsync()

Closes the session (if not already closed) and releases native resources.

```
public virtual ValueTask DisposeAsync()
```

Returns

ValueTask

~CaptureSessionBase()

```
protected ~CaptureSessionBase()
```

ThrowIfDisposed()

```
protected override void ThrowIfDisposed()
```

TryAbortCaptures(out ErrorCode)

Discard all captures currently pending and in-progress as fast as possible.

```
public bool TryAbortCaptures(out CaptureSessionBase<TProxy>.ErrorCode errorCode)
```

Parameters

errorCode [CaptureSessionBase<TProxy>.ErrorCode](#)

Error code if the operation was unsuccessful.

Returns

bool

[true](#) if successful; [false](#) otherwise.

Remarks

This makes the session unusable for the future, so call [DisposeAsync\(\)](#) afterwards.

Exceptions

ObjectDisposedException

Events

OnSessionClosed

Called when the session is closed.

```
public event Action? OnSessionClosed
```

Event Type

Action

OnSessionConfigurationFailed

Called when the session could not be configured.

```
public event Action<CaptureSessionBase<TProxy>.ErrorCode> OnSessionConfigurationFailed
```

Event Type

Action<[CaptureSessionBase](#)<TProxy>.[ErrorCode](#)>

OnSessionConfigured

Called when the session has been configured.

```
public event Action? OnSessionConfigured
```

Event Type

Action

OnSessionRequestFailed

Called when the session request could not be set.

```
public event Action<CaptureSessionBase<TProxy>.ErrorCode>? OnSessionRequestFailed
```

Event Type

Action<[CaptureSessionBase](#)<TProxy>.[ErrorCode](#)>

OnSessionRequestSet

Called when the session request has been set.

```
public event Action? OnSessionRequestSet
```

Event Type

Action

Enum CaptureSessionBase<TProxy>.ErrorCode

Namespace: [Uralstech.UXR.QuestCamera](#)

Error codes from the native plugin.

```
public enum CaptureSessionBase<TProxy>.ErrorCode
```

Fields

CameraAccessError = 1001

In case the camera device is no longer connected or has encountered a fatal error.

ConfigurationFailed = 2000

The session could not be configured.

IllegalArgumentError = 1000

In case the session configuration is invalid, if the captureTemplate is not supported by this device, or other illegal arguments were passed.

IllegalStateError = 1003

In case the camera device or session has been closed.

NativeJobBindingFailed = 3000

The Kotlin session could not bind to its C++ job.

OutOfResourcesError = 1004

If the surface or surfaceTexture for the session could not be created due to an out-of-resources error.

Class CaptureSessionBase<TProxy>.ProxyBase

Namespace: [Uralstech.UXR.QuestCamera](#)

Java proxy to handle native callbacks.

```
public abstract class CaptureSessionBase<TProxy>.ProxyBase : AndroidJavaProxy
```

Inheritance

object ← CaptureSessionBase<TProxy>.ProxyBase

Derived

[ContinuousCaptureSession.Proxy](#), [GLESCaptureSession.Proxy](#)

Remarks

All event callbacks will be on a Java thread, and are performance sensitive.

Constructors

ProxyBase()

```
public ProxyBase()
```

ProxyBase(string)

```
protected ProxyBase(string className)
```

Parameters

className string

Events

OnClosed

Called when the session is closed.

```
public event Action? OnClosed
```

Event Type

Action

OnConfigureFailed

Called when the session could not be configured.

```
public event Action<CaptureSessionBase<TProxy>.ErrorCode>? OnConfigureFailed
```

Event Type

Action<[CaptureSessionBase](#)<TProxy>.[ErrorCode](#)>

OnConfigured

Called when the session has been configured.

```
public event Action? OnConfigured
```

Event Type

Action

OnRequestFailed

Called when the session request could not be set.

```
public event Action<CaptureSessionBase<TProxy>.ErrorCode>? OnRequestFailed
```

Event Type

Action<[CaptureSessionBase](#)<TProxy>.[ErrorCode](#)>

OnRequestSet

Called when the session request has been set.

```
public event Action? OnRequestSet
```

Event Type

Action

Enum CaptureTemplate

Namespace: [Uralstech.UXR.QuestCamera](#)

Capture template to use when recording.

```
public enum CaptureTemplate
```

Fields

Preview = 1

Creates a request suitable for a camera preview window.

Record = 3

Creates a request suitable for video recording.

StillCapture = 2

Creates a request suitable for still image capture.

VideoSnapshot = 4

Creates a request suitable for still image capture while recording video.

Class ComputeShaderKernel

Namespace: [Uralstech.UXR.QuestCamera](#)

Utility class to contain ComputeShader kernel info.

```
[Serializable]  
public sealed class ComputeShaderKernel
```

Inheritance

object ← ComputeShaderKernel

Constructors

ComputeShaderKernel()

```
public ComputeShaderKernel()
```

ComputeShaderKernel(ComputeShader, string)

```
public ComputeShaderKernel(ComputeShader shader, string kernel = "CSMain")
```

Parameters

shader ComputeShader

kernel string

Properties

Index

```
public int Index { get; }
```

Property Value

int

Name

```
public string Name { get; }
```

Property Value

string

Shader

```
public ComputeShader Shader { get; }
```

Property Value

ComputeShader

ThreadGroupSizes

```
public Vector3Int ThreadGroupSizes { get; }
```

Property Value

Vector3Int

Methods

Validate()

```
public bool Validate()
```

Returns

bool

Class ContinuousCaptureSession

Namespace: [Uralstech.UXR.QuestCamera](#)

Manages a camera capture session with a continuous/repeating request.

```
public class ContinuousCaptureSession : CaptureSessionBase<ContinuousCaptureSession.Proxy>
```

Inheritance

object ← [StatefulResource](#) ← [CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)> ←
ContinuousCaptureSession

Derived

[OnDemandCaptureSession](#)

Inherited Members

[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.OnSessionConfigured ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.OnSessionConfigurationFailed ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.OnSessionRequestSet ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.OnSessionRequestFailed ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.OnSessionClosed ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.NativeProxy ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>._native ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>._disposed ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.TryAbortCaptures(out
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.ErrorCode) ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.DisposeAsync() ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.CloseWork() ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.ThrowIfDisposed() , [StatefulResource.State](#) ,
[StatefulResource.WaitForInitialization\(\)](#) ,
[StatefulResource.WaitForInitialization\(TimeSpan, Action, WaitTimeoutMode\)](#) ,
[StatefulResource.WaitForInitializationAsync\(CancellationToken\)](#).

Remarks

This does not do any image processing/conversion on its own, but classes like [YUVConverter](#) can register callbacks to [OnFrameReady](#) to do their own processing of the raw image YUV 4:2:0, BT.601 Full Range data.

Constructors

ContinuousCaptureSession(Resolution)

```
public ContinuousCaptureSession(Resolution resolution)
```

Parameters

resolution Resolution

ContinuousCaptureSession(Resolution, string)

```
protected ContinuousCaptureSession(Resolution resolution, string className)
```

Parameters

resolution Resolution

className string

Delegate ContinuousCaptureSession.OnFrameReadyCallback

Namespace: [Uralstech.UXR.QuestCamera](#)

Processes a frame received from the native capture session.

```
public delegate void ContinuousCaptureSession.OnFrameReadyCallback(nint yBuffer, long yBufferSize, nint uBuffer, nint vBuffer, long uvBufferSize, int yRowStride, int uvRowStride, int uvPixelStride, long timestamp)
```

Parameters

yBuffer nint

The pointer to this frame's Y (luminance) data.

yBufferSize long

The size of the Y buffer in bytes.

uBuffer nint

The pointer to this frame's U (color) data.

vBuffer nint

The pointer to this frame's V (color) data.

uvBufferSize long

The size of the U and V buffers in bytes.

yRowStride int

The size of each row of the image in **yBuffer** in bytes.

uvRowStride int

The size of each row of the image in **uBuffer** and **vBuffer** in bytes.

`uvPixelStride` int

The size of a pixel in a row of the image in `uBuffer` and `vBuffer` in bytes.

`timestamp` long

The timestamp the frame was captured at in nanoseconds.

Class ContinuousCaptureSession.Proxy

Namespace: [Uralstech.UXR.QuestCamera](#)

Java proxy to handle native callbacks.

```
public sealed class ContinuousCaptureSession.Proxy :  
    CaptureSessionBase<ContinuousCaptureSession.Proxy>.ProxyBase
```

Inheritance

object ← [CaptureSessionBase<ContinuousCaptureSession.Proxy>.ProxyBase](#) ←
ContinuousCaptureSession.Proxy

Inherited Members

[CaptureSessionBase<ContinuousCaptureSession.Proxy>.ProxyBase.OnConfigured](#) ,
[CaptureSessionBase<ContinuousCaptureSession.Proxy>.ProxyBase.OnConfigureFailed](#) ,
[CaptureSessionBase<ContinuousCaptureSession.Proxy>.ProxyBase.OnRequestSet](#) ,
[CaptureSessionBase<ContinuousCaptureSession.Proxy>.ProxyBase.OnRequestFailed](#) ,
[CaptureSessionBase<ContinuousCaptureSession.Proxy>.ProxyBase.OnClosed](#)

Remarks

All event callbacks will be on a Java thread, and are performance sensitive.

Constructors

Proxy()

```
public Proxy()
```

Methods

Invoke(string, nint)

```
public override nint Invoke(string methodName, nint javaArgs)
```

Parameters

methodName string

javaArgs nint

Returns

nint

Events

OnFrameReady

Processes a frame received from the native capture session.

```
public event ContinuousCaptureSession.OnFrameReadyCallback? OnFrameReady
```

Event Type

[ContinuousCaptureSession.OnFrameReadyCallback](#)

Remarks

See [ContinuousCaptureSession.OnFrameReadyCallback](#) for parameters.

Class JNIExtensions

Namespace: [Uralstech.UXR.QuestCamera](#)

QOL extensions for the JNI.

```
public static class JNIExtensions
```

Inheritance

object ← JNIExtensions

Methods

UnboxBoolElement(nint, int)

Unboxes a boolean from a native Object array.

```
public static bool UnboxBoolElement(nint args, int index)
```

Parameters

args nint

The native array to take the boolean from.

index int

The index of the boolean object in the native array.

Returns

bool

The unboxed boolean.

UnboxByteBufferElement(nint, int)

Retrieves a ByteBuffer object from a native object array and obtains its direct memory address.

```
public static (nint obj, nint ptr) UnboxByteBufferElement(nint args, int index)
```

Parameters

args nint

JNI object array containing the ByteBuffer.

index int

Index of the ByteBuffer within the array.

Returns

(nint obj, nint ptr)

A tuple containing the local JNI reference to the ByteBuffer, and the pointer to its direct buffer memory.

UnboxIntElement(nint, int)

Unboxes an integer from a native Object array.

```
public static int UnboxIntElement(nint args, int index)
```

Parameters

args nint

The native array to take the integer from.

index int

The index of the integer object in the native array.

Returns

int

The unboxed integer.

UnboxLongElement(nint, int)

Unboxes a long from a native Object array.

```
public static long UnboxLongElement(nint args, int index)
```

Parameters

args nint

The native array to take the long from.

index int

The index of the long object in the native array.

Returns

long

The unboxed long.

UnboxStringElement(nint, int)

Unboxes a string from a native Object array.

```
public static string? UnboxStringElement(nint args, int index)
```

Parameters

args nint

The native array to take the string from.

index int

The index of the string object in the native array.

Returns

string

The unboxed string.

Class OnDemandCaptureSession

Namespace: [Uralstech.UXR.QuestCamera](#)

Manages an on-demand, explicit capture session.

```
public sealed class OnDemandCaptureSession : ContinuousCaptureSession
```

Inheritance

object ← [StatefulResource](#) ← [CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)> ← [ContinuousCaptureSession](#) ← OnDemandCaptureSession

Inherited Members

[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.OnSessionConfigured ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.OnSessionConfigurationFailed ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.OnSessionRequestSet ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.OnSessionRequestFailed ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.OnSessionClosed ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.NativeProxy ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.TryAbortCaptures(out [CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.ErrorCode) ,
[CaptureSessionBase](#) <[ContinuousCaptureSession.Proxy](#)>.DisposeAsync() , [StatefulResource.State](#) ,
[StatefulResource.WaitForInitialization\(\)](#) ,
[StatefulResource.WaitForInitialization\(TimeSpan, Action, WaitTimeoutMode\)](#) ,
[StatefulResource.WaitForInitializationAsync\(CancellationToken\)](#).

Remarks

This does not do any image processing/conversion on its own, but classes like [YUVConverter](#) can register callbacks to [OnFrameReady](#) to do their own processing of the raw image YUV 4:2:0, BT.601 Full Range data.

Constructors

OnDemandCaptureSession(Resolution)

```
public OnDemandCaptureSession(Resolution resolution)
```

Parameters

resolution Resolution

Methods

TryRequestCapture(out ErrorCode, CaptureTemplate)

Requests a new capture from the session.

```
public bool TryRequestCapture(out  
    CaptureSessionBase<ContinuousCaptureSession.Proxy>.ErrorCode errorCode, CaptureTemplate  
    template = CaptureTemplate.StillCapture)
```

Parameters

errorCode [CaptureSessionBase<ContinuousCaptureSession.Proxy>.ErrorCode](#)

Error code if the operation was unsuccessful.

template [CaptureTemplate](#)

The capture template to use for the capture.

Returns

bool

[true](#) if successful; [false](#) otherwise.

Exceptions

ObjectDisposedException

Enum PCASupport

Namespace: [Uralstech.UXR.QuestCamera](#)

```
public enum PCASupport
```

Fields

Supported = 1

PCA API is supported.

Meta XR Core SDK on Quest 3/3S with Horizon OS v74+.

Unknown = 0

Support status cannot be determined.

Returned when the Meta XR Core SDK is not available.

Unsupported = 2

PCA API is not supported.

Non-Android device, or Meta XR Core SDK on unsupported devices or OS versions.

Class QuestCameraManager

Namespace: [Uralstech.UXR.QuestCamera](#)

Entry point for the native Camera2 plugin.

```
public sealed class QuestCameraManager : DontCreateNewSingleton<QuestCameraManager>
```

Inheritance

object ← QuestCameraManager

Fields

AvatarCameraPermission

Meta Quest Avatar Camera API permission string.

```
public const string AvatarCameraPermission = "android.permission.CAMERA"
```

Field Value

string

ConversionKernel

The shader and kernel to use for YUV 4:2:0 to RGBA conversion.

```
public ComputeShaderKernel ConversionKernel
```

Field Value

[ComputeShaderKernel](#)

HeadsetCameraPermission

Meta Quest Passthrough Camera API permission string.

```
public const string HeadsetCameraPermission = "horizonos.permission.HEADSET_CAMERA"
```

Field Value

string

Properties

Cameras

A managed, cached array of available cameras and their characteristics.

```
public IReadOnlyList<CameraInfo> Cameras { get; }
```

Property Value

IReadOnlyList<[CameraInfo](#)>

Support

Tries to get the runtime's support for the Passthrough Camera Access and Camera2 APIs.

```
public static PCASupport Support { get; }
```

Property Value

[PCASupport](#)

Methods

Awake()

```
protected override void Awake()
```

GetDevices()

Gets the IDs and intrinsics of all connected camera devices.

```
public CameraInfo[] GetDevices()
```

Returns

[CameraInfo\[\]](#)

OpenCamera(string)

Opens a camera device for use.

```
public CameraDevice OpenCamera(string cameraId)
```

Parameters

cameraId string

The ID of the camera to open.

Returns

[CameraDevice](#)

The camera device. Check [State](#) (inherited by [CameraDevice](#)) for the state of the device.

Remarks

Once you have finished using the camera, close and dispose of it using [DisposeAsync\(\)](#).

OpenCamera(CameraInfo)

Opens a camera device for use.

```
public CameraDevice OpenCamera(CameraInfo cameraInfo)
```

Parameters

cameraInfo [CameraInfo](#)

Returns

[CameraDevice](#)

The camera device. Check [State](#) (inherited by [CameraDevice](#)) for the state of the device.

Remarks

Once you have finished using the camera, close and dispose of it using [DisposeAsync\(\)](#).

RefreshDevices()

Refreshes cached camera device information.

```
public void RefreshDevices()
```

TryGetDevice(CameraEye, out CameraInfo?)

Finds a camera device by its corresponding eye.

```
public bool TryGetDevice(CameraInfo.CameraEye eye, out CameraInfo? cameraInfo)
```

Parameters

eye [CameraInfo.CameraEye](#)

cameraInfo [CameraInfo](#)

Returns

bool

Enum ResourceState

Namespace: [Uralstech.UXR.QuestCamera](#)

State of a Camera2 resource.

```
public enum ResourceState
```

Fields

Initializing = 0

Resource is initializing.

Invalid = 2

Resource failed with an error, was disconnected or is being/was closed normally.

Valid = 1

Resource is open and ready.

Class StatefulResource

Namespace: [Uralstech.UXR.QuestCamera](#)

```
public abstract class StatefulResource
```

Inheritance

object ← StatefulResource

Derived

[CameraDevice](#), [CaptureSessionBase<TProxy>](#)

Properties

State

The state of this resource.

```
public ResourceState State { get; protected set; }
```

Property Value

[ResourceState](#)

Remarks

This does NOT indicate disposal status, and is just an indicator for if you can use this resource.

Methods

ThrowIfDisposed()

```
protected abstract void ThrowIfDisposed()
```

WaitForInitialization()

Waits until the resource opens or errs out.

```
public WaitUntil WaitForInitialization()
```

Returns

WaitUntil

Exceptions

ObjectDisposedException

WaitForInitialization(TimeSpan, Action, WaitTimeoutMode)

Waits until the resource opens or errs out.

```
public WaitUntil WaitForInitialization(TimeSpan timeout, Action onTimeout, WaitTimeoutMode timeoutMode = null)
```

Parameters

timeout TimeSpan

Maximum time to wait.

onTimeout Action

The action to perform when the **timeout** is reached.

timeoutMode WaitTimeoutMode

Mode in which to measure time to determine **timeout**.

Returns

WaitUntil

Exceptions

ObjectDisposedException

WaitForInitializationAsync(CancellationToken)

Waits until the resource opens or errs out.

```
public Task<bool> WaitForInitializationAsync(CancellationToken token = default)
```

Parameters

token CancellationToken

Returns

Task<bool>

[true](#) if opened successfully, [false](#) otherwise.

Exceptions

ObjectDisposedException

Enum StreamUseCase

Namespace: [Uralstech.UXR.QuestCamera](#)

Stream Use Cases are a way to improve the performance of Camera2 capture sessions. They give the hardware device more information to tune parameters, which provides a better camera experience for your specific task.

```
public enum StreamUseCase : long
```

Fields

Default = 0

Default stream use case.

None = -1

Does not set any stream use case. Use this if the device does not support stream use cases or you're unsure of support.

Preview = 1

Live stream shown to the user.

PreviewVideoStill = 4

One single stream used for combined purposes of preview, video, and still capture.

StillCapture = 2

Still photo capture.

VideoCall = 5

Long-running video call optimized for both power efficiency and video quality.

VideoRecord = 3

Recording video clips.

Class YUVConverter

Namespace: [Uralstech.UXR.QuestCamera](#)

Converts raw camera capture session frames to Unity-supported RGBA.

```
public sealed class YUVConverter
```

Inheritance

object ← YUVConverter

Constructors

YUVConverter(Resolution, GraphicsFormat)

Creates a new converter with the shader and kernel described in the scene instance of [QuestCamera Manager](#).

```
public YUVConverter(Resolution resolution, GraphicsFormat textureFormat = null)
```

Parameters

resolution Resolution

textureFormat GraphicsFormat

If not specified, uses equivalent of RenderTextureFormat.ARGB32.

YUVConverter(Resolution, ComputeShaderKernel, GraphicsFormat)

```
public YUVConverter(Resolution resolution, ComputeShaderKernel kernel, GraphicsFormat textureFormat = null)
```

Parameters

resolution Resolution

kernel [ComputeShaderKernel](#)

textureFormat GraphicsFormat

If not specified, uses equivalent of RenderTextureFormat.ARGB32.

Fields

Texture

The output texture with converted frames.

```
public readonly RenderTexture Texture
```

Field Value

RenderTexture

Properties

CaptureTimestamp

The capture timestamp of the last processed frame.

```
public long CaptureTimestamp { get; }
```

Property Value

long

HasNewFrame

[true](#)  if a capture was processed this frame; [false](#)  otherwise.

```
public bool HasNewFrame { get; }
```

Property Value

bool

ShaderKernel

The shader used for conversion.

```
public ComputeShaderKernel ShaderKernel { get; set; }
```

Property Value

[ComputeShaderKernel](#)

Methods

Dispose()

Performs application-defined tasks associated with freeing, releasing, or resetting unmanaged resources.

```
public void Dispose()
```

OnFrameReady(nint, long, nint, nint, long, int, int, int, long)

Processes a frame received from the native capture session.

```
public void OnFrameReady(nint yBuffer, long yBufferSize, nint uBuffer, nint vBuffer, long uvBufferSize, int yRowStride, int uvRowStride, int uvPixelStride, long timestamp)
```

Parameters

yBuffer nint

The pointer to this frame's Y (luminance) data.

yBufferSize long

The size of the Y buffer in bytes.

uBuffer nint

The pointer to this frame's U (color) data.

vBuffer nint

The pointer to this frame's V (color) data.

uvBufferSize long

The size of the U and V buffers in bytes.

yRowStride int

The size of each row of the image in **yBuffer** in bytes.

uvRowStride int

The size of each row of the image in **uBuffer** and **vBuffer** in bytes.

uvPixelStride int

The size of a pixel in a row of the image in **uBuffer** and **vBuffer** in bytes.

timestamp long

The timestamp the frame was captured at in nanoseconds.

Events

OnFrameProcessed

Callback for when a frame has been dispatched for conversion, with the frame texture and capture timestamp.

```
public event Action<RenderTexture, long>? OnFrameProcessed
```

Event Type

Action<RenderTexture, long>

Namespace Uralstech.UXR.QuestCamera.GLES

Classes

[GLESAPI](#)

Exposes the native GLES Texture Conversion API.

[GLESCaptureSession](#)

Manages a camera capture session with a repeating request, but supports both repeating and on-demand conversion.

[GLESCaptureSession.Proxy](#)

Java proxy to handle native callbacks.

Structs

[RenderJobDisposeData](#)

Data for [Dispose](#).

[RenderJobRunData](#)

Data for [Run](#).

[RenderJobSetupData](#)

Data for [Setup](#).

Enums

[RenderJobEvent](#)

IDs of all Render Job events.

Delegates

[RenderJobDisposeData.Callback](#)

Callback for when the job is disposed or the process fails.

[RenderJobRunData.Callback](#)

Callback for when the job finishes rendering or the process fails.

[RenderJobSetupData.Callback](#)

Callback for when the job is setup or the process fails.

Class GLESAPI

Namespace: [Uralstech.UXR.QuestCamera.GLES](#)

Exposes the native GLES Texture Conversion API.

```
public static class GLESAPI
```

Inheritance

object ← GLESAPI

Fields

DisposeCallbacksRegistry

Registry of job disposal callbacks. This is a single-call registry, i.e. the entry is removed after the callback occurs.

```
public static readonly ConcurrentDictionary<uint, RenderJobDisposeData.Callback>  
DisposeCallbacksRegistry
```

Field Value

ConcurrentDictionary<uint, [RenderJobDisposeData.Callback](#)>

RenderJobDisposeCallbackPtr

Static marshalled pointer to [OnRenderJobDispose\(bool, uint\)](#).

```
public static readonly nint RenderJobDisposeCallbackPtr
```

Field Value

nint

RenderJobRunCallbackPtr

Static marshalled pointer to [OnRenderJobRun\(long, uint\)](#).

```
public static readonly nint RenderJobRunCallbackPtr
```

Field Value

nint

RenderJobSetupCallbackPtr

Static marshalled pointer to [OnRenderJobSetup\(uint, uint\)](#).

```
public static readonly nint RenderJobSetupCallbackPtr
```

Field Value

nint

RunCallbacksRegistry

Registry of job run callbacks.

```
public static readonly ConcurrentDictionary<uint, RenderJobRunData.Callback>  
RunCallbacksRegistry
```

Field Value

ConcurrentDictionary<uint, [RenderJobRunData.Callback](#)>

SetupCallbacksRegistry

Registry of job setup callbacks. This is a single-call registry, i.e. the entry is removed after the callback occurs.

```
public static readonly ConcurrentDictionary<uint, RenderJobSetupData.Callback>  
SetupCallbacksRegistry
```

Field Value

ConcurrentDictionary<uint, [RenderJobSetupData.Callback](#)>

Methods

OnRenderJobDispose(bool, uint)

Callback for when the job is disposed or the process fails.

```
public static void OnRenderJobDispose(bool result, uint renderTextureId)
```

Parameters

result bool

Whether the operation was a success or not.

renderTextureId uint

[RenderTextureId](#), for lookup.

OnRenderJobRun(long, uint)

Callback for when the job finishes rendering or the process fails.

```
public static void OnRenderJobRun(long timestamp, uint renderTextureId)
```

Parameters

timestamp long

The timestamp returned by the SurfaceTexture, or -1 if the operation failed.

renderTextureId uint

[RenderTextureId](#), for lookup.

OnRenderJobSetup(uint, uint)

Callback for when the job is setup or the process fails.

```
public static void OnRenderJobSetup(uint nativeTextureId, uint renderTextureId)
```

Parameters

nativeTextureId uint

renderTextureId uint

[RenderTextureId](#), for lookup.

getGLESTextureConverterJobEvent()

Returns a pointer to the native render job management function.

```
public static extern nint getGLESTextureConverterJobEvent()
```

Returns

nint

Class GLESCaptureSession

Namespace: [Uralstech.UXR.QuestCamera.GLES](#)

Manages a camera capture session with a repeating request, but supports both repeating and on-demand conversion.

```
public sealed class GLESCaptureSession : CaptureSessionBase<GLESCaptureSession.Proxy>
```

Inheritance

object ← [StatefulResource](#) ← [CaptureSessionBase](#)<[GLESCaptureSession.Proxy](#)> ← GLESCaptureSession

Inherited Members

[CaptureSessionBase](#)<[GLESCaptureSession.Proxy](#)>.OnSessionConfigured ,
[CaptureSessionBase](#)<[GLESCaptureSession.Proxy](#)>.OnSessionConfigurationFailed ,
[CaptureSessionBase](#)<[GLESCaptureSession.Proxy](#)>.OnSessionRequestSet ,
[CaptureSessionBase](#)<[GLESCaptureSession.Proxy](#)>.OnSessionRequestFailed ,
[CaptureSessionBase](#)<[GLESCaptureSession.Proxy](#)>.OnSessionClosed ,
[CaptureSessionBase](#)<[GLESCaptureSession.Proxy](#)>.NativeProxy ,
[CaptureSessionBase](#)<[GLESCaptureSession.Proxy](#)>.TryAbortCaptures(out
[CaptureSessionBase](#)<[GLESCaptureSession.Proxy](#)>.ErrorCode) ,
[StatefulResource.State](#) , [StatefulResource.WaitForInitialization\(\)](#) ,
[StatefulResource.WaitForInitialization\(TimeSpan, Action, WaitTimeoutMode\)](#) ,
[StatefulResource.WaitForInitializationAsync\(CancellationToken\)](#).

Remarks

Texture conversion is done in native OpenGL-ES.

Constructors

GLESCaptureSession(Resolution, GraphicsFormat)

```
public GLESCaptureSession(Resolution resolution, GraphicsFormat textureFormat = null)
```

Parameters

resolution Resolution

textureFormat GraphicsFormat

If not specified, uses equivalent of RenderTextureFormat.ARGB32.

Fields

Texture

The output texture with converted frames.

```
public readonly Texture2D Texture
```

Field Value

Texture2D

Properties

CaptureTimestamp

The capture timestamp of the last processed frame.

```
public long CaptureTimestamp { get; }
```

Property Value

long

HasNewFrame

[true](#) if a capture was processed this frame; [false](#) otherwise.

```
public bool HasNewFrame { get; }
```

Property Value

bool

Methods

DisposeAsync()

Closes the session (if not already closed) and releases native resources.

```
public override ValueTask DisposeAsync()
```

Returns

ValueTask

ProcessSingleFrameAsync(CancellationToken)

Processes a single frame and returns the result.

```
public ValueTask<(long, Texture2D)> ProcessSingleFrameAsync(CancellationToken token  
= default)
```

Parameters

token CancellationToken

Returns

ValueTask<(long, Texture2D)>

Capture timestamp and updated texture. Timestamp will be -1 if the capture could not be processed.

Exceptions

InvalidOperationException

Thrown if continuous processing is active.

ObjectDisposedException

TimeoutException

SetupJobAsync()

Registers the texture and creates a job in the native C++ manager.

```
public ValueTask<uint> SetupJobAsync()
```

Returns

ValueTask<uint>

The ID of the source texture created for the job, which the capture session will render to, or 0 if the operation failed.

StartContinuousProcessing(int)

Starts continuous frame processing.

```
public void StartContinuousProcessing(int maxFramerate = 60)
```

Parameters

maxFramerate int

The maximum rate at which frames will be processed by the GLES pipeline.

Exceptions

InvalidOperationException

Thrown if continuous processing is already active.

Events

OnFrameProcessed

Callback for when a frame has been processed, with the frame texture and capture timestamp.

```
public event Action<Texture2D, long>? OnFrameProcessed
```

Event Type

Action<Texture2D, long>

Class GLESCaptureSession.Proxy

Namespace: [Uralstech.UXR.QuestCamera.GLES](#)

Java proxy to handle native callbacks.

```
public sealed class GLESCaptureSession.Proxy :  
    CaptureSessionBase<GLESCaptureSession.Proxy>.ProxyBase
```

Inheritance

object ← [CaptureSessionBase<GLESCaptureSession.Proxy>.ProxyBase](#) ← GLESCaptureSession.Proxy

Inherited Members

[CaptureSessionBase<GLESCaptureSession.Proxy>.ProxyBase.OnConfigured](#) ,
[CaptureSessionBase<GLESCaptureSession.Proxy>.ProxyBase.OnConfigureFailed](#) ,
[CaptureSessionBase<GLESCaptureSession.Proxy>.ProxyBase.OnRequestSet](#) ,
[CaptureSessionBase<GLESCaptureSession.Proxy>.ProxyBase.OnRequestFailed](#) ,
[CaptureSessionBase<GLESCaptureSession.Proxy>.ProxyBase.OnClosed](#)

Remarks

All event callbacks will be on a Java thread, and are performance sensitive.

Struct RenderJobDisposeData

Namespace: [Uralstech.UXR.QuestCamera.GLES](#)

Data for [Dispose](#).

```
public readonly struct RenderJobDisposeData
```

Constructors

RenderJobDisposeData(uint, nint)

```
public RenderJobDisposeData(uint renderTextureId, nint onDone)
```

Parameters

renderTextureId uint

onDone nint

Fields

OnDone

Method with signature of [RenderJobDisposeData.Callback](#).

```
public readonly nint OnDone
```

Field Value

nint

RenderTextureId

The Job's ID and render target.

```
public readonly uint RenderTextureId
```

Field Value

uint

Delegate RenderJobDisposeData.Callback

Namespace: [Uralstech.UXR.QuestCamera.GLES](#)

Callback for when the job is disposed or the process fails.

```
public delegate void RenderJobDisposeData.Callback(bool result, uint renderTextureId)
```

Parameters

result bool

Whether the operation was a success or not.

renderTextureId uint

[RenderTextureId](#), for lookup.

Enum RenderJobEvent

Namespace: [Uralstech.UXR.QuestCamera.GLES](#)

IDs of all Render Job events.

```
public enum RenderJobEvent
```

Fields

Dispose = 2

Disposes the native texture and cleans up the registered job.

Run = 3

Runs a job.

Setup = 1

Sets up a native texture to convert from, and creates a registerable job for the capture session.

Struct RenderJobRunData

Namespace: [Uralstech.UXR.QuestCamera.GLES](#)

Data for [Run](#).

```
public readonly struct RenderJobRunData
```

Constructors

RenderJobRunData(uint, nint)

```
public RenderJobRunData(uint renderTextureId, nint onDone)
```

Parameters

renderTextureId uint

onDone nint

Fields

OnDone

Method with signature of [RenderJobRunData.Callback](#).

```
public readonly nint OnDone
```

Field Value

nint

RenderTextureId

The Job's ID and render target.

```
public readonly uint RenderTextureId
```

Field Value

uint

Delegate RenderJobRunData.Callback

Namespace: [Uralstech.UXR.QuestCamera.GLES](#)

Callback for when the job finishes rendering or the process fails.

```
public delegate void RenderJobRunData.Callback(long timestamp, uint renderTextureId)
```

Parameters

timestamp long

The timestamp returned by the SurfaceTexture, or -1 if the operation failed.

renderTextureId uint

[RenderTextureId](#), for lookup.

Struct RenderJobSetupData

Namespace: [Uralstech.UXR.QuestCamera.GLES](#)

Data for [Setup](#).

```
public readonly struct RenderJobSetupData
```

Constructors

RenderJobSetupData(uint, int, int, nint)

```
public RenderJobSetupData(uint renderTextureId, int width, int height, nint onDone)
```

Parameters

renderTextureId uint

width int

height int

onDone nint

Fields

Height

The height of [RenderTextureId](#).

```
public readonly int Height
```

Field Value

int

OnDone

Method with signature of [RenderJobSetupData.Callback](#).

```
public readonly nint OnDone
```

Field Value

nint

RenderTextureId

The GLES ID of the texture which will be the Job's ID and render target.

```
public readonly uint RenderTextureId
```

Field Value

uint

Width

The width of [RenderTextureId](#).

```
public readonly int Width
```

Field Value

int

Delegate RenderJobSetupData.Callback

Namespace: [Uralstech.UXR.QuestCamera.GLES](#)

Callback for when the job is setup or the process fails.

```
public delegate void RenderJobSetupData.Callback(uint nativeTexture, uint renderTextureId)
```

Parameters

nativeTexture uint

The created texture, or 0 if the operation failed.

renderTextureId uint

[RenderTextureId](#), for lookup.