
Notes on Vases

N. E. Davis ~lagrev-nocfep
Zorp Corp

Abstract

This paper explores the concept of “vases” in the Hoon programming language, an approach to managing type dynamically in a static environment. Vases find applications throughout Nock solid-state systems, including compilation, metaprogramming, and dynamic code evaluation. We will explore how vases are constructed, manipulated, and utilized in the context of Nock and Hoon, providing a foundation for understanding their role in Urbit’s programming ecosystem.

Contents

1	Introduction	2
2	Hoon Compilation in a Nutshell	3
3	Vases	5
3.1	Hoon Type	7
3.2	Producing Vases	9
3.3	Eliminating Vases	11
4	Vase Algebra	11
4.1	+slop	12
4.2	+slap	13
4.3	Supplemental Operators	14

Manuscript submitted for review.

Address author correspondence to ~lagrev-nocfep.

25	5 Applications of Vase Mode	15
26	5.1 Type Manipulation	15
27	5.2 Code Evaluation	16
28	5.3 Metacircular Interpretation	17
29	5.4 Persistent Code Artifacts	17
30	5.5 System Upgrades	17
31	6 Beyond the Vase Algebra	18
32	6.1 Comparisons	19
33	6.1.1 Python/CPython	19
34	6.1.2 Assembly Language	19
35	6.1.3 Lisp Quote	19
36	6.1.4 Haskell Dynamic	21
37	6.1.5 Untyped Virtual Machines	21
38	7 Conclusion	22

1 Introduction

Nock is homoiconic and only recognizes natural numbers, “atoms” (nonnegative integers, $\mathbb{Z}^*$) and pairs (“cells”) as values. Although Nock is untyped, it is desirable to build typed languages targeting this instruction set architecture.

The Hoon programming language solves this by using a pair of a type description and a noun, or raw Nock value. In some ways like a macro over Nock, Hoon introduces static typing (thus extending from Nock’s exclusive use of natural numbers) and other design patterns convenient to programmers.¹ Most of the time, developers work in “static Hoon”, which maintains guard rails and is easier to reason about. However, a more flexible and powerful modality is available. The type description, or type of the subject, contains information like variable names, variable types, aliases, and the overall structure of the execution environment. Essentially, it acts as a strictly defined metadata reference set for the associated Nock value and its execution environment. We call such a pair of

¹The Jock language does not directly expose vases for utilization, but does utilize them inside the compiler, written in Hoon.

type and value a “vase”.² Most commonly used in building code and in manipulating vanes, vases permit the developer to edit the type and the value directly. Essentially, a value can be lifted from a static Hoon context into a dynamic vase context, then reduced back to static Hoon or untyped Nock.

Vase mode, then, describes a design pattern for lifting statically-typed values from their normal compile-time world into a dynamically-typed operating environment, which is then used to produced valid and validated Nock ISA code while enforcing the Hoon language type constraints. Vase mode is used in building compilers, interpreters, and code imports. Since code is transmitted as a noun value to be built and executed on the receiver’s side, this also affects hotloading code and system upgrades. A vase algebra describes how to combine the type subject information and the associated value information, as in an import or a REPL. This lets Hoon have human-legible affordances in type and validation, while retaining a simple target ISA for execution, code proving, and optimized execution.³

2 Hoon Compilation in a Nutshell

Before we can really grasp the utility of vase mode, we require a brief diversion into how Hoon code is actually compiled and built into Nock. That is, given a Hoon expression, how do we get it into a form that can be executed by the Nock virtual machine? A number of convenience functions wrap various parts of the Hoon compiler, which primarily consists of `+vast` and `+ut`.

Text→Nock . To evaluate a string containing Hoon directly, one merely needs to `+make the cord (text atom)`.⁴

²Different interpreters and compilers call this pair different things. For instance, CPython calls this a “boxed value” and keeps the value as a pair of datum and type tag.

³A vase visualization tool has been produced by `~migrev-dolseg`, available at <https://hawk.computer>.

⁴Note that Nock instructions are marked as constants with % for legibility, but the value is simply the associated integer.

```

86
87 > (make '~[1 2 3]')
88 [%1 p=[1 2 3 0]]
89
90 > (make '+= (a=5 -)')
91 [%8 p=[%1 p=5] q=[%0 p=2]]
92

```

Since `+make` assumes no subject, all information must be provided in the expression. Furthermore, although not present explicitly, `+make` utilizes an internal `$type` of `%noun`.

```

96
97 > (make '- ')
98 [%0 p=2]
99
100 > .*([1 2] (make '- '))
101 1
102

```

Text→AST→Nock . The simplified high-level lifecycle of Hoon code sees it go from text to an abstract syntax tree (AST) and thence to executable Nock.⁵

To convert Hoon text from a `cord` to an AST, use `+ream`. The AST is a tree of Hoon expressions marked by rune and components such as wings (lookup names in the subject) and atoms or cells.

```

110
111 > (ream '(add 1 2)')
112 [%cncl p=[%wing p=[%add]] q=[[%sand p=%ud q=1]
113                               [%sand p=%ud q=2]]]
114
115 > (ream '-: !>(5)')
116 [%tsgl p=[%cnts p=[[%y p=2]] q=[[%zpr p=[%sand p=%ud q=5]]]
117

```

A Hoon AST is properly a `$hoon`, which is a complicated type union over all of the kinds of things that Hoon knows something to be able to be.⁶ Sugar runes can be represented simply or reparsed by `+open: ap` into a more fundamental form. However, at this point no desugaring has taken place; equivalent forms may still have different AST representations as `$hoon`:

⁵In practice, the text is commonly derived from a file via the `%hoon` mark.

⁶The relevant code may be found in `/sys/hoon`.

```

125 > (ream '~[1 2 3]')
126 [%clsg p=~[%sand p=%ud q=1] [%sand p=%ud q=2] [%sand p=%ud q=3]]]
127
128 > (ream '[1 2 3 ~]')
129 [%cltr p=~[%sand p=%ud q=1] [%sand p=%ud q=2] [%sand p=%ud q=3] [%bus

```

130 Hoon supplements “pure” values with metadata to establish
 131 context for the values and enforce its notion of type.

132 Given a reduced Hoon AST, `+mint:ut` function compiles it
 133 into Nock code. `+mint:ut` parses from a Hoon AST into a pair
 134 of the type and the Nock.⁷

```

135 > (~(mint ut %noun) %noun (ream '~[1 2 3]'))
136 [#t/[@ud @ud @ud %~] q=[%1 p=[1 2 3 0]]]

```

137 While there is much to say about `+mint`, for our purposes we
 138 simply note that it operates on each tag in an AST to convert it
 139 recursively to `$nock`.⁸

140 3 Vases

141 A `$vase` is a pair of `$type` and value, where `$type` defines
 142 the Hoon type set and the tail contains the actual data. (Vases
 143 could be treated more generally than simply Hoon types, but
 144 in practice are used only with Hoon, so the type data structure
 145 will become relevant.)

146 Vases received bare mention in the 2016 Urbit whitepaper
 147 (`~sorreg-namtyv` et al., 2016). They were noted merely as hav-
 148 ing the property of allowing a statically typed compiler to op-
 149 erate on dynamically typed runtime code—and thus, to reload
 150 portions of the kernel from source while running.

151 However, vases are critically important to practical
 152 code composition and execution on Urbit and NockApp as
 153 functional-as-in-paradigm execution environments:

⁷One simple approach to understand this part of the Hoon compiler back-
 end is to look at the 2013 Hoon compiler, which presents a relatively unclut-
 tered version.

⁸Nock code is not executed simply in either of the primary runtimes, Vere
 or NockVM (`f/k/a` Sword, née Ares). Instead it is converted into a bytecode for
 execution.

Everything about a scope, including name bindings, aliases, and docstrings, is stored in the subject's type. This allows Hoon's compilation discipline to be similarly minimal: the compiler is a function from subject type and Hoon source to product type and compiled Nock. Running this Nock against a value of the subject type produces a vase of the result. It's hard to imagine a more streamlined formalism for compilation. (Blackman2020, Blackman2020)

That is, vases enable the end developer to work at a higher level of abstraction than raw typed code and data would itself make straightforward in a statically typed functional programming environment.

Hoon's type information captures both the set of nouns valid for a particular piece of data and the subject, or environment to which the value has access. For instance, a `%face` is a lookup index into the subject for a value with an associated name.

Vases are frequently used to compile and execute Hoon code, but are also used to store typed data. Since Nock is ultimately homoiconic, any arbitrary noun may be either executable code or static data. A vase preserves the type information associated with the noun, making it possible to reconstruct it in regular (static) Hoon. For instance, as a security mechanism, "live code" is never transmitted over the wire between machines. Instead, the type and value are sent, and the recipient compiles the noun into executable code.

What vases permit over raw Nock manipulations therefore includes:

1. allowing types to be straightforwardly combined
2. permitting code evaluation (Lisp `eval`)
3. facilitating metacircular interpretation
4. managing persistent code artifacts

5. building and running system upgrades while running live (i.e. hotswapping code)

Urbit's application architecture has a persistent solid-state kernel which runs user applications in a sort of sandbox. They cannot use vase mode directly, but they are built and modified using vase mode. In particular, library imports and the REPL interface both use vase mode extensively.

Likewise, NockApp supplies a kernel wrapping specialized I/O drivers for the executable Nock, produced by Hoon or Jock. Vases are generally used for building code sent as nouns over the wire and in the compilers.

3.1 Hoon Type

The formal definitions of `$vase` and `$type` are as follows:

```

+$ vase [p=type q=*]
+$ type $~ %noun
      $@ $? %noun
              %void
      ==
      $% [%atom p=term q=(unit @)]
          [%cell p=type q=type]
          [%core p=type q=coil]
          [%face p=$@(term tune) q=type]
          [%fork p=(set type)]
          [%hint p=(pair type note) q=type]
          [%hold p=type q=hoon]
      ==

```

- `%noun` is the superset of all nouns.
- `%void` is the empty noun, but won't occur in results (i.e. a compiler affordance).
- `%atom` spans the set of all atoms.
- `%cell` contains ordered pairs.

The other types are more complex:

- 222 • %core is the descriptor type for a core. Besides the
223 \$type, it uses a \$coil, which is a tuple of variance in-
224 formation, context, and chapters (limbs).
- 225 • %face spans the same set as nouns but includes a face.
- 226 • %fork is a union, or choice over options.
- 227 • %hint is an annotation for the compiler (Nock Eleven).
- 228 • %hold types are lazily evaluated, such as a recursive type
229 (like the +list mold builder).
 - 230 – %hold types are why the compiler can have trouble
231 with lists at runtime, such as needing to distinguish
232 a lest or the TMI problem with +snag &c.
 - 233 – A %hold type is a “finite subtype” of an infinite
234 type. Hoon doesn’t actually know about these di-
235 rectly, just in that it can be lazy about evaluating
236 recursions.
 - 237 – They result from arms in cores because the hoon
238 of the arm is played against the core type as the
239 subject type to get the result. This permits poly-
240 morphism, since the core can be modified to have
241 a sample of a different type.

242 One can “evaluate” a hold by asking the compiler
243 to “play” the hoon against the subject type, mean-
244 ing to infer what type of value would result from
245 running that hoon against a value of the subject
246 type. For a recursive type, this result type refers to
247 the same hold, usually in one or more of the cases
248 of a %fork. (~rovnyis-ricfer, personal communi-
249 cation)

250 For instance, let’s evaluate a value of the type (list @ud)
251 using Hoon:

```
252 > =a `(list @ud)`~[1 2 3]
```

253
254

```

255 > !>(a)
256 [#t/it(@ud) q=[1 2 3 0]]
257
258 > -<: !>(a)
259 %hold
260
261 > -<: !>(?~(a 0 a))
262 %fork
263
264 > ->-: !>(?~(a 0 a))
265 #t/@ud
266 [%atom p=%ud q=~]
267
268 > ->+<: !>(?~(a 0 a))
269 l=[#t/[i=@ud t=it(@ud)] l=~ r=~]
270

```

271 (As an aside, while `+vase` is a reasonable name for a thing
 272 and the thing that shapes it, the original term was `+vise`,
 273 which also works in this capacity.)

274 3.2 Producing Vases

275 While vases can be constructed manually, Hoon provides sev-
 276 eral affordances for producing vases that are less error-prone
 277 and more convenient.

278 The most common way to produce a vase is to use the `!>`
 279 `zapmic` rune. This takes a noun and produces a vase of the raw
 280 value and its type.

```

281 > !>(~[1 2 3])
282 [#t/[@ud @ud @ud %~] q=[1 2 3 0]]
283
284

```

285 Note that the type is very literal: in this case, it is a three-tuple
 286 rather than a list. Hoon’s type inference is quite literalistic,
 287 and this commonly leads to the “too much information” (TMI)
 288 problem, in which the type is too specific to be useful.

289 In Nock, we are essentially pinning a new variable at the
 290 head of our existing formula, then our tail is the actual access
 291 by binary tree address.

```

292 > %+ ~(mint ut %noun)
293 %noun
294

```

```

295   (ream '=(a 5 =(b 10 [a b]))')
296   [Ⓢ Ⓢ]
297   [8 [1 5] 8 [1 10] [[0 6] [0 2]]]
298

```

Now, we may have values which appear identical in their resultant Nock, but which Hoon would enforce different type constraints upon, such as a null-terminated tuple of finite length and a list:

```

303
304   :: null-terminated tuple
305   > (compile (ream '~[1 2 3]'))
306   [#t/[Ⓢud Ⓢud Ⓢud %~] q=[%1 p=[1 2 3 0]]]
307
308   :: formal list type with deferred evaluation
309   > (~(mint ut -:>(.)) %noun (ream '(gulf 1 3)'))
310   [#t/it(Ⓢ) q=[%8 p=[%9 p=200.245.085 q=[%0 p=1.023]]
311     q=[%9 p=2 q=[%10 p=[p=6 q=[p=[%7 p=[%0 p=3]
312       q=[%1 p=1]] q=[%7 p=[%0 p=3] q=[%1 p=3]]]]
313     q=[%0 p=2]]]]]

```

We have to be able to envase and devase a value, which we will write Lisp-style. We also want to be able to combine vases by “slopping” them together. Finally, we need to “slap” an expression we wish to evaluate against a vase. Everything else in vase mode can be built out of these primitives.

A vase is a pair of type and data, particularly as used in Nock and related languages. Vase mode, therefore, describes working with such pairs rather than first-order typed data. The vase algebra allows types to be straightforwardly combined, permitting code evaluation, facilitating metacircular interpretation, managing persistent code artifacts, and otherwise working at a higher level of abstraction than raw typed code and data. In this talk, we will examine the role of vases, the vase algebra, and work through several examples of how and why vase mode is useful throughout Nock-based platforms.

We will employ two main tools in Hoon to envase (or make dynamic) and devase (or make static):

- `!> zapgar envases`, or produces a vase from a noun.
- `!< zapgal devases`, or produces a statically-typed value from a vase.

There is also a “typed quote” `!; zapmic` rune, which wraps the product of its second child as the type of the example given as the first child. This is not commonly used.

```
> !; *type [1 0x0]
[#t/[@ud @ux] 1 0x0]
```

3.3 Eliminating Vases

`!< zapgal devases`, which requires you to know what type you expect so that you can match them.

The second process is less common; while you can trivially ascend from a statically-typed environment to a dynamically-typed one, to enter Hoon’s static layer again is more difficult and you have to know exactly what the type of the result is beforehand. (If the value does not actually fit the type it claims, we say that it is an “evil vase” and cannot process it.) Normally, once you have a vase in the code builder, you will use the vase algebra which we will discuss in a moment to produce static untyped Nock code instead of static Hoon code.

(A quick review of the Urbit kernel code base suggests that most instances of `!< zapgal unsafe` vase elimination are either unpacking command-line arguments which have in principle been vetted by the runtime first, or handling a received value over the network, presumably from its remote counterpart.)

4 Vase Algebra⁹

The essential operators on vases are `+slop` and `+slap`. Essentially all other operations can be expressed in terms of these two, but many supplemental operators are supplied with the Hoon compiler for convenience.

⁹This section benefitted from discussions with `~rovnys-ricfer`, to whom I am indebted.

367 4.1 +slop

368 If one queries the Hoon REPL what the vase of a pair of numbers
369 is, it generates the following description:

```
370 > !>([100 200])
371 [#t/[@ud @ud] q=[100 200]]
372
373
374 > !<([@ud @ud] !>([100 200]))
375 [100 200]
376
```

377 Let's suppose that one intends to append a hexadecimal
378 number as a tail. The original vase no longer holds:

```
379 > !>([[100 200] 0x12c])
380 [#t/[[@ud @ud] @ux] q=[[100 200] 300]]
381
382
383 > !<([@ud @ud] @ux] !>([[100 200] 0x12c]))
384 [[100 200] 0x12c]
385
```

386 Combining these manually can be done, but it's rather tedious
387 and error-prone in general. To combine them dynamically one
388 can use the first tool of our vase algebra, +slop. +slop com-
389 bines two vases, which means combining their types and their
390 values consistently.

391 Here, +slop produces the cell of those two nouns:

```
392 > !>([100 200])
393 [#t/[@ud @ud] q=[100 200]]
394
395
396 > !>(0x12c)
397 [#t/@ux q=300]
398
399 > (slop !>([100 200]) !>(300))
400 [#t/[[@ud @ud] @ud] q=[[100 200] 300]]
```

402 +slop simply combines heads and tails using a %cell head tag:

```
403 ++ slop
404 | = [hed=vase tal=vase]
405 ^- vase
406 [%cell p.hed p.tal] [q.hed q.tal]]
407
```

4.2 +slap

Chief among our list of reasons to use vases was the ability to dynamically evaluate code at runtime. How do we actually write code to +slap a given Hoon expression against a subject as vase? The +slap operator is the second part of the vase algebra. It takes a Hoon expression and a vase, and produces a new vase of the computational result.

```

416 ++  slap
417     |= [vax=vase gen=hoon] ^- vase
418     += gun=(~(mint ut p.vax) %noun gen)
419     [p.gun .*(q.vax q.gun)]
420
421
```

With that, we can resolve a variable name (or “face”) against a vase:

```

424 > !>(a=42)
425 [#t/a=@ud q=42]
426
427
428 > (slap !>(a=42) (ream 'a'))
429 [#t/@ud q=42]
430
431 > (slap !>(a=42) (ream '[a a]'))
432 [#t/[@ud @ud] q=[42 42]]
433
```

A much more interesting case arises when we introduce functions to the mix. Since we always need to know about a function to evaluate it, we will henceforth +slop in the Hoon subject including its standard library as .. Furthermore, if we don’t have variable names in this example, we can refer to the values by their binary tree addresses, in this case the head of the tail and the tail of the tail.

```

441
442 > (slap (slop !>([a=1 b=2]) !>(..) (ream '(add a b)'))
443 [#t/@ q=3]
444
445 > (slap (slop !>([1 2]) !>(..) (ream '(add +6 +7)'))
446 [#t/@ q=3]
447
```

(It is conventional to +slop new information to the head of the subject because of the binary tree search order.)

4.3 Supplemental Operators

What else would we like to be able to do, given a subject?

The received wisdom from core developers has been that one can build whichever higher-level operations one needs from `+slap` and `+slop`. This seems to be more or less true, but the mechanics of it start to depend very much on your high-level language and its relation to the instruction set architecture it targets. In practice, Hoon provides some supplemental functions for vase mode because we need to handle the stack trace for errors as well as supplying a context for certain out-of-subject references in userspace code.

1. `+slam` is an affordance for easy execution of a Hoon gate or function. Given a gate and its arguments as vases, produce a vase containing the result.

```
> (slam !>(|=([a=@ud b=@ud] [b a])) !>([1 2]))
[#t/[@ud @ud] q=[2 1]]
```

2. `+slym` is an untyped version of `+slam`. The type of the sample (argument) is ignored, and the type of the resulting vase is determined by the gate alone. This is particularly useful with the “wet” gate system, which is a paradigm of gate-building gates used frequently in Hoon. Coming from a higher-level typed language, there is more than one way to build a Nock gate. Hoon, for instance, uses what are called “dry” and “wet” approaches. (In Jock, all gates are dry.)

Put briefly, a dry gate is essentially a regularly typed gate: function argument types are checked and then inserted into the AST expression, which is built via vases in the conventional way.

In contrast, a wet gate is more like a C-style macro, in which the types are accepted as tentatively passing the necessary checks, then as long as they work the original types are passed back out as appropriate. It’s a way of asking if the Nock formula itself will just work—if it will,

then build it and return the associated type we expect. (This is how typed lists are built, for instance.)

You see wet gates used frequently as gate builders—that is, if you need a gate operating for a particular type, the easiest way to do it is to produce a gate specialized by type. (You can see the dynamism enabled by vases shining through the cracks of this model.)

3. `+slab` tells us, given a subject, whether a name is present.

```
> (slab %read %a -:>(a=5))
%.y
> (slab %read %a -:>(b=5))
%.n
```

4. `+text` Vases are also used for the prettyprinter, since the conversion from raw value to standardized text output requires type information to resolve.

```
> (text !>(~[1 2 3]))
"[1 2 3 ~]"
> (text !>((gulf 1 3)))
"~[1 2 3]"
```

5. `+slew` retrieves the axis of a name in a vase.
6. `+swat` doubly defers a `+slap` operation for certain cases.

5 Applications of Vase Mode

5.1 Type Manipulation

Types can be manually constructed as necessary. For example, to manually reconstruct a `list` from a `lest` (or non-null `list`), we can use the `+slop` operator to combine a vase of the null terminator or empty list with the `lest`. (This is, of course, equivalent to upcasting back to a `list`, but the type system

521 doesn't quite notice this directly as it(⌘).) Because the col-
 522 lapse from dynamic vase mode to static Hoon code necessarily
 523 destroys some type information via the mold in !< zapgal, vari-
 524 ants of this code work.

```

525
526 > =/ p (gulf 1 5)
527   !>(p)
528 [#t/it(⌘) q=[1 2 3 4 5 0]]
529
530 > =/ p (gulf 1 5)
531   ?~ p !!
532   !>(p)
533 [#t/[i=⌘ t=it(⌘)] q=[1 2 3 4 5 0]]
534
535 > =/ p (gulf 1 5)
536   ?~ p !!
537   (slop !>(⌘) !>(p))
538 [#t/[%~ i=⌘ t=it(⌘)] q=[0 1 2 3 4 5 0]]
539
540 > =/ p (gulf 1 5)
541   ?~ p !!
542   !<((lest ⌘) (slop !>(⌘) !>(p)))
543 [i=0 t=~[1 2 3 4 5]]
544
545 > =/ p (gulf 1 5)
546   ?~ p !!
547   !<((list ⌘) (slop !>(⌘) !>(p)))
548 ~[0 1 2 3 4 5]
549
  
```

520 5.2 Code Evaluation

551 As a practical matter and a safety measure, executable Hoon
 552 code is not directly transmitted over the wire. Instead, the type
 553 and value are sent, and the recipient compiles the noun into
 554 executable code. This is a security measure to prevent arbitrary
 555 code execution.

556 Thus vases are used in the kernel and in userspace for cer-
 557 tain kinds of transmitted code and data operations, including
 558 pokes between user agents. In fact, ~rovny-ricfer has pro-
 559 duced a minimal working example of a userspace handler using

560 vase mode.¹⁰

561 5.3 Metacircular Interpretation

562 Nock is a crash-only language; it has no error handling when
563 run raw. To produce a manageable system, Nock is almost al-
564 ways run in a virtualized mode called `+mock`. While the main
565 operator of this engine works only on raw untyped Nock, some
566 of the adjuncts do preserve type for subsequent use of the out-
567 puts as statically-typed values to be raised back into vases at
568 various points in the compiler. By providing a `$roof` or refer-
569 ence overlay to the fake Nock 12 opcode, for instance, a Nock
570 runtime can supply a referentially transparent expedient even
571 when the perceptual subject is much more constrained.

572 5.4 Persistent Code Artifacts

573 Urbit's Arvo kernel and Vere runtime, as well as the NockApp
574 framework with the Sword runtime, aggressively cache vases
575 to expedite code execution. Vases are stored in a map from
576 their hash to the vase itself. This is a performance optimization,
577 since the type information is expensive to compute and the
578 value is expensive to reduce. For instance, Arvo's `$worm` cache
579 maps Hoon vases to pairs of type and Nock nouns.

580 5.5 System Upgrades

581 A solid-state Nock runtime such as Arvo consists of an event
582 loop over a list of input events to apply to a current state. Sys-
583 tem upgrades such as kernel updates are supplied and built us-
584 ing vases.

585 A meta-vase is a vase of a vase, that is, an untyped vase.
586 These can be used to check structural data nesting without en-
587 forcing type, for instance. (Urbit types used to be total; that
588 is, on a mismatch they would return their default rather than
589 crashing.)

¹⁰See his video of ~2022.5.10; at the time of press, a copy is available at
<https://drive.google.com/file/d/10SaE5doCfdeqc2j945t8GvGvexKIBBZq/view>.

The vane interface is normally strictly typed, but using a metavase it can punch a hole through the type system. (This used to be the only way to do vase reduction before ! < zapgal was introduced: a vane had to pass to the Arvo kernel to get into double vase mode, which Arvo would collapse into one vase mode and hand back.)

Since Urbit is built to handle hot-swapped kernel updating, one interesting complication with vase handling lies in upgrades to the type system itself:

Some subtleties regarding types arise when handling OTA updates, since they can potentially alter the type system. Put more concretely, the type of type may be updated. In that case, the update is an untyped Nock formula from the perspective of the old kernel, but ordinary typed Hoon code from the perspective of the new kernel. Besides this one detail, the only functionality of the Arvo kernel proper that is untyped are its interactions with the Unix runtime.

Urbit caches vases aggressively for performance and it is reasonable to expect that the NockApp framework will as well as it develops.

6 Beyond the Vase Algebra

Hoon used to directly expose many of the mechanics of this when file handles could be produced using a sophisticated but complicated build system. (See the Ford vane, ca. 2016–2019). While Hoon still uses vase mode explicitly to import libraries and deliver user agent pokes, these are the only places that a userspace developer would typically encounter them. The vase algebra has largely been restricted to the compiler level in contemporary practice.

6.1 Comparisons

Pairing type and data is a general and generalizable approach. Languages and compilers must, after all, track typed values in some way. How do other languages and systems handle this?

6.1.1 Python/CPython

For instance, in the CPython reference implementation all values are “boxed”, or `PyObject` structures. This pairing of meta-data and value is similar to the way that Hoon vases work, but it is not directly exposed as a first-class element of the Python user environment, nor is there an explicit vase algebra (or subject).

6.1.2 Assembly Language

Typed assembly languages such as TAL (Morrisett et al., 1999) were explored in the late 1990s and early 2000s, with the goal of providing a type-safe assembly language that could be used to write low-level code while still preserving type safety. These researchers recognized that traditional compilation procedures often destroyed type information when it was still useful for verification and optimization. Even dependently typed assembly languages have been explored (Xi and Harper, 2001), conceived as a way of improving bytecode or assembly level performance by permitting the compiler more optimizations than it would naively know enough to implement. A set of rules was defined in order to produce well-formed “type states”, or relationships of type index expressions to actual register contents. This approach offers the expedient of a certifying compiler designed to guarantee type safety. While not constituting a vase algebra, the process of retaining type to produce better target ISA code shares a goal with Hoon’s vase mode.

6.1.3 Lisp Quote

In Lisp, `'` is used to defer evaluation, or to treat an expression as data which can be introspected and evaluated at will.

```
653 (+ 1 2)          ; => 3
654 '(+ 1 2)         ; => (+ 1 2)
```

655 Without ', (+ 1 2) evaluates to 3. With ', it's a list or S-
656 expression:

```
657 (list '+ '1 '2)
```

658 This is very similar to the way that Hoon lets you directly con-
659 struct and manipulate an AST, as with +ream.

```
660 (define prog '(+ 1 2))
661 (car prog)      ; => +
662 (cdr prog)      ; => (1 2)
663 (eval prog)     ; => 3
664
665 (eval '(+ 1 2)) ; => 3
```

666 This is basically equivalent to Hoon's +ream, although the
667 Hoon AST is somewhat more regularized and opaque. (I can
668 actually do this without a text string, but the syntax is a bit
669 convoluted and I don't want to muddy the waters any more in
670 this short talk.)

```
671 > (ream '(add 1 2))
672 [%cncl p=[%wing p=~[%add]] q=[i=[%sand p=%ud q=1]
673   t=[i=[%sand p=%ud q=2] t=~]]]
674
675
676 > !,(*hoon (add 1 2))
677 [%cncl p=[%wing p=~[%add]] q=[i=[%sand p=%ud q=1]
678   t=[i=[%sand p=%ud q=2] t=~]]]
679
```

680 A vase is a typed value that an AST, like ' or +ream pro-
681 duces, can be evaluated against. Lisp uses a global or explicit
682 environment, whereas Hoon always lets you supply a subject
683 of your choice, including the “current” subject (with .).

684 Vase mode is thus a “typed dynamic” system, unlike Lisp's
685 raw dynamism. (Why not just use eval? Scheme is untyped
686 and error-prone here. Vases add type safety, which in Hoon's
687 case is used to delimit possible kinds of operations.)

688 6.14 Haskell `Dynamic`

689 Haskellers probably immediately think of `Dynamic`. It's true:
690 Hoon's vases are indeed similar to Haskell's `Dynamic`, used for
691 injecting values into a dynamically typed value. Vases carry a
692 subject, or a closure-like scope, not just an expression as data.

- 693 • In Haskell, `Dynamic` lets you pack values of different
694 types into a uniform container and defer type checking
695 until runtime. Like Hoon's vase mode, `Dynamic` lets you
696 escape static typing temporarily and deferring type res-
697 olution.
- 698 • In Hoon, a type-value mismatch is an "evil vase" and
699 results in a runtime crash. (Since we are commonly run-
700 ning in an emulated mode, this doesn't take down the
701 whole kernel.) `Dynamic` will result in `Nothing` if the
702 types don't match.
- 703 • Hoon's vases are much "closer to the metal", since they
704 can trivially result in Nock code. In the end, Hoon's vase
705 mode feels more like a dynamic interpreter or a VM oper-
706 ating against a dynamic subject, while `Dynamic` is more
707 focused on typed payloads for data evaluation.
- 708 • `Dynamic` is data-centric, safe but limited. Vases carry
709 scope and enable `eval` but risk evil vase crashes, a trade-
710 off for power.

711 6.15 Untyped Virtual Machines

712 There may even be reason to eschew vases altogether in some
713 cases; Jock, for example, does not at the current time use vases
714 except when interacting with Hoon via a foreign function in-
715 terface. Chevalier-Boisvert (2022) argued that untyped virtual
716 machines are more resistant to bit rot than typed virtual ma-
717 chines:

718 An untyped VM design can be much more mini-
719 malistic. It has to enforce a small set of hard con-
720 straints, such as making sure that pointer deref-
721 erences respect valid address bounds so that the

running program can't crash the host VM, but it doesn't really need to care about the types of values or enforcing typing constraints. For performance, it can implement a very barebones JIT compiler based on dynamic binary translation, but it doesn't have to care about optimizing type checks, and it can even allow the running program to manage its own memory and implement its own garbage collector.

... [T]here's a strong case to be made that an untyped VM design can easily be much smaller and more minimalistic than a typed VM design. A simpler untyped VM has two major strengths. The first is that it doesn't place as many restrictions on running programs. Programs can implement their own control flow structures, their own GC, or even their own JIT. The second is that a smaller, simpler VM is much easier to port, reimplement and maintain. (Chevalier-Boisvert, 2022)

Nock runtimes do indeed hew to this parsimony, but vases are frequently used particularly in interprocess communication in today's Urbit kernelspace and userspace. It is unclear how they could profitably be excised from the system given their global utility.

A final interesting question is to think about targeting other ISAs. While Hoon itself is closely tied to Nock, no part of the vase algebra (in the abstract) is specific to Nock except its instantiation as nouns.

7 Conclusion

Vase mode provides something like a gradual (un)typing pipeline: one proceeds from a static Hoon context, to a dynamic vase mode, to untyped Nock. A vase algebra describes how to combine the type subject information and the associated value information, as in an import or a REPL. This lets Hoon

756 have human-legible affordances in metaprogramming and val-
757 idation, while retaining a simple target ISA for execution, code
758 proving, and optimized execution.

759 References

- 760 Chevalier-Boisvert, Maxime (2022) “Typed vs. Untyped
761 Virtual Machines”. URL:
762 [https://pointersgonewild.com/2022/06/08/typed-vs-](https://pointersgonewild.com/2022/06/08/typed-vs-untyped-virtual-machines/)
763 [untyped-virtual-machines/](https://pointersgonewild.com/2022/06/08/typed-vs-untyped-virtual-machines/) (visited on ~2024.7.4).
- 764 Morrisett, Greg et al. (1999). “TALX86: A Realistic Typed
765 Assembly Language.” In: *Proceedings of the 1999 ACM*
766 *SIGPLAN Workshop on Compiler Support for System*
767 *Software*. Atlanta, GA, USA: ACM, pp. 25–35. URL: [https:](https://www.cs.cornell.edu/talc/papers/talx86-wcsss.pdf)
768 [//www.cs.cornell.edu/talc/papers/talx86-wcsss.pdf](https://www.cs.cornell.edu/talc/papers/talx86-wcsss.pdf)
769 (visited on ~2024.7.4).
- 770 ~sorreg-namtyv, Curtis Yarvin et al. (2016). *Urbit: A*
771 *Solid-State Interpreter*. Whitepaper. Tlon Corporation. URL:
772 <https://media.urbit.org/whitepaper.pdf> (visited on
773 ~2024.1.25).
- 774 Xi, Hongwei and Robert Harper (2001). “A Dependently
775 Typed Assembly Language.” In: *Proceedings of the 6th ACM*
776 *SIGPLAN International Conference on Functional*
777 *Programming (ICFP’01)*. Florence, Italy: ACM, pp. 169–180.