Explanation of the HTML elements

HTML element	Function
<table>	Creates a table.
<caption>	Gives the table a descriptive title.
<thead>	Contains the table headings.
<tbody>	Contains the main table data.
<tfoot>	Contains summary or footer information.
<tr>	Creates a table row.
<th>	Creates a heading cell.
<td>	Creates an ordinary data cell.
colspan	Allows one cell to cover multiple columns.
scope	Identifies whether a heading applies to a row or column.

Why are both datasets tabular?

The student results are tabular because they contain related information arranged in rows and columns. Each row represents a student, while each column represents a subject or the student's total score.

The weekly timetable is also tabular because it organizes class activities according to days and time periods. Each row represents a time period, while each column represents a day of the week.

Why should tables not be used for website page layout?

Tables should not be used to position website sections because they are designed to display structured data, not arrange webpage content.

Using tables for page layout can make websites difficult to maintain, less accessible to screen readers, and difficult to adapt to different screen sizes. Semantic HTML elements should be used to structure webpage content instead.

Explanation of colspan

In the student results table, I used:

```
<th colspan="4">Class Total</th>
```

This makes the Class Total heading occupy four columns.

In the timetable, I used:

```
<td colspan="6">End of Morning Classes</td>
```

This makes the message occupy all six columns of the timetable.