TOSHIBA
Leading Innovation >>>

> Black & White MFP
> Up to 85 PPM
> Med/Large Workgroup
> Copy, Print, Scan, Fax
> Secure MFP
> EPEAT Registered*

e-STUDIO™ 557/657/757/857

* e-STUDIO657/757/857 only

e‑STUDIO™ 557/657/757/857

TOSHIBA
Leading Innovation ≫≫≫

> Black & White MFP
> Up to 85 PPM
> Med/Large Workgroup
> Copy, Print, Scan, Fax
> Secure MFP
> EPEAT Registered*

Specifications

Copying Process/Type	IEPM (Dry Process)/Laser Technology
Original Reading Method	CCD Line Sensor
Copy/Print Resolution	2400 x 600 dpi
Gradation	256 Steps
Copy/Print Speed	55/65/75/85 PPM
Warm-Up Time	Approx. 130 Seconds
First Copy Time	556/656: Less Than 4.0 Seconds (Letter-Size)
	756/856: Less Than 3.5 Seconds (Letter-Size)
Duty Cycle	460K/515K/540K/600K
Multiple Copying	Up to 9,999 Copies
Standard Paper Supply	2 x 500-Sheet Drawer, 1 x 2,500-Sheet Tandem Drawer, 100-Sheet Stack Feed Bypass
Maximum Paper Supply	Up to 7,600 Sheets (w/Optional 4,000-Sheet LCF)
Acceptable Paper Size	Cassette: Statement-R to Ledger (17-110 lb)
	Bypass: Statement-R to 11" x 17" (17-110 lb)
	LCF: Letter Only (17-110 lb), Tab Paper
Memory	2GB RAM, 320 GB FIPS 140-2 SED
Reduction/Enlargement	25% to 400%
Bypass Tray	100-Sheet Stack Feed Bypass
Control Panel	9" Wide VGA Color Touch Screen
Dimensions	Approx. 28" x 31" x 46" (W x D x H)
Weight	Approx. 462 lb
Power Supply	120 Volts, 20 Amps
Power Consumption	Maximum 2.0kW
Black Toner Yield	73.9K Impressions

e-BRIDGE Print Specifications

PDL Support	PCL6, PostScript 3, XPS
Operating Systems	Windows Server 2003, 2008, 2012, Vista SP2, 7, 8, NetWare 6.5, Citrix, Macintosh 10.4-10.9, Solaris v10, 11, HP-UX V11.iv3, AIX 7.x, Linux, SCO
Protocol Support	Windows Printing (SMB1.0/2.0), LPR/LPD, IPP (Ver.1.1) w/Authentication, NetWare P-SERVER w/NDS, Binary, Novell NDPS Gateway, or LPD w/ iPrint, Apple Talk PAP or EtherTalk, Port 9100 (bi-directional), WS Print, FTP
Drivers	Windows Server 2003, 2008, 2012, Vista SP2, 7, 8, Macintosh OS 10.4-10.9
Connectivity	10/100/1000BaseTX Ethernet, 802.11b/g/n, Wireless LAN, USB
Wireless Device	AirPrint, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple App Store or Google Play)
Device Management	Top Access, eFMS 6.0 (e-BRIDGE Fleet Management Software)
Certification	Windows 7, 8, 8.1,2008R2, 2012, 2012 R2, WHQL, Novell, Citrix

Scan Specifications

Scan Speed	77 SPM Color/80 SPM B&W, LT-Size @300 dpi, 66 SPM LT-Size @ 600 dpi (When Copying)
Scan Resolution	Up to 600 dpi
File Format	TIFF, PDF, JPEG, XPS, MS Word, MS Excel, Searchable PDF w/Adv. Scanning Option

Facsimile Specifications

Compatibility	Super G3, G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	33.6 Kbps
Fax Memory	Transmission 500MB (HDD)
	Reception 500MB (HDD)
	Backup Permanent (HDD)
Memory Transmission	100 Jobs, 1,000 Destinations Max, 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, 50 Scans Per Minute
Other Fax Functions	Internet Fax, Network Fax

e-Filing Specifications

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folder Per Box
	400 Documents Per Folder
	1000 Pages Per Documents

Security (Standard)

Data Encryption	256 Bit AES
HDD Overwrite	Meets Department of Defense (DoD) Standard 5220.22M
Authentication	LDAP, SMTP, Windows Server Domain

Accessories (Options)

Additional Paper Options
4,000-Sheet LT-Size Large Capacity Feeder	MP4004

Finishing Options
50-Sheet Stapler Console Finisher	MJ1027
50-Sheet Saddle-Stitch Finisher	MJ1028
100-Sheet Saddle-Stitch Finisher	MJ1029
Rails for Finisher	KN1017
2/3-Hole Punch Unit	MJ6003
Post Inserter Unit	MJ7001

Connectivity/Security Options
Fax Kit	GD1350
2nd Line Fax	GD1260F
Wireless LAN Adapter	GN1060
Antenna	GN3010
Advanced Scanning	GB1280T
IPsec Kit	GP1080
Meta Scan Enabler	GS1010
Harness Kit for Coin Controller	GQ1240

* e-STUDIO657/757/857 only