Java Concurrency

Chapter-10: Avoiding Liviness Hazards

Upcode Software Engineer Team

CONTENT

- 1. Deadlock
- 2. Avoiding and diagnosing deadlocks
- 3. Conculustion
- 4. Reference


Deadlock

1. Simple lock-ordering deadlock

```
// Warning: deadlock-prone!
public class LeftRightDeadlock {
    private final Object left = new Object();
    private final Object right = new Object();
    public void leftRight() {
        synchronized (left) {
            synchronized (right) {
                doSomething();
    public void rightLeft() {
        synchronized (right) {
            synchronized (left) {
                doSomethingElse();
```

What is a Deadlock?

1. Deadlock is a situation where a set of processes are blocked because each process is holding a resource and waiting for another resource acquired by some other process



Unlucky timing in LeftRightDeadlock.

What is a Deadlock?


 Let's look at the below practical example, which may help you to understand Deadlock better.

Trains starting in the same track



What is a Deadlock?

- 1. Once a Deadlock happens in the application, it cannot be recovered
- 2. The only way to recover from Deadlock is to restart the application.
- 3. This is a classic Deadlock situation.



Deadlock

 With unlucky timing, A will acquire the lock on myAccount and wait for the lock on yourAccount, while B is holding the lock on yourAccount and waiting for the lock on myAccount.

```
// Warning: deadlock-prone!
public void transferMoney (Account fromAccount,
                           Account toAccount,
                           DollarAmount amount)
        throws InsufficientFundsException {
    synchronized (fromAccount) {
        synchronized (toAccount) {
            if (fromAccount.getBalance().compareTo(amount) < 0)</pre>
                throw new InsufficientFundsException();
            else {
                fromAccount.debit(amount);
                toAccount.credit(amount);
```

Inducing a lock ordering to avoid deadlock

```
public class DeadlockTest {
                                                                                                                                package org.example.JAVA_Concurrency_in_Practice.listing10_3:
          private static final Object tieLock = new Object();
                                                                                                                                import org.example.JAVA_Concurrency_in_Practice.listing10_2.Account;
                                                                                                                                import org.example.JAVA_Concurrency_in_Practice.listing10_2.DynamicDeadlock;
          public static void transferMoney(final Account fromAcct,
                                          final Account toAcct.
                                                                                                                                import lavax.naming.InsufficientResourcesException:
                                          final BigInteger amount) throws InsufficientFundsException {
                                                                                                                                import java.math.BigInteger:
              3 usages
              class Helper {
                                                                                                                                public class Main {
                  public void transfer() throws InsufficientFundsException {
                                                                                                                                    public static void main(String[] args) throws InsufficientResourcesException {
                      if (fromAcct.getBalance().compareTo(amount) < 0)
                                                                                                                                        Account fromAccount = new Account():
                          throw new InsufficientFundsException();
                                                                                                                                        fromAccount.setId(1L);
                      else {
                                                                                                                                        fromAccount.setBalance(BigInteger.valueOf(100));
                          fromAcct.debit(amount);
                          toAcct.credit(amount);
                                                                                                                                        Account toAccount = new Account();
                                                                                                                                        toAccount.setId(2L);
                                                                                                                                        toAccount.setBalance(BigInteger.valueOf(200));
              int fromHash = System.identityHashCode(fromAcct);
                                                                                                                                        Thread thread1 = new Thread(() -> {
              int toHash = System.identityHashCode(toAcct);
              if (fromHash < toHash) {
                                                                                                                                                Thread.sleep( millis: 1000);
                  synchronized (fromAcct) {
                                                                                                                                                DynamicDeadlock.transferMoney(fromAccount, toAccount, BigInteger.valueOf(10));
                                                                                                                                           } catch (InterruptedException | InsufficientResourcesException e) {
                      synchronized (toAcct) {
                          new Helper().transfer();
                                                                                                                                                throw new RuntimeException(e);
                                                                                                                                       });
              } else if (fromHash > toHash) {
                  synchronized (toAcct) {
                                                                                                                                        Thread thread2 = new Thread(() -> {
                      synchronized (fromAcct) {
                          new Helper().transfer();
                                                                                                                                                DeadlockTest.transferMoney(toAccount, fromAccount, BigInteger.valueOf(20));
                                                                                                                                            } catch (InterruptedException | InsufficientFundsException e) {
              } else {
                                                                                                                                                throw new RuntimeException(e):
                  synchronized (tieLock) {
                      synchronized (fromAcct) {
                          synchronized (toAcct) {
                              new Helper().transfer();
                                                                                                                                        thread1.start();
                                                                                                                                        thread2.start():
```

'transferMoney' Method: Code discussion

- 1. Sure, this code represents a method **transferMoney** responsible for transferring money from one account (fromAcct) to another account (toAcct). It ensures thread safety during this transfer operation by using synchronization blocks and a tie-breaking mechanism.
- 2. It ensures thread safety during this transfer operation by using synchronization blocks and a **tie-breaking** mechanism.

Here's a breakdown of the code:

- ☐ This method takes three parameters
- ☐ It throws an InsufficientFundsException if the fromAcct does not have sufficient balance to transfer the specified amount

```
public class DeadlockTest {
    1usage
    private static final Object tieLock = new Object();
    4usages
    public static void transferMoney(final Account fromAcct, final Account toAcct, final DollarAmount amount) throws InsufficientFundsException {...}
}
```

'Helper' Inner Class code discussion

This inner class encapsulates the logic for the actual money transfer. It checks if the
fromAcct has enough balance and then debits from one account and credits to the other

```
3 usages
public class DeadlockTest {
    1 usage
    private static final Object tieLock = new Object();
    public static void transferMoney(final Account fromAcct, final Account toAcct, final DollarAmount amount) throws InsufficientFundsException {
        class Helper {
            3 usages
            public void transfer() throws InsufficientFundsException {
                if (fromAcct.getBalance().compareTo(amount.getAmount()) < 0)</pre>
                    throw new InsufficientFundsException();
                else {
                    fromAcct.debit(amount.getAmount());
                    toAcct.credit(amount.getAmount());
```

Locking Strategy code discussion

☐ The method first calculates hash codes for the fromAcct and toAcct using System.identityHashCode.

```
int fromHash = System.identityHashCode(fromAcct);
int toHash = System.identityHashCode(toAcct);
```

It uses a tie-breaking mechanism to prevent deadlock by synchronizing on the accounts based on their hash codes

```
if (fromHash < toHash) {
    synchronized (fromAcct) {
        synchronized (toAcct) {
            new Helper().transfer();
        }
    }
} else if (fromHash > toHash) {
    synchronized (toAcct) {
        synchronized (fromAcct) {
            new Helper().transfer();
        }
}
```

If the hash code of fromAcct is less than the hash code of toAcct, it synchronizes on fromAcct first and then on toAcct to perform the transfer.

If the hash code of fromAcct is greater than the hash code of toAcct, it synchronizes on toAcct first and then on fromAcct.

'tieLock' code discussion

```
synchronized (fromAcct) {
       synchronized (toAcct)
           new Helper().transfer();
} else if (fromHash > toHash) {
   synchronized (toAcct) {
       synchronized (fromAcct) {
           new Helper().transfer();
 else {
   synchronized (tieLock) {
       synchronized (fromAcct) {
            synchronized (toAcct) {
               new Helper().transfer():
```

if (fromHash < toHash) {

If both hash codes are equal, it synchronizes on a **tieLock** object first and then on the account objects in a consistent order (fromAcct first, then toAcct) to avoid deadlock.

```
private static final Object tieLock = new Object();
```

tieLock is a private static final object used solely for the purpose of breaking ties between the two accounts when their hash codes are the same.

Summary:

The code aims to prevent deadlocks by ensuring a consistent locking order based on the hash codes of the account objects or using a tie-breaking lock (tieLock) when the hash codes are equal.

final keyword

In Java, the final keyword, when applied to method parameters, ensures that the parameter variables cannot be reassigned within the method body

public static void transferMoney(final Account fromAcct, final Account toAcct, final DollarAmount amount)

- Declaring method parameters as final serves a few purposes:
 - 1. *Immutability*: It indicates that the parameter references cannot be changed within the method.
 - 2. Thread Safety: Using final for method parameters can contribute to thread safety. In a multi-threaded environment, marking method parameters as final ensures that these parameters cannot be modified by multiple threads, reducing the chances of unexpected behavior due to concurrent modifications.
 - 3. *Intent and Documentation:* It serves as a documentation tool by explicitly stating the developer's intent that the parameters should not be modified within the method.

The discussion of Inducing a lock ordering to avoid deadlock prevent completion is over

Demonstrate Deadlock

```
public class DemonstrateDeadlock {
    private static final int NUM_THREADS = 4;
    private static final int NUM ACCOUNTS = 5:
    private static final int NUM_ITERATIONS = 1000000:
    public static void main(String[] args) {
       final Random rnd = new Random();
       final Account[] accounts = new Account[NUM_ACCOUNTS]:
       for (int i = 0; i < accounts.length; <math>i++)
            accounts[i] = new Account(i, BigInteger.vglueOf(rnd.nextInt(bound: 1000)));
       1 usage
       class TransferThread extends Thread {
            public void run() {
                for (int i=0: i<NUM_ITERATIONS: i++) {
                    int fromAcct = rnd.nextInt(NUM_ACCOUNTS);
                   int toAcct = rnd.nextInt(NUM_ACCOUNTS):
                    DollarAmount amount =
                            new DollarAmount(BigInteger.valueOf(rnd.nextInt( bound: 1000)));
                   try {
                        transferMoney(accounts[fromAcct],
                                accounts[toAcct], amount);
                   } catch (InsufficientFundsException e) {
                        throw new RuntimeException(e + " Thread name: "+Thread.currentThread().getName());
        for (int i = 0; i < NUM_THREADS; i++)
            new TransferThread().start();
```

This code simulates a scenario where multiple threads try to transfer money between different bank accounts concurrently

Let's break it down step by step:

- Constants `NUM_THREADS`,
 `NUM_ACCOUNTS`, and
 `NUM_ITERATIONS` define the
 number of threads, accounts, and
 transfer iterations to perform.
- Initialization An array of `Account` objects is created and initialized with random balances using

`BigInteger.valueOf(rnd.nextInt(1000))`.

Demonstrate Deadlock

TransferThread class

This is an inner class inside the 'main' method. It extends 'Thread' and represents the logic for transferring money between accounts in a loop.

- Inside the `run` method of each thread:
 - It selects two random accounts ('fromAcct' and 'toAcct') and a random amount to transfer ('amount').
 - Tries to perform the money transfer using the `transferMoney` method between the selected accounts.

Demonstrate Deadlock



Demonstrate Deadlock discussion completion

Deadlocks between cooperating objects

- 1. Multiple lock acquisition is not always as obvious as in LeftRightDeadlock or transferMoney.
- 2. Invoking an alien method with a lock held is asking for liveness trouble.
- 3. Calling a method with no locks held is called an open call
- 4. Using open calls to avoid deadlock is analogous to using encapsulation to provide thread safety:

Lock-ordering deadlock between cooperating

```
C Taxi.java
                                                                         C Taxi, java ×
                    C Dispatcher.java ×
2 usages
                                                          02 A5 ^ V
                                                                                 6 usages
class Dispatcher {
                                                                                 class Taxi {
    2 usages
                                                                                     2 usages
   @GuardedBy("this")
                                                                                     (@GuardedBy("this")
                                                                          6
    private final Set<Taxi> taxis;
                                                                                     private Point location, destination;
                                                                          7
    2 usages
    @GuardedBy("this")
                                                                                     private final Dispatcher dispatcher;
                                                                          8
    private final Set<Taxi> availableTaxis;
    no usages
                                                                                     public Taxi(Dispatcher dispatcher) {
                                                                          9
    public Dispatcher() {
                                                                                         this.dispatcher = dispatcher;
        taxis = new HashSet<Taxi>():
                                                                         11
        availableTaxis = new HashSet<Taxi>();
                                                                                     1 usage
                                                                                     public synchronized Point getLocation() {
    1 usage
                                                                                         return location;
    public synchronized void notifyAvailable(Taxi taxi) {
                                                                         14
        availableTaxis.add(taxi);
                                                                                     no usages
                                                                         15 @
                                                                                     public synchronized void setLocation(Point location) {
    no usages
                                                                                         this.location = location;
    public synchronized Image getImage() {
                                                                                         if (location.equals(destination))
        Image image = new Image() {
                                                                                              dispatcher.notifyAvailable( taxi: this);
                                                                         18
                                                                         19
        for (Taxi t : taxis)
            image.drawMarker(t.getLocation());
        return image;
```

```
○ Taxi.java ×
                                                                                                @ ThreadSafe.java
Main, iava
               © Taxi.java
                              Dispatcher.iava ×
                                                                   02 A2 A V
                                                                                          @ThreadSafe
                                                                                                                                                         A2 ~ ~
     @ThreadSafe
                                                                                          class Taxi {
     class Dispatcher {
                                                                                              2 usages
         2 usages
                                                                                              @GuardedBy("this")
         @GuardedBy("this") private final Set<Taxi> taxis;
10
                                                                                              private Point location, destination;
         2 usages
                                                                                              2 usages
         @GuardedBy("this") private final Set<Taxi> availableTaxis;
                                                                                              private final Dispatcher dispatcher;
                                                                                  10
         no usages
                                                                                              no usages
         Dispatcher(Set<Taxi> taxis, Set<Taxi> availableTaxis) {
                                                                                              Taxi(Point destination, Dispatcher dispatcher) {
             this.taxis = taxis;
14
                                                                                                  this.destination = destination:
             this.availableTaxis = availableTaxis;
                                                                                  14
                                                                                                  this.dispatcher = dispatcher;
16
         1 usage
         public synchronized void notifyAvailable(Taxi taxi) {
                                                                                              1 usage
18
             availableTaxis.add(taxi);
                                                                                              public synchronized Point getLocation() {
19
                                                                                                  return location:
         no usages
                                                                                  19
         public Image getImage() {
20
                                                                                              no usages
             Set<Taxi> copy;
                                                                                              public void setLocation(Point location) {
                                                                                  20 (0)
             synchronized (this) {
                                                                                                  boolean reachedDestination;
                 copy = new HashSet<Taxi>(taxis);
                                                                                                  synchronized (this) {
24
                                                                                                      this.location = location:
             Image image = new Image();
                                                                                                      reachedDestination = location.equals(destination);
             for (Taxi t : copy)
26
                 image.drawMarker(t.getLocation());
                                                                                                  if (reachedDestination)
28
              return image:
                                                                                                      dispatcher.notifyAvailable( taxi: this):
                                                                                  28
```







Figure - 2





A deadlock is a situation in which more than one process is blocked because it is holding a resource and also requires some resource that is acquired by some other process. Therefore, none of the processes gets executed.



Timed lock attempts

- Introducing timed locks can sometimes help mitigate the risk of deadlocks by setting a timeout on acquiring locks.
- 2. Here's an example of how timed lock attempts could be approached using Java's Lock interface and its implementation ReentrantLock:


Here's what this code does?

```
import java.util.concurrent.locks.ReentrantLock;
import lava.util.concurrent.TimeUnit:
public class TimedLock
    private final Lock lock1 = new ReentrantLock();
   private final Lock lock2 = new ReentrantLock():
    public void performTask() {
            // Attempt to acquire lock within 1 seconds
            if (lock1.tryLock( time: 1, TimeUnit.SECONDS)) { 2
                    // Attempt to acquire lock within 3 seconds
                    if (lock2.tryLock( time: 3, TimeUnit.SECONDS)) { 3
                            // Task using lock2
                           // Perform the necessary actions with both locks acquired
                            lock2.unlock(); // Release the lock 4
                   } else {
                        // Unable to acquire lock2, handle accordingly
                    lock1.unlock(); // Release the lock 5
            } else {
                // Unable to acquire lock1, handle accordingly
        } catch (InterruptedException e) {
            Thread.currentThread().interrupt();
            // Handle interruption
```

Timed lock attempts

- This line declares a <u>private</u> and <u>final</u> variable named *lock1*, *lock2* which is of type Lock
- 2. **private final**: These modifiers indicate that **lock1** is a private variable and cannot be reassigned once initialized

About the Lock interface on timed lock attempts



Timed lock attempts

```
public void performTask() {
        // Attempt to acquire lock within 1 seconds
                                                                tryLock(timeout, unit):
       if (lock1.tryLock( time: 1, TimeUnit.SECONDS)
                if (lock2.tryLock( time: 3, TimeUnit.SECOND
                        // Task using lock2
                        // Perform the necessary actions with both locks acquired
                        lock2 unlock(): // Release the lock
                                                                      unlock();
                } else {
                    // Unable to acquire lock2, handle accordingly
            } finally
                lock1.unlock(); // Release the lock
       } else {
            // Unable to acquire lock1, handle according)
    } catch (InterruptedException e) {
        Thread.currentThread().interrupt();
       // Handle interruption
```

- tryLock(timeout, unit) attempts to acquire
 the lock within the specified time frame (1
 second in this example). If the lock is
 unavailable within that time, it returns false.
- If the first lock (lock1) is successfully acquired, the code attempts to acquire the second lock (lock2). If successful, it performs the necessary actions and then releases both locks in a reverse order
- 3. If either lock acquisition fails within the timeout, the code proceeds to handle the situation as needed.

Disadvantages of timed lock attempts

Introducing timed lock attempts should be approached with caution:

- 1. **Risk of Additional Complexity:** Timed lock attempts can add complexity to the code and might not completely eliminate deadlocks
- 2. **Potential for Starvation:** Timed lock attempts can also lead to situations where threads are starved of access to resources if timeouts occur frequently.
- 3. **Deadlock Avoidance Design:** The best practice is to design systems to avoid deadlocks by carefully managing resource acquisition, ordering locks consistently, and using higher-level abstractions like Lock interfaces or transactional mechanisms.

Summary:

Remember, timed lock attempts might help in certain scenarios but may not be a panacea for all deadlock situations.

It's crucial to understand the underlying concurrency issues in the application and design to prevent deadlocks rather than solely relying on timed lock attempts as a solution.

Avoiding and diagnosing deadlock

Indicative signs

Look for the following indicative signs of deadlocks:

- > One or more applications are occasionally re-executing transactions
- Deadlock message entries in the administration notification log
- Increased number of deadlocks displayed for the **deadlocks** monitor element
- Increased number of roll backs displayed for the int_deadlock_rollbacks monitor element
- Increased amount of time an agent spends waiting for log records to be flushed to disk which is displayed for the log_disk_wait_time monitor element
- Collect Thread Dumps: Generate thread dumps using tools like JStack, jcmd, VisualVM, or by sending a signal to the JVM process (Ctrl + Break for Windows or kill -3 <PID> for Unix/Linux).

Avoiding and diagnosing deadlock

Examine Stack Traces:

- Analyze the stack traces of threads to understand where they are stuck and what resources (locks) they are contending for.
- Look for threads stuck in methods or code sections synchronized on multiple objects, leading to potential deadlocks.

➤ Identify Locked Resources:

- Identify which locks/resources each thread is holding or waiting for. This helps pinpoint the cause of contention.
- Look for lock information in stack traces, particularly at points where synchronized blocks or Lock interfaces are used.

Identify Deadlocked Threads:

- Look for threads that are in the BLOCKED state or have suspicious stack traces indicating a lock contention.
- Check for circular lock dependencies where Thread A is waiting for a lock held by Thread B, and Thread B is waiting for a lock held by Thread A

Resolving deadlock problems

Resolve Deadlocks:

- 1. Break the circular dependency by adjusting the order in which locks are acquired.
- 2. Ensure consistent lock acquisition order across threads to prevent cyclic waits
- 3. Use timeout-based lock acquisition (tryLock()) with appropriate error handling.
- 4. Review synchronization strategies, avoiding nested locks or long-running operations within synchronized blocks.
- 5. Consider lock-free algorithms or other concurrency control mechanisms.

Test and Validate Fixes:

1. Implement the changes to resolve deadlocks and retest the application thoroughly to ensure the issue is resolved without introducing new problems.

Resolving deadlock problems

After diagnosing a deadlock problem, the next step is to attempt to resolve the deadlock issue resulting between two concurrently running applications each of which have locked a resource the other application needs.

Use the following steps to diagnose the cause of the unacceptable deadlock problem and to apply a remedy:

1. Obtain information from the lock event monitor or administration notification log about all tables where agents are experiencing deadlocks.


Summary

Remember, preventing deadlocks requires a proactive approach during the design and development stages. It's crucial to have a solid understanding of concurrency concepts and to leverage the tools and libraries provided by Java's concurrency framework.

Summary

- → Liveness failures are a serious problem because there is no way to recover from them short of aborting the application.
- → The most common form of liveness failure is lock-ordering deadlock. Avoiding lock ordering deadlock starts at design time: ensure that when threads acquire multiple locks, they do so in a consistent order.
- → The best way to do this is by using open calls throughout your program.
- → This greatly reduces the number of places where multiple locks are held at once, and makes it more obvious where those places are

Resources



Reference

- 1. Java Concurrency in Practice
- 2. https://blog.ycrash.io/2022/08/31/simulating-troubleshooting-deadlock-in-kotlin/

Thank you!

Presented by

Temirmalik Nomozov

(temirmaliknomozov@gmail.com)