

Inspecta 5335

AI DRIVEN SECURITY.
SMARTER. FASTER. SAFER

RAYTINA
2.0



KEY FEATUTRES

- 1.Operator Status Monitoring
- 2.Ai Model Integration Platform
- 3.120 HZ High Refresh Rate Display
- 4.Variable Conveyer Speed
- 5.Network Connectivity
- 6.Event Traceback Functionality
- 7.Multi Method Quick Login
- 8.Audible & Visual Alerts
- 9.Comprehensive Data Storage
- 10.Package to Image Correlation
- 11.Video to Image Correlation

The Inspecta 5335 Intelligent X-ray Inspection System is a new-generation, small-to-medium-sized low-dose X-ray security inspection device. Utilizing the penetrating power of X-rays, it conducts visual inspection of luggage without opening them, offering excellent image quality along with extensive image processing functions. It can be operated easily. This machine is suitable for public places with small packages, such as government agencies, scenic spots, courts, procuratorates, various exhibition halls, hospitals, schools, and factories.

Modular Design

The internal circuit structure adopts a modular design concept, facilitating installation and maintenance.

Digitization

The hardware system is designed with the latest ASIC full-digital solution and IN-depth acquisition technology. Compared with analog acquisition schemes, it optimizes circuit design, featuring high integration, strong anti-interference ability, and clear imaging effect.

HD Image Enhancement Algorithm

Powered by a new generation of proprietary Raytina 2.0 image processing technology, delivering significantly clearer and more detailed X-ray images for baggage inspection.

Comprehensive

Other functional modules can be customized according to customer needs, and custom ports can be opened as required. Examples include AI intelligent image recognition and metal detection.

Double-Layer Environmentally Friendly Lead Curtain

The lead curtain coating adopts a new lamination technology to eliminate lead pollution; the double-layer cross-over installation effectively prevents radiation leakage; the lead curtain is thin, soft, and highly wear-resistant.

STANDARD FEATURES:

- **Dimensions Size**

Tunnel Size: 555mm*357mm(W*H)

Machine Size: 1645mm*875mm*1221mm(L*W*H)

- **Performance**

Line Resolution: AWG38(ø0.102mm)

Spatial Ratio: Horizontal 1.0mm; Vertical 1.0mm

Penetration: 34~38mm steel

X-ray generator: 140KV~160KV 0.5mA~1.0mA

- **Radiation Dose**

Leakage dose: <0.5μSv (50mm away from the equipment shell)

Single dose: <5μGy/h

- **Conveyor Belt**

Conveyor height: 650mm(from the ground)

Conveyor speed: 0.22m/s

- **Monitor**

Size: 21.5 inches

Resolution: 1920*1080P

- **Image Process Functions**

Image Enhancement: Color / Black & White(C/B&W), Organic stripping(ORG-), Inorganic stripping(INORG-), Negative, High / Low penetration(H/L), Absorptivity

increase(ABS+), Absorptivity decrease(ABS-), Super Enhancement(SEN), Edge Enhancement(Edge) and Suspect materials enhancement(Z789), 64X zoom in and 3X image magnifier, etc.

Material Classification: 3 Colors mode (Default)

Image Recall: Recall infinitely

Image Storage Capability: 100,000 +

- **Whole machine**

Consumption: 500W

Power supply: AC220V 50Hz

Noise: <55Db(1 meter away from

Operating temperature & humidity: 5°C-40°C 10%-90% non-condensing

Storage temperature & humidity: -20°C-40°C 0-90% non-condensing

Weight: 360Kg

- **Device Parameters**

Power Consumption: Max. 0.8 KW

Power Supply: AC 220V (-15% to +10%) , 50Hz/60Hz (±3Hz) AC 110V (-15% to +10%) , 50Hz/60Hz (±3Hz)

Noise Level: 60dB(A), 1000 mm away from the device surface

- **System Functions**

Standard: Time / Date, baggage counting, user management, log management, X-ray on time, power on self-test, bi-directional scanning, enhanced scanning, system information management, built-in system diagnostics, standby mode, training, HCP, organic materials alarm, non-penetration alarm, explosive detection, etc.

- **Networked Remote Control and Data Upload**

The device can transmit scanned images in JPG or other image formats to designated clients or servers via protocols such as HTTP and TCP/IP. Scanned images support operations like viewing, marking, image analysis, and saving.

Note: The product images shown are for illustration only. Actual design may vary slightly depending on manufacturing updates.

Distributed By:

DIMENSIONS:

