

Inspecta 6550

AI DRIVEN SECURITY.
SMARTER. FASTER. SAFER

RAYTINA
2.0



KEY FEATUTRES

- 1.Operator Status Monitoring
- 2.Ai Model Integration Platform
- 3.120 HZ High Refresh Rate Display
- 4.Variable Conveyer Speed
- 5.Network Connectivity
- 6.Event Traceback Functionality
- 7.Multi Method Quick Login
- 8.Audible & Visual Alerts
- 9.Comprehensive Data Storage
- 10.Package to Image Correlation
- 11.Video to Image Correlation

The Inspecta 6550 Intelligent X-ray Inspection System features intelligent object recognition, person-package association, and an open AI platform. It reduces missed detections caused by operator fatigue and high-pressure peak periods. Ideal for airports, customs, railways, subways, prisons, government buildings, commercial centers, hotels, embassies, sports venues, and cultural events, it is designed for inspecting satchels, parcels, hand luggage, and small packages- enhancing both security efficiency and intelligence.

Intelligent Imaging & Inspection Features

HD Image Enhancement Algorithm

Powered by a new generation of proprietary Raytina 2.0 image processing technology, delivering significantly clearer and more detailed X-ray images for baggage inspection.

Advanced Material Classification

Utilizes cutting-edge material discrimination technology to identify the effective atomic number of scanned objects, displaying them in 3 or 6 distinct colors for improved differentiation and clarity.

Intelligent Recognition

Integrated with self-developed IPR deep learning algorithms and X-ray imaging analysis to enhance the automatic identification and classification of items.

STANDARD FEATURES:

- **Dimensions Size**

Tunnel Size: 650 mm(W) × 524.7 mm(H)
Dimension: 2687.5 mm(L) × 970mm(W) × 1386.5mm(H)
Operation Desk Size: 850mm(L) × 650 mm(W) × 1180 mm(H)

- **Performance**

Line Resolution[1]: 38 AWG standard, 40 AWG typical
Penetration[1] (Steel): 32 mm standard, 36 mm typical

- **X-ray Generator**

X-ray Generators: 1
Anode Voltage / Current: 160kV / 1.0mA (Adjustable)
Cooling / Working Cycle: Oil-cooling / Continuous
Orientation: Vertically upward

- **Radiation**

External Dose Rate[2]: < 1.0 μ Sv/h (100mm away from the device surface)
Film Safety: Standard of ASA / ISO1600

- **Image Process Functions**

Image Enhancement: Color / Black & White(C/B&W), Organic stripping(ORG-), Inorganic stripping(INORG-), Negative, High / Low penetration(H/L), Absorptivity increase(ABS+), Absorptivity decrease(ABS-), Super Enhancement(SEN), Edge Enhancement(Edge) and Suspect materials enhancement(Z789), 64X zoom in and 3X image magnifier, etc.
Material Classification: 3 Colors mode (Default)
Image Recall: Recall infinitely
Image Storage Capability: 100,000 +

- **Device Parameters**

Power Consumption: Max. 0.8 KW
Power Supply: AC 220V (-15% to +10%) , 50Hz/60Hz ($\pm$ 3Hz) AC 110V (-15% to +10%) , 50Hz/60Hz ($\pm$ 3Hz)
Noise Level: 60dB(A), 1000 mm away from the device surface

- **Conveyor**

Height: 650 mm
Speed: 0.2 m/s, 0.3 m/s, 0.4m/s adjustable
Load: 165Kg
Video Storage Capability: More than 30 days

- **Display**

Screen Size: 22", Single-screen
Resolution: 1920 × 1080 @ 120Hz

- **Intelligent Functions**

Prohibited Goods: 35 categories with 64 types
Login Method: Face / Fingerprint / Password

- **System Functions**

Standard: Time / Date, baggage counting, user management, log management, X-ray on time, power on self-test, bi-directional scanning, enhanced scanning, system information management, built-in system diagnostics, standby mode, training, HCP, organic materials alarm, non-penetration alarm, explosive detection, etc.

Note: The product images shown are for illustration only. Actual design may vary slightly depending on manufacturing updates.

Distributed By:

DIMENSIONS:

