

Inspecta 6550 D

AI DRIVEN SECURITY.
SMARTER. FASTER. SAFER

RAYTINA
2.0



KEY FEATUTRES

- 1.Operator Status Monitoring
- 2.Ai Model Integration Platform
- 3.120 HZ High Refresh Rate Display
- 4.Variable Conveyer Speed
- 5.Network Connectivity
- 6.Event Traceback Functionality
- 7.Multi Method Quick Login
- 8.Audible & Visual Alerts
- 9.Comprehensive Data Storage
- 10.Package to Image Correlation
- 11.Video to Image Correlation

The Inspecta 6550D Dual-View X-ray Inspection System is a high-performance security screening solution designed for large-scale and high-risk inspection scenarios. Featuring dual-view imaging technology and dual 160KV X-ray generators, the system provides comprehensive, blind-spot-free inspection of oversized baggage and cargo.

By combining advanced AI recognition algorithms, intelligent imaging processing, and an open AI platform, the system significantly enhances detection accuracy while reducing operator workload and fatigue during high-throughput operations.

It is widely deployed in critical security environments such as airports, customs, ports, railway freight stations, logistics hubs, bonded warehouses, government facilities, embassies, and large-scale event venues.

Dual-View Intelligent Imaging Technology

Equipped with two X-ray sources positioned at different angles, enabling simultaneous acquisition of horizontal and vertical images for each scanned object.

HD Image Enhancement Algorithm

Powered by a new generation of proprietary Raytina 2.0 image processing technology, delivering significantly clearer and more detailed X-ray images for baggage inspection.

Multi-Energy Material Classification

Automatically identifies material composition using effective atomic number analysis, displayed in multi-color modes (3 / 6 colors).

AI Intelligent Threat Detection

Built-in deep learning models enable automatic recognition of prohibited items, dangerous goods, and suspicious patterns.

STANDARD FEATURES:

- **Dimensions Size**

Tunnel Size: 650 mm(W) × 524.7 mm(H)
Dimension: 2687.5 mm(L) × 1370mm(W) × 1386.5mm(H)
Operation Desk Size: 850mm(L) × 650 mm(W) × 1180 mm(H)

- **Performance**

Line Resolution: 38 AWG standard, 40 AWG typical
Penetration (Steel): 34 mm standard, 38 mm typical

- **X - ray Generator**

X - ray Generators: 2 (Dual View Configuration)
Anode Voltage / Current: 160kV / 1.0mA (Each Generator, Adjustable)
Cooling / Working Cycle: Oil Cooling / Continuous Operation
Beam Direction: Horizontal + Vertical

- **Radiation Safety**

External Dose Rate: < 1.0 μ Sv/h (100 mm from surface)
Film Safety: Complies with ASA / ISO1600

- **Conveyor System**

Conveyor Height: 650 mm
Speed: 0.2 / 0.3 / 0.4 m/s adjustable
Max Load: 165 Kg
Continuous Operation: 24/7 industrial - grade design

- **Display**

Display: 120Hz High Refresh
Screen Size: 22" Industrial Display (Dual-View Split Screen)
Resolution: 1920 × 1080 @ 120Hz

- **Intelligent Functions**

Threat Library: 35 categories / 60+ prohibited items
Login Modes: Face / Fingerprint / Password (Optional)

- **Image Processing Functions**

Color / Black & White modes
Organic / Inorganic stripping
High / Low penetration enhancement
Edge enhancement & super enhancement
Z-effective suspicious material highlighting
64× zoom and magnification tools

- **System Functions**

Includes baggage counting, user authority control, log management, system diagnostics, self-test, training mode, dual-direction scanning, explosive detection, organic/inorganic alarms, and more.

- **Network & System Integration**

ISupports centralized data management, remote monitoring, and integration with security platforms (HCP / RMS systems).

- **Audible & Visual Alarm System**

Instant alerts for detection of suspicious or prohibited items to improve response speed.

- **Device Parameters**

Power Consumption: Max. 1.5 KW
Power Supply: AC 220V / 110V $\pm$ 15%
Noise Level: $\leq$ 60 dB(A)
Operating Temperature: 5°C – 40°C
Humidity: 10% – 95% (non-condensing)
Weight: Approx. 1500–1800 Kg

Note: The product images shown are for illustration only. Actual design may vary slightly depending on manufacturing updates.

Distributed By:

DIMENSIONS:

