



Integration Specification Document [ISD] [Contracts]

Issued by: Saudi AZM Digital

Issuing Date: 07/04/2026

Document Name: ISD

Document Version: 3.4.4

Table of Contents:

1	Introduction	5
2	Services Business Overview	5
2.1	<i>Contracts Inbound Services</i>	<i>5</i>
2.1.1	Upload Contract Service	7
2.1.2	Upload Contract With Template Service	14
2.1.3	Download Un-Signed Document Service	21
2.1.4	Download Signed Document Service	24
2.1.5	Download Sanad Service	26
2.1.6	Resend Approval Page URL Service	29
2.1.7	Get Contract Audit Trail Service	32
2.1.8	Sign Hash Document Service	34
2.1.9	Get Contract Details Service	38
2.1.10	Download Un-Signed Addendum Service	41
2.1.11	Download Signed Addendum Service	43
2.1.12	Download Sanad Group Service	46
2.1.13	Get Contracts Service	48
2.1.14	Get All By Beneficiary Service	52
2.1.15	Get Nafath Login Status Service	56
2.1.16	Get Random Number Service	58
2.1.17	Update Status Service	60
2.2	<i>Contracts Entity Inbound Service</i>	<i>64</i>
2.2.1	Upload Contract Service	64
2.2.2	Upload Contract With Template Service	72
2.3	<i>Error Code</i>	<i>81</i>
2.4	<i>Contracts Outbound Service</i>	<i>87</i>
3	Integration Specifications	89
3.1	<i>Http Response Codes</i>	<i>89</i>
3.2	<i>Enum</i>	<i>89</i>
3.2.1	Contract Status	89
3.2.2	Contract Type	90
3.2.3	Nafath Authorization Status	90
3.2.4	Contract Term	90
3.2.5	Document Type	90
3.2.6	Share Via Types/Share Approval URL Via/ Send Security Code Via	90
3.2.7	Digital Signature Provider	90
3.2.8	Beneficiary Action Types	91
3.2.9	Sanad Type	91
3.2.10	Sanad Due Type	91
3.2.11	Authentication Type Id	91
3.2.12	Type (FieldType)	91
3.2.13	City	92
3.2.14	Region	96
3.2.15	Language	96

3.2.16 Signature Method	97
3.2.17 Meta Data.....	97
3.2.18 Beneficiary Type	97

Table of Tables

Table1 Modifications	4
----------------------------	---

Table of Modifications:

Date	Name	Version	Description
11/02/2025	Mohammed Masad	1.0	First version
05/08/2025	Shehryar Ahmed	2.0	- In "Get Contracts" and "Get All By Beneficiary" APIs: i. Endpoint path updated (/Contract//Contract → /Contract/getContract). ii. Data types of "dateFrom" and "dateTo" changed from string to DateTime. iii. Pagination field names updated: "PageNumber" → "pageNumber", "pageSize" → "pageSize". iv. Date format updated: e.g., "2025-02-05" → "2025-02-05T00:00:00". - In "Get Contract Details" API: Data type of "fileSharingLink" changed from string to List<string> in both request and response.
19/08/2025	Shehryar Ahmed	3.0	- In "Upload Contract" and "Upload Contract With Template" APIs: Fields removed from request payload: i. needsToSign (boolean) ii. endDate (DateTime) iii. shareApprovalURL (boolean) Upload Contract With Template APIs: Field are added: i. applyToAllPages ii. pages

			-Status codes update.
29/09/2025	Shehryar Ahmed	3.4.1	Error Code table Updated New error codes added and fixed code mismatches.
05/01/2026	Osama Dawoud	3.4.2	Update new environment URL
27/01/2026	Yousif Whby	3.4.3	- Update Template fields attributes for upload contract and upload templates. Adding upload contract and upload templates for Entity.
09/04/2026	Yousif Whby	3.4.4	- Adding Optional Fields in upload contract and upload templates : . returnUrl . metadata . sigantureMethod - Adding Optional Fields in upload contract and upload templates for Entity : . returnUrl . metadata . sigantureMethod . contractEntity

Table1 Modifications

1 Introduction

Purpose: This document aims to outline the integration specifications for the Contracts system. It provides a comprehensive guide for developers and stakeholders to understand the processes, services, and requirements involved in the integration.

Scope: The scope of this document encompasses all the integration points, services, and protocols required to integrate the Contracts system with other systems. This includes both inbound and outbound services, error handling, and specific use cases.

Stakeholders:

- **Saudi AZM Digital:** The issuing entity responsible for maintaining and updating the integration specifications.
- **Developers:** Technical teams tasked with implementing the integration as per the specifications.
- **Clients:** Entities that will interact with the Contracts system through the specified services.

2 Services Business Overview

The Conceptual architecture below show a high-level design view of a system and provides a basis for more detailed design work. These are the high-level components of the system you are building and their relationships.

The following diagram illustrates the solution's conceptual architecture:

Following is the description for each block individually:

2.1 Contracts Inbound Services

The below subsections cover the business aspect of the Contracts services; these services are considered as Consume services from the Contracts services perspective.

Baseurl: <https://api-sb.contracts.com.sa/api>

SwaggerUI: <https://api-sb.contracts.com.sa/integration/swagger/index.html>

2.1.1 Upload Contract Service

API Definition Card	
API Name	Upload Contract
API Description	This service is exposed to Upload new contract (can be with or without sanad).
End Point	POST (Baseurl)/Contract/UploadContract
HTTP Request Headers	
Element Name	Element Value
Content-Type	application/json; charset=UTF-8
X-Contracts-Timestamp	Time as a string the same value used to create the signature.
X-Contracts-ClientId	Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.
X-Contracts-APIKey	Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.
X-Contracts-Signature	Create a signature using the secret key or the certificate.

Request						
Element	Level	Data Type	Element Type	Allowed Value	Usage*	Description
file	1	string	Body Param	String	R	File name or path
templateFields	1	List<Object>	Body Param	-	O	List of template fields
id	2	string	Body Param	String	O	Field identifier
type	2	string	Body Param	Refer to the Enum section	O	Field type identifier
position	2	Object	Body Param	-	O	Position of the field
x	3	Integer	Body Param	Integer	O	X-axis coordinate
y	3	Integer	Body Param	Integer	O	Y-axis coordinate
size	2	Object	Body Param	-	O	Size of the field
width	3	Integer	Body Param	Integer	O	Width of the field
height	3	Integer	Body Param	Integer	O	Height of the field
applyToAllPages	2	boolean	Body	true/false		When you need to apply

pages	2	List<Integer>	Param Body Param	Integer	O	the field to all pages Page number where field is placed
filledBy	2	string	Body Param	String	O	Beneficiary National ID number
defaultValue	2	string	Body Param	String	O	Field default value
contractNumber	1	string	Body Param	String	R	Contract identifier
description	1	string	Body Param	String	O	Contract description
contractBeneficiaries	1	List<Object>	Body Param	-	R	List of contract beneficiaries
id	2	Integer	Body Param	String	R	Beneficiary Id default 0
nameEn	2	string	Body Param	String	R	Beneficiary name in English Max length 32
nameAr	2	string	Body Param	String	R	Beneficiary name in Arabic Max length 32
nationalIdNumber	2	string	Body Param	String	R	Beneficiary National ID number
mobileNumber	2	string	Body Param	String	R	Mobile number
email	2	string	Body Param	String	R	Email address
beneficiaryRegionId	2	Integer	Body Param	Refer to the Enum section	R	Beneficiary Region
maximumApprovalMinutes	2	Integer	Body Param	Integer	R	Max approval time
privateNote	2	String	Body Param	String	O	Private note
lang	2	String	Body Param	Refer to the Enum section	R	Approval Page Language.
type	2	Integer	Body Param	Refer to the Enum section	R	ContractBeneficiaryType
hasSanad	2	boolean	Body Param	true/false	O	Whether the beneficiary has a Sanad
sanadGroup	2	Object	Body Param	-	O	Sanad group details
type	3	Integer	Body Param	Refer to the Enum section	R	Sanad type
totalValue	3	Integer	Body Param	Integer	R	Sum of Total value of the All Sanads
referenceId	3	String	Body Param	String	R	Reference ID
countryOfIssuance	3	String	Body Param	String	R	Country of issuance

cityOfIssuanceId	3	Integer	Body Param	Refer to the Enum section	R	City of issuance ID
countryOfPayment	3	String	Body Param	String	R	Country of payment
cityOfPaymentId	3	Integer	Body Param	Refer to the Enum section	R	City of payment ID
responseTimeInMinutes	3	Integer	Body Param	Integer	R	Response time in minutes
currency	3	String	Body Param	String	R	Currency
sanads	3	List<Object>	Body Param	-	R	List of Sanads
totalValue	4	Integer	Body Param	Integer	R	Total value of the Sanad
dueType	4	Integer	Body Param	Refer to the Enum section	R	Due type
referenceId	4	String	Body Param	String	O	Reference ID
dueDate	4	String(Date-time)	Body Param	Date-Time	O	Due date of the Sanad
reason	4	String	Body Param	String	R	Reason for the Sanad
updateStatusDate	4	String(Date-time)	Body Param	Date-Time	O	Last update status date
debtor	3	Object	Body Param	-	R	Debtor details
idNumber	4	string	Body Param	String	R	Beneficiary National ID number
phoneNumber	4	string	Body Param	String	R	Mobile number
name	4	string	Body Param	String	R	Beneficiary name.
shareApprovalURLVia	2	Integer	Body Param	Refer to the Enum section	R	Method of sharing approval UR
digitalSigningProvider	2	Integer	Body Param	Refer to the Enum section	R	Digital signing provider ID
authenticationTypeId	2	Integer	Body Param	Refer to the Enum section	O	Authentication type ID
beneficiaryActionType	2	Integer	Body Param	Refer to the Enum section	R	Beneficiary action type ID
offlineCode	2	String	Body Param	String	O	Offline code for beneficiary
additionalFiles	1	List<Object>	Body Param	-	O	List of additional files
name	2	String	Body Param	String	O	File name

file	2	string	Body Param	String	O	File in base64 formay
sendInOrder	1	boolean	Body Param	true/false	R	Whether the contract should be sent in order
sendSecurityCodeVia	1	Integer	Body Param	Refer to the Enum section	O	Security code sending method
waitingPeriod	1	Integer	Body Param	Integer	O	Waiting period in days
returnURL	1	String	Body Param	String (URL)	O	Success Return URL after signing
sigantureMethod	1	Integer	Body Param	Refer to the Enum section	O	Signature display method on the contract. Values In Enum Section
metaData	1	List<Integer>	Body Param	Refer to the Enum section	O	Defines which Metadata fields displayed next to the signature on the final contract. Values In Enum Section

HTTP Response Headers

Element Name	Element Value
Content-Type	application/json; charset=UTF-8

Response Elements

Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of get contract details.
contractId	2	String		O	Customer commercial registry.
contractNumber	2	String		O	Contract number
contractStatusCode	2	String	Refer to the Enum section	O	Contract status code.
createdOn	2	String (Date-Time)		O	Contract created date.
fileSharingLink	2	List<String>		O	Contract approval link.
unSignFileLink	2	String		O	Un-Signed contract link.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data =
{
  "file": "string",
  "templateFields": [
    {
      "id": "string",
      "type": "Signature",
      "position": {
        "x": 0,
        "y": 0
      },
      "size": {
        "width": 0,
        "height": 0
      },
      "applyToAllPages": true,
      "pages": [
        0
      ],
      "filledBy": "string",
      "defaultValue": "string"
    }
  ],
  "fileName": "string",
  "contractNumber": "string",

  "description": "string",
  "contractBeneficiaries": [
    {
      "id",
      "nameEn": "string",
      "nameAr": "string",
      "nationalIdNumber": "string",
      "mobileNumber": "string",
      "email": "string",
      "beneficiaryRegionId": 0,
      "maximumApprovalMinutes": 0,
      "privateNote": "string",
      "lang": "string",
      "type": 0,
      "hasSanad": true,
      "sanadGroup": {
        "type": 0,
        "totalValue": 0,
        "referenceId": "string",
        "countryOfIssuance": "string",
        "cityOfIssuanceId": 0,
        "countryOfPayment": "string",
```

```
"cityOfPaymentId": 0,
"responseTimeInMinutes": 0,
"currency": "string",
"sanads": [
  {
    "totalValue": 0,
    "dueType": 1,
    "referenceId": "string",
    "dueDate": "2025-02-19T08:16:57.477Z",
    "reason": "string",
    "updateStatusDate": "2025-02-19T08:16:57.477Z"
  }
],
"debtor": {
  "idNumber": "string",
  "phoneNumber": "string",
  "name": "string"
},
"shareApprovalURLVia": 1,
"digitalSigningProvider": 1,
"authenticationTypeId": 0,
"beneficiaryActionType": 1,
"offlineCode": "string"
},
"additionalFiles": [
  {
    "name": "string",
    "file": "string"
  }
],
"sendInOrder": true,
"sendSecurityCodeVia": 1,
"waitingPeriod": 0,
"returnURL": "string",
"signatureMethod": 0,
"metaData": [
  1
]
}
request_endpoint = "/api/Contract/UploadContract "
request_method = "POST"
connection_url = "api-sb.contracts.com.sa"
timestamp = "1586345122"
```

secret_key= “provided_secret_key” on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

message = '{0}\n{1}\n{2}\nnt={3}&ed={4}'.format(request_method, connection_url, request_endpoint, timestamp, encoded_data)

After getting the message we start calculating the signature

signature = hmac.new(bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'), digestmod=hashlib.sha256).digest()
calculated_signature = base64.b64encode(signature).decode()

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/UploadContract
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "contractId": 0,
    "contractNumber": "string",
    "contractStatusCode": "string",
    "createdOn": "2025-02-18T08:25:14.909Z",
    "fileSharingLink": ["string"],
    "unSignFileLink": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.2 Upload Contract With Template Service

API Definition Card	
API Name	Upload Contract With Template
API Description	This service is exposed to Upload new contract using an existing template uploaded on the portal (can be with or without sanad).
End Point	POST (Baseurl)/Contract/UploadContractWithTemplate
HTTP Request Headers	
Element Name	Element Value
Content-Type	application/json; charset=UTF-8
X-Contracts-Timestamp	Time as a string the same value used to create the signature.
X-Contracts-ClientId	Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.
X-Contracts-APIKey	Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.
X-Contracts-Signature	Create a signature using the secret key or the certificate.

Request						
Element	Level	Data Type	Element Type	Allowed Value	Usage*	Description
templateFields	1	List<Object>	Body Param	-	O	List of template fields
id	2	string	Body Param	String	O	Field identifier
type	2	string	Body Param	Refer to the Enum	O	Field type identifier
position	2	Object	Body Param	-	O	Position of the field
x	3	Integer	Body Param	Integer	O	X-axis coordinate
y	3	Integer	Body Param	Integer	O	Y-axis coordinate
size	2	Object	Body Param	-	O	Size of the field
width	3	Integer	Body Param	Integer	O	Width of the field
height	3	Integer	Body Param	Integer	O	Height of the field
applyToAllPages	2	boolean	Body	true/false		When you need to apply

pages	2	List<Integer>	Param Body Param	Integer	O	the field to all pages Page number where field is placed
filledBy	2	string	Body Param	String	O	Beneficiary National ID number
defaultValue	2	string	Body Param	String	O	Field default value
contractNumber	1	string	Body Param	String	R	Contract identifier
description	1	string	Body Param	String	O	Contract description
contractBeneficiaries	1	List<Object>	Body Param	-	R	List of contract beneficiaries
id	2	Integer	Body Param	String	R	Beneficiary Id default 0
nameEn	2	string	Body Param	String	R	Beneficiary name in English Max length 32
nameAr	2	string	Body Param	String	R	Beneficiary name in Arabic Max length 32
nationalIdNumber	2	string	Body Param	String	R	Beneficiary National ID number
mobileNumber	2	string	Body Param	String	R	Mobile number
email	2	string	Body Param	String	R	Email address
beneficiaryRegionId	2	Integer	Body Param	Refer to the Enum section	R	Beneficiary Region
maximumApprovalMinutes	2	Integer	Body Param	Integer	R	Max approval time
privateNote	2	String	Body Param	String	O	Private note
lang	2	String	Body Param	Refer to the Enum section	R	Approval Page Language.
type	2	Integer	Body Param	Refer to the Enum section	R	ContractBeneficiaryType
order	2	Integer	Body Param	Integer	R	Sending Order
hasSanad	2	boolean	Body Param	true/false	O	Whether the beneficiary has a Sanad
sanadGroup	2	Object	Body Param	-	O	Sanad group details
type	3	Integer	Body Param	Refer to the Enum section	R	Sanad type
totalValue	3	Integer	Body Param	Integer	R	Sum of Total value of the All Sanads
referenceId	3	String	Body Param	String	R	Reference ID
countryOfIssuance	3	String	Body Param	String	R	Country of issuance

cityOfIssuanceId	3	Integer	Body Param	Refer to the Enum section	R	City of issuance ID
countryOfPayment	3	String	Body Param	String	R	Country of payment
cityOfPaymentId	3	Integer	Body Param	Refer to the Enum section	R	City of payment ID
responseTimeInMinutes	3	Integer	Body Param	Integer	R	Response time in minutes
currency	3	String	Body Param	String	R	Currency
sanads	3	List<Object>	Body Param	-	R	List of Sanads
totalValue	4	Integer	Body Param	Integer	R	Total value of the Sanad
dueType	4	Integer	Body Param	Refer to the Enum section	R	Due type
referenceId	4	String	Body Param	String	O	Reference ID
dueDate	4	String(Date-time)	Body Param	Date-Time	O	Due date of the Sanad
reason	4	String	Body Param	String	R	Reason for the Sanad
updateStatusDate	4	String(Date-time)	Body Param	Date-Time	O	Last update status date
debtor	3	Object	Body Param	-	R	Debtor details
idNumber	4	string	Body Param	String	R	Beneficiary National ID number
phoneNumber	4	string	Body Param	String	R	Mobile number
name	4	string	Body Param	String	R	Beneficiary name.
shareApprovalURLVia	2	Integer	Body Param	Refer to the Enum section	R	Method of sharing approval UR
digitalSigningProvider	2	Integer	Body Param	Refer to the Enum section	R	Digital signing provider ID
authenticationTypeId	2	Integer	Body Param	Refer to the Enum section	O	Authentication type ID
beneficiaryActionType	2	Integer	Body Param	Refer to the Enum section	R	Beneficiary action type ID
offlineCode	2	String	Body Param	String	O	Offline code for beneficiary
additionalFiles	1	List<Object>	Body Param	-	O	List of additional files
name	2	String	Body Param	String	O	File name

file	2	string	Body Param	String	O	File in base64 format
sendInOrder	1	boolean	Body Param	true/false	R	Whether the contract should be sent in order
sendSecurityCodeVia	1	Integer	Body Param	Refer to the Enum section	O	Security code sending method
waitingPeriod	1	Integer	Body Param	Integer	O	Waiting period in days
templateCode	1	string	Body Param	String	R	Template Code from the Portal.
templateData	1	string	Body Param	String	O	Incase of Word template Send the key with case-sensitive and the value as follows: "{\"Companyname\": \"Test\"}"
returnURL	1	String	Body Param	String (URL)	O	Success Return URL after signing
signatureMethod	1	Integer	Body Param	Refer to the Enum section	O	Signature display method on the contract. Values In Enum Section
metaData	1	List<Integer>	Body Param	Refer to the Enum section	O	Defines which Metadata fields displayed next to the signature on the final contract. Values In Enum Section

HTTP Response Headers	
Element Name	Element Value
Content-Type	application/json; charset=UTF-8

Response Elements					
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of get contract details.
contractId	2	String		O	Customer commercial registry.
contractNumber	2	String		O	Contract number
contractStatusCode	2	String	Refer to the Enum section	O	Contract status code.
createdOn	2	String (Date-Time)		O	Contract created date.
fileSharingLink	2	List<String>		O	Contract approval link.
unSignFileLink	2	String		O	Un-Signed contract link.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.

message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```

data =
{
  "templateFields": [
    {
      "id": "string",

      "type": "Signature",
      "position": {
        "x": 0,
        "y": 0
      },
      "size": {
        "width": 0,
        "height": 0
      },
      "applyToAllPages": false,
      "page": [
        0
      ],

      "filledBy": "string",
      "defaultValue": "string"
    }
  ],
  "fileName": "string",
  "contractNumber": "string",
  "description": "string",
  "contractBeneficiaries": [
    {
      "id",
      "nameEn": "string",
      "nameAr": "string",
      "nationalIdNumber": "string",
      "mobileNumber": "string",
      "email": "string",
      "beneficiaryRegionId": 0,
      "maximumApprovalMinutes": 0,
      "privateNote": "string",
      "lang": "string",
      "type": 0,
      "hasSanad": true,
      "sanadGroup": {
    
```

```

"type": 0,
"totalValue": 0,
"referenceId": "string",
"countryOfIssuance": "string",
"cityOfIssuanceId": 0,
"countryOfPayment": "string",
"cityOfPaymentId": 0,
"responseTimeInMinutes": 0,
"currency": "string",
"sanads": [
  {
    "totalValue": 0,
    "dueType": 1,
    "referenceId": "string",
    "dueDate": "2025-02-19T08:16:57.477Z",
    "reason": "string",
    "updateStatusDate": "2025-02-19T08:16:57.477Z"
  }
],
"debtor": {
  "idNumber": "string",
  "phoneNumber": "string",
  "name": "string"
},
"shareApprovalURLVia": 1,
"digitalSigningProvider": 1,
"authenticationTypeId": 0,
"beneficiaryActionType": 1,
"offlineCode": "string"
},
"additionalFiles": [
  {
    "name": "string",
    "file": "string"
  }
],
"sendInOrder": true,
"sendSecurityCodeVia": 1,
"waitingPeriod": 0,
"templateCode": "string",
"templateData": "string",
"returnURL": "string",
"signatureMethod": 0,
"metaData": [
  1
]

```

```
}
request_endpoint = "/api/Contract/UploadContractWithTemplate "

request_method = "POST"

connection_url = "api-sb.contracts.com.sa"

timestamp = "1586345122"

secret_key= "provided_secret_key" on api configuration tab
So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it
depends on many inputs (Should be sorted as on example):

message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp,
encoded_data )
After getting the message we start calculating the signature

signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),
digestmod=hashlib.sha256).digest() calculated_signature = base64.b64encode(signature).decode()

UploadContractWithTemplate Ignore the templateData object from the data.
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/UploadContractWithTemplate
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "contractId": 0,
    "contractNumber": "string",
    "contractStatusCode": "string",
    "createdOn": "2025-02-18T08:25:14.909Z",
    "fileSharingLink": ["string"],
    "unSignFileLink": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.3 Download Un-Signed Document Service

	API Definition Card				
API Name	Download Un-Signed Document				
API Description	This service is exposed to download the original version of the document.				
End Point	GET (Baseurl)/Contract/DownloadUnsignedDocument				
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
contractNo	string	Query Param	Contract number	R	Contract number that wants to

					download the original document.
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
	Response Elements				
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object include the result of download unsigned document
file	2	String		O	Original document in base64 string format
Version	2	String		O	Version of original document
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code
messages	1	Array<Object>		O	List of business validations error code and message
errorCode	2	String		O	Business validation error code
message	2	String		O	Business validation message
succeeded	1	Boolean		R	

Calculate Signature

```

data = {"contractNo": "10002000 "}
request_endpoint = "/api/Contract/ DownloadUnsignedDocument"

request_method = "GET"

connection_url = "api-sb.contracts.com.sa"

timestamp = "1586345122"

secret_key= "provided_secret_key" on api configuration tab
So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it
depends on many inputs (Should be sorted as on example):

message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp,
encoded_data )
After getting the message we start calculating the signature

signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),
digestmod=hashlib.sha256).digest()
calculated_signature = base64.b64encode(signature).decode()

Important Note: The order for the fields is important and do not include the null values on the data for
    
```

example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/DownloadUnsignedDocument?contractNo=10002000
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "file": "string",
    "version": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.4 Download Signed Document Service

	API Definition Card				
API Name		Download Signed Document			
API Description		This service is exposed to download the signed version of the document.			
End Point		GET (Baseurl)/Contract/DownloadSignedDocument			
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
contractNo	String	Query Param		R	Contract number that wants to download the original document.
version	String			O	The version of the signed documents. If the value is null, the latest signed document will retrieve in the response.
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
	Response Elements				
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of download a signed document.
file	2	String		O	signed document in base64 string format.
version	2	String		O	A version of the signed document.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"contractNo": "10002000 "}  
request_endpoint = "/api/Contract/ DownloadSignedDocument"  
  
request_method = "GET"  
  
connection_url = "api-sb.contracts.com.sa"  
  
timestamp = "1586345122"  
  
secret_key= "provided_secret_key" on api configuration tab  
So we start by encoding the json data, we represent it as mentioned below:  
  
encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it  
depends on many inputs (Should be sorted as on example):  
  
message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp,  
encoded_data )  
After getting the message we start calculating the signature  
  
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),  
digestmod=hashlib.sha256).digest() calculated_signature = base64.b64encode(signature).decode()  
  
Important Note: The order for the fields is important and do not include the null values on the data for  
example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the  
json body for the request but you should delete it on the header)
```

Sample Request

```
< HTTP/1.1 200 OK  
< Content-Type: Application/json  
(BaseUrl)/Contract/DownloadSignedDocument?contractNo=10002000
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "file": "string",
    "version": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.5 Download Sanad Service

API Definition Card					
API Name		Download Sanad			
API Description		This service is exposed to download sanad (Promissory Notes).			
End Point		GET (Baseurl)/Contract/DownloadSanad			
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
contractNo	String	Query Param		R	Contract number that wants to download the original document.

returnUrl	String	Query Param		O	The URL that redirected to it after sanad approved from Nafith portal
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
	Response Elements				
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of download sanad.
beneficiaries	2	List<Object>		O	List of beneficiary which has sanad
sanadData	2	String		O	Sanad document in base64 string format.
sanadApprovalURL	2	String		O	Approval link for sanad.
uuid	2	String		O	Sanad group UUID.
sanadGroup	2	Object		O	The object contains the sanad group and sanad details.
id	3	String		O	Sanad group UUID.
referenceId	3	String		O	Sanad group reference Id.
status	3	String		O	Sanad group status.
issuedAt	3	DateTime		O	Sanad group created date.
approvedAt	3	DateTime		O	Sanad group approved date.
sanad	3	List<Object>		O	This object contains list of sanad details.
id	4	String		O	Sanad UUID.
totalValue	4	Decimal		O	Sanad total value.
referenceId	4	String		O	Sanad Reference Id.
number	4	String		O	Sanad number.
createdAt	4	DateTime		O	Sanad created date.
updatedAt	4	DateTime		O	Sanad updated date.
dueDate	4	Datetime		O	Sanad due date
dueType	4	String		O	Sanad due type
status	4	String		O	Sanad status
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"contractNo": "10002000 ", " returnUrl"="https://www.google" }
```

```
request_endpoint = "/api/Contract/ DownloadSanad "
```

```
request_method = "GET"
```

```
connection_url = "api-sb.contracts.com.sa"
```

```
timestamp = "1586345122"
```

secret_key= "provided_secret_key" on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

```
message = '{0}\n{1}\n{2}\nnt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )
```

After getting the message we start calculating the signature

```
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'), digestmod=hashlib.sha256).digest()
calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
```

```
< Content-Type: Application/json
```

```
(BaseUrl)/Contract/DownloadSanad?contractNo=10002000&returnUrl="https://www.google.com"
```

Sample Success Response

```
< HTTP/1.1 200 OK
```

```
< Content-Type: Application/json
```

```
{
  "data": {
    "BeneficiarySanad":{
      "sanadData": "string",
      "sanadApprovalURL": "string",
      "uuid": "string",
      "sanadGroup": {
        "id": "string",
        "referenceId": "string",
        "status": "string",
```

```

"issuedAt": "string",
"approvedAt": "string",
"sanad": [
  {
    "id": "string",
    "totalValue": 0,
    "referenceId": "string",
    "number": "string",
    "createdAt": "string",
    "updatedAt": "string",
    "dueDate": "string",
    "dueType": "string",
    "status": "string"
  }
]
},
"xmlData": "string",
"httpCode": 0,
"messages": [
  {
    "errorCode": "string",
    "message": "string"
  }
],
"succeeded": true
}

```

2.1.6 Resend Approval Page URL Service

API Definition Card	
API Name	Resend Approval Page URL
API Description	This service is exposed to resend the approval page to the beneficiary
End Point	Post (Baseurl)/Contract/ResendApprovalPageURL
HTTP Request Headers	
Element Name	Element Value
Content-Type	application/json; charset=UTF-8
X-Contracts-Timestamp	Time as a string the same value used to create the signature.
X-Contracts-ClientId	Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.
X-Contracts-APIKey	Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.

X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
contractNumber	String	Query Param		R	Contract number that wants to resend the approval link to the beneficiary.
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
	Response Elements				
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of resending the approval link.
isSent	2	Boolean		O	Status of resending the approval link to the beneficiary
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"contractNumber": "10002000 "}
request_endpoint = "/api/Contract/ ResendApprovalPageURL"

request_method = "POST"

connection_url = "api-sb.contracts.com.sa"

timestamp = "1586345122"

secret_key= "provided_secret_key" on api configuration tab
So we start by encoding the json data, we represent it as mentioned below:
```

`encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode()` Then a message should be generated and it depends on many inputs (Should be sorted as on example):

`message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )`

After getting the message we start calculating the signature

`signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'), digestmod=hashlib.sha256).digest()` `calculated_signature = base64.b64encode(signature).decode()`

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

< HTTP/1.1 200 OK

< Content-Type: Application/json

(BaseUrl)/Contract/ResendApprovalPageURL?contractNumber =10002000

Sample Success Response

< HTTP/1.1 200 OK

< Content-Type: Application/json

```
{
  "data": {
    "isSent": true
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.7 Get Contract Audit Trail Service

API Definition Card					
API Name		Get Contract Audit Trail			
API Description		This service is exposed to download the contract audit trail report.			
End Point		GET (Baseurl)/Contract/GetContractAuditTrail			
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element		Data Type	Element Type	Allowed Value	Usage* Description
contractNo		String	Query Param		R Contract number that wants to download the audit trail.
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
Response Elements					
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of download the contract audit trail report.
reportFile	2	String		O	signed document in base64 string format.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"contractNo": "10002000 "}
request_endpoint = "/api/Contract/ GetContractAuditTrail"

request_method = "GET"

connection_url = "api-sb.contracts.com.sa"

timestamp = "1586345122"

secret_key= "provided_secret_key" on api configuration tab
So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it
depends on many inputs (Should be sorted as on example):

message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp,
encoded_data )
After getting the message we start calculating the signature

signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),
digestmod=hashlib.sha256).digest() calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/GetContractAuditTrail?contractNo=10002000
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "reportFile": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.8 Sign Hash Document Service

API Definition Card					
API Name		Sign Hash Document			
API Description		This service is exposed to sign hash documents using Emdha signing provider			
End Point		GET (Baseurl)/Contract/SignHashedDocument			
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
hashedDocument	String	Body Param		R	Document hashed that generated from Emdha library.

contractNumber	String	Body Param		R	Contract number that wants to sign the document using the hash document
HTTP Response Headers					
Element Name				Element Value	
Content-Type				application/json; charset=UTF-8	
	Response Elements				
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of the signed hash document
document	2	String		O	The signed document hashed that returned from Emdha service.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {
  "hashedDocument": "string",
  "contractNumber": "string"
}
request_endpoint = "/api/Contract/ SignHashedDocument"

request_method = "POST"

connection_url = "api-sb.contracts.com.sa"

timestamp = "1586345122"

secret_key= "provided_secret_key" on api configuration tab
So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )
After getting the message we start calculating the signature
```

```
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),
digestmod=hashlib.sha256).digest() calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

< HTTP/1.1 200 OK

< Content-Type: Application/json

[\(Baseurl\)/Contract/SignHashedDocument](#)

```
{
  "hashedDocument": " <SignReq version=\"1.00\" sipId=\"UAT-BFSI-CNTRC01\" ts=\"2025-01-06T14:34:34\"
txn=\"5ac1f8a0-f8c9-4608-a887-613a426117a5\" kyCld=\"2154239046\" signAlgorithm=\"ECC\"
kyCldProvider=\"SELF-NID\" sdkVer=\"3.1.0.4\" sdkDesc=\"dotnetframework\" sipIsRka=\"1\"
userConsentObtained=\"1\"><SignatoryInfo>PFNP225lckluZm8gdmVyc2lvbj0iMS4wMCIgcmtHtmFtZT0iMS4wM
Clga3ljSWQ9JlxlNTQyMzkwNDYpJxreWNEYXRhIGVuZ2xpc2h0YWw1PSJTWUVEIEITUFJTCAtIEFITUVEliBhcmFia
WNOYW1PISLYo9it2YXYryDYp9iz2YXYp9i52YrZhCAtINiz2YrYrylgY291bnRyeT0iU0EiIC8+PC9TaWduZXJJbmZvPg=
=</SignatoryInfo><Docs><InputHash hashAlgorithm=\"SHA256\" responseSigType=\"pkcs7\"
id=\"1\">94b54bf51cda9aa385e40c4c5a49db91fb096da2142d2a58193675d61e131f3c</InputHash></Docs><Sig
nature xmlns=\"http://www.w3.org/2000/09/xmldsig#\"><SignedInfo><CanonicalizationMethod
Algorithm=\"http://www.w3.org/TR/2001/REC-xml-c14n-20010315\" /><SignatureMethod
Algorithm=\"http://www.w3.org/2001/04/xmldsig-more#rsa-sha256\" /><Reference
URI=\"\"><Transforms><Transform Algorithm=\"http://www.w3.org/2000/09/xmldsig#enveloped-signature\"
/></Transforms><DigestMethod Algorithm=\"http://www.w3.org/2001/04/xmldsig#sha256\"
/><DigestValue>18wYXSyYTOYEEVDvPtvdMoeegzrxAs243Y7HPg1Leto=</DigestValue></Reference></SignedInf
o><SignatureValue>UH1qA6xsOqHDtpeWophd/rLtxkP1UqEwMTLRF06ER68D8dDa4KGWfGmS1k8zUb2juNpZ0W
FsbjPEaxrPR31edwRfSD2bjzf//ayq5tAqx5F75BcqqfiktXQmcnQ4OvbpNYuKhG6Ka8SjfqWbDZhdAOMuaCGRZNZeI
Vpm4vRtVDSVXEfx+up4vhhicnOMUzt/WeVjROmsDfVig+HfzmUQE5ri3HMLYrmi+rXxc9Jr0zbq+Ug7xjS3PTUxPed
PflVkwMwusMeMgUg9v6s3N9XUcxurFuEqbpNQm3DjDVT5aGzPctyg+YWhEKf7XA6Qfl2IMdtpLNYOayGbz2+j2b
rwDfItNf0yZrqlnuuz4/dvBLEyox6QhIH13AghjKkiAzvGFBaYgF/HtzWZicqA8gy55wv4Pk69exspsEixQ106bAZrh92
H7nXmNM4IFLwx/wkiP8BbHvGE4riQOWC/9phP3JkclGwQgYRGEp9domgGQduQLtiNuqG/l+YVIFPlx3b81RCPIfA
G6G0s3/PbVuVYs8bWiRB1fepb8994Xs+ofqdUEPjaJVq4nPYjeg34clPtRJQg9JIZpOINIZd1v1/fdXfpHK2+qrekv3t9ZB
WgA8jxn2W/7aO70yr2DjP6YZ35V3U9qAO9Mnt7ewf7flqr2QZn2jwNW05gS0WJHeaieo=</SignatureValue><KeyI
nfo><X509Data><X509Certificate>MIIIEjCCBfqgAwIBAgIRAIP9ojFs1H2t3Cq5L9vDUZ4wDQYJKoZIhvcNAQELBQA
wOjELMAkGA1UEBhMCU0ExDjAMBGNVBAoTBWVtZGhhMRswGQYDVQQDEkJlWRoYSBic2lnbiBERVYgQ0EwHh
cNMjEwMjE4MDY1OTU2WhcNMjYwMjE2MjA1OTU5WjBCMQswCQYDVQQGDAJTEOMAwGA1UECgwFZW1ka
GEXlZAhBgNVBAMMGkNsaWVudCBTResgRm9yIERldmVsb3BtZW50MIIlCjANBgkqhkiG9w0BAQEFAAOCAg8AMI
CCgKCAgEAtTtkF8oSa6yXW981Zc9E8ljigKki4EVbGuanRZYVmb+HIGlby0BEscGPXY+dt2gBw7FE0cqC8KIH82czqji6A
YsZmmi62L7qP8EqMdENHB8isifD0Hu9BGhW9gMZKv7A8/nppd+ee6lQ48UYc60SbWqGgmnTet84IILRYo45pnrXjj
9GPfuqrsoKV+tsLj9wXZl8ulk4sckNn8phbCPHxhC6pCaf979EPQ+FatSKxilVeICTtMBh9Sc1ODA7s1YbxV6BLD4nis4/
cgiOS6EHo1tKV6U/S8AsU+JA51/gwcELtnaPiGXAMZ33J8swiiFwiAZfmyHg1HEPeUrc1GrheKHISCDpfSsUn3NcDQS
7thSN0odjAXTIQiYT0pVs3Rf+gZwuO/0AMGXWNoFSZux/5MitxeIUwYDuQR52nGlzNjiz6YO2WSJrkj4Wgfp56fjYT
JioCtXr6ZqDTjyAcQztgbAhtQV/sjUrcu0IH6FN2nhY2/u6iazCKtANnkca5hyQTrWoThTs56Szu5YRi7PE9fyxNsOa7HK
591+I+V/WX3dnC7F4/MWbhQuo+R8FnognrGZJam78FFOo19VAOmhfLo3M0zxTjem+glwN0RqUhl5aW1NzONdn
7KhoBKIB5DgdKbmoS/xX6vWHe5TAokSyCBQxGcwVKcwo8lmtTbe2kCAwEAAEOCAAwkwggMFMEIGA1UdHwQ7
```

```
MDkwN6A1oDOGMWh0dHA6Ly9yZXBvc2l0b3J5ZGV2LmVtZGhhLnNhL2NybmHMvZVNpZ25ERVZDQS5jcmwwHwY
DVR0jBBgwFoAUcr1wUzQp2v62sywY/7SO4rk1NH8wHQYDVR0OBBYEFp/fbroWFYThCMNfx6QJwoSEWgTYMAw
GA1UdEwEB/wQCMAAwdQYIKwYBBQUHAQEETBnMEAGCCsGAQUFBzACHjRodHRwOi8vcmlvdWVwbn3NpdG9yeWRI
di5lbWRoYSS5zYS9jYWwNlcnRzL2VtZWduREVVWQ0EuY3J0MCMGCCsGAQUFBzABhhdodHRwOi8vb2NzcGRldi5lbW
RoYSS5zYTCCABAGA1UdIASCAacwgGjMIIBNwYNYIUqAWWnCAEEAQECAzCCAYwwIAYIKwYBBQUHAQEWFgh0dH
BzOi8vd3d3LmVtZGhhLnNhMIIBZgYIKwYBBQUHAgIwggFYHoIBVABCAFAQAwAgAEwASQBDAAEUATgBTAEUARAA
gAEMAQQAgAEMAZQBByAHQAaQBmAGkAYwBhAHQAaQBvAG4AIAABQAG8AbABpAGMAeQAAGEAbgBkACAAY
QBzAHMAbwBjAGkAYQB0AGUAZAAGAGQABwBjAHUAAbQBIAg4AdABhAHQAaQBvAG4AIAABhAHYAYQBpAGwAY
QBiAGwAZQAgAGEAdAAgAGgAdAB0AHAAcwA6AC8ALwB3AHcAdwAuAGUAbQBkAGgAYQAuAHMAYQAuACAAa
QBzACAAaABIAHIAZQBIAHkAIAABpAG4AYwBvAHIAcABvAHIAIYQB0AGUAZAAGAGkABgB0AG8AIAAB5AG8AdQByAC
AAdQBzAGUAIAABvAHIAIAByAGUAbABpAGeAbgBjAGUAIABvAG4AIAAB0AGgAaQBzACAAQwBIAHIAAdABpAGYAaQ
BjAGEAdABIAC4wDgYDVR0PAQH/BAQDAgBAMDYGA1UdJQQvMC0GCCsGAQUFBwMCBgorBgEEAYI3FAICBgorBg
EEAYI3CgMMBgkqhkiG9y8BAQUwDQYJKoZIhvcNAQELBQADggIBACIYUSKjfk7tSjZsQ6FwwO9docMP1R8z/LAOh
d60EjAOMm9r+VC44+WheD/ZQS8F5L1Ymmgfg2IQjBkUgfhepJNXqEVC8myK32mcuMorufxg60ul0Wn6B37mFTk
MYH56vfhcQ/IE/GERW5BwCp+X14hfHcRBVkhzHBxiiHiv6+viQ1CtjegJamupUS5loNh1tEiSKB1k1q2m1K6dw07zxk
OMO87LmTQOCfD07vQPd2xk+AWasGGM2eUctKBylTiOKkWvh9sG/nCYql1iFloUEg6WZhNlL5rWiDbN/nnmUNuE
v2/li8j5e1S50DxHALG0v6QranVeZXkBPdN8VPctbHEm3JCnXG94wa6dRP51x21kw2euHULkbIMLTN7fQsfhFJQ+8s
FhfwtDPdgKC7J4Kej5JTfOhxQOr+uI5IHs1Buo+SfndLwRyuLnu9rTL6bXa9P1GsHMu+sJZWeNGdBDiSOGK/fjWGPJ
ZrNb16MkBFtVbi9UDzE0XpvK/cfC0mt6Xq6R9iRE6Ep4VXn++O6kPGQTOgEuJ5fMSnRuNNODzsmYzXDqKuFP7G8B
WctXFUGLhv1CjmrPsZFmnZuT+PtozvnO61UqZR7qJfLoU4vjEI+VB0GOpqkZOpieAo3qZA/JjmkW3dTYIX9nw5vyhy
YxMfThC0qELfOsmd40ighr</X509Certificate></X509Data></KeyInfo></Signature></SignReq>",
"contractNumber": "10002000"
}
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "document": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.9 Get Contract Details Service

API Definition Card					
API Name		Get Contract Details			
API Description		This service is exposed to get the contract details.			
End Point		GET (Baseurl)/Contract/GetContractDetails			
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
contractNo	String	Query Param		R	Contract number that wants to get the details.
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
Response Elements					
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of get contract details.
customerCR	2	String		O	Customer commercial registry.
contractNumber	2	String		O	Contract number
beneficiaryIDNumbers	2	List<String>		O	List of beneficiaries IDs that were added on the contract.
contractBeneficiariesList	2	List<Object>		O	List of beneficiaries details that were added on the contract.
beneficiaryIdNumber	3	String		O	Beneficiary ID number
beneficiaryName	3	String		O	Beneficiary Name.
fileStatus	3	String		O	Beneficiary action status.

fileStatusId	3	String	Refer to the Enum section	O	Beneficiary action status code
actionDate	3	DateTime		O	Beneficiary action date.
contractStatusCode	2	String	Refer to the Enum section	O	Contract status code.
createdOn	2	DateTime		O	Contract created date.
signDate	2	Datetime		O	Contract signed date.
unSignFile	2	String		O	Un-Signed document in base64 string format.
signFile	2	String		O	Signed document in base64 string format.
fileSharingLink	2	List<String>		O	Contract approval link.
unSignFileLink	2	String		O	Un-Signed contract link.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"contractNo": "10002000 "}
request_endpoint = "/api/Contract/ GetContractDetails"

request_method = "GET"

connection_url = "api-sb.contracts.com.sa"

timestamp = "1586345122"

secret_key= "provided_secret_key" on api configuration tab
So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it
depends on many inputs (Should be sorted as on example):

message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp,
encoded_data )
After getting the message we start calculating the signature

signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),
digestmod=hashlib.sha256).digest()
calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/GetContractDetails?contractNo=10002000
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "customerCR": "string",
    "contractNumber": "string",
    "beneficiaryIDNumbers": [
      "string"
    ],
    "contractBeneficiariesList": [
      {
        "beneficiaryIdNumber": "string",
        "beneficiaryName": "string",
        "fileStatus": "string",
        "fileStatusId": "string",
        "actionDate": "string"
      }
    ],
    "contractStatusCode": "string",
    "createdOn": "2025-02-16T07:11:34.665Z",
    "signDate": "2025-02-16T07:11:34.665Z",
    "unSignFile": "string",
    "signFile": "string",
    "fileSharingLink": ["string"],
    "unSignFileLink": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
}
```

```
"succeeded": true
}
```

2.1.10 Download Un-Signed Addendum Service

API Definition Card					
API Name		Download Un-Signed Addendum			
API Description		This service is exposed to download un-signed addendum document			
End Point		GET (Baseurl)/Contract/DownloadUnsignedAddendum			
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
contractNo	String	Query Param		R	Contract number that wants to get the details.
refNumber	String	Query Param		O	Addendum document reference id.
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
Response Elements					
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of download an un-signed addendum document.
file	2	String		O	Original addendum document in base64 string format

Version	2	String		O	Version of original addendum document
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"contractNo": "10002000 ", "refNumber": "10020010002000 "}
```

```
request_endpoint = "/api/Contract/DownloadUnSignedAddendum"
```

```
request_method = "GET"
```

```
connection_url = "api-sb.contracts.com.sa"
```

```
timestamp = "1586345122"
```

secret_key= "provided_secret_key" on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

```
message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )
```

After getting the message we start calculating the signature

```
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),  
digestmod=hashlib.sha256).digest() calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
```

```
< Content-Type: Application/json
```

```
(BaseUrl)/Contract/DownloadUnSignedAddendum?contractNo=10002000&refNumber=100200
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "file": "string",
    "version": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.11 Download Signed Addendum Service

API Definition Card	
API Name	Download Signed Addendum
API Description	This service is exposed to download signed addendum document
End Point	GET (Baseurl)/Contract/DownloadSignedAddendum
HTTP Request Headers	
Element Name	Element Value
Content-Type	application/json; charset=UTF-8
X-Contracts-Timestamp	Time as a string the same value used to create the signature.
X-Contracts-ClientId	Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.
X-Contracts-APIKey	Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the

X-Contracts-Signature			APIs Settings page. Create a signature using the secret key or the certificate.		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
contractNo	String	Query Param		R	Contract number that wants to get the details.
refNumber	String	Query Param		O	Addendum document reference id.
version	String	Query Param		O	The version of the signed addendum documents. If the value is null, the latest signed addendum document will retrieve in the response.
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
	Response Elements				
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of download signed addendum document
file	2	String		O	Original addendum document in base64 string format
Version	2	String		O	Version of original addendum document
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"contractNo": "10002000 ","version": "1 "}
request_endpoint = "/api/Contract/DownloadSignedAddendum"

request_method = "GET"
```

```
connection_url = "api-sb.contracts.com.sa"
```

```
timestamp = "1586345122"
```

secret_key= "provided_secret_key" on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

```
message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )
```

After getting the message we start calculating the signature

```
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),  
digestmod=hashlib.sha256).digest() calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK  
< Content-Type: Application/json  
(BaseUrl)/Contract/DownloadSignedAddendum?contractNo=10002000&refNumber=100200&version=1
```

Sample Success Response

```
< HTTP/1.1 200 OK  
< Content-Type: Application/json  
{  
  "data": {  
    "file": "string",  
    "version": "string"  
  },  
  "xmlData": "string",  
  "httpCode": 0,  
  "messages": [  
    {  
      "errorCode": "string",  
      "message": "string"  
    }  
  ],  
  "succeeded": true  
}
```

2.1.12 Download Sanad Group Service

API Definition Card					
API Name		Download Sanad Group			
API Description		This service is exposed to get sanad group details			
End Point		GET (Baseurl)/Contract/DownloadSanadGroup			
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element		Data Type	Element Type	Allowed Value	Usage* Description
uuid		String	Query Param		R Sanad group UUID
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
Response Elements					
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of download sanad group.
sanadGroup	2	Object		O	The object contains the sanad group and sanad details.
id	3	String		O	Sanad group UUID.
referenceId	3	String		O	Sanad group reference Id.
status	3	String		O	Sanad group status.
issuedAt	3	DateTime		O	Sanad group created date.
approvedAt	3	DateTime		O	Sanad group approved date.
sanad	3	List<Object>		O	This object contains list of sanad details.
id	4	String		O	Sanad UUID.

totalValue	4	Decimal		O	Sanad total value.
referenceId	4	String		O	Sanad Reference Id.
number	4	String		O	Sanad number.
createdAt	4	DateTime		O	Sanad created date.
updatedAt	4	DateTime		O	Sanad updated date.
dueDate	4	Datetime		O	Sanad due date
dueType	4	String		O	Sanad due type
status	4	String		O	Sanad status
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"uuld": " xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxx "}
```

```
request_endpoint = "/api/Contract/ DownloadSanadGroup "
```

```
request_method = "GET"
```

```
connection_url = "api-sb.contracts.com.sa"
```

```
timestamp = "1586345122"
```

```
secret_key= "provided_secret_key" on api configuration tab
```

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

```
message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )
```

After getting the message we start calculating the signature

```
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),  
digestmod=hashlib.sha256).digest() calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/DownloadSanadGroup?uuld=xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxxxx
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
```

```
{
  "data": {
    "sanadGroup": {
      "id": "string",
      "referenceld": "string",
      "status": "string",
      "issuedAt": "string",
      "approvedAt": "string",
      "sanad": [
        {
          "id": "string",
          "totalValue": 0,
          "referenceld": "string",
          "number": "string",
          "createdAt": "string",
          "updatedAt": "string",
          "dueDate": "string",
          "dueType": "string",
          "status": "string"
        }
      ]
    }
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.13 Get Contracts Service

API Definition Card	
API Name	Get Contracts

API Description	This service is exposed to get the contracts details for the company.				
End Point	GET (Baseurl)/Contract/GetContracts				
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
dateFrom	DateTime	Query Param		O	Start date To filter the contracts by.
dateTo	DateTime	Query Param		O	End date To filter the contracts by.
pageSize	Integer	Query Param		O	
pageNumber	Integer	Query Param		O	
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
	Response Elements				
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of get contract details.
result	2	List<Object>		O	List of Contracts Details.
customerCR	3	String		O	Customer commercial registry.
contractNumber	3	String		O	Contract number
beneficiaryIDNumbers	3	List<String>		O	List of beneficiaries IDs that were added on the contract.
contractBeneficiariesList	3	List<Object>		O	List of beneficiaries details that were added on the contract.
beneficiaryIdNumber	4	String		O	Beneficiary ID number
beneficiaryName	4	String		O	Beneficiary Name.
fileStatus	4	String		O	Beneficiary action status.

fileStatusId	4	String	Refer to the Enum section	O	Beneficiary action status code
actionDate	4	DateTime		O	Beneficiary action date.
contractStatusCode	3	String	Refer to the Enum section	O	Contract status code.
createdOn	3	DateTime		O	Contract created date.
signDate	3	Datetime		O	Contract signed date.
unSignFile	3	String		O	Un-Signed document in base64 string format.
signFile	3	String		O	Signed document in base64 string format.
fileSharingLink	3	String		O	Contract approval link.
unSignFileLink	3	String		O	Un-Signed contract link.
allItemCount	2	Integer		R	Number of Returned Contracts.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = { "dateFrom":"2025-02-05T00:00:00", "dateTo":"2025-02-05T00:00:00", "pageSize":5, "pageNumber":1 }
request_endpoint = "/api/Contract/GetContracts"
```

```
request_method = "GET"
```

```
connection_url = "api-sb.contracts.com.sa"
```

```
timestamp = "1586345122"
```

secret_key= "provided_secret_key" on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

```
message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )
```

After getting the message we start calculating the signature

```
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),
digestmod=hashlib.sha256).digest()
calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/GetContracts?dateFrom=2025-02-05T00:00:00&dateTo=2025-04-05T00:00:00&pageSize=10&pageNumber=1
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "result": [
      {
        "customerCR": "string",
        "contractNumber": "string",
        "beneficiaryIDNumbers": [
          "string"
        ],
        "contractBeneficiariesList": [
          {
            "beneficiaryIdNumber": "string",
            "beneficiaryName": "string",
            "fileStatus": "string",
            "fileStatusId": "string",
            "actionDate": "string"
          }
        ],
        "contractStatusCode": "string",
        "createdOn": "2025-02-16T07:11:34.665Z",
        "signDate": "2025-02-16T07:11:34.665Z",
        "unSignFile": "string",
        "signFile": "string",
        "fileSharingLink": "string",
        "unSignFileLink": "string"
      }
    ],
    "allItemCount": 0
  }
}
```

```
"xmlData": "string",
"httpCode": 0,
"messages": [
{
"errorCode": "string",
"message": "string"
}
],
"succeeded": true
}
```

2.1.14 Get All By Beneficiary Service

API Definition Card					
API Name		Get All By Beneficiary			
API Description		This service is exposed to get the contracts details for the company By Beneficiary Id-Number .			
End Point		GET (Baseurl)/Contract/GetAllByBeneficiary			
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
beneficiaryIdNumber	String	Query Param		R	Beneficiary ID number
dateFrom	DateTime	Query Param		O	Start date To filter the contracts by.

dateTo	DateTime	Query Param		O	End date To filter the contracts by.
pageSize	Integer	Query Param		O	
pageNumber	Integer	Query Param		O	
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
	Response Elements				
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of get contract details.
result	2	List<Object>		O	List of Contracts Details.
customerCR	3	String		O	Customer commercial registry.
contractNumber	3	String		O	Contract number
beneficiaryIDNumbers	3	List<String>		O	List of beneficiaries IDs that were added on the contract.
contractBeneficiariesList	3	List<Object>		O	List of beneficiaries details that were added on the contract.
beneficiaryIdNumber	4	String		O	Beneficiary ID number
beneficiaryName	4	String		O	Beneficiary Name.
fileStatus	4	String		O	Beneficiary action status.
fileStatusId	4	String	Refer to the Enum section	O	Beneficiary action status code
actionDate	4	DateTime		O	Beneficiary action date.
contractStatusCode	3	String	Refer to the Enum section	O	Contract status code.
createdOn	3	DateTime		O	Contract created date.
signDate	3	Datetime		O	Contract signed date.
unSignFile	3	String		O	Un-Signed document in base64 string format.
signFile	3	String		O	Signed document in base64 string format.
fileSharingLink	3	String		O	Contract approval link.
unSignFileLink	3	String		O	Un-Signed contract link.
allItemCount	2	Integer		R	Number of Returned Contracts.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"beneficiaryIdNumber ":"10000000000", "dateFrom":"2025-02-05T00:00:00", "dateTo":"2025-04-05T00:00:00", "pageSize":5, "pageNumber":1}
```

```
request_endpoint = "/api/Contract/ GetAllByBeneficiary"
```

```
request_method = "GET"
```

```
connection_url = "api-sb.contracts.com.sa"
```

```
timestamp = "1586345122"
```

secret_key= "provided_secret_key" on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

```
message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )
```

After getting the message we start calculating the signature

```
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'), digestmod=hashlib.sha256).digest()
calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
```

```
< Content-Type: Application/json
```

```
(Baseurl)/Contract/GetAllByBeneficiary?beneficiaryIdNumber=10000000000&dateFrom=2025-02-05T00:00:00&dateTo=2025-04-05T00:00:00&pageSize=1&pageNumber=1
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "result": [
      {
        "customerCR": "string",
        "contractNumber": "string",
        "beneficiaryIDNumbers": [
          "string"
        ],
        "contractBeneficiariesList": [
          {
            "beneficiaryIdNumber": "string",
            "beneficiaryName": "string",
            "fileStatus": "string",
            "fileStatusId": "string",
            "actionDate": "string"
          }
        ],
        "contractStatusCode": "string",
        "createdOn": "2025-02-16T07:11:34.665Z",
        "signDate": "2025-02-16T07:11:34.665Z",
        "unSignFile": "string",
        "signFile": "string",
        "fileSharingLink": "string",
        "unSignFileLink": "string"
      }
    ],
    "allItemCount": 0
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.15 Get Nafath Login Status Service

API Definition Card					
API Name		Get Nafath Login Status			
API Description		This service is exposed to get the Nafath login status by trace id.			
End Point		GET (Baseurl)/Contract/GetNafathLoginStatus			
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element		Data Type	Element Type	Allowed Value	Usage* Description
traceId		String	Query Param		R Nafath Trace Id.
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
Response Elements					
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of get contract details.
authorizationStatus	2	String	Refer to the Enum section	O	Login Status.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"transId": " xxxx-0x0x0-0000-xxxx "}
```

request_endpoint = "/api/Contract/ GetNafathLoginStatus "

request_method = "GET"

connection_url = "api-sb.contracts.com.sa"

timestamp = "1586345122"

secret_key= "provided_secret_key" on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format(request_method, connection_url, request_endpoint, timestamp, encoded_data)

After getting the message we start calculating the signature

signature = hmac.new(bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'), digestmod=hashlib.sha256).digest() **calculated_signature** = base64.b64encode(signature).decode()

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/GetNafathLoginStatus?transId=xxxx-0x0x0-0000-xxxx
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
```

```

    "authorizationStatus": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}

```

2.1.16 Get Random Number Service

API Definition Card					
API Name		Get Random Number			
API Description		This service is exposed to get Random Number Generated By Nafath Service By contract number and beneficiary Id-Number			
End Point		GET (Baseurl)/Contract/GetRandomNumber			
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element		Data Type	Element Type	Allowed Value	Usage* Description
idNumber		String	Query Param		R Beneficiary ID number
contractNumber		String	Query Param		R Contract number

HTTP Response Headers					
Element Name				Element Value	
Content-Type				application/json; charset=UTF-8	
	Response Elements				
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of get contract details.
transId	2	String		O	Transaction Id.
random	2	String		O	Random generated Number.
status	2	String		O	Contract number
message	2	String		O	Message.
trace	2	String		O	
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data = {"idNumber": "10000000000","contractNumber": "10002000 "}}
request_endpoint = "/api/Contract/ GetRandomNumber"
```

```
request_method = "GET"
```

```
connection_url = "api-sb.contracts.com.sa"
```

```
timestamp = "1586345122"
```

secret_key= "provided_secret_key" on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

```
message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )
```

After getting the message we start calculating the signature

```
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),
digestmod=hashlib.sha256).digest()
calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/GetRandomNumber?idNumber=10000000000&contractNumbe=1000200
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "transId": "string",
    "random": "string",
    "status": "string",
    "message": "string",
    "trace": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.1.17 Update Status Service

API Definition Card	
API Name	Update Status

API Description	This service is exposed to update status				
End Point	POST (Baseurl)/Contract/UpdateStatus				
HTTP Request Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		
X-Contracts-Timestamp			Time as a string the same value used to create the signature.		
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.		
X-Contracts-Signature			Create a signature using the secret key or the certificate.		
Request					
Element	Data Type	Element Type	Allowed Value	Usage*	Description
contractNumber	String	Json body		R	Contract number
statusCode	Integer	Json body	Refer to the Enum section	R	Status Code to change the status to.
cancellationContract	String	Json body		O	Contract to be changed in base64 format.
withCancellationContract	Boolean	Json body		O	If sending the contract in base64 it will be True.
updateSanadStatus	Boolean	Json body		O	If the contract have sands and it status will be changed it will be send as True.
sanadUUIdList	List<String>	Json body		O	List of sub sanads uuid.
HTTP Response Headers					
Element Name			Element Value		
Content-Type			application/json; charset=UTF-8		

Response Elements					
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of get contract details.
customerCR	2	String		O	Customer commercial registry.

contractNumber	2	String		O	Contract number
beneficiaryIDNumbers	2	List<String>		O	List of beneficiaries IDs that were added on the contract.
contractBeneficiariesList	2	List<Object>		O	List of beneficiaries details that were added on the contract.
beneficiaryIDNumber	3	String		O	Beneficiary ID number
beneficiaryName	3	String		O	Beneficiary Name.
fileStatus	3	String		O	Beneficiary action status.
fileStatusId	3	String	Refer to the Enum section	O	Beneficiary action status code
actionDate	3	DateTime		O	Beneficiary action date.
contractStatusCode	2	String	Refer to the Enum section	O	Contract status code.
createdOn	2	DateTime		O	Contract created date.
signDate	2	Datetime		O	Contract signed date.
unSignFile	2	String		O	Un-Signed document in base64 string format.
signFile	2	String		O	Signed document in base64 string format.
fileSharingLink	2	String		O	Contract approval link.
unSignFileLink	2	String		O	Un-Signed contract link.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```

data = {
  "contractNumber": "string",
  "statusCode": 0,
  "cancellationContract": "string",
  "withCancellationContract": true,
  "updateSanadStatus": true,
  "sanadUUIdList": [
    "string"
  ]
}
request_endpoint = "/api/Contract/ UpdateStatus"

request_method = "POST"

connection_url = "api-sb.contracts.com.sa"

timestamp = "1586345122"
    
```

secret_key= “provided_secret_key” on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

message = '{0}\n{1}\n{2}\nnt={3}&ed={4}'.format(request_method, connection_url, request_endpoint, timestamp, encoded_data)

After getting the message we start calculating the signature

signature = hmac.new(bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'), digestmod=hashlib.sha256).digest() **calculated_signature** = base64.b64encode(signature).decode()

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send **beneficiaryName** the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/UpdateStatus
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "customerCR": "string",
    "contractNumber": "string",
    "beneficiaryIDNumbers": [
      "string"
    ],
    "contractBeneficiariesList": [
      {
        "beneficiaryIdNumber": "string",
        "beneficiaryName": "string",
        "fileStatus": "string",
        "fileStatusId": "string",
        "actionDate": "string"
      }
    ],
    "contractStatusCode": "string",
    "createdOn": "2025-02-16T07:11:34.665Z",
    "signDate": "2025-02-16T07:11:34.665Z",
    "unSignFile": "string",
```

```
"signFile": "string",
"fileSharingLink": "string",
"unSignFileLink": "string"
},
"xmlData": "string",
"httpCode": 0,
"messages": [
{
"errorCode": "string",
"message": "string"
}
],
"succeeded": true
}
```

2.2 Contracts Entity Inbound Service

The below subsections cover the business aspect of the Contracts services; these services are considered as Consume services from the Contracts services perspective.

Baseurl: <https://api-sb.contracts.com.sa/api/v2>

SwaggerUI: [https://api-sb.contracts.com.sa](https://api-sb.contracts.com.sa/integration/swagger/index.html?urls.primaryName=Integration%20API%20v2)

/integration/swagger/index.html?urls.primaryName=Integration%20API%20v2

2.2.1 Upload Contract Service

API Definition Card	
API Name	Upload Contract
API Description	This service is exposed to Upload new contract (can be with or without sanad).
End Point	POST (Baseurl)/Entity/Contract/UploadContract
HTTP Request Headers	
Element Name	Element Value
Content-Type	application/json; charset=UTF-8
X-Contracts-Timestamp	Time as a string the same value used to create the signature.
X-Contracts-ClientId	Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.
X-Contracts-APIKey	Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.
X-Contracts-Signature	Create a signature using the secret key or the certificate.

Request						
Element	Level	Data Type	Element Type	Allowed Value	Usage*	Description
file	1	string	Body Param	Base64 string	R	Main contract file in Base64 format
templateFields	1	List<Object>	Body Param	-	O	List of fields to be placed on the document
id	2	string	Body Param	String	O	Field identifier
type	2	string	Body Param	Refer to the Enum section	O	Field type identifier
position	2	Object	Body Param	-	O	Position of the field
x	3	Integer	Body Param	Integer	O	X-axis coordinate
y	3	Integer	Body Param	Integer	O	Y-axis coordinate
size	2	Object	Body Param	-	O	Size of the field
width	3	Integer	Body Param	Integer	O	Width of the field
height	3	Integer	Body Param	Integer	O	Height of the field
applyToAllPages	2	boolean	Body Param	true / false	O	When you need to Apply the field to all pages
pages	2	List<Integer>	Body Param	[0, 1, 2, ...]	O	Specific pages where field appears
filledBy	2	string	Body Param	String	O	National ID for who will fill this field
defaultValue	2	string	Body Param	String	O	Default value of the field
fileName	1	string	Body Param	String	R	Name of the contract file
contractNumber	1	string	Body Param	String	R	Contract identifier
description	1	string	Body Param	String	O	Contract description
contractBeneficiaries	1	List<Object>	Body Param	-	R	List of beneficiaries
id	2	Integer	Body Param	String	R	Beneficiary ID default 0
nameEn	2	string	Body Param	String (Max 32)	R	Beneficiary name in English (at least two words)

						)
nameAr	2	string	Body Param	String (Max 32)	R	Beneficiary name in Arabic (at least two words)
nationalIdNumber	2	string	Body Param	String	R	National ID
mobileNumber	2	string	Body Param	String	R	Mobile number
email	2	string	Body Param	String	R	Email address
beneficiaryRegionId	2	Integer	Body Param	Refer to Region Enum	R	Beneficiary region
maximumApprovalMinutes	2	Integer	Body Param	Integer	R	Max approval time in minutes
privateNote	2	string	Body Param	String	O	Private note for beneficiary
lang	2	string	Body Param	Refer to the Enum section	R	Approval page language
hasSanad	2	boolean	Body Param	true / false	R	Whether the beneficiary has Sanad / Promissory Note
sanadGroup	2	Object	Body Param	-	O	Sanad group details
type	3	Integer	Body Param	Refer to Sanad Type Enum	R	Sanad type
totalValue	3	Integer	Body Param	Integer	R	Sum of Total value of all Sanads
referenceId	3	string	Body Param	String	R	Reference ID
countryOfIssuance	3	string	Body Param	String	R	Country of issuance
cityOfIssuanceId	3	Integer	Body Param	Refer to the Enum section	R	City of issuance
countryOfPayment	3	string	Body Param	String	R	Country of payment
cityOfPaymentId	3	Integer	Body Param	Refer to the Enum section	R	City of payment
responseTimeInMinutes	3	Integer	Body Param	Integer	R	Response time in minutes
currency	3	string	Body Param	String	R	Currency
reason	3	string	Body Param	String	O	Reason of the Sanad
sanads	3	List<Object>	Body Param	-	R	List of individual

						Sanads
totalValue	4	Integer	Body Param	Integer	R	Sanad value
dueType	4	Integer	Body Param	Refer to the Enum section	R	Due type
referenceId	4	string	Body Param	String	O	Reference ID
dueDate	4	string (Date-Time)	Body Param	Date-Time	O	Due date
updateStatusDate	4	string (Date-Time)	Body Param	Date-Time	O	Last update date
reason	4	string	Body Param	String	R	Reason
debtor	3	Object	Body Param	-	R	Debtor details
idNumber	4	string	Body Param	String	R	Beneficiary National ID number
phoneNumber	4	string	Body Param	String	R	Mobile number
name	4	string	Body Param	String	R	Beneficiary name
email	4	string	Body Param	String	O	Beneficiary email
unifiedNumber	4	string	Body Param	String	O	Unified number
type	4	Integer	Body Param	Refer to the Enum section	O	Debtor type
guarantors	3	List<Object>	Body Param	-	O	List of guarantors
guarantorId	4	string	Body Param	String	O	Guarantor ID
phoneNumber	4	string	Body Param	String	O	Mobile number
fullName	4	string	Body Param	String	O	Full name
shareApprovalURLVia	2	Integer	Body Param	Refer to the Enum section	R	Method to share approval URL
digitalSigningProvider	2	Integer	Body Param	Refer to the Enum section	R	Digital signing provider
authenticationTypeId	2	Integer	Body Param	Refer to the Enum section	R	Authentication type
beneficiaryActionType	2	Integer	Body Param	Refer to the Enum section	R	Beneficiary action type
offlineCode	2	String	Body Param	String	O	Offline code for beneficiary
beneficiaryType	2	Integer	Body	Refer to the	R	Type of

			Param	Enum section		beneficiary
isVerifyOwner	2	boolean	Body Param	true / false	R	Verify owner identity
additionalFiles	1	List<Object>	Body Param	-	O	List of additional files
name	2	String	Body Param	String	O	File name
file	2	string	Body Param	String	O	File in "base64" format
sendInOrder	1	boolean	Body Param	true/false	R	Whether the contract should be sent in order
sendSecurityCodeVia	1	Integer	Body Param	Refer to the Enum section	R	Security code sending method
waitingPeriod	1	Integer	Body Param	Integer	R	Waiting period before take actions on the contract by the beneficiary (in days)
unifiedNumber	1	string	Body Param	String	R	Unified number for the single owner company
returnURL	1	String	Body Param	String (URL)	O	Success Return URL after signing
wathqVerify	1	boolean	Body Param	true/false	R	Verify with Ministry of Commerce (Wathq)
contractEntity	1	Object	Body Param	-	O	Contract entity details
name	2	String	Body Param	String	O	Single owner Entity name
issueDate	2	string (Date-Time)	Body Param	Date-Time	O	Single Owner Entity Issue date
signatureMethod	1	Integer	Body Param	Refer to the Enum section	O	Signature display method on the contract. Values In Enum Section
metaData	1	List<Integer>	Body Param	Refer to the Enum section	O	Defines which Metadata fields displayed next to the signature on the final contract. Values In Enum Section

HTTP Response Headers	
Element Name	Element Value
Content-Type	application/json; charset=UTF-8

Response Elements					
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of get contract details.
contractId	2	String		O	Customer commercial registry.
contractNumber	2	String		O	Contract number
contractStatusCode	2	String	Refer to the Enum section	O	Contract status code.
createdOn	2	String (Date-Time)		O	Contract created date.
fileSharingLink	2	List<String>		O	Contract approval link.
unSignFileLink	2	String		O	Un-Signed contract link.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data =
{
  "file": "string",
  "templateFields": [
    {
      "id": "string",
      "type": "Signature",
      "position": {
        "x": 0,
        "y": 0
      },
      "size": {
        "width": 0,
        "height": 0
      },
      "applyToAllPages": true,
      "pages": [
        0
      ],
    }
  ]
}
```

```

    "filledBy": "string",
    "defaultValue": "string"
  }
],
"fileName": "string",
"contractNumber": "string",
"description": "string",
"contractBeneficiaries": [
{
  "nameEn": "string",
  "nameAr": "string",
  "nationalIdNumber": "string",
  "mobileNumber": "string",
  "email": "string",
  "beneficiaryRegionId": 0,
  "maximumApprovalMinutes": 0,
  "privateNote": "string",
  "lang": "string",
  "hasSanad": true,
  "sanadGroup": {
    "type": 0,
    "totalValue": 0,
    "referenceId": "string",
    "countryOfIssuance": "string",
    "cityOfIssuanceId": 0,
    "countryOfPayment": "string",
    "cityOfPaymentId": 0,
    "responseTimeInMinutes": 0,
    "currency": "string",
    "reason": "string",
    "sanads": [
      {
        "totalValue": 0,
        "dueType": 1,
        "referenceId": "string",
        "dueDate": "2026-04-09T07:49:09.590Z",
        "updateStatusDate": "2026-04-09T07:49:09.590Z",
        "reason": "string"
      }
    ]
  },
  "debtor": {
    "idNumber": "string",
    "phoneNumber": "string",
    "name": "string",
    "email": "string",
    "unifiedNumber": "string",
    "type": 1
  },
  "guarantors": [
    {

```

```

    "guarantorId": "string",
    "phoneNumber": "string",
    "fullName": "string"
  }
},
"shareApprovalURLVia": 1,
"digitalSigningProvider": 1,
"authenticationTypeId": 0,
"beneficiaryActionType": 1,
"offlineCode": "string",
"beneficiaryType": 1,
"isVerifyOwner": true
},
"additionalFiles": [
  {
    "name": "string",
    "file": "string"
  }
],
"sendInOrder": true,
"sendSecurityCodeVia": 1,
"waitingPeriod": 0,
"unifiedNumber": "string",
"returnURL": "string",
"wathqVerify": true,
"contractEntity": {
  "name": "string",
  "issueDate": "2026-04-09T07:49:09.590Z"
},
"signatureMethod": 0,
"metaData": [
  1
]
}
request_endpoint = "/api/v2/Entity/Contract/UploadContract "
request_method = "POST"
connection_url = "api-sb.contracts.com.sa"
timestamp = "1586345122"

```

secret_key= "provided_secret_key" on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

```
message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )
```

After getting the message we start calculating the signature

```
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'), digestmod=hashlib.sha256).digest()
calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/UploadContract
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "contractId": 0,
    "contractNumber": "string",
    "contractStatusCode": "string",
    "createdOn": "2025-02-18T08:25:14.909Z",
    "fileSharingLink": ["string"],
    "unSignFileLink": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.2.2 Upload Contract With Template Service

API Definition Card

API Name	Upload Contract With Template
----------	-------------------------------

API Description	This service is exposed to Upload new contract using an existing template uploaded on the portal (can be with or without sanad).
End Point	POST (Baseurl)/Entity/Contract/UploadContractWithTemplate
HTTP Request Headers	
Element Name	Element Value
Content-Type	application/json; charset=UTF-8
X-Contracts-Timestamp	Time as a string the same value used to create the signature.
X-Contracts-ClientId	Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.
X-Contracts-APIKey	Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.
X-Contracts-Signature	Create a signature using the secret key or the certificate.

Request						
Element	Level	Data Type	Element Type	Allowed Value	Usage*	Description
templateFields	1	List<Object>	Body Param	-	R	List of fields to be placed on the document
id	2	string	Body Param	String	R	Field identifier
type	2	string	Body Param	Refer to the Enum section	R	Field type identifier
position	2	Object	Body Param	-	R	Position of the field
x	3	Integer	Body Param	Integer	R	X-axis coordinate
y	3	Integer	Body Param	Integer	R	Y-axis coordinate
size	2	Object	Body Param	-	R	Size of the field
width	3	Integer	Body Param	Integer	R	Width of the field
height	3	Integer	Body Param	Integer	R	Height of the field
applyToAllPages	2	boolean	Body Param	true / false	R	When you need to Apply the field to all pages
pages	2	List<Integer>	Body Param	[0, 1, 2, ...]	R	Specific pages where field appears
filledBy	2	string	Body Param	String	R	National ID for who will fill this field
defaultValue	2	string	Body Param	String	O	Default value of the field

contractNumber	1	string	Body Param	String	R	Contract identifier
description	1	string	Body Param	String	O	Contract description
contractBeneficiaries	1	List<Object>	Body Param	-	R	List of beneficiaries
id	2	Integer	Body Param	String	R	Beneficiary ID default 0
nameEn	2	string	Body Param	String (Max 32)	R	Beneficiary name in English (at least two words)
nameAr	2	string	Body Param	String (Max 32)	R	Beneficiary name in Arabic (at least two words)
nationalIdNumber	2	string	Body Param	String	R	National ID
mobileNumber	2	string	Body Param	String	R	Mobile number
email	2	string	Body Param	String	R	Email address
beneficiaryRegionId	2	Integer	Body Param	Refer to Region Enum	R	Beneficiary region
maximumApprovalMinutes	2	Integer	Body Param	Integer	R	Max approval time in minutes
privateNote	2	string	Body Param	String	O	Private note for beneficiary
lang	2	string	Body Param	Refer to the Enum section	R	Approval page language
hasSanad	2	boolean	Body Param	true / false	R	Whether the beneficiary has Sanad / Promissory Note
sanadGroup	2	Object	Body Param	-	O	Sanad group details
type	3	Integer	Body Param	Refer to Sanad Type Enum	R	Sanad type
totalValue	3	Integer	Body Param	Integer	R	Sum of Total value of all Sanads
referenceId	3	string	Body Param	String	R	Reference ID
countryOfIssuance	3	string	Body Param	String	R	Country of issuance
cityOfIssuanceId	3	Integer	Body Param	Refer to the Enum section	R	City of issuance
countryOfPayment	3	string	Body Param	String	R	Country of payment
cityOfPaymentId	3	Integer	Body Param	Refer to the Enum section	R	City of payment

responseTimeInMinutes	3	Integer	Body Param	Integer	R	Response time in minutes
currency	3	string	Body Param	String	R	Currency
reason	3	string	Body Param	String	O	Reason of the Sanad
sanads	3	List<Object>	Body Param	-	R	List of individual Sanads
totalValue	4	Integer	Body Param	Integer	R	Sanad value
dueType	4	Integer	Body Param	Refer to the Enum section	R	Due type
referenceId	4	string	Body Param	String	O	Reference ID
dueDate	4	string (Date-Time)	Body Param	Date-Time	O	Due date
updateStatusDate	4	string (Date-Time)	Body Param	Date-Time	O	Last update date
reason	4	string	Body Param	String	R	Reason
debtor	3	Object	Body Param	-	R	Debtor details
idNumber	4	string	Body Param	String	R	Beneficiary National ID number
phoneNumber	4	string	Body Param	String	R	Mobile number
name	4	string	Body Param	String	R	Beneficiary name
email	4	string	Body Param	String	O	Beneficiary email
unifiedNumber	4	string	Body Param	String	O	Unified number
type	4	Integer	Body Param	Refer to the Enum section	O	Debtor type
guarantors	3	List<Object>	Body Param	-	O	List of guarantors
guarantorId	4	string	Body Param	String	O	Guarantor ID
phoneNumber	4	string	Body Param	String	O	Mobile number
fullName	4	string	Body Param	String	O	Full name
shareApprovalURLVia	2	Integer	Body Param	Refer to the Enum section	R	Method to share approval URL
digitalSigningProvider	2	Integer	Body Param	Refer to the Enum section	R	Digital signing provider
authenticationTypeId	2	Integer	Body Param	Refer to the Enum section	R	Authentication type

beneficiaryActionType	2	Integer	Body Param	Refer to the Enum section	R	Beneficiary action type
offlineCode	2	String	Body Param	String	O	Offline code for beneficiary
beneficiaryType	2	Integer	Body Param	Refer to the Enum section	R	Type of beneficiary
isVerifyOwner	2	boolean	Body Param	true / false	R	Verify owner identity
EndDate						
additionalFiles	1	List<Object>	Body Param	-	O	List of additional files
name	2	String	Body Param	String	O	File name
file	2	string	Body Param	String	O	File in “base64” format
sendInOrder	1	boolean	Body Param	true/false	R	Whether the contract should be sent in order
sendSecurityCodeVia	1	Integer	Body Param	Refer to the Enum section	R	Security code sending method
waitingPeriod	1	Integer	Body Param	Integer	R	Waiting period before take actions on the contract by the beneficiary (in days)
templateCode	1	string	Body Param	String	R	Template Code from the Portal.
templateData	1	String	Body Param	String	O	In case of Word template Send the key with case-sensitive and the value as follows: "{\"Companyname\": \"Test\"}"
unifiedNumber	1	string	Body Param	String	R	Unified number
returnURL	1	String	Body Param	String (URL)	O	Return URL after signing
wathqVerify	1	boolean	Body Param	true/false	R	Verify with Ministry of Commerce (Wathq) when the client sign the contract
contractEntity	1	Object	Body Param	-	O	Contract entity details
name	2	String	Body Param	String	O	Single owner Entity Name
issueDate	2	string (Date-Time)	Body Param	Date-Time	O	Single Owner Entity Issue date
signatureMethod	1	Integer	Body Param	Refer to the Enum section	O	Signature display method on the contract. Values In Enum Section
metaData	1	List<Integer>	Body Param	Refer to the Enum section	O	Defines which Metadata fields displayed next to the signature on the final contract. Values In Enum Section

HTTP Response Headers	
Element Name	Element Value
Content-Type	application/json; charset=UTF-8

Response Elements					
Element	Level	Data Type	Allowed Value	Usage*	Description
data	1	Object		O	This object includes the result of get contract details.
contractId	2	String		O	Customer commercial registry.
contractNumber	2	String		O	Contract number
contractStatusCode	2	String	Refer to the Enum section	O	Contract status code.
createdOn	2	String (Date-Time)		O	Contract created date.
fileSharingLink	2	List<String>		O	Contract approval link.
unSignFileLink	2	String		O	Un-Signed contract link.
xmlData	1	String		O	
httpCode	1	Integer		R	Http status code.
messages	1	Array<Object>		O	List of business validations error code and message.
errorCode	2	String		O	Business validation error code.
message	2	String		O	Business validation message.
succeeded	1	Boolean		R	

Calculate Signature

```
data =
{
  "templateFields": [
    {
      "id": "string",
      "type": 1,
      "position": {
        "x": 0,
        "y": 0
      },
      "size": {
        "width": 0,
        "height": 0
      },
      "applyToAllPages": true,
      "pages": [
        0
      ]
    }
  ]
}
```

```

    ],
    "filledBy": "string",
    "defaultValue": "string"
  }
],
"contractNumber": "string",
"description": "string",
"contractBeneficiaries": [
{
  "nameEn": "string",
  "nameAr": "string",
  "nationalIdNumber": "string",
  "mobileNumber": "string",
  "email": "string",
  "beneficiaryRegionId": 0,
  "maximumApprovalMinutes": 0,
  "privateNote": "string",
  "lang": "string",
  "hasSanad": true,
  "sanadGroup": {
    "type": 0,
    "totalValue": 0,
    "referenceId": "string",
    "countryOfIssuance": "string",
    "cityOfIssuanceId": 0,
    "countryOfPayment": "string",
    "cityOfPaymentId": 0,
    "responseTimeInMinutes": 0,
    "currency": "string",
    "reason": "string",
    "sanads": [
      {
        "totalValue": 0,
        "dueType": 1,
        "referenceId": "string",
        "dueDate": "2026-04-09T10:23:19.308Z",
        "updateStatusDate": "2026-04-09T10:23:19.308Z",
        "reason": "string"
      }
    ]
  },
  "debtor": {
    "idNumber": "string",
    "phoneNumber": "string",
    "name": "string",
    "email": "string",
    "unifiedNumber": "string",
    "type": 1
  },
  "guarantors": [
    {

```

```

        "guarantorId": "string",
        "phoneNumber": "string",
        "fullName": "string"
    }
]
},
"shareApprovalURLVia": 1,
"digitalSigningProvider": 1,
"authenticationTypeId": 0,
"beneficiaryActionType": 1,
"offlineCode": "string",
"beneficiaryType": 1,
"isVerifyOwner": true
}
],
"endDate": "2026-04-09T10:23:19.308Z",
"additionalFiles": [
{
    "name": "string",
    "file": "string"
}
],
"sendInOrder": true,
"sendSecurityCodeVia": 1,
"waitingPeriod": 0,
"templateCode": "string",
"templateData": "string",
"unifiedNumber": "string",
"returnURL": "string",
"wathqVerify": true,
"contractEntity": {
    "name": "string",
    "issueDate": "2026-04-09T10:23:19.308Z"
},
"signatureMethod": 0,
"metaData": [
    1
]
}
request_endpoint = "/api/v2/Entity/Contract/UploadContractWithTemplate "
request_method = "POST"
connection_url = "api-sb.contracts.com.sa"
timestamp = "1586345122"

secret_key= "provided_secret_key" on api configuration tab
So we start by encoding the json data, we represent it as mentioned below:
    
```

`encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode()` Then a message should be generated and it depends on many inputs (Should be sorted as on example):

`message = '{0}\n{1}\n{2}\nnt={3}&ed={4}'.format( request_method, connection_url, request_endpoint, timestamp, encoded_data )`

After getting the message we start calculating the signature

`signature = hmac.new(bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'),
digestmod=hashlib.sha256).digest()` `calculated_signature = base64.b64encode(signature).decode()`

UploadContractWithTemplate Ignore the templateData object from the data.

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

Sample Request

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
(Baseurl)/Contract/UploadContractWithTemplate
```

Sample Success Response

```
< HTTP/1.1 200 OK
< Content-Type: Application/json
{
  "data": {
    "contractId": 0,
    "contractNumber": "string",
    "contractStatusCode": "string",
    "createdOn": "2025-02-18T08:25:14.909Z",
    "fileSharingLink": ["string"],
    "unSignFileLink": "string"
  },
  "xmlData": "string",
  "httpCode": 0,
  "messages": [
    {
      "errorCode": "string",
      "message": "string"
    }
  ],
  "succeeded": true
}
```

2.3 Error Code

Error code	English Message	Arabic Message	Cause
E0003	You must fill in all fields	يجب أن تملأ جميع الخانات	Missing mandatory fields such as Beneficiary ID Number
E0005	Contract not found	هذا العقد غير موجود	Sending Contract Number that has not been created
E0022	Company does not exist	الشركة غير موجودة	The Used Client Id or API is not for an existing company on the platform
E0064	Internal Error	حدث خطأ في النظام	General system error
E0071	There is a problem with accessing the Nafith	لا يمكن الوصول لنافذ	Connection issue with Nafith system(General Error)
E0076	Need To Add Beneficiary First	يجب إضافة مستفيد	No beneficiaries while uploading contract The contract is configured to include one beneficiary (as per the template), but two or more beneficiaries were added—exceeding the maximum allowed by the configured template.
E0078	Contract number (reference) exist	رقم العقد (المرجعي) موجود لهذه الشركة	The contract number sent already exist
E0079	An action has been already taken to this contract	تم اتخاذ اجراء على هذا العقد مسبقا	Status of the contract has already been updated(using the approval page)
E0080	Contract must be pending or signed	يجب أن يكون العقد قيد الموافقة أو موقعاً	While changing the status of an active contract to canceled or partially signed, signed to closed
E0085	Contract status cannot be changed	لا يمكن تغيير حالة هذا العقد	While changing the status of an active contract legally rejected or payment is due
E0086	The maximum allowed number of beneficiaries has been exceeded	تم تجاوز الحد الأقصى المسموح به لعدد المستفيدين	Uploading a contract with number of beneficiaries exceeds platform configuration
E0092	Company has no active bundle	لا يوجد باقة فعالة لهذه الشركة	Company does not have an active bundle
E0093	Beneficiary data is required	يرجى إدخال معلومات المستفيد	Uploading contract with beneficiaries that does not have English and Arabic name, Region Id, National Id, and

			Mobile number fields.
E0094	Beneficiary IdNumber is duplicated	تمت إضافة رقم وطني للمستفيد أكثر من مرة	Uploading contract Multiple beneficiaries share the same national ID
E0100	Enter the contract file	العقد ملف ادخال يرجى	contract file not found or invalid
E0104	Response Time must be between 5 minutes and 5 days	دقائق 5 من أكبر يكون أن يجب الاستجابة وقت ايام 5 من وأقل	Uploading contract MaximumApprovalMinutes is out of range
E0105	File size is larger than the maximum file size allowed	لحجم الأقصى الحد من أكبر الملف حجم به المسموح الملف	File size is larger than the maximum file size allowed
E0106	City doesn't exist	المدينة غير موجودة	Uploading contract with sanad that have the Invalid cityOfIssuanceId value not matching Enum table
E0112	Response Time must be between 5 minutes and 7 days	دقائق 5 من أكبر يكون أن يجب الاستجابة وقت ايام 7 من وأقل	Uploading contract that has sanad with MaximumApprovalMinutes out of allowed range
E0115	Individual can not take action on this contract	العقد هذا على اجراء اخذ للمستفيد يمكن لا	Using ResendApprovalURL with beneficiary national id that does not have contract to take action
E0122	Share via should not be None	شارك عبر يجب ان لا تكون بدون	Uploading contract with shareApprovalURLVia should not be null (Refer back to Enum section)
E0131	First individual with send in order should not be read only	لا ينبغي أن يكون المستفيد الأول الذي يتم إرساله بالترتيب للقراءة فقط	Uploading contract with the first beneficiary has the beneficiaryActionType field is set to readonly
E0166	Transaction Failed	فشلت العملية	General Exception
E0203	Status not found	غير موجودة	Invalid status code used during contract status update
E0204	Action not allowed	الإجراء غير مسموح	Sending the version field with 0 in DownloadSigendDocument or DownloadSignedAddendum
E0206	Invalid template data	بيانات النموذج غير صالحة	Uploading template for word template with templateData fields empty or dose not match the count or the field names on the template
E0207	Invalid fields or values	الحقول أو القيم غير صالحة	Uploading contract with no templatefields or

			templatevalues fields or upload template with word file and the sent fields is not In the word template
E0208	Invalid Signature	صالح غير التوقيع	Invalid Signature is sent in the header of the request
E0209	Invalid endpoint	صالحة غير API نهاية نقطة	Invalid Endpoint
E0210	Invalid API key	صالح غير APIKEY	The API Key dose not exists or mismatch
E0211	Invalid port	صالح غير المنفذ	The Port dose not exists or mismatch
E0216	One or more selected page numbers are not valid for the uploaded file.	داخل موجودة غير صفحات أرقام إدخال تم الملف.	One or more selected page numbers are not valid for the uploaded file.
E0218	Cannot set both "applyToAllPages" and "pages". When "applyToAllPages" is true, the "pages" array should be empty.	و "applyToAllPages" تعيين يمكن لا تفعيل عند معًا "pages" تكون أن يجب، "applyToAllPages" فارغة "pages" مصفوفة	Cannot set both "applyToAllPages" and "pages". When "applyToAllPages" is true, the "pages" array should be empty.
E0219	Beneficiary name must include both First and Last Name.	يجب أن يتضمن اسم المستفيد الاسم الأول والأخير.	NameAr or NameEn have only first name
E0220	Template fields must not be empty.	لا يجب أن تكون الحقول فارغة	Template fields must not be empty.
E0221	All template field IDs must be non-empty.	يجب أن تحتوي جميع الحقول على معرفات غير فارغة	All template field IDs must be non-empty.
E0222	All template field IDs must be valid GUIDs.	GUID يجب أن تكون جميع معرفات الحقول صالحة.	All template field IDs must be valid GUIDs.
E0223	All template field IDs must be unique.	يجب أن تكون جميع معرفات الحقول فريدة	All template field IDs must be unique.
E0224	At least one Signature or Initial field must be added for each beneficiary who needs to sign.	يجب إضافة حقل توقيع أو حرف أولي واحد على الأقل لكل مستفيد يحتاج إلى التوقيع	At least one Signature or Initial field must be added for each beneficiary who needs to sign.
E0225	Duplicate entry found in the template data.	يوجد إدخال مكرر في بيانات القالب	Repeated data in templateData
E0226	The TemplateData field cannot be empty or contain only whitespace.	TemplateData لا يمكن أن يكون حقل فارغًا أو يحتوي على مسافات فقط	The TemplateData field cannot be empty or contain only whitespace.
E0227	Mobile number duplication is not allowed	لا يسمح بتكرار رقم الجوال	Mobile number duplication is not allowed for the beneficiaries in the upload contract

E0228	Email duplication is not allowed	لا يسمح بتكرار الايميل	Email duplication is not allowed
E0229	This mobile number is already linked to a user account	هذا الرقم مرتبط بالفعل بحساب مستخدم	This mobile number is already linked to a user account
E0230	This mobile number is already registered to an individual	لمستفيد بالفعل مسجل الرقم هذا	This mobile number is already registered to an individual
E0231	This email is already linked to a user account	بحساب بالفعل مرتبط الإلكتروني البريد هذا مستخدم	This email is already linked to a user account
E0232	This email is already registered to an individual	هذا البريد الإلكتروني مسجل بالفعل لمستفيد	This email is already registered to an individual
E0233	One or more fields are overlapping or placed in invalid positions.	أماكن في مجموعة أو تتداخل الحقول بعض صالحة غير	One or more fields are overlapping or placed in invalid positions.
E0234	One or more field types are not allowed.	به مسموح غير الحقل نوع	One or more field types are not allowed.
E0236	Sanad does not exist.	موجود غير السند	Sanad is missing or invalid
E0237	City of issuance is invalid.	صالحة غير الإصدار مدينة	The provided issuance city is not found in the valid list of cities.
E0238	City of payment is invalid.	صالحة غير الدفع مدينة	The payment city entered does not match any registered/allowed city.
E0237	City of issuance is invalid.	صالحة غير الإصدار مدينة	The provided issuance city is not found in the valid list of cities.
E0238	City of payment is invalid.	صالحة غير الدفع مدينة	The payment city entered does not match any registered/allowed city.
E0239	Country of issuance is invalid.	صالح غير الإصدار بلد	The issuance country code or name is not valid or not supported.
E0240	Country of payment is invalid.	صالح غير الدفع بلد	The payment country provided does not exist in the allowed list of countries.
E0241	Currency is invalid.	صالحة غير العملة	The given currency code is missing or not recognized.
E0242	Duration is invalid.	صالحة غير المدة	The duration is missing, negative, or incorrectly formatted.
E0243	Due date is invalid.	صالح غير الاستحقاق تاريخ	The due date is in the past, not

			in proper format, or outside allowed date range.
E0244	Sanad type is invalid.	صالح غير السند نوع	The sanad type is missing, unknown, or not supported by the system.
E0245	Only one sanad is allowed for this type.	النوع لهذا فقط واحد بسند يُسمح	The request tried to create multiple sanads where only one is permitted.
E0246	Invalid number of sanads.	صالح غير السندات عدد	The number of sanads provided exceeds or doesn't meet the required count.
E0247	National ID is invalid.	صالح غير الوطنية الهوية رقم	The national ID format is incorrect or not verifiable against records.
E0248	Due type is invalid.	صالح غير الاستحقاق نوع	The due type is missing or not recognized.
E0249	Total value does not match the sum of individual items.	القيم مجموع مع تتطابق لا الإجمالية القيمة الفردية	Total value does not match the sum of individual items
E0253	For fields of type "Stamp", the "filledBy" value must be "self".	أن يجب، "Stamp" نوع من للحقول بالنسبة "self" هي "filledBy" قيمة تكون	For Stamp field, "filledBy" value must be "self".
E0255	Default value for Initials field must be empty	الأحرف لحقل الافتراضية القيمة تكون أن يجب فارغة الأولى	The initials field cannot have a pre-filled value; it must start empty.
E0256	No stamp found in system. Please upload a stamp before enabling stamp field.	تحميل يُرجى. النظام في طابع على العثور يتم لم الطابع حقل تفعيل قبل طابع	The user enabled the stamp field without uploading any stamp to the system.
E0257	Invalid region ID provided for beneficiary.	صالح غير للمستفيد المنطقة معرف	The beneficiary region ID is not recognized or does not exist.
E0258	Invalid beneficiary type provided.	صالح غير المستفيد نوع	The given beneficiary type value is not allowed.
E0259	Invalid 'Share Approval URL via' option provided.	صالح غير 'عبر الموافقة رابط مشاركة' خيار	The chosen channel for sharing the approval URL is invalid.
E0260	Invalid digital signing provider specified.	صالح غير الرقمي التوقيع مزود	The provider name for digital signing is missing or unsupported.
E0261	Invalid beneficiary action type provided.	صالح غير المستفيد إجراء نوع	The given action type for the beneficiary is invalid.
E0262	Invalid 'Send Security Code via' option provided.	صالح غير 'عبر الأمان رمز إرسال' خيار	The option selected for sending the security code is invalid.
E0263	Waiting period must be zero or greater.	أكبر أو صفر الانتظار فترة تكون أن يجب	A negative waiting period was given, which is not allowed.
E0264	Default value for Initials field must be a valid	الأحرف لحقل الافتراضية القيمة تكون أن يجب Base64 بتنسيق مشفرة صالحة سلسلة الأولى	The initials field default value is not a valid Base64 string. It

	Base64-encoded string.		must be a base 64 of type JPEG or PNG
E0265	Default value for Signature field must be a valid Base64-encoded string.	التوقيع لحقل الافتراضية القيمة تكون أن يجب Base64. بتنسيق مشفرة صالحة سلسلة	The signature field default value is not a valid Base64 string. It must be a base 64 of type JPEG or PNG
E0267	Default value for Stamp field must be a valid Base64-encoded string.	الطابع لحقل الافتراضية القيمة تكون أن يجب Base64. بتنسيق مشفرة صالحة سلسلة	The stamp field default value is not a valid Base64 string. It must be a base 64 of type JPEG or PNG
E0268	Beneficiaries can only have one signature per page.	توقيع على إلا الحصول للمستفيدين يجوز لا صفحة لكل واحد	Multiple signatures for the same beneficiary were placed on one page.
E0269	Beneficiaries can only have one initial per page.	حرف على إلا الحصول للمستفيدين يمكن لا صفحة لكل واحد أولي	Multiple initials for the same beneficiary were placed on one page.
E0270	Field positions must not overlap. Please change the position of conflicting fields.	تعديل الرجاء. الحقول مواقع تتداخل ألا يجب المتعارضة الحقول	Two or more fields overlap on the document, which is not allowed.
E0271	Beneficiary name must not exceed 60 characters.	حرفاً 60 المستفيد اسم يتجاوز ألا يجب	The beneficiary name length is greater than the maximum allowed.
E0273	Default value is not allowed for the Sign Date field.	التوقيع تاريخ لحقل افتراضية بقيمة يُسمح لا	The sign date field cannot be pre-filled with a default value.
E0274	Default value is not allowed for the Hijri Date field.	الهجري التاريخ لحقل افتراضية بقيمة يُسمح لا	The Hijri date field cannot be pre-filled with a default value.
E0275	Name of promissory note's debtor must the same as the contract's beneficiary's	لاسم مساوياً يكون أن يجب السند دائن اسم العقد صاحب	The debtor name on the promissory note does not match the contract's beneficiary.
E0277	Attachment File size is larger than the maximum file size allowed	الأقصى الحجم من أكبر المرفق الملف حجم به المسموح	The uploaded attachment exceeds the maximum file size limit. Reduce the file size
E0278	File page count exceeds the maximum allowed limit	الأقصى الحد يتجاوز الملف صفحات عدد به المسموح	The uploaded main file contains more pages than allowed.
E0279	Attachment file page count exceeds the maximum allowed limit	الحد يتجاوز المرفق الملف صفحات عدد به المسموح الأقصى	The uploaded attachment file contains more pages than allowed.
E0280	The combined page count of the main file and attachments exceeds the maximum allowed limit.	الرئيسي الملف صفحات عدد إجمالي إن به المسموح الأقصى الحد يتجاوز والمرفقات	The total number of pages (main file + attachments file) exceeds the allowed maximum.

2.4 Contracts Outbound Service

The below subsections cover the business aspect of the Outbound services; these services are considered as Outbound services from the Contracts. Such services will be invoked by the Contracts.

4.3.1 Callback Service

API Definition Card						
API Name		Callback API				
API Description		This API should be exposed by the client. Contracts will trigger this API on each update on the contract status (Signed, Rejected, Canceled, Closed, and No Response) and use it to notify the client of any changes to the contract.				
HTTP Request Headers						
Element Name			Element Value			
Content-Type			application/json; charset=UTF-8			
X-Contracts-Timestamp			Time as a string the same value used to create the signature.			
X-Contracts-ClientId			Unique value for the company. You can find it on the API Configuration tab inside the APIs Settings page.			
X-Contracts-APIKey			Unique value for the company and each sub-account. You can find it on the API Configuration tab inside the APIs Settings page.			
X-Contracts-Signature			Create a signature using the secret key or the certificate.			
Request						
Element	Level	Data Type	Element Type	Allowed Value	Usage*	Description
contractNumber	1	String			R	Contract number
contractStatusCode	1	String		You can find the status code in the Integration Specification section.	R	Contract status.
signDate	1	datetime			O	Contract sign date
Signfile	1	String			O	Version of signed contract
beneficiaryIdNumber	1	String			O	Beneficiary ID number who take an action on the contract.
updateDate	1	Datetime			O	Last update date on contracts status
Sanad	1	Object			O	Sanad section include

						the status of sanad tak
id	2	String			O	Sanad group UUID
reference_id	2	String			O	Sanad group reference id
status	2	String		Approved/Rejected	O	Sanad group status
updated_at	2	Datetime			O	Sanad status updated date with time

Sample Request

```
{
  "contractNumber": "10002000",
  "contractStatusCode": "1",
  "signDate": null,
  "signFile": null,
  "beneficiaryIdNumber": "1234567890",
  "updateDate": "2025-01-01T11:15:33.3399183",
  "sanad": {
    "id": "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx",
    "reference_id": "10002000",
    "status": "approved",
    "updated_at": "2025-01-01T11:15:31.73748"
  },
  "signFileRefId": null
}
```

request_endpoint = "/ReceiveContract"

request_method = "POST"

connection_url = "api-sb.contracts.com.sa"

timestamp = "1586345122"

secret_key= "provided_secret_key" on api configuration tab

So we start by encoding the json data, we represent it as mentioned below:

encoded_data = base64.b64encode(bytes(data, 'utf_8')).decode() Then a message should be generated and it depends on many inputs (Should be sorted as on example):

message = '{0}\n{1}\n{2}\nt={3}&ed={4}'.format(request_method, connection_url, request_endpoint, timestamp, encoded_data)

After getting the message we start calculating the signature

```
signature = hmac.new( bytes(secret_key, 'utf_8'), msg=bytes(message, 'utf_8'), digestmod=hashlib.sha256).digest()
calculated_signature = base64.b64encode(signature).decode()
```

Important Note: The order for the fields is important and do not include the null values on the data for example if you don't want to send beneficiaryName the data will be: (Note you can send the null data on the json body for the request but you should delete it on the header)

3 Integration Specifications

3.1 Http Response Codes

HTTP status code	Error Description	Correction Action	Retry
200	OK		N
400	unsupported_grant_type	Authorization grant is not supported by the Authorization Server.	N
400	invalid_scope	The scope is malformed or invalid.	N
400	invalid_request	The request is malformed, a required parameter is missing or a parameter has an invalid value.	N
401	invalid_client	Client authentication failed.	N
500	General System Error.	N/A	Y

3.2 Enum

3.2.1 Contract Status

Code	Text
1	Signed
2	Need Beneficiary Approval
3	Approved by Beneficiary
4	Rejected by Beneficiary
5	No Response
6	Cancelled by Creator
9	Closed
11	Partially Signed

12	Beneficiary Review
----	--------------------

3.2.2 Contract Type

Code	Text
0	Individual
1	Entity

3.2.3 Nafath Authorization Status

Code	Text
0	Pending
1	Approved
2	Unathorized

3.2.4 Contract Term

Code	Text
0	Definite
1	Infinite

3.2.5 Document Type

Code	Text
0	Word
1	PDF

3.2.6 Share Via Types/Share Approval URL Via/ Send Security Code Via

Code	Text
1	None
2	Email
3	EmailAndSMS

3.2.7 Digital Signature Provider

Code	Text
------	------

1	Global Signature
2	Saudi Based Signature

3.2.8 Beneficiary Action Types

Code	Text
1	Need To Sign
2	Receive Copy

3.2.9 Sanad Type

Code	Text
0	Single
1	Multiple

3.2.10 Sanad Due Type

Code	Text
1	Date
2	Upon Request

3.2.11 Authentication Type Id

Code	Text
0	None
1	Email OTP
2	SMS OTP
3	Offline Code
4	Via Nafath
5	Via Nafith

3.2.12 Type (FieldType)

Code	Text
1	Signature

2	Initials
3	Stamp
4	SignDate
5	FullName
6	Company
7	JobTitle
8	Email
9	Text
10	Checkbox
11	Dropdown
12	RadioGroup
13	HijriDate
14	QrCode
15	Mobile
16	Image

3.2.13 City

Official City_Id	English name	Arabic name
1	Riyadh	الرياض
2	Al Daracih	الدرعية
3	Al Kharaj	الخرج
4	Al Dawadimiu	الدوادمي
5	Al Mujamaeuh	المجمعه
6	Al Quayeiuh	القويعة
7	Wadi Al Dawasir	وادي الدواسر
8	Al Aflaj	الافلاج
9	Al Zulufiu	الزلفي
10	Hawtatan Bani Tamim	حوطة بني تميم
11	Eafif	عفيف
12	Al Salil	السليل
13	Darma	ضرماء
14	Al Muzahimih	المزاحمية

15	Ramah	رماح
16	Thadiq	ثادق
17	Harimla	حريملاء
18	Alhariq	الحريق
19	Mecca	مكة المكرمة
20	Jeddah	جده
21	Al Tayif	الطائف
22	Al Qunafdhuh	القنفذه
23	Al Liyth	الليث
24	Rabigh	رابغ
25	Al Jumum	الجموم
26	Khalis	خليص
27	Al Kamil	الكامل
28	Runih	رنيه
29	Tarabah	تربه
30	Medina	المدينة المنورة
31	Yanbae	ينبع
32	Al Ola	العلا
33	Al Mahd	المهد
34	Badr	بدر
35	Khaybar	خيبر
36	Al Hinakia	الحناكية
37	Buraydah	بريده
38	Eanizah	عنيزه
39	Alrus	الرس
40	Al Mudhanib	المذنّب
41	Al Bikiriu	البكريه
42	Al Badayie	البدايع
43	Al Asyah	الاسياح
44	Al Nubhaniuh	النهبانيه
45	Euyun Al Juaa	عيون الجوى
46	Al Shamasuih	الشماسيه
47	Dammam	الدمام
48	Al Ahsa	الاحساء
49	Hfr Al Batn	حفر الباطن
50	Al Jabil	الجبيل
51	Al Qatif	القطيف
52	Al Khubar	الخير

53	Al Khaffji	الخفجي
54	Ras Tanuruh	رأس تنوره
55	Abqyq	ابقيق
56	Qaryat Al Alia	قرية العليا
57	Abha	ابها
58	Khamis Mushit	خميس مشيط
59	Bayshah	بيشه
60	Al Namas	الناماص
61	Mahayil Asir	محایل عسير
62	Sarat Obaiedah	سراة عبيده
63	Tuthliyt	تثليت
64	Rijal Almaa	رجال ألمع
65	Ahd Rafidih	احد رفيدة
66	Balqurn	بلقرن
67	Al Majariduh	المجارده
68	Tabuk	تبوك
69	Al Wajh	الوجه
70	Daba	ضباء
71	Tima	تيماء
72	Amlij	املج
73	Haql	حقل
74	Hail	حائل
75	Biqaea	بقعاء
76	Al Ghizaluh	الغزاله
77	Al Shannan	الشنان
78	Earear	عرعر
79	Rafhaa	رفحاء
80	Tarif	طريف
81	Jayzan	جيزان
82	Sibyaa	صبياء
83	Abu Arish	ابو عريش
84	Samith	صامطه
85	Al Harth	الحرث
86	Damad	ضمد
87	Al Riyth	الريث
88	Baysh	بيش

89	Farsan	فرسان
90	Ahd Al Masarihih	أحد المسارحة
91	Al Eidabiu	العيدابي
92	Al Eariduh	العارضه
93	Al Darb	الدرب
94	Najran	نجران
95	Shururuh	شوره
96	Hubuwnana	حبونا
97	Badr Al Janub	بدر الجنوب
98	Yadamuh	يدمه
99	Thar	ثار
100	Khabash	خباش
101	Al Kharkhir	الخرخير
102	Al Bahah	الباحه
103	Biljurshi	بلجرشي
104	Al Munadiq	المنديق
105	Al Makhawa	المخواه
106	Al Eaqiq	العقيق
107	Quluh	قلوه
108	Al Quraa	القرى
109	Sakaka	سكاكا
110	Al Quriyat	القريات
111	Dawmat Al Jundal	دومة الجندل
112	Al Zahran	الظهران
113	Shuqara	شقراء
114	Muhafazat Al Ghat	محافظة الغاط
115	Tabirajl	طبرجل
116	Al Mawiyuh	المويه
117	Al Barak	البرك
118	Uqlat Al Suqur	عقلة الصقور
119	Al Eays	العيص
120	Al Hayit	الحائط
121	Aduma	أضم
122	Tanawma	تنومة
123	Zahran Al Janub	ظهران الجنوب
124	Mawqiq	موقع
125	Al Kharma	الخرمة

128	Aleardiat Alshamalia	العرضية الشمالية
129	Marrat	مرات
130	Al Hajra	الحجرة
131	Aleardiat Aljanubia	العرضية الجنوبية
132	Wadi Al Fare	وادي الفرع
133	Al Shamli	الشملي
134	Al Twal	الطوال
135	Duriya	ضرية
137	Fayfaa	فيفاء
138	Alkhubara Wa Riaduha	الخبراء و رياضها
139	Alriyn	الرين
140	Harub	هروب
141	Maysan	ميسان
142	Bariq	بارق
143	Al Harija	الحرية
144	Ghamid Alzinad	غامد الزناد
145	Alddayir Bani Malik	الدائر بني مالك

3.2.14 Region

Code	Text
1	Northern Region
2	Central Region
3	Eastern Region
4	Southern Region
5	Western Region

3.2.15 Language

Code	Text
1	Arabic
2	English

3.2.16 Signature Method

Code	Text
0	None
1	Use My Own Branding
2	Contract Logo
3	Customize Image

3.2.17 Meta Data

Code	Text
1	ID
2	Name
3	Position
4	Mobile Number
5	Email
6	Georgian Date
7	Hijri Date
8	Time

3.2.18 Beneficiary Type

Code	Text
1	Individual
2	Owner
3	Guarantor