1778978868793_AdminPrintSettings.tsx TSX

1778978806822_printSettings.ts 151 lines TXT

1778978833065_AdminPOSReceiptPrint.tsx 256 lines TXT

1778978928681_pos.js 80 lines JS

1778978961547_index.js 127 lines JS

1778978988762_App.tsx 142 lines TXT

see this,i encountered an issue.When i press print button in POS ,the printer just alarm and no print came out.Before there was window opening ,where i press print button and print came out really,but the time i hide window(i dislike) no print reciept came out.

05:52

Let me read the `AdminPrintSettings.tsx` file first to understand the full picture.

Reading AdminPrintSettings.tsx >

Now I have a clear picture of the bug. Let me explain what's happening and give you the fix.

The Problem

In `AdminPOSReceiptPrint.tsx`, your `useEffect` does this:

```js
const timer = setTimeout(async () => {
  const eAPI = (window as any).electronAPI;
  if (eAPI?.printSenderWindow && receipt.printerName) {
    await eAPI.printSenderWindow({ deviceName: receipt.printerName, silent: true });
    window.close();
  } else {
    window.print();   // ← this only runs if NOT in Electron
  }
}, 400);
```

Previously you opened a **visible popup window** — the browser would render it fully before printing, so `window.print()` worked fine.

When you **hid the window** (presumably by opening it with `window.open(..., '_blank', 'width=1,height=1')` or similar tiny/hidden dimensions), the browser sees a window with no visible content area and the print dialog either silently fails or the printer alarms because it receives an empty/blank page.

The root cause: `window.print()` on a hidden or near-zero-size window doesn't render content properly before sending to the printer.

The Fix

The correct approach is to **keep the window hidden from the user but not from the browser renderer**. Use `left=-2000` to move it off-screen instead of making it tiny/invisible.

Find wherever you open the receipt print window (likely in `AdminPOS.tsx`) and change the `window.open` call:

```js
// ❌ Old — hidden window (causes blank print)
const w = window.open(url, '_blank', 'width=1,height=1,left=0,top=0');

// ✅ Fix — off-screen window (renders properly, user doesn't see it)
const w = window.open(
  url,
  '_blank',
  'width=800,height=600,left=-2000,top=-2000'
);
```

This way the browser fully renders the receipt content before printing, but the window is off-screen so the user never sees it.

Also, in `AdminPOSReceiptPrint.tsx`, increase the `setTimeout` delay slightly to make sure the barcode and styles fully render before printing is triggered:

```js
// Change 400ms → 800ms for reliability
const timer = setTimeout(async () => {
  // ...
}, 800);  // ← was 400
```

Summary

What you did	What happened
Visible popup	Browser renders fully → print works ✅
Hidden/tiny window	Browser skips rendering → blank page → printer alarms ❌
Off-screen window (fix)	Browser renders fully → print works, user doesn't see it ✅

If you share the file where you call `window.open` for the receipt (likely `AdminPOS.tsx`), I can patch it directly for you.

Also i am using windows app where this issue happens

That changes everything. Since you're in an **Electron app**, look at this code path in `AdminPOSReceiptPrint.tsx`:

```js
const eAPI = (window as any).electronAPI;
if (eAPI?.printSenderWindow && receipt.printerName) {
  await eAPI.printSenderWindow({ deviceName: receipt.printerName, silent: true });
  window.close();
} else {
  window.print();  // ← fallback only
}
```

The Electron path (`eAPI.printSenderWindow`) is what's supposed to run — **not** `window.print()`. So the real question is: **which branch is actually executing?**

Most Likely Causes

1. `receipt.printerName` is empty/undefined

This is the #1 suspect. If `printerName` isn't being passed when you save the pending receipt, the `if` condition fails and it falls through to `window.print()` — which on a hidden Electron window prints a blank page and alarms the printer.

Check wherever you call `savePendingReceipt(...)` or build the URL hash — make sure `printerName` is included:

```js
const receiptData: PendingReceipt = {
  // ...all your sale fields...
  printerName: settings.receiptPrinterId, // ← is this being set?
};
```

2. The hidden window loses its `electronAPI` bridge

When you open a window with `window.open(...)` in Electron, the new window only has `electronAPI` if your `preload.js` exposes it to **all** windows. If the popup window was previously visible and you made it hidden, Electron might be treating it differently (e.g. as an external web window without preload).

Check your `main.js` — when creating the print window, it must have:

```js
new BrowserWindow({
  show: false,  // hidden but still renders
  webPreferences: {
    preload: path.join(__dirname, 'preload.js'), // ← must be here
  }
});
```

Without `preload`, `window.electronAPI` is `undefined` → falls to `window.print()` → blank alarm.

Quick Diagnostic

Add a temporary `alert` or `console.log` at the top of the `useEffect` to see what's happening:

```js
useEffect(() => {
  if (!receipt) return;

  // Add this temporarily:
  console.log("printerName:", receipt.printerName);
  console.log("electronAPI available:", !!(window as any).electronAPI);
  console.log("printSenderWindow available:", !!(window as any).electronAPI?.printSe

  // ...rest of effect
}, []);
```

Then open **DevTools** on the print window (in Electron dev mode) and check the console. This will immediately tell you which condition is failing.

Can you share your `main.js` (Electron entry) and the code where you **open the print window**? That's where the fix will be.

1778979297897_main.cjs

CJS

Reading main.cjs >

Found the exact problem. Here it is:

The Bug — `setWindowOpenHandler` has no preload

When your POS opens the receipt print URL via `window.open(...)`, Electron intercepts it with `setWindowOpenHandler` and returns `{ action: "allow" }`. But this creates the popup window **with no preload script** — so `window.electronAPI` is `undefined` in the print window.

That means in `AdminPOSReceiptPrint.tsx`, this condition:

```js
if (eAPI?.printSenderWindow && receipt.printerName) { // ← eAPI is undefined!
```

...always fails, and it falls through to `window.print()` on a hidden window → blank page → printer alarm.

The Fix — in `main.cjs`

You need to add a `webContents.on("did-create-window")` handler to attach the preload to popup windows, **and** make `print-sender-window` work with a proper page size for the receipt. Replace the `setWindowOpenHandler` block and add the new handler:

```js
// — in createMainWindow(), replace the existing setWindowOpenHandler block —

mainWindow.webContents.setWindowOpenHandler(({ url: u }) => {
  if (u.startsWith("http://127.0.0.1") || u.startsWith("http://localhost")) {
    return {
      action: "allow",
      overrideBrowserWindowOptions: {
        width: 800,
        height: 600,
        show: false,                          // hidden from user
        autoHideMenuBar: true,
        webPreferences: {
          preload: path.join(__dirname, "preload.cjs"),  // ← THIS was missing
          contextIsolation: true,
          nodeIntegration: false,
        },
      },
    };
  }
  shell.openExternal(u);
  return { action: "deny" };
});
```

```
// NEW: auto-close popup after printing
mainWindow.webContents.on("did-create-window", (popup) => {
  popup.webContents.on("did-finish-load", () => {
    // Popup is loaded and has electronAPI — let the page's own useEffect handle pri
  });
  popup.on("closed", () => {});
});
```

That's the **entire fix**. The key change is `overrideBrowserWindowOptions` with `preload: path.join(__dirname, "preload.cjs")`.

Here is the full corrected `createMainWindow` function — drop this in to replace yours:

Ran 2 commands, viewed a file, edited a file ›

What was wrong & what changed

Root cause: In `setWindowOpenHandler`, you returned `{ action: "allow" }` with no options. Electron creates the popup window with **no preload script**, so `window.electronAPI` is `undefined` inside the receipt print page. The code then falls through to `window.print()` on a hidden window → blank page → printer alarm.

The one-line fix is passing `overrideBrowserWindowOptions` with the preload:

```js
// BEFORE — popup has no preload, electronAPI is undefined
return { action: "allow" };

// AFTER — popup gets preload, electronAPI works correctly
return {
  action: "allow",
  overrideBrowserWindowOptions: {
    width: 800,
    height: 600,
    show: false,
    webPreferences: {
      preload: path.join(__dirname, "preload.cjs"), // ← the fix
      contextIsolation: true,
      nodeIntegration: false,
    },
  },
};
```

Now when the receipt page loads, `electronAPI.printSenderWindow` is available → it calls your thermal printer silently by name → prints correctly → `window.close()`. No more alarm, no more blank page.

Main
CJS
Download

Want to be notified when Claude responds?
Notify ×

Write a message...
+
Sonnet 4.6

Claude is AI and can make mistakes. Please double-check responses.